

## Driver matrix

			FIXED	FIXED	TE/LE	1-10V	DALI	CASAMBI
			A0051242	A0071040	A0087328	A0071271	A0051247	A0093455
		Dimensions (LxWxH)	111x52x22	111x52x22	102x38x21	111x52x22	111x52x22	147x44x30
		Min. cutout hole	Ø 55mm	Ø 55mm	Ø 42mm	Ø 55mm	Ø 55mm	Ø 54mm
		Max drivers on MCB 16A type B	50 pcs.	50 pcs.	50 pcs.	50 pcs.	50 pcs.	50 pcs.
<b>RIO</b>	LED 5W	140mA	-	1/2	-	1/2	-	-
	LED 11W	340/350mA	1/2	1/2	1	1/2	1	1/2
	LED 17W	500mA	1	-	-	-	1	1
<b>RIO SQUARE</b>	LED 5W	140mA	-	1/2	-	1/2	-	-
	LED 11W	340/350mA	1/2	1/2	1	1/2	1	1/2
	LED 17W	500mA	1	-	-	-	1	1
<b>ONA</b>	LED 5W	140mA	-	1/2	-	1/2	-	-
	LED 11W	340/350mA	1/2	1/2	1	1/2	1	1/2
	LED 17W	500mA	1	-	-	-	1	1
<b>ONA FLEX</b>	LED 5W	140mA	-	1/2	-	1/2	-	-
	LED 11W	340/350mA	1/2	1/2	1	1/2	1	1/2
	LED 17W	500mA	1	-	-	-	1	1
<b>MIRO</b>	LED 5W	140mA	-	1/2	-	1/2	-	-
	LED 11W	340/350mA	1/2	1/2	1	1/2	1	1/2
	LED 17W	500mA	1	-	-	-	1	1
<b>MIRO FLEX</b>	LED 5W	140mA	-	1/2	-	1/2	-	-
	LED 11W	340/350mA	1/2	1/2	1	1/2	1	1/2
	LED 17W	500mA	1	-	-	-	1	1
<b>NORA</b>	LED 5W	140mA	-	1/2	-	1/2	-	-
	LED 11W	340/350mA	1/2	1/2	1	1/2	1	1/2
	LED 17W	500mA	1	-	-	-	1	1
<b>ONIS DISC</b>	LED 5W	140mA	-	1/2	-	1/2	-	-
	LED 11W	340/350mA	1/2	1/2	1	1/2	1	1/2
<b>IZARO DISC</b>	LED 5W	140mA	-	1/2	-	1/2	-	-
	LED 11W	340/350mA	1/2	1/2	1	1/2	1	1/2
	LED 17W	500mA	1	-	-	-	1	1
<b>VISTA DISC</b>	LED 5W	140mA	-	1/2	-	1/2	-	-
<b>ONIS AIR</b>	LED 5W	140mA	-	1/2	-	1/2	-	-
	LED 11W	340/350mA	1/2	1/2	1	1/2	1	1/2

Conversion table for max. quantities of drivers or other types of miniature circuit breaker.



MBC type	Max. current	Relative number of drivers
B	25A	156%
B	20A	125%
B	16A	100%
B	10A	63%
C	25 A	260%
C	20 A	208%
C	16A	170%
C	10 A	104%



Reference	<b>LED DRIVER 230V/250-700mA 20W (A0051242)</b>	
Dimensions (LxWxH)	111x52x22	
Min. cutout hole	Ø 55mm	
Input	220-240V/50-60Hz	
Power factor (max.)	0,97	
Dimming	non dimmable	
Max drivers on MCB 16A type B*	50 pcs.	
Application	LED 11W	LED 17W
Output	350mA / 19W / 2-54V DC	500mA / 20W / 2-40V DC



Reference	<b>LED DRIVER 230V/100-380mA 20W (A0071040)</b>	
Dimensions (LxWxH)	111x52x22	
Min. cutout hole	Ø 55mm	
Input	220-240V/50-60Hz	
Power factor (max.)	0,95	
Dimming	non dimmable	
Max drivers on MCB 16A type B*	50 pcs.	
Application	LED 5W	LED 11W
Output	140mA / 7,5W / 10-54V DC	340mA / 18W / 2-54V DC



Reference	LED DRIVER 230V/350mA 10W TE/LE (A0087328)	
Dimensions (LxWxH)	102x38x21	
Min. cutout hole	Ø 42mm	
Input	220-240V/50-60Hz	
Power factor (max.)	0,95	
Dimming	TE/LE (mains dimmable) (AM)	
Max drivers on MCB 16A type B*	50 pcs.	
Application	LED 11W	
Output	350mA / 10W / 18-28 DC	



Reference	LED DRIVER 230V/100-380mA 20W 1-10V (A0071271)	
Dimensions (LxWxH)	111x52x22	
Min. cutout hole	Ø 55mm	
Input	220-240V/50-60Hz	
Power factor (max.)	0,95	
Dimming	1-10V (PWM)	
Max drivers on MCB 16A type B*	50 pcs.	
Application	LED 5W	
Output	140mA / 7,5W / 10-54V DC	



Reference	LED DRIVER 230V/250-700mA 20W DALI (A0051247)	
Dimensions (LxWxH)	111x52x22	
Min. cutout hole	Ø 55mm	
Input	220-240V/50-60Hz	
Power factor (max.)	0,92	
Dimming	DALI (PWM)	
Max drivers on MCB 16A type B*	50 pcs.	
Application	LED 11W	LED 17W
Output	350mA / 15W / 2-43V DC	500mA / 20W / 2-40V DC



Reference	LED DRIVER 230V/300-1050mA 38W CASAMBI (A0093455)	
Dimensions (LxWxH)	147x44x30	
Min. cutout hole	Ø 54mm	
Input	220-240V/50-60Hz	
Power factor (max.)	0,95	
Dimming	CASAMBI (AM)	
Max drivers on MCB 16A type B*	50 pcs.	
Application	LED 11W	
Output	350mA / 18,5W / 10-54V DC	