

















Suspended decorative luminaire for LED light sources.

TECHNICAL DATA **Mounting:** suspended, on wire suspension (included)

**Body:** top quality aluminum Colour: white, silver

**ELECTRICAL DATA Power:** 220-240V 50/60Hz

Includes light source: yes Type of equipment: ED

**OPTICAL DATA** Way of lighting: direct Reflector: polished


**GENERAL DATA** Available on request: DIM 1..10V, DALI, other RAL colours

Warranty: 5 years


Application: offices, conference rooms, reception desks, shopping centers, galleries, boutiques, museums



Code	Beam angle	Power LED [W]	Luminaire power [W]	Lumen LED [lm]	Lumen luminaire [lm]	Efficacy [lm/W]	Colour temperature [K]	CRI/Ra
20011X.5L01.11X	102°	26	30	3000	3000	100	3000	≥80
20011X.5L02.11X	102°	25	29	3000	3000	103	4000	≥80
20011X.5L03.11X	102°	46	54	5000	5000	93	3000	≥80
20011X.5L04.11X	102°	42	49	5000	5000	102	4000	≥80



Code	Dimensions [mm] L H	Mounting dimensions [mm] L	Pallet quantity	Quantity in package	Net weight [kg]
20011X.5L01.11X	403 312	247	18	1	4.0
20011X.5L02.11X	403 312	247	18	1	4.0
20011X.5L03.11X	403 312	247	18	1	4.0
20011X.5L04.11X	403 312	247	18	1	4.0



Designed by LUG Design Team

Luminous flux tolerance +/- 10%.

Lighting beam, light intensity distribution and light efficiency were examined in accordance with the EN ISO 17025:2005 norm for EN13032 norm series and the LM-79 norm. Up-to-date product info available on our website www.flashdq.com





## **OTHER PICTURES**



## **LIGHT BEAM CURVES**

