

















Suspended decorative luminaire for LED light sources.

TECHNICAL DATA **Mounting:** suspended, on wire suspension (included)

Body: plastic polyester reinforced with fiberglass

Colour: white, black

Diffuser: opal plexiglass (PLX), microprismatic diffuser (MPRM)

ELECTRICAL DATA Power: 220-240V 50/60Hz

Includes light source: yes Type of equipment: ED

OPTICAL DATA Way of lighting: direct **GENERAL DATA**

Available on request: opal diffuser, DALI, DIM 1..10V


Warranty: 5 years

Application: offices, conference rooms, reception desks,


shopping centers, car showrooms, boutiques



Code	Power LED [W]	Luminaire power [W]	Lumen LED [lm]	Lumen luminaire [lm]	Efficacy [lm/W]	Colour temperature [K]	CRI/Ra
Diffuser: opal plex	iglass (PLX)						
20005X.5L01.1X1	36	43	5200	3900	91	4000	≥80
20005X.5L02.1X1	36	43	5000	3800	88	3000	≥80
Diffuser: micropris	matic diffuser (M	PRM)					
20005X.5L01.1X2	36	43	5200	4100	95	4000	≥80
20005X.5L02.1X2	36	43	5000	3950	92	3000	≥80



Code	Dimensions [mm] L H	Mounting dimensions [mm] L	Pallet quantity	Quantity in package	Net weight [kg]					
Diffuser: opal plexiglass (PLX)										
20005X.5L01.1X1	443 540	220	4	1	5.5					
20005X.5L02.1X1	443 540	220	4	1	5.5					
Diffuser: microprismatic diffuser (MPRM)										
20005X.5L01.1X2	443 540	220	4	1	5.5					
20005X.5L02.1X2	443 540	220	4	1	5.5					



Designed by LUG Design Team

Luminous flux tolerance +/- 10%.

Lighting beam, light intensity distribution and light efficiency were examined in accordance with the EN ISO 17025:2005 norm for EN13032 norm series and the LM-79 norm. Up-to-date product info available on our website www.flashdq.com





OTHER PICTURES











LIGHT BEAM CURVES

