



















Modern downlight luminaire for LED light sources for plaster board cellings.

TECHNICAL DATA

**Mounting:** in the ceiling, with mounting brackets (included) **Body:** powder painted steel sheet and anodized aluminum

Colour: white, black

**ELECTRICAL DATA** 

**Power:** 220-240V 50/60Hz Includes light source: yes Type of equipment: ED

**OPTICAL DATA GENERAL DATA**  Way of lighting: direct **Lifetime (L70B50):** 60 000 h

Available on request: metal halide lamps (on request), DALI Other remarks: for metal halide version - please order MH light


Warranty: 5 years

Application: hotels, offices, delicatessen, galleries, boutiques,


shopping centers



	Code	Beam angle	Power LED [W]	Luminaire power [W]	Lumen LED [lm]	Lumen luminaire [lm]	Efficacy [lm/W]	Colour temperature [K]	CRI/Ra
-	22002X.5L101.3X1	24°	1x17,5	21	1560	1560	74	4000	92
	22002X.5L102.3X1	24°	1x17,5	21	1430	1430	68	3000	92
	22002X.5L103.3X1	40°	1x17,5	21	1560	1560	74	4000	92
	22002X.5L104.3X1	40°	1x17.5	21	1430	1430	68	3000	92



	Code	Dimensions [mm] L W H	Pallet quantity	Quantity in package	Net weight [kg]
22	002X.5L101.3X1	196 196 144	120	1	2.4
22	002X.5L102.3X1	196 196 144	120	1	2.4
22	002X.5L103.3X1	196 196 144	120	1	2.4
22	002X.5L104.3X1	196 196 144	120	1	2.4



Designed by LUG Design Team

Luminous flux tolerance +/- 10%.

Lighting beam, light intensity distribution and light efficiency were examined in accordance with the EN ISO 17025:2005 norm for EN13032 norm series and the LM-79 norm. Up-to-date product info available on our website www.flashdq.com





## **LIGHT BEAM CURVES**

