



















Modern downlight luminaire for LED light sources for plaster board cellings.

TECHNICAL DATA

Mounting: in the ceiling, with mounting brackets (included) **Body:** powder painted steel sheet and anodized aluminum

Colour: white, black

ELECTRICAL DATA

Power: 220-240V 50/60Hz Includes light source: yes Type of equipment: ED Way of lighting: direct

OPTICAL DATA **GENERAL DATA**

Available on request: metal halide lamps (on request), DALI Other remarks: for metal halide version - please order MH light

sources


Warranty: 5 years

Application: hotels, offices, delicatessen, galleries, boutiques,


shopping centers



	Code	Beam angle	Power LED [W]	Luminaire power [W]	Lumen LED [lm]	Lumen luminaire [lm]	Efficacy [lm/W]	Colour temperature [K]	CRI/Ra
_	22002X.5L401.3X5	24°	4x17,5	83	4x1560	6240	75	4000	92
	22002X.5L402.3X5	24°	4x17,5	83	4x1430	5720	69	3000	92
	22002X.5L403.3X5	40°	4x17,5	83	4x1560	6240	75	4000	92
	22002X.5L404.3X5	40°	4x17.5	83	4x1430	5720	69	3000	92



Code	Dimensions [mm] L W H	Pallet quantity	Quantity in package	Net weight [kg]	
22002X.5L401.3X5	348 348 144	30	1	5.2	
22002X.5L402.3X5	348 348 144	30	1	5.2	
22002X.5L403.3X5	348 348 144	30	1	5.2	
22002X.5L404.3X5	348 348 144	30	1	5.2	





Designed by LUG Design Team

Luminous flux tolerance +/- 10%.

Lighting beam, light intensity distribution and light efficiency were examined in accordance with the EN ISO 17025:2005 norm for EN13032 norm series and the LM-79 norm. Up-to-date product info available on our website www.flashdq.com

Date of issue:

23-6-2017





LIGHT BEAM CURVES

