



MACRON

Product Image





Application Type: WALL MOUNT LUMINAIRES
 Product Name: MACRON Flat - Wall Light
 Ordering Code: 7507-0-3-873-XX
 Lamp Type: LED
 Socket: N/A
 Watt: 20 W
 Lumen: 1800 lm
 Beam: N/A
 Kelvin: 3000 K

Dimension



Light Distribution



*Due to the constancy of product development,
 we reserve the right to alter all specification
 without prior notice.

MACRON

Specification

IEC Standard	IEC 60598-1 General Requirement IEC 60598-2-1 Fixed Luminaires
Protection	IP65 Class I
IK Rating	Protection against mechanical impact IK08 on body and IK10 optical part.
Luminaires Body Housing	High-pressure Die Cast Aluminium alloy body and components. Extruded Aluminium S6063 alloy body with low copper content.
Coating Process	Nano Ceramic surface conversion, resistant to corrosive environment. Luminaire primarily coated with epoxy resin and top coated with UV stabilized polyester powder and cured in digital temperature controlled chamber at 200°C.
Diffuser	Self-extinguishing high impact resistant clear polycarbonate diffuser with UV stabilized additive. Material from Teijin – Japan.
Reflector	Glare shield slanted aluminium louvers.
Gasket	Weather resistant silicone gasket. Working temperature -40°C to +200°C.
External screws	External screws are in stainless steel with protection dipping.
Cable Entry	Cable entry protected by weather proof EPDM grommet and to be used with H05RN-F/ H07RN-F cable with 7-10mm. diameter.
LED	High quality AC LED module. Conform to safety standard and electromagnetic compatibility standard. The whole systems tested to be operated under maximum ambient environment up to +40°C.
Internal wire	Tinned copper conductor with silicone insulated internal wire from ENCO or equivalents. IMQ approved. Working temperature -40°C to +180°C.
Caution	Installation work has to be carried on according to the enclosed installation manual.
Terminal Block/ Connector	Assembled with quick connector for cable with cross section up to 2.5mm ² from ADELS or equivalents. VDE approved. Class1 luminaire provided with the earth connection.
Color	Black (replace the last 2 digits of ordering code with 01) Graphite (replace the last 2 digits of ordering code with 02) Dark Gray (replace the last 2 digits of ordering code with 03) Aluminium Silver (replace the last 2 digits of ordering code with 04) White (replace the last 2 digits of ordering code with 06)