

Modern recessed luminaire for LED light sources.

TECHNICAL DATA

Mounting: directly in the ceiling construction

Body: powder-painted steel sheet

Colour: white

Diffuser: opal plexiglass (PLX)

ELECTRICAL DATA

Power supply efficiency: >90%

Power: 220-240V 50/60Hz

Includes light source: yes

Type of equipment: ED

Electrical connection: WIELAND white GST18i3 plug

OPTICAL DATA

Light distribution: double asymmetric

Way of lighting: direct

Louver: mat aluminum

GENERAL DATA

Lifetime (L70B50): 100 000 h

Lifetime (L80B10): 100 000 h

Lifetime (TM21 L90B10): 50 000 h

Operating temperature range: 0° C ... +40° C

Available on request: emergency module

Additional information: RAL 9003 matte

Other remarks: index PR-10-1707-229-01 - MIRO5 raster

index PR-10-1707-229-02 - MIRO4 raster




Warranty: 3 years

Application: offices, classrooms, auditorium



Code	Power LED [W]	Luminaire power [W]	Lumen LED [lm]	Lumen luminaire [lm]	Colour temperature [K]	CRI/Ra
PR-10-1707-229-01	26	29	3750	3000	4000	≥80
PR-10-1707-229-02	26	29	3750	3000	4000	≥80

Code	Dimensions [mm] L W H	Mounting dimensions [mm] L W	Pallet quantity	Quantity in package	Net weight [kg]
PR-10-1707-229-01	1195 105 86	600 600	105	1	2.4
PR-10-1707-229-02	1195 105 86	600 600	105	1	2.4



Luminous flux tolerance +/- 10%.