

220-240V
50/60 HzIK
10IP
66


Park luminaire in modern form for LED light sources.

TECHNICAL DATA**Mounting:** on pillar $\varnothing 48/60/76$ mm, with mounting bracket (included)**Body:** high pressure die-cast aluminum**Lateral Surface Wind Exposed:** 0,088 m²**Colour:** gray, graphite**Diffuser:** polycarbonate**ELECTRICAL DATA****Power supply efficiency:** >89%**Power:** 220-240V 50/60Hz**Includes light source:** yes**Type of equipment:** ED, DALI**Electrical connection:** luminaire equipped with 2x1,5 mm² wire with a length of 6 m (II class), luminaire equipped with 4x1,5 mm² wire with a length of 6 m (II class)**OPTICAL DATA****Light distribution:** omnidirectional**Way of lighting:** direct**Type of optic:** O17 - for pedestrian zones**GENERAL DATA****Lifetime (L80B10):** 75 000 h**Available on request:** DALI, LLOC, twilight sensor, 10kV surge protection, NTC**Other remarks:** the pole is not part of the luminaire**Warranty:** 5 years**Application:** avenues, sidewalks, parks, residential, public spaces, playgrounds, promenade, residential area roads

Code	Luminaire power [W]	Lumen luminaire [lm]	Efficacy [lm/W]	Colour temperature [K]	CRI/Ra	Operating temperature range [°C]
13026X.XL012.011	23	2350	102	3000	>80	-40 ... +55
13026X.XL022.011	23	2500	109	4000	>80	-40 ... +55
13026X.XL042.011	32	3350	105	3000	>80	-40 ... +55
13026X.XL052.011	32	3500	109	4000	>80	-40 ... +55
13026X.XL072.011	40	4250	106	3000	>80	-40 ... +50
13026X.XL082.011	40	4400	110	4000	>80	-40 ... +50

13026	.	L012.011
		Type of equipment
	5	ED
	3	DALI
		Colour
	2	gray
	5	graphite

Code	Dimensions [mm] L H	Mounting dimensions [mm] ØS	Pallet quantity	Quantity in package	Net weight [kg]
13026X.XL012.011	360 482	76	18	1	4.4
13026X.XL022.011	360 482	76	18	1	4.4
13026X.XL042.011	360 482	76	18	1	4.4
13026X.XL052.011	360 482	76	18	1	4.4
13026X.XL072.011	360 482	76	18	1	4.4
13026X.XL082.011	360 482	76	18	1	4.4



Luminous flux tolerance +/- 10%.

Power tolerance +/- 5%.

Please note that the standard luminaire is not intended for use in an environment with a high degree of salinity. If it is required to adapt the luminaire to work in such an environment, please contact our Sales Department to confirm the possibility of using an additional protective coating.

Up-to-date product info and General Warranty Terms available on our website www.luglightfactory.com

OTHER PICTURES**ACCESSORIES**


■ 150175.00983
□ 150172.00968

Cover masking ø48 mm



■ 150175.00982
□ 150172.00966

Cover masking ø60 mm

LIGHT BEAM CURVES**WAY OF LIGHTING**

130262.5L082.011



Luminous flux tolerance +/- 10%.

Power tolerance +/- 5%.

Please note that the standard luminaire is not intended for use in an environment with a high degree of salinity. If it is required to adapt the luminaire to work in such an environment, please contact our Sales Department to confirm the possibility of using an additional protective coating.

Up-to-date product info and General Warranty Terms available on our website www.luglightfactory.com