## WHC923E16X





## Freestanding wall chimney cooker hood



Polyurethane filter



TouchFree coating



LedLight

Re-circulating hoods



Noise level

Useful tips

What capacity do you need?

Freestanding wall cooker hood

Venting with air extraction or recirculation

Energy class: B

Material of housing/chimney: stainless steel / stainless steel Colour of housing/chimney: stainless steel / stainless steel

Lightning efficiency class: A Grease filtering efficiency class: A Fluid dynamic efficiency class: B

Maximum extraction rate by extraction operation: 520 m³/h Maximum extraction rate by recirculation operation: 390 m³/h

Venting tube diameter: 15 cm

Air flow by extraction version, step 1: 238 m³/h Air flow by extraction version, step 2: 380 m³/h Air flow by extraction version, step 3: 520 m³/h

Mechanic control

Control setting: Button control Number of speed positions: 3

TouchFree Inox Lamp type: LED On/off light switch Number of lights: 2 Power of lights: 6 W

Filter material: Washable aluminium with polyurethane foam Coal filter code (optional as separate purchase): 315275

Motor type: Capacitor motor

Number of motors: 1

No return airflow flap: 150 mm

Max. noise level: 63 dB(A)re 1 pW

Height: 250 mm

Min. height of the chimney: 545 mm Max. height of the chimney: 875 mm Annual energy consumption: 60.4 kWh Dimensions (W×H×D): 90 x 25 x 50 cm

Dimensions of packed product (W×H×D): 101.5 × 43.5 × 56 cm

Net weight: 11.5 kg Gross weight: 16.4 kg Connected load: 141 W

Nominal current of fuse: 10 amp

Product code: 514496 EAN code: 3838942072369

