



Product Data Sheet:

OUTBOARD ENGINE OIL 2T

Product Description:

OUTBOARD ENGINE OIL 2T is a premium ashless 2-stroke lubricant developed for high powered water-cooled outboard engines fitted with oil-injection or premix systems and is formulated with the latest additive technology that helps in keeping the engine cleaner.

OUTBOARD ENGINE OIL 2T is easy to mix and forms stable mixtures with gasoline also at lower temperatures.

OUTBOARD ENGINE OIL 2T is suited for high powered 2-cycle water cooled outboard engines requiring an NMMA TC-W3® quality specification.

Specifications:
Exceeds: NMMA TC-W3®

Property:	Test Method:	Typical Values:
Density @ 15°C	ASTM D4052	881 kg/m ³
Kinematic Viscosity @ 40°C	ASTM D7042	46 mm ² /s
Kinematic Viscosity @ 100°C	ASTM D7042	6.9 mm ² /s
Viscosity Index	ASTM D2270	130
Flash Point	ASTM D92	>96°C
Pour Point	ASTM D97	-33°C
Total Base Number	ASTM D2896	3.45 mgKOH/g

Product nr: 4296

Date Issued: 08/08/2011

Date Superseded: 07/07/2010

Revision nr: 01