



## Neste Allrex EP 2

Universal grease

### PERFORMANCE CLAIMS

DIN 51502: KP2K-30

ISO 6743: ISO-L-XCCIB2

MAN 283 Li-P 2

MB Blatt 267.0

VOLVO Std 1277.18

### DESCRIPTION

Neste Allrex EP 2 is made of high-quality lithium soap and top class mineral base oils. The grease contains effective EP additives as well as additives against rust, oxidation and wear.

### SPECIAL FEATURES AND BENEFITS

- Multiple applications
- Good pumpability
- Good antirust properties
- Good EP and antiwear properties

---

### TYPICAL CHARACTERISTICS

|                                   |            |
|-----------------------------------|------------|
| Density kg/m <sup>3</sup> 20°C    | 950        |
| NLGI class                        | 2          |
| Penetration                       | 265-295    |
| Dropping point °C                 | >180       |
| Base oil viscosity cSt/40 °C      | 200        |
| Base oil viscosity cSt/100 °C     | 15         |
| SKF Emcor ISO 11007, salt water   | 2-3        |
| 4-ball test, welding load N       | 2600       |
| Water resistance 90°C DIN 51807:1 | 0          |
| Operating temperature range, °C   | -30...+120 |
| Max. temporary temperature, °C    | 130        |

---

### APPLICATIONS

Allrex EP 2 is recommended for general use in industrial grease lubrication, including impact-type loads. It can also be used for the general and wheel-bearing lubrication of vehicles, construction machinery and agricultural equipment.

---