



Neste Avora Spray

Open-gear and wire rope grease

PERFORMANCE CLAIMS

DIN 51502: OGP0.5N-20

ISO 12924: ISO-L-XB(F)DIB0.5

DESCRIPTION

Neste Avora Spray is made of mineral base oil and lithium/calcium complex thickener. The product has excellent water resistance, load carrying capacity and EP properties

SPECIAL FEATURES AND BENEFITS

- easy to apply
- excellent corrosion protection
- excellent resistance against water
- excellent anti-wear and EP properties

TYPICAL CHARACTERISTICS

Density kg/m ³ 20°C	940
NLGI class	0.5
Penetration	335-365
Dropping point °C	>260
Base oil viscosity cSt/40 °C	850
Base oil viscosity cSt/100 °C	43
SKF Emcor ISO 11007, salt water	0-0
4-ball test, welding load N	7500
Water resistance 90°C DIN 51807:1	1
Operating temperature range °C	-20...+140
Max. temporary temperature, °C	180

APPLICATIONS

Neste Avora Spray is used for the lubrication of open gears, gear racks, steel cables and chains at both hot and cold temperatures. It has also good damp and water wash-out resistance. Neste Avora Spray can be applied on both dry and wet surfaces.

Neste Avora Spray is packed in a handy aerosol bottle.