



Neste Hydraulic 22 Super

Super grade hydraulic oil

PERFORMANCE CLAIMS

DIN 51524 part 3 HVLP

ISO 11158 HV

DESCRIPTION

Neste Hydraulic 15 Super is top quality Super-class multigrade hydraulic oil for demanding outdoor use. It has an extremely wide operating temperature range and superb cold properties. Cold properties and high viscosity index enable best performance even in extremely cold conditions. Special additives developed for extreme conditions give effective protection against wear, oxidation and corrosion. Due to its good air release and de-emulsibility properties it can be used even in severe conditions.

SPECIAL FEATURES AND BENEFITS

- Extra wide operating temperature area
- Excellent antiwear properties
- Effective protection against corrosion

TYPICAL CHARACTERISTICS

Density kg/m ³ 15°C	850
Flash Point °C (COC)	202
Pour Point °C	-54
Viscosity index	168
Viscosity cSt/ 40 °C	22
Viscosity cSt/ 100 °C	5.1
Viscosity cSt/-20 °C	664

APPLICATIONS

Neste Hydraulic 22 Super has excellent cold properties for winter time use.

Neste Hydraulic Super oils are used, for example in excavators, forestry equipments, earth movers, fork lift trucks, cranes etc. hydraulics.
