



## Neste Hydraulic HLP 68

Industrial hydraulic oil

### PERFORMANCE CLAIMS

DIN 51524 part 2, HLP

ISO 11158 HL, HM

Denison HF-0, HF-1, HF-2

Vickers (Eaton) I-286-S

Vickers (Eaton) M-2950-S

Cincinnati Machine P-68, P-69, P-70

Bosch Rexroth RE 90 220

DIN 51506 VDL

### DESCRIPTION

Neste Hydraulic HLP 68 is made of top quality mineral oil. Special additives give them efficient protection against wear, corrosion, oxidation and foaming.

### SPECIAL FEATURES AND BENEFITS

- Effective protection against wear
- Good corrosion protection
- Good oxidation stability
- Excellent shear stability

---

### TYPICAL CHARACTERISTICS

Density kg/m <sup>3</sup> 15°C	862
Flash Point °C (COC)	242
Pour Point °C	-27
Viscosity index	102
Viscosity cSt/ 40 °C	68
Viscosity cSt/ 100 °C	8.9
FZG test (A/8,3/90) DIN 51354	12

---

### APPLICATIONS

Neste Hydraulic HLP 68 is a hydraulic oil suitable for industrial and many automotive hydraulic systems. It can also be used to lubricate a number of different machine tools, gear systems and various bearings..

---