

Neste Industrial Gear 460 EP

Industrial EP gear oil

PERFORMANCE CLAIMS DIN 51517-3 (CLP) ISO-L-CKC 460 AGMA 9005-E02 7 EP David Brown 7EP U.S. Steel 224

DESCRIPTION

Neste Industrial Gear EP oils are made of top-quality paraffinic base oils mixed with unleaded extreme pressure additives containing phosphorus and sulphur.

SPECIAL FEATURES AND BENEFITS

- -Excellent EP properties
- -Good anti-corrosion properties
- -Excellent oxidation resistance

TYPICAL CHARACTERISTICS

Density kg/m ³ 15°C	902
Flash Point ^o C (COC)	278
Pour Point ^o C	-15
Viscosity index	98
Viscosity cSt/ 40 °C	460
Viscosity cSt/ 100 °C	31.1
Rust-Preventing Characteristics, ASTM D665 B	pass
4-Ball EP, Weld load, kg, ASTM D2783	250
FZG test (A/8.3/90), DIN 51354	>12
FZG Micropitting, FVA Nr. 54, Fail	10
Foaming Characteristics, ASTM D892, I/II/III	0/0,0/0,0/0
Dynamic seal test, DIN 3761	pass
Static seal test, DIN 53521	pass

APPLICATIONS

Neste Industrial Gear EP oils are recommended for lubricating heavy-duty gears. They are also suitable for many heavily loaded sleeve and rolling bearings, and can be used for vibrating and over-loaded objects. Neste Industrial Gear EP oils include a suitable grade for every gear type, every size and every performance