



Neste OH Grease 0

Special grease for off-highway equipment during wintertime

PERFORMANCE CLAIMS

DIN 51502: KP0K-40

ISO 12924: ISO-L-XD(F)CHB0

DESCRIPTION

Neste OH Grease 0 is made of high viscosity mineral oil and calcium-12-hydroxystearate. The product has excellent adhesion to metal surfaces, tackified structure, excellent pumpability and excellent resistance against water. These properties give good protection against wear and corrosion for longer service intervals. EP and antiwear additives of Neste OH Grease 0 give excellent protection against heavy or shock loads.

SPECIAL FEATURES AND BENEFITS

- Excellent adhesion on metal surfaces
- Excellent pumpability also during winterime
- Good protectiong against shock loads
- Excellent water protection

TYPICAL CHARACTERISTICS

Density kg/m ³ 20°C	890
Drop point °C	>120
Penetration , worked 60 strokes	355 - 385
NLGI grade	0
Operating temperature range °C	-40...+120
Base oil viscosity cSt/40 °C	1370
Thickener	anhydrous calcium
Colour	Red

Neste OH Grease 0 is recommended for lubrication of pin and bushing assemblies, hydraulic linkage pins, pivot pins etc. in construction and logging machines and agricultural equipment during wintertime.
