



## Neste OH Grease 2

Special grease for off-highway equipment

### PERFORMANCE CLAIMS

DIN 51502: KP2K-30

ISO 12924: ISO-L-XC(F)CIB2

### DESCRIPTION

Neste OH Grease 2 is made of high viscosity mineral oil and calcium-12-hydroxystearate. The product has excellent adhesion to metal surfaces, tackified structure and excellent resistance against water. These properties give good protection against wear and corrosion for longer service intervals. EP and antiwear additives of Neste OH Grease 2 give excellent protection against heavy or shock loads.

### SPECIAL FEATURES AND BENEFITS

- Excellent adhesion on metal surfaces
- Good antiwear and EP properties
- Good protection against shock loads
- Excellent water protection

---

### TYPICAL CHARACTERISTICS

Density kg/m <sup>3</sup> 20°C	900
Drop point °C	>140
Penetration , worked 60 strokes	265 - 295
NLGI grade	2
Operating temperature range °C	-30...+120
Base oil viscosity cSt/40 °C	1380
Thickener	anhydrous calcium
Colour	Red

---

Neste OH Grease 2 is recommended for lubrication of pin and bushing assemblies, hydraulic linkage pins, pivot pins etc. in construction and logging machines and agricultural equipment. The product can be also used as chassis grease for vehicles and for lubrication of slow speed journal and roller bearings. Not recommended for wheel bearings of vehicles.

---