



Neste Premium Gear UTTO

Synthetic hydraulic and driveline oil for agricultural equipment

PERFORMANCE CLAIMS

API GL-4
 Caterpillar TO-2
 Case MS 1206
 Case MS 1207
 Case MS 1209
 Ford M2C 86 A/B/C, 134 C/D
 John Deere J 20 A/C
 John Deere J 20 B/D
 Massey Ferguson M1110, M1127A, M1135, M1143
 MF CMS M1145
 New Holland NH-410B
 Volvo 97303 (VCE WB 101)

DESCRIPTION

Neste Premium Gear UTTO is a combined gear and hydraulic oils for tractors, with the friction properties required for wet brakes. Its wear resistance exceeds that of ordinary gear/hydraulic oils. It also offers good oxidation and corrosion resistance.

SPECIAL FEATURES AND BENEFITS

- Good EP properties
- Multipurpose lubricant
- Very good wear protection
- Extra wide operating temperature area

TYPICAL CHARACTERISTICS

Density kg/m ³ 15°C	867
Flash Point °C (COC)	226
Pour Point °C	-42
Viscosity index	160
Viscosity cSt/ 40 °C	64
Viscosity cSt/ 100 °C	10.8
Viscosity cP/ °C	3000 / -20
SAE equivalence	5W-30

APPLICATIONS

Neste Premium Gear UTTO is a synthetic quality suitable for an extremely wide range of temperatures. It works just as well in hot summer conditions as in a severe below-zero cold. Neste Premium Gear UTTO fills Caterpillar's hydraulic oil requirement min. 900ppm for zinc.
