



Neste Pro+ Coolant M

Longlife multi vehicle coolant concentrate

PERFORMANCE CLAIMS

Cummins CES 14603
 Deutz DQC CC-14
 Liebherr Minimum LH-01-COL3A
 MAN 324 Typ Si-OAT
 MB-Approval 325.5
 MB-Approval 325.6
 MTU MTL 5048
 Porsche: MY 1996-
 Scania 2008-
 VW G12++ (TL-774 G)

BS 6580:2010
 ASTM D3306 Type I
 ASTM D4985
 SAE J1034
 ÖNORM V 5123
 CUNA NC 956-16
 JIS K 2234:2006
 SANS 1251:2005
 China GB 29743-2013
 AS 2108-2004

DESCRIPTION

Neste Pro+ Coolant M is an monoethylene glycol based longlife engine coolant concentrate. It fullfills requirements of many car manufacturers and gives excellent protection for engine and cooling system.

SPECIAL FEATURES AND BENEFITS

- Hybrid organic acid technology (Si-OAT)
- Nitrite free
- Excellent freezing protection
- Ultimate corrosion protection

TYPICAL CHARACTERISTICS

Density kg/m ³ 20°C	1125
Equilibrium boiling point, 50 vol-%/ASTM D1120	min 160 °C
Reserve alkalinity, 50 vol-%/ASTM D1121	8-11 ml
pH, vol-50 %/ASTM D1287	8,2-8,6
Freezing point, 50 vol-%	-37 °C
Freezing point, 33 vol-%	-18 °C
Colour	Red

APPLICATIONS

Neste Pro+ Coolant M is suitable for both passenger cars and trucks. It fullfills the requirements of many engine OEMs, e. g. Audi/Seat/Skoda/Volkswagen (G12++), Porsche, Scania, Cummins & Deutz.

Check the suitability of the product in the manual. It is not recommended to mix the product with other coolants.
