



Neste Turbo+ E6 5W-30

Fully synthetic multigrade diesel engine oil

PERFORMANCE CLAIMS

SAE 5W-30

API CJ-4, CI-4, CH-4

ACEA E9/E7/E6/E4

Cummins CES 20081

Deutz DQC IV-10 LA

Iveco 18-1804 TLS E6

Mack EO-O Premium Plus

MAN 3271-1, 3477, 3575, 3677, 3691

MB-Approval 228.51

MB 228.31

MTU Type 3.1, 2.1

Renault RLD-3, RXD

Scania LDF-4, Scania Low Ash

Volvo VDS-4, VDS-3, CNG

DESCRIPTION

Neste Turbo+ E6 5W-30 is fully synthetic ultra high performance heavy duty diesel engine oil for new Euro 4 and Euro 5 low emission diesel engines with long oil drain intervals. In these engines emission aftertreatment systems such as DPF, CRT and SCR requires low SAPS (Sulphated Ash, Phosphorus and Sulphur) oils.

SPECIAL FEATURES AND BENEFITS

- Excellent cold start performance
- Improved fuel economy benefits
- Long drain interval
- Low emission

TYPICAL CHARACTERISTICS

Density kg/m ³ 15°C	861
Flash Point °C (COC)	214
Pour Point °C	-45
Viscosity index	166
Viscosity cSt/ 40 °C	73.7
Viscosity cSt/ 100 °C	12.2
Viscosity cP/ °C	6600 / -30
TBN, mg KOH/g	13
Sulfated ash	0,9

APPLICATIONS

Suitable for Euro 1,2,3,4,5,6 engines. Please consult your owners handbook.