



Neste Pro 5W-30

Fully synthetic motor oil

PERFORMANCE CLAIMS

SAE 5W-30

API SL, SJ/CF

ACEA A3/B4, A3/B3

BMW Longlife-01

Fiat 9.55535-G1

GM-LL-A-025, GM-LL-B-025

APPROVALS

MB-Approval 229.3

MB-Approval 229.5

VW 50200/50500

DESCRIPTION

Neste Pro 5W-30 is a fully synthetic high performance motor oil for extended oil drain intervals for passenger cars and vans.

SPECIAL FEATURES AND BENEFITS

- Excellent cold start performance
- Improved fuel economy benefits
- Long drain interval

TYPICAL CHARACTERISTICS

	5W-30
Density kg/m ³ 15°C	855
Flash Point °C (COG)	228
Pour Point °C	-42
Viscosity index	170
Viscosity cSt/ 40 °C	67
Viscosity cSt/ 100 °C	11.6
Viscosity cP/ °C	6100 / -30
TBN (mg KOH/g)	10,4

APPLICATIONS

Neste Pro 5W-30 is recommended for engines with turbocharges and provides easy start-up required by catalytic converters. Exceeds the requirements of many car manufacturer's requirements but it is excellent oil also for older vehicles and for general use.
