



Neste Pro C3 5W-40

Fully Synthetic Motor Oil

PERFORMANCE CLAIMS

SAE 5W-40

API SN, SM, SL, SJ/CF

ACEA C3

BMW Longlife -04

Ford WSS-M2C917A

Meets GM dexos2 requirements

MB-Approval 226.5

MB-Approval 229.31

Porsche A40

Renault RN0700,RN0710

VW 502.00/505.00/505.01

DESCRIPTION

Neste Pro C3 5W-40 is new age fully synthetic motor oil.

Neste Pro C3 5W-40 is especially designed for highly developed modern engines with emission after treatment systems in both diesel and gasoline powered vehicles.

It exceeds new API SN and ACEA C3 performance requirements and many of car manufacturers' standards required for newer modern diesel and gasoline car engines such as BMW LL-04 and MB 229.31.

SPECIAL FEATURES AND BENEFITS

- Excellent cold start performance
- Fuel economy benefits
- Long drain interval
- Low emission

TYPICAL CHARACTERISTICS

Density kg/m ³ 15°C	853
Flash Point °C (COC)	244
Pour Point °C	-51
Viscosity index	170
Viscosity cSt/ 40 °C	87
Viscosity cSt/ 100 °C	14.2
Viscosity cP/ °C	6000 / -30

APPLICATIONS

Neste Pro C3 5W-40 is recommended for year-round use in gasoline and diesel engines of passenger cars and vans in all conditions.

Neste Pro C3 5W-40 exceeds the requirements of many car manufacturers' standards required for newer modern car engines but it is excellent oil also for older vehicles and for general use.