



Product Data Sheet

MOTOR OIL SM 5W-40

Product Description:

MOTOR OIL SM 5W-40 is an universal high performance fuel saving oil based on 100% synthetic technology for use in gasoline- and diesel engines of passenger car and light vans with or without turbocharger. This product is unsuitable for diesel engines equipped with a Diesel Particle Filter (DPF).

MOTOR OIL SM 5W-40 is formulated with high quality synthetic base stocks in combination with an unique additive technology to achieve the following performance:

- Very good low temperature properties.
- Protection to wear by cold start.
- Very high thermal- and oxidation stability.
- Excellent resistance against foaming, corrosion and wear.
- High dispersancy and detergency level.
- High viscosity index.

MOTOR OIL SM 5W-40 exceeds the following performance criteria:

Approved	MB-Approval 229.3	BMW LL-01	VW 502.00 / 505.00
Exceeds	API SN/CF GM-LL-B025	ACEA A3/B4 PSA B 71 2296	Renault RN 0700/0710 Porsche A40

Property	Unit	Test Method	Typical Value
SAE Grade		SAE J3000	5W-40
Density@15°C	kg/m ³	ASTM D4052	851
Kin. Viscosity @40°C	mm ² /s	ASTM D7042	86
Kin. Viscosity @100°C	mm ² /s	ASTM D7042	14.1
Viscosity Index		ASTM D2270	155
Viscosity CCS @-30°C, max	cP	ASTM D2270	6600
Flash Point COC	°C	ASTM D92	>201
Pour Point	°C	ASTM D97	-39
Total Base Number	mgKOH/g	ASTM d2896	9.6
Sulphated Ash	%Wt	ASTM D874	1.16

Product Nr: 4204	Date Issued: 24-08-2012	Date Superseded: 19-08-2013	Revision nr: 4
------------------	-------------------------	-----------------------------	----------------