

## **Product Data Sheet**

## **ENGINE OIL EHPD 10W-40**

## **Product Description:**

ENGINE OIL EHPD 10W-40 is a high performance semi synthetic engine oil to be used in diesel engines in lightand heavy commercial vehicles with or without turbocharger designed for use in Euro-II, Euro-III and EURO-IV emission requirements and engines equipped with EGR and/or SCR exhaust after treatment system. ENGINE OIL EHPD 10W-40 is unsuitable for diesel engines equipped with a Diesel Particle Filter (DPF)

ENGINE OIL EHPD 10W-40 is based on high performance synthetic and mineral base oil in combination with a specially selected additive technology to ensure the following properties:

- Excellent thermal and oxidation stability.
- Excellent protection against forming of "Bore Polishing".
- Suitable for Low emission engine equipped with EGR and SCR technology
- Excellent protection against wear, foam en corrosion.
- Low temperature properties, to ensure a smooth cold start.
- Extended oil drain interval possible.

**ENGINE OIL EHPD 10W-40** exceeds the following performance criteria:

API CI-4	ACEA E7/E4	MB 228.5	MAN M3277	Renault RLD-2
Volvo VDS-3	Mack EO-N	MTU Type 3	Scania LDF-2	
Property		Unit	Test Method	Typical Value
SAE Grade			SAE J3000	10W-40
Density@15°C		kg/m <sup>3</sup>	<b>ASTM D4052</b>	873
Kin. Viscosity @40°C		mm²/s	<b>ASTM D7042</b>	99
Kin. Viscosity @100°C		mm²/s	<b>ASTM D7042</b>	14.6
Viscosity Index			<b>ASTM D2270</b>	155
Viscosity CCS @-25°C, max		сР	<b>ASTM D2270</b>	7000
Flash Point COC		°C	ASTM D92	>201
Pour Point		<b>°C</b>	ASTM D97	-33
Total Base Number		mgKOH/g	ASTM d2896	12.5
Sulpated Ash		%Wt	ASTM D874	1.6
Product Nr: 4250	Date Issued: 06-07	7-2012 Date Superse	eded: 07-08-2013	Revision nr: 05