



**Product Data Sheet:**

# ATF DX II

**Product Description:**

ATF DX II is an oil for automatic transmissions in older vehicles specifying the use of DEXRON® II quality fluids. High quality base oils and special additives provides resistance towards oxidation, provides and shows improved frictional properties.

ATF DX II exceeds the performance requirements of General Motors DEXRON® IID and provides excellent shifting behaviour under all conditions.

ATF DX II has good thermo-oxidative stability preventing the formation of undesirable deposits. The high viscosity index ensures adequate lubrication under all circumstances, while the excellent foam control leads to a long lasting, smooth shifting.

ATF DX II is recommended for all vehicles of General Motors requiring DEXRON® IID quality fluids and is also recommended for certain power steering units, certain manual transmissions and hydraulic systems where such fluids are required.

**Specifications:**

**Exceeds:** General Motors DEXRON® IID

Property:	Test Method:	Typical Values:
Density @ 15°C	ASTM D4052	863 kg/m <sup>3</sup>
Kinematic Viscosity @ 40°C	ASTM D7042	37.3 mm <sup>2</sup> /s
Kinematic Viscosity @ 100°C	ASTM D7042	7.0 mm <sup>2</sup> /s
Dynamic Viscosity @ -40°C	ASTM D2983	<50000 mPa.s
Viscosity Index	ASTM D2270	>140
Flash Point (COC)	ASTM D92	170°C
Pour Point	ASTM D97	<-42°C

Product nr: 4320

Date Issued: 29/05/2012

Date Superseded: 08/08/2011

Revision nr: 01