



**Product Data Sheet:**

# ATF DX VI

## Product Description:

**ATF DX VI** is a supreme performance long lasting automatic transmission fluid, especially developed for all 2006, and beyond, General Motors vehicles equipped with automatic transmissions.

**ATF DX VI** is formulated with exceptional quality base fluids and the latest additive technology in order to achieve outstanding oxidation resistance, improved friction characteristics and optimal wear protection.

**ATF DX VI** has outstanding thermo-oxidative stability, preventing the formation of undesirable deposits. The high viscosity index ensures adequate lubrication in both high operating and low starting temperatures. Enhanced low temperature fluidity assists in good cold shifting performance.

**ATF DX VI** provides better protection against rust and corrosion while the excellent foam control leads to long lasting, smooth shifting behaviour.

**ATF DX VI** is recommended for all vehicles of General Motors from 2006 and beyond equipped with Hydramatic transmissions. General Motors vehicles with six speed Hydramatic transmissions requiring DEXRON® VI quality fluids. Being fully backwards compatible, **ATF DX VI** is also recommended for automatic transmissions requiring DEXRON® III (H), DEXRON® III(G), DEXRON®IIE and DEXRON®IID fluids.

## Specifications:

**Exceeds:** General Motors DEXRON®VI

<b>Property:</b>	<b>Test Method:</b>	<b>Typical Values:</b>
Density @ 15°C	ASTM D4052	842 kg/m <sup>3</sup>
Kinematic Viscosity @ 40°C	ASTM D7042	30 mm <sup>2</sup> /s
Kinematic Viscosity @ 100°C	ASTM D7042	6.1 mm <sup>2</sup> /s
Dynamic Viscosity @ -40°C	ASTM D5293	<150000 mPa.s
Viscosity Index	ASTM D2270	150
Flash Point (COC)	ASTM D92	290°C
Pour Point	ASTM D97	-48°C
Colour	Visual	Red

Product nr: 4324

Date Issued: 08/08/2011

Date Superseded: 11/07/2010

Revision nr: 01