



Product Data Sheet

AUTOGEAR OIL MTF 75W-80

Product Description:

AUTOGEAR OIL MTF 75W-80 is a high quality manual transmission fluid designed for passenger- and light commercial vehicles using both manual transmissions and transaxles. Not suitable for differentials and other API: GL-5 applications

AUTOGEAR OIL MTF 75W-80 is based on high quality synthetic technology base oil in combination with a special additive package to ensure the following properties:

- Exceptional thermo-oxidative stability.
- Superior lubricating properties provide improved fuel economy.
- Exceptional load bearing characteristics.
- Effective rust and corrosion protection.
- Outstanding low temperature fluidity provides smoother shifting at low ambient temperatures.
- Good gear engagement with a variety of synchronizer materials including brass, carbon, sintered bronze and molybdenum

AUTOGEAR OIL MTF 75W-80 exceeds the following performance criteria.:

API: GL-4	BMW MTF LT-2	BMW MTF LT-3	Ford WSD-M2C200-C
GM 1940182	GM 1940764	GM 1940768	Ford WSS-M2C200-D
MB 235.10	PSA B71 2230	MTF94	Honda MTF
Honda MTF II	Volvo 97308	Volvo 97309	VW G 009 317
VW G 052 171	VW G 052 178	VW G 052 512	VW G 052 726
VW G 060 726	VW G50	Renault	

Property	Unit	Test Method	Typical Value
SAE Grade		SAE J3000	75W-80
Density@15°C	kg/m ³	ASTM D4052	869
Kin. Viscosity @40°C	mm ² /s	ASTM D7042	55
Kin. Viscosity @100°C	mm ² /s	ASTM D7042	9.4
Brookfield Viscosity @-40°C	cP	ASTM D2983	120000
Viscosity Index		ASTM D2270	156
Flash Point COC	°C	ASTM D92	>201
Pour Point	°C	ASTM D97	-36

Product Nr: 4338

Date Issued: 08-10-2015

Date Superseded:

Revision nr: -