

# SAFETY DATA SHEET



according to regulation 1907/2006/EC (REACH) and 1272/2008/EC

**MOL-LUB Ltd.**

Trade name: **MOL DOT 5.1 brake fluid**

Version: 6

Latest revision: 07. 11. 2022

Date of issue: 03. 02. 2015

Page: 1/(12)

## SECTION 1 Identification of the substance/mixture and of the company/undertaking

### 1.1 Product identifier:

**MOL DOT 5.1 brake fluid**

UFI: RF10-G0D2-100S-N32N

### 1.2 Relevant identified uses of the substance or mixture and uses advised against

Relevant identified uses: brake fluid.

Uses advised against: application other than the above.

### 1.3 Details of the supplier of the safety data sheet:

MOL-LUB Lubricant Production Trade and Service Limited Liability Company

H-2931 Almásfüzitő, Fő út 21., Hungary

Phone / Fax: +36 34 526 330 / +36 34 526 391

E-mail: kenoanyag@mol.hu

Request SDS of:

MOL-LUB Lubricant Production Trade and Service Limited Liability Company

Customer Service Center

H-2931 Almásfüzitő, Fő út 21., Hungary

Phone / Fax: +36 80 201 296 / +36 34 348 010

Responsible for SDS:

MOL-LUB Ltd.

Phone: +36 80 201 296

e-mail: EBKHelpdesk@MOL.hu

### 1.4 Emergency telephone number

Emergency telephone (on workdays: 07-15<sup>20</sup> h (CET)): +36 34 526 210

Health Toxicological Information Service (ETTSZ 1097 Budapest, Albert Flórián st. 2-6.)

Tel.: +36 80 201 199 (0-24 h, free number, can only be called from Hungary).

+36 1 476 6464 (0-24 h, can be called for a normal fee - also from abroad)

National Health Toxicological Information Service:

## SECTION 2 Hazards identification

### 2.1 Classification of the substance or mixture

Hazard Class and Category: Hazard statement:

Repr. 2

H361d

Suspected of damaging the unborn child.

# SAFETY DATA SHEET

according to regulation 1907/2006/EC (REACH) and 1272/2008/EC



**MOL-LUB Ltd.**

Trade name: **MOL DOT 5.1 brake fluid**

Version: 6    Latest revision: 07. 11. 2022    Date of issue: 03. 02. 2015    Page: 2/(12)

## 2.2 Label elements

Product identification: Trade name: **MOL DOT 5.1 brake fluid**

Hazardous components: Tris[2-[2-(2-methoxyethoxy) ethoxy]ethyl] orthoborate

GHS Pictogram:



Signal word:

Warning

Hazard statement:

**H361d** Suspected of damaging the unborn child.

Supplemental hazard information: -

Precautionary statements – General:

**P101** If medical advice is needed, have product container or label at hand.

**P102** Keep out of reach of children.

Precautionary statements – Prevention:

**P202** Do not handle until all safety precautions have been read and understood.

**P280** Wear protective gloves, protective clothing, eye protection/face protection.

Precautionary statements - Response

**P301 + P310** IF SWALLOWED: Immediately call a POISON CENTER or a doctor.

**P305 + P351 + P338** IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing.

Precautionary statements – Storage: -

Precautionary statements – Disposal:

**P501** Dispose of contents/container in accordance with national regulation.

Other liabilities for labelling:

Tactile warning of danger: not required.

Transport classification: see section 14.

## 2.3 Other hazards

The product does not contain any PBT or vPvB substance according to annex XIII of regulation (EC) 1907/2006, at a concentration of 0.1% or more.

The mixture does not contain any substance with endocrine disrupting properties, at a concentration of 0.1% or more.

# SAFETY DATA SHEET



according to regulation 1907/2006/EC (REACH) and 1272/2008/EC

**MOL-LUB Ltd.**

Trade name: **MOL DOT 5.1 brake fluid**

Version: 6

Latest revision: 07. 11. 2022

Date of issue: 03. 02. 2015

Page: 3/(12)

## SECTION 3 Composition/information on ingredients

### 3.2 Mixtures

Chemical description: Mixture of the substance.

Component(s) / Hazardous component(s):

Name	EC number	CAS number	Hazard classes and cat.	Hazard statements	Conc. % (m/m)
Tris[2-[2-(2-methoxyethoxy)ethoxy]ethyl] orthoborate REACH Registr. Nr.: 01-2119462824-33	250-418-4	30989-05-0	Repr. 2	H361d	30-90
Triethylene glycol monobutylether* REACH Registr. Nr.: 01-2119531322-53	205-592-6	143-22-6	Eye Dam. 1	H318	1-9.9
Poly(oxy-1,2-ethanediyl), $\alpha$ -butyl- $\omega$ -hydroxy- REACH Registr. Nr.: 01-2119475115-41	500-012-0	9004-77-7	Eye Irrit. 2	H319	0-5
2-(2-Methoxyethoxy) ethanol REACH Registr. Nr.: 01-2119475100-52	203-906-6	111-77-3	Repr. 2	H361d	0-2.99

\*Specific concentration limit:

Eye Irrit. 2; H319:  $20\% \leq C < 30\%$ , Eye Dam. 1; H318:  $C \geq 30\%$

The full text of each relevant H- phrase and Hazard classes and cat. see in Section 16.

## SECTION 4 First aid measures

### 4.1 Description of first aid measures

General information: Never give anything by mouth to an unconscious person, or never induce vomiting.

Inhalation: Remove the affected person to fresh air. Remove the affected person to fresh air. Keep him warm. Keep at rest. If symptoms persist, call medical attention.

Skin contact: Remove contaminated clothing and wash skin with plenty of water, use soap. Do not use solvents or thinners. In case of complaints, get medical attention.

# SAFETY DATA SHEET



according to regulation 1907/2006/EC (REACH) and 1272/2008/EC

**MOL-LUB Ltd.**

Trade name: **MOL DOT 5.1 brake fluid**

Version: 6

Latest revision: 07. 11. 2022

Date of issue: 03. 02. 2015

Page: 4/(12)

Eye contact: Wash affected eyes for at least 10-15 minutes under running water or with isotonic water (20-30°C), with eyelids held open. Remove contact lenses, if present and easy to do. Get medical attention. Continue rinsing during transport.

Ingestion: If swallowed rinse mouth, give to drink plenty of water.  
If medical treatment is delayed, drink 90-120 ml of 40% alcohol (e.g. liqueur) for an adult. Children should be given 2 ml/kg body weight. Do not induce vomiting unless directed to do so by your doctor. Do not induce vomiting unless directed to do so by your doctor. In case of spontaneous vomiting, the head should be turned down. Get medical attention immediately.

Protection of first-aid person: No individual specifications.

4.2 Most important symptoms and effects, both acute and delayed  
Suspected of damaging the unborn child.

4.3 Indication of any immediate medical attention and special treatment needed  
Treat according to symptoms, no known specific antidote.

## SECTION 5 Fire-fighting measures

Fire hazards:  
Combustible.

5.1 Extinguishing media

Suitable extinguishing media:

Alcohol resistant foam, carbon dioxide, dry chemical powder, water spray (fog).

Unsuitable extinguishing media:

Full water jet.

5.2 Special hazards arising from the substance or mixture

Hazardous combustion products:

On burning carbon dioxide, carbon monoxide and other toxic fumes / gases can be formed.

5.3 Advice for fire-fighters

Special protective equipment:

According to the existing fire-fighting regulations (breathing apparatus).

Further information:

In case of fire, keep containers cool with water spray.

Collect contaminated firefighting water separately. It must not enter drains.

Contaminated extinguishing water must be disposed of in accordance with official regulations.

# SAFETY DATA SHEET

according to regulation 1907/2006/EC (REACH) and 1272/2008/EC



**MOL-LUB Ltd.**

Trade name: **MOL DOT 5.1 brake fluid**

Version: 6

Latest revision: 07. 11. 2022

Date of issue: 03. 02. 2015

Page: 5/(12)

## SECTION 6 Accidental release measures

### 6.1 Personal precautions, protective equipment and emergency procedures

Personal precautions: see Section 8.

Keep unnecessary personnel away.

Avoid contact with eyes, skin and clothing.

Danger of slipping on leaked out/spilled product.

Adequate ventilation required.

### 6.2 Environmental precautions:

Prevent spills from entering into natural water, soil and drains by containing the liquid.

Notify relevant authority.

### 6.3 Methods and material for containment and cleaning up

On soil: Contain spilled liquid with sand, earth or other suitable absorbents. Recover free liquid by pumping. Dispose of according to local regulations.

For smaller spills, rags or absorbent granules may be used.

Do not use solvents.

On water: Confine the spillage. Notify local authorities according to regulations.

### 6.4 Reference to other sections

Personal precautions: see section 8.

Waste treatment methods: see section 13.

## SECTION 7 Handling and storage

### 7.1 Precautions for safe handling

Keep general measures applied for normal operations with chemicals.

Use in a well-ventilated area.

Avoid contact with skin and eyes. Avoid prolonged breathing of oil vapours or aerosol formation.

Keep unused containers closed.

Wash hands before breaks and at end of work.

Take off contaminated clothing and wash it before reuse.

When using do not eat, drink or smoke. Avoid splashing the product.

Handling temperature: no data

# SAFETY DATA SHEET



according to regulation 1907/2006/EC (REACH) and 1272/2008/EC

**MOL-LUB Ltd.**

Trade name: **MOL DOT 5.1 brake fluid**

Version: 6    Latest revision: 07. 11. 2022    Date of issue: 03. 02. 2015    Page: 6/(12)

## 7.2 Conditions for safe storage, including any incompatibilities

Storage facilities must comply with regulations for storing of chemicals.

Store in cool, dry, well-ventilated area, in original, tightly closed containers.

Strong oxidizing agents, mineral oils be stored separately.

Suitable container material: mild steel, stainless steel.

Always store in a container made of the same material as the material of the original container.

Storage temperature: 15-30°C

## 7.3 Specific end use(s)

Brake fluid.

## SECTION 8 Exposure controls / personal protection

### 8.1 Control parameters:

EU limits

*2-(2-Methoxyethoxy) ethanol*: TWA (Time weighted average): 50.1 mg/m<sup>3</sup>

CAS: 111-77-3

### 8.2 Exposure controls

Engineering control measures:

Adequate ventilation (general and local exhaust).

Personal protection:

(a) Eye/face protection    Safety glasses with side-shields (EN 166) in case of splashes.

(b) Skin protection

(i) Hand protection    Chemical resistant gloves are recommended (EN 374-2, 374-3, 388),

Material: Butyl

Layer thickness: 0.3 mm. Breakthrough time: 480 minutes.

Material: Nitrile

Layer thickness: 0.2 mm. Breakthrough time: 480 minutes.

Note: Manufacturer's directions for use and the conditions of application should be observed.

(ii) Other

An emergency shower and eye wash station shall be available at the workplace.

# SAFETY DATA SHEET



according to regulation 1907/2006/EC (REACH) and 1272/2008/EC

**MOL-LUB Ltd.**

Trade name: **MOL DOT 5.1 brake fluid**

Version: 6

Latest revision: 07. 11. 2022

Date of issue: 03. 02. 2015

Page: 7/(12)

(c) Respiratory protection Under normal conditions not required.  
When concentrations in air may exceed the limits recommended to use a half face filter mask to protect from overexposure by inhalation (filter against organic vapor: A-P2).

(d) Thermal hazards No data.

Environmental exposure controls:

Do not discharge into drains/surface waters/groundwater.

## SECTION 9 Physical and chemical properties

### 9.1 Information on basic physical and chemical properties

a) Physical state:	liquid
b) Colour:	amber yellow
c) Odour:	mild
d) Melting point/freezing point:	<- 50°C
e) Boiling point or initial boiling point and boiling range:	> 260°C
f) Flammability:	combustible
g) Lower and upper explosion limit:	not explosive
h) Flash point:	> 120°C
i) Auto-ignition temperature:	not available
j) Decomposition temperature:	> 300°C
k) pH at 20°C:	7.0 – 10.5
l) Kinematic viscosity (ASTM D 445) at 20°C:	approx. 5-10 cSt
at 100°C:	not available
m) Solubility Solubility in water:	miscible with water
Solubility in other solvents:	not available
n) Partition coefficient n-octanol/water (log value):	<2.0 (each main component)
o) Vapour pressure at 20°C:	1.00 mbar
p) Density and/or relative density at 20°C:	1.02 – 1.07 g/cm <sup>3</sup>
q) Relative vapour density:	not available
r) Particle characteristics:	not available

### 9.2 Other information

Oxidizing properties:	not oxidize
Ignition temperature:	> 280°C
Evaporation rate:	0.01 (n-butyl acetate = 100)

# SAFETY DATA SHEET



according to regulation 1907/2006/EC (REACH) and 1272/2008/EC

**MOL-LUB Ltd.**

Trade name: **MOL DOT 5.1 brake fluid**

Version: 6

Latest revision: 07. 11. 2022

Date of issue: 03. 02. 2015

Page: 8/(12)

## SECTION 10 Stability and reactivity

- 10.1 Reactivity: Dangerous reactivity not known.  
10.2 Chemical stability: No decomposition if stored and handled properly.  
10.3 Possibility of hazardous reactions: Not known.  
10.4 Conditions to avoid: Not known.  
10.5 Incompatible materials: Strong acids, bases, oxidizing agents, reducing agents.  
10.6 Hazardous decomposition products: No dangerous decomposition products are formed under normal conditions. Hazardous combustion products: See Section 5.

## SECTION 11 Toxicological information

### 11.1 Information on hazard classes as defined in Regulation (EC) No 1272/2008

Acute toxicity: Based on available data, the classification criteria are not met.

Oral: LD<sub>50</sub> (rat) ≥ 5000 mg/kg

Dermal: LD<sub>50</sub> (rabbit) ≥ 3000 mg/kg

Skin corrosion/irritation: Based on available data, the classification criteria are not met.

Serious eye damage/irritation: Based on available data, the classification criteria are not met.

Respiratory or skin sensitisation: Based on available data, the classification criteria are not met.

Germ cell mutagenicity: Based on available data, the classification criteria are not met.

Carcinogenicity: Based on available data, the classification criteria are not met.

Reproductive toxicity: Suspected of damaging the unborn child.

STOT-single exposure: Based on available data, the classification criteria are not met.

STOT-repeated exposure: Based on available data, the classification criteria are not met.

Aspiration hazard: Based on available data, the classification criteria are not met.

### 11.2 Information on other hazards

The mixture does not contain any substance with endocrine disrupting properties, at a concentration of 0.1% or more.

## SECTION 12 Ecological information

### 12.1 Toxicity

Fish (*Oncorhynchus mykiss*): LC<sub>50</sub> > 100 mg/L (96 h)

### 12.2 Persistence and degradability

Biodegradability: The product is inherently degradable. Expected to be easily degradable (based on components, OECD 302B)



# SAFETY DATA SHEET



according to regulation 1907/2006/EC (REACH) and 1272/2008/EC

**MOL-LUB Ltd.**

Trade name: **MOL DOT 5.1 brake fluid**

Version: 6

Latest revision: 07. 11. 2022

Date of issue: 03. 02. 2015

Page: 9/(12)

12.3 Bioaccumulative potential	Log Pow: $\leq 2.0$ (each main component).
12.4 Mobility in soil Mobility in water:	Mobile in the soil until degradation. It is completely miscible with water. Evaporation is not expected.
12.5 Results of PBT and vPvB assessment	Does not contain PBT and vPvB substances, at a concentration of 0.1% or more.
12.6 Endocrine disrupting properties	The mixture does not contain any substance with endocrine disrupting properties, at a concentration of 0.1% or more.
12.7 Other adverse effects Environmental effects: Water hazard class (German):	Large spills may be hazardous to the environment. No data.

## SECTION 13 Disposal considerations

### 13.1 Waste treatment methods

#### Product disposal:

Wastes of the product or used oil should be treated as hazardous waste.

Waste Identification Code: 16 01 13\*

Brake fluids.

Recommended waste treatment method: Must be dumper or incinerated in accordance with local regulations.

#### Packaging disposal:

Containers with product residue should also be treated as hazardous waste according to national and local disposal regulations.

Waste Identification Code: 15 01 10\*

Packaging containing residues of or contaminated by dangerous substances.

Uncontaminated pack can be re-used.

Packs that cannot be cleaned should be disposed of in the same manner as the contents.

Disposal must be in compliance with national and local regulations.

#### Wastewater:

Quality of wastewater emitted to natural water must comply with national and local regulations.

Care should be taken in any case to ensure compliance with EC, national and local regulations.

It is the responsibility of the user to know all relevant national and local regulations.

# SAFETY DATA SHEET



according to regulation 1907/2006/EC (REACH) and 1272/2008/EC

**MOL-LUB Ltd.**

Trade name: **MOL DOT 5.1 brake fluid**

Version: 6

Latest revision: 07. 11. 2022

Date of issue: 03. 02. 2015

Page: 10/(12)

## SECTION 14 Transport information

Land transport:

Road/ Railway

ADR/RID:

Not classified.

14.1 UN number or ID number:

not classified.

14.2 UN proper shipping name:

not classified.

14.3 Transport hazard class(es):

not classified.

14.4 Packing group

not classified.

14.5 Environmental hazards:

not classified.

14.6 Special precautions for user:

not classified.

Waterways:

Inland waterways/ Sea transport ADN/IMDG:

Not apply to the product.

Air transport: ICAO / IATA:

Not apply to the product.

## SECTION 15 Regulatory information

15.1 Safety, health and environmental regulations/legislation specific for the substance or mixture

This safety data sheet has been prepared according to Regulation (EC) No 1907/2006 (mod.: 2020/878/EU) and to Regulation (EC) 1272/2008.

Seveso category: not classified.

15.2 Chemical safety assessment.

not available

## SECTION 16 Other information

The information given in this data sheet is based on our best knowledge at the time of publication. The information is related only to this product and is intended to assist its safe transport, handling and use. The given physical and chemical parameters describe the product only for the purpose of safety requirements and therefore should not be construed as guaranteeing any specific property of the product or as being part of a product specification or any contract.

The manufacturer or supplier shall not take responsibility for any damages from the use other than recommended or other misuse of the product. It is the responsibility of the user to keep regulatory precautions and observe recommendations for safe use of the product.

Classification for mixtures and used evaluation method according to regulation 1272/2008/EC (CLP)

Repr. 2

H361d

calculation method

# SAFETY DATA SHEET



according to regulation 1907/2006/EC (REACH) and 1272/2008/EC

**MOL-LUB Ltd.**

Trade name: **MOL DOT 5.1 brake fluid**

Version: 6

Latest revision: 07. 11. 2022

Date of issue: 03. 02. 2015

Page: 11/(12)

*The full text of each relevant H- phrase and Hazard classes and cat. in Section 3.:*

H318	Causes serious eye damage.
H319	Causes serious eye irritation.
H361d	Suspected of damaging the unborn child.
Eye Dam. 1	Serious eye damage/eye irritation Category 1
Eye Irrit. 2	Serious eye damage/eye irritation Category 2
Repr. 2	Reproductive toxicity Category 2

## Legend:

ADN	European Agreement concerning the International Carriage of Dangerous Goods by Inland Waterways
ADR	European Agreement concerning the International Carriage of Dangerous Goods by Road
ATE	Acute Toxicity Estimate
BCF	Bioconcentration Factor
BOD	Biological Oxygen Demand
Bw	Body Weight
C&L	Classification and Labelling
CAS	Chemical Abstracts Service
CLP	Classification, Labelling and Packaging
CMR	Carcinogenic, Mutagenic or toxic to Reproduction
COD	Chemical Oxygen Demand
CSA	Chemical Safety Assessment
CSR	Chemical Safety Report
DMEL	Derived Minimal Effect Level
DNEL	Derived No Effect Level
ECHA	European Chemicals Agency
Ecx	Effective Concentration x%
Edx	Effective Dose x%
ELINCS	European List of Notified Chemical Substances
ErC50	EC50 in terms of reduction of growth rate;
ES	Exposure Scenario
IARC	International Agency for Research on Cancer
IATA	International Air Transport Association
IMDG	International Maritime Dangerous Goods
LCx	Lethal Concentration x%
LDx	Lethal Dose x%
LOAEC	Lowest Observed Adverse Effect Concentration
LOAEL	Lowest Observed Adverse Effect Level
LOEC	Lowest Observed Effect Concentration
LOEL	Lowest Observed Effect Level
NOEC	No observed effect concentration
NOEL	No observed effect level

# SAFETY DATA SHEET



according to regulation 1907/2006/EC (REACH) and 1272/2008/EC

**MOL-LUB Ltd.**

Trade name: **MOL DOT 5.1 brake fluid**

Version: 6    Latest revision: 07. 11. 2022    Date of issue: 03. 02. 2015    Page: 12/(12)

NLP	No-Longer Polymer
NOAEL	No Observed Adverse Effect Level
OECD	Organisation for Economic Cooperation and Development
PBT	Persistent Bioaccumulative and Toxic
PNEC	Predicted No-Effect Concentration
REACH	Registration, Evaluation, Authorisation and Restriction of Chemicals
RID	Regulations concerning the International Carriage of Dangerous Goods by Rail
SVHC	Substance of Very High Concern
UVCB	substance of unknown or variable composition, complex reaction products or biological materials
VOC	Volatile organic compounds
vPvB	Very Persistent and very Bio-accumulative

## Revision Indicators:

Section	Subject of change	Date	Version
1 2 5 14	Responsible for SDS Other hazards Fire hazards Transport information	10. 04. 2015	2
1-16 2.2 3	Full revision. According to 2015/830 /EU. Label elements Composition/information on ingredients	14. 05. 2018	3
1-16	Full revision due to changes in composition	01. 11. 2018	4
1 2 3 4 6 7 8 9 10 11 12 1-16	Identification of the mixture and of the company/undertaking Hazards identification Composition/information on ingredients First aid measures Accidental release measures Handling and storage Exposure controls / personal protection Physical and chemical properties Stability and reactivity Toxicological information Ecological information Other corrections	18. 12. 2020	5
1-16	Revision modification according to 2020/878/EU	07. 11. 2022	6