

according to regulation (EC) No 1907/2006 (REACH) and 1272/2008/EC MOL-LUB Ltd.

Trade name: MOL Dynamic Global Diesel VL 15W-40 LA

Version: 1 Latest revision: - Date of issue: 04. 03. 2021 Page: 1/(13)

SECTION 1 Identification of the substance/mixture and of the company/undertaking

1.1 Product identifier:

MOL Dynamic Global Diesel VL 15W-40 LA

1.2 Relevant identified uses of the substance or mixture and uses advised against

Relevant identified uses: multigrade diesel engine oil.

Uses advised against: no data

1.3 Details of the supplier of the safety data sheet:

MOL-LUB Lubricant Production Distribution and Service Ltd.

H-2931 Almásfüzitő, Fő út 21., Hungary

Phone / Fax: +36 34 526 330 / +36 34 526 391

E-mail: kenoanyag@mol.hu

Request SDS of:

MOL-LUB Lubricant Production Distribution and Service Ltd.

Customer Service Center

H-2931 Almásfüzitő, Fő út 21., Hungary

Phone / Fax: +36 80 201 296 / +36 34 348 010

Responsible for SDS:

MOL-LUB Ltd.

Phone: +36 80 201 296

e-mail: EBKHelpdesk@MOL.hu

1.4 Emergency telephone number

Emergency telephone (on workdays: 07-15²⁰ h (CET)): +36 34 526 210

Health Toxicological Information Service (ETTSZ 1097 Budapest, Albert Flórián st. 2-6.)

Tel.: +36 80 201 199 (0-24 h, free number, can only be called from Hungary). +36 1 476 6464 (0-24 h, can be called for a normal fee - also from abroad)

National Health Toxicological Information Service:

SECTION 2 Hazards identification

2.1 Classification of the substance or mixture

Hazard Class and Category: Hazard statement:

Eve Irrit. 2 H319 Causes serious eye irritation.

Aquatic Chronic 3 H412 Harmful to aquatic life with long lasting

effects.



according to regulation (EC) No 1907/2006 (REACH) and 1272/2008/EC MOL-LUB Ltd.

Trade name: MOL Dynamic Global Diesel VL 15W-40 LA

Version: 1 Latest revision: - Date of issue: 04. 03. 2021 Page: 2/(13)

2.2 Label elements

Product identification: Trade name: MOL Dynamic Global Diesel VL 15W-40 LA

Hazardous components:

GHS Pictogram:

Signal word: Warning

Hazard statement:

H319 Causes serious eye irritation.

H412 Harmful to aquatic life with long lasting effects.

Supplemental hazard information: -

Precautionary statements – General:

P101 If medical advice is needed, have product container or label at hand.

P102 Keep out of reach of children.

Precautionary statements – Prevention:

P273 Avoid release to the environment.
P280 Wear eye protection/ face protection.

Precautionary statements – Response:

P305 + P351 + IF IN EYES: Rinse cautiously with water for several minutes. Remove

P338 contact lenses, if present and easy to do. Continue rinsing.
P337 + P313 If eye irritation persists: Get medical advice/attention.

Precautionary statements - Storage: -

Precautionary statements – Disposal:

P501 Dispose of contents/container in accordance with national regulation.

Other liabilities for labelling:

Tactile warning of danger: Not required.

Transport classification: see section 14.

2.3 Other hazards

The product does not contain any PBT or vPvB substance according to annex XIII of regulation (EC) 1907/2006.



according to regulation (EC) No 1907/2006 (REACH) and 1272/2008/EC MOL-LUB Ltd.

Trade name: MOL Dynamic Global Diesel VL 15W-40 LA

Version: 1 Latest revision: - Date of issue: 04. 03. 2021 Page: 3/(13)

SECTION 3 Composition/information on ingredients

3.2 Mixtures

Chemical description: Mixture of refined mineral base oils containing additives.

Component(s) / Hazardous component(s):

Name	EC	CAS	Hazard classes and	Hazard	Conc.
Ivaine	number	number	cat.	statements	% (m/m)
Distillates (petroleum),	265-169-7	64742-65-0	-	-	max. 75
solvent-dewaxed heavy			(Note L)		
paraffinic*					
REACH Registr. Nr.:					
01-2119471299-27					
Distillates (petroleum),	265-157-1	64742-54-7	-	-	max. 25
hydrotreated heavy paraffinic*			(Note L)		
REACH Registr. Nr.:					
01-2119484627-25					
Distillates (petroleum),	265-157-1	64742-54-7	Asp. Tox. 1	H304	max. 25
hydrotreated heavy paraffinic			(Note L)		
REACH Registr. Nr.:					
01-2119484627-25					
Distillates (petroleum),	265-169-7	64742-65-0	Asp. Tox. 1	H304	max. 5.0
solvent-dewaxed heavy			(Note L)		
paraffinic					
REACH Registr. Nr.:					
01-2119471299-27					
Phosphorodithioic acid, mixed	288-917-4	85940-28-9	Skin Irrit. 2	H315	max. 2.0
O,O-bis(1,3-dimethylbutyl and			Eye Dam. 1	H318	
iso-Pr)esters, zinc salts			Aquatic Chronic 2	H411	
REACH Registr. Nr.:					
01-2119521201-61					
Phenol, (tetrapropenyl)	616-100-8	74499-35-7	Skin Corr. 1C	H314	< 0.06
derivatives			Eye Dam. 1	H318	
REACH Registr. Nr.:			Repr. 1B	H360F	
no data			Aquatic Acute 1	H400 (M=10)	
			Aquatic Chronic 1	H410 (M=10)	

^{*:} with exposure limit

Note L: The classification as a carcinogen need not apply according to 1272/2008/EC, because it can be shown that the substance contains less than 3 % DMSO extract as measured by IP 346.

The full text of each relevant H- phrase and Hazard classes and cat. see in Section 16.



according to regulation (EC) No 1907/2006 (REACH) and 1272/2008/EC MOL-LUB Ltd.

Trade name: MOL Dynamic Global Diesel VL 15W-40 LA

Version: 1 Latest revision: - Date of issue: 04. 03. 2021 Page: 4/(13)

SECTION 4 First aid measures

4.1 Description of first aid measures

General information: Never give anything by mouth to an unconscious person, or never

induce vomiting.

Inhalation: Remove the affected person to fresh air. If rapid recovery does not occur, obtain

medical attention.

Skin contact: Remove contaminated clothing. Wash skin with large amounts of water, use soap.

In case of persistent irritation, get medical attention.

Eye contact: In case of contact, immediately flush eyes with plenty of water for at least 15

minutes. Remove contact lenses, if present and easy to do. Continue rinsing. Get

medical attention.

Ingestion: If swallowed, give water. Do not induce vomiting. Get medical attention.

Protection of first-aid person: No individual specifications.

4.2 Most important symptoms and effects, both acute and delayed

Serious eye irritation.

Prolonged and/or repeated contact may cause irritation on skin depending on individual

sensitivity.

4.3 Indication of any immediate medical attention and special treatment needed

No data.

SECTION 5 Fire-fighting measures

Fire hazards:

Combustible

5.1 Extinguishing media

Suitable extinguishing media:

Foam, carbon dioxide, dry chemical powder.

Unsuitable extinguishing media:

Water jet.

5.2 Special hazards arising from the substance or mixture

Hazardous combustion products:

On burning, carbon monoxide, carbon dioxide, sulphur oxides, phosphor oxides, various hydrocarbons and soot can be formed.



according to regulation (EC) No 1907/2006 (REACH) and 1272/2008/EC MOL-LUB Ltd.

Trade name: MOL Dynamic Global Diesel VL 15W-40 LA

Version: 1 Latest revision: - Date of issue: 04. 03. 2021 Page: 5/(13)

5.3 Advice for fire-fighters

Special protective equipment:

According to the existing fire-fighting regulations. Respiratory protection.

Further information:

Collect contaminated fire fighting water separately. It must not enter the sewage system. Contaminated extinguishing water must be disposed of in accordance with official regulations.

SECTION 6 Accidental release measures

6.1 Personal precautions, protective equipment and emergency procedures

Personal precautions: see Section 8.

Danger of slipping on leaked out/spilled product.

6.2 Environmental precautions:

Confine spills to prevent material from entering sewers, watercourses, drains and into soil Notify relevant authority.

6.3 Methods and material for containment and cleaning up

On soil: All kind of ignition sources should be removing. Contain spilled liquid with

sand, earth or other suitable absorbents. Recover free liquid by pumping.

Dispose of according to local regulations.

On water: Confine the spillage. Remove from surface by skimming or suitable

absorbents. Notify local authorities according to regulations.

6.4 Reference to other sections

Personal precautions: see section 8.

Waste treatment methods: see section 13.

SECTION 7 Handling and storage

7.1 Precautions for safe handling

Keep general measures applied for normal operations with lubricants.

Keep away from radiant heat and open flame.

Avoid contact with skin and eyes. Avoid prolonged breathing of oil vapours or mists.

Ensure washing facilities after working hours and before breaks.

Take off contaminated clothing and wash it before reuse.

When using do not eat, drink or smoke. Avoid splashing the product.

Handling temperature: no data





according to regulation (EC) No 1907/2006 (REACH) and 1272/2008/EC MOL-LUB Ltd.

Trade name: MOL Dynamic Global Diesel VL 15W-40 LA

Version: 1 Latest revision: - Date of issue: 04. 03. 2021 Page: 6/(13)

7.2 Conditions for safe storage, including any incompatibilities

Storage facilities must comply with regulations for storing of flammable liquids.

Store in dry, well ventilated place in original, closed containers.

Keep away from radiant heat, open flame and strong oxidizing agents.

Storage temperature: max. 40°C

7.3 Specific end use(s)

Multigrade diesel engine oil.

SECTION 8 Exposure controls / personal protection

8.1 Control parameters:

Mineral oil mist: TWA: 5 mg/m³; STEL: 10 mg/m³, for oil mist, vapour excluded

(ACGIH).

Method of testing, recommended: NIOSH 5026

8.2 Exposure controls

Engineering control measures:

Not required.

Personal protection:

(a) Eye/face protection Where splashing is possible, wear safety glasses (EN 166).

(b) Skin protection

(i) Hand protection Oil resistant gloves (EN 374, Breakthrough time 480 min) (e.g.

nitrile rubber – minimal thickness 0.33 mm).

Note: Manufacturer's directions for use and the conditions of

application should be observed.

(ii) Other Protective clothing (oil resistant).

(c) Respiratory protection Under normal conditions it is not necessary. In case of exceeded

exposure-limits respiratory protection with suitable-filter is

recommended.

(d) Thermal hazards No data.

Environmental exposure controls:

Do not discharge into drains/surface waters/groundwater.



according to regulation (EC) No 1907/2006 (REACH) and 1272/2008/EC MOL-LUB Ltd.

MOL Dynamic Global Diesel VL 15W-40 LA Trade name:

Version: 1 Latest revision: -Date of issue: 04. 03. 2021 Page: 7/(13)

SECTION 9 Physical and chemical properties

9.1 Information on basic physical and chemical properties

Physical state: liquid Colour: bright, clear b) Odour: characteristic c)

d) Melting point/freezing point (Pour point) (ISO 3016): typ. -45°C

Boiling point or initial boiling point and boiling e)

range (DIN 51356): not available Flammability: f) combustible Lower and upper explosion limit: not available

g) Flash point (COC) (EN ISO 2592): h) typ. 220°C i) Auto-ignition temperature: not available Decomposition temperature: not available j) not applicable k) pH:

1) Kinematic viscosity at (DIN EN ISO 3104):

40°C: typ. $99.0 \text{ mm}^2/\text{s}$ 100°C typ. $14.2 \text{ mm}^2/\text{s}$

m) Solubility

Solubility in water: practically insoluble in water Solubility in other solvents: gasoline, kerosene, toluene, etc.

n) Partition coefficient n-octanol/water (log value): not available Vapour pressure at 20°C: negligible

p) Density and/or relative density at 15°C

(DIN EN ISO 12185): $0.860 - 0.880 \text{ g/cm}^3$ q) Relative vapour density: not available Particle characteristics: not available

9.2 Other information

r)

No data available

SECTION 10 Stability and reactivity

10.1 Reactivity: Dangerous reactivity not known.

10.2 Chemical stability: No decomposition if stored and handled properly.

10.3 Possibility of hazardous

reactions: Not known

10.4 Conditions to avoid: Direct heat or ignition sources.

10.5 Incompatible materials: Strong oxidizing agents.

10.6 Hazardous decomposition No dangerous decomposition products are formed under normal

conditions. Hazardous combustion products: See Section 5. products:



according to regulation (EC) No 1907/2006 (REACH) and 1272/2008/EC MOL-LUB Ltd.

MOL Dynamic Global Diesel VL 15W-40 LA Trade name:

Version: 1 Latest revision: -Date of issue: 04. 03. 2021 Page: 8/(13)

SECTION 11 Toxicological information

11.1 Information on hazard classes as defined in Regulation (EC) No 1272/2008

Acute toxicity: Based on available data, the classification criteria are not met.

Acute toxicity:

Oral: LD_{50} (rat) > 2000 mg/kg(based on components) > 2000 mg/kg(based on components) Dermal: LD₅₀ (rabbit)

Components:

Distillates (petroleum), solvent-dewaxed heavy paraffinic (CAS: 64742-65-0)

Oral: LD₅₀ (rat) > 5000 mg/kg(literature data) Dermal: LD₅₀ (rabbit) > 2000 mg/kg(literature data) > 5.53 mg/L (4 h) Inhalation: LC₅₀ (rat) (literature data)

Distillates (petroleum), hydrotreated heavy paraffinic (CAS: 64742-54-7)

LD₅₀ (rat) > 2000 mg/kg**OECD 401** Oral: Dermal: LD₅₀ (rabbit) > 2000 mg/kg**OECD 402** $> 5000 \text{ mg/m}^3$ **OECD 403** Inhalation: LC_{50} (rat)

Phosphorodithioic acid, mixed O,O-bis(1,3-dimethylbutyl and iso-Pr)esters, zinc salts

(CAS: 85940-28-9)

Oral: 3080 mg/kg **OECD 401** LD_{50} (rat) Dermal: LD₅₀ (rabbit) > 20000 mg/kg **OECD 402**

Inhalation: LC₅₀ (rat) $> 2.3 \text{ mg/m}^3$ OECD 403 (vapor)

Phenol, (tetrapropenyl) derivatives (CAS: 74499-35-7)

2200 mg/kg Oral: LD₅₀ (rat) **OECD 401** Dermal: LD₅₀ (rabbit) 15 000 mg/kg **OECD 402**

Skin corrosion/irritation: Based on available data, the classification criteria are not met.

Serious eye damage/irritation Causes serious eye irritation.

Respiratory or skin sensitisation: Based on available data, the classification criteria are not met.

Germ cell mutagenicity: Based on available data, the classification criteria are not met. Carcinogenicity: Based on available data, the classification criteria are not met. Reproductive toxicity: Based on available data, the classification criteria are not met. STOT-single exposure: Based on available data, the classification criteria are not met. STOT-repeated exposure: Based on available data, the classification criteria are not met.

Aspiration hazard: Based on available data, the classification criteria are not met.

11.2 Information on other hazards

No data.



Harmful to aquatic life with long lasting effects.

SAFETY DATA SHEET

according to regulation (EC) No 1907/2006 (REACH) and 1272/2008/EC MOL-LUB Ltd.

Trade name: MOL Dynamic Global Diesel VL 15W-40 LA

Version: 1 Latest revision: - Date of issue: 04. 03. 2021 Page: 9/(13)

SECTION 12 Ecological information

Components:

12.1 Toxicity

Distillates (petroleum), solvent-dewaxed heavy paraffinic (CAS: 64742-65-0)

Fishes: LC_{50} > 100 mg/L(literature data) Daphnia: EC_{50} > 100 mg/L(literature data) Other aquatic organisms: > 100 mg/L EC_{50} (literature data) Algae: ErC₅₀ > 100 mg/L(literature data) Other living beings: TLM >1 mg/L (literature data)

Distillates (petroleum), hydrotreated heavy paraffinic (CAS: 64742-54-7)

Fishes: >1000 mg/L 96 h (OECD 203)
Daphnia: >100 mg/L 48 h (OECD 202)
Algae: >100 mg/L 72 h (OECD 201)

Phosphorodithioic acid, mixed O,O-bis(1,3-dimethylbutyl and iso-Pr)esters, zinc salts (CAS: 85940-28-9)

Fishes (Oncorhynchus mykiss): LC_{50} 4.5 mg/L96 h 5.4 mg/L Daphnia (Daphnia magna): EL50 48 h Algae (Selenastrum capricornutum): 2.1 mg/L EL_{50} 72 h Microorganism: $>10\,000\,\text{mg/L}$ EL_{50} 3 h Daphnia (Daphnia magna): 0.4 mg/LNOEL 21days Algae (Selenastrum capricornutum): 1.0 mg/L 96 h NOEL

Phenol, (tetrapropenyl) derivatives (CAS: 74499-35-7)

Fishes (Pimephales promelas): LC_{50} 40 mg/L 96 h Daphnia (Daphnia magna): EC_{50} 0.037 mg/L48 h Daphnia (Daphnia magna): 0.0037 mg/L NOEL 21 days Algae (Desmodesmus subspicatus): 0.36 mg/L EC_{50} 72 h Algae (Desmodesmus subspicatus): NOEL 0.07 mg/L72 h >1000 mg/LMicroorganisms: EC_{50} 3 h

12.2 Persistence and degradability

Biodegradability: Hydrocarbons are inherently degradable.

Phosphorodithioic acid, mixed O,O-bis(1,3-dimethylbutyl and iso-Pr)esters, zinc salts Phosphorodithioic acid, mixed O,O-bis(1,3-dimethylbutyl and iso-Pr)esters, zinc salts

Phosphorodithioic acid, mixed O,O-bis(1,3-1.5% (28 days, OECD 301B), not readily dimethylbutyl and iso-Pr)esters, zinc salts degradable

6.0-25 % (28 days, OECD 301B), not readily degradable

12.3 Bioaccumulative potential No data available.

Phenol, (tetrapropenyl) derivatives BCF: 289 - 1601 (high potential)





according to regulation (EC) No 1907/2006 (REACH) and 1272/2008/EC MOL-LUB Ltd.

Trade name: MOL Dynamic Global Diesel VL 15W-40 LA

Version: 1 Latest revision: - Date of issue: 04. 03. 2021 Page: 10/(13)

12.4 Mobility in soil Absorbs in soil.

Mobility in water: Floats on water.

12.5 Results of PBT and vPvB assessment Does not contain PBT and vPvB substances.

12.6 Endocrine disrupting properties No data.

12.7 Other adverse effects

Heavy metal content: None.

PCT, PCB and other chlorinated

hydrocarbons: None.

Water hazard class (German): WGK 1 (Classification by AwSV)

SECTION 13 Disposal considerations

13.1 Waste treatment methods

Product disposal:

Wastes of the product or used oil should be treated as hazardous waste.

Waste Identification Code: 13 02 05*

Mineral-based non-chlorinated engine, gear and lubricating oils.

Recommended waste treatment method: incineration

Packaging disposal:

Containers with product residue should also be treated as hazardous waste according to national and local disposal regulations.

Waste Identification Code: 15 01 10*

Packaging containing residues of or contaminated by dangerous substances.

Disposal must be in compliance with national and local regulations.

Wastewater:

Quality of wastewater emitted to natural water must comply with national and local regulations.

Care should be taken in any case to ensure compliance with EC, national and local regulations. It is the responsibility of the user to know all relevant national and local regulations.





according to regulation (EC) No 1907/2006 (REACH) and 1272/2008/EC MOL-LUB Ltd.

Trade name: MOL Dynamic Global Diesel VL 15W-40 LA

Version: 1 Latest revision: - Date of issue: 04. 03. 2021 Page: 11/(13)

SECTION 14 Transport information

Land transport:

Road/ Railway ADR/RID: Not classified.

14.1. UN number or ID number: Not classified. 14.2. UN proper shipping name: Not classified. 14.3. Transport hazard class(es): Not classified. 14.4. Packing group: Not classified. 14.5. Environmental hazards: Not classified. Special precautions for user: 14.6. Not classified.

Waterways:

Inland waterways/ Sea transport ADN/IMDG: Not apply to the product.

Air transport: ICAO / IATA: Not apply to the product.

SECTION 15 Regulatory information

15.1 Safety, health and environmental regulations/legislation specific for the substance or mixture. This safety data sheet has been prepared according to Regulation (EC) No 1907/2006 (mod.: 2020/878/EU) and to Regulation (EC) 1272/2008. Seveso category: not classified.

15.2 Chemical safety assessment.

Not available.

SECTION 16 Other information

The information given in this data sheet is based on our best knowledge at the time of publication. The information is related only to this product and is intended to assist its safe transport, handling and use. The given physical and chemical parameters describe the product only for the purpose of safety requirements and therefore should not be construed as guaranteeing any specific property of the product or as being part of a product specification or any contract.

The manufacturer or supplier shall not take responsibility for any damages from the use other than recommended or other misuse of the product. It is the responsibility of the user to keep regulatory precautions and observe recommendations for safe use of the product.



according to regulation (EC) No 1907/2006 (REACH) and 1272/2008/EC MOL-LUB Ltd.

Trade name: MOL Dynamic Global Diesel VL 15W-40 LA

Version: 1 Latest revision: - Date of issue: 04. 03. 2021 Page: 12/(13)

Classification for mixtures and used evaluation method according to regulation (EC) 1272/2008

(CLP)

Eye Irrit. 2 H319 calculated method Aquatic Chronic 3 H412 calculated method

The full text of each relevant H- phrase and Hazard classes and cat. in Section 3.:

H304 May be fatal if swallowed and enters airways. H314 Causes severe skin burns and eye damage.

H315 Causes skin irritation.

H318 Causes serious eye damage. H360F May damage fertility. H400 Very toxic to aquatic life.

H410 Very toxic to aquatic life with long lasting effects.H411 Toxic to aquatic life with long lasting effects.

Asp. Tox. 1 Aspiration hazard Category 1

Skin Corr. 1C Skin corrosion/irritation Category 1C Skin Irrit. 2 Skin corrosion/irritation Category 2

Eye Dam. 1 Serious eye damage/eye irritation Category 1

Repr. 1B Reproductive toxicity Category 1B

Aquatic Acute 1 Hazardous to the aquatic environment, Acute Category 1
Aquatic Chronic 1 Hazardous to the aquatic environment, Chronic Category 1
Hazardous to the aquatic environment, Chronic Category 2

Legend:

ADN European Agreement concerning the International Carriage of Dangerous Goods by Inland

Waterways

ADR European Agreement concerning the International Carriage of Dangerous Goods by Road

ATE Acute Toxicity Estimate
BCF Bioconcentration Factor
BOD Biological Oxygen Demand

Bw Body Weight

C&L Classification and Labelling CAS Chemical Abstracts Service

CLP Classification, Labelling and Packaging (1272/2008/EC)



according to regulation (EC) No 1907/2006 (REACH) and 1272/2008/EC MOL-LUB Ltd.

Trade name: MOL Dynamic Global Diesel VL 15W-40 LA

Version: 1 Latest revision: - Date of issue: 04. 03. 2021 Page: 13/(13)

CMR Carcinogenic, Mutagenic or toxic to Reproduction

COD Chemical Oxygen Demand
CSA Chemical Safety Assessment
CSR Chemical Safety Report
DMEL Derived Minimal Effect Level
DNEL Derived No Effect Level
ECHA European Chemicals Agency
Ecx Effective Concentration x%

ErC50 EC50 in terms of reduction of growth rate

Edx Effective Dose x%
EC European Community

EC number European Community number

ELINCS European List of Notified Chemical Substances

ES Exposure Scenario

IARC International Agency for Research on Cancer
IATA International Air Transport Association
IMDG International Maritime Dangerous Goods

LCx Lethal Concentration x%

LDx Lethal Dose x%

LOAEC Lowest Observed Adverse Effect Concentration

LOAEL Lowest Observed Adverse Effect Level LOEC Lowest Observed Effect Concentration

LOEL Lowest Observed Effect Level NOEC No observed effect concentration

NOEL No observed effect level NLP No-Longer Polymer

NOAEL No Observed Adverse Effect Level

OECD Organisation for Economic Cooperation and Development

PBT Persistent Bioaccumulative and Toxic
PNEC Predicted No-Effect Concentration

ppm parts/million

REACH Registration, Evaluation, Authorisation and Restriction of Chemicals

RID Regulations concerning the International carriage of Dangerous Goods by Rail

SVHC Substance of Very High Concern

UVCB substance of unknown or variable composition, complex reaction products or biological materials

VOC Volatile organic compounds

vPvB Very Persistent and very Bio-accumulative

Revision Indicators:

Section	Subject of change	Date	Version