


MOL ATF 3G

automatic transmission fluid



MOL ATF 3G is an automatic transmission fluid produced from mineral base oils made using unique oil refining processes, and containing additives that comply with stringent quality requirements. It provides optimum lubrication and protection to transmissions in all operating conditions.

Application



Automatic transmissions of passenger cars and light commercial vehicles

Automatic gearboxes of buses

Marine gears

Hydraulic servo equipment

Features and benefits

Optimal friction characteristics

Improved cold flow properties

Low foaming tendency

Excellent shear stability

Good thermal and oxidation stability

Precise and noiseless switching between gears
Convenient and economical operation

Reliable operation even at low temperatures

Continuous, stable lubricating film, even at high speeds

Sustains lubricity during long oil drain intervals

No deposit or sludge formation
Operational, maintenance and disposal costs are reduced

Specifications and approvals

MAN 339 Typ L1
MAN 339 Typ V1
MAN 339 Typ Z1
ZF TE-ML 04D[ZF001179]
ZF TE-ML 14A[ZF001179]
Voith H55.6335
ZETOR
GM Dexron-III G
Ford Mercon
ZF TE-ML 05L
ZF TE-ML 09
ZF TE-ML 11B
Allison C-4
Volvo CE 97341

MOL ATF 3G

automatic transmission fluid



Properties

Properties	Typical values
Density at 15°C [g/cm ³]	0,855
Kinematic viscosity at 40°C [mm ² /s]	34,8
Kinematic viscosity at 100 °C [mm ² /s]	7,2
Viscosity index	182
Pour point [°C]	-51
Flash point (Cleveland) [°C]	210

The characteristics in table are typical values of the product and do not constitute a specification.

Storage and handling instructions

Store in the original container in dry, properly ventilated area. Keep away from direct flame and other sources of ignition. Protect from direct sunlight.

During transport, storage and use of the product follow the work safety instructions and environmental regulations relating to mineral oil products.

For further details please read the Material Safety Data Sheet of the product.

Gear oils are finished lubricant formulations where additional additives are unnecessary and may result in unforeseeable adverse effects. The manufacturer and distributor shall not be held liable for such possible damages.

In the original container under the recommended storage conditions: 60 months

Recommended storage temperature: max. 40°C

Ordering information

Custom Tariff Number 27101987

SAP code and packaging:

13011138	MOL ATF 3G 1L	1 l plastic bottle
13006043	MOL ATF 3G X1L	1 l plastic bottle
13009340	MOL ATF 3G 47KG	60 l steel drum
13009356	MOL ATF 3G 170KG	216.5 l steel drum

Order booking:

Please contact your local distributor or sales partner for ordering details.