

# MOL ATF

## automatic transmission fluid



MOL ATF is an automatic transmission fluid produced from mineral base oils made using unique oil refining processes, and containing additives that comply with stringent quality requirements.

### Application



Automatic transmissions of passenger cars and light commercial vehicles

Hydraulic servo equipment

Fork-lift trucks, cranes

Marine gears

### Features and benefits

Optimal friction characteristics

Precise and noiseless switching between gears  
Convenient and economical operation

Good thermal and oxidation stability

Reliable operation, so reduced operational costs

Good wear protection

Contributes to increasing equipment lifetime

Excellent shear stability

Sustains lubricity during long oil drain intervals

### Specifications and approvals

MAN 339 Typ L2  
MAN 339 Typ V1  
MAN 339 Typ Z1  
ZF TE-ML 04D[ZF001251]  
ZF TE-ML 14A[ZF001251]  
ZF TE-ML 17C[ZF001251]  
Voith H55.6335  
GM Dexron-IID  
GM Type A Suffix A  
Ford Mercon  
ZF TE-ML 02F  
ZF TE-ML 03D  
ZF TE-ML 05L  
ZF TE-ML 09  
ZF TE-ML 11A  
Allison C-4

# MOL ATF

## automatic transmission fluid



### Properties

| Properties   | Typical values |
|--|----------------|
| Density at 15°C [g/cm <sup>3</sup> ]               | 0,863          |
| Kinematic viscosity at 40°C [mm <sup>2</sup> /s]   | 37,7           |
| Kinematic viscosity at 100 °C [mm <sup>2</sup> /s] | 8,00           |
| Viscosity index                                    | 175            |
| Pourpoint [°C]                                     | -42            |
| Flash point (Cleveland) [°C]                       | 210            |

The characteristics in table are typical values of the product and do not constitute a specification.

### Storage and handling instructions

Store in the original container in dry, properly ventilated area.

Keep away from direct flame and other sources of ignition.

Protect from direct sunlight.

During transport, storage and use of the product follow the work safety instructions and environmental regulations relating to mineral oil products.

For further details please read the Material Safety Data Sheet of the product.

Gear oils are finished lubricant formulations where additional additives are unnecessary and may result in unforeseeable adverse effects.

The manufacturer and distributor shall not be held liable for such possible damages.

In the original container under the recommended storage conditions: 60 months

Recommended storage temperature: max. 40°C

### Ordering information

Custom Tariff Number 27101987

#### SAP code and packaging:

|          |                   |                                   |
|----------|-------------------|-----------------------------------|
| 13301059 | MOL ATF 1L        | 1 l plastic bottle                |
| 13300366 | MOL ATF 10LA      | 10 l plastic can (for order only) |
| 13100973 | MOL ATF 47KG      | 60 l steel drum                   |
| 13100974 | MOL ATF 170KG     | 216.5 l steel drum                |
| 13301064 | MOL ATF 860KG R1W | IBC (for order only)              |
| 13301058 | MOL ATF           | Road tank car (for order only)    |

#### Order booking:

Please contact your local distributor or sales partner for ordering details.