

MOL DSG / DCT Fluid

dual-clutch gearbox oil



MOL DSG / DCT Fluid is an unique gearbox oil produced from severely hydrocracked, high quality base oils, using a special additive system that meets the highest quality requirements. Provides excellent wear protection as well as outstanding wet clutch performance.

Application



Dual-clutch transmissions of passenger cars and light commercial vehicles

Features and benefits

Optimal friction characteristics
Excellent cold flow properties
Low foaming tendency
Excellent wear protection
Exceptional thermal and oxidation stability

Wet clutches operate silently and judder-free
Fuel-saving operation at low temperature
Continuous, stable lubricating film, even at high speeds
Long gear lifetime, giving reliable operation
Perfect protection against sludge formation and sedimentation

Specifications and approvals

VW G 052 182 (TL 52 182)
VW G 052 529 (TL 52 529)
BMW 83 22 0 440 214
BMW 83 22 2 147 477
BMW 83 22 2 148 578
BMW 83 22 2 148 579
Ford M2C936A
MZ320065 Dia-Queen SSTF-I
PSA 9734.S2
Porsche Oil No. 999.917.080.00
Volvo 1161838/1161839

Properties

Properties	Typical values
Appearance	yellow, clear, bright
Density at 15°C [g/cm ³]	0,854
Kinematic viscosity at 40°C [mm ² /s]	34,3
Kinematic viscosity at 100 °C [mm ² /s]	7,20
Pour point [°C]	-42
Flash point (Cleveland) [°C]	200

The characteristics in table are typical values of the product and do not constitute a specification.

MOL DSG / DCT Fluid

dual-clutch gearbox oil



Storage and handling instructions

Store in the original container in dry, properly ventilated area.

Keep away from direct flame and other sources of ignition.

Protect from direct sunlight.

During transport, storage and use of the product follow the work safety instructions and environmental regulations relating to mineral oil products.

For further details please read the Material Safety Data Sheet of the product.

Gear oils are finished lubricant formulations where additional additives are unnecessary and may result in unforeseeable adverse effects.

The manufacturer and distributor shall not be held liable for such possible damages.

In the original container under the recommended storage conditions: 60 months

Recommended storage temperature: +5°C - +40°C

Ordering information

Custom Tariff Number 27101987

SAP code and packaging:

13300189 MOL DSG / DCT Fluid X1L

1 l plastic bottle (for order only)

Order booking:

Please contact your local distributor or sales partner for ordering details.