

# MOL Dynamic Garden 4T 30/40

## garden equipment motor oil



MOL Dynamic Garden 4T 30/40 is a mineral oil based engine oil produced with a complex additive system, that ensures the highest performance level and good flow characteristics, for use in small gardening machines. It meets and even outperforms the engine oil specifications issued by the leading manufacturers of small gardening machines, including MTD, Briggs & Stratton, Honda, and Tecumseh.

### Application



Four-stroke engines of small garden equipment and power generators

### Features and benefits

Exceptional thermal and oxidation stability

Resists ageing processes in the long term and harmful deposits are not formed

High performance level

Stable load-carrying lubricating film and high-level wear protection even under heavy loads

Outstanding shear stability

Sustains lubricity during long oil drain intervals

### Specifications and approvals

API SJ/CF

### Properties

Properties	Typical values
Density at 15°C [g/cm <sup>3</sup> ]	0,892
Kinematic viscosity at 40°C [mm <sup>2</sup> /s]	117,0
Kinematic viscosity at 100 °C [mm <sup>2</sup> /s]	13,2
Viscosity index	102
Pour point [°C]	-24
Flash point (Cleveland) [°C]	240
Base number (BN) [mg KOH/g]	7,6

The characteristics in table are typical values of the product and do not constitute a specification.

### Storage and handling instructions

Store in the original container in dry, properly ventilated area.

Keep away from direct flame and other sources of ignition.

Protect from direct sunlight.

During transport, storage and use of the product follow the work safety instructions and environmental regulations relating to mineral oil products.

For further details please read the Material Safety Data Sheet of the product.

Engine oils are finished lubricant formulations where additional additives are unnecessary and may result in unforeseeable adverse effects.

The manufacturer and distributor shall not be held liable for such possible damages.

In the original container under the recommended storage conditions: 60 months

Recommended storage temperature: max. 40°C

# MOL Dynamic Garden 4T 30/40

## garden equipment motor oil



### Ordering information

Custom Tariff Number 27101981

#### SAP code and packaging:

13301098	MOL Dynamic Garden 4T 30/40 0,6L	0,6 l plastic bottle
13300614	MOL Dynamic Garden 4T 30/40 50KG	60 l steel drum (for order only)
13301097	MOL Dynamic Garden 4T 30/40	Road tank car (for order only)

#### Order booking:

Please contact your local distributor or sales partner for ordering details.