

MOL Dynamic Moto 4T HP 10W-40

synthetic four-stroke motorcycle motor oil



MOL Dynamic Moto 4T HP 10W-40 is a high performance, synthetic engine oil, having outstanding engine protecting abilities, and withstanding intensive thermal and mechanical shear stresses, for four-stroke motorcycles.

Application



Four-stroke naked bikes, choppers, cruiser and sports cruiser motorbikes

Four-stroke scooters and street motorbikes

Dry and wet clutch motorbikes

Motorcycles with or without a catalyst

Air- or water-cooled motorcycles

Motorcycles with separate or integrated gearboxes

Features and benefits

Excellent shear stability

Maintains its favourable properties for a long period even under heavy loads and shear stresses

Optimal friction characteristics

Correct torque transmission between clutch plates

Outstanding detergent-dispersant properties

Preserves engine cleanliness for a long period and prevents deposition of solid contaminants

Specifications and approvals

API SN
JASO MA2

Properties

Properties	Typical values
Density at 15°C [g/cm ³]	0,869
Kinematic viscosity at 100 °C [mm ² /s]	14,3
Viscosity index	160
Pour point [°C]	-33
Flash point (Cleveland) [°C]	220

The characteristics in table are typical values of the product and do not constitute a specification.

MOL Dynamic Moto 4T HP 10W-40

synthetic four-stroke motorcycle motor oil



Storage and handling instructions

Store in the original container in dry, properly ventilated area.

Keep away from direct flame and other sources of ignition.

Protect from direct sunlight.

During transport, storage and use of the product follow the work safety instructions and environmental regulations relating to mineral oil products.

For further details please read the Material Safety Data Sheet of the product.

Engine oils are finished lubricant formulations where additional additives are unnecessary and may result in unforeseeable adverse effects.

The manufacturer and distributor shall not be held liable for such possible damages.

In the original container under the recommended storage conditions: 60 months

Recommended storage temperature: max. 40°C

Ordering information

Custom Tariff Number 27101981

SAP code and packaging:

13302773 MOL Dynamic Moto 4T HP 10W-40 1L

1 l plastic bottle

Order booking:

Please contact your local distributor or sales partner for ordering details.