

MOL Dynamic Moto 4T Scooter 10W-40

semi-synthetic four-stroke motorcycle motor oil



MOL Dynamic Moto 4T Scooter 10W-40 is a high performance partially synthetic engine oil having excellent engine protection capabilities, which withstands even the intensive thermal and mechanical shear stresses of state-of-art four-stroke motorcycles.

Application



Four-stroke scooters and street motorbikes
Dry and wet clutch motorbikes
Motorcycles with or without a catalyst
Air- or water-cooled motorcycles
Motorcycles with separate or integrated gearboxes

Features and benefits

Excellent shear stability	Maintains its favourable properties for a long period even under heavy loads and shear stresses
Optimal friction characteristics	Correct torque transmission between clutch plates
Outstanding detergent-dispersant properties	Preserves engine cleanliness for a long period and prevents deposition of solid contaminants

Specifications and approvals

Viscosity grade: SAE 10W-40
API SN
JASO MA2

Properties

Properties	Typical values
Density at 15°C [g/cm ³]	0,869
Kinematic viscosity at 40°C [mm ² /s]	98,3
Kinematic viscosity at 100 °C [mm ² /s]	14,7
Viscosity index	156
Pour point [°C]	-33
Flash point (Cleveland) [°C]	225
Base number (BN) [mg KOH/g]	6,4

The characteristics in table are typical values of the product and do not constitute a specification.

MOL Dynamic Moto 4T Scooter 10W-40

semi-synthetic four-stroke motorcycle motor oil



Storage and handling instructions

Store in the original container in dry, properly ventilated area.

Keep away from direct flame and other sources of ignition.

Protect from direct sunlight.

During transport, storage and use of the product follow the work safety instructions and environmental regulations relating to mineral oil products.

For further details please read the Material Safety Data Sheet of the product.

Engine oils are finished lubricant formulations where additional additives are unnecessary and may result in unforeseeable adverse effects.

The manufacturer and distributor shall not be held liable for such possible damages.

In the original container under the recommended storage conditions: 60 months

Recommended storage temperature: max. 40°C

Ordering information

Custom Tariff Number 27101981

SAP code and packaging:

13301131 MOL Dynamic Moto 4T Scooter 10W-40 1L 1 l plastic bottle

Order booking:

Please contact your local distributor or sales partner for ordering details.