


MOL Hydro HV 32

multigrade hydraulic oil



MOL Hydro HV 32 is a premium quality hydraulic fluid, produced from carefully selected mineral base oils, containing additives that have detergent effect, including a zinc additive for reducing wear, which can be used over a wide temperature range. It provides consistently high performance even in an environment with widely fluctuating temperatures in industrial and mobile hydraulic systems working under heavy load conditions. It ensures outstanding wear resistance. In the standard vane pump test (Vickers V104C), the wear is 85 % lower than the specified limit.

Application



- Equipment operating in a wide range of temperatures
- Hydraulic systems operating at high pressures and under heavy operating conditions
- Industrial equipment operating at low temperatures (pumps, servo systems)
- Hydraulic presses operated indoors or outdoors
- Hydraulic systems of machine-tools
- Hydraulic systems of earthmoving and forestry machines
- Circulation systems

Features and benefits

- | | |
|--|--|
| High viscosity index | Optimum lubrication and reliable operation in a wide range of environmental and operational temperatures |
| Excellent shear stability | Low hydraulic loss |
| Outstanding wear protection | Safe application throughout the year |
| Outstanding thermal and hydrolytic stability | Forms a tenacious lubricating film even under exposure to heavy stress |
| Outstanding filterability | Anti-wear performance close to that of gear oils |
| Rapid air release together with low foaming | Reliable operation, even in equipment exposed to heavy loads at high pressures |
| | Long equipment lifetime |
| | Provides stick-free operation of servo and control valves |
| | Long oil drain intervals |
| | No deterioration of filterability, even in the presence of moisture |
| | Calculably low filter usage even with 2-3 micron pore size filter cartridges |
| | Stable balanced lubricating film between friction surfaces, giving long equipment lifetimes |
| | Reduced risk of cavitation |

MOL Hydro HV 32

multigrade hydraulic oil



Features and benefits (continue)

Good water separation	Abnormal corrosion and wear of equipment can be prevented Longer oil change interval and equipment lifetime
Improved cold flow properties	Reliable operation even at low temperatures

Specifications and approvals

Viscosity grade: ISO VG 32
ZETOR
ISO 11158 HV
ISO 6743-4
DIN 51524-3 (HVLP)
Parker Hannifin (Denison) HF-0/HF-1/HF-2
SAE MS1004 Type HV
AFNOR NF-E-48603 (HV)

Properties

Properties	Typical values
Density at 15°C [g/cm ³]	0,860
Kinematic viscosity at 40°C [mm ² /s]	32,7
Kinematic viscosity at 100 °C [mm ² /s]	6,45
Viscosity index	155
Pour point [°C]	-42
Flash point (Cleveland) [°C]	205

The characteristics in table are typical values of the product and do not constitute a specification.

Storage and handling instructions

Store in the original container in dry, properly ventilated area. Keep away from direct flame and other sources of ignition. Protect from direct sunlight.

During transport, storage and use of the product follow the work safety instructions and environmental regulations relating to mineral oil products.

For further details please read the Material Safety Data Sheet of the product.

In the original container under the recommended storage conditions: 48 months

Recommended storage temperature: max. 40°C

Ordering information

Custom Tariff Number 27101983

SAP code and packaging:

13006339	MOL Hydro HV 32 X10L	10 l plastic can
13009342	MOL Hydro HV 32 47KG	60 l steel drum
13009360	MOL Hydro HV 32 170KG	216.5 l steel drum
13008255	MOL Hydro HV 32	Road tank car (for order only)

Order booking:

Please contact your local distributor or sales partner for ordering details.