


MOL Hydro HV 68

multigrade hydraulic oil



MOL Hydro HV 68 is a premium quality hydraulic fluid, produced from carefully selected mineral base oils, containing additives that have detergent effect, including a zinc additive for reducing wear, which can be used over a wide temperature range. It provides consistently high performance even in an environment with widely fluctuating temperatures in industrial and mobile hydraulic systems working under heavy load conditions. It ensures outstanding wear resistance. In the standard vane pump test (Vickers V104C), the wear is 85 % lower than the specified limit.

Application



Equipment operating in a wide range of temperatures

Hydraulic systems operating at high pressures and under heavy operating conditions

Industrial equipment operating at low temperatures (pumps, servo systems)

Hydraulic presses operated indoors or outdoors

Hydraulic systems of machine-tools

Hydraulic systems of earthmoving and forestry machines

Circulation systems

Features and benefits

High viscosity index

Optimum lubrication and reliable operation in a wide range of environmental and operational temperatures
Low hydraulic loss
Safe application throughout the year

Excellent shear stability

Forms a tenacious lubricating film even under exposure to heavy stress

Outstanding wear protection

Anti-wear performance close to that of gear oils
Reliable operation, even in equipment exposed to heavy loads at high pressures
Long equipment lifetime

Outstanding thermal and hydrolytic stability

Provides stick-free operation of servo and control valves
Long oil drain intervals

Outstanding filterability

No deterioration of filterability, even in the presence of moisture
Calculably low filter usage even with 2-3 micron pore size filter cartridges

Rapid air release together with low foaming

Stable balanced lubricating film between friction surfaces, giving long equipment lifetimes
Reduced risk of cavitation

MOL Hydro HV 68

multigrade hydraulic oil



Features and benefits (continue)

| | |
|-------------------------------|--|
| Good water separation | Abnormal corrosion and wear of equipment can be prevented Longer oil change interval and equipment lifetime |
| Improved cold flow properties | Reliable operation even at low temperatures |

Specifications and approvals

Viscosity grade: ISO VG 68
ISO 11158 HV
ISO-L-HV
DIN 51524-3 (HVLP)
Parker Hannifin (Denison) HF-0/HF-1/HF-2
SAE MS1004 Type HV
AFNOR NF-E-48603 (HV)

Properties

| Properties | Typical values |
|--|----------------|
| Density at 15°C [g/cm ³] | 0,880 |
| Kinematic viscosity at 40°C [mm ² /s] | 68,4 |
| Kinematic viscosity at 100 °C [mm ² /s] | 11,2 |
| Viscosity index | 156 |
| Pour point [°C] | -33 |
| Flash point (Cleveland) [°C] | 230 |

The characteristics in table are typical values of the product and do not constitute a specification.

Storage and handling instructions

Store in the original container in dry, properly ventilated area. Keep away from direct flame and other sources of ignition. Protect from direct sunlight.

During transport, storage and use of the product follow the work safety instructions and environmental regulations relating to mineral oil products.

For further details please read the Material Safety Data Sheet of the product.

In the original container under the recommended storage conditions: 48 months

Recommended storage temperature: max. 40°C

Ordering information

Custom Tariff Number 27101983

SAP code and packaging:

| | | |
|----------|---------------------------|-----------------------------------|
| 13300126 | MOL Hydro HV 68 10LA | 10 l plastic can (for order only) |
| 13100491 | MOL Hydro HV 68 50KG | 60 l steel drum |
| 13100492 | MOL Hydro HV 68 180KG | 216.5 l steel drum |
| 13301320 | MOL Hydro HV 68 860KG R1W | IBC (for order only) |
| 13100490 | MOL Hydro HV 68 | Road tank car (for order only) |

Order booking:

Please contact your local distributor or sales partner for ordering details.