


# MOL Hykomol Synt 75W-90

## semi-synthetic automotive gear oil



MOL Hykomol Synt 75W-90 is a multigrade automotive gear oil, produced from synthetic and highly refined mineral oil, using a complex additive system.

### Application



Differential drives of commercial vehicles  
Manual and automatic mechanical gearboxes of commercial vehicles  
Differential drives of passenger cars and light commercial vehicles  
Manual gearboxes of passenger cars and light commercial vehicles  
Fork-lift trucks, cranes  
Hypoid gears

### Features and benefits

Excellent load-carrying properties	Forms a stable lubricating film, protects against seizure
Up-to-date additive system	Efficient EP performance, giving a long life for synchronizing rings
Semi-synthetic formula	Optimum lubrication over a wide temperature range
Excellent wear protection	Long gear lifetime, giving reliable operation
Low foaming tendency	Continuous, stable lubricating film, even at high speeds
Good thermal and oxidation stability	Extended service interval is achievable

### Specifications and approvals

Viscosity grade: SAE 75W-90  
API GL-5  
API GL-4  
MIL-L-2105D  
Tatra TDS 80/32  
ZF TE-ML 07A  
ZF TE-ML 08  
ZF TE-ML 17B

# MOL Hykomol Synt 75W-90

## semi-synthetic automotive gear oil



### Properties

Properties	Typical values
Density at 15°C [g/cm <sup>3</sup> ]	0,859
Kinematic viscosity at 40°C [mm <sup>2</sup> /s]	109,3
Kinematic viscosity at 100 °C [mm <sup>2</sup> /s]	15,4
Viscosity index	147
Pour point [°C]	-45
Flash point (Cleveland) [°C]	215

The characteristics in table are typical values of the product and do not constitute a specification.

### Storage and handling instructions

Store in the original container in dry, properly ventilated area.

Keep away from direct flame and other sources of ignition.

Protect from direct sunlight.

During transport, storage and use of the product follow the work safety instructions and environmental regulations relating to mineral oil products.

For further details please read the Material Safety Data Sheet of the product.

Gear oils are finished lubricant formulations where additional additives are unnecessary and may result in unforeseeable adverse effects.

The manufacturer and distributor shall not be held liable for such possible damages.

In the original container under the recommended storage conditions: 60 months

Recommended storage temperature: max. 40°C

### Ordering information

Custom Tariff Number 27101987

#### SAP code and packaging:

13302047	MOL Hykomol Synt 75W-90 X1L	1 l plastic bottle
13300376	MOL Hykomol Synt 75W-90 10LA	10 l plastic can
13300374	MOL Hykomol Synt 75W-90 20LA	20 l plastic can (for order only)
13300618	MOL Hykomol Synt 75W-90 50KG	60 l steel drum
13300380	MOL Hykomol Synt 75W-90 170KG	216.5 l steel drum
	MOL Hykomol Synt 75W-90	Road tank car (for order only)

#### Order booking:

Please contact your local distributor or sales partner for ordering details.