


MOL Hykomol Syntrans LL 75W-80

synthetic automotive gear oil



MOL Hykomol Syntrans LL 75W-80 is a multigrade gear oil produced from a premium quality synthetic base oil using a modern additive system that allows a long oil change interval. Due to its special viscosity properties, it contributes to a reduction in fuel consumption.

Application



Manual and automatic mechanical gearboxes in modern commercial vehicles

Manual gearboxes in modern passenger cars, SUVs and light commercial vehicles

Features and benefits

Outstanding oxidation stability
Low coefficient of friction
Excellent thermal stability
Excellent cold flow properties
Low foaming tendency
Excellent wear protection

Enables long drain interval application
Good efficiency and low fuel consumption
Prevents formation of sludge and deposits, so servicing needs are reduced
Fuel-saving operation at low temperature
Continuous, stable lubricating film, even at high speeds
Long gear lifetime, giving reliable operation

Specifications and approvals

Viscosity grade: SAE 75W-80
API GL-4
MAN 341 Typ Z4
Volvo 97307
Renault
DAF
IVECO
ZF TE-ML 02L
ZF TE-ML 16K
Eaton

Properties

Properties	Typical values
Density at 15°C [g/cm ³]	0,853
Kinematic viscosity at 40°C [mm ² /s]	53,8
Kinematic viscosity at 100 °C [mm ² /s]	9,7
Pour point [°C]	-54
Flash point (Cleveland) [°C]	215

The characteristics in table are typical values of the product and do not constitute a specification.

MOL Hykomol Syntrans LL 75W-80

synthetic automotive gear oil



Storage and handling instructions

Store in the original container in dry, properly ventilated area. Keep away from direct flame and other sources of ignition. Protect from direct sunlight.

During transport, storage and use of the product follow the work safety instructions and environmental regulations relating to mineral oil products.

For further details please read the Material Safety Data Sheet of the product.

Gear oils are finished lubricant formulations where additional additives are unnecessary and may result in unforeseeable adverse effects. The manufacturer and distributor shall not be held liable for such possible damages.

In the original container under the recommended storage conditions: 60 months

Recommended storage temperature: max. 40°C