Easyflex Page 1 of 7



# SAFETY DATA SHEET Easyflex



The safety data sheet is in accordance with Commission Regulation (EU) 2015/830 of 28 May 2015 amending Regulation (EC) No 1907/2006 of the European Parliament and of the Council on the Registration, Evaluation, Authorisation and Restriction of Chemicals (REACH)

# SECTION 1: Identification of the substance/mixture and of the

# company/undertaking

Date issued 13.10.2016

#### 1.1. Product identifier

Product name Easyflex

#### 1.2. Relevant identified uses of the substance or mixture and uses advised against

Product group Waterbaserd bitumen liquid membrane

Use of the substance/preparation Water- and radonproof bitumen membrane for various applications.

#### 1.3. Details of the supplier of the safety data sheet

#### **Distributor**

Company name	PazKar Nor AS
Postal address	Hellaveien 100
Postcode	1458
City	Fjellstrand
Country	Norway
Tel	+4798461575
E-mail	post@pazkarnor.com
Website	http://www.pazkarnor.com

#### 1.4. Emergency telephone number

Emergency telephone Giftinformasjonen:22 59 13 00

#### SECTION 2: Hazards identification

#### 2.1. Classification of substance or mixture

CLP Classification, Comments Classification according to (EC) No.1272/2008: Not classified.

2.2. Label elements

Supplemental label information EUH 210 Safety data sheet available on request.

2.3. Other hazards

PBT / vPvB PBT/vPvB assessment has not been performed.

# SECTION 3: Composition/information on ingredients

# 3.2. Mixtures

Substance	Identification	Classification	Contents
Bitumen (Residues(petroleum),	CAS no.: 64741-56-6		30 - 40 %
vacuum)	EC no.: 265-057-8		
Polychlorobutadiene	CAS no.: 9010-98-4		10 - 20 %
Solvent naphtha (petroleum), heavy	CAS no.: 64742-94-5	Asp. Tox. 1; H304	< 1 %
arom.	EC no.: 265-198-5	Note : H	
	Index no.: 649-424-00-3		
Substance comments	See section 16 for explanation of hazard statements (H) listed above		

Easyflex Page 2 of 7

#### SECTION 4: First aid measures

#### 4.1. Description of first aid measures

General Emergency telephone number: see section 1.4.

Inhalation Fresh air and rest. Get medical attention if any discomfort continues.

Skin contact Remove contaminated clothing. Wash the skin immediately with soap and

water. Get medical attention if any discomfort continues.

Eye contact Immediately flush with plenty of water for up to 15 minutes. Remove any

contact lenses and open eyes wide apart. Get medical attention if any

discomfort continues.

Ingestion Rinse the mouth and drink plenty of water. Do not induce vomiting. Get

medical attention.

#### 4.2. Most important symptoms and effects, both acute and delayed

#### 4.3. Indication of any immediate medical attention and special treatment needed

Other Information No specific information from the manufacturer.

# SECTION 5: Firefighting measures

#### 5.1. Extinguishing media

Suitable extinguishing media Foam, carbon dioxide or dry powder.

Improper extinguishing media Do not use water jet.

#### 5.2. Special hazards arising from the substance or mixture

Fire and explosion hazards

The chemical is not classified as flammable.

Hazardous combustion products May include, but is not limited to: Carbon dioxide (CO2). Carbon monoxide

(CO). Hydrogen sulphide (H2S). Hydrogen chloride (HCI). Sulphurous gases

(SOx). Calcium oxide.

#### 5.3. Advice for firefighters

also section 8.

Other Information Containers close to fire should be removed immediately or cooled with water.

#### SECTION 6: Accidental release measures

#### 6.1. Personal precautions, protective equipment and emergency procedures

General measures Keep away from sources of ignition - No smoking.

Personal protection measures Use protective equipment as referred to in section 8.

#### 6.2. Environmental precautions

Environmental precautionary

Do not allow to enter into sewer, water system or soil.

measures

#### 6.3. Methods and material for containment and cleaning up

Cleaning method Absorb in vermiculite, dry sand or earth and place into containers. Collect in

suitable containers and deliver as waste according to section 13.

#### 6.4. Reference to other sections

Other instructions See also sections 8 and 13.

# SECTION 7: Handling and storage

#### 7.1. Precautions for safe handling

Handling Avoid inhalation of vapours and contact with skin and eyes. Provide adequate

ventilation. Use protective equipment as referred to in section 8.

#### **Protective Safety Measures**

Advice on general occupational

hygiene

Wash hands after contact with the chemical. Change contaminated clothing and take off protective equipment before the meal. Do not eat, drink or

Easyflex Page 3 of 7

smoke during work.

#### 7.2. Conditions for safe storage, including any incompatibilities

Storage Store in tightly closed original container in a dry, cool and well-ventilated place. Store protected against heat and direct sunlight. Protect from frost.

#### Conditions for safe storage

Advice on storage compatability Keep away from: Strong oxidizing agents. Acids.

Storage Temperature Value: > 10 °C

Comments, Storage temperature Protect from sunlight. Do not expose to temperatures exceeding 50 °C /122

٥F

Storage Stabilit The chemical has a shelf life of 12 months.

#### 7.3. Specific end use(s)

Specific use(s) See section 1.2.

# SECTION 8: Exposure controls/personal protection

#### 8.1. Control parameters

#### **Occupational Exposure limit values**

Substance	Identification	Value	TWA Year
Solvent naphtha (petroleum), heavy	CAS no.: 64742-94-5	8-hour TWA: 25 ppm	
aromatic (Norway)	EC no.: 265-198-5	8-hour TWA: 120 mg/n	1 <sup>3</sup>
Other Information about threshold	References (laws/regulations): Norwegian regulation on exposure limits: "FOR-		
limit values	2011-12-06-1358 Forskrift om tiltaksverdier og grenseverdier for fysiske og kjemiske faktorer i arbeidsmiljøet samt smitterisikogrupper for biologiske faktorer (forskrift om tiltaks- og grenseverdier)".		

#### 8.2. Exposure controls

Limitation of exposure on workplace The personal protective equipment must be CE-marked and the latest version of the standards shall be used. The protective equipment and the specified

standards recommended below are only suggestions, and should be selected

on advice from the supplier of such equipment.

A risk assessment of the work place/work activities (the actual risk) may lead

to other control measures.

The protection equipments suitability and durability will depend on application. Provide adequate ventilation.

#### Respiratory protection

Respiratory protection Use filtercombination A/P2 while spraying.

Reference to relevant standard EN 14387 (Respiratory protective devices. Gas filter(s) and combined filter(s).

Requirements, testing, marking).

#### **Hand protection**

Hand protection Use chemical resistant gloves. The recommended material of gloves is

recommended after a study of the single components in the chemical. Glove thickness must be chosen in consultation with the glove supplier, who can

inform about the breakthrough time for the glove.

Suitable gloves type Butyl rubber

Reference to relevant standard BS-EN 420 (Protective gloves. General requirements and test methods). BS-

EN 374 (Protective gloves against chemicals and micro-organisms).

Breakthrough time No specific information from the manufacturer.

Thickness of glove material No specific information from the manufacturer.

Additional hand protection measures Replace gloves if signs of wear and tear.

#### Eye / face protection

Eye protection Wear safety goggles if there is a risk of splash.

Reference to relevant standard EN 166 (Personal eye-protection. Specifications).

#### Skin protection

Easyflex Page 4 of 7

Skin protection (except hands) Wear appropriate clothing to prevent reasonably probable skin contact.

#### Appropriate environmental exposure control

Environmental exposure controls 
Do not allow to enter into sewer, water system or soil.

Other Information

Other Information Eye wash facilities should be available when handling this chemical.

# SECTION 9: Physical and chemical properties

#### 9.1. Information on basic physical and chemical properties

Paste. Physical state Colour Brown Odour Not specified by the manufacturer. Not specified by the manufacturer. Comments, Odour limit pH (as supplied) Value: 8-11 Comments, Melting point / melting Not specified by the manufacturer. Comments, Boiling point / boiling Not specified by the manufacturer. range Comments, Flash point Not flammable. Not specified by the manufacturer. Comments, Evaporation rate Flammability (solid, gas) Not relevant, see flash point. Comments, Explosion limit Not specified by the manufacturer. Comments, Vapour pressure Not specified by the manufacturer. Not specified by the manufacturer. Comments, Vapour density Value: 1,15 g/cm3 Density Temperature: 25 °C Insoluble. Solubility in water Comments, Partition coefficient: n-Not relevant for a mixture. octanol / water Comments, Spontaneous Not specified by the manufacturer. combustability Decomposition temperature Value: 100 °C Viscous Comments, Viscosity

#### 9.2. Other information

#### Other physical and chemical properties

Comments No further information is available.

Not explosive.

Not oxidising.

#### SECTION 10: Stability and reactivity

#### 10.1. Reactivity

Explosive properties

Oxidising properties

Reactivity No reactivity hazards.

#### 10.2. Chemical stability

Stability The chemical is stable under normal conditions of storage and use.

#### 10.3. Possibility of hazardous reactions

Possibility of hazardous reactions No hazardous reactions known.

#### 10.4. Conditions to avoid

Conditions to avoid Strong heat.

#### 10.5. Incompatible materials

Materials to avoid Strong oxidizing agents. Acids.

### 10.6. Hazardous decomposition products

Hazardous decomposition products None under normal conditions. See also section 5.2.

Easyflex Page 5 of 7

# SECTION 11: Toxicological information

# 11.1. Information on toxicological effects

# **Toxicological Information:**

•		
LD50 oral	<b>Value:</b> > 40000 mg/kg	
	Animal test species: Rat	
	Comments: CAS-nr.: 9010-98-4	
LD50 dermal	Value: > 2 ml/kg	
	Animal test species: Kanin	
	Comments: CAS-nr.: 64742-94-5	
LC50 inhalation	Value: > 590 mg/m³	
	Animal test species: Rat	

Animal test species: Rat

Duration: 4 h

Comments: CAS-nr.: 64742-94-5

# Acute toxicity, Mixture estimate

Assessment of acute toxicity	Based on available data, the classification criteria are not met.
classification	

#### Potential acute effects

Inhalation	Low evaporation.
Skin contact	Slightly irritating. Degreases the skin. May cause dry skin or cracking of the
	skin and may also cause eczema.
Eye contact	Moderately irritating.
Ingestion	May irritate and cause malaise.
Assessment corrosion / irritation	Based on available data, the classification criteria are not met.
classification	
Aspiration hazard	Based on available data, the classification criteria are not met.
Assessment eye damage or	Based on available data, the classification criteria are not met.
irritation, classification	

# Delayed effects / repeated exposure

•	•	•
Sensitisation		Based on available data, the classification criteria are not met.
STOT-single exposure		Based on available data, the classification criteria are not met.
STOT-repeated exposure		Based on available data the classification criteria are not met.

# Carcinogenic, Mutagenic or Reprotoxic

Carcinogenicity	Based on available data, the classification criteria are not met.
Mutagenicity	Based on available data, the classification criteria are not met.
Reproductive toxicity	Based on available data, the classification criteria are not met.

# SECTION 12: Ecological information

# 12.1. Toxicity

Ecotoxicity	The chemical is not classified as environmentally hazardous. However, this
	does not exclude the possibility that large or frequent spills may be potentially
	hazardous.

# 12.2. Persistence and degradability

Persistence and degradability Contains substances that are not considered readily biodegradable.

# 12.3. Bioaccumulative potential

No data available on bioaccumulation. Bioaccumulative potential

# 12.4. Mobility in soil

Mobility Insoluble in water.

#### 12.5. Results of PBT and vPvB assessment

PBT assessment results	PBT assessment has not been performed.
vPvB evaluation results	vPvB assessment has not been performed.

Easyflex Page 6 of 7

#### 12.6. Other adverse effects

Other adverse effects / Remarks

Do not allow to enter into sewer, water system or soil. Forms an oil film on water surfaces that may harm organisms in the water and disrupt oxygen

transport in the boundary layer between air and water.

### SECTION 13: Disposal considerations

#### 13.1. Waste treatment methods

Specify the appropriate methods of disposal

Deliver to authorised waste vendor.

Product classified as hazardous No

waste

# SECTION 14: Transport information

#### 14.1. UN number

Comments Not considered as dangerous goods under UN, IMO, ADR/RID or IATA/ICAO

regulations.

# 14.2. UN proper shipping name

Comments Not relevant.

# 14.3. Transport hazard class(es)

Comments Not relevant.

#### 14.4. Packing group

Comments Not relevant.

#### 14.5. Environmental hazards

Comments Not relevant.

#### 14.6. Special precautions for user

Special safety precautions for user Not entered.

#### 14.7. Transport in bulk according to Annex II of MARPOL 73/78 and the IBC Code

Pollution category Not relevant.

#### SECTION 15: Regulatory information

# 15.1. Safety, health and environmental regulations/legislation specific for the substance or mixture

References (laws/regulations)

FOR-2012-06-16 nr 622 Norwegian regulation on classification, labeling and packaging of substances and mixtures (CLP), with later amendments.

FOR-2008-05-30 nr 516 Norwegian regulation on the registration, evaluation, authorization and restriction of chemicals (REACH Regulation), with later amendments.

Norwegian regulations on waste, no. 930/2004, from the Ministry of Environment.

Dangerous Goods regulations.

#### 15.2. Chemical safety assessment

Chemical safety assessment performed

No

#### SECTION 16: Other information

Supplier's notes

The information contained in this SDS must be made available to all those who handle the product.

List of relevant H-phrases (Section 2 and 3).

Abbreviations and acronyms used

The information contained in this SDS must be made available to all those who handle the product.

H304 May be fatal if swallowed and enters airways.

ADR: The European Agreement concerning the International Carriage of

Easyflex Page 7 of 7

	+g - +
	Dangerous Goods by Road EWC: European Waste Code (a code from the EU's common classification system for waste) IATA: The International Air Transport Association IMDG: The International Maritime Dangerous Goods Code LC50: Median concentration lethal to 50% of a test population. LD50: Lethal dose, is the amount of a substance given to a group of test animals, which causes the death of 50%. PBT: Persistent, Bioaccumulative and Toxic RID: The Regulations concerning the International Carriage of Dangerous Goods by Rail vPvB: very Persistent and very Bioaccumulative
Important data sources used to construct the safety data sheet	Suppliers Safety data sheet dated: 09.12.2015
Information which has been added, deleted or revised	New Safety Data Sheet.
Checking quality of information	This SDS is quality controlled by Kiwa Teknologisk Institutt in Norway, certified according to the Quality Management System requirements specified in ISO 9001:2008.
Version	1
Responsible for safety data sheet	PazKar Nor AS
Prepared by	Teknologisk Institutt as, Norway v/ Knut Finsveen