



SANET power Q&E 6x325ml west

WM 0713747

Order number: 0713747

Version 4.2

Revision Date 16.06.2016

Print Date 30.06.2016

SECTION 1: Identification of the substance/mixture and of the company/undertaking

1.1 Product identifier

Trade name : SANET power Q&E 6x325ml west
Identification number : 64534

1.2 Relevant identified uses of the substance or mixture and uses advised against

Use of the Substance/Mixture : Cleaning agent

1.3 Details of the supplier of the safety data sheet

Company : Erdal-Rex GmbH
Rheinallee 96
55120 Mainz
Telephone : +49613196402
Telefax : +4961319642413
E-mail address : Produktsicherheit@werner-mertz.com
Responsible/issuing person
Contact person : Product development / product safety

1.4 Emergency telephone number

+49(0)6131-19240

SECTION 2: Hazards identification

2.1 Classification of the substance or mixture

Classification (REGULATION (EC) No 1272/2008)

Corrosive to metals, Category 1 H290: May be corrosive to metals.

Skin corrosion, Category 1B H314: Causes severe skin burns and eye damage.

2.2 Label elements

Labelling (REGULATION (EC) No 1272/2008)

Hazard pictograms :



Signal word : Danger

Hazard statements : H290 May be corrosive to metals.
H314 Causes severe skin burns and eye damage.

Precautionary statements : P102 Keep out of reach of children.
Prevention:
P260 Do not breathe spray.
P280 Wear protective gloves/ protective clothing/ eye protection/ face protection.



SANET power Q&E 6x325ml west

WM 0713747

Order number: 0713747

Version 4.2

Revision Date 16.06.2016

Print Date 30.06.2016

Response:

P305 + P351 + P338 + P310 IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing. Immediately call a POISON CENTER or doctor/ physician.

P302 + P350 IF ON SKIN: Gently wash with plenty of soap and water.

P333 + P313 If skin irritation or rash occurs: Get medical advice/ attention.

Disposal:

P501 Only give completely emptied container to special waste disposer.

Hazardous components which must be listed on the label:

l-(+)-lactic acid
methanesulphonic acid

Classification in use concentration

Hazard pictograms :



Signal word :

Warning

Hazard statements :

H290 May be corrosive to metals.
H315 Causes skin irritation.
H319 Causes serious eye irritation.

Precautionary statements :

P102 Keep out of reach of children.
P260 Do not breathe spray.
P280 Wear protective gloves/ eye protection/ face protection.

P305 + P351 + P338 + P310 IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing. Immediately call a POISON CENTER or doctor/ physician.

P302 + P350 IF ON SKIN: Gently wash with plenty of soap and water.

P501 Only give completely emptied container to special waste disposer.

2.3 Other hazards

This substance/mixture contains no components considered to be either persistent, bioaccumulative and toxic (PBT), or very persistent and very bioaccumulative (vPvB) at levels of 0.1% or higher.
No information available.

SECTION 3: Composition/information on ingredients

3.2 Mixtures

Hazardous components



SANET power Q&E 6x325ml west

WM 0713747

Order number: 0713747

Version 4.2

Revision Date 16.06.2016

Print Date 30.06.2016

Chemical name	CAS-No. EC-No. Registration number	Classification (REGULATION (EC) No 1272/2008)	Concentration (%)
l-(+)-lactic acid	79-33-4 201-196-2 01-2119474164-39	Skin Irrit.2; H315 Eye Dam.1; H318	>= 15 - < 20
methanesulphonic acid	75-75-2 200-898-6 01-2119491166-34	Skin Corr.1B; H314 Met. Corr.1; H290 Acute Tox.4; H312 Acute Tox.4; H302 STOT SE3; H335 Eye Dam.1; H314	>= 5 - < 10
Alcohols, C12-14, ethoxylated, sulfates, sodium salts	68891-38-3 01-2119488639-16	Skin Irrit.2; H315 Eye Dam.1; H318 Aquatic Chronic3; H412	>= 5 - < 10
D-Glucopyranose, oligomers, decyl octyl glycosides	68515-73-1 01-2119488530-36	Eye Dam.1; H318	>= 2 - < 5

For explanation of abbreviations see section 16.

SECTION 4: First aid measures

4.1 Description of first aid measures

- General advice : Move out of dangerous area.
Consult a physician.
Show this safety data sheet to the doctor in attendance.
- If inhaled : Move to fresh air.
If symptoms persist, call a physician.
- In case of skin contact : Take off contaminated clothing and shoes immediately.
In case of contact, immediately flush skin with soap and plenty of water.
If symptoms persist, call a physician.
- In case of eye contact : Protect unharmed eye.
If easy to do, remove contact lens, if worn.
Rinse immediately with plenty of water, also under the eyelids, for at least 15 minutes.
If eye irritation persists, consult a specialist.
- If swallowed : Clean mouth with water and drink afterwards plenty of water.
Do NOT induce vomiting.
Do not give milk or alcoholic beverages.
Never give anything by mouth to an unconscious person.
Take victim immediately to hospital.

4.2 Most important symptoms and effects, both acute and delayed

- Symptoms : corrosive effects
- Risks : No information available.



SANET power Q&E 6x325ml west

WM 0713747

Order number: 0713747

Version 4.2

Revision Date 16.06.2016

Print Date 30.06.2016

4.3 Indication of any immediate medical attention and special treatment needed

Treatment : For specialist advice physicians should contact the Poisons Information Service.

SECTION 5: Firefighting measures

5.1 Extinguishing media

Suitable extinguishing media : Use extinguishing measures that are appropriate to local circumstances and the surrounding environment.

5.2 Special hazards arising from the substance or mixture

Specific hazards during firefighting : Do not allow run-off from fire fighting to enter drains or water courses.

Hazardous combustion products :

5.3 Advice for firefighters

Special protective equipment for firefighters : In the event of fire, wear self-contained breathing apparatus.

Further information : Collect contaminated fire extinguishing water separately. This must not be discharged into drains. Fire residues and contaminated fire extinguishing water must be disposed of in accordance with local regulations.

SECTION 6: Accidental release measures

6.1 Personal precautions, protective equipment and emergency procedures

Personal precautions : Use personal protective equipment.
Ensure adequate ventilation.
Evacuate personnel to safe areas.

6.2 Environmental precautions

Environmental precautions : Do not flush into surface water or sanitary sewer system.

6.3 Methods and materials for containment and cleaning up

Methods for cleaning up : Neutralize with chalk, alkali solution or ammonia.
Soak up with inert absorbent material (e.g. sand, silica gel, acid binder, universal binder, sawdust).
Keep in suitable, closed containers for disposal.

6.4 Reference to other sections

For personal protection see section 8., Treat recovered material as described in the section "Disposal considerations"., Refer to section 15 for specific national regulation.



SANET power Q&E 6x325ml west

WM 0713747

Order number: 0713747

Version 4.2

Revision Date 16.06.2016

Print Date 30.06.2016

SECTION 7: Handling and storage

7.1 Precautions for safe handling

- Advice on safe handling : For personal protection see section 8. Smoking, eating and drinking should be prohibited in the application area. To avoid spills during handling keep bottle on a metal tray. Dispose of rinse water in accordance with local and national regulations.
- Advice on protection against fire and explosion : Normal measures for preventive fire protection.
- Hygiene measures : Handle in accordance with good industrial hygiene and safety practice. Wash hands before breaks and at the end of workday.

7.2 Conditions for safe storage, including any incompatibilities

- Requirements for storage areas and containers : Keep container tightly closed in a dry and well-ventilated place. Containers which are opened must be carefully resealed and kept upright to prevent leakage. Store at room temperature in the original container.
- Other data : No decomposition if stored and applied as directed.

7.3 Specific end use(s)

- Specific use(s) : Cleaning agent

SECTION 8: Exposure controls/personal protection

8.1 Control parameters

Contains no substances with occupational exposure limit values.

DNEL

I-(+)-lactic acid 79-33-4:

- : End Use: Workers
Exposure routes: Inhalation
Potential health effects: Short-term exposure, Local effects
Value: 592 mg/m³

End Use: Consumers
Exposure routes: Ingestion
Potential health effects: Short-term exposure, Systemic effects

End Use: Consumers
Exposure routes: Inhalation
Potential health effects: Short-term exposure, Local effects
Value: 296 mg/m³

methanesulphonic acid 75-75-2:

- : End Use: Workers
Exposure routes: Inhalation
Potential health effects: Long-term exposure, Local effects



SANET power Q&E 6x325ml west

WM 0713747

Order number: 0713747

Version 4.2

Revision Date 16.06.2016

Print Date 30.06.2016

Value: 2,89 mg/m3

End Use: Workers
Exposure routes: Skin contact
Potential health effects: Long-term exposure, Systemic effects

End Use: Consumers
Exposure routes: Inhalation
Potential health effects: Long-term exposure, Systemic effects

End Use: Consumers
Exposure routes: Inhalation
Potential health effects: Short-term exposure, Systemic effects

End Use: Consumers
Exposure routes: Skin contact
Potential health effects: Long-term exposure, Systemic effects

Alcohols, C12-14, ethoxylated, sulfates, sodium salts 68891-38-3:

End Use: Workers
Exposure routes: Skin contact
Potential health effects: Long-term systemic effects

End Use: Workers
Exposure routes: Inhalation
Potential health effects: Long-term systemic effects
Value: 175 mg/m3

End Use: Consumers
Exposure routes: Skin contact
Potential health effects: Long-term systemic effects

End Use: Consumers
Exposure routes: Inhalation
Potential health effects: Long-term systemic effects
Value: 52 mg/m3

End Use: Consumers
Exposure routes: Ingestion
Potential health effects: Long-term systemic effects

End Use: Workers
Exposure routes: Skin contact
Potential health effects: Long-term local effects
Value: 0,132 mg/cm2

End Use: Consumers
Exposure routes: Skin contact
Potential health effects: Long-term local effects
Value: 0,079 mg/cm2

D-Glucopyranose, oligomers, decyl octyl glycosides 68515-73-1:

End Use: Workers
Exposure routes: Skin contact
Potential health effects: Long-term systemic effects

End Use: Workers
Exposure routes: Inhalation
Potential health effects: Long-term systemic effects
Value: 420 mg/m3



SANET power Q&E 6x325ml west

WM 0713747

Order number: 0713747

Version 4.2

Revision Date 16.06.2016

Print Date 30.06.2016

End Use: Consumers
Exposure routes: Skin contact
Potential health effects: Long-term systemic effects

End Use: Consumers
Exposure routes: Inhalation
Potential health effects: Long-term systemic effects
Value: 124 mg/m³

End Use: Consumers
Exposure routes: Ingestion
Potential health effects: Long-term systemic effects

PNEC

I-(+)-lactic acid
79-33-4: : Fresh water
Value: 1,3 mg/l

STP
Value: 10 mg/l

methanesulphonic acid
75-75-2: : Fresh water
Value: 0,012 mg/l

Marine water
Value: 0,0012 mg/l

Fresh water sediment
Value: 0,0251 mg/kg

Soil
Value: 0,00183 mg/kg

Alcohols, C12-14, ethoxylated,
sulfates, sodium salts
68891-38-3: : Fresh water
Value: 0,24 mg/l

Marine water
Value: 0,024 mg/l

Fresh water sediment
Value: 0,9168 mg/kg

Marine sediment
Value: 0,09168 mg/kg

Soil
Value: 7,5 mg/kg

STP
Value: 10000 mg/kg

intermittent release
Value: 0,071 mg/l

D-Glucopyranose, oligomers,
decyl octyl glycosides : Fresh water
Value: 0,176 mg/l



SANET power Q&E 6x325ml west

WM 0713747

Order number: 0713747

Version 4.2

Revision Date 16.06.2016

Print Date 30.06.2016

68515-73-1:

Marine water
Value: 0,0176 mg/l

intermittent release
Value: 0,27 mg/l

STP
Value: 560 mg/l

Fresh water sediment
Value: 1,516 mg/kg

Marine sediment
Value: 0,152 mg/kg

Soil
Value: 0,654 mg/kg

8.2 Exposure controls

Personal protective equipment

Eye protection : If splashes are likely to occur, wear:
Tightly fitting safety goggles

Hand protection

Material : For prolonged or repeated contact use protective gloves.
Chemical resistant gloves made of butyl rubber or nitrile rubber
category III according to EN 374.

Glove thickness : 0,4 mm

Remarks : Take note of the information given by the producer concerning
permeability and break through times, and of special workplace
conditions (mechanical strain, duration of contact).

Skin and body protection : Choose body protection according to the amount and concentration
of the dangerous substance at the work place.
Remove and wash contaminated clothing before re-use.

Respiratory protection : Not required; except in case of aerosol formation.
Recommended Filter type:
ABEK-P3-filter
Ensure adequate ventilation, especially in confined areas.

Environmental exposure controls

General advice : Do not flush into surface water or sanitary sewer system.

SECTION 9: Physical and chemical properties

9.1 Information on basic physical and chemical properties



SANET power Q&E 6x325ml west

WM 0713747

Order number: 0713747

Version 4.2

Revision Date 16.06.2016

Print Date 30.06.2016

Appearance	: liquid
Colour	: red
Odour	: characteristic
Odour Threshold	: No data available
pH	: 0
Melting point/range	: No data available
Boiling point/boiling range	: No information available.
Flash point	: Not applicable
Evaporation rate	: No data available
Flammability (solid, gas)	: No data available
Burning rate	: No data available
Lower explosion limit	: No data available
Upper explosion limit	: No data available
Vapour pressure	: No data available
Relative vapour density	: No data available
Relative density	: No data available
Density	: 1,096 g/cm ³ at 20 °C
Water solubility	: soluble
Solubility in other solvents	: No data available
Partition coefficient: n-octanol/water	: No data available
Ignition temperature	: No data available
Thermal decomposition	: No data available
Viscosity, dynamic	: No data available
Viscosity, kinematic	: No data available
Explosive properties	: No data available
Oxidizing properties	: No data available

9.2 Other information

none

SECTION 10: Stability and reactivity

10.1 Reactivity

Stable under recommended storage conditions., No dangerous reaction known under conditions of normal use.

10.2 Chemical stability

No decomposition if stored and applied as directed.



SANET power Q&E 6x325ml west

WM 0713747

Order number: 0713747

Version 4.2

Revision Date 16.06.2016

Print Date 30.06.2016

10.3 Possibility of hazardous reactions

Hazardous reactions : Stable under recommended storage conditions., No decomposition if used as directed.

10.4 Conditions to avoid

Conditions to avoid : No data available

10.5 Incompatible materials

Materials to avoid : No data available

10.6 Hazardous decomposition products

Hazardous decomposition products : No hazardous decomposition products are known.
Other information : No hazardous decomposition products are known.

SECTION 11: Toxicological information

11.1 Information on toxicological effects

Product

Acute oral toxicity : Acute toxicity estimate : > 2.000 mg/kg
Method: Calculation method

Acute dermal toxicity : Acute toxicity estimate : > 2.000 mg/kg
Method: Calculation method

Skin corrosion/irritation : Extremely corrosive and destructive to tissue.

Serious eye damage/eye irritation : May cause irreversible eye damage.

Respiratory or skin sensitisation : No data available

Further information : No data available

Components:

I-(+)-lactic acid

79-33-4:

Acute oral toxicity : LD50 Rat: 3.730 mg/kg
LD50 Mouse: 4.875 mg/kg
LD50 Oral Guinea pig: 1.810 mg/kg

Acute inhalation toxicity : LC50 Rat: 7,94 mg/l
Exposure time: 4 h

Acute dermal toxicity : LD50 Rabbit: > 2.000 mg/kg



SANET power Q&E 6x325ml west

WM 0713747

Order number: 0713747

Version 4.2

Revision Date 16.06.2016

Print Date 30.06.2016

methanesulphonic acid

75-75-2:

Acute oral toxicity : LD50 Rat: 200 mg/kg

LD50 Rat: 649 mg/kg

Acute inhalation toxicity : LC0 Mouse: > 1,88 mg/l
Exposure time: 1 h

Acute dermal toxicity : LD50 Rabbit: > 1.000 - 2.000 mg/kg

Alcohols, C12-14, ethoxylated, sulfates, sodium salts

68891-38-3:

Acute oral toxicity : LD50 Oral Rat: 4.100 mg/kg
Method: OECD Test Guideline 401
GLP: no

LD50 Oral Rat: 2.000 - 5.000 mg/kg
Method: OECD Test Guideline 401
Test substance: see user defined free text

LD50 Oral Rat: > 5.000 mg/kg
Method: OECD Test Guideline 401
Test substance: see user defined free text

Acute dermal toxicity : LD50 Rat: > 2.000 mg/kg
Method: OECD Test Guideline 402
GLP: yes

Skin corrosion/irritation : Species: Rabbit
Method: OECD Test Guideline 404

Serious eye damage/eye irritation : Species: Rabbit
Method: OECD Test Guideline 405
Test substance: see user defined free text

Species: Rabbit
Method: OECD Test Guideline 405
Test substance: see user defined free text

Respiratory or skin sensitisation : Test Method: Maximisation Test (GPMT)
Species: Guinea pig
Result: Did not cause sensitisation on laboratory animals.
Method: OECD Test Guideline 406

Germ cell mutagenicity

Genotoxicity in vitro : Result: negative
Method: OECD Test Guideline 471



SANET power Q&E 6x325ml west

WM 0713747

Order number: 0713747

Version 4.2

Revision Date 16.06.2016

Print Date 30.06.2016

Reproductive toxicity : Species: Rat
Application Route: Oral
NOAEL: > 300 mg/kg,
F1: > 300 mg/kg, Method: OECD Test Guideline 416

Teratogenicity : Species: Rat
Application Route: Oral
>1.000 mg/kg
> 1.000 mg/kg
Method: see user defined free text

Repeated dose toxicity : Rat: NOAEL: > 225 mg/kg

Application Route: Oral
Exposure time: 90 Days
Method: see user defined free text
Target Organs: Liver

STOT - repeated exposure : Exposure routes: Ingestion
Target Organs: Liver

D-Glucopyranose, oligomers, decyl octyl glycosides

68515-73-1:

Acute oral toxicity : LD50 Rat: > 5.000 mg/kg
Method: OECD Test Guideline 401

Acute dermal toxicity : Rabbit: > 2.000 mg/kg
Method: OECD Test Guideline 402

Skin corrosion/irritation : Species: Rabbit
Result: Mild skin irritation
Method: OECD Test Guideline 404

Serious eye damage/eye irritation : Species: Rabbit
Result: Irreversible effects on the eye
Method: OECD Test Guideline 405

Respiratory or skin sensitisation : Species: Guinea pig
Result: Does not cause skin sensitisation.
Method: OECD Test Guideline 406

Germ cell mutagenicity

Genotoxicity in vitro : Type: Ames test
Result: negative
Method: OECD Test Guideline 471



SANET power Q&E 6x325ml west

WM 0713747

Order number: 0713747

Version 4.2

Revision Date 16.06.2016

Print Date 30.06.2016

SECTION 12: Ecological information

12.1 Toxicity

Components:

I-(+)-lactic acid

79-33-4:

- Toxicity to fish : LC50 (Lepomis macrochirus (Bluegill sunfish)): 130 mg/l
Exposure time: 96 h
- LC50 (Fish): 320 mg/l
Exposure time: 48 h
- Toxicity to daphnia and other aquatic invertebrates : EC50 (Daphnia magna (Water flea)): 130 mg/l
Exposure time: 48 h
- EC50 (Daphnia pulex (Water flea)): 240 mg/l
Exposure time: 48 h
- Toxicity to algae : EC50 (Selenastrum capricornutum): 3.500 mg/l
- ErC50 (Pseudokirchneriella subcapitata (microalgae)): 2.800 mg/l
Exposure time: 72 h
- Toxicity to bacteria : EC50 : > 100 mg/l
Exposure time: 3 h

methanesulphonic acid

75-75-2:

- Toxicity to fish : LC50 (Oncorhynchus mykiss (rainbow trout)): 10 - 100 mg/l
Exposure time: 96 h
Test Type: static test
Method: OECD Test Guideline 203
- Toxicity to daphnia and other aquatic invertebrates : EC50 (Daphnia magna (Water flea)): 10 - 100 mg/l
Exposure time: 48 h
Test Type: static test
Method: OECD Test Guideline 202
- Toxicity to algae : EC50 (Scenedesmus capricornutum (fresh water algae)): 10 - 100 mg/l
Exposure time: 72 h
Test Type: Growth inhibition
Method: OECD Test Guideline 201
- Toxicity to bacteria : EC50 : 10 - 100 mg/l
Exposure time: 72 h
Method: see user defined free text
Remarks: see user defined free text

Alcohols, C12-14, ethoxylated, sulfates, sodium salts

68891-38-3:

- Toxicity to fish : LC50 (Danio rerio (zebra fish)): 7,1 mg/l
Exposure time: 96 h
Test Type: flow-through test
Method: OECD Test Guideline 203



SANET power Q&E 6x325ml west

WM 0713747

Order number: 0713747

Version 4.2

Revision Date 16.06.2016

Print Date 30.06.2016

- GLP: yes
- LC50 (Fish): > 1 - 10 mg/l
Test Type: semi-static test
Method: OECD Test Guideline 203
- LC50 (Leuciscus idus (Golden orfe)): 10 - 100 mg/l
Method: OECD Test Guideline 203
- Toxicity to daphnia and other aquatic invertebrates : EC50 (Daphnia pulex (Water flea)): 7,4 mg/l
- EC50 (Daphnia magna (Water flea)): > 1 - 10 mg/l
Exposure time: 48 h
Test Type: static test
Method: OECD Test Guideline 202
- Toxicity to algae : EC50 (Desmodesmus subspicatus (green algae)): 27,7 mg/l
Exposure time: 72 h
Test Type: Growth inhibition
Method: OECD Test Guideline 201
GLP: yes
- EC50 (Scenedesmus subspicatus): 10 - 100 mg/l
Method: OECD Test Guideline 201
- EC50 (Desmodesmus subspicatus (green algae)): > 10 - 100 mg/l
Exposure time: 72 h
Test Type: static test
Method: OECD Test Guideline 201
- NOEC : 0,95 mg/l
Test Type: Growth inhibition
Method: OECD Test Guideline 201
- Toxicity to bacteria : EC50 (Pseudomonas putida): > 10 g/l
Exposure time: 16 h
Test Type: Cell multiplication inhibition test
Method: DIN 38412
GLP: yes
- EC10 (Pseudomonas putida): > 10 g/l
Test Type: Cell multiplication inhibition test
GLP:
- Toxicity to fish (Chronic toxicity) : NOEC: 1,2 mg/l
- NOEC: 1 - 10 mg/l
Species: Leuciscus idus (Golden orfe)
- Toxicity to daphnia and other aquatic invertebrates (Chronic toxicity) : NOEC: > 0,1 - 1 mg/l
Exposure time: 21 d
Species: Daphnia magna (Water flea)
Method: OECD Test Guideline 211

12.2 Persistence and degradability

Product:



SANET power Q&E 6x325ml west

WM 0713747

Order number: 0713747

Version 4.2

Revision Date 16.06.2016

Print Date 30.06.2016

Biodegradability : Remarks: The surfactant(s) contained in this preparation complies (comply) with the biodegradability criteria as laid down in Regulation (EC) No. 648/2004 on detergents.

Components:

I-(+)-lactic acid 79-33-4:

Biodegradability : Result: rapidly biodegradable

Biochemical Oxygen Demand (BOD) : 450 mg/g
Incubation time: 5 d

600 mg/g
Incubation time: 20 d

Chemical Oxygen Demand (COD) : 900 mg/g

ThOD : 1.067 mg/g

methanesulphonic acid 75-75-2:

Biodegradability : Result: rapidly biodegradable
Biodegradation: > 99 %
Exposure time: 28 d

Alcohols, C12-14, ethoxylated, sulfates, sodium salts 68891-38-3:

Biodegradability : Result: rapidly biodegradable
Biodegradation: > 70 %
Exposure time: 28 d
Method: OECD 301 A

12.3 Bioaccumulative potential

Components:

methanesulphonic acid 75-75-2:

Partition coefficient: n-octanol/water : log Pow: -2,38

12.4 Mobility in soil

Components:

methanesulphonic acid 75-75-2:

Distribution among environmental compartments : Koc: 1Remarks: Highly mobile in soils

Alcohols, C12-14, ethoxylated, sulfates, sodium salts 68891-38-3:

Distribution among environmental compartments : Adsorption/Soil
Medium: Soil
Koc: 191Method: see user defined free text



SANET power Q&E 6x325ml west

WM 0713747

Order number: 0713747

Version 4.2

Revision Date 16.06.2016

Print Date 30.06.2016

12.5 Results of PBT and vPvB assessment

Product:

Assessment : This substance/mixture contains no components considered to be either persistent, bioaccumulative and toxic (PBT), or very persistent and very bioaccumulative (vPvB) at levels of 0.1% or higher..

Components:

Alcohols, C12-14, ethoxylated, sulfates, sodium salts

68891-38-3:

Assessment : This substance is not considered to be very persistent and very bioaccumulating (vPvB).. This substance is not considered to be persistent, bioaccumulating and toxic (PBT)..

12.6 Other adverse effects

Product:

Additional ecological information : There is no data available for this product.

SECTION 13: Disposal considerations

13.1 Waste treatment methods

Product : Do not dispose of waste into sewer.
Do not contaminate ponds, waterways or ditches with chemical or used container.
Offer surplus and non-recyclable solutions to a licensed disposal company.

Contaminated packaging : Empty remaining contents.
Dispose of as unused product.
Do not re-use empty containers.

Waste Code : European Waste Catalogue
200129
According to the European Waste Catalogue, Waste Codes are not product specific, but application specific. Waste codes should be assigned by the user, preferably in discussion with the waste disposal authorities.

SECTION 14: Transport information

14.1 UN number

ADR : 3265
IMDG : 3265
IATA : 3265

14.2 Proper shipping name

ADR : CORROSIVE LIQUID, ACIDIC, ORGANIC, N.O.S.
(l-(+)-lactic acid, methanesulphonic acid)

IMDG : CORROSIVE LIQUID, ACIDIC, ORGANIC, N.O.S.
(l-(+)-lactic acid, methanesulphonic acid)

IATA : Corrosive liquid, acidic, organic, n.o.s.
(l-(+)-lactic acid, methanesulphonic acid)



SANET power Q&E 6x325ml west

WM 0713747

Order number: 0713747

Version 4.2

Revision Date 16.06.2016

Print Date 30.06.2016

14.3 Transport hazard class

ADR : 8
IMDG : 8
IATA : 8

14.4 Packing group

ADR
Classification Code : C3
Packaging group : III
Hazard Identification Number : 80
Labels : 8
Tunnel restriction code : (E)
IMDG
Packaging group : III
Labels : 8
EmS Number : F-A, S-B
IATA
Packing instruction (cargo aircraft) : 856
Packing instruction (LQ) : Y841
Packaging group : III
Labels : 8

14.5 Environmental hazards

ADR
Environmentally hazardous : no

IMDG
Marine pollutant : no

IATA
Environmentally hazardous : no

14.6 Special precautions for user

For personal protection see section 8.

14.7 Transport in bulk according to Annex II of MARPOL 73/78 and the IBC Code

Not applicable for product as supplied.

SECTION 15: Regulatory information

15.1 Safety, health and environmental regulations/legislation specific for the substance or mixture

ZEU_SEVES3

Not applicable

TA Luft List (Germany) : Total dust: Not applicable
: Inorganic substances in powdered form: Not applicable
: Inorganic substances in vapour or gaseous form: Not applicable
: Organic Substances: : portionClass 1: < 0,01 %
: Carcinogenic substances: Not applicable
: Mutagenic: Not applicable
: Toxic to reproduction: Not applicable
Volatile organic compounds : Directive 1999/13/EC
: Volatile organic compounds (VOC) content: 27,91 %, 1.000,59 g/l

Directive 1999/13/EC



SANET power Q&E 6x325ml west

WM 0713747

Order number: 0713747

Version 4.2

Revision Date 16.06.2016

Print Date 30.06.2016

Volatile organic compounds (VOC) content: 27,91 %, 305,92 g/l

according to Detergents Regulation EC 648/2004 : 5 - <15% Anionic surfactants, <5% Non-ionic surfactants, Perfumes

Diğer kurallar : 26 Aralık 2008 tarihli, 27092 mükerrer sayılı, " T.C. Çevre ve Orman Bakanlığı Tehlikeli Maddeler ve Müstahzarlara İlişkin Güvenlik Bilgi Formlarının Hazırlanması ve Dağıtılması Hakkında Yönetmeliği " ne uygun düzenlenmiştir.
26 Aralık 2008 27092 (mükerrer) sayılı Tehlikeli Maddelerin ve Müstahzarların Sınıflandırılması, Ambalajlanması ve Etiketlenmesi Hakkında Yönetmelik hükümlerine göre hazırlanmıştır.

15.2 Chemical safety assessment

There is no data available for this product.

SECTION 16: Other information

Full text of H-Statements

H290	May be corrosive to metals.
H302	Harmful if swallowed.
H312	Harmful in contact with skin.
H314	Causes severe skin burns and eye damage.
H315	Causes skin irritation.
H318	Causes serious eye damage.
H335	May cause respiratory irritation.
H412	Harmful to aquatic life with long lasting effects.

Further information

Classification procedure:	H290	Calculation method
	H314	Calculation method

The information provided in this Safety Data Sheet is correct to the best of our knowledge, information and belief at the date of its publication. The information given is designed only as a guidance for safe handling, use, processing, storage, transportation, disposal and release and is not to be considered a warranty or quality specification. The information relates only to the specific material designated and may not be valid for such material used in combination with any other materials or in any process, unless specified in the text.