

SAFETY DATA SHEET

NORDIC SHIELD SURFACE SANITIZER

1: Identification of the substance/mixture and of the company/undertaking

1.1. Product identifier

Trade name	Surface Sanitizer
Produkt no.	NS2004
REACH registration number	Not applicable

1.2. Relevant identified uses of the substance or mixture and uses advised against

Relevant identified uses of the substance or mixture	Aerosol cleaner, degreaser and solvent.
------------------------------------------------------	-----------------------------------------

1.3. Details of the supplier of the safety data sheet

Company and address	The Army Painter A/S Nydamsvej 1 DK-8362 Hørning tlf: +45 71 79 11 50
Contact person	Bo Penstoft
E-mail	contact@thearmypainter.com

SDS date	2020-04-23
SDS Version	1.0

1.4. Emergency telephone number

Contact The National Poisons Information Service (dial 111, 24 h service). See section 4 "First aid measures".

2: Hazards identification

2.1. Classification of the substance or mixture

The product is classified as hazardous pursuant to the provisions set forth in (EC) Regulation 1272/2008 (CLP) (and subsequent amendments and supplements). The product thus requires a safety datasheet that complies with the provisions of (EU) Regulation 2015/830.

Any additional information concerning the risks for health and/or the environment are given in sections 11 and 12 of this sheet.

Hazard classification and indication:

Aerosol, category 1	H222	Extremely flammable aerosol.
	H229	Pressurised container: may burst if heated.
Eye irritation, category 2	H319	Causes serious eye irritation.
Specific target organ toxicity - single exposure, category 3	H336	May cause drowsiness or dizziness.

2.2. Label elements

Hazard pictograms:



Signal word	Danger
Hazard statement(s)	H222 Extremely flammable aerosol. H229 Pressurised container: may burst if heated. H319 Causes serious eye irritation. H336 May cause drowsiness or dizziness.
Precautionary statements	P210 Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking. P251 Do not pierce or burn, even after use. P410+P412 Protect from sunlight. Do not expose to temperatures exceeding 50°C / 122°F. P211 Do not spray on an open flame or other ignition source. P102 Keep out of reach of children. P261 Avoid breathing dust / fume / gas / mist / vapours / spray.
Contains	Isopropyl Alcohol Ethyl acetate

2.3. Other hazards

On the basis of available data, the product does not contain any PBT or vPvB in percentage greater than 0,1%.

3: Composition/information on ingredients

3.1/3.2. Stoffer/Blandinger

Name:	Isopropyl alcohol
Identification no.:	CAS-no.: 67-63-0, EC-no.: 200-661-7, INDEX: 603-117-00-0
Content:	51 ≤ x < 55 %
Clp classification:	Flam. Liq. 2 H225, Eye Irrit. 2 H319, STOT SE 3 H336
Note:	O
Name:	Propane
Identification no.:	CAS-no.: 74-98-6, EC-no.: 200-827-9, INDEX 601-003-00-5
Clp classification:	Flam. Gas 1A H220, Press. Gas (Liq.) H280, Classification note according to Annex VI to the CLP Regulation: U
Content:	23 ≤ x < 27 %
Name:	Butane
Identification no.:	CAS no.: 106-97-8, EC-no.: 203-448-7, INDEX 601-004-00-0
Clp classification:	Flam. Gas 1A H220, Press. Gas (Liq.) H280, Classification note according to Annex VI to the CLP Regulation: C U
Content:	11 ≤ x < 15 %
Name:	Ethyl acetate
Identification no.:	CAS no.: 141-78-6, EC no.: 205-500-4, INDEX 607-022-00-5
Content:	5 ≤ x < 7%
Clp classification:	Flam. Liq. 2 H225, Eye Irrit. 2 H319, STOT SE 3 H336, EUH066
Name:	Isobutane
Identification no.:	CAS nr.: 8001-97-6, EC-no. 200-857-2, INDEX 601-004-00-0
Content:	1 ≤ x < 3 %
Clp classification:	Flam. Gas 1A H220, Press. Gas H280

The full wording of hazard (H) phrases is given in section 16 of the sheet.

The product is an aerosol containing propellants. For the purposes of calculation of the health hazards, propellants are not considered (unless they have health hazards). The percentages indicated are inclusive of the propellants.

Percentage of propellants: 40,30 %

4: First aid measures

4.1. Description of first aid measures

Inhalation	Remove to open air. In the event of breathing difficulties, get medical advice/attention immediately.
Skin contact	Remove contaminated clothing. Wash immediately with plenty of water. If irritation persists, get medical advice/attention. Wash contaminated clothing before using it again.
Eye contact	Remove contact lenses, if present. Wash immediately with plenty of water for at least 15 minutes, opening the eyelids fully. If problem persists, seek medical advice.
Ingestion	Get medical advice/attention. Induce vomiting only if indicated by the doctor. Never give anything by mouth to an unconscious person, unless authorised by a doctor.

4.2. Most important symptoms and effects, both acute and delayed

Specific information on symptoms and effects caused by the product are unknown.

4.3. Indication of any immediate medical attention and special treatment needed

Information not available

5: Firefighting measures

5.1. Extinguishing media

SUITABLE EXTINGUISHING EQUIPMENT

The extinguishing equipment should be of the conventional kind: carbon dioxide, foam, powder and water spray.

UNSUITABLE

EXTINGUISHING EQUIPMENT

None in particular.

5.2. Special hazards arising from the substance or mixture

HAZARDS CAUSED BY EXPOSURE IN THE EVENT OF FIRE

If overheated, aerosol cans can deform, explode and be propelled considerable distances. Put a protective helmet on before approaching the fire. Do not breathe combustion products.

5.3. Advice for firefighters

GENERAL INFORMATION

Use jets of water to cool the containers to prevent product decomposition and the development of substances potentially hazardous for health. Always wear full fire prevention gear.

SPECIAL PROTECTIVE EQUIPMENT FOR FIRE-FIGHTERS

Normal fire fighting clothing i.e. fire kit (BS EN 469), gloves (BS EN 659) and boots (HO specification A29 and A30) in combination with self-contained open circuit positive pressure compressed air breathing apparatus (BS EN 137).

6: Accidental release measures

6.1. Personal precautions, protective equipment and emergency procedures

Eliminate all sources of ignition (cigarettes, flames, sparks, etc.) from the leakage site. Send away individuals who are not suitably equipped. Wear protective gloves / protective clothing / eye protection / face protection.

6.2. Environmental precautions

Do not disperse in the environment.

6.3. Methods and material for containment and cleaning up

Use inert absorbent material to soak up leaked product. Make sure the leakage site is well aired. Contaminated material should be disposed of in compliance with the provisions set forth in point 13.

6.4. Reference to other sections

Any information on personal protection and disposal is given in sections 8 and 13.

7: Handling and storage

7.1. Precautions for safe handling

Avoid bunching of electrostatic charges. Do not spray on flames or incandescent bodies. Vapours may catch fire and an explosion may occur; vapour accumulation is therefore to be avoided by leaving windows and doors open and ensuring good cross ventilation. Do not eat, drink or smoke during use. Do not breathe spray.

7.2. Conditions for safe storage, including any incompatibilities

Store in a place where adequate ventilation is ensured, away from direct sunlight at a temperature below 50°C / 122°F, away from any combustion sources.

7.3. Specific end use(s)

Information not available

8: Exposure controls/personal protection

8.1. Control parameters

Regulatory References

DEU	Deutschland	TRGS 900 - Seite 1 von 69 (Fassung 29.03.2019)- Liste der Arbeitsplatzgrenzwerte und Kurzzeitwerte
ESP	España	LÍMITES DE EXPOSICIÓN PROFESIONAL PARA AGENTES QUÍMICOS EN ESPAÑA 2019 (INSST)
FRA	France	Valeurs limites d'exposition professionnelle aux agents chimiques en France. ED 984 - INRS
GBR	United Kingdom	EH40/2005 Workplace exposure limits (Third edition,published 2018)
ITA	Italia	DIRETTIVA (UE) 2017/164 DELLA COMMISSIONE del 31 gennaio 2017
POL	Polska	ROZPORZ DZENIE MINISTRA RODZINY, PRACY I POLITYKI SPOŁECZNEJ z dnia 12 czerwca 2018 r
PRT	Portugal	Ministério da Economia e do Emprego Consolida as prescrições mínimas em matéria de protecção dos trabalhadores contra os riscos para a segurança e a saúde devido à exposição a agentes químicos no trabalho - Diário da República, 1.ª série - N.º 111 - 11 de junho de 2018
EU	OEL EU	Directive (EU) 2017/2398; Directive (EU) 2017/164; Directive 2009/161/EU; Directive 2006/15/EC; Directive 2004/37/EC; Directive 2000/39/EC; Directive 91/322/EEC.
	TLV-ACGIH	ACGIH 2019

Isopropyl Alcohol Threshold Limit Value

Type	Country	TWA/8h		STEL/15min		Remarks / Observations
		mg/m3	ppm	mg/m3	ppm	
AGW	DEU	500	200	1000	400	
MAK	DEU	500	200	1000	400	
VLA	ESP	500	200	1000	400	
VLEP	FRA			980	400	
WEL	GBR	999	400	1250	500	
NDS/NDSch	POL	900		1200		SKIN
TLV-ACGIH		492	200	983	400	

Predicted no-effect concentration - PNEC		
Normal value in fresh water	140,9	mg/l
Normal value in marine water	140,9	mg/l
Normal value for fresh water sediment	552	mg/kg/d
Normal value for marine water sediment	552	mg/kg/d
Normal value for water, intermittent release	140,9	mg/l
Normal value of STP microorganisms	2,251	g/l
Normal value for the food chain (secondary poisoning)	160	mg/kg
Normal value for the terrestrial compartment	28	mg/kg/d

Health - Derived no-effect level - DNEL / DMEL								
Route of exposure	Effects on consumers				Effects on workers			
	Acute local	Acute systemic	Chronic local	Chronic systemic	Acute local	Acute systemic	Chronic local	Chronic systemic
Oral	VND	VND	VND	26 mg/kg bw/d	VND	VND	VND	VND
Inhalation	VND	VND	VND	89 mg/m3	VND	VND	VND	500 mg/m3
Skin	VND	VND	VND	319 mg/kg	VND	VND	VND	888 mg/kg

Propane Threshold Limit Value					
Type	Country	TWA/8h	STEL/15min		Remarks / Observations
		mg/m3	ppm	mg/m3	ppm
AGW	DEU	1800	1000	7200	4000
MAK	DEU	1800	1000	7200	4000
VLA	ESP		1000		
NDS/NDSCh	POL	1800			

Butane Threshold Limit Value					
Type	Country	TWA/8h	STEL/15min		Remarks / Observations
		mg/m3	ppm	mg/m3	ppm
AGW	DEU	2400	1000	9600	4000
MAK	DEU	2400	1000	9600	4000
VLA	ESP		1000		Gases
VLEP	FRA	1900	800		

Isobutane Threshold Limit Value					
Type	Country	TWA/8h	STEL/15min		Remarks / Observations
		mg/m3	ppm	mg/m3	ppm
TLV-ACGIH			800		

Ethyl acetate Threshold Limit Value					
Type	Country	TWA/8h	STEL/15min		Remarks / Observations
		mg/m3	ppm	mg/m3	ppm
AGW	DEU	730	200	1460	400
MAK	DEU	750	200	1500	400
VLA	ESP	734	200	1468	400
VLEP	FRA	1400	400		
WEL	GBR	734	200	1468	400
VLEP	ITA	734	200	1468	400
NDS/NDSCh	POL	734		1468	
VLE	PRT	734	200	1468	400

OEL	EU	734	200	1468	400				
TLV-ACGIH		1441	400						
Predicted no-effect concentration - PNEC									
Normal value in fresh water				240					µg/l
Normal value in marine water				24					µg/l
Normal value for fresh water sediment				1,15					µg/kg
Normal value for marine water sediment				115					µg/kg
Normal value for water, intermittent release				1,65					mg/l
Normal value of STP microorganisms				650					mg/l
Normal value for the food chain (secondary poisoning)				200					mg/kg
Normal value for the terrestrial compartment				148					µg/kg/d
Normal value for the atmosphere				NPI					
Health - Derived no-effect level - DNEL / DMEL									
		Effects on consumers				Effects on workers			
Route of exposure		Acute local	Acute systemic	Chronic local	Chronic systemic	Acute local	Acute systemic	Chronic local	Chronic systemic
Oral				VND	4,5 mg/kg				
Inhalation	734 mg/kg	734 mg/kg	367 mg/m3	367 mg/m3	1468 mg/m3	1468 mg/m3	734 mg/m3	734 mg/m3	734 mg/m3
Skin			VND	37 mg/kg					63 mg/kg

Legend:

(C) = CEILING ; INHAL = Inhalable Fraction ; RESP = Respirable Fraction ; THORA = Thoracic Fraction.

VND = hazard identified but no DNEL/PNEC available ; NEA = no exposure expected ; NPI = no hazard identified.

TLV of solvent mixture: 527 mg/m³

8.2. Exposure controls

As the use of adequate technical equipment must always take priority over personal protective equipment, make sure that the workplace is well aired through effective local aspiration.

When choosing personal protective equipment, ask your chemical substance supplier for advice.

Personal protective equipment must be CE marked, showing that it complies with applicable standards.

Provide an emergency shower with face and eye wash station.

Hand protection

None required

Skin protection

Wear category I professional long-sleeved overalls and safety footwear (see Regulation 2016/425 and standard EN ISO 20344). Wash body with soap and water after removing protective clothing.

Exposure limits

Professional users are subjected to the legally set maximum concentrations for occupational exposure. See occupational hygiene limit values above.

Eye protection

Wear airtight protective goggles (see standard EN 166).

Respiratory protection

If the threshold value (e.g. TLV-TWA) is exceeded for the substance or one of the substances present in the product, a mask with a type AX filter combined with a type P filter should be worn (see standard EN 14387).

Respiratory protection devices must be used if the technical measures adopted are not suitable for restricting the worker's exposure to the threshold values considered. The protection provided by masks is in any case limited.

Environmental exposure controls

The emissions generated by manufacturing processes, including those generated by ventilation equipment, should be checked to ensure compliance with environmental standards.

9: Physical and chemical properties

9.1. Information on basic physical and chemical properties

Form

Aerosol

Colour	Clear
Odour	Alcoholic characteristic
pH	No data available.
Viscosity (40°C)	No data available.
Density (g/cm³)	No data available.

Phase changes	
Melting point (°C)	No data available.
Boiling point (°C)	No data available.
Vapour pressure	No data available.
Decomposition temperature (°C)	No data available.
Evaporation rate (n-butylacetate = 100)	No data available.

Data on fire and explosion hazards

Flash point (°C)	< 0 °C
Evaporation Rate	Not available
Flammability of solids and gases	flammable gas
Lower inflammability limit	Not available
Upper inflammability limit	Not available
Lower explosive limit	Not available
Upper explosive limit	Not available
Vapour pressure	Not available
Vapour density	Not available
Relative density	0,65 ÷ 0,69 g/ml a 20°C
Solubility	Not available
Partition coefficient: n-octanol/water	Not available
Auto-ignition temperature	Not available
Decomposition temperature	Not available
Viscosity	Not available
Explosive properties	not applicable
Oxidising properties	not applicable

9.2. Other information

VOC (Directive 2010/75/EC)	100,00 % - 670,00 g/litre
Solvent base	alcool isopropilico 90%
Flash point	10 C°

10: Stability and reactivity

10.1. Reactivity

There are no particular risks of reaction with other substances in normal conditions of use.

Ethyl acetate	It slowly decomposes into acetic acid and ethanol due to the action of light, air and water.
----------------------	----------------------------------------------------------------------------------------------

10.2. Chemical stability

The product is stable in normal conditions of use and storage.

10.3. Possibility of hazardous reactions

No hazardous reactions are foreseeable in normal conditions of use and storage.

Ethyl acetate	Risk of explosion on contact with: alkaline metals,hydrides,oleum. May react violently
----------------------	----------------------------------------------------------------------------------------

with: fluorine, strong oxidising agents, chlorosulphuric acid, potassium tert-butoxide. Forms explosive mixtures with: air.

10.4. Conditions to avoid

Avoid overheating.

Ethyl acetate

Avoid exposure to: light, sources of heat, naked flames.

10.5. Incompatible materials

Strong reducing or oxidising agents, strong acids or alkalis, hot material.

Ethyl acetate

Incompatible with: acids, bases, strong oxidants, aluminium, nitrates, chlorosulphuric acid.
Incompatible materials: plastic materials.

10.6. Hazardous decomposition products

Information not available

11: Toxicological information

In the absence of experimental data for the product itself, health hazards are evaluated according to the properties of the substances it contains, using the criteria specified in the applicable regulation for classification.

It is therefore necessary to take into account the concentration of the individual hazardous substances indicated in section 3, to evaluate the toxicological effects of exposure to the product.

11.1. Information on toxicological effects

Metabolism, toxicokinetics, mechanism of action and other information

Information not available

Information on likely routes of exposure

Information not available

Delayed and immediate effects as well as chronic effects from short and long-term exposure

Information not available

Interactive effects

Information not available

Acute toxicity

LC50 (Inhalation) of the mixture:
Not classified (no significant component)
LD50 (Oral) of the mixture:
Not classified (no significant component)
LD50 (Dermal) of the mixture:
Not classified (no significant component)

Substance: Butane
LC50 (Inhalation) > 1442,738 mg/l/15min rat

Substance: Propane
LC50 (Inhalation) 800000 ppm 15 min

Substance: Isopropyle Alcohol
D50 (Oral) 5840 mg/kg bw Rat
LD50 (Dermal) 16,4 ml/kg rabbit

LC50 (Inhalation) > 10000 ppm/6h Rat

Substance: Ethyl Acetate
LD50 (Oral) 11,3 mg/kg bw rat
LD50 (Dermal) 20000 mg/kg bw rabbit
LC50 (Inhalation) > 22,5 mg/l/6h rat

Substance: Isobutane
LC50 (Inhalation) > 1442,738 mg/l/15min rat

Skin corrosion/irritation	Does not meet the classification criteria for this hazard class
Serious eye damage/irritation	Causes serious eye irritation.
Respiratory or skin sensitisation	Does not meet the classification criteria for this hazard class
Germ cell mutagenicity	Does not meet the classification criteria for this hazard class
Carcinogenicity	Does not meet the classification criteria for this hazard class
Reproductive toxicity	Does not meet the classification criteria for this hazard class
STOT-single exposure	May cause drowsiness or dizziness
STOT-repeated exposure	Does not meet the classification criteria for this hazard class
Aspiration hazard	Does not meet the classification criteria for this hazard class

12: Ecological information

12.1. Toxicity

Substance: Butane
LC50 - for Fish > 24,11 mg/l/96h

Substance: Propane
LC50 - for Fish 85,82 mg/l/96h

EC50 - for Crustacea 41,82 mg/l/48h

Substance: Isopropyl Alcohol
LC50 - for Fish 9,6 g/l/96h
Substance: Ethyl acetate
LC50 - for Fish 230 mg/l/96h
EC50 - for Algae / Aquatic Plants 100 mg/l/72h
Chronic NOEC for Fish 9,65 mg/l 32 days
Chronic NOEC for Crustacea 2,4 mg/l 21 days

Substance: Isobutane
LC50 - for Fish > 24,11 mg/l/96h

12.2. Persistence and degradability

Propane

Global Warming Potential (GWP): 3. Ozone Depletion Potential (ODP): 0.

Butane

Solubility in water 0,1 - 100 mg/l
Rapidly degradable

Propane

Solubility in water 0,1 - 100 mg/l
Rapidly degradable

Isopropyl Alcohol

Rapidly degradable
Readily biodegradable (50%)

Ethyl acetate

Solubility in water > 10000 mg/l
Rapidly degradable

Isobutane

Rapidly degradable

12.3. Bioaccumulative potential

Butane

Partition coefficient: n-octanol/water 1,09

Propane

Partition coefficient: n-octanol/water 1,09

Isopropyl

Alcohol Partition coefficient: n-octanol/water 0,05

Ethyl acetate

Partition coefficient: n-octanol/water 0,68
BCF 30

12.4. Mobility in soil

No data available

12.5. Results of PBT and vPvB assessment

On the basis of available data, the product does not contain any PBT or vPvB in percentage greater than 0,1%.

12.6. Other adverse effects

Nothing special

13: Disposal considerations

13.1. Waste treatment methods

Reuse, when possible. Product residues should be considered special hazardous waste. The hazard level of waste containing this product should be evaluated according to applicable regulations.

Disposal must be performed through an authorised waste management firm, in compliance with national and local regulations.

Waste transportation may be subject to ADR restrictions.

CONTAMINATED PACKAGING

Contaminated packaging must be recovered or disposed of in compliance with national waste management regulations.

14: Transport information

14.1. UN Number

ADR / RID, IMDG, IATA: 1950

14.2. UN proper shipping name

ADR / RID: AEROSOLS
IMDG: AEROSOLS
IATA: AEROSOLS, FLAMMABLE

14.3. Transport hazard class(es)

ADR / RID: Class: 2 Label: 2.1
IMDG: Class: 2 Label: 2.1
IATA: Class: 2 Label: 2.1

14.4. Packing group

ADR / RID, IMDG, IATA: -

14.5 Environmental hazards

ADR / RID: No
IMDG: No
IATA: No
-

14.6. Special precautions for user

ADR / RID: HIN - Kemler: -- Limited Quantities: 1 L Tunnel restriction code: (D)
Special Provision: -
IMDG: EMS: F-D, S-U Limited Quantities: 1 L
IATA: Cargo: Maximum quantity: 150Kg Packaging instructions: 203
Pass.: Maximum quantity: 75 Kg Packaging instructions: 203
Special Instructions: A145, A167, A802

14.7. Transport in bulk according to Annex II of Marpol and the IBC Code

No data available

15: Regulatory information

15.1. Safety, health and environmental regulations/legislation specific for the substance or mixture

Seveso Category - Directive 2012/18/EC: P3a

Restrictions relating to the product or contained substances pursuant to Annex XVII to EC Regulation 1907/2006

Product

Point 40

Substances in Candidate List (Art. 59 REACH)

On the basis of available data, the product does not contain any SVHC in percentage greater than 0,1%.

-

Substances subject to authorisation (Annex XIV REACH)

None

Substances subject to exportation reporting pursuant to (EC) Reg. 649/2012:

None

Substances subject to the Rotterdam Convention:

None

Substances subject to the Stockholm Convention:

None

Healthcare controls

Workers exposed to this chemical agent must not undergo health checks, provided that available risk-assessment data prove that the risks related to the workers' health and safety are modest and that the 98/24/EC directive is respected.

15.2. Chemical safety assessment

A chemical safety assessment has been performed for the following contained substances

Butane

16: Other information

Text of hazard (H) indications mentioned in section 2-3 of the sheet:

Flam. Gas 1A	Flammable gas, category 1A
Aerosol 1	Aerosol, category 1
Aerosol 3	Aerosol, category 3
Flam. Liq. 2	Flammable liquid, category 2
Press. Gas (Liq.)	Liquefied gas
Press. Gas	Pressurised gas
Eye Irrit. 2	Eye irritation, category 2
STOT SE 3	Specific target organ toxicity - single exposure, category 3
H220	Extremely flammable gas.
H222	Extremely flammable aerosol.
H229	Pressurised container: may burst if heated.
H225	Highly flammable liquid and vapour.
H280	Contains gas under pressure; may burst if heated.
H319	Causes serious eye irritation.
H336	May cause drowsiness or dizziness.
EUH066	Repeated exposure may cause skin dryness or cracking.

LEGEND:

- ADR: European Agreement concerning the carriage of Dangerous goods by Road
- CAS NUMBER: Chemical Abstract Service Number
- CE50: Effective concentration (required to induce a 50% effect)
- CE NUMBER: Identifier in ESIS (European archive of existing substances)
- CLP: EC Regulation 1272/2008
- DNEL: Derived No Effect Level
- EmS: Emergency Schedule
- GHS: Globally Harmonized System of classification and labeling of chemicals
- IATA DGR: International Air Transport Association Dangerous Goods Regulation
- IC50: Immobilization Concentration 50%
- IMDG: International Maritime Code for dangerous goods
- IMO: International Maritime Organization
- INDEX NUMBER: Identifier in Annex VI of CLP
- LC50: Lethal Concentration 50%
- LD50: Lethal dose 50%
- OEL: Occupational Exposure Level
- PBT: Persistent bioaccumulative and toxic as REACH Regulation
- PEC: Predicted environmental Concentration
- PEL: Predicted exposure level
- PNEC: Predicted no effect concentration
- REACH: EC Regulation 1907/2006
- RID: Regulation concerning the international transport of dangerous goods by train

- TLV: Threshold Limit Value
- TLV CEILING: Concentration that should not be exceeded during any time of occupational exposure.
- TWA STEL: Short-term exposure limit
- TWA: Time-weighted average exposure limit
- VOC: Volatile organic Compounds
- vPvB: Very Persistent and very Bioaccumulative as for REACH Regulation
- WGK: Water hazard classes (German).

GENERAL BIBLIOGRAPHY

1. Regulation (EC) 1907/2006 (REACH) of the European Parliament
 2. Regulation (EC) 1272/2008 (CLP) of the European Parliament
 3. Regulation (EU) 790/2009 (I Atp. CLP) of the European Parliament
 4. Regulation (EU) 2015/830 of the European Parliament
 5. Regulation (EU) 286/2011 (II Atp. CLP) of the European Parliament
 6. Regulation (EU) 618/2012 (III Atp. CLP) of the European Parliament
 7. Regulation (EU) 487/2013 (IV Atp. CLP) of the European Parliament
 8. Regulation (EU) 944/2013 (V Atp. CLP) of the European Parliament
 9. Regulation (EU) 605/2014 (VI Atp. CLP) of the European Parliament
 10. Regulation (EU) 2015/1221 (VII Atp. CLP) of the European Parliament
 11. Regulation (EU) 2016/918 (VIII Atp. CLP) of the European Parliament
 12. Regulation (EU) 2016/1179 (IX Atp. CLP)
 13. Regulation (EU) 2017/776 (X Atp. CLP)
 14. Regulation (EU) 2018/669 (XI Atp. CLP)
 15. Regulation (EU) 2018/1480 (XIII Atp. CLP)
 16. Regulation (EU) 2019/521 (XII Atp. CLP)
- The Merck Index. - 10th Edition
 - Handling Chemical Safety
 - INRS - Fiche Toxicologique (toxicological sheet)
 - Patty - Industrial Hygiene and Toxicology
 - N.I. Sax - Dangerous properties of Industrial Materials-7, 1989 Edition
 - IFA GESTIS website
 - ECHA website
 - Database of SDS models for chemicals - Ministry of Health and ISS (Istituto Superiore di Sanità) - Italy

Note for users:

The information contained in the present sheet are based on our own knowledge on the date of the last version. Users must verify the suitability and thoroughness of provided information according to each specific use of the product.

This document must not be regarded as a guarantee on any specific product property.

The use of this product is not subject to our direct control; therefore, users must, under their own responsibility, comply with the current health and safety laws and regulations. The producer is relieved from any liability arising from improper uses.

Provide appointed staff with adequate training on how to use chemical products.

Product's classification is based on the calculation methods set out in Annex I of the CLP Regulation, unless otherwise indicated in sections 11 and 12.

The data for evaluation of chemical-physical properties are reported in section 9.

The safety data sheet is validated by

Bo Penstoft

Date of last essential change

23-04-2020

Date of last minor change

23-04-2020