
Pre-Vulcanisation Oven SHOCK Oven MINI R3

OVEN TYPE SHOCK

Infrared pre-vulcanisation treatment oven. Particularly suitable for extrusion lines combined with Air Jet tunnel ovens.

Distributer:


PU Consulting AB info@puconsulting.se





OVENTYPE	Mini 120	Mini 230	Mini 300
A(mm)	120	230	300
Oven width (mm)	890	890	890
Oven depth (mm)	890	890	890
Oven height (mm)	from 1250 to 1550	from 1250 to 1550	from 1250 to 1550
Height of product from ground (mm)	from 930 to 1230	from 930 to 1230	from 930 to 1230
Approximate weight (kg)	200	200	200
Bectric power (kw)	9/10,5/12	12	12
Operating temperature (°C)	400	400	400
Max temperature (°C)	800	800	800
Pneumatic opening door	optional	included	included

SERMAC S.r.I. reserves itself the faculty to possibly apply technical or construction changes without notice



Main features:

- > Inner chamber made of stainless steel, painted carbon steel outer structure
- Hydraulic product height adjustment.
- Pneumatic inspection door opening, standard on models 230 and 300, optional for the 120 model.
- Innovative insulation system and thermal insulation \geq
- Sliding ceramic material shutters at both ends of the oven \geq for reduced energy consumption
- Reduced dimensions and excellent manoeuvrability