

TECHNICAL SPECIFICATIONS

RF 5.2mm F2.8L DUAL FISHEYE

OPTICAL FEATURES/SPECIFICATIONS

Image size	Full Frame
35mm film equivalent focal length (mm)	-
Angle of view (horzntl, vertl, diagnol)	190°, 190°, 190°
Lens construction (elements/groups)	12/10
Special optics	2 x UD
Special features	Dual Fisheye with Baseline length of 60mm
No. of diaphragm blades	7
Minimum aperture	1.6
Closest focusing distance (m)	0.2
Maximum magnification (x)	0.03
Control Ring	No
Image stabilizer OIS ¹	-
Image stabilizer IBIS x OIS ¹	-
AF actuator	-
Coatings	Super Spectra, SWC
Fluorine	Front

PHYSICAL SPECIFICATIONS

Dust/moisture resistance ³	Rubber ring on lens mount
Exterior coating	-
Filter diameter (mm)	Rear-mounted gelatin filter (35x20mm)
Max. diameter x length (mm) ²	(121.1 x 83.6) x 53.5
Weight (g)	350

ACCESSORIES

Lens cap	Lens Cap 5.2 (center pinch type)
Lens hood	-
Lens case/pouch	LS1014
Rear cap	Lens Dust Cap RF
Extender Compatibility	Not Compatible
Other Accessories	Hexagon wrench

Footnote:

¹Tested under CIPA standards

²Lens dimensions when in retracted state

³Lenses with dust/moisture resistance are fitted with a rubber ring on the lens mount which may cause slight abrasion of the camera mount. This in no way effects either the lens or camera performance.

Live for the story_

Canon Inc.
canon.com
Canon Europe
canon-europe.com
English edition
Canon Europa NV 2021