

## Grease Separator (Above Ground or Inside Kuranglez Use)

Suitable for EN 1825 and DIN 4040-100 standards, TSE and ISO Certificated, manufactured with HDPE (Polyethylene) material rotobuilding manufacturing method, with built-in sludge-sludge retainer, 2-year body warranty, above ground (in-room) use in places where there is no frost risk Suitable, for odorless waste discharge without opening the device, with DN 32 / PN 10 oil intake and DN 50 / PN 10 sludge discharge mouth, with ventilation mouth, water filling opening (R ¾ ”), sight window, plastic inlet and outlet connections ( PVC) pipe connection, can use hot or cold water for washing, odor-proof sealed polyethylene intervention cover (Ø 455 mm), inner and outer surface resistant to oil and acids, smooth surface without residue on the wall, oil and solid waste separator with left inlet connection.

### Technical Specifications

Name of the product	YTTP 2000	YTTP 3000	YTTP 4000	YTTP 6000	YTTP 8000	YTTP 20000
Flow (lt.)	2	3	4	6	8	20
Total Volume (lt.)	538	795	1092	1530	2059	5135
Sludge Capacity (lt.)	210	310	420	630	840	2100
Grease Capacity (lt.)	80	120	160	240	398	800
Inlet-Outlet (mm.)	110/110	110/110	110/110	125/125	160/160	200/200
Tank Dimension (mm.)	1280x600x920	1480x680x1050	2040x630x1130	2300x700x1320	2600x800x1400	3570x1190x1760



## Grease Separator (Underground Embedded Use)

Compliant with EN 1825 and DIN 4040-100 standards, TSE and ISO certified, produced by rotobuilding manufacturing method from HDPE (Polyethylene) material, with built-in sludge-sludge retainer, 2-year body warranty, suitable for underground (buried) use in places where there is no frost risk , inlet and outlet connections are suitable for plastic (PVC) pipe connection, with riser (riser), composite cover (Ø 515 mm), inner and outer surface resistant to oil and acids, smooth surface without residue on the periphery, oil and solid waste separator with left inlet connection .

### Technical Specifications

Name of the product	YTTP 2000	YTTP 3000	YTTP 4000	YTTP 6000	YTTP 8000	YTTP YS 10000	YTTP YS 20000	YTTP 20000
Flow (lt.)	2	3	4	6	8	10	20	20
Total Volume (lt.)	538	795	1092	1530	2059	3030	5120	5135
Sludge Capacity (lt.)	210	310	420	630	840	1090	2100	2100
Grease Capacity (lt.)	80	120	160	240	398	510	800	800
Inlet-Outlet (mm.)	110/110	110/110	110/110	125/125	160/160	160/160	200/200	200/200
Tank dimensions (Including riser) (mm.)	1280x600 x1270	1480x680x1400	2040x630x1480	2300x700x1670	2600x800x1750	1840x1600x2050	2900x1600x2050	3570x1190x2110

