

Produkt - splitt varmepumpe

Outdoor unit	Singelsplitt inverter	RAS-25U2AVPG-ND
Indoor unit	Console	RAS-25U2FVG-ND

Function

Cooling	Y
Oppvarming - gjennomsnittlig	Y
Oppvarming - Varmere	N
Oppvarming - Kaldere	N

Design load

Cooling	Pdesignc	2.5	kW
Heating/Average	Pdesignh	3.5	kW

Capacity control = Variable

Årsvarmefaktor eller SCOP

Cooling	SEER	8.60	A+++
Heating/Average	SCOP(A)	4.60	A++

Cooling

Kapasitet

Declared capacity for cooling at indoor temperature 27(19)°C and outdoor temperature Tj.

Effektivitet

Declared Energy efficiency ratio for cooling at indoor temperature 27(19)°C and outdoor temperature Tj.

Tj=35°C	Pdc	2.50	kW	Tj=35°C	EERd	4.63
Tj=30°C	Pdc	1.84	kW	Tj=30°C	EERd	7.95
Tj=25°C	Pdc	1.18	kW	Tj=25°C	EERd	11.84
Tj=20°C	Pdc	1.15	kW	Tj=20°C	EERd	14.45

Oppvarming (gjennomsnittsklima)

Kapasitet

Declared capacity for Heating/Average season, at indoor temperature 20°C and outdoor temperature Tj.

Effektivitet

Declared coefficient of performance/Average season, at indoor temperature 20°C and outdoor temperature Tj.

Tj=-7°C	Pdh	3.10	kW	Tj=-7°C	COPd	2.60
Tj=2°C	Pdh	1.88	kW	Tj=2°C	COPd	4.66
Tj=7°C	Pdh	1.21	kW	Tj=7°C	COPd	6.28
Tj=12°C	Pdh	0.94	kW	Tj=12°C	COPd	7.10
Tj=bivalent temperature	Pdh	3.50	kW	Tj=bivalent temperature	COPd	2.30
Tj=driftsbegrensning	Pdh	1.92	kW	Tj=driftsbegrensning	COPd	1.88
Bivalent temperature		-10	°C			
Laveste utetemperatur for drift		-30	°C			

Elektrisitet

Electric power input in power modes other than "on mode"

Sesonggjennomsnittlig tilført elektrisk energi

off mode	Poff	0.004	kW	Cooling	QCE	102	kWh/a
standby mode	Psb	0.004	kW	Heating/Average	QHE/A	1064	kWh/a
thermostat-off mode	Pto	0.018	kW	Heating/Warmer	QHE/B	x	kWh/a
crankcase heater mode	Pck	0.000	kW	Heating/Colder	QHE/C	x	kWh/a

Kuldemedium

Type	R32
Vekt	0.93 kg
Globalt oppvarmingspotensial	GWP 675 kgCO ₂ eq.

Sound power level - db(A)

Rated air flow - m³/h

	Cooling	Heating		Cooling	Heating
RAS-25U2AVPG-ND	61	62	RAS-25U2AVPG-ND	1870	2160
RAS-25U2FVG-ND	55	56	RAS-25U2FVG-ND	510	550

Dimensjoner

	Høyde	Bredde	Dybde	Vekt
RAS-25U2AVPG-ND	630 mm	800 mm	300 mm	39 kg
RAS-25U2FVG-ND	600 mm	700 mm	220 mm	16 kg

Harmonisert standard EN14511:2007, EN12102

Kalkulasjonsmetode - målestandard PrEN 14825: 2011 Kapittel 8 og 9

Kontakt for mer informasjon

Importør/distributør i EU:
Toshiba Carrier UK Ltd.
Porsham Close, Belliver Industrial Estate,
PLYMOUTH, Devon, PL6 7DB.
United Kingdom

Supplier	TOSHIBA CARRIER CORPORATION
----------	-----------------------------

Innedel	RAS-25U2FVG-ND
---------	----------------

Utedel	RAS-25U2AVPG-ND
--------	-----------------

Sound power level

innedel (kjøling)	dB	55
-------------------	----	----

utedel (kjøling)	dB	61
------------------	----	----

innedel (oppvarming)	dB	56
----------------------	----	----

utedel (oppvarming)	dB	62
---------------------	----	----

Kuldemedium

Type		R32
------	--	-----

Globalt oppvarmingspotensial	kgCO ₂ eq	675
------------------------------	----------------------	-----

Refrigerant leakage contributes to climate change. Refrigerant with lower global warming potential (GWP) would contribute less to global warming than a refrigerant with higher GWP, if leaked to the atmosphere. This appliance contains a refrigerant fluid with a GWP equal to 1975. This means that if 1 kg of this refrigerant fluid would be leaked to the atmosphere, the impact on global warming would be 1975 times higher than 1 kg of CO₂, over a period of 100 years. Never try to interfere with the refrigerant circuit yourself or disassemble the product yourself and always ask a professional.

Cooling

Energy efficiency class		A+++
-------------------------	--	------

Design load (P _{designc})	kW	2.5
-------------------------------------	----	-----

Årsvarmefaktor eller SCOP (SEER)		8.60
----------------------------------	--	------

Sesonggjennomsnittlig tilført elektrisk energi (Q _{CE})	kWh/annum	102
---	-----------	-----

Heating

		Heating/Average	Heating/Warmer	Heating/Colder
Energy efficiency class		A++	x	x
Design load (Pdesignh)	kW	3.5	x,x	x,x
Årsvarmefaktor eller SCOP (SCOP)		4.60	x,xx	x,xx
Sesonggjennomsnittlig tilført elektrisk energi (Q _{HE})	kWh/annum	1064	x	x
Back-up varmekapasitet	kW	0.00		
Spesifisert varmekapasitet ved innetemperatur 20 °C og utetemperatur Tj.				
Tj= -7°C (Pdh)	kW	3.10	-	x,xx
Tj= 2°C (Pdh)	kW	1.88	x,xx	x,xx
Tj= 7°C (Pdh)	kW	1.21	x,xx	x,xx
Tj= 12°C (Pdh)	kW	0.94	x,xx	x,xx
Tj=bivalent temperature (Pdh)	kW	3.50	x,xx	x,xx
Tj=driftsbegrensning (Pdh)	kW	1.92	x,xx	x,xx
Tj= -15°C (Pdh)	kW	-	-	x,xx