

TT 5-A

ACTIVE HIGH OUTPUT TWO-WAY SPEAKER

DESCRIPTION

Thanks to the powerful 4" compression driver, the large sized horn, the incredibly fast woofer, TT5-A offers the highest performance from a wide dispersion, active, 2 way system. High output and dynamics, extreme linearity and fidelity makes the TT5-A a unique product in its category. The TT5-A is the ideal professional two-way speaker for mid field and near field sound reinforcement, live performance and events. The RCF Precision newly designed 4" compression driver guarantees the exceptional sound projection and pattern control. The integration of the 1600 Watt, digital amplification and the advanced digital processing set a new standard for distortion, noise and thermal efficiency. The speaker is equipped with a complete set of integrated rigging mechanics for rental or installation. Dedicated accessories to create clusters are available.



FEATURES

- 1600 Watt, 2 way amplification
- 15" neo woofer, 4" v.c.
- 2" titanium dome neo compression driver, 4.0" v.c.
- 90° x 50° precision waveguide
- 96 Khz, 32 bit DSP processing
- Maximum output, perfect audio fidelity
- Tour grade cabinet and mechanics
- RDNet Ready

TECHNICAL SPECIFICATIONS

Acoustical specifications	Frequency Response:	45 Hz ÷ 20000 Hz
	Max SPL @ 1m:	136 dB
	Horizontal coverage angle:	90°
	Vertical coverage angle:	50°
Transducers	Compression Driver:	2.0" neo, 4.0" v.c
	Woofer:	15" neo, 4.0" v.c
Input/Output section	Input signal:	bal/unbal
	Input connectors:	XLR, RDNet Ethercon
	Output connectors:	XLR, RDNet Ethercon
	Input sensitivity:	+4 dBu
Processor section	Crossover Frequencies:	650 Hz
	Protections:	Thermal, RMS
	Limiter:	Soft Limiter
	Controls:	Gain reduction, RDNet local setup/bypass, Time Delay, Presets (Linear, Close, Far listening, High- Pass), RDNet Ready
	RDNet:	Yes
Power section	Total Power:	3200 W Peak, 1600 W RMS
	High frequencies:	1000 W Peak, 500 W RMS
	Low frequencies:	2200 W Peak, 1100 W RMS
	Cooling:	Convection
	Connections:	Powercon IN/OUT
Standard compliance	CE marking:	Yes
Physical specifications	Cabinet/Case Material:	Baltic birch plywood
	Hardware:	Installation/Rental fittings
	Handles:	2 side
	Pole mount/Cap:	Yes
	Grille:	Steel
	Color:	Black
Size	Height:	735 mm / 28.94 inches
	Width:	444 mm / 17.48 inches
	Depth:	529 mm / 20.83 inches
	Weight:	42.5 kg / 93.7 lbs
Shipping informations	Package Height:	870 mm / 34.25 inches
	Package Width:	630 mm / 24.8 inches
	Package Depth:	580 mm / 22.83 inches
	Package Weight:	47.5 kg / 104.72 lbs



PART NUMBER

• **13000383**

TT 5-A

115V

EAN 8024530010508

• **13000379**

TT 5-A

220-240V

EAN 8024530010447

TTS-A







