



BST 300

- DC25V
- Rated Pressure: 700 kPa
- Max Pressure: 800 kPa
- Brushless Motor

Model: **BST300**

Rated Voltage (V): **DC24V**

Input Power (W): **<380 W**

Speed (r/min): **>1750**

Rated Pressure (kPa): **700 kPa**

Max Pressure (kPa): **800 kPa**

Restart Pressure (kPa): **0 kPa**

Rated Volume Flow (m³/h): **2.1 m³/h @700 kPa**

Noise dB(A): **<58 dB(A)**. The air inlet is connected to the air filter and the exhaust is connected to the 2m air pipe. The noise is tested at the place 1m above the air inlet and the ambient noise is less than 40 dB.

Ambient Temperature °C: **-41~55 °C**

Insulation Class: **F**

Cold Insulation Resistance (MΩ): **>100 MΩ**

Net Weight (kg): **5 kg**

Installation Dimensions (mm): **100x83 mm (4*M6)**

External Dimensions (mm): **192x103x165 mm**



Info@swautomatik.se | Phone: +46 (0)8-620 33 20 | www.swautomatik.se

*Head Office: Mårbackagatan 27, Box 64, 123 22 Farsta
Delivery Address: Rålsгатan 6, 802 91 Gävle*