



O-SCENT SPRAY



O-Scent Spray is a vaporising suppression machine which generates a consistent stream of atomized water.

O-Scent Spray products provide a column of air that exits the aerodynamic shaped cone at high velocity and can travel big distances. A dense spray of properly atomized water is injected into the air column as result there is an extremely effective means of air suppression.



GENERAL SPECIFICATIONS

- Throw 25m
- Aerodynamic composite lightweight cone
- Hot dipped galvanized structure
- Low noise high efficiency fan
- Adjustable angle of throw -10° to 50°
- Integrated water filter system

WATER SPECIFICATIONS

- A constant inlet press. of 1,5 bar with the rated flow
- HP Pump
- Waterbox filtersystem with flushfunction
- 1/2" BSP male fitting
- Stainless steel nozzlering
- HP nozzles
- Last chance filter before nozzle
- Droplet size spectrum vary from 30 to 50 micron
- Waterflow 400l/h

OPTIONS

- Bigger boosterpump(s)
- Pressure detection incl.
- Water cut off valve incl.
- Remote control
- Dosage pump
- Horizontal oscillation
- 3 x 480V 60Hz
- 1 x 230V

ELECTRICAL SPECIFICATIONS

- Voltage 3x400V 50Hz
- Fan (kw) 2,2
- Pump (kw) 1,5
- Rot. (kw) NA
- IP66 steel cabinet

DIMENSIONS & WEIGHT

- length 1350 mm
- Width 1100mm
- Height 1550mm
- Weight 210kg



Technic Eco Services s.a.
62, Av. de la Liberté - L-1930 Luxembourg
LUXEMBOURG

T +35 226 008 248
info@teslux.be

www.teslux.eu