

Part #	Description	Product Datasheet	Product Group
1040290200	Xtreme/104, 2 ports RS-232/422/485, 3 kV optical isolation	http://connecttech.com/product/xtreme104-opto-pc104-serial/	Xtreme/104 Opto – PC/104 Serial
1040290201	Xtreme/104, 2 ports RS-232/422/485, 3 kV optical isolation, DB-9 cables	http://connecttech.com/product/xtreme104-opto-pc104-serial/	Xtreme/104 Opto – PC/104 Serial
1040290220	Xtreme/104, 2 ports RS-232/422/485, 3 kV optical isolation, industrial Temp. -40°C to 85°C	http://connecttech.com/product/xtreme104-opto-pc104-serial/	Xtreme/104 Opto – PC/104 Serial
1040290221	Xtreme/104, 2 ports RS-232/422/485, 3 kV optical isolation, industrial Temp. -40°C to 85°C, DB-9 cables	http://connecttech.com/product/xtreme104-opto-pc104-serial/	Xtreme/104 Opto – PC/104 Serial
1040490200	Xtreme/104, 4 ports RS-232/422/485, 3 kV optical isolation	http://connecttech.com/product/xtreme104-opto-pc104-serial/	Xtreme/104 Opto – PC/104 Serial
1040490201	Xtreme/104, 4 ports RS-232/422/485, 3 kV optical isolation, DB-9 cables	http://connecttech.com/product/xtreme104-opto-pc104-serial/	Xtreme/104 Opto – PC/104 Serial
1040490220	Xtreme/104, 4 ports RS-232/422/485, 3 kV optical isolation, industrial Temp. -40°C to 85°C	http://connecttech.com/product/xtreme104-opto-pc104-serial/	Xtreme/104 Opto – PC/104 Serial
1040490221	Xtreme/104, 4 ports RS-232/422/485, 3 kV optical isolation, industrial Temp. -40°C to 85°C, DB-9 cables	http://connecttech.com/product/xtreme104-opto-pc104-serial/	Xtreme/104 Opto – PC/104 Serial
1040800020	Xtreme-8/104, 8 ports RS-232, industrial Temp. -40°C to 85°C	http://connecttech.com/product/xtreme104-rs-232-pc104-serial-expansion/	Xtreme/104 RS-232 – PC/104 Serial Expansion
1040800021	Xtreme-8/104, 8 ports RS-232, industrial Temp. -40°C to 85°C, DB-9 cables	http://connecttech.com/product/xtreme104-rs-232-pc104-serial-expansion/	Xtreme/104 RS-232 – PC/104 Serial Expansion
1040890000	Xtreme-8/104, 8 ports RS-232/422/485	http://connecttech.com/product/xtreme104-rs-232-pc104-serial-expansion/	Xtreme/104 RS-232 – PC/104 Serial Expansion
1040890001	Xtreme-8/104, 8 ports RS-232/422/485, DB-9 cables	http://connecttech.com/product/xtreme104-rs-232-pc104-serial-expansion/	Xtreme/104 RS-232 – PC/104 Serial Expansion
1040890020	Xtreme-8/104, 8 ports RS-232/422/485, industrial Temp. -40°C to 85°C	http://connecttech.com/product/xtreme104-rs-232-pc104-serial-expansion/	Xtreme/104 RS-232 – PC/104 Serial Expansion
1040890021	Xtreme-8/104, 8 ports RS-232/422/485, industrial Temp. -40°C to 85°C, DB-9 cables	https://developer.nvidia.com/embedded/faq	Xtreme/104 RS-232 – PC/104 Serial Expansion
04001460	4-port DB9 Male DTE Fan-out mini-cable. Length is 15 in (38.1 cm). For use with 4 port UltraPort and SpeedLE serial cards. This accessory is designed to be used with the Perle SPEED and UltraPort Serial Cards Universal PCI or PCI Express variants.	https://www.perle.com/products/product_detail.asp?a=4&c=14&i=04001460	Accessories: PCI Serial Cards

Part #	Description	Product Datasheet	Product Group
04001660	UltraPort4 PCI Serial Card - 4 x on-board RJ45 RS232 ports, Universal 3.3v/5v PCI serial card, 921.6Kbps/port wire speed, Enhanced modem support, ESD protection to 15kv. Alternative pin-out converters available.	https://www.perle.com/products/ultraport-serial-card.shtml	PCI Serial Cards
04001670	UltraPort8 PCI Serial Card - Card only, requires fan out cable or connector box for 8 x RS232 ports, Low profile Universal 3.3v/5v PCI serial card with standard bracket (low profile bracket included), 921.6Kbps/port wire speed, Enhanced modem support, ESD protection to 15kv	https://www.perle.com/products/ultraport-serial-card.shtml	PCI Serial Cards
04001680	UltraPort16 PCI Serial Card - Card only, requires fan out cables or connector box for 16 x RS232 ports, Universal 3.3v/5v PCI serial card with standard bracket, 921.6Kbps/port wire speed, Enhanced modem support, ESD protection to 15kv.	https://www.perle.com/products/ultraport-serial-card.shtml	PCI Serial Cards
04001710	RJ45 10pin to DB25 Male DTE Converter: Pack of 4. For use with UltraPort and SpeedLE serial cards. This accessory is designed to be used with the Perle SPEED and UltraPort Serial Cards Universal PCI or PCI Express variants.	https://www.perle.com/products/product_detail.asp?a=4&i=04001710&c=46	Accessories: PCI Serial Cards
04001720	RJ45 10pin to DB9 Male DTE Converter: Pack of 4. For use with UltraPort and SpeedLE serial cards. This accessory is designed to be used with the Perle SPEED and UltraPort Serial Cards Universal PCI or PCI Express variants.	https://www.perle.com/products/product_detail.asp?a=4&c=12&i=04001720	Accessories: PCI Serial Cards
04001760	8-port DB25 Female DTE Connector Box. For use with 8 and 16 port UltraPort and SpeedLE serial cards.	https://www.perle.com/products/product_detail.asp?a=4&c=12&j=04001760	Accessories: PCI Serial Cards
04001770	8-port RJ45 10pin Connector Box. For use with 8 and 16 port UltraPort and SpeedLE serial cards.	https://www.perle.com/products/product_detail.asp?a=4&c=12&i=04001770	Accessories: PCI Serial Cards
04001800	8-port DB25 Female DTE Fan-out cable. For use with 8 and 16 port UltraPort and SpeedLE serial cards.	https://www.perle.com/products/product_detail.asp?a=4&c=12&i=04001800	Accessories: PCI Serial Cards
04001810	8-port DB9 Male DTE Fan-out cable. For use with 8 and 16 port UltraPort and SpeedLE serial cards.	https://www.perle.com/products/product_detail.asp?a=4&c=12&i=04001810	Accessories: PCI Serial Cards
04001820	RJ45 10pin to DB25 Female DTE Converter: Pack of 4. For use with UltraPort and SpeedLE serial cards. This accessory is designed to be used with the Perle SPEED and UltraPort Serial Cards Universal PCI or PCI Express variants.	https://www.perle.com/products/product_detail.asp?a=4&c=12&i=04001820	Accessories: PCI Serial Cards
04001860	8-port DB9 Male DTE Connector Box. For use with 8 and 16 port UltraPort and SpeedLE serial cards.	https://www.perle.com/products/product_detail.asp?a=4&c=12&j=04001860	Accessories: PCI Serial Cards

Part #	Description	Product Datasheet	Product Group
04001870	UltraPort2 PCI Serial Card - 2 x -On-board DB9 male RS232 ports. Universal 3.3v/5v PCI serial card. 921.6Kbps/port wire speed. Enhanced modem support. ESD protection to 15kv.	https://www.perle.com/products/ultraport-serial-card.shtml	PCI Serial Cards
04001880	UltraPort8i PCI Serial Card - 8 x on-board RJ11/12 RS232 ports. Universal 3.3v/5v PCI serial card. 921Kbps/port wire speed. Enhanced modem support. ESD protection to 15kv	https://www.perle.com/products/ultraport-serial-card.shtml	PCI Serial Cards
04001920	UltraPort1 PCI Serial Card - 1x On-board DB9 male RS232 ports. Universal 3.3v/5v PCI serial card. 921Kbps/port wire speed. Enhanced modem support. ESD protection to 15kv	https://www.perle.com/products/ultraport-serial-card.shtml	PCI Serial Cards
04001930	UltraPort1 SI PCI Serial Card - 1x On-board DB9M software selectable RS232/422/485 serial port. Universal 3.3v/5v Low profile PCI serial card w/ standard bracket (Low profile bracket included). 921.6 Kbps on RS232, 3.6 Mbps on RS422/485. 25Kv ESD.	https://www.perle.com/products/ultraport-si-serial-card.shtml	PCI Serial Cards
04001940	UltraPort2 SI PCI Serial Card - 2x on-board DB9M software selectable RS232/RS422/RS485 serial ports. Universal 3.3v/5v PCI serial card w/ standard bracket. 921.6 Kbps on RS232, 3.6 Mbps on RS422/485. 25Kv ESD	https://www.perle.com/products/ultraport-si-serial-card.shtml	PCI Serial Cards
04001960	UltraPort8 SI PCI Serial Card - Card only, requires fan out cable or connector box for 8 x software selectable RS232/422/485 serial ports. Universal 3.3v/5v Low profile PCI serial card w/ standard bracket (Low profile bracket include). 921.6 Kbps on RS232, 3.6 Mbps on RS422/485. 25Kv ESD	https://www.perle.com/products/ultraport-si-serial-card.shtml	PCI Serial Cards
04001970	UltraPort16 SIPCI Serial Card - Card only, requires fan out cables or connector boxes for 16 x software selectable RS232/422/485 serial ports. Universal 3.3v/5v PCI serial card w/ standard bracket. 921.6 Kbps on RS232, 3.6 Mbps on RS422/485. 25Kv ESD	https://www.perle.com/products/ultraport-si-serial-card.shtml	PCI Serial Cards
04002000	4 port DB25 Male DTE Fan-out cable. For use with For use with 4 port UltraPort and SpeedLE serial cards. This accessory is designed to be used with the Perle SPEED and UltraPort Serial Cards Universal PCI or PCI Express variants.	https://www.perle.com/products/product_detail.asp?a=4&c=12&i=04002000	Accessories: PCI Serial Cards
04002020	4-port DB9 Female DTE Connection Box. For use with 4 port UltraPort and SpeedLE serial cards. This accessory is designed to be used with the Perle SPEED and UltraPort Serial Cards Universal PCI or PCI Express variants.	https://www.perle.com/products/product_detail.asp?a=4&c=12&i=04002020	Accessories: PCI Serial Cards

Part #	Description	Product Datasheet	Product Group
04002030	UltraPort4 SI PCI Serial Card - Card only, requires fan out cable or connector box for 4 x software selectable RS232/422/485 serial ports. Universal 3.3v/5v Low profile PCI serial card w/ standard bracket (Low profile bracket include). 921.6 Kbps on RS232, 3.6 Mbps on RS422/485. 25Kv ESD	https://www.perle.com/products/ultraport-si-serial-card.shtml	PCI Serial Cards
04002040	UltraPort4 PCI Serial Card - Card only, requires fan out cable or connector box for 4 x RS232 ports. Low profile Universal 3.3v/5v PCI Serial card, with standard bracket (low profile bracket included). 921Kbps/port wire speed. Enhanced modem support. ESD protection to 15Kv.	https://www.perle.com/products/ultraport-serial-card.shtml	PCI Serial Cards
04002070	UltraPort8iPCI Serial Card Bulk Pack- Pack of 40 Cards. 8 x on-board RJ11/12 RS232 ports. Universal 3.3v/5v PCI serial card. 921Kbps/port wire speed. Enhanced modem support. ESD protection to 15kv	https://www.perle.com/products/ultraport-serial-card.shtml	PCI Serial Cards
04003000	UltraPort1 PCI Express Serial Card - 1 x on-board DB9M RS232 port. Low profile PCI Express 1-lane (x1) Serial card, with standard bracket (low profile bracket included). 921Kbps port speed. Enhanced modem support. ESD protection to 15kv	https://www.perle.com/products/ultraport-express-serial-card.shtml	PCI Serial Cards
04003010	UltraPort2 PCI Express Serial Card - 2 x on-board DB9M RS232 ports. Low profile PCI Express 1-lane (x1) Serial card, with standard bracket (low profile bracket included). 921Kbps port speed. Enhanced modem support. ESD protection to 15kv	https://www.perle.com/products/ultraport-express-serial-card.shtml	PCI Serial Cards
04003050	SPEED1 LE PCI Serial Card - 1 x on board DB9M RS232 port. Low profile Universal 3.3v/5v PCI Serial card, with standard bracket (low profile bracket included). 921.6Kbps, ESD protection to 15Kv	https://www.perle.com/products/pci-serial-port-cards/speed1le-1-port-serial-card.shtml	PCI Serial Cards
04003060	SPEED2 LE PCI Serial Card - 2 x on board DB9M RS232 ports. Low profile Universal 3.3v/5v PCI Serial card, with standard bracket (low profile bracket included). 921.6Kbps, ESD protection to 15Kv	https://www.perle.com/products/pci-serial-port-cards/speed2le-dual-port-serial-card.shtml	PCI Serial Cards
04003070	SPEED4 LE PCI Serial Card - 4 x on board RJ45 RS232 ports. Universal 3.3v/5v Standard height PCI Serial card. 921Kbps, ESD protection to 15Kv	https://www.perle.com/products/pci-serial-port-cards/speed4le-4-port-serial-card.shtml	PCI Serial Cards
04003080	SPEED4 LE PCI Serial Card - includes DB9 fan out cable w/ 4 x RS232 ports. Low profile Universal 3.3v/5v PCI Serial card with Standard bracket (low profile bracket included). 921Kbps, ESD protection to 15Kv.	https://www.perle.com/products/pci-serial-port-cards/speed4lehd-4-port-serial-card.shtml	PCI Serial Cards
04003140	SPEED1 LE PCI Express Serial Card - 1 x on-board DB9M RS232 port. Low profile PCI Express 1-lane (x1) Serial card, with standard bracket (low profile bracket included). 921Kbps port speed. ESD protection to 15kv	https://www.perle.com/products/pci-express-serial-port-cards/speed1le-express-1-port-serial-card.shtml	PCI Serial Cards

Part #	Description	Product Datasheet	Product Group
04003230	SPEED LE1P PCI Parallel Card - 1 x DB25 EPP/ECP parallel port. Low profile Universal 3.3v/5v PCI Card, with standard bracket (low profile bracket included)	https://www.perle.com/products/serial-parallel-pci-card/speedle1p-1-port-parallel-pci-card.shtml	PCI Parallel Cards
04003240	SPEED2 LE1P PCI Serial Card / Parallel Card - 2 x DB9M RS232 port and 1 x DB25 EPP/ECP parallel port. Low profile Universal 3.3v/5v PCI Card, with standard bracket (low profile bracket included)	https://www.perle.com/products/serial-parallel-pci-card/speed2le1p-2-port-serial-parallel-pci-card.shtml	PCI Parallel Cards
04003310	SPEED2 LE PCI Express Serial Card - 2 x on-board DB9M RS232 ports. Low profile PCI Express 1-lane (x1) Serial card with standard bracket (low profile bracket included). 921Kbps port speed. ESD protection to 15kv	https://www.perle.com/products/pci-express-serial-port-cards/speed2le-express-dual-port-serial-card.shtml	PCI Serial Cards
04003320	SPEED1 LE1P PCI Express Serial Card / Parallel Card - 1 x on-board DB9M RS232 port and 1 x DB25 EPP/ECP parallel port. Low profile PCI Express 1-lane (x1) card with standard bracket (low profile bracket included)	https://www.perle.com/products/pci-express-parallel-card/speed1le1p-express-1-port-serial-parallel-pci-express-card.shtml	PCI Parallel Cards
04003330	SPEED LE 1P PCI Express Parallel Card - 1 x on board DB25 EPP/ECP parallel port. Low profile PCI Express 1-lane (x1) parallel card with standard bracket (low profile bracket included)	https://www.perle.com/products/pci-express-parallel-card/speedle1p-express-1-port-parallel-pci-express-card.shtml	PCI Parallel Cards
04005120	3 meter RJ45 to RJ45 CAT5 Straight-thru cable. #1100360-10. This accessory is designed to be used with the IOLAN range of Terminal Servers and Device Servers.	https://www.perle.com/support_services/cabling/documents/3m_cbl-straightthru.shtml	Accessories: Serial Servers
04005130	3 meter RJ45 to RJ45 CAT5 Rolled (crossover) cable #1100370-10 for IOLAN with Cisco pinout. This accessory is designed to be used with the IOLAN range of Terminal Servers and Device Servers.	https://www.perle.com/support_services/cabling/documents/3m_cbl-rolledc.shtml	Accessories: Serial Servers
04006902	IOLAN+16 Rack Terminal Server: 1U Rack mountable terminal/serial server, 10/100 Network, 16 x RS422 serial ports, RJ45 connectors. EU power adapter included.	https://www.perle.com/products/iolan+-terminal-server.shtml	Serial Terminal Server: IOLAN+
04006905	IOLAN+16 Rack Terminal Server: 1U Rack mountable terminal/serial server, 10/100 Network, 16 x RS422 serial ports, RJ45 connectors. South Africa / India power adapter included.	https://www.perle.com/products/iolan+-terminal-server.shtml	Serial Terminal Server: IOLAN+
04006930	RJ45-DB25 converter for IOLAN to Modem DB25 Male. This accessory is designed to be used with the IOLAN range of Terminal Servers and Device Servers.	https://www.perle.com/support_services/cabling/documents/iolan%20-%20rj45%20cable%20diagrams.doc	Accessories: Serial Servers
04006931	RJ45-DB25 converter for IOLAN to Modem DB25 Male. This accessory is designed to be used with the IOLAN range of Terminal Servers and Device Servers.	https://www.perle.com/support_services/cabling/documents/iolan%20-%20rj45%20cable%20diagrams.doc	Accessories: Serial Servers

Part #	Description	Product Datasheet	Product Group
04006932	RJ45-DB25 converter for IOLAN to Modem DB25 Male. This accessory is designed to be used with the IOLAN range of Terminal Servers and Device Servers.	https://www.perle.com/support_services/cabling/documents/iolan%20-%20rj45%20cable%20diagrams.doc	Accessories: Serial Servers
04006933	RJ45-DB25 converter for IOLAN to Modem DB25 Male. This accessory is designed to be used with the IOLAN range of Terminal Servers and Device Servers.	https://www.perle.com/support_services/cabling/documents/iolan%20-%20rj45%20cable%20diagrams.doc	Accessories: Serial Servers
04006950	IOLAN 8 - wire RJ-45F to DB-25F crossover (DTE) adapter for console port #1100220-10. This accessory is designed to be used with the IOLAN range of Terminal Servers and Device Servers.	https://www.perle.com/support_services/cabling/documents/dba0010.shtml	Accessories: Serial Servers
04006960	IOLAN 8 - wire, RJ-45F to DB-25M crossover (DTE) adapter for console ports. #1100230-10. This accessory is designed to be used with the IOLAN range of Terminal Servers and Device Servers.	https://www.perle.com/support_services/cabling/documents/dba0011.shtml	Accessories: Serial Servers
04006970	IOLAN RJ45F to DB-9F (DTE) crossover adapter. #1100240-10. This accessory is designed to be used with the IOLAN range of Terminal Servers and Device Servers.	https://www.perle.com/support_services/cabling/documents/dba0020.shtml	Accessories: Serial Servers
04006980	IOLAN RJ-45F to DB-9M crossover (DTE) adapter for console ports. #1100250-10. This accessory is designed to be used with the IOLAN range of Terminal Servers and Device Servers.	https://www.perle.com/support_services/cabling/documents/dba0021.shtml	Accessories: Serial Servers
04006990	IOLAN RJ-45F to DB-25M straight-thru (DCE) adapter for modems. #1100260-10. This accessory is designed to be used with the IOLAN range of Terminal Servers and Device Servers.	https://www.perle.com/support_services/cabling/documents/dba0013.shtml	Accessories: Serial Servers
04007000	IOLAN Starter Kit Includes: (1) RJ-45 to DB-25 DTE Male adapter, (1) RJ-45 to DB-25 DCE Male adapter, (1) RJ-45 to DB-25 DTE Female adapter, (1) RJ-45 to DB-9 Male DTE adapter, (1) RJ-45 to DB-9 Female DTE adapter and (1)3M-RJ45M-RJ45M 8-wire Sun-Cisco modular cable. This accessory is designed to be used with the IOLAN range of Terminal Servers and Device Servers.	https://www.perle.com/products/product_detail.asp?a=4&i=04007000&c=74	Accessories: Serial Servers
04007010	DBA0010C - RJ-45F to DB-25F crossover (DTE) adapter for IOLAN with Cisco pinout. #1100270-10. This accessory is designed to be used with the IOLAN SCSC Console Server.	https://www.perle.com/support_services/cabling/documents/dba0010c.shtml	Accessories: Serial Servers
04007020	DBA0011C - RJ-45F to DB-25M crossover (DTE) adapter for IOLAN with Cisco pinout. #1100280-10. This accessory is designed to be used with the IOLAN SCSC Console Server.	https://www.perle.com/support_services/cabling/documents/dba0011c.shtml	Accessories: Serial Servers

Part #	Description	Product Datasheet	Product Group
04007030	DBA0013C - RJ-45F to DB-25M straight-thru (DCE) adapter for modems on IOLAN with Cisco pinout. #1100290-10. This accessory is designed to be used with the IOLAN SCSC Console Server.	https://www.perle.com/support_services/cabling/documents/dba0013c.shtml	Accessories: Serial Servers
04007040	DBA0020C - RJ-45F to DB-9F crossover (DTE) adapter for IOLAN with Cisco pinout. #1100300-10. This accessory is designed to be used with the IOLAN SCSC Console Server.	https://www.perle.com/support_services/cabling/documents/dba0020c.shtml	Accessories: Serial Servers
04007050	DBA0021C - RJ-45F to DB-9M crossover (DTE) adapter for IOLAN with Cisco pinout. #1100310-10. This accessory is designed to be used with the IOLAN SCSC Console Server.	https://www.perle.com/support_services/cabling/documents/dba0021c.shtml	Accessories: Serial Servers
04007060	DBA0031C - RJ-45m to RJ-45F Cisco crossover adapter for IOLAN with Cisco pinout. #1100320-10. This accessory is designed to be used with the IOLAN SCSC Console Server.	https://www.perle.com/support_services/cabling/documents/dba0031c.shtml	Accessories: Serial Servers
04007070	IOLAN C Model Wiring Starter Kit for IOLAN with Cisco pinout -- Kit Includes: (1) RJ-45 to DB-25 DTE Male adapter, (1) RJ-45 to DB-25 DCE Male adapter, (1) RJ-45 to DB-25 DTE Female adapter, (1) RJ-45 to DB-9Male DTE adapter, (1) RJ-45 to DB-9 Female DTE adapter and (1) RJ45M-RJ45F Cisco crossover adapter. This accessory is designed to be used with the IOLAN SCSC Console Server.	https://www.perle.com/products/product_detail.asp?a=4&i=04007070&c=70	Accessories: Serial Servers
04007200	RJ-45F to DB-9M straight-thru (DCE) adapter for modems. #1100340-10. This accessory is designed to be used with the IOLAN range of Terminal Servers and Device Servers.	https://www.perle.com/support_services/cabling/documents/dba0023.shtml	Accessories: Serial Servers
04007210	DBA0023C - RJ-45F to DB-9M straight-thru (DCE) adapter for IOLAN with Cisco pinout. This accessory is designed to be used with the IOLAN SCSC Console Server.	https://www.perle.com/support_services/cabling/documents/dba0023c.shtml	Accessories: Serial Servers
04007220	DBA0400: IOLAN SCG Console RJ45F to DB9M adapter	https://www.perle.com/support_services/cabling/documents/dba0040.shtml	Accessories: IOLAN SCG
04007230	DBA0041: IOLAN SCG Console RJ45F to DB25M adapter	https://www.perle.com/support_services/cabling/documents/dba0041.shtml	Accessories: IOLAN SCG
04030002	IOLAN DS1 Serial Device Server: 1 x DB25M connector with software selectable RS232/422/485 interface, 10/100 Ethernet, IPv6, COM port redirector, 15kv ESD, EU power adapter included	https://www.perle.com/products/iolan-ds-terminal-server.shtml	Serial Device Server: IOLAN DS
04030010	IOLAN DS1 Serial Device Server (BULK PACK): 1 x DB25M connector with software selectable RS232/422/485 interface, 10/100 Ethernet, IPv6, COM port redirector, 15kv ESD, pack of 20 units, no AC adapters, 1 CD included	https://www.perle.com/products/iolan-ds-terminal-server.shtml	Serial Device Server: IOLAN DS

Part #	Description	Product Datasheet	Product Group
04030022	IOLAN SDS1 Secure Device Server: 1 x DB25M connector with software selectable RS232/422/485 interface, 10/100 Ethernet, advanced data encryption, user authentication and event management security features included, IPv6, COM port redirector, 15kv ESD, EU power adapter included	https://www.perle.com/products/iolan-sds-terminal-server.shtml	Serial Device Server: IOLAN SDS
04030030	DIN Rail Mounting Kit for 1 or 2 port IOLAN DS, TS, SDS	https://www.perle.com/products/product_detail.asp?a=4&i=04030030&c=9	Accessories: Mounting Kits
04030040	IOLAN SDS1 Secure Device Server (BULK PACK): 1 x DB25M connector bulk pack of 20units, no power cords, 1 CD included software selectable RS232/422/485 interface, 10/100 Ethernet, advanced data encryption, user authentication and event management security	https://www.perle.com/products/iolan-sds-terminal-server.shtml	Serial Device Server: IOLAN SDS
04030070	RJ45-RJ45 IOLAN DS to Cisco 3m Cable. This accessory is designed to be used with the IOLAN range of Terminal Servers and Device Servers.	https://www.perle.com/support_services/cabling/documents/dba0031.shtml	Accessories: Serial Servers
04030080	IOLAN-RJ45M to RJ45F Cisco crossover adaptor. #1100219-10. This accessory is designed to be used with the IOLAN range of Terminal Servers and Device Servers.	https://www.perle.com/support_services/cabling/documents/dba0031.shtml	Accessories: Serial Servers
04030102	IOLAN SDS2 Secure Device Server: 2 x RJ45 connectors with software selectable RS232/422/485 interfaces, 10/100 Ethernet, advanced data encryption, user authentication and event management security features included, IPv6, COM port redirector, 15kv ESD, EU power adapter included	https://www.perle.com/products/iolan-sds-terminal-server.shtml	Serial Device Server: IOLAN SDS
04030112	IOLAN DS1 Serial Device Server: 1 x RJ45 10 pin connector with software selectable RS232/422/485 interface, 10/100 Ethernet, IPv6, COM port redirector, 15kv ESD, EU power adapter included	https://www.perle.com/products/iolan-ds-terminal-server.shtml	Serial Device Server: IOLAN DS
04030122	IOLAN DS1 Serial Device Server: 1 x DB9M connector with software selectable, RS232/422/485 interface, 10/100 Ethernet, IPv6, COM port redirector, 15kv ESD, EU power adapter included	https://www.perle.com/products/iolan-ds-terminal-server.shtml	Serial Device Server: IOLAN DS
04030132	IOLAN DS1 Serial Device Server: 1 x DB25F connector with software selectable RS232/422/485 interface, 10/100 Ethernet, IPv6, COM port redirector, 15kv ESD, EU power adapter included	https://www.perle.com/products/iolan-ds-terminal-server.shtml	Serial Device Server: IOLAN DS
04030142	IOLAN SDS1 Secure Device Server: 1 x RJ45 10 pin connector with software selectable Rs232/422/485 interface, 10/100 Ethernet advanced data encryption, user authentication and event management security features included, IPv6, COM port redirector, 15kv ESD, EU power adapter included	https://www.perle.com/products/iolan-sds-terminal-server.shtml	Serial Device Server: IOLAN SDS

Part #	Description	Product Datasheet	Product Group
04030152	IOLAN SDS1 Secure Device Server: 1 x DB9M connector with software selectable RS232/422/485 interface, 10/100 Ethernet advanced data encryption, user authentication and event management security features included, IPv6, COM port redirector, 15kv ESD, EU power adapter included	https://www.perle.com/products/iolan-sds-terminal-server.shtml	Serial Device Server: IOLAN SDS
04030162	IOLAN SDS1 Secure Device Server: 1 x DB25F connector with software selectable RS232/422/485 interface, 10/100 Ethernet advanced data encryption, user authentication and event management security features included, IPv6, COM port redirector, 15kv ESD, EU power adapter included	https://www.perle.com/products/iolan-sds-terminal-server.shtml	Serial Device Server: IOLAN SDS
04030170	IOLAN SDS1 PoE Secure Serial Device Server: 1 x RJ45 10 pin connector with software selectable RS232/422/485 interface, 802.3af Power over Ethernet (PoE) compliant, 10/100 Ethernet advanced data encryption, user authentication and event management security features included, IPv6, COM port redirector, 15kv ESD	https://www.perle.com/products/iolan-sdsp-terminal-server.shtml	Serial Device Server: IOLAN SDS P
04030180	IOLAN SDS2 PoE Secure Device Server: 2 x RJ45 10 pin connector with software selectable RS232/422/485 interface, 802.3af Power over Ethernet (PoE) compliant, 10/100 Ethernet, advanced data encryption, user authentication and event management security features included, IPv6, COM port redirector, 15kv ESD	https://www.perle.com/products/iolan-sdsp-terminal-server.shtml	Serial Device Server: IOLAN SDS P
04030202	IOLAN SCS32 DAC Secure Console Server: 32 x RJ45 RS232 ports with IOLAN pinout, Dual AC power EIA232 interface, Dual 10/100/1000Base-T Ethernet, PCI slot for V.92 modem card, advanced data encryption, user authentication and event management security features IPv6, COM port redirector, 15kv ESD. EU power adapter included.	https://www.perle.com/products/product_detail.asp?a=1&i=6	Serial Console Server: IOLAN SCS
04030212	IOLAN SCS48 DAC Secure Console Server: 48 x RJ45 RS232 ports with IOLAN pinout, Dual AC power, EIA232interface, Dual 10/100/1000Base-T Ethernet, PCI slot for V.92 modem card, advanced data encryption, user authentication and event management security features included, IPv6, COM port redirector, 15kv ESD. EU power adapter included.	https://www.perle.com/products/product_detail.asp?a=1&i=6	Serial Console Server: IOLAN SCS
04030222	IOLAN SCS8 Secure Console Server: 8 x RJ45 RS232 ports with IOLAN pinout, EIA232 interface, Dual 10/100/1000Base-T Ethernet, PCI slot for V.92 modem card advanced data encryption, user authentication and event management security features included, IPv6, COM port redirector, 15kv ESD. EU power adapter included.	https://www.perle.com/products/product_detail.asp?a=1&i=6	Serial Console Server: IOLAN SCS

Part #	Description	Product Datasheet	Product Group
04030232	IOLAN SCS8 DAC Secure Console Server: 8 x RJ45 RS232 ports with IOLAN pinout, Dual AC power, EIA232 interface, Dual 10/100/1000Base-T Ethernet, PCI slot for V.92 modem card, advanced data encryption, user authentication and event management security features included, IPv6, COM port redirector, 15kv ESD. EU power adapter included.	https://www.perle.com/products/product_detail.asp?a=1&i=6	Serial Console Server: IOLAN SCS
04030242	IOLAN SCS16 Secure Console Server: 16 x RJ45 RS232 ports with IOLAN pinout, EIA232 interface, Dual 10/100/1000Base-T Ethernet, PCI slot for V.92 modem card, advanced data encryption, user authentication and event management security features included, IPv6, COM port redirector, 15kv ESD. EU power adapter included.	https://www.perle.com/products/product_detail.asp?a=1&i=6	Serial Console Server: IOLAN SCS
04030252	IOLAN SCS16 DAC Secure Console Server: 16 x RJ45 RS232 ports with IOLAN pinout, Dual AC power EIA232 interface, Dual 10/100/1000Base-T Ethernet, PCI slot for V.92 modem card, advanced data encryption, user authentication and event management security features included, IPv6, COM port redirector, 15kv ESD. EU power adapter included.	https://www.perle.com/products/product_detail.asp?a=1&i=6	Serial Console Server: IOLAN SCS
04030270	IOLAN SCS32 DC Secure Console Server: 32 x RJ45 RS232 ports with IOLAN pinout, 48VDC power, EIA232 interface, Dual 10/100/1000Base-T Ethernet, PCI slot for V.92 modem card, advanced data encryption, user authentication and event management security features included, IPv6, COM port redirector, 15kv ESD.	https://www.perle.com/products/product_detail.asp?a=1&i=6	Serial Console Server: IOLAN SCS
04030282	IOLAN SCS32 Secure Console Server: 32 x RJ45 RS232 ports with IOLAN pinout, EIA232 interface, Dual 10/100/1000Base-T Ethernet, PCI slot for V.92 modem card, advanced data encryption, user authentication and event management security features included, IPv6, COM port redirector, 15kv ESD. EU power adapter included.	https://www.perle.com/products/product_detail.asp?a=1&i=6	Serial Console Server: IOLAN SCS
04030292	IOLAN SCS48 Secure Console Server: 48 x RJ45 RS232 ports with IOLAN pinout, EIA232 interface, Dual 10/100/1000Base-T Ethernet, PCI slot for V.92 modem card, advanced data encryption, user authentication and event management security features included, IPv6, COM port redirector, 15kv ESD. EU power adapter included.	https://www.perle.com/products/product_detail.asp?a=1&i=6	Serial Console Server: IOLAN SCS
04030302	IOLAN SDS4 Secure Device Server: 4 x RJ45 connectors with software selectable RS232/422/485 interfaces, 10/100 Ethernet, advanced data encryption, user authentication and event management security features included, IPv6, COM port redirector, 15kv ESD, EU power adapter included	https://www.perle.com/products/iolan-sds-terminal-server.shtml	Serial Device Server: IOLAN SDS

Part #	Description	Product Datasheet	Product Group
04030312	IOLAN SDS8 Secure Device Server: 8 x RJ45 connectors with software selectable EIA232/422/485 interface, 1U rack mount, 10/100/1000Base-T Ethernet, advanced data encryption, user authentication and event management security features included, IPv6, COM port redirector, 15kv ESD. EU power adapter included.	https://www.perle.com/products/iolan-sds-rack-terminal-server.shtml	Serial Device Server: IOLAN SDS
04030322	IOLAN SDS16 Secure Device Server: 16 x RJ45 connector, 1U rack mount, software selectable EIA232/422/485 interface, 10/100/1000Base-T Ethernet advanced data encryption, user authentication and event management security features included, IPv6, COM port redirector, 15kv ESD. EU power adapter included.	https://www.perle.com/products/iolan-sds-rack-terminal-server.shtml	Serial Device Server: IOLAN SDS
04030340	IOLAN SDS4 PoE Secure Device Server: 4 x RJ45 10 pin connector with software selectable RS232/422/485 interfaces, 802.3af Power over Ethernet (PoE) compliant, 10/100 Ethernet, advanced data encryption, user authentication and event management security features included, IPv6, COM port redirector, 15kv ESD	https://www.perle.com/products/iolan-sdsp-terminal-server.shtml	Serial Device Server: IOLAN SDS P
04030350	IOLAN STS4 PoE Secure Terminal Server: 4 x RJ45 connectors with RS232 interface, 10/100 Ethernet, 802.3af Power over Ethernet (PoE) compliant, desktop/wall mount, advanced data encryption, user authentication and event management security features included, IPv6, COM port redirector, 15kv ESD	https://www.perle.com/products/4-port-terminal-server-poe.shtml	Serial Terminal Server: IOLAN STS P
04030370	IOLAN SDS4 HL Secure Device Server: Class 1 Division 2 Certified, Conformal Coating, 4 X RJ45 connectors with software selectable RS232/422/485 interfaces, 10/100 Ethernet, advanced data encryption, user authentication and event management security features included, IPv6, COM port redirector, 15kv ESD, Extended temperature	https://www.perle.com/products/iolan-sdshl-terminal-server.shtml	Serial Device Server: IOLAN SDS HL
04030390	IOLAN STS4 DC Secure Terminal Server: 4 x RJ45 connector, 10/100/1000 Ethernet, 1U rack mount, 48VDC, RS232 interface, advanced data encryption, user authentication and event management security features included, IPv6, COM port redirector, 15kv ESD	https://www.perle.com/products/terminal-servers-48vdc.shtml	Serial Terminal Server: IOLAN STS DC
04030402	IOLAN STS4 Secure Terminal Server: 4 x RJ45 connector, 10/100/1000 Ethernet, 1U rack mount, RS232 interface, advanced data encryption, user authentication and event management security features included, IPv6, COM port redirector, 15kv ESD, EU power adapter included	https://www.perle.com/products/iolan-sts-terminal-server.shtml	Serial Terminal Server: IOLAN STS

Part #	Description	Product Datasheet	Product Group
04030412	IOLAN STS8 Secure Terminal Server: 8 x RJ45 connector, 10/100/1000 Ethernet 1U rack mount, RS232 interface, advanced data encryption user authentication and event management security features included, IPv6, COM port redirector, 15kv ESD, EU power adapter included	https://www.perle.com/products/iolan-sts-terminal-server.shtml	Serial Terminal Server: IOLAN STS
04030420	IOLAN STS8 DC Secure Terminal Server: 8 x RJ45 connector, 10/100/1000 Ethernet, 1U rack mount, 48VDC power, RS232 interface, advanced data encryption, user authentication and event management security features included, IPv6, COM port redirector, 15kv ESD	https://www.perle.com/products/terminal-servers-48vdc.shtml	Serial Terminal Server: IOLAN STS DC
04030432	IOLAN STS8 D Secure Terminal Server: 8 x RJ45 connector with RS232 interface, 10/100 Ethernet, desktop/wall mount, advanced data encryption, user authentication and event management security features included, IPv6, COM port redirector, 15kv ESD, EU power adapter included	https://www.perle.com/products/iolan-sts-d-terminal-server.shtml	Serial Terminal Server: IOLAN STS D
04030442	IOLAN STS16 Secure Terminal Server: 16 x RJ45 connector, EIA232 interface, 10/100/1000Base-T Ethernet 1U rack mount, advanced data encryption user authentication and event management security features included, IPv6, COM port redirector, 15kv ESD. EU power adapter included.	https://www.perle.com/products/iolan-sts-terminal-server.shtml	Serial Terminal Server: IOLAN STS
04030450	IOLAN STS16 DC Secure Terminal Server: 16 x RJ45 connector, EIA232 interface, 10/100/1000Base-T Ethernet 1U rack mount, 48VDC power, advanced data encryption, user authentication and event management security features included, IPv6, COM port redirector, 15kv ESD.	https://www.perle.com/products/terminal-servers-48vdc.shtml	Serial Terminal Server: IOLAN STS DC
04030462	IOLAN STS24 Secure Terminal Server: 24 x RJ45 connector, EIA232 interface, 10/100/1000Base-T Ethernet 1U rack mount, advanced data encryption user authentication and event management security features included, IPv6, COM port redirector, 15kv ESD. EU power adapter included.	https://www.perle.com/products/iolan-sts-terminal-server.shtml	Serial Terminal Server: IOLAN STS
04030610	IOLAN SDS1T Secure Device Server: 1 x DB9M connector with software selectable RS232/422/485 interface, Extended Temperature, 10/100 Ethernet, advanced data encryption, user authentication and event management security features included, IPv6, COM port redirector, 15kv ESD, pigtail power connector included	https://www.perle.com/products/iolan-sdst-terminal-server.shtml	Serial Device Server: IOLAN SDS T

Part #	Description	Product Datasheet	Product Group
04030620	IOLAN SDS2T Secure Device Server: 2 X RJ45 connectors with software selectable RS232/422/485 interfaces, Extended temperature, 10/100 Ethernet, advanced data encryption, user authentication and event management security features included, IPv6, COM port redirector, 15kv ESD, pigtail power connector included	https://www.perle.com/products/iolan-sdst-terminal-server.shtml	Serial Device Server: IOLAN SDS T
04030630	IOLAN SDS4T Secure Device Server: 4 X RJ45 connectors with software selectable RS232/422/485 interfaces, Extended temperature, 10/100 Ethernet, advanced data encryption, user authentication and event management security features included, IPv6, COM port redirector, 15kv ESD, pigtail power connector included	https://www.perle.com/products/iolan-sdst-terminal-server.shtml	Serial Device Server: IOLAN SDS T
04030642	IOLAN TS2 Terminal Server: 2 x RJ45 connectors with RS232 interface, 10/100 Ethernet, desktop/wall mount, IPv6, COM redirector, 15kv ESD, EU power adapter included	https://www.perle.com/products/iolan-ds-terminal-server.shtml	Serial Terminal Server: IOLAN TS
04030672	Extended Temperature EU power adapter for 12 volt Extended Temperature Terminal Servers, Media Converters and Ethernet Extenders	https://www.perle.com/products/product_detail.asp?a=4&i=04030672&c=572	Power Supplies
04030742	IOLAN SCS48C Secure Console Server: 48 x RJ45 RS232 ports with Cisco pinout, EIA232 interface, Dual 10/100/1000Base-T Ethernet, PCI slot for V.92 modem card, advanced data encryption, user authentication and event management security features included, IPv6, COM port redirector, 15kv ESD. EU power adapter included.	https://www.perle.com/products/iolan-scs-terminal-server.shtml	Serial Console Server: IOLAN SCSC
04030752	IOLAN SCS48C DAC Secure Console Server: 48 x RJ45 RS232 ports with Cisco pinout, Dual AC power, EIA232 interface, Dual 10/100/1000Base-T Ethernet, PCI slot for V.92 modem card, advanced data encryption, user authentication and event management security features included, IPv6, COM port redirector, 15kv ESD. EU power adapter included.	https://www.perle.com/products/iolan-scs-terminal-server.shtml	Serial Console Server: IOLAN SCSC
04030762	IOLAN SCS32C Secure Console Server: 32 x RJ45 RS232 ports with Cisco pinout, EIA232 interface, Dual 10/100/1000Base-T Ethernet, PCI slot for V.92 modem card, advanced data encryption, user authentication and event management security features included, IPv6, COM port redirector, 15kv ESD. EU power adapter included.	https://www.perle.com/products/iolan-scs-terminal-server.shtml	Serial Console Server: IOLAN SCSC
04030772	IOLAN SCS32C DAC Secure Console Server: 32 x RJ45 RS232 ports with Cisco pinout, Dual AC power, EIA232 interface, Dual 10/100/1000Base-T Ethernet, PCI slot for V.92 modem card, advanced data encryption, user authentication and event management security features included, IPv6, COM port redirector, 15kv ESD. EU power adapter included.	https://www.perle.com/products/iolan-scs-terminal-server.shtml	Serial Console Server: IOLAN SCSC

Part #	Description	Product Datasheet	Product Group
04030782	IOLAN SCS16C Secure Console Server: 16 x RJ45 RS232 ports with Cisco pinout, EIA232 interface, Dual 10/100/1000Base-T Ethernet, PCI slot for V.92 modem card, advanced data encryption, user authentication and event management security features included, IPv6, COM port redirector, 15kv ESD. EU power adapter included.	https://www.perle.com/products/iolan-scs-terminal-server.shtml	Serial Console Server: IOLAN SCSC
04030792	IOLAN SCS16C DAC Secure Console Server: 16 x RJ45 RS232 ports with Cisco pinout, Dual AC power, EIA232 interface, Dual 10/100/1000Base-T Ethernet, PCI slot for V.92 modem card, advanced data encryption, user authentication and event management security features included, IPv6, COM port redirector, 15kv ESD. EU power adapter included.	https://www.perle.com/products/iolan-scs-terminal-server.shtml	Serial Console Server: IOLAN SCSC
04030802	IOLAN SDS1 M Secure Device Server: 1 x RJ45 connector with software selectable RS232/422/485 interface, one integrated V.92/V.90 data modem, 10/100 Ethernet, advanced data encryption, user authentication and event management security features included, IPv6, COM port redirector, 15kv ESD, EU power adapter included	https://www.perle.com/products/iolan-sdsm-terminal-server.shtml	Serial Device Server: IOLAN SDS M
04030832	IOLAN STS4 D Secure Terminal Server: 4 x RJ45 connectors with RS232 interface, 10/100 Ethernet, desktop/wall mount, advanced data encryption, user authentication and event management security features included, IPv6, COM port redirector, 15kv ESD, EU power adapter included	https://www.perle.com/products/iolan-sts-d-terminal-server.shtml	Serial Terminal Server: IOLAN STS D
04030840	DIN Rail Mounting Kit for 4 & 8 port IOLAN SDS/STS wall mount models, all Stand-Alone Media Converters and all Stand-alone Ethernet Extenders. Two of these brackets are required for the 8 port STS8-D model.	https://www.perle.com/products/product_detail.asp?a=4&i=04030840&c=71	Accessories: Mounting Kits
04030852	Internal V.92 Modem Card for IOLAN SCS rack series - EU version	https://www.perle.com/products/product_detail.asp?a=4&i=04030852&c=70	Accessories: Serial Console Servers
04030860	IOLAN SCS16 DC Secure Console Server: 16 x RJ45 RS232 ports with IOLAN pinout, 48VDC power, EIA232 interface, Dual 10/100/1000Base-T Ethernet, PCI slot for V.92 modem card, advanced data encryption, user authentication and event management security features included, IPv6, COM port redirector, 15kv ESD.	https://www.perle.com/products/product_detail.asp?a=1&i=6	Serial Console Server: IOLAN SCS
04030870	IOLAN SCS8 DC Secure Console Server: 8 x RJ45 RS232 ports with IOLAN pinout, 48VDC power, EIA232 interface, Dual 10/100/1000Base-T Ethernet, PCI slot for V.92 modem card, advanced data encryption, user authentication and event management security features included, IPv6, COM port redirector, 15kv ESD.	https://www.perle.com/products/product_detail.asp?a=1&i=6	Serial Console Server: IOLAN SCS

Part #	Description	Product Datasheet	Product Group
04030902	IOLAN SCS8C Secure Console Server: 8 x RJ45 RS232 ports with Cisco pinout, EIA232 interface, Dual 10/100/1000Base-T Ethernet, PCI slot for V.92 modem card, advanced data encryption, user authentication and event management security features included, IPv6, COM port redirector, 15kv ESD. EU power adapter included.	https://www.perle.com/products/iolan-scs-terminal-server.shtml	Serial Console Server: IOLAN SCSC
04030912	IOLAN SCS8C DAC Secure Console Server: 8 x RJ45 RS232 ports with Cisco pinout, Dual AC power, EIA232 interface, Dual 10/100/1000Base-T Ethernet, PCI slot for V.92 modem card, advanced data encryption, user authentication and event management security features included, IPv6, COM port redirector, 15kv ESD. EU power adapter included.	https://www.perle.com/products/iolan-scs-terminal-server.shtml	Serial Console Server: IOLAN SCSC
04030920	IOLAN SCS8C DC Secure Console Server: 8 x RJ45 RS232 ports with Cisco pinout, 48 VDC power, EIA232 interface, Dual 10/100/1000Base-T Ethernet, PCI slot for V.92 modem card, advanced data encryption, user authentication and event management security features included, IPv6, COM port redirector, 15kv ESD.	https://www.perle.com/products/iolan-scs-terminal-server.shtml	Serial Console Server: IOLAN SCSC
04030930	IOLAN SCS16C DC Secure Console Server: 16 x RJ45 RS232 ports with Cisco pinout, 48VDC power, EIA232 interface, Dual 10/100/1000Base-T Ethernet, PCI slot for modem or wireless card, advanced data encryption, user authentication and event management security features included, IPv6, COM port redirector, 15kv ESD. AC power adapter included.	https://www.perle.com/products/iolan-scs-terminal-server.shtml	Serial Console Server: IOLAN SCSC DC
04030940	IOLAN SCS32C DC Secure Console Server: 32 x RJ45 RS232 ports with Cisco pinout, 48 VDC power, EIA232 interface, Dual 10/100/1000Base-T Ethernet, PCI slot for V.92 modem card, advanced data encryption, user authentication and event management security features included, IPv6, COM port redirector, 15kv ESD.	https://www.perle.com/products/iolan-scs-terminal-server.shtml	Serial Console Server: IOLAN SCSC DC
04030960	IOLAN DS1T Device Server: 1 x DB9M connector, Extended Temperature, pigtail power connector included, software selectable, EIA-232/422/485 interface, 10/100 Ethernet, IPv6, COM port redirector, 15kv ESD.	https://www.perle.com/products/iolan-ds1t-terminal-server.shtml	Serial Device Server: IOLAN DS
04030970	IOLAN SCS48C DC Secure Console Server: 48 x RJ45 RS232 ports with Cisco pinout, 48v DC power, EIA232 interface, Dual 10/100/1000Base-T Ethernet, PCI slot for modem or wireless card, advanced data encryption, user authentication and event management security features included, IPv6, COM port redirector, 15kv ESD.	https://www.perle.com/products/iolan-scs-terminal-server.shtml	Serial Console Server: IOLAN SCSC DC

Part #	Description	Product Datasheet	Product Group
04030980	IOLAN DS1T Serial Device Server: 1 x DB9M connector with software selectable RS232/422/485 interface, Extended Temperature, terminal block power connector, 10/100 Ethernet, IPv6, COM port redirector, 15kv ESD	https://www.perle.com/products/iolan-ds1t-terminal-server.shtml	Serial Device Server: IOLAN DS
04031000	IOLAN DS1 D4 Ethernet I/O Device Server: four digital I/O, 1 x DB9M connector, software selectable EIA-232/422/485 interface, 10/100 Ethernet, IPv6, COM port redirector, 15kv ESD. Terminal block connectors for power and I/O.	https://www.perle.com/products/ethernet-io-device-server.shtml	Serial I/O Device Server: IOLAN DS
04031010	IOLAN DS1 D2R2 Ethernet I/O Device Server: two digital I/O and two relay outputs, 1 x DB9M connector, software selectable EIA-232/422/485 interface, 10/100 Ethernet, IPv6, COM port redirector, 15kv ESD. Terminal block connectors for power and I/O.	https://www.perle.com/products/ethernet-io-device-server.shtml	Serial I/O Device Server: IOLAN DS
04031020	IOLAN DS1 A4 Ethernet I/O Device Server: four analog inputs, 1 x DB9M connector, software selectable EIA-232/422/485 interface, 10/100 Ethernet, IPv6, COM port redirector, 15kv ESD. Terminal block connectors for power and I/O.	https://www.perle.com/products/ethernet-io-device-server.shtml	Serial I/O Device Server: IOLAN DS
04031030	IOLAN DS1 T4 Ethernet I/O Device Server: four thermocouple/RTD inputs, 1 x DB9M connector, software selectable EIA-232/422/485 interface, 10/100 Ethernet, IPv6, COM port redirector, 15kv ESD. Terminal block connectors for power and I/O.	https://www.perle.com/products/ethernet-io-device-server.shtml	Serial I/O Device Server: IOLAN DS
04031040	IOLAN DS1 A4R2 Ethernet I/O Device Server: four analog inputs and two relay outputs, 1 x DB9M connector, software selectable EIA-232/422/485 interface, 10/100 Ethernet, IPv6, COM port redirector, 15kv ESD. Terminal block connectors for power and I/O.	https://www.perle.com/products/ethernet-io-device-server.shtml	Serial I/O Device Server: IOLAN DS
04031050	IOLAN DS1 A4D2 Ethernet I/O Device Server: four analog inputs and two digital I/O, 1 x DB9M connector, software selectable EIA-232/422/485 interface, 10/100 Ethernet, IPv6, COM port redirector, 15kv ESD. Terminal block connectors for power and I/O.	https://www.perle.com/products/ethernet-io-device-server.shtml	Serial I/O Device Server: IOLAN DS
04031060	IOLAN SDS1 TD4 Secure Ethernet I/O Device Server: four digital I/O, 1 x DB9M connector, software selectable EIA-232/422/485 interface, 10/100 Ethernet advanced data encryption, user authentication and event management security features included, IPv6, COM port redirector, 15kv ESD. Terminal block connectors for power and I/O. Extended Temperature	https://www.perle.com/products/ethernet-io-secure-device-server.shtml	Serial I/O Device Server: IOLAN SDS

Part #	Description	Product Datasheet	Product Group
04031070	IOLAN SDS1 TD2R2 Secure Ethernet I/O Device Server: two digital I/O and two relay outputs, 1 x DB9M connector, software selectable EIA-232/422/485 interface, 10/100 Ethernet advanced data encryption, user authentication and event management security features included, IPv6, COM port redirector, 15kv ESD. Terminal block connectors for power and I/O. Extended Temperature	https://www.perle.com/products/ethernet-io-secure-device-server.shtml	Serial I/O Device Server: IOLAN SDS
04031080	IOLAN SDS1 TA4 Secure Ethernet I/O Device Server: four analog inputs, 1 x DB9M connector, software selectable EIA-232/422/485 interface, 10/100 Ethernet advanced data encryption, user authentication and event management security features included, IPv6, COM port redirector, 15kv ESD. Terminal block connectors for power and I/O. Extended Temperature	https://www.perle.com/products/ethernet-io-secure-device-server.shtml	Serial I/O Device Server: IOLAN SDS
04031090	IOLAN SDS1 TT4 Secure Ethernet I/O Device Server: four thermocouple/RTD inputs, 1 x DB9M connector, software selectable EIA-232/422/485 interface, 10/100 Ethernet advanced data encryption, user authentication and event management security features included, IPv6, COM port redirector, 15kv ESD. Terminal block connectors for power and I/O. Extended Temperature	https://www.perle.com/products/ethernet-io-secure-device-server.shtml	Serial I/O Device Server: IOLAN SDS
04031100	IOLAN SDS1 TA4D2 Secure Ethernet I/O Device Server: four analog inputs and 2 digital I/O, 1 x DB9M connector, software selectable EIA-232/422/485 interface, 10/100 Ethernet advanced data encryption, user authentication and event management security features included, IPv6, COM port redirector, 15kv ESD. Terminal block connectors for power and I/O. Extended Temperature	https://www.perle.com/products/ethernet-io-secure-device-server.shtml	Serial I/O Device Server: IOLAN SDS
04031110	IOLAN SDS1 TA4R2 Secure Ethernet I/O Device Server: four analog inputs and 2 relay outputs, 1x DB9M connector, software selectable EIA-232/422/485 interface, 10/100 Ethernet advanced data encryption, user authentication and event management security features included, IPv6, COM port redirector, 15kv ESD. Terminal block connectors for power and I/O. Extended Temperature	https://www.perle.com/products/ethernet-io-secure-device-server.shtml	Serial I/O Device Server: IOLAN SDS
04031152	12VDC adapter for terminal block power on IOLAN I/O Device server models (Euro)	https://www.perle.com/products/product_detail.asp?a=4&i=04031152&c=64	Power Supplies
04031160	4 pack of # 04001460. 4-port DB9M mini fan-out cables. For use with 4 port UltraPort and SpeedLE serial cards. This accessory is designed to be used with the Perle SPEED and UltraPort Serial Cards Universal PCI or PCI Express variants.	https://www.perle.com/products/product_detail.asp?a=4&c=12&i=04031160	Accessories: PCI Serial Cards

Part #	Description	Product Datasheet	Product Group
04031190	4 pack of # 04002000. 4-port DB25M DTE fan out cables. For use with 4 port UltraPort and SpeedLE serial cards. This accessory is designed to be used with the Perle SPEED and UltraPort Serial Cards Universal PCI or PCI Express variants.	https://www.perle.com/products/product_detail.asp?a=4&c=12&i=04031190	Accessories: PCI Serial Cards
04031200	RJ45 to DB25 male DTE converters. Pack of 8. For use with UltraPort and SpeedLE serial cards. This accessory is designed to be used with the Perle SPEED and UltraPort Serial Cards Universal PCI or PCI Express variants.	https://www.perle.com/products/product_detail.asp?a=4&c=12&i=04031200	Accessories: PCI Serial Cards
04031210	RJ45 to DB25 female DTE converters. Pack of 8. For use with UltraPort and SpeedLE serial cards. This accessory is designed to be used with the Perle SPEED and UltraPort Serial Cards Universal PCI or PCI Express variants.	https://www.perle.com/products/product_detail.asp?a=4&c=12&i=04031210	Accessories: PCI Serial Cards
04031220	RJ45 to DB9 male DTE converters. Pack of 8. For use with UltraPort and SpeedLE serial cards. This accessory is designed to be used with the Perle SPEED and UltraPort Serial Cards Universal PCI or PCI Express variants.	https://www.perle.com/products/product_detail.asp?a=4&c=12&i=04031220	Accessories: PCI Serial Cards
04031230	8 pack of # 04030080 IOLAN-RJ45M to RJ45F Cisco crossover adapter. This accessory is designed to be used with the IOLAN range of Terminal Servers and Device Servers.	https://www.perle.com/support_services/cabling/documents/dba0031.shtml	Accessories: Serial Servers
04031240	8 pack of # 04006950 IOLAN RJ45F to DB-25F (DTE) crossover adapter. This accessory is designed to be used with the IOLAN range of Terminal Servers and Device Servers.	https://www.perle.com/support_services/cabling/documents/dba0010.shtml	Accessories: Serial Servers
04031250	8 pack of # 04006960 IOLAN RJ45F to DB-25M (DTE) crossover adapter. This accessory is designed to be used with the IOLAN range of Terminal Servers and Device Servers.	https://www.perle.com/support_services/cabling/documents/dba0011.shtml	Accessories: Serial Servers
04031260	8 pack of # 04006970 IOLAN RJ45F to DB-9F (DTE) crossover adapter. This accessory is designed to be used with the IOLAN range of Terminal Servers and Device Servers.	https://www.perle.com/support_services/cabling/documents/dba0020.shtml	Accessories: Serial Servers
04031270	8 pack of # 04006980 IOLAN RJ45F to DB-9M (DTE) crossover adapter. This accessory is designed to be used with the IOLAN range of Terminal Servers and Device Servers.	https://www.perle.com/support_services/cabling/documents/dba0021.shtml	Accessories: Serial Servers
04031280	8 pack of # 04006990 IOLAN RJ45F to DB25M Straight-thru adapter for modems. This accessory is designed to be used with the IOLAN range of Terminal Servers and Device Servers.	https://www.perle.com/support_services/cabling/documents/dba0013.shtml	Accessories: Serial Servers
04031290	DBA0031C 8pck - 8 pack of # 04007060 RJ45M to RJ45F Cisco crossover adapter for IOLAN with Cisco pinout. This accessory is designed to be used with the IOLAN SCSC Console Server.	https://www.perle.com/support_services/cabling/documents/dba0031c.shtml	Accessories: Serial Servers

Part #	Description	Product Datasheet	Product Group
04031300	DBA0010C 8pck - 8 pack of # 04007010 RJ45F to DB-25F (DTE) crossover adapter for IOLAN with Cisco pinout. This accessory is designed to be used with the IOLAN SCSC Console Server.	https://www.perle.com/support_services/cabling/documents/dba0010c.shtml	Accessories: Serial Servers
04031310	DBA0011C 8pck - 8 pack of # 04007020 RJ45F to DB-25M (DTE) crossover adapter for IOLAN with Cisco pinout. This accessory is designed to be used with the IOLAN SCSC Console Server.	https://www.perle.com/support_services/cabling/documents/dba0011c.shtml	Accessories: Serial Servers
04031320	DBA0020C 8pck - 8 pack of # 04007040 RJ45F to DB-9F (DTE) crossover adapter for IOLAN with Cisco pinout. This accessory is designed to be used with the IOLAN SCSC Console Server.	https://www.perle.com/support_services/cabling/documents/dba0020c.shtml	Accessories: Serial Servers
04031330	DBA0021C 8pck - 8 pack of # 04007050 RJ45F to DB-9M (DTE) crossover adapter for IOLAN with Cisco pinout. This accessory is designed to be used with the IOLAN SCSC Console Server.	https://www.perle.com/support_services/cabling/documents/dba0021c.shtml	Accessories: Serial Servers
04031340	DBA0013C 8 pck - 8 pack of # 04007030 RJ45F to DB25M Straight-thru adapter for modems for IOLAN with Cisco pinout. This accessory is designed to be used with the IOLAN SCSC Console Server.	https://www.perle.com/support_services/cabling/documents/dba0013c.shtml	Accessories: Serial Servers
04031360	DBA0040 8pck - 8 pack of #04007220 IOLAN SCG Console RJ45F to DB9M adapter	https://www.perle.com/support_services/cabling/documents/dba0040.shtml	Accessories: IOLAN SCG
04031390	DBA0041 8pck - 8 pack of #04007230 IOLAN SCG Console RJ45F to DB25M adapter	https://www.perle.com/support_services/cabling/documents/dba0041.shtml	Accessories: IOLAN SCG
04031402	IOLAN SCS48CM Secure Console Server: 48 x RJ45 RS232 ports with Cisco pinout, single AC power, EIA232 interface, Dual 10/100/1000Base-T Ethernet, integrated V.92 modem, advanced data encryption, user authentication and event management security features included, IPv6, COM port redirector, 15kv ESD. EU power adapter included.	https://www.perle.com/products/iolan-scs-terminal-server.shtml	Serial Console Server: IOLAN SCSC
04031414	IOLAN SCS48CM DC Secure Console Server: 48 x RJ45 RS232 ports with Cisco pinout, 48v DC power, EIA232 interface, Dual 10/100/1000Base-T Ethernet, integrated V.92 modem, advanced data encryption, user authentication and event management security features included, IPv6, COM port redirector, 15kv ESD.	https://www.perle.com/products/iolan-scs-terminal-server.shtml	Serial Console Server: IOLAN SCSC DC
04031422	IOLAN SCS48CM DAC Secure Console Server: 48 x RJ45 RS232 ports with Cisco pinout, Dual AC power, EIA232 interface, Dual 10/100/1000Base-T Ethernet, integrated V.92 modem, advanced data encryption, user authentication and event management security features included, IPv6, COM port redirector, 15kv ESD. EU power adapter included.	https://www.perle.com/products/iolan-scs-terminal-server.shtml	Serial Console Server: IOLAN SCSC

Part #	Description	Product Datasheet	Product Group
04031432	IOLAN SCS32CM Secure Console Server: 32 x RJ45 RS232 ports with Cisco pinout, single AC power, EIA232 interface, Dual 10/100/1000Base-T Ethernet, integrated V.92 modem, advanced data encryption, user authentication and event management security features included, IPv6, COM port redirector, 15kv ESD. EU power adapter included.	https://www.perle.com/products/iolan-scs-terminal-server.shtml	Serial Console Server: IOLAN SCSC
04031444	IOLAN SCS32CM DC Secure Console Server: 32 x RJ45 RS232 ports with Cisco pinout, 48v DC power, EIA232 interface, Dual 10/100/1000Base-T Ethernet, integrated V.92 modem, advanced data encryption, user authentication and event management security features included, IPv6, COM port redirector, 15kv ESD	https://www.perle.com/products/iolan-scs-terminal-server.shtml	Serial Console Server: IOLAN SCSC DC
04031452	IOLAN SCS32CM DAC Secure Console Server: 32 x RJ45 RS232 ports with Cisco pinout, Dual AC power, EIA232 interface, Dual 10/100/1000Base-T Ethernet, integrated V.92 modem, advanced data encryption, user authentication and event management security features included, IPv6, COM port redirector, 15kv ESD. EU power adapter included.	https://www.perle.com/products/iolan-scs-terminal-server.shtml	Serial Console Server: IOLAN SCSC
04031462	IOLAN SCS16CM Secure Console Server: 16 x RJ45 RS232 ports with Cisco pinout, single AC power, EIA232 interface, Dual 10/100/1000Base-T Ethernet, integrated V.92 modem, advanced data encryption, user authentication and event management security features included, IPv6, COM port redirector, 15kv ESD. EU power adapter included.	https://www.perle.com/products/iolan-scs-terminal-server.shtml	Serial Console Server: IOLAN SCSC
04031474	IOLAN SCS16CM DC Secure Console Server: 16 x RJ45 RS232 ports with Cisco pinout, 48v DC power, EIA232 interface, Dual 10/100/1000Base-T Ethernet, integrated V.92 modem, advanced data encryption, user authentication and event management security features included, IPv6, COM port redirector, 15kv ESD.	https://www.perle.com/products/iolan-scs-terminal-server.shtml	Serial Console Server: IOLAN SCSC
04031482	IOLAN SCS16CM DAC Secure Console Server: 16 x RJ45 RS232 ports with Cisco pinout, Dual AC power, EIA232 interface, Dual 10/100/1000Base-T Ethernet, integrated V.92 modem, advanced data encryption, user authentication and event management security features included, IPv6, COM port redirector, 15kv ESD. EU power adapter included.	https://www.perle.com/products/iolan-scs-terminal-server.shtml	Serial Console Server: IOLAN SCSC
04031492	IOLAN SCS8CM Secure Console Server: 8 x RJ45 RS232 ports with Cisco pinout, single AC power, EIA232 interface, Dual 10/100/1000Base-T Ethernet, integrated V.92 modem, advanced data encryption, user authentication and event management security features included, IPv6, COM port redirector, 15kv ESD. EU power adapter included.	https://www.perle.com/products/iolan-scs-terminal-server.shtml	Serial Console Server: IOLAN SCSC

Part #	Description	Product Datasheet	Product Group
04031504	IOLAN SCS8CM DC Secure Console Server: 8 x RJ45 RS232 ports with Cisco pinout, 48v DC power, EIA232 interface, Dual 10/100/1000Base-T Ethernet, integrated V.92 modem, advanced data encryption, user authentication and event management security features included, IPv6, COM port redirector, 15kv ESD.	https://www.perle.com/products/iolan-scs-terminal-server.shtml	Serial Console Server: IOLAN SCSC
04031512	IOLAN SCS8CM DAC Secure Console Server: 8 x RJ45 RS232 ports with Cisco pinout, Dual AC power, EIA232 interface, Dual 10/100/1000Base-T Ethernet, integrated V.92 modem, advanced data encryption, user authentication and event management security features included, IPv6, COM port redirector, 15kv ESD. EU power adapter included.	https://www.perle.com/products/iolan-scs-terminal-server.shtml	Serial Console Server: IOLAN SCSC
04031542	IOLAN SCS16C-DSFP Secure Console Server: 16 x RJ45 RS232 ports with Cisco pinout, Dual SFP, PCI slot for V.92 modem card, advanced data encryption, user authentication and event management security features included, IPv6, COM port redirector, 15kv ESD. EU power adapter included.	https://www.perle.com/products/iolan-scs-terminal-server.shtml	Serial Console Server: IOLAN SCSC
04031552	IOLAN SCS16C-DSFP DAC Secure Console Server: 16 x RJ45 connectors with Cisco pinout, Dual AC power, RS232 interface, Dual SFP , PCI slot for V.92 modem card, advanced data encryption, user authentication and event management security features included, IPv6, COM port redirector, 15kv ESD. EU power adapter included.	https://www.perle.com/products/iolan-scs-terminal-server.shtml	Serial Console Server: IOLAN SCSC
04031602	IOLAN SDS8C Secure Device Server: 8 x RJ45 connectors with software selectable RS232/422/485 interface, Cisco pinout, 1U rack mount, dual 10/100/1000Base-T Ethernet, advanced data encryption, user authentication and event management security features included, IPv6, COM port redirector, 15kv ESD. EU power adapter included.	https://www.perle.com/products/iolan-sdsc-rack-terminal-server.shtml	Serial Device Server: IOLAN SDSC
04031612	IOLAN SDS16C Secure Device Server: 16 x RJ45 connector with Cisco pinout, 1U rack mount, software selectable RS232/422/485 interface, dual 10/100/1000Base-T Ethernet, advanced data encryption, user authentication and event management security features included, IPv6, COM port redirector, 15kv ESD. EU power adapter included.	https://www.perle.com/products/iolan-sdsc-rack-terminal-server.shtml	Serial Device Server: IOLAN SDSC
04031622	IOLAN SDS32C Secure Device Server: 32 x RJ45 connector with Cisco pinout, 1U rack mount, software selectable RS232/422/485 interface, dual 10/100/1000Base-T Ethernet, advanced data encryption, user authentication and event management security features included, IPv6, COM port redirector, 15kv ESD. EU power adapter included.	https://www.perle.com/products/iolan-sdsc-rack-terminal-server.shtml	Serial Device Server: IOLAN SDSC

Part #	Description	Product Datasheet	Product Group
04031630	IOLAN SDS8C DC Secure Device Server: 8 x RJ45 connectors with software selectable RS232/422/485 interface, Cisco pinout, dual feed 48v DC power, 1U rack mount, dual 10/100/1000Base-T Ethernet, advanced data encryption, user authentication and event management security features included, IPv6, COM port redirector, 15kv ESD.	https://www.perle.com/products/iolan-sdsc-rack-terminal-server.shtml	Serial Device Server: IOLAN SDSC
04031640	IOLAN SDS16C DC Secure Device Server: 16 x RJ45 connector with Cisco pinout, dual feed 48v DC power, 1U rack mount, software selectable RS232/422/485 interface, dual 10/100/1000Base-T Ethernet, advanced data encryption, user authentication and event management security features included, IPv6, COM port redirector, 15kv ESD.	https://www.perle.com/products/iolan-sdsc-rack-terminal-server.shtml	Serial Device Server: IOLAN SDSC
04031650	IOLAN SDS32C DC Secure Device Server: 32 x RJ45 connector with Cisco pinout, dual feed 48v DC power, 1U rack mount, software selectable RS232/422/485 interface, dual 10/100/1000Base-T Ethernet, advanced data encryption, user authentication and event management security features included, IPv6, COM port redirector, 15kv ESD.	https://www.perle.com/products/iolan-sdsc-rack-terminal-server.shtml	Serial Device Server: IOLAN SDSC
04031662	IOLAN SDG1 W Device Server: Wireless LAN (WiFi) client IEEE 802.11 a, b, g, n @ 2.4Ghz/5Ghz, 1 x DB9M connector with software selectable RS232/422/485 interface, 10/100/1000 Ethernet, advanced data encryption, user authentication and event management security features included, IPv6, COM port redirector, 15kv ESD, EU power adapter included	https://www.perle.com/products/iolan-sds-wireless-device-server.shtml	Serial Device Server: IOLAN SDG W
04031672	IOLAN SDG2 W Device Server: Wireless LAN (WiFi) client IEEE 802.11 a, b, g, n @ 2.4Ghz/5Ghz, 2 x DB9M connectors with software selectable RS232/422/485 interface, 10/100/1000 Ethernet, advanced data encryption, user authentication and event management security features included, IPv6, COM port redirector, 15kv ESD, EU power adapter included	https://www.perle.com/products/iolan-sds-wireless-device-server.shtml	Serial Device Server: IOLAN SDG W
04031682	IOLAN SDG4 W Device Server: Wireless LAN (WiFi) client IEEE 802.11 a, b, g, n @ 2.4Ghz/5Ghz, 4 x RJ45 connectors with software selectable RS232/422/485 interface, 10/100/1000 Ethernet, advanced data encryption, user authentication and event management security features included, IPv6, COM port redirector, 15kv ESD, EU power adapter included	https://www.perle.com/products/iolan-sds-wireless-device-server.shtml	Serial Device Server: IOLAN SDG W
04031690	The DRC DIN Rail Clip and an accessory designed to be used with the IOLAN SDG W and SDG L Device Servers.	https://www.perle.com/products/product_detail.asp?a=4&i=04031690&c=1180	Accessories: Mounting Kits

Part #	Description	Product Datasheet	Product Group
04031732	IOLAN SDG1 LE Device Server: 1x RJ45 serial port with software selectable RS232/422/485 interface. Cellular WWAN capability based on 4G LTE (ETSI Europe) with fallback networks (HSPA+, UMTS, EDGE and GPRS). 1 x 10/100/1000 Ethernet port. Advanced data encryption, user authentication and event management security, IPv6, COM port redirector, 15kv ESD, EU power adapter included	https://www.perle.com/products/iolan-sds-lte-device-server.shtml	Serial Device Server: IOLAN SDG L
04031742	IOLAN SDG2 LE Device Server: 2x RJ45 serial port with software selectable RS232/422/485 interface. Cellular WWAN capability based on 4G LTE (ETSI Europe) with fallback networks (HSPA+, UMTS, EDGE and GPRS). 1 x 10/100/1000 Ethernet port. Advanced data encryption, user authentication and event management security, IPv6, COM port redirector, 15kv ESD, EU power adapter included	https://www.perle.com/products/iolan-sds-lte-device-server.shtml	Serial Device Server: IOLAN SDG L
04031752	IOLAN SDG4 LE Device Server: 4x RJ45 serial port with software selectable RS232/422/485 interface. Cellular WWAN capability based on 4G LTE (ETSI Europe) with fallback networks (HSPA+, UMTS, EDGE and GPRS). 1 x 10/100/1000 Ethernet port. Advanced data encryption, user authentication and event management security, IPv6, COM port redirector, 15kv ESD, EU power adapter included	https://www.perle.com/products/iolan-sds-lte-device-server.shtml	Serial Device Server: IOLAN SDG L
04031762	IOLAN DG1 RJ45 Device Server: 1 x RJ45 connector with software selectable, RS232/422/485 interface, 10/100/1000 Ethernet, IPv6, COM port redirector, 15kv ESD, EU power adapter included	https://www.perle.com/products/iolan-ds-terminal-server.shtml	Serial Device Server: IOLAN DG
04031772	IOLAN DG1 DB9 Device Server: 1 x DB9M connector with software selectable, RS232/422/485 interface, 10/100/1000 Ethernet, IPv6, COM port redirector, 15kv ESD, EU power adapter included	https://www.perle.com/products/iolan-ds-terminal-server.shtml	Serial Device Server: IOLAN DG
04031782	IOLAN DG1 DB25 Device Server: 1 x DB25F connector with software selectable RS232/422/485 interface, 10/100/1000 Ethernet, IPv6, COM port redirector, 15kv ESD, EU power adapter included	https://www.perle.com/products/iolan-ds-terminal-server.shtml	Serial Device Server: IOLAN DG
04031790	IOLAN DG1 TX Device Server: 1 x DB9M connector with software selectable RS232/422/485 interface, 10/100/1000 Ethernet, Extended Temperature, IPv6, COM port redirector, 15kv ESD, terminal block power connector	https://www.perle.com/products/iolan-ds-terminal-server.shtml	Serial Device Server: IOLAN DG
04031802	IOLAN TG2 Terminal Server: 2 x RJ45 connectors with RS232 interface, 10/100/1000 Ethernet, IPv6, COM redirector, 15kv ESD, EU power adapter included	https://www.perle.com/products/iolan-ds-terminal-server.shtml	Serial Terminal Server: IOLAN TG

Part #	Description	Product Datasheet	Product Group
04031812	IOLAN SDG2 Device Server: 2 x RJ45 connectors with software selectable RS232/422/485 interfaces, 10/100/1000 Ethernet, advanced data encryption, user authentication and event management security features included, IPv6, COM port redirector, 15kv ESD, EU power adapter included	https://www.perle.com/products/iolan-sds-terminal-server.shtml	Serial Device Server: IOLAN SDG
04031822	IOLAN SDG1 RJ45 Device Server: 1 x RJ45 connectors with software selectable RS232/422/485 interface, 10/100/1000 Ethernet, advanced data encryption, user authentication and event management security features included, IPv6, COM port redirector, 15kv ESD, EU power adapter included	https://www.perle.com/products/iolan-sds-terminal-server.shtml	Serial Device Server: IOLAN SDG
04031832	IOLAN SDG1 DB9 Device Server: 1 x DB9M connector with software selectable RS232/422/485 interface, 10/100/1000 Ethernet, advanced data encryption, user authentication and event management security features included, IPv6, COM port redirector, 15kv ESD, EU power adapter included	https://www.perle.com/products/iolan-sds-terminal-server.shtml	Serial Device Server: IOLAN SDG
04031842	IOLAN SDG1 DB25 Device Server: 1 x DB25F connector with software selectable RS232/422/485 interface, 10/100/1000 Ethernet, advanced data encryption, user authentication and event management security features included, IPv6, COM port redirector, 15kv ESD, EU power adapter included	https://www.perle.com/products/iolan-sds-terminal-server.shtml	Serial Device Server: IOLAN SDG
04031852	IOLAN SDG4 Device Server: 4 x RJ45 connectors with software selectable RS232/422/485 interfaces, 10/100/1000 Ethernet, advanced data encryption, user authentication and event management security features included, IPv6, COM port redirector, 15kv ESD, EU power adapter included	https://www.perle.com/products/iolan-sds-terminal-server.shtml	Serial Device Server: IOLAN SDG
04031860	IOLAN SDG2 TX Device Server: 2 X RJ45 connectors with software selectable RS232/422/485 interfaces, Extended temperature, 10/100/1000 Ethernet, advanced data encryption, user authentication and event management security features included, IPv6, COM port redirector, 15kv ESD, pigtail power connector included	https://www.perle.com/products/iolan-sdst-terminal-server.shtml	Serial Device Server: IOLAN SDG
04031870	IOLAN SDG4 TX Device Server: 4 X RJ45 connectors with software selectable RS232/422/485 interfaces, Extended temperature, 10/100/1000 Ethernet, advanced data encryption, user authentication and event management security features included, IPv6, COM port redirector, 15kv ESD, pigtail power connector included	https://www.perle.com/products/iolan-sdst-terminal-server.shtml	Serial Device Server: IOLAN SDG

Part #	Description	Product Datasheet	Product Group
04031880	IOLAN SDG1 TX Device Server: 1 x DB9M connector with software selectable RS232/422/485 interface, Extended Temperature, 10/100/1000 Ethernet, advanced data encryption, user authentication and event management security features included, IPv6, COM port redirector, 15kv ESD, pigtail power connector included	https://www.perle.com/products/iolan-sdst-terminal-server.shtml	Serial Device Server: IOLAN SDG
04031892	IOLAN STG8 Terminal Server: 8 x RJ45 connectors with RS232 interface, 10/100/1000 Ethernet, advanced data encryption, user authentication and event management security features included, IPv6, COM port redirector, 15kv ESD, EU power adapter included	https://www.perle.com/products/iolan-sts-d-terminal-server.shtml	Serial Terminal Server: IOLAN STG
04031902	IOLAN STG4 Terminal Server: 4 x RJ45 connectors with RS232 interface, 10/100/1000 Ethernet, advanced data encryption, user authentication and event management security features included, IPv6, COM port redirector, 15kv ESD, EU power adapter included	https://www.perle.com/products/iolan-sts-d-terminal-server.shtml	Serial Terminal Server: IOLAN STG
04031910	IOLAN SDG4 P Device Server: 4 x RJ45 connectors with software selectable RS232/422/485 interfaces, 10/100/1000 Ethernet, advanced data encryption, user authentication and event management security features included, IPv6, COM port redirector, 15kv ESD, 802.3af Power over Ethernet (PoE) compliant PD	https://www.perle.com/products/iolan-sdsp-terminal-server.shtml	Serial Device Server: IOLAN SDG
04031920	IOLAN STG4 P Device Server: 4 x RJ45 connectors with RS232 interface, 10/100/1000 Ethernet, 802.3af Power over Ethernet (PoE) compliant, advanced data encryption, user authentication and event management security features included, IPv6, COM port redirector, 15kv ESD	https://www.perle.com/products/4-port-terminal-server-poe.shtml	Serial Terminal Server: IOLAN STG
04031932	IOLAN SDG8 P Device Server: 8 x RJ45 connector with software selectable RS232/422/485 interfaces, 10/100/1000 Ethernet, advanced data encryption, user authentication and event management security features included, IPv6, COM port redirector, 15kv ESD, 802.3af Power over Ethernet (PoE) compliant PD, EU power adapter included	https://www.perle.com/products/iolan-sdsp-terminal-server.shtml	Serial Device Server: IOLAN SDG
04032020	RPS820 Remote Power Switch R2 - 1U, 8 IEC320-C13 plugs, 32 Amps total, 200 - 240 VAC.	https://www.perle.com/products/remote-power-switch.shtml	Remote Power Switch
04032040	RPS 1620H Remote Power Switch - 2U, 16 IEC320-C13 plugs, 32 Amps total, 200 - 250 VAC, horizontal rack mountable.	https://www.perle.com/products/remote-power-switch.shtml	Remote Power Switch
04032110	6 ft power cord IEC320-C13 to IEC320-C14 for Perle RPS820 and RPS1620	https://www.perle.com/products/product_detail.asp?a=4&i=04032110&c=66	Accessories: Remote Power Switch
04032120	IOLAN SCS Adapter for 3rd party PC (PCMCIA) cards. This accessory is designed to be used with the IOLAN SCSC Console Server.	https://www.perle.com/products/product_detail.asp?a=4&i=04032120&c=70	Accessories: Serial Console Servers

Part #	Description	Product Datasheet	Product Group
04032400	IOLAN SDS8C HV Electric Utility Terminal Server: 8 x RJ45 serial ports with software selectable RS232/422/485 interface, Cisco Rj45 pinout, dual 10/100/1000Base-T Ethernet, 1U rack mount, Universal High Voltage AC/DC power, Advanced Features for NERC-CIP compliance, Meets IEC 61850-3, IEEE 1613 electric power substation environmental standard.	https://www.perle.com/products/electric-utility-terminal-server.shtml	Serial Device Server: IOLAN SDSC HV
04032410	IOLAN SDS8C DHV Electric Utility Terminal Server: 8 x RJ45 serial ports, dual 10/100/1000Base-T Ethernet, 1U rack mount, Dual Universal High Voltage AC/DC power, Software selectable RS232/422/485 interface, Cisco Rj45 pinout, Advanced Features for NERC-CIP compliance, Meets IEC 61850-3, IEEE 1613 electric power substation environmental standard.	https://www.perle.com/products/electric-utility-terminal-server.shtml	Serial Device Server: IOLAN SDSC HV
04032420	IOLAN SDS8C LDC Utility Terminal Server: 8 x RJ45 serial ports, software selectable RS232/422/485 interface, Cisco Rj45 pinout, 24/48 VDC power, dual 10/100/1000Base-T Ethernet, 1U rack mount, Advanced Features for NERC-CIP compliance, Meets IEC 61850-3, IEEE 1613 electric power substation environmental standard. Certified for NEBS Level 3 for Telecommunications Facilities.	https://www.perle.com/products/electric-utility-terminal-server.shtml	Serial Device Server: IOLAN SDSC LDC
04032430	IOLAN SDS16C LDC Utility Terminal Server: 16 x RJ45 serial ports with software selectable RS232/422/485 interface, Cisco Rj45 pinout, 24/48 VDC power, dual 10/100/1000Base-T Ethernet, 1U rack mount, Advanced Features for NERC-CIP compliance, Meets IEC 61850-3, IEEE 1613 electric power substation environmental standard. Certified for NEBS Level 3 for Telecommunications Facilities.	https://www.perle.com/products/electric-utility-terminal-server.shtml	Serial Device Server: IOLAN SDSC LDC
04032440	IOLAN SDS16C DHV Electric Utility Terminal Server: 16 x RJ45 serial ports with software selectable RS232/422/485 interface, Cisco Rj45 pinout, dual 10/100/1000Base-T Ethernet, 1U rack mount, Dual Universal High Voltage AC/DC power, Advanced Features for NERC-CIP compliance, Meets IEC 61850-3, IEEE 1613 electric power substation environmental standard.	https://www.perle.com/products/electric-utility-terminal-server.shtml	Serial Device Server: IOLAN SDSC HV
04032450	IOLAN SDS16C HV Electric Utility Terminal Server: 16 x RJ45 serial ports with software selectable RS232/422/485 interface, Cisco Rj45 pinout, dual 10/100/1000Base-T Ethernet, 1U rack mount, Universal High Voltage AC/DC power, Advanced Features for NERC-CIP compliance, Meets IEC 61850-3, IEEE 1613 electric power substation environmental standard.	https://www.perle.com/products/electric-utility-terminal-server.shtml	Serial Device Server: IOLAN SDSC HV

Part #	Description	Product Datasheet	Product Group
04032490	DIN Rail Mounting Kit for IOLAN - all 1U 19 inch rack models. This accessory is designed to be used with the IOLAN range of Terminal Servers and Device Servers.	https://www.perle.com/products/product_detail.asp?a=4&i=04032490&c=74	Accessories: Mounting Kits
04032500	IOLAN SDS32C HV Electric Utility Terminal Server: 32 x RJ45 serial ports, Software selectable RS232/422/485 interface, Cisco Rj45 pinout, dual 10/100/1000Base-T Ethernet, 1U rack mount, Universal High Voltage AC/DC power, Advanced Features for NERC-CIP compliance, Meets IEC 61850-3, IEEE 1613 electric power substation environmental standard.	https://www.perle.com/products/electric-utility-terminal-server.shtml	Serial Device Server: IOLAN SDSC HV
04032510	IOLAN SDS32C DHV Electric Utility Terminal Server: 32 x RJ45 serial ports with Software selectable RS232/422/485 interface, Cisco Rj45 pinout, dual 10/100/1000Base-T Ethernet, 1U rack mount, Dual Universal High Voltage AC/DC power, Advanced Features for NERC-CIP compliance, Meets IEC 61850-3, IEEE 1613 electric power substation environmental standard.	https://www.perle.com/products/electric-utility-terminal-server.shtml	Serial Device Server: IOLAN SDSC HV
04032520	IOLAN SDS32C LDC Utility Terminal Server: 32 x RJ45 serial ports, Software selectable RS232/422/485 interface, Cisco Rj45 pinout, 24/48 VDC power, dual 10/100/1000Base-T Ethernet, 1U rack mount, Advanced Features for NERC-CIP compliance, Meets IEC 61850-3, IEEE 1613 electric power substation environmental standard. Certified for NEBS Level 3 for Telecommunications Facilities.	https://www.perle.com/products/electric-utility-terminal-server.shtml	Serial Device Server: IOLAN SDSC LDC
04032652	IOLAN SCG16 Console Server: 16 x RS232 RJ45 interfaces with software configurable Cisco pinouts, 1 x auto-sensing 10/100/1000 RJ45 Ethernet Port, Micro USB and RS232 RJ45 Console Admin Ports, advanced data encryption, user authentication and event management security features included, IPv6, COM port redirector, 15kv ESD, AC Power, EU power adapter included.	https://www.perle.com/products/iolan-scg-console-server.shtml	Serial Console Server: IOLAN SCG
04032672	IOLAN SCG32 Console Server: 32 x RS232 RJ45 interfaces with software configurable Cisco pinouts, 1 x auto-sensing 10/100/1000 RJ45 Ethernet Port, Micro USB and RS232 RJ45 Console Admin Ports, advanced data encryption, user authentication and event management security features included, IPv6, COM port redirector, 15kv ESD, AC Power, EU power adapter included.	https://www.perle.com/products/iolan-scg-console-server.shtml	Serial Console Server: IOLAN SCG

Part #	Description	Product Datasheet	Product Group
04032682	IOLAN SCG48 Console Server: 48 x RS232 RJ45 interfaces with software configurable Cisco pinouts, 1 x auto-sensing 10/100/1000 RJ45 Ethernet Port, Micro USB and RS232 RJ45 Console Admin Ports, advanced data encryption, user authentication and event management security features included, IPv6, COM port redirector, 15kv ESD, AC Power, EU power adapter included.	https://www.perle.com/products/iolan-scg-console-server.shtml	Serial Console Server: IOLAN SCG
04032762	IOLAN SCG18 R-LEWM Console Server: 16 x RS232 RJ45 interfaces with software configurable Cisco pinouts, 2 x USB Ports, Front Panel Display and Keyboard, 2 x auto-sensing 10/100/1000 Ethernet Combo Ports (RJ45 or SFP), Cellular WWAN capability based on 4G LTE (ETSI Europe) with fallback networks (HSPA+, UMTS, EDGE and GPRS), Wireless LAN (WiFi) client IEEE 802.11 a, b, g, n @ 2.4Ghz/5Ghz, integrated RJ45 V.92 modem, Micro SD Card Slot, Expandable using IOLAN G16 RS232 Card and IOLAN G16 USB Card, Micro USB and RS232 RJ45 Console Admin Ports, advanced data encryption, user authentication and event management security features included, IPv6, COM port redirector, 15kv ESD, Dual AC Power, EU power adapter included.	https://www.perle.com/products/iolan-scglwm-console-server.shtml	Serial Console Server: IOLAN SCG LWM
04032772	IOLAN SCG18 R-LEW Console Server: 16 x RS232 RJ45 interfaces with software configurable Cisco pinouts, 2 x USB Ports, Front Panel Display and Keyboard, 2 x auto-sensing 10/100/1000 Ethernet Combo Ports (RJ45 or SFP), Cellular WWAN capability based on 4G LTE (ETSI Europe) with fallback networks (HSPA+, UMTS, EDGE and GPRS), Wireless LAN (WiFi) client IEEE 802.11 a, b, g, n @ 2.4Ghz/5Ghz, Mico SD Card Slot, Expandable using IOLAN G16 RS232 Card and IOLAN G16 USB Card, Micro USB and RS232 RJ45 Console Admin Ports, advanced data encryption, user authentication and event management security features included, IPv6, COM port redirector, 15kv ESD, Dual AC Power, EU power adapter included.	https://www.perle.com/products/iolan-scglw-console-server.shtml	Serial Console Server: IOLAN SCG LW

Part #	Description	Product Datasheet	Product Group
04032782	IOLAN SCG18 R-LEM Console Server: 16 x RS232 RJ45 interfaces with software configurable Cisco pinouts, 2 x USB Ports, Front Panel Display and Keyboard, 2 x auto-sensing 10/100/1000 Ethernet Combo Ports (RJ45 or SFP), Cellular WWAN capability based on 4G LTE (ETSI Europe) with fallback networks (HSPA+, UMTS, EDGE and GPRS), integrated RJ45 V.92 modem, Micro SD Card Slot, Expandable using IOLAN G16 RS232 Card and IOLAN G16 USB Card, Micro USB and RS232 RJ45 Console Admin Ports, advanced data encryption, user authentication and event management security features included, IPv6, COM port redirector, 15kv ESD, Dual AC Power, EU power adapter included.	https://www.perle.com/products/iolan-scglm-console-server.shtml	Serial Console Server: IOLAN SCG LM
04032792	IOLAN SCG18 R-LE Console Server: 16 x RS232 RJ45 interfaces with software configurable Cisco pinouts, 2 x USB Ports, Front Panel Display and Keyboard, 2 x auto-sensing 10/100/1000 Ethernet Combo Ports (RJ45 or SFP), Cellular WWAN capability based on 4G LTE (ETSI Europe) with fallback networks (HSPA+, UMTS, EDGE and GPRS), Micro SD Card Slot, Expandable using IOLAN G16 RS232 Card and IOLAN G16 USB Card, Micro USB and RS232 RJ45 Console Admin Ports, advanced data encryption, user authentication and event management security features included, IPv6, COM port redirector, 15kv ESD, Dual AC Power, EU power adapter included.	https://www.perle.com/products/iolan-scgl-console-server.shtml	Serial Console Server: IOLAN SCG L
04032802	IOLAN SCG18 R-WM Console Server: 16 x RS232 RJ45 interfaces with software configurable Cisco pinouts, 2 x USB Ports, Front Panel Display and Keyboard, 2 x auto-sensing 10/100/1000 Ethernet Combo Ports (RJ45 or SFP), Wireless LAN (WiFi) client IEEE 802.11 a, b, g, n @ 2.4Ghz/5Ghz, integrated RJ45 V.92 modem, Micro SD Card Slot, Expandable using IOLAN G16 RS232 Card and IOLAN G16 USB Card, Micro USB and RS232 RJ45 Console Admin Ports, advanced data encryption, user authentication and event management security features included, IPv6, COM port redirector, 15kv ESD, Dual AC Power, EU power adapter included.	https://www.perle.com/products/iolan-scgwm-console-server.shtml	Serial Console Server: IOLAN SCG WM

Part #	Description	Product Datasheet	Product Group
04032812	IOLAN SCG18 R-W Console Server: 16 x RS232 RJ45 interfaces with software configurable Cisco pinouts, 2 x USB Ports, Front Panel Display and Keyboard, 2 x auto-sensing 10/100/1000 Ethernet Combo Ports (RJ45 or SFP), Wireless LAN (WiFi) client IEEE 802.11 a, b, g, n @ 2.4Ghz/5Ghz, Mico SD Card Slot, Expandable using IOLAN G16 RS232 Card and IOLAN G16 USB Card, Micro USB and RS232 RJ45 Console Admin Ports, advanced data encryption, user authentication and event management security features included, IPv6, COM port redirector, 15kv ESD, Dual AC Power, EU power adapter included.	https://www.perle.com/products/iolan-scgw-console-server.shtml	Serial Console Server: IOLAN SCG W
04032822	IOLAN SCG18 R-M Console Server: 16 x RS232 RJ45 interfaces with software configurable Cisco pinouts, 2 x USB Ports, Front Panel Display and Keyboard, 2 x auto-sensing 10/100/1000 Ethernet Combo Ports (RJ45 or SFP), integrated RJ45 V.92 modem, Micro SD Card Slot, Expandable using IOLAN G16 RS232 Card and IOLAN G16 USB Card, Micro USB and RS232 RJ45 Console Admin Ports, advanced data encryption, user authentication and event management security features included, IPv6, COM port redirector, 15kv ESD, Dual AC Power, EU power adapter included.	https://www.perle.com/products/iolan-scgm-console-server.shtml	Serial Console Server: IOLAN SCG M
04032832	IOLAN SCG18 R Console Server: 16 x RS232 RJ45 interfaces with software configurable Cisco pinouts, 2 x USB Ports, Front Panel Display and Keyboard, 2 x auto-sensing 10/100/1000 Ethernet Combo Ports (RJ45 or SFP), Micro SD Card Slot, Expandable using IOLAN G16 RS232 Card and IOLAN G16 USB Card, Micro USB and RS232 RJ45 Console Admin Ports, advanced data encryption, user authentication and event management security features included, IPv6, COM port redirector, 15kv ESD, Dual AC Power, EU power adapter included.	https://www.perle.com/products/iolan-scgru-console-server.shtml	Serial Console Server: IOLAN SCG R/U

Part #	Description	Product Datasheet	Product Group
04032882	IOLAN SCG34 R-LEWM Console Server: 32 x RS232 RJ45 interfaces with software configurable Cisco pinouts, 2 x USB Ports, Front Panel Display and Keyboard, 2 x auto-sensing 10/100/1000 Ethernet Combo Ports (RJ45 or SFP), Cellular WWAN capability based on 4G LTE (ETSI Europe) with fallback networks (HSPA+, UMTS, EDGE and GPRS), Wireless LAN (WiFi) client IEEE 802.11 a, b, g, n @ 2.4Ghz/5Ghz,integrated RJ45 V.92 modem, Micro SD Card Slot, Expandable using IOLAN G16 RS232 Card and IOLAN G16 USB Card, Micro USB and RS232 RJ45 Console Admin Ports, advanced data encryption, user authentication and event management security features included, IPv6, COM port redirector, 15kv ESD, Dual AC Power, EU power adapter included.	https://www.perle.com/products/iolan-scglwm-console-server.shtml	Serial Console Server: IOLAN SCG LWM
04032892	IOLAN SCG34 R-LEW Console Server: 32 x RS232 RJ45 interfaces with software configurable Cisco pinouts, 2 x USB Ports, Front Panel Display and Keyboard, 2 x auto-sensing 10/100/1000 Ethernet Combo Ports (RJ45 or SFP), Cellular WWAN capability based on 4G LTE (ETSI Europe) with fallback networks (HSPA+, UMTS, EDGE and GPRS), Wireless LAN (WiFi) client IEEE 802.11 a, b, g, n @ 2.4Ghz/5Ghz,Mico SD Card Slot, Expandable using IOLAN G16 RS232 Card and IOLAN G16 USB Card, Micro USB and RS232 RJ45 Console Admin Ports, advanced data encryption, user authentication and event management security features included, IPv6, COM port redirector, 15kv ESD, Dual AC Power, EU power adapter included.	https://www.perle.com/products/iolan-scglw-console-server.shtml	Serial Console Server: IOLAN SCG LW
04032902	IOLAN SCG34 R-LEM Console Server: 32 x RS232 RJ45 interfaces with software configurable Cisco pinouts, 2 x USB Ports, Front Panel Display and Keyboard, 2 x auto-sensing 10/100/1000 Ethernet Combo Ports (RJ45 or SFP), Cellular WWAN capability based on 4G LTE (ETSI Europe) with fallback networks (HSPA+, UMTS, EDGE and GPRS), integrated RJ45 V.92 modem, Micro SD Card Slot, Expandable using IOLAN G16 RS232 Card and IOLAN G16 USB Card, Micro USB and RS232 RJ45 Console Admin Ports, advanced data encryption, user authentication and event management security features included, IPv6, COM port redirector, 15kv ESD, Dual AC Power, EU power adapter included.	https://www.perle.com/products/iolan-scglm-console-server.shtml	Serial Console Server: IOLAN SCG LM

Part #	Description	Product Datasheet	Product Group
04032912	IOLAN SCG34 R-LE Console Server: 32 x RS232 RJ45 interfaces with software configurable Cisco pinouts, 2 x USB Ports, Front Panel Display and Keyboard, 2 x auto-sensing 10/100/1000 Ethernet Combo Ports (RJ45 or SFP), Cellular WWAN capability based on 4G LTE (ETSI Europe) with fallback networks (HSPA+, UMTS, EDGE and GPRS), Micro SD Card Slot, Expandable using IOLAN G16 RS232 Card and IOLAN G16 USB Card, Micro USB and RS232 RJ45 Console Admin Ports, advanced data encryption, user authentication and event management security features included, IPv6, COM port redirector, 15kv ESD, Dual AC Power, EU power adapter included.	https://www.perle.com/products/iolan-scgl-console-server.shtml	Serial Console Server: IOLAN SCG L
04032922	IOLAN SCG34 R-WM Console Server: 32 x RS232 RJ45 interfaces with software configurable Cisco pinouts, 2 x USB Ports, Front Panel Display and Keyboard, 2 x auto-sensing 10/100/1000 Ethernet Combo Ports (RJ45 or SFP), Wireless LAN (WiFi) client IEEE 802.11 a, b, g, n @ 2.4Ghz/5Ghz, integrated RJ45 V.92 modem, Micro SD Card Slot, Expandable using IOLAN G16 RS232 Card and IOLAN G16 USB Card, Micro USB and RS232 RJ45 Console Admin Ports, advanced data encryption, user authentication and event management security features included, IPv6, COM port redirector, 15kv ESD, Dual AC Power, EU power adapter included.	https://www.perle.com/products/iolan-scgwm-console-server.shtml	Serial Console Server: IOLAN SCG WM
04032932	IOLAN SCG34 R-W Console Server: 32 x RS232 RJ45 interfaces with software configurable Cisco pinouts, 2 x USB Ports, Front Panel Display and Keyboard, 2 x auto-sensing 10/100/1000 Ethernet Combo Ports (RJ45 or SFP), Wireless LAN (WiFi) client IEEE 802.11 a, b, g, n @ 2.4Ghz/5Ghz, Micro SD Card Slot, Expandable using IOLAN G16 RS232 Card and IOLAN G16 USB Card, Micro USB and RS232 RJ45 Console Admin Ports, advanced data encryption, user authentication and event management security features included, IPv6, COM port redirector, 15kv ESD, Dual AC Power, EU power adapter included.	https://www.perle.com/products/iolan-scgw-console-server.shtml	Serial Console Server: IOLAN SCG W

Part #	Description	Product Datasheet	Product Group
04032942	IOLAN SCG34 R-M Console Server: 32 x RS232 RJ45 interfaces with software configurable Cisco pinouts, 2 x USB Ports, Front Panel Display and Keyboard, 2 x auto-sensing 10/100/1000 Ethernet Combo Ports (RJ45 or SFP), integrated RJ45 V.92 modem, Micro SD Card Slot, Expandable using IOLAN G16 RS232 Card and IOLAN G16 USB Card, Micro USB and RS232 RJ45 Console Admin Ports, advanced data encryption, user authentication and event management security features included, IPv6, COM port redirector, 15kv ESD, Dual AC Power, EU power adapter included.	https://www.perle.com/products/iolan-scgm-console-server.shtml	Serial Console Server: IOLAN SCG M
04032952	IOLAN SCG34 R Console Server: 32 x RS232 RJ45 interfaces with software configurable Cisco pinouts, 2 x USB Ports, Front Panel Display and Keyboard, 2 x auto-sensing 10/100/1000 Ethernet Combo Ports (RJ45 or SFP), Micro SD Card Slot, Expandable using IOLAN G16 RS232 Card and IOLAN G16 USB Card, Micro USB and RS232 RJ45 Console Admin Ports, advanced data encryption, user authentication and event management security features included, IPv6, COM port redirector, 15kv ESD, Dual AC Power, EU power adapter included.	https://www.perle.com/products/iolan-scgru-console-server.shtml	Serial Console Server: IOLAN SCG R/U
04033002	IOLAN SCG50 R-LEWM Console Server: 48 x RS232 RJ45 interfaces with software configurable Cisco pinouts, 2 x USB Ports, Front Panel Display and Keyboard, 2 x auto-sensing 10/100/1000 Ethernet Combo Ports (RJ45 or SFP), Cellular WWAN capability based on 4G LTE (ETSI Europe) with fallback networks (HSPA+, UMTS, EDGE and GPRS), Wireless LAN (WiFi) client IEEE 802.11 a, b, g, n @ 2.4Ghz/5Ghz, integrated RJ45 V.92 modem, Micro SD Card Slot, Micro USB and RS232 RJ45 Console Admin Ports, advanced data encryption, user authentication and event management security features included, IPv6, COM port redirector, 15kv ESD, Dual AC Power, EU power adapter included.	https://www.perle.com/products/iolan-scglwm-console-server.shtml	Serial Console Server: IOLAN SCG LWM

Part #	Description	Product Datasheet	Product Group
04033012	IOLAN SCG50 R-LEW Console Server: 48 x RS232 RJ45 interfaces with software configurable Cisco pinouts, 2 x USB Ports, Front Panel Display and Keyboard, 2 x auto-sensing 10/100/1000 Ethernet Combo Ports (RJ45 or SFP), Cellular WWAN capability based on 4G LTE (ETSI Europe) with fallback networks (HSPA+, UMTS, EDGE and GPRS), Wireless LAN (WiFi) client IEEE 802.11 a, b, g, n @ 2.4Ghz/5Ghz, Mico SD Card Slot, Micro USB and RS232 RJ45 Console Admin Ports, advanced data encryption, user authentication and event management security features included, IPv6, COM port redirector, 15kv ESD, Dual AC Power, EU power adapter included.	https://www.perle.com/products/iolan-scglw-console-server.shtml	Serial Console Server: IOLAN SCG LW
04033022	IOLAN SCG50 R-LEM Console Server: 48 x RS232 RJ45 interfaces with software configurable Cisco pinouts, 2 x USB Ports, Front Panel Display and Keyboard, 2 x auto-sensing 10/100/1000 Ethernet Combo Ports (RJ45 or SFP), Cellular WWAN capability based on 4G LTE (ETSI Europe) with fallback networks (HSPA+, UMTS, EDGE and GPRS), integrated RJ45 V.92 modem, Micro SD Card Slot, Micro USB and RS232 RJ45 Console Admin Ports, advanced data encryption, user authentication and event management security features included, IPv6, COM port redirector, 15kv ESD, Dual AC Power, EU power adapter included.	https://www.perle.com/products/iolan-scglm-console-server.shtml	Serial Console Server: IOLAN SCG LM
04033032	IOLAN SCG50 R-LE Console Server: 48 x RS232 RJ45 interfaces with software configurable Cisco pinouts, 2 x USB Ports, Front Panel Display and Keyboard, 2 x auto-sensing 10/100/1000 Ethernet Combo Ports (RJ45 or SFP), Cellular WWAN capability based on 4G LTE (ETSI Europe) with fallback networks (HSPA+, UMTS, EDGE and GPRS), Micro SD Card Slot, Micro USB and RS232 RJ45 Console Admin Ports, advanced data encryption, user authentication and event management security features included, IPv6, COM port redirector, 15kv ESD, Dual AC Power, EU power adapter included.	https://www.perle.com/products/iolan-scgl-console-server.shtml	Serial Console Server: IOLAN SCG L

Part #	Description	Product Datasheet	Product Group
04033042	IOLAN SCG50 R-WM Console Server: 48 x RS232 RJ45 interfaces with software configurable Cisco pinouts, 2 x USB Ports, Front Panel Display and Keyboard, 2 x auto-sensing 10/100/1000 Ethernet Combo Ports (RJ45 or SFP), Wireless LAN (WiFi) client IEEE 802.11 a, b, g, n @ 2.4Ghz/5Ghz, integrated RJ45 V.92 modem, Micro SD Card Slot, Micro USB and RS232 RJ45 Console Admin Ports, advanced data encryption, user authentication and event management security features included, IPv6, COM port redirector, 15kv ESD, Dual AC Power, EU power adapter included.	https://www.perle.com/products/iolan-scgwm-console-server.shtml	Serial Console Server: IOLAN SCG WM
04033052	IOLAN SCG50 R-W Console Server: 48 x RS232 RJ45 interfaces with software configurable Cisco pinouts, 2 x USB Ports, Front Panel Display and Keyboard, 2 x auto-sensing 10/100/1000 Ethernet Combo Ports (RJ45 or SFP), Wireless LAN (WiFi) client IEEE 802.11 a, b, g, n @ 2.4Ghz/5Ghz, Micro SD Card Slot, Micro USB and RS232 RJ45 Console Admin Ports, advanced data encryption, user authentication and event management security features included, IPv6, COM port redirector, 15kv ESD, Dual AC Power, EU power adapter included.	https://www.perle.com/products/iolan-scgw-console-server.shtml	Serial Console Server: IOLAN SCG W
04033062	IOLAN SCG50 R-M Console Server: 48 x RS232 RJ45 interfaces with software configurable Cisco pinouts, 2 x USB Ports, Front Panel Display and Keyboard, 2 x auto-sensing 10/100/1000 Ethernet Combo Ports (RJ45 or SFP), integrated RJ45 V.92 modem, Micro SD Card Slot, Micro USB and RS232 RJ45 Console Admin Ports, advanced data encryption, user authentication and event management security features included, IPv6, COM port redirector, 15kv ESD, Dual AC Power, EU power adapter included.	https://www.perle.com/products/iolan-scgm-console-server.shtml	Serial Console Server: IOLAN SCG M
04033072	IOLAN SCG50 R Console Server: 48 x RS232 RJ45 interfaces with software configurable Cisco pinouts, 2 x USB Ports, Front Panel Display and Keyboard, 2 x auto-sensing 10/100/1000 Ethernet Combo Ports (RJ45 or SFP), Micro SD Card Slot, Micro USB and RS232 RJ45 Console Admin Ports, advanced data encryption, user authentication and event management security features included, IPv6, COM port redirector, 15kv ESD, Dual AC Power, EU power adapter included.	https://www.perle.com/products/iolan-scgru-console-server.shtml	Serial Console Server: IOLAN SCG R/U

Part #	Description	Product Datasheet	Product Group
04033122	IOLAN SCG18 U-LEWM Console Server: 18 x USB Ports, Front Panel Display and Keyboard, 2 x auto-sensing 10/100/1000 Ethernet Combo Ports (RJ45 or SFP), Cellular WWAN capability based on 4G LTE (ETSI Europe) with fallback networks (HSPA+, UMTS, EDGE and GPRS), Wireless LAN (WiFi) client IEEE 802.11 a, b, g, n @ 2.4Ghz/5Ghz,integrated RJ45 V.92 modem, Micro SD Card Slot, Expandable using IOLAN G16 RS232 Card and IOLAN G16 USB Card, Micro USB and RS232 RJ45 Console Admin Ports, advanced data encryption, user authentication and event management security features included, IPv6, COM port redirector, 15kv ESD, Dual AC Power, EU power adapter included.	https://www.perle.com/products/iolan-scglwm-console-server.shtml	Serial Console Server: IOLAN SCG LWM
04033132	IOLAN SCG18 U-LEW Console Server: 18 x USB Ports, Front Panel Display and Keyboard, 2 x auto-sensing 10/100/1000 Ethernet Combo Ports (RJ45 or SFP), Cellular WWAN capability based on 4G LTE (ETSI Europe) with fallback networks (HSPA+, UMTS, EDGE and GPRS), Wireless LAN (WiFi) client IEEE 802.11 a, b, g, n @ 2.4Ghz/5Ghz,Mico SD Card Slot, Expandable using IOLAN G16 RS232 Card and IOLAN G16 USB Card, Micro USB and RS232 RJ45 Console Admin Ports, advanced data encryption, user authentication and event management security features included, IPv6, COM port redirector, 15kv ESD, Dual AC Power, EU power adapter included.	https://www.perle.com/products/iolan-scglw-console-server.shtml	Serial Console Server: IOLAN SCG LW
04033142	IOLAN SCG18 U-LEM Console Server: 18 x USB Ports, Front Panel Display and Keyboard, 2 x auto-sensing 10/100/1000 Ethernet Combo Ports (RJ45 or SFP), Cellular WWAN capability based on 4G LTE (ETSI Europe) with fallback networks (HSPA+, UMTS, EDGE and GPRS), integrated RJ45 V.92 modem, Micro SD Card Slot, Expandable using IOLAN G16 RS232 Card and IOLAN G16 USB Card, Micro USB and RS232 RJ45 Console Admin Ports, advanced data encryption, user authentication and event management security features included, IPv6, COM port redirector, 15kv ESD, Dual AC Power, EU power adapter included.	https://www.perle.com/products/iolan-scglm-console-server.shtml	Serial Console Server: IOLAN SCG LM

Part #	Description	Product Datasheet	Product Group
04033152	IOLAN SCG18 U-LE Console Server: 18 x USB Ports, Front Panel Display and Keyboard, 2 x auto-sensing 10/100/1000 Ethernet Combo Ports (RJ45 or SFP), Cellular WWAN capability based on 4G LTE (ETSI Europe) with fallback networks (HSPA+, UMTS, EDGE and GPRS), Micro SD Card Slot, Expandable using IOLAN G16 RS232 Card and IOLAN G16 USB Card, Micro USB and RS232 RJ45 Console Admin Ports, advanced data encryption, user authentication and event management security features included, IPv6, COM port redirector, 15kv ESD, Dual AC Power, EU power adapter included.	https://www.perle.com/products/iolan-scgl-console-server.shtml	Serial Console Server: IOLAN SCG L
04033162	IOLAN SCG18 U-WM Console Server: 18 x USB Ports, Front Panel Display and Keyboard, 2 x auto-sensing 10/100/1000 Ethernet Combo Ports (RJ45 or SFP), Wireless LAN (WiFi) client IEEE 802.11 a, b, g, n @ 2.4Ghz/5Ghz, integrated RJ45 V.92 modem, Micro SD Card Slot, Expandable using IOLAN G16 RS232 Card and IOLAN G16 USB Card, Micro USB and RS232 RJ45 Console Admin Ports, advanced data encryption, user authentication and event management security features included, IPv6, COM port redirector, 15kv ESD, Dual AC Power, EU power adapter included.	https://www.perle.com/products/iolan-scgwm-console-server.shtml	Serial Console Server: IOLAN SCG WM
04033172	IOLAN SCG18 U-W Console Server: 18 x USB Ports, Front Panel Display and Keyboard, 2 x auto-sensing 10/100/1000 Ethernet Combo Ports (RJ45 or SFP), Wireless LAN (WiFi) client IEEE 802.11 a, b, g, n @ 2.4Ghz/5Ghz, Micro SD Card Slot, Expandable using IOLAN G16 RS232 Card and IOLAN G16 USB Card, Micro USB and RS232 RJ45 Console Admin Ports, advanced data encryption, user authentication and event management security features included, IPv6, COM port redirector, 15kv ESD, Dual AC Power, EU power adapter included.	https://www.perle.com/products/iolan-scgw-console-server.shtml	Serial Console Server: IOLAN SCG W
04033182	IOLAN SCG18 U-M Console Server: 18 x USB Ports, Front Panel Display and Keyboard, 2 x auto-sensing 10/100/1000 Ethernet Combo Ports (RJ45 or SFP), integrated RJ45 V.92 modem, Micro SD Card Slot, Expandable using IOLAN G16 RS232 Card and IOLAN G16 USB Card, Micro USB and RS232 RJ45 Console Admin Ports, advanced data encryption, user authentication and event management security features included, IPv6, COM port redirector, 15kv ESD, Dual AC Power, EU power adapter included.	https://www.perle.com/products/iolan-scgm-console-server.shtml	Serial Console Server: IOLAN SCG M

Part #	Description	Product Datasheet	Product Group
04033192	IOLAN SCG18 U Console Server: 18 x USB Ports, Front Panel Display and Keyboard, 2 x auto-sensing 10/100/1000 Ethernet Combo Ports (RJ45 or SFP), Micro SD Card Slot, Expandable using IOLAN G16 RS232 Card and IOLAN G16 USB Card, Micro USB and RS232 RJ45 Console Admin Ports, advanced data encryption, user authentication and event management security features included, IPv6, COM port redirector, 15kv ESD, Dual AC Power, EU power adapter included.	https://www.perle.com/products/iolan-scgru-console-server.shtml	Serial Console Server: IOLAN SCG R/U
04033242	IOLAN SCG34 U-LEWM Console Server: 34 x USB Ports, Front Panel Display and Keyboard, 2 x auto-sensing 10/100/1000 Ethernet Combo Ports (RJ45 or SFP), Cellular WWAN capability based on 4G LTE (ETSI Europe) with fallback networks (HSPA+, UMTS, EDGE and GPRS), Wireless LAN (WiFi) client IEEE 802.11 a, b, g, n @ 2.4Ghz/5Ghz,integrated RJ45 V.92 modem, Micro SD Card Slot, Expandable using IOLAN G16 RS232 Card and IOLAN G16 USB Card, Micro USB and RS232 RJ45 Console Admin Ports, advanced data encryption, user authentication and event management security features included, IPv6, COM port redirector, 15kv ESD, Dual AC Power, EU power adapter included.	https://www.perle.com/products/iolan-scglwm-console-server.shtml	Serial Console Server: IOLAN SCG LWM
04033252	IOLAN SCG34 U-LEW Console Server: 34 x USB Ports, Front Panel Display and Keyboard, 2 x auto-sensing 10/100/1000 Ethernet Combo Ports (RJ45 or SFP), Cellular WWAN capability based on 4G LTE (ETSI Europe) with fallback networks (HSPA+, UMTS, EDGE and GPRS), Wireless LAN (WiFi) client IEEE 802.11 a, b, g, n @ 2.4Ghz/5Ghz,Mico SD Card Slot, Expandable using IOLAN G16 RS232 Card and IOLAN G16 USB Card, Micro USB and RS232 RJ45 Console Admin Ports, advanced data encryption, user authentication and event management security features included, IPv6, COM port redirector, 15kv ESD, Dual AC Power, EU power adapter included.	https://www.perle.com/products/iolan-scglw-console-server.shtml	Serial Console Server: IOLAN SCG LW

Part #	Description	Product Datasheet	Product Group
04033262	IOLAN SCG34 U-LEM Console Server: 34 x USB Ports, Front Panel Display and Keyboard, 2 x auto-sensing 10/100/1000 Ethernet Combo Ports (RJ45 or SFP), Cellular WWAN capability based on 4G LTE (ETSI Europe) with fallback networks (HSPA+, UMTS, EDGE and GPRS), integrated RJ45 V.92 modem, Micro SD Card Slot, Expandable using IOLAN G16 RS232 Card and IOLAN G16 USB Card, Micro USB and RS232 RJ45 Console Admin Ports, advanced data encryption, user authentication and event management security features included, IPv6, COM port redirector, 15kv ESD, Dual AC Power, EU power adapter included.	https://www.perle.com/products/iolan-scglm-console-server.shtml	Serial Console Server: IOLAN SCG LM
04033272	IOLAN SCG34 U-LE Console Server: 34 x USB Ports, Front Panel Display and Keyboard, 2 x auto-sensing 10/100/1000 Ethernet Combo Ports (RJ45 or SFP), Cellular WWAN capability based on 4G LTE (ETSI Europe) with fallback networks (HSPA+, UMTS, EDGE and GPRS), Micro SD Card Slot, Expandable using IOLAN G16 RS232 Card and IOLAN G16 USB Card, Micro USB and RS232 RJ45 Console Admin Ports, advanced data encryption, user authentication and event management security features included, IPv6, COM port redirector, 15kv ESD, Dual AC Power, EU power adapter included.	https://www.perle.com/products/iolan-scgl-console-server.shtml	Serial Console Server: IOLAN SCG L
04033282	IOLAN SCG34 U-WM Console Server: 34 x USB Ports, Front Panel Display and Keyboard, 2 x auto-sensing 10/100/1000 Ethernet Combo Ports (RJ45 or SFP), Wireless LAN (WiFi) client IEEE 802.11 a, b, g, n @ 2.4Ghz/5Ghz, integrated RJ45 V.92 modem, Micro SD Card Slot, Expandable using IOLAN G16 RS232 Card and IOLAN G16 USB Card, Micro USB and RS232 RJ45 Console Admin Ports, advanced data encryption, user authentication and event management security features included, IPv6, COM port redirector, 15kv ESD, Dual AC Power, EU power adapter included.	https://www.perle.com/products/iolan-scgwm-console-server.shtml	Serial Console Server: IOLAN SCG WM
04033292	IOLAN SCG34 U-W Console Server: 34 x USB Ports, Front Panel Display and Keyboard, 2 x auto-sensing 10/100/1000 Ethernet Combo Ports (RJ45 or SFP), Wireless LAN (WiFi) client IEEE 802.11 a, b, g, n @ 2.4Ghz/5Ghz, Micro SD Card Slot, Expandable using IOLAN G16 RS232 Card and IOLAN G16 USB Card, Micro USB and RS232 RJ45 Console Admin Ports, advanced data encryption, user authentication and event management security features included, IPv6, COM port redirector, 15kv ESD, Dual AC Power, EU power adapter included.	https://www.perle.com/products/iolan-scgw-console-server.shtml	Serial Console Server: IOLAN SCG W

Part #	Description	Product Datasheet	Product Group
04033302	IOLAN SCG34 U-M Console Server: 34 x USB Ports, Front Panel Display and Keyboard, 2 x auto-sensing 10/100/1000 Ethernet Combo Ports (RJ45 or SFP), integrated RJ45 V.92 modem, Micro SD Card Slot, Expandable using IOLAN G16 RS232 Card and IOLAN G16 USB Card, Micro USB and RS232 RJ45 Console Admin Ports, advanced data encryption, user authentication and event management security features included, IPv6, COM port redirector, 15kv ESD, Dual AC Power, EU power adapter included.	https://www.perle.com/products/iolan-scgm-console-server.shtml	Serial Console Server: IOLAN SCG M
04033312	IOLAN SCG34 U Console Server: 34 x USB Ports, Front Panel Display and Keyboard, 2 x auto-sensing 10/100/1000 Ethernet Combo Ports (RJ45 or SFP), Micro SD Card Slot, Expandable using IOLAN G16 RS232 Card and IOLAN G16 USB Card, Micro USB and RS232 RJ45 Console Admin Ports, advanced data encryption, user authentication and event management security features included, IPv6, COM port redirector, 15kv ESD, Dual AC Power, EU power adapter included.	https://www.perle.com/products/iolan-scgru-console-server.shtml	Serial Console Server: IOLAN SCG R/U
04033362	IOLAN SCG50 U-LEWM Console Server: 50 x USB Ports, Front Panel Display and Keyboard, 2 x auto-sensing 10/100/1000 Ethernet Combo Ports (RJ45 or SFP), Cellular WWAN capability based on 4G LTE (ETSI Europe) with fallback networks (HSPA+, UMTS, EDGE and GPRS), Wireless LAN (WiFi) client IEEE 802.11 a, b, g, n @ 2.4Ghz/5Ghz,integrated RJ45 V.92 modem, Micro SD Card Slot, Micro USB and RS232 RJ45 Console Admin Ports, advanced data encryption, user authentication and event management security features included, IPv6, COM port redirector, 15kv ESD, Dual AC Power, EU power adapter included.	https://www.perle.com/products/iolan-scglwm-console-server.shtml	Serial Console Server: IOLAN SCG LWM
04033372	IOLAN SCG50 U-LEW Console Server: 50 x USB Ports, Front Panel Display and Keyboard, 2 x auto-sensing 10/100/1000 Ethernet Combo Ports (RJ45 or SFP), Cellular WWAN capability based on 4G LTE (ETSI Europe) with fallback networks (HSPA+, UMTS, EDGE and GPRS), Wireless LAN (WiFi) client IEEE 802.11 a, b, g, n @ 2.4Ghz/5Ghz,Mico SD Card Slot, Micro USB and RS232 RJ45 Console Admin Ports, advanced data encryption, user authentication and event management security features included, IPv6, COM port redirector, 15kv ESD, Dual AC Power, EU power adapter included.	https://www.perle.com/products/iolan-scglw-console-server.shtml	Serial Console Server: IOLAN SCG LW

Part #	Description	Product Datasheet	Product Group
04033382	IOLAN SCG50 U-LEM Console Server: 50 x USB Ports, Front Panel Display and Keyboard, 2 x auto-sensing 10/100/1000 Ethernet Combo Ports (RJ45 or SFP), Cellular WWAN capability based on 4G LTE (ETSI Europe) with fallback networks (HSPA+, UMTS, EDGE and GPRS), integrated RJ45 V.92 modem, Micro SD Card Slot, Micro USB and RS232 RJ45 Console Admin Ports, advanced data encryption, user authentication and event management security features included, IPv6, COM port redirector, 15kv ESD, Dual AC Power, EU power adapter included.	https://www.perle.com/products/iolan-scglm-console-server.shtml	Serial Console Server: IOLAN SCG LM
04033392	IOLAN SCG50 U-LE Console Server: 50 x USB Ports, Front Panel Display and Keyboard, 2 x auto-sensing 10/100/1000 Ethernet Combo Ports (RJ45 or SFP), Cellular WWAN capability based on 4G LTE (ETSI Europe) with fallback networks (HSPA+, UMTS, EDGE and GPRS), Micro SD Card Slot, Micro USB and RS232 RJ45 Console Admin Ports, advanced data encryption, user authentication and event management security features included, IPv6, COM port redirector, 15kv ESD, Dual AC Power, EU power adapter included.	https://www.perle.com/products/iolan-scgl-console-server.shtml	Serial Console Server: IOLAN SCG L
04033402	IOLAN SCG50 U-WM Console Server: 50 x USB Ports, Front Panel Display and Keyboard, 2 x auto-sensing 10/100/1000 Ethernet Combo Ports (RJ45 or SFP), Wireless LAN (WiFi) client IEEE 802.11 a, b, g, n @ 2.4Ghz/5Ghz, integrated RJ45 V.92 modem, Micro SD Card Slot, Micro USB and RS232 RJ45 Console Admin Ports, advanced data encryption, user authentication and event management security features included, IPv6, COM port redirector, 15kv ESD, Dual AC Power, EU power adapter included.	https://www.perle.com/products/iolan-scgwm-console-server.shtml	Serial Console Server: IOLAN SCG WM
04033412	IOLAN SCG50 U-W Console Server: 50 x USB Ports, Front Panel Display and Keyboard, 2 x auto-sensing 10/100/1000 Ethernet Combo Ports (RJ45 or SFP), Wireless LAN (WiFi) client IEEE 802.11 a, b, g, n @ 2.4Ghz/5Ghz, Micro SD Card Slot, Micro USB and RS232 RJ45 Console Admin Ports, advanced data encryption, user authentication and event management security features included, IPv6, COM port redirector, 15kv ESD, Dual AC Power, EU power adapter included.	https://www.perle.com/products/iolan-scgw-console-server.shtml	Serial Console Server: IOLAN SCG W

Part #	Description	Product Datasheet	Product Group
04033422	IOLAN SCG50 U-M Console Server: 50 x USB Ports, Front Panel Display and Keyboard, 2 x auto-sensing 10/100/1000 Ethernet Combo Ports (RJ45 or SFP), integrated RJ45 V.92 modem, Micro SD Card Slot, Micro USB and RS232 RJ45 Console Admin Ports, advanced data encryption, user authentication and event management security features included, IPv6, COM port redirector, 15kv ESD, Dual AC Power, EU power adapter included.	https://www.perle.com/products/iolan-scgm-console-server.shtml	Serial Console Server: IOLAN SCG M
04033432	IOLAN SCG50 U Console Server: 50 x USB Ports, Front Panel Display and Keyboard, 2 x auto-sensing 10/100/1000 Ethernet Combo Ports (RJ45 or SFP), Micro SD Card Slot, Micro USB and RS232 RJ45 Console Admin Ports, advanced data encryption, user authentication and event management security features included, IPv6, COM port redirector, 15kv ESD, Dual AC Power, EU power adapter included.	https://www.perle.com/products/iolan-scgru-console-server.shtml	Serial Console Server: IOLAN SCG R/U
04033482	IOLAN SCG34 RU-LEWM Console Server: 16 x RS232 RJ45 interfaces with software configurable Cisco pinouts, 18 x USB Ports, Front Panel Display and Keyboard, 2 x auto-sensing 10/100/1000 Ethernet Combo Ports (RJ45 or SFP), Cellular WWAN capability based on 4G LTE (ETSI Europe) with fallback networks (HSPA+, UMTS, EDGE and GPRS), Wireless LAN (WiFi) client IEEE 802.11 a, b, g, n @ 2.4Ghz/5Ghz,integrated RJ45 V.92 modem, Micro SD Card Slot, Expandable using IOLAN G16 RS232 Card and IOLAN G16 USB Card, Micro USB and RS232 RJ45 Console Admin Ports, advanced data encryption, user authentication and event management security features included, IPv6, COM port redirector, 15kv ESD, Dual AC Power, EU power adapter included.	https://www.perle.com/products/iolan-scglwm-console-server.shtml	Serial Console Server: IOLAN SCG LWM
04033492	IOLAN SCG34 RU-LEW Console Server: 16 x RS232 RJ45 interfaces with software configurable Cisco pinouts, 18 x USB Ports, Front Panel Display and Keyboard, 2 x auto-sensing 10/100/1000 Ethernet Combo Ports (RJ45 or SFP), Cellular WWAN capability based on 4G LTE (ETSI Europe) with fallback networks (HSPA+, UMTS, EDGE and GPRS), Wireless LAN (WiFi) client IEEE 802.11 a, b, g, n @ 2.4Ghz/5Ghz,Mico SD Card Slot, Expandable using IOLAN G16 RS232 Card and IOLAN G16 USB Card, Micro USB and RS232 RJ45 Console Admin Ports, advanced data encryption, user authentication and event management security features included, IPv6, COM port redirector, 15kv ESD, Dual AC Power, EU power adapter included.	https://www.perle.com/products/iolan-scglw-console-server.shtml	Serial Console Server: IOLAN SCG LW

Part #	Description	Product Datasheet	Product Group
04033502	IOLAN SCG34 RU-LEM Console Server: 16 x RS232 RJ45 interfaces with software configurable Cisco pinouts, 18 x USB Ports, Front Panel Display and Keyboard, 2 x auto-sensing 10/100/1000 Ethernet Combo Ports (RJ45 or SFP), Cellular WWAN capability based on 4G LTE (ETSI Europe) with fallback networks (HSPA+, UMTS, EDGE and GPRS), integrated RJ45 V.92 modem, Micro SD Card Slot, Expandable using IOLAN G16 RS232 Card and IOLAN G16 USB Card, Micro USB and RS232 RJ45 Console Admin Ports, advanced data encryption, user authentication and event management security features included, IPv6, COM port redirector, 15kv ESD, Dual AC Power, EU power adapter included.	https://www.perle.com/products/iolan-scglm-console-server.shtml	Serial Console Server: IOLAN SCG LM
04033512	IOLAN SCG34 RU-LE Console Server: 16 x RS232 RJ45 interfaces with software configurable Cisco pinouts, 18 x USB Ports, Front Panel Display and Keyboard, 2 x auto-sensing 10/100/1000 Ethernet Combo Ports (RJ45 or SFP), Cellular WWAN capability based on 4G LTE (ETSI Europe) with fallback networks (HSPA+, UMTS, EDGE and GPRS), Micro SD Card Slot, Expandable using IOLAN G16 RS232 Card and IOLAN G16 USB Card, Micro USB and RS232 RJ45 Console Admin Ports, advanced data encryption, user authentication and event management security features included, IPv6, COM port redirector, 15kv ESD, Dual AC Power, EU power adapter included.	https://www.perle.com/products/iolan-scgl-console-server.shtml	Serial Console Server: IOLAN SCG L
04033522	IOLAN SCG34 RU-WM Console Server: 16 x RS232 RJ45 interfaces with software configurable Cisco pinouts, 18 x USB Ports, Front Panel Display and Keyboard, 2 x auto-sensing 10/100/1000 Ethernet Combo Ports (RJ45 or SFP), Wireless LAN (WiFi) client IEEE 802.11 a, b, g, n @ 2.4Ghz/5Ghz, integrated RJ45 V.92 modem, Micro SD Card Slot, Expandable using IOLAN G16 RS232 Card and IOLAN G16 USB Card, Micro USB and RS232 RJ45 Console Admin Ports, advanced data encryption, user authentication and event management security features included, IPv6, COM port redirector, 15kv ESD, Dual AC Power, EU power adapter included.	https://www.perle.com/products/iolan-scgwm-console-server.shtml	Serial Console Server: IOLAN SCG WM

Part #	Description	Product Datasheet	Product Group
04033532	IOLAN SCG34 RU-W Console Server: 16 x RS232 RJ45 interfaces with software configurable Cisco pinouts, 18 x USB Ports, Front Panel Display and Keyboard, 2 x auto-sensing 10/100/1000 Ethernet Combo Ports (RJ45 or SFP), Wireless LAN (WiFi) client IEEE 802.11 a, b, g, n @ 2.4Ghz/5Ghz, Mico SD Card Slot, Expandable using IOLAN G16 RS232 Card and IOLAN G16 USB Card, Micro USB and RS232 RJ45 Console Admin Ports, advanced data encryption, user authentication and event management security features included, IPv6, COM port redirector, 15kv ESD, Dual AC Power, EU power adapter included.	https://www.perle.com/products/iolan-scgw-console-server.shtml	Serial Console Server: IOLAN SCG W
04033542	IOLAN SCG34 RU-M Console Server: 16 x RS232 RJ45 interfaces with software configurable Cisco pinouts, 18 x USB Ports, Front Panel Display and Keyboard, 2 x auto-sensing 10/100/1000 Ethernet Combo Ports (RJ45 or SFP), integrated RJ45 V.92 modem, Micro SD Card Slot, Expandable using IOLAN G16 RS232 Card and IOLAN G16 USB Card, Micro USB and RS232 RJ45 Console Admin Ports, advanced data encryption, user authentication and event management security features included, IPv6, COM port redirector, 15kv ESD, Dual AC Power, EU power adapter included.	https://www.perle.com/products/iolan-scgm-console-server.shtml	Serial Console Server: IOLAN SCG M
04033552	IOLAN SCG34 RU Console Server: 16 x RS232 RJ45 interfaces with software configurable Cisco pinouts, 18 x USB Ports, Front Panel Display and Keyboard, 2 x auto-sensing 10/100/1000 Ethernet Combo Ports (RJ45 or SFP), Micro SD Card Slot, Expandable using IOLAN G16 RS232 Card and IOLAN G16 USB Card, Micro USB and RS232 RJ45 Console Admin Ports, advanced data encryption, user authentication and event management security features included, IPv6, COM port redirector, 15kv ESD, Dual AC Power, EU power adapter included.	https://www.perle.com/products/iolan-scgru-console-server.shtml	Serial Console Server: IOLAN SCG R/U

Part #	Description	Product Datasheet	Product Group
04033602	IOLAN SCG50 RRU-LEWM Console Server: 32 x RS232 RJ45 interfaces with software configurable Cisco pinouts, 18 x USB Ports, Front Panel Display and Keyboard, 2 x auto-sensing 10/100/1000 Ethernet Combo Ports (RJ45 or SFP), Cellular WWAN capability based on 4G LTE (ETSI Europe) with fallback networks (HSPA+, UMTS, EDGE and GPRS), Wireless LAN (WiFi) client IEEE 802.11 a, b, g, n @ 2.4Ghz/5Ghz,integrated RJ45 V.92 modem, Micro SD Card Slot, Micro USB and RS232 RJ45 Console Admin Ports, advanced data encryption, user authentication and event management security features included, IPv6, COM port redirector, 15kv ESD, Dual AC Power, EU power adapter included.	https://www.perle.com/products/iolan-scglwm-console-server.shtml	Serial Console Server: IOLAN SCG LWM
04033612	IOLAN SCG50 RRU-LEW Console Server: 32 x RS232 RJ45 interfaces with software configurable Cisco pinouts, 18 x USB Ports, Front Panel Display and Keyboard, 2 x auto-sensing 10/100/1000 Ethernet Combo Ports (RJ45 or SFP), Cellular WWAN capability based on 4G LTE (ETSI Europe) with fallback networks (HSPA+, UMTS, EDGE and GPRS), Wireless LAN (WiFi) client IEEE 802.11 a, b, g, n @ 2.4Ghz/5Ghz,Mico SD Card Slot, Micro USB and RS232 RJ45 Console Admin Ports, advanced data encryption, user authentication and event management security features included, IPv6, COM port redirector, 15kv ESD, Dual AC Power, EU power adapter included.	https://www.perle.com/products/iolan-scglw-console-server.shtml	Serial Console Server: IOLAN SCG LW
04033622	IOLAN SCG50 RRU-LEM Console Server: 32 x RS232 RJ45 interfaces with software configurable Cisco pinouts, 18 x USB Ports, Front Panel Display and Keyboard, 2 x auto-sensing 10/100/1000 Ethernet Combo Ports (RJ45 or SFP), Cellular WWAN capability based on 4G LTE (ETSI Europe) with fallback networks (HSPA+, UMTS, EDGE and GPRS), integrated RJ45 V.92 modem, Micro SD Card Slot, Micro USB and RS232 RJ45 Console Admin Ports, advanced data encryption, user authentication and event management security features included, IPv6, COM port redirector, 15kv ESD, Dual AC Power, EU power adapter included.	https://www.perle.com/products/iolan-scglm-console-server.shtml	Serial Console Server: IOLAN SCG LM

Part #	Description	Product Datasheet	Product Group
04033632	IOLAN SCG50 RRU-LE Console Server: 32 x RS232 RJ45 interfaces with software configurable Cisco pinouts, 18 x USB Ports, Front Panel Display and Keyboard, 2 x auto-sensing 10/100/1000 Ethernet Combo Ports (RJ45 or SFP), Cellular WWAN capability based on 4G LTE (ETSI Europe) with fallback networks (HSPA+, UMTS, EDGE and GPRS), Micro SD Card Slot, Micro USB and RS232 RJ45 Console Admin Ports, advanced data encryption, user authentication and event management security features included, IPv6, COM port redirector, 15kv ESD, Dual AC Power, EU power adapter included.	https://www.perle.com/products/iolan-scgl-console-server.shtml	Serial Console Server: IOLAN SCG L
04033642	IOLAN SCG50 RRU-WM Console Server: 32 x RS232 RJ45 interfaces with software configurable Cisco pinouts, 18 x USB Ports, Front Panel Display and Keyboard, 2 x auto-sensing 10/100/1000 Ethernet Combo Ports (RJ45 or SFP), Wireless LAN (WiFi) client IEEE 802.11 a, b, g, n @ 2.4Ghz/5Ghz, integrated RJ45 V.92 modem, Micro SD Card Slot, Micro USB and RS232 RJ45 Console Admin Ports, advanced data encryption, user authentication and event management security features included, IPv6, COM port redirector, 15kv ESD, Dual AC Power, EU power adapter included.	https://www.perle.com/products/iolan-scgwm-console-server.shtml	Serial Console Server: IOLAN SCG WM
04033652	IOLAN SCG50 RRU-W Console Server: 32 x RS232 RJ45 interfaces with software configurable Cisco pinouts, 18 x USB Ports, Front Panel Display and Keyboard, 2 x auto-sensing 10/100/1000 Ethernet Combo Ports (RJ45 or SFP), Wireless LAN (WiFi) client IEEE 802.11 a, b, g, n @ 2.4Ghz/5Ghz, Micro SD Card Slot, Micro USB and RS232 RJ45 Console Admin Ports, advanced data encryption, user authentication and event management security features included, IPv6, COM port redirector, 15kv ESD, Dual AC Power, EU power adapter included.	https://www.perle.com/products/iolan-scgw-console-server.shtml	Serial Console Server: IOLAN SCG W
04033662	IOLAN SCG50 RRU-M Console Server: 32 x RS232 RJ45 interfaces with software configurable Cisco pinouts, 18 x USB Ports, Front Panel Display and Keyboard, 2 x auto-sensing 10/100/1000 Ethernet Combo Ports (RJ45 or SFP), integrated RJ45 V.92 modem, Micro SD Card Slot, Micro USB and RS232 RJ45 Console Admin Ports, advanced data encryption, user authentication and event management security features included, IPv6, COM port redirector, 15kv ESD, Dual AC Power, EU power adapter included.	https://www.perle.com/products/iolan-scgm-console-server.shtml	Serial Console Server: IOLAN SCG M

Part #	Description	Product Datasheet	Product Group
04033672	IOLAN SCG50 RRU Console Server: 32 x RS232 RJ45 interfaces with software configurable Cisco pinouts, 18 x USB Ports, Front Panel Display and Keyboard, 2 x auto-sensing 10/100/1000 Ethernet Combo Ports (RJ45 or SFP), Micro SD Card Slot, Micro USB and RS232 RJ45 Console Admin Ports, advanced data encryption, user authentication and event management security features included, IPv6, COM port redirector, 15kv ESD, Dual AC Power, EU power adapter included.	https://www.perle.com/products/iolan-scgru-console-server.shtml	Serial Console Server: IOLAN SCG R/U
04033722	IOLAN SCG50 RUU-LEWM Console Server: 16 x RS232 RJ45 interfaces with software configurable Cisco pinouts, 34 x USB Ports, Front Panel Display and Keyboard, 2 x auto-sensing 10/100/1000 Ethernet Combo Ports (RJ45 or SFP), Cellular WWAN capability based on 4G LTE (ETSI Europe) with fallback networks (HSPA+, UMTS, EDGE and GPRS), Wireless LAN (WiFi) client IEEE 802.11 a, b, g, n @ 2.4Ghz/5Ghz,integrated RJ45 V.92 modem, Micro SD Card Slot, Micro USB and RS232 RJ45 Console Admin Ports, advanced data encryption, user authentication and event management security features included, IPv6, COM port redirector, 15kv ESD, Dual AC Power, EU power adapter included.	https://www.perle.com/products/iolan-scglwm-console-server.shtml	Serial Console Server: IOLAN SCG LWM
04033732	IOLAN SCG50 RUU-LEW Console Server: 16 x RS232 RJ45 interfaces with software configurable Cisco pinouts, 34 x USB Ports, Front Panel Display and Keyboard, 2 x auto-sensing 10/100/1000 Ethernet Combo Ports (RJ45 or SFP), Cellular WWAN capability based on 4G LTE (ETSI Europe) with fallback networks (HSPA+, UMTS, EDGE and GPRS), Wireless LAN (WiFi) client IEEE 802.11 a, b, g, n @ 2.4Ghz/5Ghz,Mico SD Card Slot, Micro USB and RS232 RJ45 Console Admin Ports, advanced data encryption, user authentication and event management security features included, IPv6, COM port redirector, 15kv ESD, Dual AC Power, EU power adapter included.	https://www.perle.com/products/iolan-scglw-console-server.shtml	Serial Console Server: IOLAN SCG LW

Part #	Description	Product Datasheet	Product Group
04033742	IOLAN SCG50 RUU-LEM Console Server: 16 x RS232 RJ45 interfaces with software configurable Cisco pinouts, 34 x USB Ports, Front Panel Display and Keyboard, 2 x auto-sensing 10/100/1000 Ethernet Combo Ports (RJ45 or SFP), Cellular WWAN capability based on 4G LTE (ETSI Europe) with fallback networks (HSPA+, UMTS, EDGE and GPRS), integrated RJ45 V.92 modem, Micro SD Card Slot, Micro USB and RS232 RJ45 Console Admin Ports, advanced data encryption, user authentication and event management security features included, IPv6, COM port redirector, 15kv ESD, Dual AC Power, EU power adapter included.	https://www.perle.com/products/iolan-scglm-console-server.shtml	Serial Console Server: IOLAN SCG LM
04033752	IOLAN SCG50 RUU-LE Console Server: 16 x RS232 RJ45 interfaces with software configurable Cisco pinouts, 34 x USB Ports, Front Panel Display and Keyboard, 2 x auto-sensing 10/100/1000 Ethernet Combo Ports (RJ45 or SFP), Cellular WWAN capability based on 4G LTE (ETSI Europe) with fallback networks (HSPA+, UMTS, EDGE and GPRS), Micro SD Card Slot, Micro USB and RS232 RJ45 Console Admin Ports, advanced data encryption, user authentication and event management security features included, IPv6, COM port redirector, 15kv ESD, Dual AC Power, EU power adapter included.	https://www.perle.com/products/iolan-scgl-console-server.shtml	Serial Console Server: IOLAN SCG L
04033762	IOLAN SCG50 RUU-WM Console Server: 16 x RS232 RJ45 interfaces with software configurable Cisco pinouts, 34 x USB Ports, Front Panel Display and Keyboard, 2 x auto-sensing 10/100/1000 Ethernet Combo Ports (RJ45 or SFP), Wireless LAN (WiFi) client IEEE 802.11 a, b, g, n @ 2.4Ghz/5Ghz, integrated RJ45 V.92 modem, Micro SD Card Slot, Micro USB and RS232 RJ45 Console Admin Ports, advanced data encryption, user authentication and event management security features included, IPv6, COM port redirector, 15kv ESD, Dual AC Power, EU power adapter included.	https://www.perle.com/products/iolan-scgwm-console-server.shtml	Serial Console Server: IOLAN SCG WM
04033772	IOLAN SCG50 RUU-W Console Server: 16 x RS232 RJ45 interfaces with software configurable Cisco pinouts, 34 x USB Ports, Front Panel Display and Keyboard, 2 x auto-sensing 10/100/1000 Ethernet Combo Ports (RJ45 or SFP), Wireless LAN (WiFi) client IEEE 802.11 a, b, g, n @ 2.4Ghz/5Ghz, Micro SD Card Slot, Micro USB and RS232 RJ45 Console Admin Ports, advanced data encryption, user authentication and event management security features included, IPv6, COM port redirector, 15kv ESD, Dual AC Power, EU power adapter included.	https://www.perle.com/products/iolan-scgw-console-server.shtml	Serial Console Server: IOLAN SCG W

Part #	Description	Product Datasheet	Product Group
04033782	IOLAN SCG50 RUU-M Console Server: 16 x RS232 RJ45 interfaces with software configurable Cisco pinouts, 34 x USB Ports, Front Panel Display and Keyboard, 2 x auto-sensing 10/100/1000 Ethernet Combo Ports (RJ45 or SFP), integrated RJ45 V.92 modem, Micro SD Card Slot, Micro USB and RS232 RJ45 Console Admin Ports, advanced data encryption, user authentication and event management security features included, IPv6, COM port redirector, 15kv ESD, Dual AC Power, EU power adapter included.	https://www.perle.com/products/iolan-scgm-console-server.shtml	Serial Console Server: IOLAN SCG M
04033792	IOLAN SCG50 RUU Console Server: 16 x RS232 RJ45 interfaces with software configurable Cisco pinouts, 34 x USB Ports, Front Panel Display and Keyboard, 2 x auto-sensing 10/100/1000 Ethernet Combo Ports (RJ45 or SFP), Micro SD Card Slot, Micro USB and RS232 RJ45 Console Admin Ports, advanced data encryption, user authentication and event management security features included, IPv6, COM port redirector, 15kv ESD, Dual AC Power, EU power adapter included.	https://www.perle.com/products/iolan-scgru-console-server.shtml	Serial Console Server: IOLAN SCG R/U
04033800	IOLAN G16 RS232 Card: Interface Module with 16 x RS232 RJ45 interfaces with software configurable Cisco pinouts. Field upgradeable accessory to add ports to expandable IOLAN SCG Console Servers.	https://www.perle.com/products/product_detail.asp?a=4&i=04033800&c=1321	Accessories: IOLAN SCG
04033810	IOLAN G16 USB Card: Interface Module with 16 x USB Ports. Field upgradeable accessory to add ports to expandable IOLAN SCG Console Servers.	https://www.perle.com/products/product_detail.asp?a=4&i=04033810&c=1321	Accessories: IOLAN SCG
05040782	S-100-S1ST20U - Fast Ethernet Media Converter: 100Base-TX (RJ-45) [100 m/328 ft.] to 100Base-BX 1310nm TX / 1550nm RX single strand fiber, single mode (ST) [20 km/12.4 miles] - EU Power Cord	https://www.perle.com/products/fast-ethernet-media-converters.shtml	Media Converter: S-100
05040792	S-100-S1ST20D - Fast Ethernet Media Converter: 100Base-TX (RJ-45) [100 m/328 ft.] to 100Base-BX 1550nm TX / 1310nm RX single strand fiber, single mode (ST) [20 km/12.4 miles] - EU Power Cord	https://www.perle.com/products/fast-ethernet-media-converters.shtml	Media Converter: S-100
05040802	S-100-M1ST2D - Fast Ethernet Media Converter: 100Base-TX (RJ-45) [100 m/328 ft.] to 100Base-BX 1550nm TX / 1310nm RX single strand fiber, multimode (ST) [2 km/1.2 miles] - EU Power Cord	https://www.perle.com/products/fast-ethernet-media-converters.shtml	Media Converter: S-100
05040812	S-100-M1ST2U - Fast Ethernet Media Converter: 100Base-TX (RJ-45) [100 m/328 ft.] to 100Base-BX 1310nm TX / 1550nm RX single strand fiber, multimode (ST) [2 km/1.2 miles] - EU Power Cord	https://www.perle.com/products/fast-ethernet-media-converters.shtml	Media Converter: S-100

Part #	Description	Product Datasheet	Product Group
05040822	S-110-S1ST20U - 10/100Base-TX Media and Rate Converter: 10/100Base-TX (RJ-45) [100 m/328 ft.] to 100Base-BX 1310nm TX / 1550nm RX single strand fiber, single mode (ST) [20 km/12.4 miles] - EU Power Cord	https://www.perle.com/products/10-100-converters.shtml	Media Converter: S-110
05040832	S-110-S1ST20D - 10/100Base-TX Media and Rate Converter: 10/100Base-TX (RJ-45) [100 m/328 ft.] to 100Base-BX 1550nm TX / 1310nm RX single strand fiber, single mode (ST) [20 km/12.4 miles] - EU Power Cord	https://www.perle.com/products/10-100-converters.shtml	Media Converter: S-110
05040842	S-110-M1ST2D - 10/100Base-TX Media and Rate Converter: 10/100Base-TX (RJ-45) [100 m/328 ft.] to 100Base-BX 1550nm TX / 1310nm RX single strand fiber, multimode (ST) [2 km/1.2 miles] - EU Power Cord	https://www.perle.com/products/10-100-converters.shtml	Media Converter: S-110
05040852	S-110-M1ST2U - 10/100Base-TX Media and Rate Converter: 10/100Base-TX (RJ-45) [100 m/328 ft.] to 100Base-BX 1310nm TX / 1550nm RX single strand fiber, multimode (ST) [2 km/1.2 miles] - EU Power Cord	https://www.perle.com/products/10-100-converters.shtml	Media Converter: S-110
05040862	S-1110-M1SC05D - 10/100/1000Base-T Media and Rate Converter: 10/100/1000BASE-T (RJ-45) [100 m/328 ft.] to 1000BASE-BX 1550nm TX / 1310nm RX single strand fiber, multimode (SC) [500 m/1640 ft] - EU Power Cord	https://www.perle.com/products/10-100-1000-media-converters.shtml	Media Converter: S-1110
05040872	S-1110-M1SC05U - 10/100/1000Base-T Media and Rate Converter: 10/100/1000BASE-T (RJ-45) [100 m/328 ft.] to 1000BASE-BX 1310nm TX / 1550nm RX single strand fiber, multimode (SC) [500 m/1640 ft] - EU Power Cord	https://www.perle.com/products/10-100-1000-media-converters.shtml	Media Converter: S-1110
05040882	S-1000-M1SC05D - Gigabit Media Converter: 1000BASE-T (RJ-45) [100 m/328 ft.] to 1000BASE-BX 1550nm TX / 1310nm RX single strand fiber, multimode (SC) [500 m/1640 ft] - EU Power Cord	https://www.perle.com/products/gigabit-media-converters.shtml	Media Converter: S-1000
05040892	S-1000-M1SC05U - Gigabit Media Converter: 1000BASE-T (RJ-45) [100 m/328 ft.] to 1000BASE-BX 1310nm TX / 1550nm RX single strand fiber, multimode (SC) [500 m/1640 ft] - EU Power Cord	https://www.perle.com/products/gigabit-media-converters.shtml	Media Converter: S-1000
05040902	S-110-M1SC2D - 10/100Base-TX Media and Rate Converter: 10/100Base-TX (RJ-45) [100 m/328 ft.] to 100Base-BX 1550nm TX / 1310nm RX single strand fiber, multimode (SC) [2 km/1.2 miles] - EU Power Cord	https://www.perle.com/products/10-100-converters.shtml	Media Converter: S-110
05040912	S-110-M1SC2U - 10/100Base-TX Media and Rate Converter: 10/100Base-TX (RJ-45) [100 m/328 ft.] to 100Base-BX 1310nm TX / 1550nm RX single strand fiber, multimode (SC) [2 km/1.2 miles] - EU Power Cord	https://www.perle.com/products/10-100-converters.shtml	Media Converter: S-110
05040922	S-100-M1SC2D - Fast Ethernet Media Converter: 100Base-TX (RJ-45) [100 m/328 ft.] to 100Base-BX 1550nm TX / 1310nm RX single strand fiber, multimode (SC) [2 km/1.2 miles] - EU Power Cord	https://www.perle.com/products/fast-ethernet-media-converters.shtml	Media Converter: S-100

Part #	Description	Product Datasheet	Product Group
05040932	S-100-M1SC2U - Fast Ethernet Media Converter: 100Base-TX (RJ-45) [100 m/328 ft.] to 100Base-BX 1310nm TX / 1550nm RX single strand fiber, multimode (SC) [2 km/1.2 miles] - EU Power Cord	https://www.perle.com/products/fast-ethernet-media-converters.shtml	Media Converter: S-100
05040942	S-1000-M2SC2 - Gigabit Media Converter: 1000BASE-T (RJ-45) [100 m/328 ft.] to 1000BASE-LX 1310nm extended multimode (SC) [2km /6562 ft.] - EU Power Cord	https://www.perle.com/products/gigabit-media-converters.shtml	Media Converter: S-1000
05040952	S-1000-M2ST2 - Gigabit Media Converter: 1000BASE-T (RJ-45) [100 m/328 ft.] to 1000BASE-LX 1310nm extended multimode (ST) [2km /6562 ft.] - EU Power Cord	https://www.perle.com/products/gigabit-media-converters.shtml	Media Converter: S-1000
05040962	S-1000-M2LC2 - Gigabit Media Converter: 1000BASE-T (RJ-45) [100 m/328 ft.] to 1000BASE-LX 1310nm extended multimode (LC) [2km /6562 ft.] - EU Power Cord	https://www.perle.com/products/gigabit-media-converters.shtml	Media Converter: S-1000
05040972	S-1110-M2SC2 - 10/100/1000Base-T Media and Rate Converter: 10/100/1000BASE-T (RJ-45) [100 m/328 ft.] to 1000BASE-LX 1310nm Extended multimode (SC) [2km /6562 ft.] - EU Power Cord	https://www.perle.com/products/10-100-1000-media-converters.shtml	Media Converter: S-1110
05040982	S-1110-M2ST2 - 10/100/1000Base-T Media and Rate Converter: 10/100/1000BASE-T (RJ-45) [100 m/328 ft.] to 1000BASE-LX 1310nm Extended multimode (ST) [2km /6562 ft.] - EU Power Cord	https://www.perle.com/products/10-100-1000-media-converters.shtml	Media Converter: S-1110
05040992	S-1110-M2LC2 - 10/100/1000Base-T Media and Rate Converter: 10/100/1000BASE-T (RJ-45) [100 m/328 ft.] to 1000BASE-LX 1310nm Extended multimode (LC) [2km /6562 ft.] - EU Power Cord	https://www.perle.com/products/10-100-1000-media-converters.shtml	Media Converter: S-1110
05041780	C-100-S1ST20U - Fast Ethernet Media Converter Module: 100Base-TX (RJ-45) [100 m/328 ft.] to 100Base-BX 1310nm TX / 1550nm RX single strand fiber, single mode (ST) [20 km/12.4 miles]	https://www.perle.com/products/fast-ethernet-media-converter-module.shtml	Media Converter Module: C-100
05041790	C-100-S1ST20D - Fast Ethernet Media Converter Module: 100Base-TX (RJ-45) [100 m/328 ft.] to 100Base-BX 1550nm TX / 1310nm RX single strand fiber, single mode (ST) [20 km/12.4 miles]	https://www.perle.com/products/fast-ethernet-media-converter-module.shtml	Media Converter Module: C-100
05041800	C-100-M1ST2D - Fast Ethernet Media Converter Module: 100Base-TX (RJ-45) [100 m/328 ft.] to 100Base-BX 1550nm TX / 1310nm RX single strand fiber, multimode (ST) [2 km/1.2 miles]	https://www.perle.com/products/fast-ethernet-media-converter-module.shtml	Media Converter Module: C-100
05041810	C-100-M1ST2U - Fast Ethernet Media Converter Module: 100Base-TX (RJ-45) [100 m/328 ft.] to 100Base-BX 1310nm TX / 1550nm RX single strand fiber, multimode (ST) [2 km/1.2 miles]	https://www.perle.com/products/fast-ethernet-media-converter-module.shtml	Media Converter Module: C-100

Part #	Description	Product Datasheet	Product Group
05041820	C-110-S1ST20U - 10/100Base-TX Media and Rate Converter Module: 10/100Base-TX (RJ-45) [100 m/328 ft.] to 100Base-BX 1310nm TX / 1550nm RX single strand fiber, single mode (ST) [20 km/12.4 miles]	https://www.perle.com/products/10-100-media-converter-module.shtml	Media Converter Module: C-110
05041830	C-110-S1ST20D - 10/100Base-TX Media and Rate Converter Module: 10/100Base-TX (RJ-45) [100 m/328 ft.] to 100Base-BX 1550nm TX / 1310nm RX single strand fiber, single mode (ST) [20 km/12.4 miles]	https://www.perle.com/products/10-100-media-converter-module.shtml	Media Converter Module: C-110
05041840	C-110-M1ST2D - 10/100Base-TX Media and Rate Converter Module: 10/100Base-TX (RJ-45) [100 m/328 ft.] to 100Base-BX 1550nm TX / 1310nm RX single strand fiber, multimode (ST) [2 km/1.2 miles]	https://www.perle.com/products/10-100-media-converter-module.shtml	Media Converter Module: C-110
05041850	C-110-M1ST2U - 10/100Base-TX Media and Rate Converter Module: 10/100Base-TX (RJ-45) [100 m/328 ft.] to 100Base-BX 1310nm TX / 1550nm RX single strand fiber, multimode (ST) [2 km/1.2 miles]	https://www.perle.com/products/10-100-media-converter-module.shtml	Media Converter Module: C-110
05041860	C-1110-M1SC05D - 10/100/1000Base-T Media and Rate Converter Module: 10/100/1000BASE-T (RJ-45) [100 m/328 ft.] to 1000BASE-BX 1550nm TX / 1310nm RX single strand fiber, multimode (SC) [500 m/1640 ft]	https://www.perle.com/products/10-100-1000-media-converter-module.shtml	Media Converter Module: C-1110
05041870	C-1110-M1SC05U - 10/100/1000Base-T Media and Rate Converter Module: 10/100/1000BASE-T (RJ-45) [100 m/328 ft.] to 1000BASE-BX 1310nm TX / 1550nm RX single strand fiber, multimode (SC) [500 m/1640 ft]	https://www.perle.com/products/10-100-1000-media-converter-module.shtml	Media Converter Module: C-1110
05041880	C-1000-M1SC05D - Gigabit Media Converter Module: 1000BASE-T (RJ-45) [100 m/328 ft.] to 1000BASE-BX 1550nm TX / 1310nm RX single strand fiber, multimode (SC) [500 m/1640 ft]	https://www.perle.com/products/gigabit-media-converter-module.shtml	Media Converter Module: C-1000
05041890	C-1000-M1SC05U - Gigabit Media Converter Module: 1000BASE-T (RJ-45) [100 m/328 ft.] to 1000BASE-BX 1310nm TX / 1550nm RX single strand fiber, multimode (SC) [500 m/1640 ft]	https://www.perle.com/products/gigabit-media-converter-module.shtml	Media Converter Module: C-1000
05041900	C-110-M1SC2D - 10/100Base-TX Media and Rate Converter Module: 10/100Base-TX (RJ-45) [100 m/328 ft.] to 100Base-BX 1550nm TX / 1310nm RX single strand fiber, multimode (SC) [2 km/1.2 miles]	https://www.perle.com/products/10-100-media-converter-module.shtml	Media Converter Module: C-110
05041910	C-110-M1SC2U - 10/100Base-TX Media and Rate Converter Module: 10/100Base-TX (RJ-45) [100 m/328 ft.] to 100Base-BX 1310nm TX / 1550nm RX single strand fiber, multimode (SC) [2 km/1.2 miles]	https://www.perle.com/products/10-100-media-converter-module.shtml	Media Converter Module: C-110
05041920	C-100-M1SC2D - Fast Ethernet Media Converter Module: 100Base-TX (RJ-45) [100 m/328 ft.] to 100Base-BX 1550nm TX / 1310nm RX single strand fiber, multimode (SC) [2 km/1.2 miles]	https://www.perle.com/products/fast-ethernet-media-converter-module.shtml	Media Converter Module: C-100

Part #	Description	Product Datasheet	Product Group
05041930	C-100-M1SC2U - Fast Ethernet Media Converter Module: 100Base-TX (RJ-45) [100 m/328 ft.] to 100Base-BX 1310nm TX / 1550nm RX single strand fiber, multimode (SC) [2 km/1.2 miles]	https://www.perle.com/products/fast-ethernet-media-converter-module.shtml	Media Converter Module: C-100
05041940	C-1000-M2SC2 - Gigabit Media Converter Module: 1000BASE-T (RJ-45) [100 m/328 ft.] to 1000BASE-LX 1310nm Extended multimode (SC) [2km /6562 ft.]	https://www.perle.com/products/gigabit-media-converter-module.shtml	Media Converter Module: C-1000
05041950	C-1000-M2ST2 - Gigabit Media Converter Module: 1000BASE-T (RJ-45) [100 m/328 ft.] to 1000BASE-LX 1310nm Extended multimode (ST) [2km /6562 ft.]	https://www.perle.com/products/gigabit-media-converter-module.shtml	Media Converter Module: C-1000
05041960	C-1000-M2LC2 - Gigabit Media Converter Module: 1000BASE-T (RJ-45) [100 m/328 ft.] to 1000BASE-LX 1310nm Extended multimode (LC) [2km /6562 ft.]	https://www.perle.com/products/gigabit-media-converter-module.shtml	Media Converter Module: C-1000
05041970	C-1110-M2SC2 - 10/100/1000Base-T Media and Rate Converter Module: 10/100/1000BASE-T (RJ-45) [100 m/328 ft.] to 1000BASE-LX 1310nm Extended multimode (SC) [2km /6562 ft.]	https://www.perle.com/products/10-100-1000-media-converter-module.shtml	Media Converter Module: C-1110
05041980	C-1110-M2ST2 - 10/100/1000Base-T Media and Rate Converter Module: 10/100/1000BASE-T (RJ-45) [100 m/328 ft.] to 1000BASE-LX 1310nm Extended multimode (ST) [2km /6562 ft.]	https://www.perle.com/products/10-100-1000-media-converter-module.shtml	Media Converter Module: C-1110
05041990	C-1110-M2LC2 - 10/100/1000Base-T Media and Rate Converter Module: 10/100/1000BASE-T (RJ-45) [100 m/328 ft.] to 1000BASE-LX 1310nm Extended multimode (LC) [2km /6562 ft.]	https://www.perle.com/products/10-100-1000-media-converter-module.shtml	Media Converter Module: C-1110
05042780	CM-100-S1ST20U - Managed Fast Ethernet Media Converter Module: 100Base-TX (RJ-45) [100 m/328 ft.] to 100Base-BX 1310nm TX / 1550nm RX single strand fiber, single mode (ST) [20 km/12.4 miles]. Managed or unmanaged operation	https://www.perle.com/products/fast-ethernet-managed-media-converter-module.shtml	Media Converter Module: CM-100
05042790	CM-100-S1ST20D - Managed Fast Ethernet Media Converter Module: 100Base-TX (RJ-45) [100 m/328 ft.] to 100Base-BX 1550nm TX / 1310nm RX single strand fiber, single mode (ST) [20 km/12.4 miles]. Managed or unmanaged operation	https://www.perle.com/products/fast-ethernet-managed-media-converter-module.shtml	Media Converter Module: CM-100
05042800	CM-100-M1ST2D - Managed Fast Ethernet Media Converter Module: 100Base-TX (RJ-45) [100 m/328 ft.] to 100Base-BX 1550nm TX / 1310nm RX single strand fiber, multimode (ST) [2 km/1.2 miles]. Managed or unmanaged operation	https://www.perle.com/products/fast-ethernet-managed-media-converter-module.shtml	Media Converter Module: CM-100

Part #	Description	Product Datasheet	Product Group
05042810	CM-100-M1ST2U - Managed Fast Ethernet Media Converter Module: 100Base-TX (RJ-45) [100 m/328 ft.] to 100Base-BX 1310nm TX / 1550nm RX single strand fiber, multimode (ST) [2 km/1.2 miles]. Managed or unmanaged operation	https://www.perle.com/products/fast-ethernet-managed-media-converter-module.shtml	Media Converter Module: CM-100
05042820	CM-110-S1ST20U - Managed 10/100Base-TX Media and Rate Converter Module: 10/100Base-TX (RJ-45) [100 m/328 ft.] to 100Base-BX 1310nm TX / 1550nm RX single strand fiber, single mode (ST) [20 km/12.4 miles]. Managed or unmanaged operation	https://www.perle.com/products/10-100-managed-media-converter-module.shtml	Media Converter Module: CM-110
05042830	CM-110-S1ST20D - Managed 10/100Base-TX Media and Rate Converter Module: 10/100Base-TX (RJ-45) [100 m/328 ft.] to 100Base-BX 1550nm TX / 1310nm RX single strand fiber, single mode (ST) [20 km/12.4 miles]. Managed or unmanaged operation	https://www.perle.com/products/10-100-managed-media-converter-module.shtml	Media Converter Module: CM-110
05042840	CM-110-M1ST2D - Managed 10/100Base-TX Media and Rate Converter Module: 10/100Base-TX (RJ-45) [100 m/328 ft.] to 100Base-BX 1550nm TX / 1310nm RX single strand fiber, multimode (ST) [2 km/1.2 miles]. Managed or unmanaged operation	https://www.perle.com/products/10-100-managed-media-converter-module.shtml	Media Converter Module: CM-110
05042850	CM-110-M1ST2U - Managed 10/100Base-TX Media and Rate Converter Module: 10/100Base-TX (RJ-45) [100 m/328 ft.] to 100Base-BX 1310nm TX / 1550nm RX single strand fiber, multimode (ST) [2 km/1.2 miles]. Managed or unmanaged operation	https://www.perle.com/products/10-100-managed-media-converter-module.shtml	Media Converter Module: CM-110
05042860	CM-1110-M1SC05D - Managed 10/100/1000Base-T Media and Rate Converter Module: 10/100/1000BASE-T (RJ-45) [100 m/328 ft.] to 1000BASE-BX 1550nm TX / 1310nm RX single strand fiber, multimode (SC) [500 m/1640 ft]. Managed or unmanaged operation	https://www.perle.com/products/10-100-1000-managed-media-converter-module.shtml	Media Converter Module: CM-1110
05042870	CM-1110-M1SC05U - Managed 10/100/1000Base-T Media and Rate Converter Module: 10/100/1000BASE-T (RJ-45) [100 m/328 ft.] to 1000BASE-BX 1310nm TX / 1550nm RX single strand fiber, multimode (SC) [500 m/1640 ft]. Managed or unmanaged operation	https://www.perle.com/products/10-100-1000-managed-media-converter-module.shtml	Media Converter Module: CM-1110
05042880	CM-1000-M1SC05D - Managed Gigabit Media Converter Module: 1000BASE-T (RJ-45) [100 m/328 ft.] to 1000BASE-BX 1550nm TX / 1310nm RX single strand fiber, multimode (SC) [500 m/1640 ft]. Managed or unmanaged operation	https://www.perle.com/products/gigabit-managed-media-converter-module.shtml	Media Converter Module: CM-1000

Part #	Description	Product Datasheet	Product Group
05042890	CM-1000-M1SC05U - Managed Gigabit Media Converter Module: 1000BASE-T (RJ-45) [100 m/328 ft.] to 1000BASE-BX 1310nm TX / 1550nm RX single strand fiber, multimode (SC) [500 m/1640 ft]. Managed or unmanaged operation	https://www.perle.com/products/gigabit-managed-media-converter-module.shtml	Media Converter Module: CM-1000
05042900	CM-110-M1SC2D - Managed 10/100Base-TX Media and Rate Converter Module: 10/100Base-TX (RJ-45) [100 m/328 ft.] to 100Base-BX 1550nm TX / 1310nm RX single strand fiber, multimode (SC) [2 km/1.2 miles]. Managed or unmanaged operation	https://www.perle.com/products/10-100-managed-media-converter-module.shtml	Media Converter Module: CM-110
05042910	CM-110-M1SC2U - Managed 10/100Base-TX Media and Rate Converter Module: 10/100Base-TX (RJ-45) [100 m/328 ft.] to 100Base-BX 1310nm TX / 1550nm RX single strand fiber, multimode (SC) [2 km/1.2 miles]. Managed or unmanaged operation	https://www.perle.com/products/10-100-managed-media-converter-module.shtml	Media Converter Module: CM-110
05042920	CM-100-M1SC2D - Managed Fast Ethernet Media Converter Module: 100Base-TX (RJ-45) [100 m/328 ft.] to 100Base-BX 1550nm TX / 1310nm RX single strand fiber, multimode (SC) [2 km/1.2 miles]. Managed or unmanaged operation	https://www.perle.com/products/fast-ethernet-managed-media-converter-module.shtml	Media Converter Module: CM-100
05042930	CM-100-M1SC2U - Managed Fast Ethernet Media Converter Module: 100Base-TX (RJ-45) [100 m/328 ft.] to 100Base-BX 1310nm TX / 1550nm RX single strand fiber, multimode (SC) [2 km/1.2 miles]. Managed or unmanaged operation	https://www.perle.com/products/fast-ethernet-managed-media-converter-module.shtml	Media Converter Module: CM-100
05042940	CM-1000-M2SC2 - Managed Gigabit Media Converter Module: 1000BASE-T (RJ-45) [100 m/328 ft.] to 1000BASE-LX 3100nm Extended multimode (SC) [2km /6562 ft.]. Managed or unmanaged operation	https://www.perle.com/products/gigabit-managed-media-converter-module.shtml	Media Converter Module: CM-1000
05042950	CM-1000-M2ST2 - Managed Gigabit Media Converter Module: 1000BASE-T (RJ-45) [100 m/328 ft.] to 1000BASE-LX 3100nm Extended multimode (ST) [2km /6562 ft.]. Managed or unmanaged operation	https://www.perle.com/products/gigabit-managed-media-converter-module.shtml	Media Converter Module: CM-1000
05042960	CM-1000-M2LC2 - Managed Gigabit Media Converter Module: 1000BASE-T (RJ-45) [100 m/328 ft.] to 1000BASE-LX 3100nm Extended multimode (LC) [2km /6562 ft.]. Managed or unmanaged operation	https://www.perle.com/products/gigabit-managed-media-converter-module.shtml	Media Converter Module: CM-1000
05042970	CM-1110-M2SC2 - Managed 10/100/1000Base-T Media and Rate Converter Module: 10/100/1000BASE-T (RJ-45) [100 m/328 ft.] to 1000BASE-LX 1310nm Extended multimode (SC) [2km /6562 ft.]. Managed or unmanaged operation	https://www.perle.com/products/10-100-1000-managed-media-converter-module.shtml	Media Converter Module: CM-1110

Part #	Description	Product Datasheet	Product Group
05042980	CM-1110-M2ST2 - Managed 10/100/1000Base-T Media and Rate Converter Module: 10/100/1000BASE-T (RJ-45) [100 m/328 ft.] to 1000BASE-LX 1310nm Extended multimode (ST) [2km /6562 ft.]. Managed or unmanaged operation	https://www.perle.com/products/10-100-1000-managed-media-converter-module.shtml	Media Converter Module: CM-1110
05042990	CM-1110-M2LC2 - Managed 10/100/1000Base-T Media and Rate Converter Module: 10/100/1000BASE-T (RJ-45) [100 m/328 ft.] to 1000BASE-LX 1310nm Extended multimode (LC) [2km /6562 ft.]. Managed or unmanaged operation	https://www.perle.com/products/10-100-1000-managed-media-converter-module.shtml	Media Converter Module: CM-1110
05050002	S-1000-M2SC05 - Gigabit Media Converter: 1000BASE-T (RJ-45) [100 m/328 ft.] to 1000BASE-SX 850nm multimode (SC) [550 m/1804 ft.] - EU Power Cord	https://www.perle.com/products/gigabit-media-converters.shtml	Media Converter: S-1000
05050012	S-1000-M2LC05 - Gigabit Media Converter: 1000BASE-T (RJ-45) [100 m/328 ft.] to 1000BASE-SX 850nm multimode (LC) [550 m/1804 ft.] - EU Power Cord	https://www.perle.com/products/gigabit-media-converters.shtml	Media Converter: S-1000
05050022	S-1000-S2LC10 - Gigabit Media Converter: 1000BASE-T (RJ-45) [100 m/328 ft.] to 1000BASE-LX/LH 1310 nm single mode (LC) [10 km/6.2 miles] or multimode (LC) [550 m/1804 ft.] using a mode conditioning patch cord. - EU Power Cord	https://www.perle.com/products/gigabit-media-converters.shtml	Media Converter: S-1000
05050032	S-1000-S2SC10 - Gigabit Media Converter: 1000BASE-T (RJ-45) [100 m/328 ft.] to 1000BASE-LX/LH 1310 nm single mode (SC) [10 km/6.2 miles] or multimode (SC) [550 m/1804 ft.] using a mode conditioning adapter. - EU Power Cord	https://www.perle.com/products/gigabit-media-converters.shtml	Media Converter: S-1000
05050042	S-1000-S2LC40 - Gigabit Media Converter: 1000BASE-T (RJ-45) [100 m/328 ft.] to 1000BASE-EX 1310 nm single mode (LC) [40 km/24.9 miles] - EU Power Cord	https://www.perle.com/products/gigabit-media-converters.shtml	Media Converter: S-1000
05050052	S-1000-S2SC70 - Gigabit Media Converter: 1000BASE-T (RJ-45) [100 m/328 ft.] to 1000BASE-ZX 1550 nm single mode (SC) [70 km/43.5 miles] - EU Power Cord	https://www.perle.com/products/gigabit-media-converters.shtml	Media Converter: S-1000
05050062	S-1000-S2LC70 - Gigabit Media Converter: 1000BASE-T (RJ-45) [100 m/328 ft.] to 1000BASE-ZX 1550 nm single mode (LC) [70 km/43.5 miles] - EU Power Cord	https://www.perle.com/products/gigabit-media-converters.shtml	Media Converter: S-1000
05050072	S-1000-S1SC10U - Gigabit Media Converter: 1000BASE-T (RJ-45) [100 m/328 ft.] to 1000BASE-BX 1310nm TX / 1490nm RX single strand fiber, single mode (SC) [10 km/6.2 miles] - EU Power Cord	https://www.perle.com/products/gigabit-media-converters.shtml	Media Converter: S-1000

Part #	Description	Product Datasheet	Product Group
05050082	S-1000-S1SC10D - Gigabit Media Converter: 1000BASE-T (RJ-45) [100 m/328 ft.] to 1000BASE-BX 1490nm TX / 1310nm RX single strand fiber, single mode (SC) [10 km/6.2 miles] - EU Power Cord	https://www.perle.com/products/gigabit-media-converters.shtml	Media Converter: S-1000
05050092	S-1000-S2SC40 - Gigabit Media Converter: 1000BASE-T (RJ-45) [100 m/328 ft.] to 1000BASE-EX 1310 nm single mode (SC) [40 km/24.9 miles] - EU Power Cord	https://www.perle.com/products/gigabit-media-converters.shtml	Media Converter: S-1000
05050102	S-1000-M2ST05 - Gigabit Media Converter: 1000BASE-T (RJ-45) [100 m/328 ft.] to 1000BASE-SX 850nm multimode (ST) [550 m/1804 ft.] - EU Power Cord	https://www.perle.com/products/gigabit-media-converters.shtml	Media Converter: S-1000
05050112	S-1000-S2ST10 - Gigabit Media Converter: 1000BASE-T (RJ-45) [100 m/328 ft.] to 1000BASE-LX/LH 1310 nm single mode (ST) [10 km/6.2 miles] - EU Power Cord	https://www.perle.com/products/gigabit-media-converters.shtml	Media Converter: S-1000
05050122	S-1000-S2ST40 - Gigabit Media Converter: 1000BASE-T (RJ-45) [100 m/328 ft.] to 1000BASE-EX 1310 nm single mode (ST) [40 km/24.9 miles] - EU Power Cord	https://www.perle.com/products/gigabit-media-converters.shtml	Media Converter: S-1000
05050132	S-1000-S2ST70 - Gigabit Media Converter: 1000BASE-T (RJ-45) [100 m/328 ft.] to 1000BASE-ZX 1550 nm single mode (ST) [70 km/43.5 miles] - EU Power Cord	https://www.perle.com/products/gigabit-media-converters.shtml	Media Converter: S-1000
05050142	S-1000-S2ST120 - Gigabit Media Converter: 1000BASE-T (RJ-45) [100 m/328 ft.] to 1000BASE-ZX 1550 nm single mode (ST) [120 km/74.6 miles] - EU Power Cord	https://www.perle.com/products/gigabit-media-converters.shtml	Media Converter: S-1000
05050152	S-1000-S2SC120 - Gigabit Media Converter: 1000BASE-T (RJ-45) [100 m/328 ft.] to 1000BASE-ZX 1550 nm single mode (SC) [120 km/74.6 miles] - EU Power Cord	https://www.perle.com/products/gigabit-media-converters.shtml	Media Converter: S-1000
05050162	S-1000-S2LC120 - Gigabit Media Converter: 1000BASE-T (RJ-45) [100 m/328 ft.] to 1000BASE-ZX 1550 nm single mode (LC) [120 km/74.6 miles] - EU Power Cord	https://www.perle.com/products/gigabit-media-converters.shtml	Media Converter: S-1000
05050182	S-1000-SFP - Gigabit Media Converter: 1000BASE-T (RJ-45) [100 m/328 ft.] to 1000BASE-X - SFP slot (empty) - EU Power Cord	https://www.perle.com/products/gigabit-sfp-media-converters.shtml	Media Converter: S-1000
05050192	S-1110-SFP - 10/100/1000Base-T Media and Rate Converter: 10/100/1000BASE-T (RJ-45) [100 m/328 ft.] to 1000BASE-X or 100BASE-X - SFP Slot (empty) - EU Power Cord	https://www.perle.com/products/10-100-1000-sfp-media-converters.shtml	Media Converter: S-1110
05050202	S-100-M2ST2 - Fast Ethernet Media Converter: 100BASE-TX (RJ-45) [100 m/328 ft.] to 100BASE-FX 1310nm multimode (ST) [2 km/1.2 miles] - EU Power Cord	https://www.perle.com/products/fast-ethernet-media-converters.shtml	Media Converter: S-100

Part #	Description	Product Datasheet	Product Group
05050212	S-100-M2SC2 - Fast Ethernet Media Converter: 100BASE-TX (RJ-45) [100 m/328 ft.] to 100BASE-FX 1310nm multimode (SC) [2 km/1.2 miles] - EU Power Cord	https://www.perle.com/products/fast-ethernet-media-converters.shtml	Media Converter: S-100
05050222	S-100-M2LC2 - Fast Ethernet Media Converter: 100BASE-TX (RJ-45) [100 m/328 ft.] to 100BASE-FX 1310nm multimode (LC) [2 km/1.2 miles] - EU Power Cord	https://www.perle.com/products/fast-ethernet-media-converters.shtml	Media Converter: S-100
05050232	S-100-S2SC20 - Fast Ethernet Media Converter: 100BASE-TX (RJ-45) [100 m/328 ft.] to 100Base-LX 1310nm single mode (SC) [20 km/12.4 miles] - EU Power Cord	https://www.perle.com/products/fast-ethernet-media-converters.shtml	Media Converter: S-100
05050242	S-100-S2LC20 - Fast Ethernet Media Converter: 100BASE-TX (RJ-45) [100 m/328 ft.] to 100Base-LX 1310nm single mode (LC) [20 km/12.4 miles] - EU Power Cord	https://www.perle.com/products/fast-ethernet-media-converters.shtml	Media Converter: S-100
05050252	S-100-S2SC40 - Fast Ethernet Media Converter: 100BASE-TX (RJ-45) [100 m/328 ft.] to 100Base-EX 1310nm single mode (SC) [40 km/24.9 miles] - EU Power Cord	https://www.perle.com/products/fast-ethernet-media-converters.shtml	Media Converter: S-100
05050262	S-100-S2SC80 - Fast Ethernet Media Converter: 100BASE-TX (RJ-45) [100 m/328 ft.] to 100Base-ZX 1550nm single mode (SC) [80 km/49.7 miles] - EU Power Cord	https://www.perle.com/products/fast-ethernet-media-converters.shtml	Media Converter: S-100
05050272	S-100-S1SC20U - Fast Ethernet Media Converter: 100Base-TX (RJ-45) [100 m/328 ft.] to 100Base-BX 1310nm TX / 1550nm RX single strand fiber, single mode (SC) [20 km/12.4 miles] - EU Power Cord	https://www.perle.com/products/fast-ethernet-media-converters.shtml	Media Converter: S-100
05050282	S-100-S1SC20D - Fast Ethernet Media Converter: 100Base-TX (RJ-45) [100 m/328 ft.] to 100Base-BX 1550nm TX / 1310nm RX single strand fiber, single mode (SC) [20 km/12.4 miles] - EU Power Cord	https://www.perle.com/products/fast-ethernet-media-converters.shtml	Media Converter: S-100
05050292	S-100-S1SC40U - Fast Ethernet Media Converter: 100Base-TX (RJ-45) [100 m/328 ft.] to 100Base-BX 1310nm TX / 1550nm RX single strand fiber, single mode (SC) [40 km/24.9 miles] - EU Power Cord	https://www.perle.com/products/fast-ethernet-media-converters.shtml	Media Converter: S-100
05050302	S-100-S1SC40D - Fast Ethernet Media Converter: 100Base-TX (RJ-45) [100 m/328 ft.] to 100Base-BX 1550nm TX / 1310nm RX single strand fiber, single mode (SC) [40 km/24.9 miles] - EU Power Cord	https://www.perle.com/products/fast-ethernet-media-converters.shtml	Media Converter: S-100
05050312	S-100-S2SC120 - Fast Ethernet Media Converter: 100BASE-TX (RJ-45) [100 m/328 ft.] to 100Base-ZX 1550nm single mode (SC) [120 km/74.6 miles] - EU Power Cord	https://www.perle.com/products/fast-ethernet-media-converters.shtml	Media Converter: S-100

Part #	Description	Product Datasheet	Product Group
05050322	S-100-S2ST20 - Fast Ethernet Media Converter: 100BASE-TX (RJ-45) [100 m/328 ft.] to 100Base-LX 1310nm single mode (ST) [20 km/12.4 miles] - EU Power Cord	https://www.perle.com/products/fast-ethernet-media-converters.shtml	Media Converter: S-100
05050332	S-100-S2ST40 - Fast Ethernet Media Converter: 100BASE-TX (RJ-45) [100 m/328 ft.] to 100Base-EX 1310nm single mode (ST) [40 km/24.9 miles] - EU Power Cord	https://www.perle.com/products/fast-ethernet-media-converters.shtml	Media Converter: S-100
05050342	S-100-S2ST80 - Fast Ethernet Media Converter: 100BASE-TX (RJ-45) [100 m/328 ft.] to 100Base-ZX 1550nm single mode (ST) [80 km/49.7 miles] - EU Power Cord	https://www.perle.com/products/fast-ethernet-media-converters.shtml	Media Converter: S-100
05050352	S-100-S2ST120 - Fast Ethernet Media Converter: 100BASE-TX (RJ-45) [100 m/328 ft.] to 100Base-ZX 1550nm single mode (ST) [120 km/74.6 miles] - EU Power Cord	https://www.perle.com/products/fast-ethernet-media-converters.shtml	Media Converter: S-100
05050362	S-100-S2LC40 - Fast Ethernet Media Converter: 100BASE-TX (RJ-45) [100 m/328 ft.] to 100Base-EX 1310nm single mode (LC) [40 km/24.9 miles] - EU Power Cord	https://www.perle.com/products/fast-ethernet-media-converters.shtml	Media Converter: S-100
05050372	S-100-S2LC80 - Fast Ethernet Media Converter: 100BASE-TX (RJ-45) [100 m/328 ft.] to 100Base-ZX 1550nm single mode (LC) [80 km/49.7 miles] - EU Power Cord	https://www.perle.com/products/fast-ethernet-media-converters.shtml	Media Converter: S-100
05050382	S-100-S2LC120 - Fast Ethernet Media Converter: 100BASE-TX (RJ-45) [100 m/328 ft.] to 100Base-ZX 1550nm single mode (LC) [120 km/74.6 miles] - EU Power Cord	https://www.perle.com/products/fast-ethernet-media-converters.shtml	Media Converter: S-100
05050402	S-110-M2ST2 - 10/100Base-TX Media and Rate Converter: 10/100Base-TX (RJ-45) [100 m/328 ft.] to 100BASE-FX 1310nm multimode (ST) [2 km/1.2 miles] - EU Power Cord	https://www.perle.com/products/10-100-converters.shtml	Media Converter: S-110
05050412	S-110-M2SC2 - 10/100Base-TX Media and Rate Converter: 10/100Base-TX (RJ-45) [100 m/328 ft.] to 100BASE-FX 1310nm multimode (SC) [2 km/1.2 miles] - EU Power Cord	https://www.perle.com/products/10-100-converters.shtml	Media Converter: S-110
05050422	S-110-M2LC2 - 10/100Base-TX Media and Rate Converter: 10/100Base-TX (RJ-45) [100 m/328 ft.] to 100BASE-FX 1310nm multimode (LC) [2 km/1.2 miles] - EU Power Cord	https://www.perle.com/products/10-100-converters.shtml	Media Converter: S-110
05050432	S-110-S2SC20 - 10/100Base-TX Media and Rate Converter: 10/100Base-TX (RJ-45) [100 m/328 ft.] to 100Base-LX 1310nm single mode (SC) [20 km/12.4 miles] - EU Power Cord	https://www.perle.com/products/10-100-converters.shtml	Media Converter: S-110

Part #	Description	Product Datasheet	Product Group
05050442	S-110-S2LC20 - 10/100Base-TX Media and Rate Converter: 10/100Base-TX (RJ-45) [100 m/328 ft.] to 100Base-LX 1310nm single mode (LC) [20 km/12.4 miles] - EU Power Cord	https://www.perle.com/products/10-100-converters.shtml	Media Converter: S-110
05050452	S-110-S2SC40 - 10/100Base-TX Media and Rate Converter: 10/100Base-TX (RJ-45) [100 m/328 ft.] to 100Base-EX 1310nm single mode (SC) [40 km/24.9 miles] - EU Power Cord	https://www.perle.com/products/10-100-converters.shtml	Media Converter: S-110
05050462	S-110-S2SC80 - 10/100Base-TX Media and Rate Converter: 10/100Base-TX (RJ-45) [100 m/328 ft.] to 100Base-ZX 1550nm single mode (SC) [80 km/49.7 miles] - EU Power Cord	https://www.perle.com/products/10-100-converters.shtml	Media Converter: S-110
05050472	S-110-S1SC20U - 10/100Base-TX Media and Rate Converter: 10/100Base-TX (RJ-45) [100 m/328 ft.] to 100Base-BX 1310nm TX / 1550nm RX single strand fiber, single mode (SC) [20 km/12.4 miles] - EU Power Cord	https://www.perle.com/products/10-100-converters.shtml	Media Converter: S-110
05050482	S-110-S1SC20D - 10/100Base-TX Media and Rate Converter: 10/100Base-TX (RJ-45) [100 m/328 ft.] to 100Base-BX 1550nm TX / 1310nm RX single strand fiber, single mode (SC) [20 km/12.4 miles] - EU Power Cord	https://www.perle.com/products/10-100-converters.shtml	Media Converter: S-110
05050492	S-110-S1SC40U - 10/100Base-TX Media and Rate Converter: 10/100Base-TX (RJ-45) [100 m/328 ft.] to 100Base-BX 1310nm TX / 1550nm RX single strand fiber, single mode (SC) [40 km/24.9 miles] - EU Power Cord	https://www.perle.com/products/10-100-converters.shtml	Media Converter: S-110
05050502	S-110-S1SC40D - 10/100Base-TX Media and Rate Converter: 10/100Base-TX (RJ-45) [100 m/328 ft.] to 100Base-BX 1550nm TX / 1310nm RX single strand fiber, single mode (SC) [40 km/24.9 miles] - EU Power Cord	https://www.perle.com/products/10-100-converters.shtml	Media Converter: S-110
05050512	S-110-S2SC120 - 10/100Base-TX Media and Rate Converter: 10/100Base-TX (RJ-45) [100 m/328 ft.] to 100Base-ZX 1550nm single mode (SC) [120 km/74.6 miles] - EU Power Cord	https://www.perle.com/products/10-100-converters.shtml	Media Converter: S-110
05050522	S-110-S2ST20 - 10/100Base-TX Media and Rate Converter: 10/100Base-TX (RJ-45) [100 m/328 ft.] to 100Base-LX 1310nm single mode (ST) [20 km/12.4 miles] - EU Power Cord	https://www.perle.com/products/10-100-converters.shtml	Media Converter: S-110
05050532	S-110-S2ST40 - 10/100Base-TX Media and Rate Converter: 10/100Base-TX (RJ-45) [100 m/328 ft.] to 100Base-EX 1310nm single mode (ST) [40 km/24.9 miles] - EU Power Cord	https://www.perle.com/products/10-100-converters.shtml	Media Converter: S-110
05050542	S-110-S2ST80 - 10/100Base-TX Media and Rate Converter: 10/100Base-TX (RJ-45) [100 m/328 ft.] to 100Base-ZX 1550nm single mode (ST) [80 km/49.7 miles] - EU Power Cord	https://www.perle.com/products/10-100-converters.shtml	Media Converter: S-110

Part #	Description	Product Datasheet	Product Group
05050552	S-110-S2ST120 - 10/100Base-TX Media and Rate Converter: 10/100Base-TX (RJ-45) [100 m/328 ft.] to 100Base-ZX 1550nm single mode (ST) [120 km/74.6 miles] - EU Power Cord	https://www.perle.com/products/10-100-converters.shtml	Media Converter: S-110
05050562	S-110-S2LC40 - 10/100Base-TX Media and Rate Converter: 10/100Base-TX (RJ-45) [100 m/328 ft.] to 100Base-EX 1310nm single mode (LC) [40 km/24.9 miles] - EU Power Cord	https://www.perle.com/products/10-100-converters.shtml	Media Converter: S-110
05050572	S-110-S2LC80 - 10/100Base-TX Media and Rate Converter: 10/100Base-TX (RJ-45) [100 m/328 ft.] to 100Base-ZX 1550nm single mode (LC) [80 km/49.7 miles] - EU Power Cord	https://www.perle.com/products/10-100-converters.shtml	Media Converter: S-110
05050582	S-110-S2LC120 - 10/100Base-TX Media and Rate Converter: 10/100Base-TX (RJ-45) [100 m/328 ft.] to 100Base-ZX 1550nm single mode (LC) [120 km/74.6 miles] - EU Power Cord	https://www.perle.com/products/10-100-converters.shtml	Media Converter: S-110
05050592	S-1110-S1SC120D - 10/100/1000Base-T Media and Rate Converter: 10/100/1000BASE-T (RJ-45) [100 m/328 ft.] to 1000BASE-BX 1590nm TX / 1510nm RX single strand fiber, single mode (SC) [120 km/75 miles] - EU Power Cord	https://www.perle.com/products/10-100-1000-media-converters.shtml	Media Converter: S-1110
05050602	S-1110-M2SC05 - 10/100/1000Base-T Media and Rate Converter: 10/100/1000BASE-T (RJ-45) [100 m/328 ft.] to 1000BASE-SX 850nm multimode (SC) [550 m/1804 ft.] - EU Power Cord	https://www.perle.com/products/10-100-1000-media-converters.shtml	Media Converter: S-1110
05050612	S-1110-M2LC05 - 10/100/1000Base-T Media and Rate Converter: 10/100/1000BASE-T (RJ-45) [100 m/328 ft.] to 1000BASE-SX 850nm multimode (LC) [550 m/1804 ft.] - EU Power Cord	https://www.perle.com/products/10-100-1000-media-converters.shtml	Media Converter: S-1110
05050622	S-1110-S2LC10 - 10/100/1000Base-T Media and Rate Converter: 10/100/1000BASE-T (RJ-45) [100 m/328 ft.] to 1000BASE-LX/LH 1310 nm single mode (LC) [10 km/6.2 miles] or multimode (LC) [550 m/1804 ft.] using a mode conditioning patch cord. - EU Power Cord	https://www.perle.com/products/10-100-1000-media-converters.shtml	Media Converter: S-1110
05050632	S-1110-S2SC10 - 10/100/1000Base-T Media and Rate Converter: 10/100/1000BASE-T (RJ-45) [100 m/328 ft.] to 1000BASE-LX/LH 1310 nm single mode (SC) [10 km/6.2 miles] or multimode (SC) [550 m/1804 ft.] using a mode conditioning adapter. - EU Power Cord	https://www.perle.com/products/10-100-1000-media-converters.shtml	Media Converter: S-1110
05050642	S-1110-S2LC40 - 10/100/1000Base-T Media and Rate Converter: 10/100/1000BASE-T (RJ-45) [100 m/328 ft.] to 1000BASE-EX 1310 nm single mode (LC) [40 km/24.9 miles] - EU Power Cord	https://www.perle.com/products/10-100-1000-media-converters.shtml	Media Converter: S-1110

Part #	Description	Product Datasheet	Product Group
05050652	S-1110-S2SC70 - 10/100/1000Base-T Media and Rate Converter: 10/100/1000BASE-T (RJ-45) [100 m/328 ft.] to 1000BASE-ZX 1550 nm single mode (SC) [70 km/43.5 miles] - EU Power Cord	https://www.perle.com/products/10-100-1000-media-converters.shtml	Media Converter: S-1110
05050662	S-1110-S2LC70 - 10/100/1000Base-T Media and Rate Converter: 10/100/1000BASE-T (RJ-45) [100 m/328 ft.] to 1000BASE-ZX 1550 nm single mode (LC) [70 km/43.5 miles] - EU Power Cord	https://www.perle.com/products/10-100-1000-media-converters.shtml	Media Converter: S-1110
05050672	S-1110-S1SC10U - 10/100/1000Base-T Media and Rate Converter: 10/100/1000BASE-T (RJ-45) [100 m/328 ft.] to 1000BASE-BX 1310nm TX / 1490nm RX single strand fiber, single mode (SC) [10 km/6.2 miles] - EU Power Cord	https://www.perle.com/products/10-100-1000-media-converters.shtml	Media Converter: S-1110
05050682	S-1110-S1SC10D - 10/100/1000Base-T Media and Rate Converter: 10/100/1000BASE-T (RJ-45) [100 m/328 ft.] to 1000BASE-BX 1490nm TX / 1310nm RX single strand fiber, single mode (SC) [10 km/6.2 miles] - EU Power Cord	https://www.perle.com/products/10-100-1000-media-converters.shtml	Media Converter: S-1110
05050692	S-1110-S2SC40 - 10/100/1000Base-T Media and Rate Converter: 10/100/1000BASE-T (RJ-45) [100 m/328 ft.] to 1000BASE-EX 1310 nm single mode (SC) [40 km/24.9 miles] - EU Power Cord	https://www.perle.com/products/10-100-1000-media-converters.shtml	Media Converter: S-1110
05050712	S-1110-M2ST05 - 10/100/1000Base-T Media and Rate Converter: 10/100/1000BASE-T (RJ-45) [100 m/328 ft.] to 1000BASE-SX 850nm multimode (ST) [550 m/1804 ft.] - EU Power Cord	https://www.perle.com/products/10-100-1000-media-converters.shtml	Media Converter: S-1110
05050722	S-1110-S2ST10 - 10/100/1000Base-T Media and Rate Converter: 10/100/1000BASE-T (RJ-45) [100 m/328 ft.] to 1000BASE-LX/LH 1310 nm single mode (ST) [10 km/6.2 miles] - EU Power Cord	https://www.perle.com/products/10-100-1000-media-converters.shtml	Media Converter: S-1110
05050732	S-1110-S2ST40 - 10/100/1000Base-T Media and Rate Converter: 10/100/1000BASE-T (RJ-45) [100 m/328 ft.] to 1000BASE-EX 1310 nm single mode (ST) [40 km/24.9 miles] - EU Power Cord	https://www.perle.com/products/10-100-1000-media-converters.shtml	Media Converter: S-1110
05050742	S-1110-S2ST70 - 10/100/1000Base-T Media and Rate Converter: 10/100/1000BASE-T (RJ-45) [100 m/328 ft.] to 1000BASE-ZX 1550 nm single mode (ST) [70 km/43.5 miles] - EU Power Cord	https://www.perle.com/products/10-100-1000-media-converters.shtml	Media Converter: S-1110
05050752	S-1110-S2ST120 - 10/100/1000Base-T Media and Rate Converter: 10/100/1000BASE-T (RJ-45) [100 m/328 ft.] to 1000BASE-ZX 1550 nm single mode (ST) [120 km/74.6 miles] - EU Power Cord	https://www.perle.com/products/10-100-1000-media-converters.shtml	Media Converter: S-1110
05050762	S-1110-S2SC120 - 10/100/1000Base-T Media and Rate Converter: 10/100/1000BASE-T (RJ-45) [100 m/328 ft.] to 1000BASE-ZX 1550 nm single mode (SC) [120 km/74.6 miles] - EU Power Cord	https://www.perle.com/products/10-100-1000-media-converters.shtml	Media Converter: S-1110

Part #	Description	Product Datasheet	Product Group
05050772	S-1110-S2LC120 - 10/100/1000Base-T Media and Rate Converter: 10/100/1000BASE-T (RJ-45) [100 m/328 ft.] to 1000BASE-ZX 1550 nm single mode (LC) [120 km/74.6 miles] - EU Power Cord	https://www.perle.com/products/10-100-1000-media-converters.shtml	Media Converter: S-1110
05050782	S-1000-S2ST160 - Gigabit Media Converter: 1000BASE-T (RJ-45) [100 m/328 ft.] to 1000BASE-ZX 1550 nm single mode (ST) [160 km/100 miles] - EU Power Cord	https://www.perle.com/products/gigabit-media-converters.shtml	Media Converter: S-1000
05050792	S-1000-S2SC160 - Gigabit Media Converter: 1000BASE-T (RJ-45) [100 m/328 ft.] to 1000BASE-ZX 1550 nm single mode (SC) [160 km/100 miles] - EU Power Cord	https://www.perle.com/products/gigabit-media-converters.shtml	Media Converter: S-1000
05050802	S-1000-S2LC160 - Gigabit Media Converter: 1000BASE-T (RJ-45) [100 m/328 ft.] to 1000BASE-ZX 1550 nm single mode (LC) [160 km/100 miles] - EU Power Cord	https://www.perle.com/products/gigabit-media-converters.shtml	Media Converter: S-1000
05050812	S-1000-S1SC20U - Gigabit Media Converter: 1000BASE-T (RJ-45) [100 m/328 ft.] to 1000BASE-BX 1310nm TX / 1490nm RX single strand fiber, single mode (SC) [20 km/12.4 miles] - EU Power Cord	https://www.perle.com/products/gigabit-media-converters.shtml	Media Converter: S-1000
05050822	S-1000-S1SC20D - Gigabit Media Converter: 1000BASE-T (RJ-45) [100 m/328 ft.] to 1000BASE-BX 1490nm TX / 1310nm RX single strand fiber, single mode (SC) [20 km/12.4 miles] - EU Power Cord	https://www.perle.com/products/gigabit-media-converters.shtml	Media Converter: S-1000
05050832	S-1000-S1SC40U - Gigabit Media Converter: 1000BASE-T (RJ-45) [100 m/328 ft.] to 1000BASE-BX 1310nm TX / 1490nm RX single strand fiber, single mode (SC) [40 km/25 miles] - EU Power Cord	https://www.perle.com/products/gigabit-media-converters.shtml	Media Converter: S-1000
05050842	S-1000-S1SC40D - Gigabit Media Converter: 1000BASE-T (RJ-45) [100 m/328 ft.] to 1000BASE-BX 1490nm TX / 1310nm RX single strand fiber, single mode (SC) [40 km/25 miles] - EU Power Cord	https://www.perle.com/products/gigabit-media-converters.shtml	Media Converter: S-1000
05050852	S-1000-S1SC80U - Gigabit Media Converter: 1000BASE-T (RJ-45) [100 m/328 ft.] to 1000BASE-BX 1510nm TX / 1590nm RX single strand fiber, single mode (SC) [80 km/50 miles] - EU Power Cord	https://www.perle.com/products/gigabit-media-converters.shtml	Media Converter: S-1000
05050862	S-1000-S1SC80D - Gigabit Media Converter: 1000BASE-T (RJ-45) [100 m/328 ft.] to 1000BASE-BX 1590nm TX / 1510nm RX single strand fiber, single mode (SC) [80 km/50 miles] - EU Power Cord	https://www.perle.com/products/gigabit-media-converters.shtml	Media Converter: S-1000
05050872	S-1000-S1SC120U - Gigabit Media Converter: 1000BASE-T (RJ-45) [100 m/328 ft.] to 1000BASE-BX 1510nm TX / 1590nm RX single strand fiber, single mode (SC) [120 km/75 miles] - EU Power Cord	https://www.perle.com/products/gigabit-media-converters.shtml	Media Converter: S-1000

Part #	Description	Product Datasheet	Product Group
05050882	S-1000-S1SC120D - Gigabit Media Converter: 1000BASE-T (RJ-45) [100 m/328 ft.] to 1000BASE-BX 1590nm TX / 1510nm RX single strand fiber, single mode (SC) [120 km/75 miles] - EU Power Cord	https://www.perle.com/products/gigabit-media-converters.shtml	Media Converter: S-1000
05050892	S-1110-S2ST160 - 10/100/1000Base-T Media and Rate Converter: 10/100/1000BASE-T (RJ-45) [100 m/328 ft.] to 1000BASE-ZX 1550 nm single mode (ST) [160 km/100 miles] - EU Power Cord	https://www.perle.com/products/10-100-1000-media-converters.shtml	Media Converter: S-1110
05050912	S-1110-S2SC160 - 10/100/1000Base-T Media and Rate Converter: 10/100/1000BASE-T (RJ-45) [100 m/328 ft.] to 1000BASE-ZX 1550 nm single mode (SC) [160 km/100 miles] - EU Power Cord	https://www.perle.com/products/10-100-1000-media-converters.shtml	Media Converter: S-1110
05050922	S-1110-S2LC160 - 10/100/1000Base-T Media and Rate Converter: 10/100/1000BASE-T (RJ-45) [100 m/328 ft.] to 1000BASE-ZX 1550 nm single mode (LC) [160 km/100 miles] - EU Power Cord	https://www.perle.com/products/10-100-1000-media-converters.shtml	Media Converter: S-1110
05050932	S-1110-S1SC20U - 10/100/1000Base-T Media and Rate Converter: 10/100/1000BASE-T (RJ-45) [100 m/328 ft.] to 1000BASE-BX 1310nm TX / 1490nm RX single strand fiber, single mode (SC) [20 km/12.4 miles] - EU Power Cord	https://www.perle.com/products/10-100-1000-media-converters.shtml	Media Converter: S-1110
05050942	S-1110-S1SC20D - 10/100/1000Base-T Media and Rate Converter: 10/100/1000BASE-T (RJ-45) [100 m/328 ft.] to 1000BASE-BX 1490nm TX / 1310nm RX single strand fiber, single mode (SC) [20 km/12.4 miles] - EU Power Cord	https://www.perle.com/products/10-100-1000-media-converters.shtml	Media Converter: S-1110
05050952	S-1110-S1SC40U - 10/100/1000Base-T Media and Rate Converter: 10/100/1000BASE-T (RJ-45) [100 m/328 ft.] to 1000BASE-BX 1310nm TX / 1490nm RX single strand fiber, single mode (SC) [40 km/25 miles] - EU Power Cord	https://www.perle.com/products/10-100-1000-media-converters.shtml	Media Converter: S-1110
05050962	S-1110-S1SC40D - 10/100/1000Base-T Media and Rate Converter: 10/100/1000BASE-T (RJ-45) [100 m/328 ft.] to 1000BASE-BX 1490nm TX / 1310nm RX single strand fiber, single mode (SC) [40 km/25 miles] - EU Power Cord	https://www.perle.com/products/10-100-1000-media-converters.shtml	Media Converter: S-1110
05050972	S-1110-S1SC80U - 10/100/1000Base-T Media and Rate Converter: 10/100/1000BASE-T (RJ-45) [100 m/328 ft.] to 1000BASE-BX 1510nm TX / 1590nm RX single strand fiber, single mode (SC) [80 km/50 miles] - EU Power Cord	https://www.perle.com/products/10-100-1000-media-converters.shtml	Media Converter: S-1110

Part #	Description	Product Datasheet	Product Group
05050982	S-1110-S1SC80D - 10/100/1000Base-T Media and Rate Converter: 10/100/1000BASE-T (RJ-45) [100 m/328 ft.] to 1000BASE-BX 1590nm TX / 1510nm RX single strand fiber, single mode (SC) [80 km/50 miles] - EU Power Cord	https://www.perle.com/products/10-100-1000-media-converters.shtml	Media Converter: S-1110
05050992	S-1110-S1SC120U - 10/100/1000Base-T Media and Rate Converter: 10/100/1000BASE-T (RJ-45) [100 m/328 ft.] to 1000BASE-BX 1510nm TX / 1590nm RX single strand fiber, single mode (SC) [120 km/75 miles] - EU Power Cord	https://www.perle.com/products/10-100-1000-media-converters.shtml	Media Converter: S-1110
05051000	C-1000-M2SC05 - Gigabit Media Converter Module: 1000BASE-T (RJ-45) [100 m/328 ft.] to 1000BASE-SX 850nm multimode (SC) [550 m/1804 ft.].	https://www.perle.com/products/gigabit-media-converter-module.shtml	Media Converter Module: C-1000
05051010	C-1000-M2LC05 - Gigabit Media Converter Module: 1000BASE-T (RJ-45) [100 m/328 ft.] to 1000BASE-SX 850nm multimode (LC) [550 m/1804 ft.].	https://www.perle.com/products/gigabit-media-converter-module.shtml	Media Converter Module: C-1000
05051020	C-1000-S2LC10 - Gigabit Media Converter Module: 1000BASE-T (RJ-45) [100 m/328 ft.] to 1000BASE-LX/LH 1310 nm single mode (LC) [10 km/6.2 miles] or multimode (LC) [550 m/1804 ft.] using a mode conditioning patch cord.	https://www.perle.com/products/gigabit-media-converter-module.shtml	Media Converter Module: C-1000
05051030	C-1000-S2SC10 - Gigabit Media Converter Module: 1000BASE-T (RJ-45) [100 m/328 ft.] to 1000BASE-LX/LH 1310 nm single mode (SC) [10 km/6.2 miles] or multimode (SC) [550 m/1804 ft.] using a mode conditioning adapter.	https://www.perle.com/products/gigabit-media-converter-module.shtml	Media Converter Module: C-1000
05051040	C-1000-S2LC40 - Gigabit Media Converter Module: 1000BASE-T (RJ-45) [100 m/328 ft.] to 1000BASE-EX 1310 nm single mode (LC) [40 km/24.9 miles].	https://www.perle.com/products/gigabit-media-converter-module.shtml	Media Converter Module: C-1000
05051050	C-1000-S2SC70 - Gigabit Media Converter Module: 1000BASE-T (RJ-45) [100 m/328 ft.] to 1000BASE-ZX 1550 nm single mode (SC) [70 km/43.5 miles]	https://www.perle.com/products/gigabit-media-converter-module.shtml	Media Converter Module: C-1000
05051060	C-1000-S2LC70 - Gigabit Media Converter Module: 1000BASE-T (RJ-45) [100 m/328 ft.] to 1000BASE-ZX 1550 nm single mode (LC) [70 km/43.5 miles]	https://www.perle.com/products/gigabit-media-converter-module.shtml	Media Converter Module: C-1000
05051070	C-1000-S1SC10U - Gigabit Media Converter Module: 1000BASE-T (RJ-45) [100 m/328 ft.] to 1000BASE-BX 1310nm TX / 1490nm RX single strand fiber, single mode (SC) [10 km/6.2 miles]	https://www.perle.com/products/gigabit-media-converter-module.shtml	Media Converter Module: C-1000
05051080	C-1000-S1SC10D - Gigabit Media Converter Module: 1000BASE-T (RJ-45) [100 m/328 ft.] to 1000BASE-BX 1490nm TX / 1310nm RX single strand fiber, single mode (SC) [10 km/6.2 miles]	https://www.perle.com/products/gigabit-media-converter-module.shtml	Media Converter Module: C-1000

Part #	Description	Product Datasheet	Product Group
05051090	C-1000-S2SC40 - Gigabit Media Converter Module: 1000BASE-T (RJ-45) [100 m/328 ft.] to 1000BASE-EX 1310 nm single mode (SC) [40 km/24.9 miles].	https://www.perle.com/products/gigabit-media-converter-module.shtml	Media Converter Module: C-1000
05051100	C-1000-M2ST05 - Gigabit Media Converter Module: 1000BASE-T (RJ-45) [100 m/328 ft.] to 1000BASE-SX 850nm multimode (ST) [550 m/1804 ft.].	https://www.perle.com/products/gigabit-media-converter-module.shtml	Media Converter Module: C-1000
05051110	C-1000-S2ST10 - Gigabit Media Converter Module: 1000BASE-T (RJ-45) [100 m/328 ft.] to 1000BASE-LX/LH 1310 nm single mode (ST) [10 km/6.2 miles] or multimode (ST) [550 m/1804 ft.] using a mode conditioning adapter.	https://www.perle.com/products/gigabit-media-converter-module.shtml	Media Converter Module: C-1000
05051120	C-1000-S2ST40 - Gigabit Media Converter Module: 1000BASE-T (RJ-45) [100 m/328 ft.] to 1000BASE-EX 1310 nm single mode (ST) [40 km/24.9 miles].	https://www.perle.com/products/gigabit-media-converter-module.shtml	Media Converter Module: C-1000
05051130	C-1000-S2ST70 - Gigabit Media Converter Module: 1000BASE-T (RJ-45) [100 m/328 ft.] to 1000BASE-ZX 1550 nm single mode (ST) [70 km/43.5 miles]	https://www.perle.com/products/gigabit-media-converter-module.shtml	Media Converter Module: C-1000
05051140	C-1000-S2ST120 - Gigabit Media Converter Module: 1000BASE-T (RJ-45) [100 m/328 ft.] to 1000BASE-ZX 1550 nm single mode (ST) [120 km/74.6 miles]	https://www.perle.com/products/gigabit-media-converter-module.shtml	Media Converter Module: C-1000
05051150	C-1000-S2SC120 - Gigabit Media Converter Module: 1000BASE-T (RJ-45) [100 m/328 ft.] to 1000BASE-ZX 1550 nm single mode (SC) [120 km/74.6 miles]	https://www.perle.com/products/gigabit-media-converter-module.shtml	Media Converter Module: C-1000
05051160	C-1000-S2LC120 - Gigabit Media Converter Module: 1000BASE-T (RJ-45) [100 m/328 ft.] to 1000BASE-ZX 1550 nm single mode (LC) [120 km/74.6 miles]	https://www.perle.com/products/gigabit-media-converter-module.shtml	Media Converter Module: C-1000
05051180	C-1000-SFP - Gigabit Media Converter Module: 1000BASE-T (RJ-45) [100 m/328 ft.] to 1000BASE-X - SFP slot (empty)	https://www.perle.com/products/gigabit-sfp-media-converter-module.shtml	Media Converter Module: C-1000
05051190	C-1110-SFP - 10/100/1000Base-T Media and Rate Converter Module: 10/100/1000BASE-T (RJ-45) [100 m/328 ft.] to 1000BASE-X or 100BASE-X - SFP Slot (empty)	https://www.perle.com/products/10-100-1000-sfp-media-converter-module.shtml	Media Converter Module: C-1110
05051200	C-100-M2ST2 - Fast Ethernet Media Converter Module: 100BASE-TX (RJ-45) [100 m/328 ft.] to 100BASE-FX 1310nm multimode (ST) [2 km/1.2 miles]	https://www.perle.com/products/fast-ethernet-media-converter-module.shtml	Media Converter Module: C-100
05051210	C-100-M2SC2 - Fast Ethernet Media Converter Module: 100BASE-TX (RJ-45) [100 m/328 ft.] to 100BASE-FX 1310nm multimode (SC) [2 km/1.2 miles]	https://www.perle.com/products/fast-ethernet-media-converter-module.shtml	Media Converter Module: C-100

Part #	Description	Product Datasheet	Product Group
05051220	C-100-M2LC2 - Fast Ethernet Media Converter Module: 100BASE-TX (RJ-45) [100 m/328 ft.] to 100BASE-FX 1310nm multimode (LC) [2 km/1.2 miles]	https://www.perle.com/products/fast-ethernet-media-converter-module.shtml	Media Converter Module: C-100
05051230	C-100-S2SC20 - Fast Ethernet Media Converter Module: 100BASE-TX (RJ-45) [100 m/328 ft.] to 100Base-LX 1310nm single mode (SC) [20 km/12.4 miles]	https://www.perle.com/products/fast-ethernet-media-converter-module.shtml	Media Converter Module: C-100
05051240	C-100-S2LC20 - Fast Ethernet Media Converter Module: 100BASE-TX (RJ-45) [100 m/328 ft.] to 100Base-LX 1310nm single mode (LC) [20 km/12.4 miles]	https://www.perle.com/products/fast-ethernet-media-converter-module.shtml	Media Converter Module: C-100
05051250	C-100-S2SC40 - Fast Ethernet Media Converter Module: 100BASE-TX (RJ-45) [100 m/328 ft.] to 100Base-EX 1310nm single mode (SC) [40 km/24.9 miles]	https://www.perle.com/products/fast-ethernet-media-converter-module.shtml	Media Converter Module: C-100
05051260	C-100-S2SC80 - Fast Ethernet Media Converter Module: 100BASE-TX (RJ-45) [100 m/328 ft.] to 100Base-ZX 1550nm single mode (SC) [80 km/49.7 miles]	https://www.perle.com/products/fast-ethernet-media-converter-module.shtml	Media Converter Module: C-100
05051270	C-100-S1SC20U - Fast Ethernet Media Converter Module: 100Base-TX (RJ-45) [100 m/328 ft.] to 100Base-BX 1310nm TX / 1550nm RX single strand fiber, single mode (SC) [20 km/12.4 miles]	https://www.perle.com/products/fast-ethernet-media-converter-module.shtml	Media Converter Module: C-100
05051280	C-100-S1SC20D - Fast Ethernet Media Converter Module: 100Base-TX (RJ-45) [100 m/328 ft.] to 100Base-BX 1550nm TX / 1310nm RX single strand fiber, single mode (SC) [20 km/12.4 miles]	https://www.perle.com/products/fast-ethernet-media-converter-module.shtml	Media Converter Module: C-100
05051290	C-100-S1SC40U - Fast Ethernet Media Converter Module: 100Base-TX (RJ-45) [100 m/328 ft.] to 100Base-BX 1310nm TX / 1550nm RX single strand fiber, single mode (SC) [40 km/24.9 miles]	https://www.perle.com/products/fast-ethernet-media-converter-module.shtml	Media Converter Module: C-100
05051300	C-100-S1SC40D - Fast Ethernet Media Converter Module: 100Base-TX (RJ-45) [100 m/328 ft.] to 100Base-BX 1550nm TX / 1310nm RX single strand fiber, single mode (SC) [40 km/24.9 miles]	https://www.perle.com/products/fast-ethernet-media-converter-module.shtml	Media Converter Module: C-100
05051310	C-100-S2SC120 - Fast Ethernet Media Converter Module: 100BASE-TX (RJ-45) [100 m/328 ft.] to 100Base-ZX 1550nm single mode (SC) [120 km/74.6 miles]	https://www.perle.com/products/fast-ethernet-media-converter-module.shtml	Media Converter Module: C-100
05051320	C-100-S2ST20 - Fast Ethernet Media Converter Module: 100BASE-TX (RJ-45) [100 m/328 ft.] to 100Base-LX 1310nm single mode (ST) [20 km/12.4 miles]	https://www.perle.com/products/fast-ethernet-media-converter-module.shtml	Media Converter Module: C-100

Part #	Description	Product Datasheet	Product Group
05051330	C-100-S2ST40 - Fast Ethernet Media Converter Module: 100BASE-TX (RJ-45) [100 m/328 ft.] to 100Base-EX 1310nm single mode (ST) [40 km/24.9 miles]	https://www.perle.com/products/fast-ethernet-media-converter-module.shtml	Media Converter Module: C-100
05051340	C-100-S2ST80 - Fast Ethernet Media Converter Module: 100BASE-TX (RJ-45) [100 m/328 ft.] to 100Base-ZX 1550nm single mode (ST) [80 km/49.7 miles]	https://www.perle.com/products/fast-ethernet-media-converter-module.shtml	Media Converter Module: C-100
05051350	C-100-S2ST120 - Fast Ethernet Media Converter Module: 100BASE-TX (RJ-45) [100 m/328 ft.] to 100Base-ZX 1550nm single mode (ST) [120 km/74.6 miles]	https://www.perle.com/products/fast-ethernet-media-converter-module.shtml	Media Converter Module: C-100
05051360	C-100-S2LC40 - Fast Ethernet Media Converter Module: 100BASE-TX (RJ-45) [100 m/328 ft.] to 100Base-EX 1310nm single mode (LC) [40 km/24.9 miles]	https://www.perle.com/products/fast-ethernet-media-converter-module.shtml	Media Converter Module: C-100
05051370	C-100-S2LC80 - Fast Ethernet Media Converter Module: 100BASE-TX (RJ-45) [100 m/328 ft.] to 100Base-ZX 1550nm single mode (LC) [80 km/49.7 miles]	https://www.perle.com/products/fast-ethernet-media-converter-module.shtml	Media Converter Module: C-100
05051380	C-100-S2LC120 - Fast Ethernet Media Converter Module: 100BASE-TX (RJ-45) [100 m/328 ft.] to 100Base-ZX 1550nm single mode (LC) [120 km/74.6 miles]	https://www.perle.com/products/fast-ethernet-media-converter-module.shtml	Media Converter Module: C-100
05051400	C-110-M2ST2 - 10/100Base-TX Media and Rate Converter Module: 10/100Base-TX (RJ-45) [100 m/328 ft.] to 100BASE-FX 1310nm multimode (ST) [2 km/1.2 miles]	https://www.perle.com/products/10-100-media-converter-module.shtml	Media Converter Module: C-110
05051410	C-110-M2SC2 - 10/100Base-TX Media and Rate Converter Module: 10/100Base-TX (RJ-45) [100 m/328 ft.] to 100BASE-FX 1310nm multimode (SC) [2 km/1.2 miles]	https://www.perle.com/products/10-100-media-converter-module.shtml	Media Converter Module: C-110
05051420	C-110-M2LC2 - 10/100Base-TX Media and Rate Converter Module: 10/100Base-TX (RJ-45) [100 m/328 ft.] to 100BASE-FX 1310nm multimode (LC) [2 km/1.2 miles]	https://www.perle.com/products/10-100-media-converter-module.shtml	Media Converter Module: C-110
05051430	C-110-S2SC20 - 10/100Base-TX Media and Rate Converter Module: 10/100Base-TX (RJ-45) [100 m/328 ft.] to 100Base-LX 1310nm single mode (SC) [20 km/12.4 miles]	https://www.perle.com/products/10-100-media-converter-module.shtml	Media Converter Module: C-110
05051440	C-110-S2LC20 - 10/100Base-TX Media and Rate Converter Module: 10/100Base-TX (RJ-45) [100 m/328 ft.] to 100Base-LX 1310nm single mode (LC) [20 km/12.4 miles]	https://www.perle.com/products/10-100-media-converter-module.shtml	Media Converter Module: C-110

Part #	Description	Product Datasheet	Product Group
05051450	C-110-S2SC40 - 10/100Base-TX Media and Rate Converter Module: 10/100Base-TX (RJ-45) [100 m/328 ft.] to 100Base-EX 1310nm single mode (SC) [40 km/24.9 miles]	https://www.perle.com/products/10-100-media-converter-module.shtml	Media Converter Module: C-110
05051460	C-110-S2SC80 - 10/100Base-TX Media and Rate Converter Module: 10/100Base-TX (RJ-45) [100 m/328 ft.] to 100Base-ZX 1550nm single mode (SC) [80 km/49.7 miles]	https://www.perle.com/products/10-100-media-converter-module.shtml	Media Converter Module: C-110
05051470	C-110-S1SC20U - 10/100Base-TX Media and Rate Converter Module: 10/100Base-TX (RJ-45) [100 m/328 ft.] to 100Base-BX 1310nm TX / 1550nm RX single strand fiber, single mode (SC) [20 km/12.4 miles]	https://www.perle.com/products/10-100-media-converter-module.shtml	Media Converter Module: C-110
05051480	C-110-S1SC20D - 10/100Base-TX Media and Rate Converter Module: 10/100Base-TX (RJ-45) [100 m/328 ft.] to 100Base-BX 1550nm TX / 1310nm RX single strand fiber, single mode (SC) [20 km/12.4 miles]	https://www.perle.com/products/10-100-media-converter-module.shtml	Media Converter Module: C-110
05051490	C-110-S1SC40U - 10/100Base-TX Media and Rate Converter Module: 10/100Base-TX (RJ-45) [100 m/328 ft.] to 100Base-BX 1310nm TX / 1550nm RX single strand fiber, single mode (SC) [40 km/24.9 miles]	https://www.perle.com/products/10-100-media-converter-module.shtml	Media Converter Module: C-110
05051500	C-110-S1SC40D - 10/100Base-TX Media and Rate Converter Module: 10/100Base-TX (RJ-45) [100 m/328 ft.] to 100Base-BX 1550nm TX / 1310nm RX single strand fiber, single mode (SC) [40 km/24.9 miles]	https://www.perle.com/products/10-100-media-converter-module.shtml	Media Converter Module: C-110
05051510	C-110-S2SC120 - 10/100Base-TX Media and Rate Converter Module: 10/100Base-TX (RJ-45) [100 m/328 ft.] to 100Base-ZX 1550nm single mode (SC) [120 km/74.6 miles]	https://www.perle.com/products/10-100-media-converter-module.shtml	Media Converter Module: C-110
05051520	C-110-S2ST20 - 10/100Base-TX Media and Rate Converter Module: 10/100Base-TX (RJ-45) [100 m/328 ft.] to 100Base-LX 1310nm single mode (ST) [20 km/12.4 miles]	https://www.perle.com/products/10-100-media-converter-module.shtml	Media Converter Module: C-110
05051530	C-110-S2ST40 - 10/100Base-TX Media and Rate Converter Module: 10/100Base-TX (RJ-45) [100 m/328 ft.] to 100Base-EX 1310nm single mode (ST) [40 km/24.9 miles]	https://www.perle.com/products/10-100-media-converter-module.shtml	Media Converter Module: C-110
05051540	C-110-S2ST80 - 10/100Base-TX Media and Rate Converter Module: 10/100Base-TX (RJ-45) [100 m/328 ft.] to 100Base-ZX 1550nm single mode (ST) [80 km/49.7 miles]	https://www.perle.com/products/10-100-media-converter-module.shtml	Media Converter Module: C-110
05051550	C-110-S2ST120 - 10/100Base-TX Media and Rate Converter Module: 10/100Base-TX (RJ-45) [100 m/328 ft.] to 100Base-ZX 1550nm single mode (ST) [120 km/74.6 miles]	https://www.perle.com/products/10-100-media-converter-module.shtml	Media Converter Module: C-110

Part #	Description	Product Datasheet	Product Group
05051560	C-110-S2LC40 - 10/100Base-TX Media and Rate Converter Module: 10/100Base-TX (RJ-45) [100 m/328 ft.] to 100Base-EX 1310nm single mode (LC) [40 km/24.9 miles]	https://www.perle.com/products/10-100-media-converter-module.shtml	Media Converter Module: C-110
05051570	C-110-S2LC80 - 10/100Base-TX Media and Rate Converter Module: 10/100Base-TX (RJ-45) [100 m/328 ft.] to 100Base-ZX 1550nm single mode (LC) [80 km/49.7 miles]	https://www.perle.com/products/10-100-media-converter-module.shtml	Media Converter Module: C-110
05051580	C-110-S2LC120 - 10/100Base-TX Media and Rate Converter Module: 10/100Base-TX (RJ-45) [100 m/328 ft.] to 100Base-ZX 1550nm single mode (LC) [120 km/74.6 miles]	https://www.perle.com/products/10-100-media-converter-module.shtml	Media Converter Module: C-110
05051590	C-1110-S1SC120D - 10/100/1000Base-T Media and Rate Converter Module: 10/100/1000BASE-T (RJ-45) [100 m/328 ft.] to 1000BASE-BX 1590nm TX / 1510nm RX single strand fiber, single mode (SC) [120 km/75 miles]	https://www.perle.com/products/10-100-1000-media-converter-module.shtml	Media Converter Module: C-1110
05051600	C-1110-M2SC05 - 10/100/1000Base-T Media and Rate Converter Module: 10/100/1000BASE-T (RJ-45) [100 m/328 ft.] to 1000BASE-SX 850nm multimode (SC) [550 m/1804 ft.].	https://www.perle.com/products/10-100-1000-media-converter-module.shtml	Media Converter Module: C-1110
05051610	C-1110-M2LC05 - 10/100/1000Base-T Media and Rate Converter Module: 10/100/1000BASE-T (RJ-45) [100 m/328 ft.] to 1000BASE-SX 850nm multimode (LC) [550 m/1804 ft.].	https://www.perle.com/products/10-100-1000-media-converter-module.shtml	Media Converter Module: C-1110
05051620	C-1110-S2LC10 - 10/100/1000Base-T Media and Rate Converter Module: 10/100/1000BASE-T (RJ-45) [100 m/328 ft.] to 1000BASE-LX/LH 1310 nm single mode (LC) [10 km/6.2 miles] or multimode (LC) [550 m/1804 ft.] using a mode conditioning patch cord.	https://www.perle.com/products/10-100-1000-media-converter-module.shtml	Media Converter Module: C-1110
05051630	C-1110-S2SC10 - 10/100/1000Base-T Media and Rate Converter Module: 10/100/1000BASE-T (RJ-45) [100 m/328 ft.] to 1000BASE-LX/LH 1310 nm single mode (SC) [10 km/6.2 miles] or multimode (SC) [550 m/1804 ft.] using a mode conditioning adapter.	https://www.perle.com/products/10-100-1000-media-converter-module.shtml	Media Converter Module: C-1110
05051640	C-1110-S2LC40 - 10/100/1000Base-T Media and Rate Converter Module: 10/100/1000BASE-T (RJ-45) [100 m/328 ft.] to 1000BASE-EX 1310 nm single mode (LC) [40 km/24.9 miles].	https://www.perle.com/products/10-100-1000-media-converter-module.shtml	Media Converter Module: C-1110
05051650	C-1110-S2SC70 - 10/100/1000Base-T Media and Rate Converter Module: 10/100/1000BASE-T (RJ-45) [100 m/328 ft.] to 1000BASE-ZX 1550 nm single mode (SC) [70 km/43.5 miles]	https://www.perle.com/products/10-100-1000-media-converter-module.shtml	Media Converter Module: C-1110

Part #	Description	Product Datasheet	Product Group
05051660	C-1110-S2LC70 - 10/100/1000Base-T Media and Rate Converter Module: 10/100/1000BASE-T (RJ-45) [100 m/328 ft.] to 1000BASE-ZX 1550 nm single mode (LC) [70 km/43.5 miles]	https://www.perle.com/products/10-100-1000-media-converter-module.shtml	Media Converter Module: C-1110
05051670	C-1110-S1SC10U - 10/100/1000Base-T Media and Rate Converter Module: 10/100/1000BASE-T (RJ-45) [100 m/328 ft.] to 1000BASE-BX 1310nm TX / 1490nm RX single strand fiber, single mode (SC) [10 km/6.2 miles]	https://www.perle.com/products/10-100-1000-media-converter-module.shtml	Media Converter Module: C-1110
05051680	C-1110-S1SC10D - 10/100/1000Base-T Media and Rate Converter Module: 10/100/1000BASE-T (RJ-45) [100 m/328 ft.] to 1000BASE-BX 1490nm TX / 1310nm RX single strand fiber, single mode (SC) [10 km/6.2 miles]	https://www.perle.com/products/10-100-1000-media-converter-module.shtml	Media Converter Module: C-1110
05051690	C-1110-S2SC40 - 10/100/1000Base-T Media and Rate Converter Module: 10/100/1000BASE-T (RJ-45) [100 m/328 ft.] to 1000BASE-EX 1310 nm single mode (SC) [40 km/24.9 miles].	https://www.perle.com/products/10-100-1000-media-converter-module.shtml	Media Converter Module: C-1110
05051710	C-1110-M2ST05 - 10/100/1000Base-T Media and Rate Converter Module: 10/100/1000BASE-T (RJ-45) [100 m/328 ft.] to 1000BASE-SX 850nm multimode (ST) [550 m/1804 ft.].	https://www.perle.com/products/10-100-1000-media-converter-module.shtml	Media Converter Module: C-1110
05051720	C-1110-S2ST10 - 10/100/1000Base-T Media and Rate Converter Module: 10/100/1000BASE-T (RJ-45) [100 m/328 ft.] to 1000BASE-LX/LH 1310 nm single mode (ST) [10 km/6.2 miles] or multimode (ST) [550 m/1804 ft.] using a mode conditioning adapter.	https://www.perle.com/products/10-100-1000-media-converter-module.shtml	Media Converter Module: C-1110
05051730	C-1110-S2ST40 - 10/100/1000Base-T Media and Rate Converter Module: 10/100/1000BASE-T (RJ-45) [100 m/328 ft.] to 1000BASE-EX 1310 nm single mode (ST) [40 km/24.9 miles].	https://www.perle.com/products/10-100-1000-media-converter-module.shtml	Media Converter Module: C-1110
05051740	C-1110-S2ST70 - 10/100/1000Base-T Media and Rate Converter Module: 10/100/1000BASE-T (RJ-45) [100 m/328 ft.] to 1000BASE-ZX 1550 nm single mode (ST) [70 km/43.5 miles]	https://www.perle.com/products/10-100-1000-media-converter-module.shtml	Media Converter Module: C-1110
05051750	C-1110-S2ST120 - 10/100/1000Base-T Media and Rate Converter Module: 10/100/1000BASE-T (RJ-45) [100 m/328 ft.] to 1000BASE-ZX 1550 nm single mode (ST) [120 km/74.6 miles]	https://www.perle.com/products/10-100-1000-media-converter-module.shtml	Media Converter Module: C-1110
05051760	C-1110-S2SC120 - 10/100/1000Base-T Media and Rate Converter Module: 10/100/1000BASE-T (RJ-45) [100 m/328 ft.] to 1000BASE-ZX 1550 nm single mode (SC) [120 km/74.6 miles]	https://www.perle.com/products/10-100-1000-media-converter-module.shtml	Media Converter Module: C-1110

Part #	Description	Product Datasheet	Product Group
05051770	C-1110-S2LC120 - 10/100/1000Base-T Media and Rate Converter Module: 10/100/1000BASE-T (RJ-45) [100 m/328 ft.] to 1000BASE-ZX 1550 nm single mode (LC) [120 km/74.6 miles]	https://www.perle.com/products/10-100-1000-media-converter-module.shtml	Media Converter Module: C-1110
05051780	C-1000-S2ST160 - Gigabit Media Converter Module: 1000BASE-T (RJ-45) [100 m/328 ft.] to 1000BASE-ZX 1550 nm single mode (ST) [160 km/100 miles]	https://www.perle.com/products/gigabit-media-converter-module.shtml	Media Converter Module: C-1000
05051790	C-1000-S2SC160 - Gigabit Media Converter Module: 1000BASE-T (RJ-45) [100 m/328 ft.] to 1000BASE-ZX 1550 nm single mode (SC) [160 km/100 miles]	https://www.perle.com/products/gigabit-media-converter-module.shtml	Media Converter Module: C-1000
05051800	C-1000-S2LC160 - Gigabit Media Converter Module: 1000BASE-T (RJ-45) [100 m/328 ft.] to 1000BASE-ZX 1550 nm single mode (LC) [160 km/100 miles]	https://www.perle.com/products/gigabit-media-converter-module.shtml	Media Converter Module: C-1000
05051810	C-1000-S1SC20U - Gigabit Media Converter Module: 1000BASE-T (RJ-45) [100 m/328 ft.] to 1000BASE-BX 1310nm TX / 1490nm RX single strand fiber, single mode (SC) [20 km/12.4 miles]	https://www.perle.com/products/gigabit-media-converter-module.shtml	Media Converter Module: C-1000
05051820	C-1000-S1SC20D - Gigabit Media Converter Module: 1000BASE-T (RJ-45) [100 m/328 ft.] to 1000BASE-BX 1490nm TX / 1310nm RX single strand fiber, single mode (SC) [20 km/12.4 miles]	https://www.perle.com/products/gigabit-media-converter-module.shtml	Media Converter Module: C-1000
05051830	C-1000-S1SC40U - Gigabit Media Converter Module: 1000BASE-T (RJ-45) [100 m/328 ft.] to 1000BASE-BX 1310nm TX / 1490nm RX single strand fiber, single mode (SC) [40 km/25 miles]	https://www.perle.com/products/gigabit-media-converter-module.shtml	Media Converter Module: C-1000
05051840	C-1000-S1SC40D - Gigabit Media Converter Module: 1000BASE-T (RJ-45) [100 m/328 ft.] to 1000BASE-BX 1490nm TX / 1310nm RX single strand fiber, single mode (SC) [40 km/25 miles]	https://www.perle.com/products/gigabit-media-converter-module.shtml	Media Converter Module: C-1000
05051850	C-1000-S1SC80U - Gigabit Media Converter Module: 1000BASE-T (RJ-45) [100 m/328 ft.] to 1000BASE-BX 1510nm TX / 1590nm RX single strand fiber, single mode (SC) [80 km/50 miles]	https://www.perle.com/products/gigabit-media-converter-module.shtml	Media Converter Module: C-1000
05051860	C-1000-S1SC80D - Gigabit Media Converter Module: 1000BASE-T (RJ-45) [100 m/328 ft.] to 1000BASE-BX 1590nm TX / 1510nm RX single strand fiber, single mode (SC) [80 km/50 miles]	https://www.perle.com/products/gigabit-media-converter-module.shtml	Media Converter Module: C-1000
05051870	C-1000-S1SC120U - Gigabit Media Converter Module: 1000BASE-T (RJ-45) [100 m/328 ft.] to 1000BASE-BX 1510nm TX / 1590nm RX single strand fiber, single mode (SC) [120 km/75 miles]	https://www.perle.com/products/gigabit-media-converter-module.shtml	Media Converter Module: C-1000

Part #	Description	Product Datasheet	Product Group
05051880	C-1000-S1SC120D - Gigabit Media Converter Module: 1000BASE-T (RJ-45) [100 m/328 ft.] to 1000BASE-BX 1590nm TX / 1510nm RX single strand fiber, single mode (SC) [120 km/75 miles]	https://www.perle.com/products/gigabit-media-converter-module.shtml	Media Converter Module: C-1000
05051890	C-1110-S2ST160 - 10/100/1000Base-T Media and Rate Converter Module: 10/100/1000BASE-T (RJ-45) [100 m/328 ft.] to 1000BASE-ZX 1550 nm single mode (ST) [160 km/100 miles]	https://www.perle.com/products/10-100-1000-media-converter-module.shtml	Media Converter Module: C-1110
05051900	MCR-MGT Management Module for the MCR chassis: 10/100/1000 ethernet RJ45, serial console port RJ45, SNMP read/write, Telnet/SSH and Internet Browser access and advanced security	https://www.perle.com/products/media-converter-management-module.shtml	MCR-MGT Management Module
05051910	C-1110-S2SC160 - 10/100/1000Base-T Media and Rate Converter Module: 10/100/1000BASE-T (RJ-45) [100 m/328 ft.] to 1000BASE-ZX 1550 nm single mode (SC) [160 km/100 miles]	https://www.perle.com/products/10-100-1000-media-converter-module.shtml	Media Converter Module: C-1110
05051920	C-1110-S2LC160 - 10/100/1000Base-T Media and Rate Converter Module: 10/100/1000BASE-T (RJ-45) [100 m/328 ft.] to 1000BASE-ZX 1550 nm single mode (LC) [160 km/100 miles]	https://www.perle.com/products/10-100-1000-media-converter-module.shtml	Media Converter Module: C-1110
05051930	C-1110-S1SC20U - 10/100/1000Base-T Media and Rate Converter Module: 10/100/1000BASE-T (RJ-45) [100 m/328 ft.] to 1000BASE-BX 1310nm TX / 1490nm RX single strand fiber, single mode (SC) [20 km/12.4 miles]	https://www.perle.com/products/10-100-1000-media-converter-module.shtml	Media Converter Module: C-1110
05051940	C-1110-S1SC20D - 10/100/1000Base-T Media and Rate Converter Module: 10/100/1000BASE-T (RJ-45) [100 m/328 ft.] to 1000BASE-BX 1490nm TX / 1310nm RX single strand fiber, single mode (SC) [20 km/12.4 miles]	https://www.perle.com/products/10-100-1000-media-converter-module.shtml	Media Converter Module: C-1110
05051950	C-1110-S1SC40U - 10/100/1000Base-T Media and Rate Converter Module: 10/100/1000BASE-T (RJ-45) [100 m/328 ft.] to 1000BASE-BX 1310nm TX / 1490nm RX single strand fiber, single mode (SC) [40 km/25 miles]	https://www.perle.com/products/10-100-1000-media-converter-module.shtml	Media Converter Module: C-1110
05051960	C-1110-S1SC40D - 10/100/1000Base-T Media and Rate Converter Module: 10/100/1000BASE-T (RJ-45) [100 m/328 ft.] to 1000BASE-BX 1490nm TX / 1310nm RX single strand fiber, single mode (SC) [40 km/25 miles]	https://www.perle.com/products/10-100-1000-media-converter-module.shtml	Media Converter Module: C-1110
05051970	C-1110-S1SC80U - 10/100/1000Base-T Media and Rate Converter Module: 10/100/1000BASE-T (RJ-45) [100 m/328 ft.] to 1000BASE-BX 1510nm TX / 1590nm RX single strand fiber, single mode (SC) [80 km/50 miles]	https://www.perle.com/products/10-100-1000-media-converter-module.shtml	Media Converter Module: C-1110

Part #	Description	Product Datasheet	Product Group
05051980	C-1110-S1SC80D - 10/100/1000Base-T Media and Rate Converter Module: 10/100/1000BASE-T (RJ-45) [100 m/328 ft.] to 1000BASE-BX 1590nm TX / 1510nm RX single strand fiber, single mode (SC) [80 km/50 miles]	https://www.perle.com/products/10-100-1000-media-converter-module.shtml	Media Converter Module: C-1110
05051990	C-1110-S1SC120U - 10/100/1000Base-T Media and Rate Converter Module: 10/100/1000BASE-T (RJ-45) [100 m/328 ft.] to 1000BASE-BX 1510nm TX / 1590nm RX single strand fiber, single mode (SC) [120 km/75 miles]	https://www.perle.com/products/10-100-1000-media-converter-module.shtml	Media Converter Module: C-1110
05052000	CM-1000-M2SC05 - Managed Gigabit Media Converter Module: 1000BASE-T (RJ-45) [100 m/328 ft.] to 1000BASE-SX 850nm multimode (SC) [550 m/1804 ft.]. Managed or unmanaged operation	https://www.perle.com/products/gigabit-managed-media-converter-module.shtml	Media Converter Module: CM-1000
05052010	CM-1000-M2LC05 - Managed Gigabit Media Converter Module: 1000BASE-T (RJ-45) [100 m/328 ft.] to 1000BASE-SX 850nm multimode (LC) [550 m/1804 ft.]. Managed or unmanaged operation	https://www.perle.com/products/gigabit-managed-media-converter-module.shtml	Media Converter Module: CM-1000
05052020	CM-1000-S2LC10 - Managed Gigabit Media Converter Module: 1000BASE-T (RJ-45) [100 m/328 ft.] to 1000BASE-LX/LH 1310 nm single mode (LC) [10 km/6.2 miles] or multimode (LC) [550 m/1804 ft.] using a mode conditioning patch cord. Managed or unmanaged operation	https://www.perle.com/products/gigabit-managed-media-converter-module.shtml	Media Converter Module: CM-1000
05052030	CM-1000-S2SC10 - Managed Gigabit Media Converter Module: 1000BASE-T (RJ-45) [100 m/328 ft.] to 1000BASE-LX/LH 1310 nm single mode (SC) [10 km/6.2 miles] or multimode (SC) [550 m/1804 ft.] using a mode conditioning adapter. Managed or unmanaged operation	https://www.perle.com/products/gigabit-managed-media-converter-module.shtml	Media Converter Module: CM-1000
05052040	CM-1000-S2LC40 - Managed Gigabit Media Converter Module: 1000BASE-T (RJ-45) [100 m/328 ft.] to 1000BASE-EX 1310 nm single mode (LC) [40 km/24.9 miles]. Managed or unmanaged operation	https://www.perle.com/products/gigabit-managed-media-converter-module.shtml	Media Converter Module: CM-1000
05052050	CM-1000-S2SC70 - Managed Gigabit Media Converter Module: 1000BASE-T (RJ-45) [100 m/328 ft.] to 1000BASE-ZX 1550 nm single mode (SC) [70 km/43.5 miles]. Managed or unmanaged operation	https://www.perle.com/products/gigabit-managed-media-converter-module.shtml	Media Converter Module: CM-1000
05052060	CM-1000-S2LC70 - Managed Gigabit Media Converter Module: 1000BASE-T (RJ-45) [100 m/328 ft.] to 1000BASE-ZX 1550 nm single mode (LC) [70 km/43.5 miles]. Managed or unmanaged operation	https://www.perle.com/products/gigabit-managed-media-converter-module.shtml	Media Converter Module: CM-1000
05052070	CM-1000-S1SC10U - Managed Gigabit Media Converter Module: 1000BASE-T (RJ-45) [100 m/328 ft.] to 1000BASE-BX 1310nm TX / 1490nm RX single strand fiber, single mode (SC) [10 km/6.2 miles]. Managed or unmanaged operation	https://www.perle.com/products/gigabit-managed-media-converter-module.shtml	Media Converter Module: CM-1000

Part #	Description	Product Datasheet	Product Group
05052080	CM-1000-S1SC10D - Managed Gigabit Media Converter Module: 1000BASE-T (RJ-45) [100 m/328 ft.] to 1000BASE-BX 1490nm TX / 1310nm RX single strand fiber, single mode (SC) [10 km/6.2 miles]. Managed or unmanaged operation	https://www.perle.com/products/gigabit-managed-media-converter-module.shtml	Media Converter Module: CM-1000
05052090	CM-1000-S2SC40 - Managed Gigabit Media Converter Module: 1000BASE-T (RJ-45) [100 m/328 ft.] to 1000BASE-EX 1310 nm single mode (SC) [40 km/24.9 miles]. Managed or unmanaged operation	https://www.perle.com/products/gigabit-managed-media-converter-module.shtml	Media Converter Module: CM-1000
05052100	CM-1000-M2ST05 - Managed Gigabit Media Converter Module: 1000BASE-T (RJ-45) [100 m/328 ft.] to 1000BASE-SX 850nm multimode (ST) [550 m/1804 ft.]. Managed or unmanaged operation	https://www.perle.com/products/gigabit-managed-media-converter-module.shtml	Media Converter Module: CM-1000
05052110	CM-1000-S2ST10 - Managed Gigabit Media Converter Module: 1000BASE-T (RJ-45) [100 m/328 ft.] to 1000BASE-LX/LH 1310 nm single mode (ST) [10 km/6.2 miles]. Managed or unmanaged operation	https://www.perle.com/products/gigabit-managed-media-converter-module.shtml	Media Converter Module: CM-1000
05052120	CM-1000-S2ST40 - Managed Gigabit Media Converter Module: 1000BASE-T (RJ-45) [100 m/328 ft.] to 1000BASE-EX 1310 nm single mode (ST) [40 km/24.9 miles]. Managed or unmanaged operation	https://www.perle.com/products/gigabit-managed-media-converter-module.shtml	Media Converter Module: CM-1000
05052130	CM-1000-S2ST70 - Managed Gigabit Media Converter Module: 1000BASE-T (RJ-45) [100 m/328 ft.] to 1000BASE-ZX 1550 nm single mode (ST) [70 km/43.5 miles]. Managed or unmanaged operation	https://www.perle.com/products/gigabit-managed-media-converter-module.shtml	Media Converter Module: CM-1000
05052140	CM-1000-S2ST120 - Managed Gigabit Media Converter Module: 1000BASE-T (RJ-45) [100 m/328 ft.] to 1000BASE-ZX 1550 nm single mode (ST) [120 km/74.6 miles]. Managed or unmanaged operation	https://www.perle.com/products/gigabit-managed-media-converter-module.shtml	Media Converter Module: CM-1000
05052150	CM-1000-S2SC120 - Managed Gigabit Media Converter Module: 1000BASE-T (RJ-45) [100 m/328 ft.] to 1000BASE-ZX 1550 nm single mode (SC) [120 km/74.6 miles]. Managed or unmanaged operation	https://www.perle.com/products/gigabit-managed-media-converter-module.shtml	Media Converter Module: CM-1000
05052160	CM-1000-S2LC120 - Managed Gigabit Media Converter Module: 1000BASE-T (RJ-45) [100 m/328 ft.] to 1000BASE-ZX 1550 nm single mode (LC) [120 km/74.6 miles]. Managed or unmanaged operation	https://www.perle.com/products/gigabit-managed-media-converter-module.shtml	Media Converter Module: CM-1000
05052180	CM-1000-SFP - Managed Gigabit Media Converter Module: 1000BASE-T (RJ-45) [100 m/328 ft.] to 1000BASE-X - SFP slot (empty). Managed or unmanaged operation	https://www.perle.com/products/gigabit-sfp-managed-media-converter-module.shtml	Media Converter Module: CM-1000
05052190	CM-1110-SFP - Managed 10/100/1000Base-T Media and Rate Converter Module: 10/100/1000BASE-T (RJ-45) [100 m/328 ft.] to 1000BASE-X or 100BASE-X - SFP Slot (empty). Managed or unmanaged operation	https://www.perle.com/products/10-100-1000-sfp-managed-media-converter-module.shtml	Media Converter Module: CM-1110

Part #	Description	Product Datasheet	Product Group
05052200	CM-100-M2ST2 - Managed Fast Ethernet Media Converter Module: 100BASE-TX (RJ-45) [100 m/328 ft.] to 100BASE-FX 1310nm multimode (ST) [2 km/1.2 miles]. Managed or unmanaged operation	https://www.perle.com/products/fast-ethernet-managed-media-converter-module.shtml	Media Converter Module: CM-100
05052210	CM-100-M2SC2 - Managed Fast Ethernet Media Converter Module: 100BASE-TX (RJ-45) [100 m/328 ft.] to 100BASE-FX 1310nm multimode (SC) [2 km/1.2 miles]. Managed or unmanaged operation	https://www.perle.com/products/fast-ethernet-managed-media-converter-module.shtml	Media Converter Module: CM-100
05052220	CM-100-M2LC2 - Managed Fast Ethernet Media Converter Module: 100BASE-TX (RJ-45) [100 m/328 ft.] to 100BASE-FX 1310nm multimode (LC) [2 km/1.2 miles]. Managed or unmanaged operation	https://www.perle.com/products/fast-ethernet-managed-media-converter-module.shtml	Media Converter Module: CM-100
05052230	CM-100-S2SC20 - Managed Fast Ethernet Media Converter Module: 100BASE-TX (RJ-45) [100 m/328 ft.] to 100Base-LX 1310nm single mode (SC) [20 km/12.4 miles]. Managed or unmanaged operation	https://www.perle.com/products/fast-ethernet-managed-media-converter-module.shtml	Media Converter Module: CM-100
05052240	CM-100-S2LC20 - Managed Fast Ethernet Media Converter Module: 100BASE-TX (RJ-45) [100 m/328 ft.] to 100Base-LX 1310nm single mode (LC) [20 km/12.4 miles]. Managed or unmanaged operation	https://www.perle.com/products/fast-ethernet-managed-media-converter-module.shtml	Media Converter Module: CM-100
05052250	CM-100-S2SC40 - Managed Fast Ethernet Media Converter Module: 100BASE-TX (RJ-45) [100 m/328 ft.] to 100Base-EX 1310nm single mode (SC) [40 km/24.9 miles]. Managed or unmanaged operation	https://www.perle.com/products/fast-ethernet-managed-media-converter-module.shtml	Media Converter Module: CM-100
05052260	CM-100-S2SC80 - Managed Fast Ethernet Media Converter Module: 100BASE-TX (RJ-45) [100 m/328 ft.] to 100Base-ZX 1550nm single mode (SC) [80 km/49.7 miles]. Managed or unmanaged operation	https://www.perle.com/products/fast-ethernet-managed-media-converter-module.shtml	Media Converter Module: CM-100
05052270	CM-100-S1SC20U - Managed Fast Ethernet Media Converter Module: 100Base-TX (RJ-45) [100 m/328 ft.] to 100Base-BX 1310nm TX / 1550nm RX single strand fiber, single mode (SC) [20 km/12.4 miles]. Managed or unmanaged operation	https://www.perle.com/products/fast-ethernet-managed-media-converter-module.shtml	Media Converter Module: CM-100
05052280	CM-100-S1SC20D - Managed Fast Ethernet Media Converter Module: 100Base-TX (RJ-45) [100 m/328 ft.] to 100Base-BX 1550nm TX / 1310nm RX single strand fiber, single mode (SC) [20 km/12.4 miles]. Managed or unmanaged operation	https://www.perle.com/products/fast-ethernet-managed-media-converter-module.shtml	Media Converter Module: CM-100
05052290	CM-100-S1SC40U - Managed Fast Ethernet Media Converter Module: 100Base-TX (RJ-45) [100 m/328 ft.] to 100Base-BX 1310nm TX / 1550nm RX single strand fiber, single mode (SC) [40 km/24.9 miles]. Managed or unmanaged operation	https://www.perle.com/products/fast-ethernet-managed-media-converter-module.shtml	Media Converter Module: CM-100

Part #	Description	Product Datasheet	Product Group
05052300	CM-100-S1SC40D - Managed Fast Ethernet Media Converter Module: 100Base-TX (RJ-45) [100 m/328 ft.] to 100Base-BX 1550nm TX / 1310nm RX single strand fiber, single mode (SC) [40 km/24.9 miles]. Managed or unmanaged operation	https://www.perle.com/products/fast-ethernet-managed-media-converter-module.shtml	Media Converter Module: CM-100
05052310	CM-100-S2SC120 - Managed Fast Ethernet Media Converter Module: 100BASE-TX (RJ-45) [100 m/328 ft.] to 100Base-ZX 1550nm single mode (SC) [120 km/74.6 miles]. Managed or unmanaged operation	https://www.perle.com/products/fast-ethernet-managed-media-converter-module.shtml	Media Converter Module: CM-100
05052320	CM-100-S2ST20 - Managed Fast Ethernet Media Converter Module: 100BASE-TX (RJ-45) [100 m/328 ft.] to 100Base-LX 1310nm single mode (ST) [20 km/12.4 miles]. Managed or unmanaged operation	https://www.perle.com/products/fast-ethernet-managed-media-converter-module.shtml	Media Converter Module: CM-100
05052330	CM-100-S2ST40 - Managed Fast Ethernet Media Converter Module: 100BASE-TX (RJ-45) [100 m/328 ft.] to 100Base-EX 1310nm single mode (ST) [40 km/24.9 miles]. Managed or unmanaged operation	https://www.perle.com/products/fast-ethernet-managed-media-converter-module.shtml	Media Converter Module: CM-100
05052340	CM-100-S2ST80 - Managed Fast Ethernet Media Converter Module: 100BASE-TX (RJ-45) [100 m/328 ft.] to 100Base-ZX 1550nm single mode (ST) [80 km/49.7 miles]. Managed or unmanaged operation	https://www.perle.com/products/fast-ethernet-managed-media-converter-module.shtml	Media Converter Module: CM-100
05052350	CM-100-S2ST120 - Managed Fast Ethernet Media Converter Module: 100BASE-TX (RJ-45) [100 m/328 ft.] to 100Base-ZX 1550nm single mode (ST) [120 km/74.6 miles]. Managed or unmanaged operation	https://www.perle.com/products/fast-ethernet-managed-media-converter-module.shtml	Media Converter Module: CM-100
05052360	CM-100-S2LC40 - Managed Fast Ethernet Media Converter Module: 100BASE-TX (RJ-45) [100 m/328 ft.] to 100Base-EX 1310nm single mode (LC) [40 km/24.9 miles]. Managed or unmanaged operation	https://www.perle.com/products/fast-ethernet-managed-media-converter-module.shtml	Media Converter Module: CM-100
05052370	CM-100-S2LC80 - Managed Fast Ethernet Media Converter Module: 100BASE-TX (RJ-45) [100 m/328 ft.] to 100Base-ZX 1550nm single mode (LC) [80 km/49.7 miles]. Managed or unmanaged operation	https://www.perle.com/products/fast-ethernet-managed-media-converter-module.shtml	Media Converter Module: CM-100
05052380	CM-100-S2LC120 - Managed Fast Ethernet Media Converter Module: 100BASE-TX (RJ-45) [100 m/328 ft.] to 100Base-ZX 1550nm single mode (LC) [120 km/74.6 miles]. Managed or unmanaged operation	https://www.perle.com/products/fast-ethernet-managed-media-converter-module.shtml	Media Converter Module: CM-100
05052400	CM-110-M2ST2 - Managed 10/100Base-TX Media and Rate Converter Module: 10/100Base-TX (RJ-45) [100 m/328 ft.] to 100BASE-FX 1310nm multimode (ST) [2 km/1.2 miles]. Managed or unmanaged operation	https://www.perle.com/products/10-100-managed-media-converter-module.shtml	Media Converter Module: CM-110
05052410	CM-110-M2SC2 - Managed 10/100Base-TX Media and Rate Converter Module: 10/100Base-TX (RJ-45) [100 m/328 ft.] to 100BASE-FX 1310nm multimode (SC) [2 km/1.2 miles]. Managed or unmanaged operation	https://www.perle.com/products/10-100-managed-media-converter-module.shtml	Media Converter Module: CM-110

Part #	Description	Product Datasheet	Product Group
05052420	CM-110-M2LC2 - Managed 10/100Base-TX Media and Rate Converter Module: 10/100Base-TX (RJ-45) [100 m/328 ft.] to 100BASE-FX 1310nm multimode (LC) [2 km/1.2 miles]. Managed or unmanaged operation	https://www.perle.com/products/10-100-managed-media-converter-module.shtml	Media Converter Module: CM-110
05052430	CM-110-S2SC20 - Managed 10/100Base-TX Media and Rate Converter Module: 10/100Base-TX (RJ-45) [100 m/328 ft.] to 100Base-LX 1310nm single mode (SC) [20 km/12.4 miles]. Managed or unmanaged operation	https://www.perle.com/products/10-100-managed-media-converter-module.shtml	Media Converter Module: CM-110
05052440	CM-110-S2LC20 - Managed 10/100Base-TX Media and Rate Converter Module: 10/100Base-TX (RJ-45) [100 m/328 ft.] to 100Base-LX 1310nm single mode (LC) [20 km/12.4 miles]. Managed or unmanaged operation	https://www.perle.com/products/10-100-managed-media-converter-module.shtml	Media Converter Module: CM-110
05052450	CM-110-S2SC40 - Managed 10/100Base-TX Media and Rate Converter Module: 10/100Base-TX (RJ-45) [100 m/328 ft.] to 100Base-EX 1310nm single mode (SC) [40 km/24.9 miles]. Managed or unmanaged operation	https://www.perle.com/products/10-100-managed-media-converter-module.shtml	Media Converter Module: CM-110
05052460	CM-110-S2SC80 - Managed 10/100Base-TX Media and Rate Converter Module: 10/100Base-TX (RJ-45) [100 m/328 ft.] to 100Base-ZX 1550nm single mode (SC) [80 km/49.7 miles]. Managed or unmanaged operation	https://www.perle.com/products/10-100-managed-media-converter-module.shtml	Media Converter Module: CM-110
05052470	CM-110-S1SC20U - Managed 10/100Base-TX Media and Rate Converter Module: 10/100Base-TX (RJ-45) [100 m/328 ft.] to 100Base-BX 1310nm TX / 1550nm RX single strand fiber, single mode (SC) [20 km/12.4 miles]. Managed or unmanaged operation	https://www.perle.com/products/10-100-managed-media-converter-module.shtml	Media Converter Module: CM-110
05052480	CM-110-S1SC20D - Managed 10/100Base-TX Media and Rate Converter Module: 10/100Base-TX (RJ-45) [100 m/328 ft.] to 100Base-BX 1550nm TX / 1310nm RX single strand fiber, single mode (SC) [20 km/12.4 miles]. Managed or unmanaged operation	https://www.perle.com/products/10-100-managed-media-converter-module.shtml	Media Converter Module: CM-110
05052490	CM-110-S1SC40U - Managed 10/100Base-TX Media and Rate Converter Module: 10/100Base-TX (RJ-45) [100 m/328 ft.] to 100Base-BX 1310nm TX / 1550nm RX single strand fiber, single mode (SC) [40 km/24.9 miles]. Managed or unmanaged operation	https://www.perle.com/products/10-100-managed-media-converter-module.shtml	Media Converter Module: CM-110
05052500	CM-110-S1SC40D - Managed 10/100Base-TX Media and Rate Converter Module: 10/100Base-TX (RJ-45) [100 m/328 ft.] to 100Base-BX 1550nm TX / 1310nm RX single strand fiber, single mode (SC) [40 km/24.9 miles]. Managed or unmanaged operation	https://www.perle.com/products/10-100-managed-media-converter-module.shtml	Media Converter Module: CM-110
05052510	CM-110-S2SC120 - Managed 10/100Base-TX Media and Rate Converter Module: 10/100Base-TX (RJ-45) [100 m/328 ft.] to 100Base-ZX 1550nm single mode (SC) [120 km/74.6 miles]. Managed or unmanaged operation	https://www.perle.com/products/10-100-managed-media-converter-module.shtml	Media Converter Module: CM-110

Part #	Description	Product Datasheet	Product Group
05052520	CM-110-S2ST20 - Managed 10/100Base-TX Media and Rate Converter Module: 10/100Base-TX (RJ-45) [100 m/328 ft.] to 100Base-LX 1310nm single mode (ST) [20 km/12.4 miles]. Managed or unmanaged operation	https://www.perle.com/products/10-100-managed-media-converter-module.shtml	Media Converter Module: CM-110
05052530	CM-110-S2ST40 - Managed 10/100Base-TX Media and Rate Converter Module: 10/100Base-TX (RJ-45) [100 m/328 ft.] to 100Base-EX 1310nm single mode (ST) [40 km/24.9 miles]. Managed or unmanaged operation	https://www.perle.com/products/10-100-managed-media-converter-module.shtml	Media Converter Module: CM-110
05052540	CM-110-S2ST80 - Managed 10/100Base-TX Media and Rate Converter Module: 10/100Base-TX (RJ-45) [100 m/328 ft.] to 100Base-ZX 1550nm single mode (ST) [80 km/49.7 miles]. Managed or unmanaged operation	https://www.perle.com/products/10-100-managed-media-converter-module.shtml	Media Converter Module: CM-110
05052550	CM-110-S2ST120 - Managed 10/100Base-TX Media and Rate Converter Module: 10/100Base-TX (RJ-45) [100 m/328 ft.] to 100Base-ZX 1550nm single mode (ST) [120 km/74.6 miles]. Managed or unmanaged operation	https://www.perle.com/products/10-100-managed-media-converter-module.shtml	Media Converter Module: CM-110
05052560	CM-110-S2LC40 - Managed 10/100Base-TX Media and Rate Converter Module: 10/100Base-TX (RJ-45) [100 m/328 ft.] to 100Base-EX 1310nm single mode (LC) [40 km/24.9 miles]. Managed or unmanaged operation	https://www.perle.com/products/10-100-managed-media-converter-module.shtml	Media Converter Module: CM-110
05052570	CM-110-S2LC80 - Managed 10/100Base-TX Media and Rate Converter Module: 10/100Base-TX (RJ-45) [100 m/328 ft.] to 100Base-ZX 1550nm single mode (LC) [80 km/49.7 miles]. Managed or unmanaged operation	https://www.perle.com/products/10-100-managed-media-converter-module.shtml	Media Converter Module: CM-110
05052580	CM-110-S2LC120 - Managed 10/100Base-TX Media and Rate Converter Module: 10/100Base-TX (RJ-45) [100 m/328 ft.] to 100Base-ZX 1550nm single mode (LC) [120 km/74.6 miles]. Managed or unmanaged operation	https://www.perle.com/products/10-100-managed-media-converter-module.shtml	Media Converter Module: CM-110
05052590	CM-1110-S1SC120D - Managed 10/100/1000Base-T Media and Rate Converter Module: 10/100/1000BASE-T (RJ-45) [100 m/328 ft.] to 1000BASE-BX 1590nm TX / 1510nm RX single strand fiber, single mode (SC) [120 km/75 miles]. Managed or unmanaged operation	https://www.perle.com/products/10-100-1000-managed-media-converter-module.shtml	Media Converter Module: CM-1110
05052600	CM-1110-M2SC05 - Managed 10/100/1000Base-T Media and Rate Converter Module: 10/100/1000BASE-T (RJ-45) [100 m/328 ft.] to 1000BASE-SX 850nm multimode (SC) [550 m/1804 ft.]. Managed or unmanaged operation	https://www.perle.com/products/10-100-1000-managed-media-converter-module.shtml	Media Converter Module: CM-1110
05052610	CM-1110-M2LC05 - Managed 10/100/1000Base-T Media and Rate Converter Module: 10/100/1000BASE-T (RJ-45) [100 m/328 ft.] to 1000BASE-SX 850nm multimode (LC) [550 m/1804 ft.]. Managed or unmanaged operation	https://www.perle.com/products/10-100-1000-managed-media-converter-module.shtml	Media Converter Module: CM-1110

Part #	Description	Product Datasheet	Product Group
05052620	CM-1110-S2LC10 - Managed 10/100/1000Base-T Media and Rate Converter Module: 10/100/1000BASE-T (RJ-45) [100 m/328 ft.] to 1000BASE-LX/LH 1310 nm single mode (LC) [10 km/6.2 miles] or multimode (LC) [550 m/1804 ft.] using a mode conditioning patch cord. Managed or unmanaged operation	https://www.perle.com/products/10-100-1000-managed-media-converter-module.shtml	Media Converter Module: CM-1110
05052630	CM-1110-S2SC10 - Managed 10/100/1000Base-T Media and Rate Converter Module: 10/100/1000BASE-T (RJ-45) [100 m/328 ft.] to 1000BASE-LX/LH 1310 nm single mode (SC) [10 km/6.2 miles] or multimode (SC) [550 m/1804 ft.] using a mode conditioning adapter. Managed or unmanaged operation	https://www.perle.com/products/10-100-1000-managed-media-converter-module.shtml	Media Converter Module: CM-1110
05052640	CM-1110-S2LC40 - Managed 10/100/1000Base-T Media and Rate Converter Module: 10/100/1000BASE-T (RJ-45) [100 m/328 ft.] to 1000BASE-EX 1310 nm single mode (LC) [40 km/24.9 miles]. Managed or unmanaged operation	https://www.perle.com/products/10-100-1000-managed-media-converter-module.shtml	Media Converter Module: CM-1110
05052650	CM-1110-S2SC70 - Managed 10/100/1000Base-T Media and Rate Converter Module: 10/100/1000BASE-T (RJ-45) [100 m/328 ft.] to 1000BASE-ZX 1550 nm single mode (SC) [70 km/43.5 miles]. Managed or unmanaged operation	https://www.perle.com/products/10-100-1000-managed-media-converter-module.shtml	Media Converter Module: CM-1110
05052660	CM-1110-S2LC70 - Managed 10/100/1000Base-T Media and Rate Converter Module: 10/100/1000BASE-T (RJ-45) [100 m/328 ft.] to 1000BASE-ZX 1550 nm single mode (LC) [70 km/43.5 miles]. Managed or unmanaged operation	https://www.perle.com/products/10-100-1000-managed-media-converter-module.shtml	Media Converter Module: CM-1110
05052670	CM-1110-S1SC10U - Managed 10/100/1000Base-T Media and Rate Converter Module: 10/100/1000BASE-T (RJ-45) [100 m/328 ft.] to 1000BASE-BX 1310nm TX / 1490nm RX single strand fiber, single mode (SC) [10 km/6.2 miles]. Managed or unmanaged operation	https://www.perle.com/products/10-100-1000-managed-media-converter-module.shtml	Media Converter Module: CM-1110
05052680	CM-1110-S1SC10D - Managed 10/100/1000Base-T Media and Rate Converter Module: 10/100/1000BASE-T (RJ-45) [100 m/328 ft.] to 1000BASE-BX 1490nm TX / 1310nm RX single strand fiber, single mode (SC) [10 km/6.2 miles]. Managed or unmanaged operation	https://www.perle.com/products/10-100-1000-managed-media-converter-module.shtml	Media Converter Module: CM-1110
05052690	CM-1110-S2SC40 - Managed 10/100/1000Base-T Media and Rate Converter Module: 10/100/1000BASE-T (RJ-45) [100 m/328 ft.] to 1000BASE-EX 1310 nm single mode (SC) [40 km/24.9 miles]. Managed or unmanaged operation	https://www.perle.com/products/10-100-1000-managed-media-converter-module.shtml	Media Converter Module: CM-1110

Part #	Description	Product Datasheet	Product Group
05052710	CM-1110-M2ST05 - Managed 10/100/1000Base-T Media and Rate Converter Module: 10/100/1000BASE-T (RJ-45) [100 m/328 ft.] to 1000BASE-SX 850nm multimode (ST) [550 m/1804 ft.]. Managed or unmanaged operation	https://www.perle.com/products/10-100-1000-managed-media-converter-module.shtml	Media Converter Module: CM-1110
05052720	CM-1110-S2ST10 - Managed 10/100/1000Base-T Media and Rate Converter Module: 10/100/1000BASE-T (RJ-45) [100 m/328 ft.] to 1000BASE-LX/LH 1310 nm single mode (ST) [10 km/6.2 miles. Managed or unmanaged operation	https://www.perle.com/products/10-100-1000-managed-media-converter-module.shtml	Media Converter Module: CM-1110
05052730	CM-1110-S2ST40 - Managed 10/100/1000Base-T Media and Rate Converter Module: 10/100/1000BASE-T (RJ-45) [100 m/328 ft.] to 1000BASE-EX 1310 nm single mode (ST) [40 km/24.9 miles]. Managed or unmanaged operation	https://www.perle.com/products/10-100-1000-managed-media-converter-module.shtml	Media Converter Module: CM-1110
05052740	CM-1110-S2ST70 - Managed 10/100/1000Base-T Media and Rate Converter Module: 10/100/1000BASE-T (RJ-45) [100 m/328 ft.] to 1000BASE-ZX 1550 nm single mode (ST) [70 km/43.5 miles]. Managed or unmanaged operation	https://www.perle.com/products/10-100-1000-managed-media-converter-module.shtml	Media Converter Module: CM-1110
05052750	CM-1110-S2ST120 - Managed 10/100/1000Base-T Media and Rate Converter Module: 10/100/1000BASE-T (RJ-45) [100 m/328 ft.] to 1000BASE-ZX 1550 nm single mode (ST) [120 km/74.6 miles]. Managed or unmanaged operation	https://www.perle.com/products/10-100-1000-managed-media-converter-module.shtml	Media Converter Module: CM-1110
05052760	CM-1110-S2SC120 - Managed 10/100/1000Base-T Media and Rate Converter Module: 10/100/1000BASE-T (RJ-45) [100 m/328 ft.] to 1000BASE-ZX 1550 nm single mode (SC) [120 km/74.6 miles]. Managed or unmanaged operation	https://www.perle.com/products/10-100-1000-managed-media-converter-module.shtml	Media Converter Module: CM-1110
05052770	CM-1110-S2LC120 - Managed 10/100/1000Base-T Media and Rate Converter Module: 10/100/1000BASE-T (RJ-45) [100 m/328 ft.] to 1000BASE-ZX 1550 nm single mode (LC) [120 km/74.6 miles]. Managed or unmanaged operation	https://www.perle.com/products/10-100-1000-managed-media-converter-module.shtml	Media Converter Module: CM-1110
05052780	CM-1000-S2ST160 - Managed Gigabit Media Converter Module: 1000BASE-T (RJ-45) [100 m/328 ft.] to 1000BASE-ZX 1550 nm single mode (ST) [160 km/100 miles]. Managed or unmanaged operation	https://www.perle.com/products/gigabit-managed-media-converter-module.shtml	Media Converter Module: CM-1000
05052790	CM-1000-S2SC160 - Managed Gigabit Media Converter Module: 1000BASE-T (RJ-45) [100 m/328 ft.] to 1000BASE-ZX 1550 nm single mode (SC) [160 km/100 miles]. Managed or unmanaged operation	https://www.perle.com/products/gigabit-managed-media-converter-module.shtml	Media Converter Module: CM-1000

Part #	Description	Product Datasheet	Product Group
05052800	CM-1000-S2LC160 - Managed Gigabit Media Converter Module: 1000BASE-T (RJ-45) [100 m/328 ft.] to 1000BASE-ZX 1550 nm single mode (LC) [160 km/100 miles]. Managed or unmanaged operation	https://www.perle.com/products/gigabit-managed-media-converter-module.shtml	Media Converter Module: CM-1000
05052810	CM-1000-S1SC20U - Managed Gigabit Media Converter Module: 1000BASE-T (RJ-45) [100 m/328 ft.] to 1000BASE-BX 1310nm TX / 1490nm RX single strand fiber, single mode (SC) [20 km/12.4 miles]. Managed or unmanaged operation	https://www.perle.com/products/gigabit-managed-media-converter-module.shtml	Media Converter Module: CM-1000
05052820	CM-1000-S1SC20D - Managed Gigabit Media Converter Module: 1000BASE-T (RJ-45) [100 m/328 ft.] to 1000BASE-BX 1490nm TX / 1310nm RX single strand fiber, single mode (SC) [20 km/12.4 miles]. Managed or unmanaged operation	https://www.perle.com/products/gigabit-managed-media-converter-module.shtml	Media Converter Module: CM-1000
05052830	CM-1000-S1SC40U - Managed Gigabit Media Converter Module: 1000BASE-T (RJ-45) [100 m/328 ft.] to 1000BASE-BX 1310nm TX / 1490nm RX single strand fiber, single mode (SC) [40 km/25 miles]. Managed or unmanaged operation	https://www.perle.com/products/gigabit-managed-media-converter-module.shtml	Media Converter Module: CM-1000
05052840	CM-1000-S1SC40D - Managed Gigabit Media Converter Module: 1000BASE-T (RJ-45) [100 m/328 ft.] to 1000BASE-BX 1490nm TX / 1310nm RX single strand fiber, single mode (SC) [40 km/25 miles]. Managed or unmanaged operation	https://www.perle.com/products/gigabit-managed-media-converter-module.shtml	Media Converter Module: CM-1000
05052850	CM-1000-S1SC80U - Managed Gigabit Media Converter Module: 1000BASE-T (RJ-45) [100 m/328 ft.] to 1000BASE-BX 1510nm TX / 1590nm RX single strand fiber, single mode (SC) [80 km/50 miles]. Managed or unmanaged operation	https://www.perle.com/products/gigabit-managed-media-converter-module.shtml	Media Converter Module: CM-1000
05052860	CM-1000-S1SC80D - Managed Gigabit Media Converter Module: 1000BASE-T (RJ-45) [100 m/328 ft.] to 1000BASE-BX 1590nm TX / 1510nm RX single strand fiber, single mode (SC) [80 km/50 miles]. Managed or unmanaged operation	https://www.perle.com/products/gigabit-managed-media-converter-module.shtml	Media Converter Module: CM-1000
05052870	CM-1000-S1SC120U - Managed Gigabit Media Converter Module: 1000BASE-T (RJ-45) [100 m/328 ft.] to 1000BASE-BX 1510nm TX / 1590nm RX single strand fiber, single mode (SC) [120 km/75 miles]. Managed or unmanaged operation	https://www.perle.com/products/gigabit-managed-media-converter-module.shtml	Media Converter Module: CM-1000
05052880	CM-1000-S1SC120D - Managed Gigabit Media Converter Module: 1000BASE-T (RJ-45) [100 m/328 ft.] to 1000BASE-BX 1590nm TX / 1510nm RX single strand fiber, single mode (SC) [120 km/75 miles]. Managed or unmanaged operation	https://www.perle.com/products/gigabit-managed-media-converter-module.shtml	Media Converter Module: CM-1000

Part #	Description	Product Datasheet	Product Group
05052890	CM-1110-S2ST160 - Managed 10/100/1000Base-T Media and Rate Converter Module: 10/100/1000BASE-T (RJ-45) [100 m/328 ft.] to 1000BASE-ZX 1550 nm single mode (ST) [160 km/100 miles]. Managed or unmanaged operation	https://www.perle.com/products/10-100-1000-managed-media-converter-module.shtml	Media Converter Module: CM-1110
05052910	CM-1110-S2SC160 - Managed 10/100/1000Base-T Media and Rate Converter Module: 10/100/1000BASE-T (RJ-45) [100 m/328 ft.] to 1000BASE-ZX 1550 nm single mode (SC) [160 km/100 miles]. Managed or unmanaged operation	https://www.perle.com/products/10-100-1000-managed-media-converter-module.shtml	Media Converter Module: CM-1110
05052920	CM-1110-S2LC160 - Managed 10/100/1000Base-T Media and Rate Converter Module: 10/100/1000BASE-T (RJ-45) [100 m/328 ft.] to 1000BASE-ZX 1550 nm single mode (LC) [160 km/100 miles]. Managed or unmanaged operation	https://www.perle.com/products/10-100-1000-managed-media-converter-module.shtml	Media Converter Module: CM-1110
05052930	CM-1110-S1SC20U - Managed 10/100/1000Base-T Media and Rate Converter Module: 10/100/1000BASE-T (RJ-45) [100 m/328 ft.] to 1000BASE-BX 1310nm TX / 1490nm RX single strand fiber, single mode (SC) [20 km/12.4 miles]. Managed or unmanaged operation	https://www.perle.com/products/10-100-1000-managed-media-converter-module.shtml	Media Converter Module: CM-1110
05052940	CM-1110-S1SC20D - Managed 10/100/1000Base-T Media and Rate Converter Module: 10/100/1000BASE-T (RJ-45) [100 m/328 ft.] to 1000BASE-BX 1490nm TX / 1310nm RX single strand fiber, single mode (SC) [20 km/12.4 miles]. Managed or unmanaged operation	https://www.perle.com/products/10-100-1000-managed-media-converter-module.shtml	Media Converter Module: CM-1110
05052950	CM-1110-S1SC40U - Managed 10/100/1000Base-T Media and Rate Converter Module: 10/100/1000BASE-T (RJ-45) [100 m/328 ft.] to 1000BASE-BX 1310nm TX / 1490nm RX single strand fiber, single mode (SC) [40 km/25 miles]. Managed or unmanaged operation	https://www.perle.com/products/10-100-1000-managed-media-converter-module.shtml	Media Converter Module: CM-1110
05052960	CM-1110-S1SC40D - Managed 10/100/1000Base-T Media and Rate Converter Module: 10/100/1000BASE-T (RJ-45) [100 m/328 ft.] to 1000BASE-BX 1490nm TX / 1310nm RX single strand fiber, single mode (SC) [40 km/25 miles]. Managed or unmanaged operation	https://www.perle.com/products/10-100-1000-managed-media-converter-module.shtml	Media Converter Module: CM-1110
05052970	CM-1110-S1SC80U - Managed 10/100/1000Base-T Media and Rate Converter Module: 10/100/1000BASE-T (RJ-45) [100 m/328 ft.] to 1000BASE-BX 1510nm TX / 1590nm RX single strand fiber, single mode (SC) [80 km/50 miles]. Managed or unmanaged operation	https://www.perle.com/products/10-100-1000-managed-media-converter-module.shtml	Media Converter Module: CM-1110

Part #	Description	Product Datasheet	Product Group
05052980	CM-1110-S1SC80D - Managed 10/100/1000Base-T Media and Rate Converter Module: 10/100/1000BASE-T (RJ-45) [100 m/328 ft.] to 1000BASE-BX 1590nm TX / 1510nm RX single strand fiber, single mode (SC) [80 km/50 miles]. Managed or unmanaged operation	https://www.perle.com/products/10-100-1000-managed-media-converter-module.shtml	Media Converter Module: CM-1110
05052990	CM-1110-S1SC120U - Managed 10/100/1000Base-T Media and Rate Converter Module: 10/100/1000BASE-T (RJ-45) [100 m/328 ft.] to 1000BASE-BX 1510nm TX / 1590nm RX single strand fiber, single mode (SC) [120 km/75 miles]. Managed or unmanaged operation	https://www.perle.com/products/10-100-1000-managed-media-converter-module.shtml	Media Converter Module: CM-1110
05058970	PSFP-100D-M2LC05 Fast Ethernet SFP Optical Transceiver: 100BASE-SX 850nm multimode (LC) [550m / 1804 ft]. DOM (DMI) - Digital Optical Monitoring.	https://www.perle.com/products/sfp-optical-transceiver.shtml	Optical Transceivers: SFP
05058980	PSFP-100D-S1LC40U Fast Ethernet SFP Optical Transceiver: 100BASE-BX 1310nm TX / 1550nm RX single fiber single mode (LC) [40 km/24.9 miles]. DOM (DMI) - Digital Optical Monitoring. (GLC-FE-100BX-U-40km).	https://www.perle.com/products/sfp-optical-transceiver.shtml	Optical Transceivers: SFP
05058990	PSFP-100D-S1LC40D Fast Ethernet SFP Optical Transceiver: 100BASE-BX 1550nm TX / 1310nm RX single fiber single mode (LC) [40 km/24.9 miles]. DOM (DMI) - Digital Optical Monitoring. (GLC-FE-100BX-D-40km).	https://www.perle.com/products/sfp-optical-transceiver.shtml	Optical Transceivers: SFP
05059000	PSFP-100D-S1LC80U Fast Ethernet SFP Optical Transceiver: 100BASE-BX 1490nm TX / 1550nm RX single fiber single mode (LC) [80 km/49.8 miles]. DOM (DMI) - Digital Optical Monitoring. (GLC-FE-100BX-U-80km).	https://www.perle.com/products/sfp-optical-transceiver.shtml	Optical Transceivers: SFP
05059010	PSFP-100D-S1LC80D Fast Ethernet SFP Optical Transceiver: 100BASE-BX 1550nm TX / 1490nm RX single fiber single mode (LC) [80 km/49.8 miles]. DOM (DMI) - Digital Optical Monitoring. (GLC-FE-100BX-D-80km).	https://www.perle.com/products/sfp-optical-transceiver.shtml	Optical Transceivers: SFP
05059020	PSFP-100D-S2LC10 Gigabit SFP Optical Transceiver: 1000BASE-LH 1310nm single mode (LC) [10 km/6.2 miles]. DOM (DMI) - Digital Optical Monitoring. (SFP-GE-L).	https://www.perle.com/products/sfp-optical-transceiver.shtml	Optical Transceivers: SFP
05059030	PSFP-100D-S2LC80 Gigabit SFP Optical Transceiver: 1000BASE-ZX 1550nm single mode (LC) [80 km/49.8 miles]. DOM (DMI) - Digital Optical Monitoring. (SFP-GE-Z).	https://www.perle.com/products/sfp-optical-transceiver.shtml	Optical Transceivers: SFP
05059040	PSFP-100D-S2LC80-XT Gigabit SFP Optical Transceiver: 1000BASE-ZX 1550nm single mode (LC) [80 km/49.8 miles]. -40 to 85C industrial extended operating temperature. DOM (DMI) - Digital Optical Monitoring. (GLC-ZX-SM-RGD).	https://www.perle.com/products/sfp-optical-transceiver.shtml	Optical Transceivers: SFP

Part #	Description	Product Datasheet	Product Group
05059050	PSFP-1000D-S1LC40U Gigabit SFP Optical Transceiver: 1000BASE-BX 1310nm TX / 1490nm RX single strand fiber, single mode (LC) [40 km/24.9 miles]. DOM (DMI) - Digital Optical Monitoring (GLC-BX-U-40km).	https://www.perle.com/products/sfp-optical-transceiver.shtml	Optical Transceivers: SFP
05059060	PSFP-1000D-S1LC40D Gigabit SFP Optical Transceiver: 1000BASE-BX 1490nm TX / 1310nm RX single strand fiber, single mode (LC) [40 km/24.9 miles]. DOM (DMI) - Digital Optical Monitoring (GLC-BX-D-40km).	https://www.perle.com/products/sfp-optical-transceiver.shtml	Optical Transceivers: SFP
05059070	PSFP-1000D-S1LC60U Gigabit SFP Optical Transceiver: 1000BASE-BX 1490nm TX / 1550nm RX single strand fiber, single mode (LC) [60 km/37.3 miles]. DOM (DMI) - Digital Optical Monitoring. (GLC-BX-U-60km).	https://www.perle.com/products/sfp-optical-transceiver.shtml	Optical Transceivers: SFP
05059080	PSFP-1000D-S1LC60D Gigabit SFP Optical Transceiver: 1000BASE-BX 1550nm TX / 1490nm RX single strand fiber, single mode (LC) [60 km/37.3 miles]. DOM (DMI) - Digital Optical Monitoring. (GLC-BX-D-60km).	https://www.perle.com/products/sfp-optical-transceiver.shtml	Optical Transceivers: SFP
05059090	PSFP-1000D-S1LC80U Gigabit SFP Optical Transceiver: 1000BASE-BX 1490nm TX / 1550nm RX single strand fiber, single mode (LC) [80 km/49.8 miles]. DOM (DMI) - Digital Optical Monitoring (GLC-BX-U-80km).	https://www.perle.com/products/sfp-optical-transceiver.shtml	Optical Transceivers: SFP
05059100	PSFP-1000D-S1LC80D Gigabit SFP Optical Transceiver: 1000BASE-BX 1550nm TX / 1490nm RX single strand fiber, single mode (LC) [80 km/49.8 miles]. DOM (DMI) - Digital Optical Monitoring (GLC-BX-D-80km).	https://www.perle.com/products/sfp-optical-transceiver.shtml	Optical Transceivers: SFP
05059210	PSFP-CWDM-SFP-1470 CWDM SFP Optical Transceiver: Gigabit Ethernet and Fibre Channel - 1470nm single mode (LC) [80 km/49.8 miles]. DOM (DMI) - Digital Optical Monitoring. (CWDM-SFP-1470)	https://www.perle.com/products/sfp-optical-transceiver.shtml	Optical Transceivers: SFP
05059220	PSFP-CWDM-SFP-1490 CWDM SFP Optical Transceiver: Gigabit Ethernet and Fibre Channel - 1490nm single mode (LC) [80 km/49.8 miles]. DOM (DMI) - Digital Optical Monitoring. (CWDM-SFP-1490)	https://www.perle.com/products/sfp-optical-transceiver.shtml	Optical Transceivers: SFP
05059230	PSFP-CWDM-SFP-1510 CWDM SFP Optical Transceiver: Gigabit Ethernet and Fibre Channel - 1510nm single mode (LC) [80 km/49.8 miles]. DOM (DMI) - Digital Optical Monitoring. (CWDM-SFP-1510)	https://www.perle.com/products/sfp-optical-transceiver.shtml	Optical Transceivers: SFP
05059240	PSFP-CWDM-SFP-1530 CWDM SFP Optical Transceiver: Gigabit Ethernet and Fibre Channel - 1530nm single mode (LC) [80 km/49.8 miles]. DOM (DMI) - Digital Optical Monitoring. (CWDM-SFP-1530)	https://www.perle.com/products/sfp-optical-transceiver.shtml	Optical Transceivers: SFP
05059250	PSFP-CWDM-SFP-1550 CWDM SFP Optical Transceiver: Gigabit Ethernet and Fibre Channel - 1550nm single mode (LC) [80 km/49.8 miles]. DOM (DMI) - Digital Optical Monitoring. (CWDM-SFP-1550)	https://www.perle.com/products/sfp-optical-transceiver.shtml	Optical Transceivers: SFP

Part #	Description	Product Datasheet	Product Group
05059260	PSFP-CWDM-SFP-1570 CWDM SFP Optical Transceiver: Gigabit Ethernet and Fibre Channel - 1570nm single mode (LC) [80 km/49.8 miles]. DOM (DMI) - Digital Optical Monitoring. (CWDM-SFP-1570)	https://www.perle.com/products/sfp-optical-transceiver.shtml	Optical Transceivers: SFP
05059270	PSFP-CWDM-SFP-1590 CWDM SFP Optical Transceiver: Gigabit Ethernet and Fibre Channel - 1590nm single mode (LC) [80 km/49.8 miles]. DOM (DMI) - Digital Optical Monitoring. (CWDM-SFP-1590)	https://www.perle.com/products/sfp-optical-transceiver.shtml	Optical Transceivers: SFP
05059280	PSFP-CWDM-SFP-1610 CWDM SFP Optical Transceiver: Gigabit Ethernet and Fibre Channel - 1610nm single mode (LC) [80 km/49.8 miles]. DOM (DMI) - Digital Optical Monitoring. (CWDM-SFP-1610)	https://www.perle.com/products/sfp-optical-transceiver.shtml	Optical Transceivers: SFP
05059290	PSFP-100D-M2LC2-XT Fast Ethernet SFP Optical Transceiver: 100BASE-FX 1310 nm multimode (LC) [2km / 1.2 miles].-40 to 85C industrial extended operating temperature. DOM (DMI) - Digital Optical Monitoring. (GLC-FE-100FX-RGD).	https://www.perle.com/products/sfp-optical-transceiver.shtml	Optical Transceivers: SFP
05059300	PSFP-100D-S2LC10 Fast Ethernet SFP Optical Transceiver: 100BASE-LX-10 1310 nm single mode (LC) [10km / 6.2 miles]. DOM (DMI) - Digital Optical Monitoring. (GLC-FE-100LX).	https://www.perle.com/products/sfp-optical-transceiver.shtml	Optical Transceivers: SFP
05059310	PSFP-100D-S2LC10-XT Fast Ethernet SFP Optical Transceiver: 100BASE-LX-10 1310 nm single mode (LC) [10km / 6.2 miles].-40 to 85C industrial extended operating temperature. DOM (DMI) - Digital Optical Monitoring. (GLC-FE-100LX-RGD).	https://www.perle.com/products/sfp-optical-transceiver.shtml	Optical Transceivers: SFP
05059320	PSFP-100D-S2LC40 Fast Ethernet SFP Optical Transceiver: 100BASE-EX 1310 nm single mode (LC) [40km / 24.9 miles] DOM (DMI) - Digital Optical Monitoring. (GLC-FE-100EX).	https://www.perle.com/products/sfp-optical-transceiver.shtml	Optical Transceivers: SFP
05059330	PSFP-100D-S2LC80 Fast Ethernet SFP Optical Transceiver: 100BASE-ZX 1550 nm single mode (LC) [80km / 49.7 miles]. DOM (DMI) - Digital Optical Monitoring. (GLC-FE-100ZX).	https://www.perle.com/products/sfp-optical-transceiver.shtml	Optical Transceivers: SFP
05059340	PSFP-100D-S1LC10U Fast Ethernet SFP Optical Transceiver: 100BASE-BX 1310nm TX / 1550nm RX single fiber single mode (LC) [10 km/6.2 miles]. DOM (DMI) - Digital Optical Monitoring. (GLC-FE-100BX-U).	https://www.perle.com/products/sfp-optical-transceiver.shtml	Optical Transceivers: SFP
05059350	PSFP-100D-S1LC10U-XT Fast Ethernet SFP Optical Transceiver: 100BASE-BX 1310nm TX / 1550nm RX single fiber single mode (LC) [10 km/6.2 miles]. -40 to 85C industrial extended operating temperature. DOM (DMI) - Digital Optical Monitoring. (GLC-FE-100BX-URGD).	https://www.perle.com/products/sfp-optical-transceiver.shtml	Optical Transceivers: SFP

Part #	Description	Product Datasheet	Product Group
05059360	PSFP-100D-S1LC10D Fast Ethernet SFP Optical Transceiver: 100BASE-BX 1550nm TX / 1310nm RX single fiber single mode (LC) [10 km/6.2 miles]. DOM (DMI) - Digital Optical Monitoring. (GLC-FE-100BX-D).	https://www.perle.com/products/sfp-optical-transceiver.shtml	Optical Transceivers: SFP
05059370	PSFP-100D-S1LC10D-XT Fast Ethernet SFP Optical Transceiver: 100BASE-BX 1550nm TX / 1310nm RX single fiber single mode (LC) [10 km/6.2 miles]. -40 to 85C industrial extended operating temperature. DOM (DMI) - Digital Optical Monitoring. (GLC-FE-100BX-DRGD).	https://www.perle.com/products/sfp-optical-transceiver.shtml	Optical Transceivers: SFP
05059380	PSFP-100D-S1LC20U Fast Ethernet SFP Optical Transceiver: 100BASE-BX 1310nm TX / 1550nm RX single fiber single mode (LC) [20 km/12.4 miles]. DOM (DMI) - Digital Optical Monitoring. (GLC-FE-100BX-U-20km).	https://www.perle.com/products/sfp-optical-transceiver.shtml	Optical Transceivers: SFP
05059390	PSFP-100D-S1LC20D Fast Ethernet SFP Optical Transceiver: 100BASE-BX 1550nm TX / 1310nm RX single fiber single mode (LC) [20 km/12.4 miles]. DOM (DMI) - Digital Optical Monitoring. (GLC-FE-100BX-D-20km).	https://www.perle.com/products/sfp-optical-transceiver.shtml	Optical Transceivers: SFP
05059400	PSFP-1000D-M2LC05-XT Gigabit SFP Optical Transceiver: 1000BASE-SX 850nm multimode duplex (LC) [550 m/1804 ft.]. -40 to 85C industrial extended operating temperature. DOM (DMI) - Digital Optical Monitoring.	https://www.perle.com/products/sfp-optical-transceiver.shtml	Optical Transceivers: SFP
05059410	PSFP-1000D-M2LC2 Gigabit SFP Optical Transceiver: 1000BASE-BX 1310nm multimode duplex (LC) [2km/1.2 miles] DOM (DMI) - Digital Optical Monitoring.	https://www.perle.com/products/sfp-optical-transceiver.shtml	Optical Transceivers: SFP
05059420	PSFP-1000D-M2LC2-XT Gigabit SFP Optical Transceiver: 1000BASE-LX 1310nm multimode duplex (LC) [2km/1.2 miles]. -40 to 85C industrial extended operating temperature. DOM (DMI) - Digital Optical Monitoring.	https://www.perle.com/products/sfp-optical-transceiver.shtml	Optical Transceivers: SFP
05059430	PSFP-1000D-S2LC10-XT Gigabit SFP Optical Transceiver: 1000Base-LX/LH 1310nm single mode (LC) [10 km/6.2 miles]. -40 to 85C industrial extended operating temperature. DOM (DMI) - Digital Optical Monitoring.	https://www.perle.com/products/sfp-optical-transceiver.shtml	Optical Transceivers: SFP
05059440	PSFP-1000D-S1LC10U-XT Gigabit SFP Optical Transceiver: 1000BASE-BX 1310nm TX / 1490nm RX single strand fiber, single mode (LC) [10 km/6.2 miles]. -40 to 85C industrial extended operating temperature. DOM (DMI) - Digital Optical Monitoring.	https://www.perle.com/products/sfp-optical-transceiver.shtml	Optical Transceivers: SFP
05059450	PSFP-1000D-S1LC10D-XT Gigabit SFP Optical Transceiver: 1000BASE-BX 1490nm TX / 1310nm RX single strand fiber, single mode (LC) [10 km/6.2 miles]. -40 to 85C industrial extended operating temperature. DOM (DMI) - Digital Optical Monitoring.	https://www.perle.com/products/sfp-optical-transceiver.shtml	Optical Transceivers: SFP

Part #	Description	Product Datasheet	Product Group
05059460	PSFP-1000D-S2LC20 Gigabit SFP Optical Transceiver: 1000Base-EX 1310nm single mode (LC) [20 km/12.4 miles]. DOM (DMI) - Digital Optical Monitoring.	https://www.perle.com/products/sfp-optical-transceiver.shtml	Optical Transceivers: SFP
05059470	PSFP-1000D-S2LC20-XT Gigabit SFP Optical Transceiver: 1000Base-EX 1310nm single mode (LC) [20 km/12.4 miles]. -40 to 85C industrial extended operating temperature. DOM (DMI) - Digital Optical Monitoring.	https://www.perle.com/products/sfp-optical-transceiver.shtml	Optical Transceivers: SFP
05059480	PSFP-1000D-S2LC40 Gigabit SFP Optical Transceiver: 1000Base-EX 1310nm single mode (LC) [40 km/24.9 miles]. DOM (DMI) - Digital Optical Monitoring.	https://www.perle.com/products/sfp-optical-transceiver.shtml	Optical Transceivers: SFP
05059490	PSFP-1000D-S2LC40-XT Gigabit SFP Optical Transceiver: 1000Base-EX 1310nm single mode (LC) [40 km/24.9 miles]. -40 to 85C industrial extended operating temperature. DOM (DMI) - Digital Optical Monitoring.	https://www.perle.com/products/sfp-optical-transceiver.shtml	Optical Transceivers: SFP
05059520	PSFP-2GD-M2LC03 Gigabit SFP Optical Transceiver: Multimode Duplex LC, 850nm, [300 meters/984ft], 2.488 Gbps for Gigabit Ethernet, 1x/2xFC, OC48 and SDH STM-16 applications. DOM / DMI capability. Cisco compatible.	https://www.perle.com/products/sfp-optical-transceiver.shtml	Optical Transceivers: SFP
05059530	PSFP-2GD-S2LC20 - Small Form Pluggable - SM Duplex LC, 1310nm, [20km/12.4 miles], 2.488 Gbps for Gigabit Ethernet, 1x/2xFC, OC48 and SDH STM-16 applications. DOM / DMI capability. Cisco Compatible.	https://www.perle.com/products/sfp-optical-transceiver.shtml	Optical Transceivers: SFP
05059560	PSFP-4GD-M2LC054.35 Gigabit Optical Transceiver: MM Duplex LC, 850nm, [500 meters/1640 ft], 4.25 Gbps for Gigabit Ethernet and 1x/2x/4xFC applications. DOM / DMI capability. Cisco compatible.	https://www.perle.com/products/sfp-optical-transceiver.shtml	Optical Transceivers: SFP
05059570	PSFP-4GD-S2LC10 4.25 Gigabit SFP Optical Transceiver: Single Mode Duplex LC, 1310nm, [10 km/ 6.2 miles], 4.25 Gbps for Gigabit Ethernet and 1x/2x/4xFC applications. DOM / DMI capability. Cisco Compatible.	https://www.perle.com/products/sfp-optical-transceiver.shtml	Optical Transceivers: SFP
05059600	PerleVIEW Device Management System Software for Single Windows Server license. This activation code is required for continued use of the PerleVIEW centralized management package after the initial 30-day evaluation period expires. This license also includes a 1 year of Technical Support. The PerleVIEW software is available for download at www.perle.com	https://www.perle.com/products/perleview.shtml	PerleVIEW
05059620	PXFP-10GD-M2LC008 10 Gigabit XFP Optical Transceiver: 10GBASE-SR 850nm multimode (LC) [82m / 269 ft with OM2 MMF, 33m/] with DOM (DMI) - Digital Optical Monitoring.	https://www.perle.com/products/10g-optical-transceiver.shtml	Optical Transceivers: XFP

Part #	Description	Product Datasheet	Product Group
05059640	PXFP-10GD-S2LC10 10 Gigabit XFP Optical Transceiver: 10GBASE-LR 1310nm (LC) [10km / 6.2 miles with SMF] with DOM (DMI) - Digital Optical Monitoring.	https://www.perle.com/products/10g-optical-transceiver.shtml	Optical Transceivers: XFP
05059650	PXFP-10GD-S2LC40 10 Gigabit XFP Optical Transceiver: 10GBASE-ER 1550nm (LC) [40km / 25 miles with SMF] with DOM (DMI) - Digital Optical Monitoring.	https://www.perle.com/products/10g-optical-transceiver.shtml	Optical Transceivers: XFP
05059660	PSFP-10GD-M2LC008 10 Gigabit SFP+ Optical Transceiver: 10GBASE-SR 850nm multimode (LC) [82m / 269 ft with OM2 MMF, 33m/] with DOM (DMI) - Digital Optical Monitoring.	https://www.perle.com/products/10g-optical-transceiver.shtml	Optical Transceivers: SFP
05059670	PSFP-10GD-M2LC02 10 Gigabit SFP+ Optical Transceiver: 10GBASE-LRM 1310nm long reach multimode (LC) [220m / 722 ft. with OM1].	https://www.perle.com/products/10g-optical-transceiver.shtml	Optical Transceivers: SFP
05059680	PSFP-10GD-S2LC10 10 Gigabit SFP+ Optical Transceiver: 10GBASE-LR 1310nm (LC) [10km / 6.2 miles with SMF] with DOM (DMI) - Digital Optical Monitoring.	https://www.perle.com/products/10g-optical-transceiver.shtml	Optical Transceivers: SFP
05059690	PSFP-10GD-S2LC40 10 Gigabit SFP+ Optical Transceiver: 10GBASE-ER 1550nm (LC) [40km / 25 miles with SMF] with DOM (DMI) - Digital Optical Monitoring.	https://www.perle.com/products/10g-optical-transceiver.shtml	Optical Transceivers: SFP
05059700	PSFP-1000-M2LC05 Gigabit SFP Optical Transceiver: 1000BASE-SX 850nm multimode (LC) [550 m/1804 ft.]	https://www.perle.com/products/sfp-optical-transceiver.shtml	Optical Transceivers: SFP
05059710	PSFP-1000-S2LC10 Gigabit SFP Optical Transceiver: 1000BASE-LX 1310nm single mode (LC) [10 km/6.2 miles]	https://www.perle.com/products/sfp-optical-transceiver.shtml	Optical Transceivers: SFP
05059720	PSFP-1000-S1LC10U Gigabit SFP Optical Transceiver: 1310nm TX / 1490nm RX single strand fiber, single mode (LC) [10 km/6.2 miles].	https://www.perle.com/products/sfp-optical-transceiver.shtml	Optical Transceivers: SFP
05059730	PSFP-1000-S1LC10D -Gigabit SFP Optical Transceiver, Single LC - 1000BASE-BX 1490nm TX / 1310nm RX single strand fiber, single mode (LC) [10 km/6.2 miles].	https://www.perle.com/products/sfp-optical-transceiver.shtml	Optical Transceivers: SFP
05059740	PSFP-100-M2LC2 Fast Ethernet SFP Optical Transceiver: 100BASE-FX 1310 nm multimode (LC) [2km / 1.2 miles].	https://www.perle.com/products/sfp-optical-transceiver.shtml	Optical Transceivers: SFP
05059750	PSFP-1000D-M2LC05 Gigabit SFP Optical Transceiver: 1000BASE-SX 850nm multimode (LC) [550 m/1804 ft.] with DOM (DMI) - Digital Optical Monitoring.	https://www.perle.com/products/sfp-optical-transceiver.shtml	Optical Transceivers: SFP
05059780	PSFP-1000D-M1LC2U Gigabit SFP Optical Transceiver: 1310nm TX / 1550nm RX dual-rate 1.25Gbps/1.063Gbps, multi mode (LC) [2 km/2.4 miles]. Gigabit Ethernet, Fibre Channel and SONET applications	https://www.perle.com/products/sfp-optical-transceiver.shtml	Optical Transceivers: SFP

Part #	Description	Product Datasheet	Product Group
05059790	PSFP-1000D-M1LC2D Gigabit SFP Optical Transceiver: 1550nm TX / 1310nm RX dual-rate 1.25Gbps/1.063Gbps, multi mode (LC) [2 km/2.4 miles]. Gigabit Ethernet, Fibre Channel and SONET applications	https://www.perle.com/products/sfp-optical-transceiver.shtml	Optical Transceivers: SFP
05059812	MCR-ACPWR Power Supply: Add a redundant AC power supply to the MCR1900-AC Modular Chassis System - EU Power Cord	https://www.perle.com/products/product_detail.asp?a=4&i=05059812&c=135	Accessories: MCR Chassis
05059820	MCR-DCPWR Power Supply: Redundant 48vDC power supply for MCR1900-DC Modular Chassis System.	https://www.perle.com/products/product_detail.asp?a=4&i=05059820&c=135	Accessories: MCR Chassis
05059830	MCR-FPL Face plate. For empty slots on MCR Modular Chassis Systems.	https://www.perle.com/products/product_detail.asp?a=4&i=05059830&c=135	Accessories: MCR Chassis
05059840	MCR-RMK23 Rack Mount Bracket. For 23 inch racks. This accessory is designed to be used with the MCR1900 Modular Chassis System:	https://www.perle.com/products/product_detail.asp?a=4&i=05059840&c=135	Accessories: MCR Chassis
05059920	MCR1900-DC 19 slot Modular Chassis System: Single DC power, expandable to redundant DC. 15 empty slot cover plates included. Mounting brackets for 19-inch rack included.	https://www.perle.com/products/media-converter-19-slot-chassis.shtml	MCR Chassis
05059930	MCR1900-DDC 19 slot Modular Chassis System: Dual 48vDC power. 15 empty slot cover plates included. Mounting brackets for 19-inch rack included.	https://www.perle.com/products/media-converter-19-slot-chassis.shtml	MCR Chassis
05059942	MCR1900-AC 19 slot Modular Chassis System: Single AC power, expandable to redundant AC. 15 empty slot cover plates included. Mounting brackets for 19-inch rack included.	https://www.perle.com/products/media-converter-19-slot-chassis.shtml	MCR Chassis
05059952	MCR1900-DAC 19 slot Modular Chassis System: Dual AC power. 15 empty slot cover plates included. Mounting brackets for 19-inch racks included.	https://www.perle.com/products/media-converter-19-slot-chassis.shtml	MCR Chassis
05059962	MCR200 2 slot Modular Chassis System: EU power adapter included.	https://www.perle.com/products/media-converter-2-slot-chassis.shtml	MCR Chassis
05059982	PINJ130 - PoE Power Injector: One port 10/100/1000Base-T , 30 watts, IEEE 802.3at compliant. PoE+ and PoE compatible. EU AC Power cord included	https://www.perle.com/products/poe-injectors/pinj30-poe-injector.shtml	PoE Injector
05059999	MCSM wall / rack mount bracket. This accessory is designed to be used with Perle Standalone Media Converters and Ethernet Extenders.	https://www.perle.com/products/product_detail.asp?a=4&i=05059999&c=99	Accessories: Mounting Kits
05060002	S-100MM-M2SC2 - Fast Ethernet Fiber to Fiber Media Converter: 100BASE-FX 1310nm multimode (SC) [2 km/1.2 miles] to 100BASE-FX 1310nm multimode (SC) [2 km/1.2 miles] - EU Power Cord	https://www.perle.com/products/fast-ethernet-fiber-converter.shtml	Media Converter: S100MM
05060012	S-100MM-M2ST2 - Fast Ethernet Fiber to Fiber Media Converter: 100BASE-FX 1310nm multimode (ST) [2 km/1.2 miles] to 100BASE-FX 1310nm multimode (ST) [2 km/1.2 miles] - EU Power Cord	https://www.perle.com/products/fast-ethernet-fiber-converter.shtml	Media Converter: S100MM

Part #	Description	Product Datasheet	Product Group
05060022	S-100MM-M2LC2 - Fast Ethernet Fiber to Fiber Media Converter: 100BASE-FX 1310nm multimode (LC) [2 km/1.2 miles] to 100BASE-FX 1310nm multimode (LC) [2 km/1.2 miles] - EU Power Cord	https://www.perle.com/products/fast-ethernet-fiber-converter.shtml	Media Converter: S100MM
05060032	S-100MM-S2SC20 - Fast Ethernet Fiber to Fiber Media Converter: 100BASE-FX 1310nm multimode (SC) [2 km/1.2 miles] to 100Base-LX 1310nm single mode (SC) [20 km/12.4 miles] - EU Power Cord	https://www.perle.com/products/fast-ethernet-fiber-converter.shtml	Media Converter: S100MM
05060042	S-100MM-S2ST20 - Fast Ethernet Fiber to Fiber Media Converter: 100BASE-FX 1310nm multimode (ST) [2 km/1.2 miles] to 100Base-LX 1310nm single mode (ST) [20 km/12.4 miles] - EU Power Cord	https://www.perle.com/products/fast-ethernet-fiber-converter.shtml	Media Converter: S100MM
05060052	S-100MM-S2LC20 - Fast Ethernet Fiber to Fiber Media Converter: 100BASE-FX 1310nm multimode (LC) [2 km/1.2 miles] to 100Base-LX 1310nm single mode (LC) [20 km/12.4 miles] - EU Power Cord	https://www.perle.com/products/fast-ethernet-fiber-converter.shtml	Media Converter: S100MM
05060062	S-100MM-S2SC40 - Fast Ethernet Fiber to Fiber Media Converter: 100BASE-FX 1310nm multimode (SC) [2 km/1.2 miles] to 100Base-EX 1310nm single mode (SC) [40 km/24.9 miles] - EU Power Cord	https://www.perle.com/products/fast-ethernet-fiber-converter.shtml	Media Converter: S100MM
05060072	S-100MM-S2ST40 - Fast Ethernet Fiber to Fiber Media Converter: 100BASE-FX 1310nm multimode (ST) [2 km/1.2 miles] to 100Base-EX 1310nm single mode (ST) [40 km/24.9 miles] - EU Power Cord	https://www.perle.com/products/fast-ethernet-fiber-converter.shtml	Media Converter: S100MM
05060082	S-100MM-S2LC40 - Fast Ethernet Fiber to Fiber Media Converter: 100BASE-FX 1310nm multimode (LC) [2 km/1.2 miles] to 100Base-EX 1310nm single mode (LC) [40 km/24.9 miles] - EU Power Cord	https://www.perle.com/products/fast-ethernet-fiber-converter.shtml	Media Converter: S100MM
05060092	S-100MM-S2SC80 - Fast Ethernet Fiber to Fiber Media Converter: 100BASE-FX 1310nm multimode (SC) [2 km/1.2 miles] to 100Base-ZX 1550nm single mode (SC) [80 km/49.7 miles] - EU Power Cord	https://www.perle.com/products/fast-ethernet-fiber-converter.shtml	Media Converter: S100MM
05060102	S-100MM-S2ST80 - Fast Ethernet Fiber to Fiber Media Converter: 100BASE-FX 1310nm multimode (ST) [2 km/1.2 miles] to 100Base-ZX 1550nm single mode (ST) [80 km/49.7 miles] - EU Power Cord	https://www.perle.com/products/fast-ethernet-fiber-converter.shtml	Media Converter: S100MM
05060112	S-100MM-S2LC80 - Fast Ethernet Fiber to Fiber Media Converter: 100BASE-FX 1310nm multimode (LC) [2 km/1.2 miles] to 100Base-ZX 1550nm single mode (LC) [80 km/49.7 miles] - EU Power Cord	https://www.perle.com/products/fast-ethernet-fiber-converter.shtml	Media Converter: S100MM
05060122	S-100MM-S2SC120 - Fast Ethernet Fiber to Fiber Media Converter: 100BASE-FX 1310nm multimode (SC) [2 km/1.2 miles] to 100Base-ZX 1550nm single mode (SC) [120 km/74.6 miles] - EU Power Cord	https://www.perle.com/products/fast-ethernet-fiber-converter.shtml	Media Converter: S100MM

Part #	Description	Product Datasheet	Product Group
05060132	S-100MM-S2ST120 - Fast Ethernet Fiber to Fiber Media Converter: 100BASE-FX 1310nm multimode (ST) [2 km/1.2 miles] to 100Base-ZX 1550nm single mode (ST) [120 km/74.6 miles] - EU Power Cord	https://www.perle.com/products/fast-ethernet-fiber-converter.shtml	Media Converter: S100MM
05060142	S-100MM-S2LC120 - Fast Ethernet Fiber to Fiber Media Converter: 100BASE-FX 1310nm multimode (LC) [2 km/1.2 miles] to 100Base-ZX 1550nm single mode (LC) [120 km/74.6 miles] - EU Power Cord	https://www.perle.com/products/fast-ethernet-fiber-converter.shtml	Media Converter: S100MM
05060152	S-100MM-S1SC20U - Fast Ethernet Fiber to Fiber Media Converter: 100BASE-FX 1310nm multimode (SC) [2 km/1.2 miles] to 100Base-BX 1310nm TX / 1550nm RX single strand fiber, single mode (SC) [20 km/12.4 miles] - EU Power Cord	https://www.perle.com/products/fast-ethernet-fiber-converter.shtml	Media Converter: S100MM
05060162	S-100MM-S1SC20D - Fast Ethernet Fiber to Fiber Media Converter: 100BASE-FX 1310nm multimode (SC) [2 km/1.2 miles] to 100Base-BX 1550nm TX / 1310nm RX single strand fiber, single mode (SC) [20 km/12.4 miles] - EU Power Cord	https://www.perle.com/products/fast-ethernet-fiber-converter.shtml	Media Converter: S100MM
05060172	S-100MM-S1SC40U - Fast Ethernet Fiber to Fiber Media Converter: 100BASE-FX 1310nm multimode (SC) [2 km/1.2 miles] to 100Base-BX 1310nm TX / 1550nm RX single strand fiber, single mode (SC) [40 km/24.9 miles] - EU Power Cord	https://www.perle.com/products/fast-ethernet-fiber-converter.shtml	Media Converter: S100MM
05060182	S-100MM-S1SC40D - Fast Ethernet Fiber to Fiber Media Converter: 100BASE-FX 1310nm multimode (SC) [2 km/1.2 miles] to 100Base-BX 1550nm TX / 1310nm RX single strand fiber, single mode (SC) [40 km/24.9 miles] - EU Power Cord	https://www.perle.com/products/fast-ethernet-fiber-converter.shtml	Media Converter: S100MM
05060192	S-1000MM-M2SC05 - Gigabit Fiber to Fiber Media Converter: 1000BASE-SX 850nm multimode (SC) [550 m/1804 ft.] to 1000BASE-SX 850nm multimode (SC) [550 m/1804 ft.] - EU Power Cord	https://www.perle.com/products/gigabit-fiber-converters.shtml	Media Converter: S-1000MM
05060202	S-1000MM-M2LC05 - Gigabit Fiber to Fiber Media Converter: 1000BASE-SX 850nm multimode (LC) [550 m/1804 ft.] to 1000BASE-SX 850nm multimode (LC) [550 m/1804 ft.] - EU Power Cord	https://www.perle.com/products/gigabit-fiber-converters.shtml	Media Converter: S-1000MM
05060212	S-1000MM-M2ST05 - Gigabit Fiber to Fiber Media Converter: 1000BASE-SX 850nm multimode (ST) [550 m/1804 ft.] to 1000BASE-SX 850nm multimode (ST) [550 m/1804 ft.] - EU Power Cord	https://www.perle.com/products/gigabit-fiber-converters.shtml	Media Converter: S-1000MM
05060222	S-1000MM-S2SC10 - Gigabit Fiber to Fiber Media Converter: 1000BASE-SX 850nm multimode (SC) [550 m/1804 ft.] to 1000BASE-LX/LH 1310 nm single mode (SC) [10 km/6.2 miles] - EU Power Cord	https://www.perle.com/products/gigabit-fiber-converters.shtml	Media Converter: S-1000MM

Part #	Description	Product Datasheet	Product Group
05060232	S-1000MM-S2LC10 - Gigabit Fiber to Fiber Media Converter: 1000BASE-SX 850nm multimode (LC) [550 m/1804 ft.] to 1000BASE-LX/LH 1310 nm single mode (LC) [10 km/6.2 miles] - EU Power Cord	https://www.perle.com/products/gigabit-fiber-converters.shtml	Media Converter: S-1000MM
05060242	S-1000MM-S2ST10 - Gigabit Fiber to Fiber Media Converter: 1000BASE-SX 850nm multimode (ST) [550 m/1804 ft.] to 1000BASE-LX/LH 1310 nm single mode (ST) [10 km/6.2 miles] - EU Power Cord	https://www.perle.com/products/gigabit-fiber-converters.shtml	Media Converter: S-1000MM
05060252	S-1000MM-S2SC40 - Gigabit Fiber to Fiber Media Converter: 1000BASE-SX 850nm multimode (SC) [550 m/1804 ft.] to 1000BASE-EX 1310 nm single mode (SC) [40 km/24.9 miles] - EU Power Cord	https://www.perle.com/products/gigabit-fiber-converters.shtml	Media Converter: S-1000MM
05060262	S-1000MM-S2LC40 - Gigabit Fiber to Fiber Media Converter: 1000BASE-SX 850nm multimode (LC) [550 m/1804 ft.] to 1000BASE-EX 1310 nm single mode (LC) [40 km/24.9 miles] - EU Power Cord	https://www.perle.com/products/gigabit-fiber-converters.shtml	Media Converter: S-1000MM
05060272	S-1000MM-S2ST40 - Gigabit Fiber to Fiber Media Converter: 1000BASE-SX 850nm multimode (ST) [550 m/1804 ft.] to 1000BASE-EX 1310 nm single mode (ST) [40 km/24.9 miles] - EU Power Cord	https://www.perle.com/products/gigabit-fiber-converters.shtml	Media Converter: S-1000MM
05060282	S-1000MM-S2SC70 - Gigabit Fiber to Fiber Media Converter: 1000BASE-SX 850nm multimode (SC) [550 m/1804 ft.] to 1000BASE-ZX 1550 nm single mode (SC) [70 km/43.5 miles] - EU Power Cord	https://www.perle.com/products/gigabit-fiber-converters.shtml	Media Converter: S-1000MM
05060292	S-1000MM-S2LC70 - Gigabit Fiber to Fiber Media Converter: 1000BASE-SX 850nm multimode (LC) [550 m/1804 ft.] to 1000BASE-ZX 1550 nm single mode (LC) [70 km/43.5 miles] - EU Power Cord	https://www.perle.com/products/gigabit-fiber-converters.shtml	Media Converter: S-1000MM
05060302	S-1000MM-S2ST70 - Gigabit Fiber to Fiber Media Converter: 1000BASE-SX 850nm multimode (ST) [550 m/1804 ft.] to 1000BASE-ZX 1550 nm single mode (ST) [70 km/43.5 miles] - EU Power Cord	https://www.perle.com/products/gigabit-fiber-converters.shtml	Media Converter: S-1000MM
05060312	S-1000MM-S2SC120 - Gigabit Fiber to Fiber Media Converter: 1000BASE-SX 850nm multimode (SC) [550 m/1804 ft.] to 1000BASE-ZX 1550 nm single mode (SC) [120 km/74.6 miles] - EU Power Cord	https://www.perle.com/products/gigabit-fiber-converters.shtml	Media Converter: S-1000MM
05060322	S-1000MM-S2LC120 - Gigabit Fiber to Fiber Media Converter: 1000BASE-SX 850nm multimode (LC) [550 m/1804 ft.] to 1000BASE-ZX 1550 nm single mode (LC) [120 km/74.6 miles] - EU Power Cord	https://www.perle.com/products/gigabit-fiber-converters.shtml	Media Converter: S-1000MM
05060332	S-1000MM-S2ST120 - Gigabit Fiber to Fiber Media Converter: 1000BASE-SX 850nm multimode (ST) [550 m/1804 ft.] to 1000BASE-ZX 1550 nm single mode (ST) [120 km/74.6 miles] - EU Power Cord	https://www.perle.com/products/gigabit-fiber-converters.shtml	Media Converter: S-1000MM

Part #	Description	Product Datasheet	Product Group
05060342	S-1000MM-S1SC10U - Gigabit Fiber to Fiber Media Converter: 1000BASE-SX 850nm multimode (SC) [550 m/1804 ft.] to 1000BASE-BX 1310nm TX / 1490nm RX single strand fiber, single mode (SC) [10 km/6.2 miles] - EU Power Cord	https://www.perle.com/products/gigabit-fiber-converters.shtml	Media Converter: S-1000MM
05060352	S-1000MM-S1SC10D - Gigabit Fiber to Fiber Media Converter: 1000BASE-SX 850nm multimode (SC) [550 m/1804 ft.] to 1000BASE-BX 1490nm TX / 1310nm RX single strand fiber, single mode (SC) [10 km/6.2 miles] - EU Power Cord	https://www.perle.com/products/gigabit-fiber-converters.shtml	Media Converter: S-1000MM
05060362	S-1000MM-S1SC20U - Gigabit Fiber to Fiber Media Converter: 1000BASE-SX 850nm multimode (SC) [550 m/1804 ft.] to 1000BASE-BX 1310nm TX / 1490nm RX single strand fiber, single mode (SC) [20 km/12.4 miles] - EU Power Cord	https://www.perle.com/products/gigabit-fiber-converters.shtml	Media Converter: S-1000MM
05060372	S-1000MM-S1SC20D - Gigabit Fiber to Fiber Media Converter: 1000BASE-SX 850nm multimode (SC) [550 m/1804 ft.] to 1000BASE-BX 1490nm TX / 1310nm RX single strand fiber, single mode (SC) [20 km/12.4 miles] - EU Power Cord	https://www.perle.com/products/gigabit-fiber-converters.shtml	Media Converter: S-1000MM
05060382	S-1000MM-S1SC40U - Gigabit Fiber to Fiber Media Converter: 1000BASE-SX 850nm multimode (SC) [550 m/1804 ft.] to 1000BASE-BX 1310nm TX / 1490nm RX single strand fiber, single mode (SC) [40 km/25 miles] - EU Power Cord	https://www.perle.com/products/gigabit-fiber-converters.shtml	Media Converter: S-1000MM
05060392	S-1000MM-S1SC40D - Gigabit Fiber to Fiber Media Converter: 1000BASE-SX 850nm multimode (SC) [550 m/1804 ft.] to 1000BASE-BX 1490nm TX / 1310nm RX single strand fiber, single mode (SC) [40 km/25 miles] - EU Power Cord	https://www.perle.com/products/gigabit-fiber-converters.shtml	Media Converter: S-1000MM
05060402	S-1000MM-S1SC80U - Gigabit Fiber to Fiber Media Converter: 1000BASE-SX 850nm multimode (SC) [550 m/1804 ft.] to 1000BASE-BX 1510nm TX / 1590nm RX single strand fiber, single mode (SC) [80 km/50 miles] - EU Power Cord	https://www.perle.com/products/gigabit-fiber-converters.shtml	Media Converter: S-1000MM
05060412	S-1000MM-S1SC80D - Gigabit Fiber to Fiber Media Converter: 1000BASE-SX 850nm multimode (SC) [550 m/1804 ft.] to 1000BASE-BX 1590nm TX / 1510nm RX single strand fiber, single mode (SC) [80 km/50 miles] - EU Power Cord	https://www.perle.com/products/gigabit-fiber-converters.shtml	Media Converter: S-1000MM

Part #	Description	Product Datasheet	Product Group
05060422	S-1000MM-S1SC120U - Gigabit Fiber to Fiber Media Converter: 1000BASE-SX 850nm multimode (SC) [550 m/1804 ft.] to 1000BASE-BX 1510nm TX / 1590nm RX single strand fiber, single mode (SC) [120 km/75 miles] - EU Power Cord	https://www.perle.com/products/gigabit-fiber-converters.shtml	Media Converter: S-1000MM
05060432	S-1000MM-S1SC120D - Gigabit Fiber to Fiber Media Converter: 1000BASE-SX 850nm multimode (SC) [550 m/1804 ft.] to 1000BASE-BX 1590nm TX / 1510nm RX single strand fiber, single mode (SC) [120 km/75 miles] - EU Power Cord	https://www.perle.com/products/gigabit-fiber-converters.shtml	Media Converter: S-1000MM
05060442	S-1000MM-S2SC160 - Gigabit Fiber to Fiber Media Converter: 1000BASE-SX 850nm multimode (SC) [550 m/1804 ft.] to 1000BASE-ZX 1550 nm single mode (SC) [160 km/100 miles] - EU Power Cord	https://www.perle.com/products/gigabit-fiber-converters.shtml	Media Converter: S-1000MM
05060452	S-1000MM-S2LC160 - Gigabit Fiber to Fiber Media Converter: 1000BASE-SX 850nm multimode (LC) [550 m/1804 ft.] to 1000BASE-ZX 1550 nm single mode (LC) [160 km/100 miles] - EU Power Cord	https://www.perle.com/products/gigabit-fiber-converters.shtml	Media Converter: S-1000MM
05060462	S-1000MM-S2ST160 - Gigabit Fiber to Fiber Media Converter: 1000BASE-SX 850nm multimode (ST) [550 m/1804 ft.] to 1000BASE-ZX 1550 nm single mode (ST) [160 km/100 miles] - EU Power Cord	https://www.perle.com/products/gigabit-fiber-converters.shtml	Media Converter: S-1000MM
05060472	S-1000MM-M2SC2 - Gigabit Fiber to Fiber Media Converter: 1000BASE-SX 850nm multimode (SC) [550 m/1804 ft.] to 1000BASE-LX 1310nm Extended multimode (SC) [2km /6562 ft.] - EU Power Cord	https://www.perle.com/products/gigabit-fiber-converters.shtml	Media Converter: S-1000MM
05060482	S-1000MM-M2LC2 - Gigabit Fiber to Fiber Media Converter: 1000BASE-SX 850nm multimode (LC) [550 m/1804 ft.] to 1000BASE-LX 1310nm Extended multimode (LC) [2km /6562 ft.] - EU Power Cord	https://www.perle.com/products/gigabit-fiber-converters.shtml	Media Converter: S-1000MM
05060492	S-1000MM-M2ST2 - Gigabit Fiber to Fiber Media Converter: 1000BASE-SX 850nm multimode (ST) [550 m/1804 ft.] to 1000BASE-LX 1310nm Extended multimode (ST) [2km /6562 ft.] - EU Power Cord	https://www.perle.com/products/gigabit-fiber-converters.shtml	Media Converter: S-1000MM
05060502	S-10G-ST5 - 10 Gigabit Media Converter with dual SFP+ slots (empty). Includes AC power Adapter - EU Power Cord	https://www.perle.com/products/media-converters/10-gigabit-standalone-media-converters.shtml	Media Converter: S-10G
05060512	S-10G-XT5 - 10 Gigabit Media Converter: with one XFP slot (empty) and one SFP+ slot (empty). AC adapter included - EU Power Cord	https://www.perle.com/products/media-converters/10-gigabit-standalone-media-converters.shtml	Media Converter: S-10G
05060522	S-10G-XTSH - 10 Gigabit Media Converter: with one XFP slot (empty) and one SFP+ slot (empty). Supports Power Level 4 XFPs. AC adapter included - EU Power Cord	https://www.perle.com/products/media-converters/10-gigabit-standalone-media-converters.shtml	Media Converter: S-10G

Part #	Description	Product Datasheet	Product Group
05060532	S-10G-XTX - 10 Gigabit Media Converter: with dual XFP slots (empty). AC adapter included - EU Power Cord	https://www.perle.com/products/media-converters/10-gigabit-standalone-media-converters.shtml	Media Converter: S-10G
05060542	S-10G-XTXH - 10 Gigabit Media Converter: with dual XFP slots (empty). Support Power Level 4 XFPs. AC adapter included - EU Power Cord	https://www.perle.com/products/media-converters/10-gigabit-standalone-media-converters.shtml	Media Converter: S-10G
05060562	S-10GT-XFPH - 10 Gigabit Media Converter: 10GBASE-T (RJ-45) [100 m/328 ft.] (CAT6A or better) to fiber 10GBase-X or copper 10GBase-CX4 XFP. XFP slot (empty). Supports Power Level 4 XFPs. AC Adapter included - EU Power Cord	https://www.perle.com/products/media-converters/10gbase-t-standalone-media-converters.shtml	Media Converter: S-10G
05060572	S-4GPT-DSFP - Protocol Transparent Media Converter with dual SFP slots (empty). Supports two SFPs with identical speeds up to 4.25 Gbps. AC adapter included - EU Power Cord	https://www.perle.com/products/sfp-to-sfp-media-converter.shtml	Media Converter: S-4GPT
05060580	S-4GPT-DSFP-XT - Industrial Temperature Protocol Transparent Media Converter with dual SFP slots (empty). Supports two SFPs with identical speeds up to 4.25 Gbps. Extended Temperature, terminal block power connector for external DC power source	https://www.perle.com/products/sfp-to-sfp-industrial-media-converter.shtml	Media Converter: S-4GPT
05060592	S-100MM-S1ST20U - Fast Ethernet Fiber to Fiber Media Converter: 100BASE-FX 1310nm multimode (ST) [2 km/1.2 miles] to 100Base-BX 1310nm TX / 1550nm RX single strand fiber, single mode (ST) [20 km/12.4 miles] - EU Power Cord	https://www.perle.com/products/fast-ethernet-fiber-converter.shtml	Media Converter: S100MM
05060602	S-100MM-S1ST20D - Fast Ethernet Fiber to Fiber Media Converter: 100BASE-FX 1310nm multimode (ST) [2 km/1.2 miles] to 100Base-BX 1550nm TX / 1310nm RX single strand fiber, single mode (ST) [20 km/12.4 miles] - EU Power Cord	https://www.perle.com/products/fast-ethernet-fiber-converter.shtml	Media Converter: S100MM
05060612	S-10GRT-SFP - 10 Gigabit Media and Rate Converter: 10/100/1000/2.5G/10GBase-T (RJ-45) [100 m/328 ft.] (CAT6A or better) to SFP+ slot (empty). AC Adapter included - EU Power Cord	https://www.perle.com/products/media-converters/10gbase-t-standalone-rate-converter.shtml	Media Converter: S-10GR
05060622	S-10GR-STX - 10 Gigabit Media and Rate Converter with dual SFP+ slots (empty). Includes AC Power Adapter - EU Power Cord	https://www.perle.com/products/media-converters/10-gigabit-standalone-rate-converter.shtml	Media Converter: S-10GR
05061000	C-100MM-M2SC2 - Fast Ethernet Fiber to Fiber Media Converter Module: 100BASE-FX 1310nm multimode (SC) [2 km/1.2 miles] to 100BASE-FX 1310nm multimode (SC) [2 km/1.2 miles]	https://www.perle.com/products/fast-ethernet-fiber-converter-modules.shtml	Media Converter Module: C-100MM

Part #	Description	Product Datasheet	Product Group
05061010	C-100MM-M2ST2 - Fast Ethernet Fiber to Fiber Media Converter Module: 100BASE-FX 1310nm multimode (ST) [2 km/1.2 miles] to 100BASE-FX 1310nm multimode (ST) [2 km/1.2 miles]	https://www.perle.com/products/fast-ethernet-fiber-converter-modules.shtml	Media Converter Module: C-100MM
05061020	C-100MM-M2LC2 - Fast Ethernet Fiber to Fiber Media Converter Module: 100BASE-FX 1310nm multimode (LC) [2 km/1.2 miles] to 100BASE-FX 1310nm multimode (LC) [2 km/1.2 miles]	https://www.perle.com/products/fast-ethernet-fiber-converter-modules.shtml	Media Converter Module: C-100MM
05061030	C-100MM-S2SC20 - Fast Ethernet Fiber to Fiber Media Converter Module: 100BASE-FX 1310nm multimode (SC) [2 km/1.2 miles] to 100Base-LX 1310nm single mode (SC) [20 km/12.4 miles]	https://www.perle.com/products/fast-ethernet-fiber-converter-modules.shtml	Media Converter Module: C-100MM
05061040	C-100MM-S2ST20 - Fast Ethernet Fiber to Fiber Media Converter Module: 100BASE-FX 1310nm multimode (ST) [2 km/1.2 miles] to 100Base-LX 1310nm single mode (ST) [20 km/12.4 miles]	https://www.perle.com/products/fast-ethernet-fiber-converter-modules.shtml	Media Converter Module: C-100MM
05061050	C-100MM-S2LC20 - Fast Ethernet Fiber to Fiber Media Converter Module: 100BASE-FX 1310nm multimode (LC) [2 km/1.2 miles] to 100Base-LX 1310nm single mode (LC) [20 km/12.4 miles]	https://www.perle.com/products/fast-ethernet-fiber-converter-modules.shtml	Media Converter Module: C-100MM
05061060	C-100MM-S2SC40 - Fast Ethernet Fiber to Fiber Media Converter Module: 100BASE-FX 1310nm multimode (SC) [2 km/1.2 miles] to 100Base-EX 1310nm single mode (SC) [40 km/24.9 miles]	https://www.perle.com/products/fast-ethernet-fiber-converter-modules.shtml	Media Converter Module: C-100MM
05061070	C-100MM-S2ST40 - Fast Ethernet Fiber to Fiber Media Converter Module: 100BASE-FX 1310nm multimode (ST) [2 km/1.2 miles] to 100Base-EX 1310nm single mode (ST) [40 km/24.9 miles]	https://www.perle.com/products/fast-ethernet-fiber-converter-modules.shtml	Media Converter Module: C-100MM
05061080	C-100MM-S2LC40 - Fast Ethernet Fiber to Fiber Media Converter Module: 100BASE-FX 1310nm multimode (LC) [2 km/1.2 miles] to 100Base-EX 1310nm single mode (LC) [40 km/24.9 miles]	https://www.perle.com/products/fast-ethernet-fiber-converter-modules.shtml	Media Converter Module: C-100MM
05061090	C-100MM-S2SC80 - Fast Ethernet Fiber to Fiber Media Converter Module: 100BASE-FX 1310nm multimode (SC) [2 km/1.2 miles] to 100Base-ZX 1550nm single mode (SC) [80 km/49.7 miles]	https://www.perle.com/products/fast-ethernet-fiber-converter-modules.shtml	Media Converter Module: C-100MM
05061100	C-100MM-S2ST80 - Fast Ethernet Fiber to Fiber Media Converter Module: 100BASE-FX 1310nm multimode (ST) [2 km/1.2 miles] to 100Base-ZX 1550nm single mode (ST) [80 km/49.7 miles]	https://www.perle.com/products/fast-ethernet-fiber-converter-modules.shtml	Media Converter Module: C-100MM
05061110	C-100MM-S2LC80 - Fast Ethernet Fiber to Fiber Media Converter Module: 100BASE-FX 1310nm multimode (LC) [2 km/1.2 miles] to 100Base-ZX 1550nm single mode (LC) [80 km/49.7 miles]	https://www.perle.com/products/fast-ethernet-fiber-converter-modules.shtml	Media Converter Module: C-100MM

Part #	Description	Product Datasheet	Product Group
05061120	C-100MM-S2SC120 - Fast Ethernet Fiber to Fiber Media Converter Module: 100BASE-FX 1310nm multimode (SC) [2 km/1.2 miles] to 100Base-ZX 1550nm single mode (SC) [120 km/74.6 miles]	https://www.perle.com/products/fast-ethernet-fiber-converter-modules.shtml	Media Converter Module: C-100MM
05061130	C-100MM-S2ST120 - Fast Ethernet Fiber to Fiber Media Converter Module: 100BASE-FX 1310nm multimode (ST) [2 km/1.2 miles] to 100Base-ZX 1550nm single mode (ST) [120 km/74.6 miles]	https://www.perle.com/products/fast-ethernet-fiber-converter-modules.shtml	Media Converter Module: C-100MM
05061140	C-100MM-S2LC120 - Fast Ethernet Fiber to Fiber Media Converter Module: 100BASE-FX 1310nm multimode (LC) [2 km/1.2 miles] to 100Base-ZX 1550nm single mode (LC) [120 km/74.6 miles]	https://www.perle.com/products/fast-ethernet-fiber-converter-modules.shtml	Media Converter Module: C-100MM
05061150	C-100MM-S1SC20U - Fast Ethernet Fiber to Fiber Media Converter Module: 100BASE-FX 1310nm multimode (SC) [2 km/1.2 miles] to 100Base-BX 1310nm TX / 1550nm RX single strand fiber, single mode (SC) [20 km/12.4 miles]	https://www.perle.com/products/fast-ethernet-fiber-converter-modules.shtml	Media Converter Module: C-100MM
05061160	C-100MM-S1SC20D - Fast Ethernet Fiber to Fiber Media Converter Module: 100BASE-FX 1310nm multimode (SC) [2 km/1.2 miles] to 100Base-BX 1550nm TX / 1310nm RX single strand fiber, single mode (SC) [20 km/12.4 miles]	https://www.perle.com/products/fast-ethernet-fiber-converter-modules.shtml	Media Converter Module: C-100MM
05061170	C-100MM-S1SC40U - Fast Ethernet Fiber to Fiber Media Converter Module: 100BASE-FX 1310nm multimode (SC) [2 km/1.2 miles] to 100Base-BX 1310nm TX / 1550nm RX single strand fiber, single mode (SC) [40 km/24.9 miles]	https://www.perle.com/products/fast-ethernet-fiber-converter-modules.shtml	Media Converter Module: C-100MM
05061180	C-100MM-S1SC40D - Fast Ethernet Fiber to Fiber Media Converter Module: 100BASE-FX 1310nm multimode (SC) [2 km/1.2 miles] to 100Base-BX 1550nm TX / 1310nm RX single strand fiber, single mode (SC) [40 km/24.9 miles]	https://www.perle.com/products/fast-ethernet-fiber-converter-modules.shtml	Media Converter Module: C-100MM
05061190	C-1000MM-M2SC05 - Gigabit Fiber to Fiber Media Converter Module: 1000BASE-SX 850nm multimode (SC) [550 m/1804 ft.] to 1000BASE-SX 850nm multimode (SC) [550 m/1804 ft.]	https://www.perle.com/products/gigabit-fiber-converter-modules.shtml	Media Converter Module: C-1000MM
05061200	C-1000MM-M2LC05 - Gigabit Fiber to Fiber Media Converter Module: 1000BASE-SX 850nm multimode (LC) [550 m/1804 ft.] to 1000BASE-SX 850nm multimode (LC) [550 m/1804 ft.]	https://www.perle.com/products/gigabit-fiber-converter-modules.shtml	Media Converter Module: C-1000MM
05061210	C-1000MM-M2ST05 - Gigabit Fiber to Fiber Media Converter Module: 1000BASE-SX 850nm multimode (ST) [550 m/1804 ft.] to 1000BASE-SX 850nm multimode (ST) [550 m/1804 ft.]	https://www.perle.com/products/gigabit-fiber-converter-modules.shtml	Media Converter Module: C-1000MM

Part #	Description	Product Datasheet	Product Group
05061220	C-1000MM-S2SC10 - Gigabit Fiber to Fiber Media Converter Module: 1000BASE-SX 850nm multimode (SC) [550 m/1804 ft.] to 1000BASE-LX/LH 1310 nm single mode (SC) [10 km/6.2 miles]	https://www.perle.com/products/gigabit-fiber-converter-modules.shtml	Media Converter Module: C-1000MM
05061230	C-1000MM-S2LC10 - Gigabit Fiber to Fiber Media Converter Module: 1000BASE-SX 850nm multimode (LC) [550 m/1804 ft.] to 1000BASE-LX/LH 1310 nm single mode (LC) [10 km/6.2 miles]	https://www.perle.com/products/gigabit-fiber-converter-modules.shtml	Media Converter Module: C-1000MM
05061240	C-1000MM-S2ST10 - Gigabit Fiber to Fiber Media Converter Module: 1000BASE-SX 850nm multimode (ST) [550 m/1804 ft.] to 1000BASE-LX/LH 1310 nm single mode (ST) [10 km/6.2 miles]	https://www.perle.com/products/gigabit-fiber-converter-modules.shtml	Media Converter Module: C-1000MM
05061250	C-1000MM-S2SC40 - Gigabit Fiber to Fiber Media Converter Module: 1000BASE-SX 850nm multimode (SC) [550 m/1804 ft.] to 1000BASE-EX 1310 nm single mode (SC) [40 km/24.9 miles].	https://www.perle.com/products/gigabit-fiber-converter-modules.shtml	Media Converter Module: C-1000MM
05061260	C-1000MM-S2LC40 - Gigabit Fiber to Fiber Media Converter Module: 1000BASE-SX 850nm multimode (LC) [550 m/1804 ft.] to 1000BASE-EX 1310 nm single mode (LC) [40 km/24.9 miles].	https://www.perle.com/products/gigabit-fiber-converter-modules.shtml	Media Converter Module: C-1000MM
05061270	C-1000MM-S2ST40 - Gigabit Fiber to Fiber Media Converter Module: 1000BASE-SX 850nm multimode (ST) [550 m/1804 ft.] to 1000BASE-EX 1310 nm single mode (ST) [40 km/24.9 miles].	https://www.perle.com/products/gigabit-fiber-converter-modules.shtml	Media Converter Module: C-1000MM
05061280	C-1000MM-S2SC70 - Gigabit Fiber to Fiber Media Converter Module: 1000BASE-SX 850nm multimode (SC) [550 m/1804 ft.] to 1000BASE-ZX 1550 nm single mode (SC) [70 km/43.5 miles]	https://www.perle.com/products/gigabit-fiber-converter-modules.shtml	Media Converter Module: C-1000MM
05061290	C-1000MM-S2LC70 - Gigabit Fiber to Fiber Media Converter Module: 1000BASE-SX 850nm multimode (LC) [550 m/1804 ft.] to 1000BASE-ZX 1550 nm single mode (LC) [70 km/43.5 miles]	https://www.perle.com/products/gigabit-fiber-converter-modules.shtml	Media Converter Module: C-1000MM
05061300	C-1000MM-S2ST70 - Gigabit Fiber to Fiber Media Converter Module: 1000BASE-SX 850nm multimode (ST) [550 m/1804 ft.] to 1000BASE-ZX 1550 nm single mode (ST) [70 km/43.5 miles]	https://www.perle.com/products/gigabit-fiber-converter-modules.shtml	Media Converter Module: C-1000MM
05061310	C-1000MM-S2SC120 - Gigabit Fiber to Fiber Media Converter Module: 1000BASE-SX 850nm multimode (SC) [550 m/1804 ft.] to 1000BASE-ZX 1550 nm single mode (SC) [120 km/74.6 miles]	https://www.perle.com/products/gigabit-fiber-converter-modules.shtml	Media Converter Module: C-1000MM
05061320	C-1000MM-S2LC120 - Gigabit Fiber to Fiber Media Converter Module: 1000BASE-SX 850nm multimode (LC) [550 m/1804 ft.] to 1000BASE-ZX 1550 nm single mode (LC) [120 km/74.6 miles]	https://www.perle.com/products/gigabit-fiber-converter-modules.shtml	Media Converter Module: C-1000MM

Part #	Description	Product Datasheet	Product Group
05061330	C-1000MM-S2ST120 - Gigabit Fiber to Fiber Media Converter Module: 1000BASE-SX 850nm multimode (ST) [550 m/1804 ft.] to 1000BASE-ZX 1550 nm single mode (ST) [120 km/74.6 miles]	https://www.perle.com/products/gigabit-fiber-converter-modules.shtml	Media Converter Module: C-1000MM
05061340	C-1000MM-S1SC10U - Gigabit Fiber to Fiber Media Converter Module: 1000BASE-SX 850nm multimode (SC) [550 m/1804 ft.] to 1000BASE-BX 1310nm TX / 1490nm RX single strand fiber, single mode (SC) [10 km/6.2 miles]	https://www.perle.com/products/gigabit-fiber-converter-modules.shtml	Media Converter Module: C-1000MM
05061350	C-1000MM-S1SC10D - Gigabit Fiber to Fiber Media Converter Module: 1000BASE-SX 850nm multimode (SC) [550 m/1804 ft.] to 1000BASE-BX 1490nm TX / 1310nm RX single strand fiber, single mode (SC) [10 km/6.2 miles]	https://www.perle.com/products/gigabit-fiber-converter-modules.shtml	Media Converter Module: C-1000MM
05061360	C-1000MM-S1SC20U - Gigabit Fiber to Fiber Media Converter Module: 1000BASE-SX 850nm multimode (SC) [550 m/1804 ft.] to 1000BASE-BX 1310nm TX / 1490nm RX single strand fiber, single mode (SC) [20 km/12.4 miles]	https://www.perle.com/products/gigabit-fiber-converter-modules.shtml	Media Converter Module: C-1000MM
05061370	C-1000MM-S1SC20D - Gigabit Fiber to Fiber Media Converter Module: 1000BASE-SX 850nm multimode (SC) [550 m/1804 ft.] to 1000BASE-BX 1490nm TX / 1310nm RX single strand fiber, single mode (SC) [20 km/12.4 miles]	https://www.perle.com/products/gigabit-fiber-converter-modules.shtml	Media Converter Module: C-1000MM
05061380	C-1000MM-S1SC40U - Gigabit Fiber to Fiber Media Converter Module: 1000BASE-SX 850nm multimode (SC) [550 m/1804 ft.] to 1000BASE-BX 1310nm TX / 1490nm RX single strand fiber, single mode (SC) [40 km/25 miles]	https://www.perle.com/products/gigabit-fiber-converter-modules.shtml	Media Converter Module: C-1000MM
05061390	C-1000MM-S1SC40D - Gigabit Fiber to Fiber Media Converter Module: 1000BASE-SX 850nm multimode (SC) [550 m/1804 ft.] to 1000BASE-BX 1490nm TX / 1310nm RX single strand fiber, single mode (SC) [40 km/25 miles]	https://www.perle.com/products/gigabit-fiber-converter-modules.shtml	Media Converter Module: C-1000MM
05061400	C-1000MM-S1SC80U - Gigabit Fiber to Fiber Media Converter Module: 1000BASE-SX 850nm multimode (SC) [550 m/1804 ft.] to 1000BASE-BX 1510nm TX / 1590nm RX single strand fiber, single mode (SC) [80 km/50 miles]	https://www.perle.com/products/gigabit-fiber-converter-modules.shtml	Media Converter Module: C-1000MM
05061410	C-1000MM-S1SC80D - Gigabit Fiber to Fiber Media Converter Module: 1000BASE-SX 850nm multimode (SC) [550 m/1804 ft.] to 1000BASE-BX 1590nm TX / 1510nm RX single strand fiber, single mode (SC) [80 km/50 miles]	https://www.perle.com/products/gigabit-fiber-converter-modules.shtml	Media Converter Module: C-1000MM

Part #	Description	Product Datasheet	Product Group
05061420	C-1000MM-S1SC120U - Gigabit Fiber to Fiber Media Converter Module: 1000BASE-SX 850nm multimode (SC) [550 m/1804 ft.] to 1000BASE-BX 1510nm TX / 1590nm RX single strand fiber, single mode (SC) [120 km/75 miles]	https://www.perle.com/products/gigabit-fiber-converter-modules.shtml	Media Converter Module: C-1000MM
05061430	C-1000MM-S1SC120D - Gigabit Fiber to Fiber Media Converter Module: 1000BASE-SX 850nm multimode (SC) [550 m/1804 ft.] to 1000BASE-BX 1590nm TX / 1510nm RX single strand fiber, single mode (SC) [120 km/75 miles]	https://www.perle.com/products/gigabit-fiber-converter-modules.shtml	Media Converter Module: C-1000MM
05061440	C-1000MM-S2SC160 - Gigabit Fiber to Fiber Media Converter Module: 1000BASE-SX 850nm multimode (SC) [550 m/1804 ft.] to 1000BASE-ZX 1550 nm single mode (SC) [160 km/100 miles]	https://www.perle.com/products/gigabit-fiber-converter-modules.shtml	Media Converter Module: C-1000MM
05061450	C-1000MM-S2LC160 - Gigabit Fiber to Fiber Media Converter Module: 1000BASE-SX 850nm multimode (LC) [550 m/1804 ft.] to 1000BASE-ZX 1550 nm single mode (LC) [160 km/100 miles]	https://www.perle.com/products/gigabit-fiber-converter-modules.shtml	Media Converter Module: C-1000MM
05061460	C-1000MM-S2ST160 - Gigabit Fiber to Fiber Media Converter Module: 1000BASE-SX 850nm multimode (ST) [550 m/1804 ft.] to 1000BASE-ZX 1550 nm single mode (ST) [160 km/100 miles]	https://www.perle.com/products/gigabit-fiber-converter-modules.shtml	Media Converter Module: C-1000MM
05061470	C-1000MM-M2SC2 - Gigabit Fiber to Fiber Media Converter Module: 1000BASE-SX 850nm multimode (SC) [550 m/1804 ft.] to 1000BASE-LX 1310nm Extended multimode (SC) [2km /6562 ft.]	https://www.perle.com/products/gigabit-fiber-converter-modules.shtml	Media Converter Module: C-1000MM
05061480	C-1000MM-M2LC2 - Gigabit Fiber to Fiber Media Converter Module: 1000BASE-SX 850nm multimode (LC) [550 m/1804 ft.] to 1000BASE-LX 1310nm Extended multimode (LC) [2km /6562 ft.]	https://www.perle.com/products/gigabit-fiber-converter-modules.shtml	Media Converter Module: C-1000MM
05061490	C-1000MM-M2ST2 - Gigabit Fiber to Fiber Media Converter Module: 1000BASE-SX 850nm multimode (ST) [550 m/1804 ft.] to 1000BASE-LX 1310nm Extended multimode (ST) [2km /6562 ft.]	https://www.perle.com/products/gigabit-fiber-converter-modules.shtml	Media Converter Module: C-1000MM
05061500	C-10G-ST5 - 10 Gigabit Media Converter Module with dual SFP+ slots (empty)	https://www.perle.com/products/media-converters/10-gigabit-media-converter-modules.shtml	Media Converter Module: C-10G
05061510	C-10G-XT5 - 10 Gigabit Media Converter Module with one XFP slot (empty) and one SFP+ slot (empty)	https://www.perle.com/products/media-converters/10-gigabit-media-converter-modules.shtml	Media Converter Module: C-10G
05061520	C-10G-XTSH - 10 Gigabit Media Converter Module with one XFP slot (empty) and one SFP+ slot (empty). Supports Power Level 4 XFPs	https://www.perle.com/products/media-converters/10-gigabit-media-converter-modules.shtml	Media Converter Module: C-10G

Part #	Description	Product Datasheet	Product Group
05061530	C-10G-XTX - 10 Gigabit Media Converter Module with dual XFP slots (empty)	https://www.perle.com/products/media-converters/10-gigabit-media-converter-modules.shtml	Media Converter Module: C-10G
05061540	C-10G-XTXH - 10 Gigabit Media Converter Module with dual XFP slots (empty). Supports Power Level 4 XFPs	https://www.perle.com/products/media-converters/10-gigabit-media-converter-modules.shtml	Media Converter Module: C-10G
05061560	C-10GT-XFPH - 10 Gigabit Media Converter Module: 10GBASE-T (RJ-45) [100 m/328 ft.] (CAT6A or better) to fiber 10GBase-X or copper 10GBase-CX4 XFP. XFP slot (empty). Supports Power Level 4 XFPs	https://www.perle.com/products/media-converters/10gbase-t-media-converter-modules.shtml	Media Converter Module: C-10G
05061570	C-4GPT-DSFP - Protocol Transparent Media Converter module with dual SFP slots (empty). Supports two SFPs with identical speeds up to 4.25 Gbps.	https://www.perle.com/products/sfp-to-sfp-media-converter-module.shtml	Media Converter Module: C-4GPT
05061590	C-100MM-S1ST20U - Fast Ethernet Fiber to Fiber Media Converter Module: 100BASE-FX 1310nm multimode (ST) [2 km/1.2 miles] to 100Base-BX 1310nm TX / 1550nm RX single strand fiber, single mode (ST) [20 km/12.4 miles]	https://www.perle.com/products/fast-ethernet-fiber-converter-modules.shtml	Media Converter Module: C-100MM
05061600	C-100MM-S1ST20D - Fast Ethernet Fiber to Fiber Media Converter Module: 100BASE-FX 1310nm multimode (ST) [2 km/1.2 miles] to 100Base-BX 1550nm TX / 1310nm RX single strand fiber, single mode (ST) [20 km/12.4 miles]	https://www.perle.com/products/fast-ethernet-fiber-converter-modules.shtml	Media Converter Module: C-100MM
05061610	C-10GRT-SFP - 10 Gigabit Media and Rate Converter Module: 10/100/1000/2.5G/10GBase-T (RJ-45) [100 m/328 ft.] (CAT6A or better) to SFP+ slot (empty).	https://www.perle.com/products/media-converters/10gbase-t-rate-converter-module.shtml	Media Converter Module: C-10GR
05061620	C-10GR-STX - 10 Gigabit Media and Rate Converter Module with dual SFP+ slots (empty)	https://www.perle.com/products/media-converters/10-gigabit-rate-converter-module.shtml	Media Converter Module: C-10GR
05062000	CM-100MM-M2SC2 Managed Fast Ethernet Fiber to Fiber Converter Module: 100BASE-FX 1310nm multimode (SC) [2 km/1.2 miles] to 100BASE-FX 1310nm multimode (SC) [2 km/1.2 miles]. Managed or unmanaged operation.	https://www.perle.com/products/fast-ethernet-fiber-managed-converter-module.shtml	Media Converter Module: CM-100MM
05062010	CM-100MM-M2ST2 Managed Fast Ethernet Fiber to Fiber Converter Module: 100BASE-FX 1310nm multimode (ST) [2 km/1.2 miles] to 100BASE-FX 1310nm multimode (ST) [2 km/1.2 miles]. Managed or unmanaged operation.	https://www.perle.com/products/fast-ethernet-fiber-managed-converter-module.shtml	Media Converter Module: CM-100MM

Part #	Description	Product Datasheet	Product Group
05062020	CM-100MM-M2LC2 Managed Fast Ethernet Fiber to Fiber Converter Module: 100BASE-FX 1310nm multimode (LC) [2 km/1.2 miles] to 100BASE-FX 1310nm multimode (LC) [2 km/1.2 miles]. Managed or unmanaged operation.	https://www.perle.com/products/fast-ethernet-fiber-managed-converter-module.shtml	Media Converter Module: CM-100MM
05062030	CM-100MM-S2SC20 Managed Fast Ethernet Fiber to Fiber Converter Module: 100BASE-FX 1310nm multimode (SC) [2 km/1.2 miles] to 100Base-LX 1310nm single mode (SC) [20 km/12.4 miles]. Managed or unmanaged operation.	https://www.perle.com/products/fast-ethernet-fiber-managed-converter-module.shtml	Media Converter Module: CM-100MM
05062040	CM-100MM-S2ST20 Managed Fast Ethernet Fiber to Fiber Converter Module: 100BASE-FX 1310nm multimode (ST) [2 km/1.2 miles] to 100Base-LX 1310nm single mode (ST) [20 km/12.4 miles]. Managed or unmanaged operation.	https://www.perle.com/products/fast-ethernet-fiber-managed-converter-module.shtml	Media Converter Module: CM-100MM
05062050	CM-100MM-S2LC20 Managed Fast Ethernet Fiber to Fiber Converter Module: 100BASE-FX 1310nm multimode (LC) [2 km/1.2 miles] to 100Base-LX 1310nm single mode (LC) [20 km/12.4 miles]. Managed or unmanaged operation.	https://www.perle.com/products/fast-ethernet-fiber-managed-converter-module.shtml	Media Converter Module: CM-100MM
05062060	CM-100MM-S2SC40 Managed Fast Ethernet Fiber to Fiber Converter Module: 100BASE-FX 1310nm multimode (SC) [2 km/1.2 miles] to 100Base-EX 1310nm single mode (SC) [40 km/24.9 miles]. Managed or unmanaged operation.	https://www.perle.com/products/fast-ethernet-fiber-managed-converter-module.shtml	Media Converter Module: CM-100MM
05062070	CM-100MM-S2ST40 Managed Fast Ethernet Fiber to Fiber Converter Module: 100BASE-FX 1310nm multimode (ST) [2 km/1.2 miles] to 100Base-EX 1310nm single mode (ST) [40 km/24.9 miles]. Managed or unmanaged operation.	https://www.perle.com/products/fast-ethernet-fiber-managed-converter-module.shtml	Media Converter Module: CM-100MM
05062080	CM-100MM-S2LC40 Managed Fast Ethernet Fiber to Fiber Converter Module: 100BASE-FX 1310nm multimode (LC) [2 km/1.2 miles] to 100Base-EX 1310nm single mode (LC) [40 km/24.9 miles]. Managed or unmanaged operation.	https://www.perle.com/products/fast-ethernet-fiber-managed-converter-module.shtml	Media Converter Module: CM-100MM
05062090	CM-100MM-S2SC80 Managed Fast Ethernet Fiber to Fiber Converter Module: 100BASE-FX 1310nm multimode (SC) [2 km/1.2 miles] to 100Base-ZX 1550nm single mode (SC) [80 km/49.7 miles]. Managed or unmanaged operation.	https://www.perle.com/products/fast-ethernet-fiber-managed-converter-module.shtml	Media Converter Module: CM-100MM

Part #	Description	Product Datasheet	Product Group
05062100	CM-100MM-S2ST80 Managed Fast Ethernet Fiber to Fiber Converter Module: 100BASE-FX 1310nm multimode (ST) [2 km/1.2 miles] to 100Base-ZX 1550nm single mode (ST) [80 km/49.7 miles]. Managed or unmanaged operation.	https://www.perle.com/products/fast-ethernet-fiber-managed-converter-module.shtml	Media Converter Module: CM-100MM
05062110	CM-100MM-S2LC80 Managed Fast Ethernet Fiber to Fiber Converter Module: 100BASE-FX 1310nm multimode (LC) [2 km/1.2 miles] to 100Base-ZX 1550nm single mode (LC) [80 km/49.7 miles]. Managed or unmanaged operation.	https://www.perle.com/products/fast-ethernet-fiber-managed-converter-module.shtml	Media Converter Module: CM-100MM
05062120	CM-100MM-S2SC120 Managed Fast Ethernet Fiber to Fiber Converter Module: 100BASE-FX 1310nm multimode (SC) [2 km/1.2 miles] to 100Base-ZX 1550nm single mode (SC) [120 km/74.6 miles]. Managed or unmanaged operation.	https://www.perle.com/products/fast-ethernet-fiber-managed-converter-module.shtml	Media Converter Module: CM-100MM
05062130	CM-100MM-S2ST120 Managed Fast Ethernet Fiber to Fiber Converter Module: 100BASE-FX 1310nm multimode (ST) [2 km/1.2 miles] to 100Base-ZX 1550nm single mode (ST) [120 km/74.6 miles]. Managed or unmanaged operation.	https://www.perle.com/products/fast-ethernet-fiber-managed-converter-module.shtml	Media Converter Module: CM-100MM
05062140	CM-100MM-S2LC120 Managed Fast Ethernet Fiber to Fiber Converter Module: 100BASE-FX 1310nm multimode (LC) [2 km/1.2 miles] to 100Base-ZX 1550nm single mode (LC) [120 km/74.6 miles]. Managed or unmanaged operation.	https://www.perle.com/products/fast-ethernet-fiber-managed-converter-module.shtml	Media Converter Module: CM-100MM
05062150	CM-100MM-S1SC20U Managed Fast Ethernet Fiber to Fiber Converter Module: 100BASE-FX 1310nm multimode (SC) [2 km/1.2 miles] to 100Base-BX 1310nm TX / 1550nm RX single strand fiber, single mode (SC) [20 km/12.4 miles]. Managed or unmanaged operation.	https://www.perle.com/products/fast-ethernet-fiber-managed-converter-module.shtml	Media Converter Module: CM-100MM
05062160	CM-100MM-S1SC20D Managed Fast Ethernet Fiber to Fiber Converter Module: 100BASE-FX 1310nm multimode (SC) [2 km/1.2 miles] to 100Base-BX 1550nm TX / 1310nm RX single strand fiber, single mode (SC) [20 km/12.4 miles]. Managed or unmanaged operation.	https://www.perle.com/products/fast-ethernet-fiber-managed-converter-module.shtml	Media Converter Module: CM-100MM
05062170	CM-100MM-S1SC40U Managed Fast Ethernet Fiber to Fiber Converter Module: 100BASE-FX 1310nm multimode (SC) [2 km/1.2 miles] to 100Base-BX 1310nm TX / 1550nm RX single strand fiber, single mode (SC) [40 km/24.9 miles]. Managed or unmanaged operation.	https://www.perle.com/products/fast-ethernet-fiber-managed-converter-module.shtml	Media Converter Module: CM-100MM

Part #	Description	Product Datasheet	Product Group
05062180	CM-100MM-S1SC40D Managed Fast Ethernet Fiber to Fiber Converter Module: 100BASE-FX 1310nm multimode (SC) [2 km/1.2 miles] to 100Base-BX 1550nm TX / 1310nm RX single strand fiber, single mode (SC) [40 km/24.9 miles]. Managed or unmanaged operation.	https://www.perle.com/products/fast-ethernet-fiber-managed-converter-module.shtml	Media Converter Module: CM-100MM
05062190	CM-1000MM-M2SC05 - Managed Gigabit Fiber to Fiber Converter Module: 1000BASE-SX 850nm multimode (SC) [550 m/1804 ft.] to 1000BASE-SX 850nm multimode (SC) [550 m/1804 ft.]. Managed or unmanaged operation.	https://www.perle.com/products/gigabit-fiber-managed-converter-modules.shtml	Media Converter Module: CM-1000MM
05062200	CM-1000MM-M2LC05 - Managed Gigabit Fiber to Fiber Converter Module: 1000BASE-SX 850nm multimode (LC) [550 m/1804 ft.] to 1000BASE-SX 850nm multimode (LC) [550 m/1804 ft.]. Managed or unmanaged operation.	https://www.perle.com/products/gigabit-fiber-managed-converter-modules.shtml	Media Converter Module: CM-1000MM
05062210	CM-1000MM-M2ST05 - Managed Gigabit Fiber to Fiber Converter Module: 1000BASE-SX 850nm multimode (ST) [550 m/1804 ft.] to 1000BASE-SX 850nm multimode (ST) [550 m/1804 ft.]. Managed or unmanaged operation.	https://www.perle.com/products/gigabit-fiber-managed-converter-modules.shtml	Media Converter Module: CM-1000MM
05062220	CM-1000MM-S2SC10 - Managed Gigabit Fiber to Fiber Converter Module: 1000BASE-SX 850nm multimode (SC) [550 m/1804 ft.] to 1000BASE-LX/LH 1310 nm single mode (SC) [10 km/6.2 miles]. Managed or unmanaged operation.	https://www.perle.com/products/gigabit-fiber-managed-converter-modules.shtml	Media Converter Module: CM-1000MM
05062230	CM-1000MM-S2LC10 - Managed Gigabit Fiber to Fiber Converter Module: 1000BASE-SX 850nm multimode (LC) [550 m/1804 ft.] to 1000BASE-LX/LH 1310 nm single mode (LC) [10 km/6.2 miles]. Managed or unmanaged operation.	https://www.perle.com/products/gigabit-fiber-managed-converter-modules.shtml	Media Converter Module: CM-1000MM
05062240	CM-1000MM-S2ST10 - Managed Gigabit Fiber to Fiber Converter Module: 1000BASE-SX 850nm multimode (ST) [550 m/1804 ft.] to 1000BASE-LX/LH 1310 nm single mode (ST) [10 km/6.2 miles]. Managed or unmanaged operation.	https://www.perle.com/products/gigabit-fiber-managed-converter-modules.shtml	Media Converter Module: CM-1000MM
05062250	CM-1000MM-S2SC40 - Managed Gigabit Fiber to Fiber Converter Module: 1000BASE-SX 850nm multimode (SC) [550 m/1804 ft.] to 1000BASE-EX 1310 nm single mode (SC) [40 km/24.9 miles]. Managed or unmanaged operation.	https://www.perle.com/products/gigabit-fiber-managed-converter-modules.shtml	Media Converter Module: CM-1000MM

Part #	Description	Product Datasheet	Product Group
05062260	CM-1000MM-S2LC40 - Managed Gigabit Fiber to Fiber Converter Module: 1000BASE-SX 850nm multimode (LC) [550 m/1804 ft.] to 1000BASE-EX 1310 nm single mode (LC) [40 km/24.9 miles]. Managed or unmanaged operation.	https://www.perle.com/products/gigabit-fiber-managed-converter-modules.shtml	Media Converter Module: CM-1000MM
05062270	CM-1000MM-S2ST40 - Managed Gigabit Fiber to Fiber Converter Module: 1000BASE-SX 850nm multimode (ST) [550 m/1804 ft.] to 1000BASE-EX 1310 nm single mode (ST) [40 km/24.9 miles]. Managed or unmanaged operation.	https://www.perle.com/products/gigabit-fiber-managed-converter-modules.shtml	Media Converter Module: CM-1000MM
05062280	CM-1000MM-S2SC70 - Managed Gigabit Fiber to Fiber Converter Module: 1000BASE-SX 850nm multimode (SC) [550 m/1804 ft.] to 1000BASE-ZX 1550 nm single mode (SC) [70 km/43.5 miles]. Managed or unmanaged operation.	https://www.perle.com/products/gigabit-fiber-managed-converter-modules.shtml	Media Converter Module: CM-1000MM
05062290	CM-1000MM-S2LC70 - Managed Gigabit Fiber to Fiber Converter Module: 1000BASE-SX 850nm multimode (LC) [550 m/1804 ft.] to 1000BASE-ZX 1550 nm single mode (LC) [70 km/43.5 miles]. Managed or unmanaged operation.	https://www.perle.com/products/gigabit-fiber-managed-converter-modules.shtml	Media Converter Module: CM-1000MM
05062300	CM-1000MM-S2ST70 - Managed Gigabit Fiber to Fiber Converter Module: 1000BASE-SX 850nm multimode (ST) [550 m/1804 ft.] to 1000BASE-ZX 1550 nm single mode (ST) [70 km/43.5 miles]. Managed or unmanaged operation.	https://www.perle.com/products/gigabit-fiber-managed-converter-modules.shtml	Media Converter Module: CM-1000MM
05062310	CM-1000MM-S2SC120 - Managed Gigabit Fiber to Fiber Converter Module: 1000BASE-SX 850nm multimode (SC) [550 m/1804 ft.] to 1000BASE-ZX 1550 nm single mode (SC) [120 km/74.6 miles]. Managed or unmanaged operation.	https://www.perle.com/products/gigabit-fiber-managed-converter-modules.shtml	Media Converter Module: CM-1000MM
05062320	CM-1000MM-S2LC120 - Managed Gigabit Fiber to Fiber Converter Module: 1000BASE-SX 850nm multimode (LC) [550 m/1804 ft.] to 1000BASE-ZX 1550 nm single mode (LC) [120 km/74.6 miles]. Managed or unmanaged operation.	https://www.perle.com/products/gigabit-fiber-managed-converter-modules.shtml	Media Converter Module: CM-1000MM
05062330	CM-1000MM-S2ST120 - Managed Gigabit Fiber to Fiber Converter Module: 1000BASE-SX 850nm multimode (ST) [550 m/1804 ft.] to 1000BASE-ZX 1550 nm single mode (ST) [120 km/74.6 miles]. Managed or unmanaged operation.	https://www.perle.com/products/gigabit-fiber-managed-converter-modules.shtml	Media Converter Module: CM-1000MM

Part #	Description	Product Datasheet	Product Group
05062340	CM-1000MM-S1SC10U - Managed Gigabit Fiber to Fiber Converter Module: 1000BASE-SX 850nm multimode (SC) [550 m/1804 ft.] to 1000BASE-BX 1310nm TX / 1490nm RX single strand fiber, single mode (SC) [10 km/6.2 miles]. Managed or unmanaged operation.	https://www.perle.com/products/gigabit-fiber-managed-converter-modules.shtml	Media Converter Module: CM-1000MM
05062350	CM-1000MM-S1SC10D - Managed Gigabit Fiber to Fiber Converter Module: 1000BASE-SX 850nm multimode (SC) [550 m/1804 ft.] to 1000BASE-BX 1490nm TX / 1310nm RX single strand fiber, single mode (SC) [10 km/6.2 miles]. Managed or unmanaged operation.	https://www.perle.com/products/gigabit-fiber-managed-converter-modules.shtml	Media Converter Module: CM-1000MM
05062360	CM-1000MM-S1SC20U - Managed Gigabit Fiber to Fiber Converter Module: 1000BASE-SX 850nm multimode (SC) [550 m/1804 ft.] to 1000BASE-BX 1310nm TX / 1490nm RX single strand fiber, single mode (SC) [20 km/12.4 miles]. Managed or unmanaged operation.	https://www.perle.com/products/gigabit-fiber-managed-converter-modules.shtml	Media Converter Module: CM-1000MM
05062370	CM-1000MM-S1SC20D - Managed Gigabit Fiber to Fiber Converter Module: 1000BASE-SX 850nm multimode (SC) [550 m/1804 ft.] to 1000BASE-BX 1490nm TX / 1310nm RX single strand fiber, single mode (SC) [20 km/12.4 miles]. Managed or unmanaged operation.	https://www.perle.com/products/gigabit-fiber-managed-converter-modules.shtml	Media Converter Module: CM-1000MM
05062380	CM-1000MM-S1SC40U - Managed Gigabit Fiber to Fiber Converter Module: 1000BASE-SX 850nm multimode (SC) [550 m/1804 ft.] to 1000BASE-BX 1310nm TX / 1490nm RX single strand fiber, single mode (SC) [40 km/25 miles]. Managed or unmanaged operation.	https://www.perle.com/products/gigabit-fiber-managed-converter-modules.shtml	Media Converter Module: CM-1000MM
05062390	CM-1000MM-S1SC40D - Managed Gigabit Fiber to Fiber Converter Module: 1000BASE-SX 850nm multimode (SC) [550 m/1804 ft.] to 1000BASE-BX 1490nm TX / 1310nm RX single strand fiber, single mode (SC) [40 km/25 miles]. Managed or unmanaged operation.	https://www.perle.com/products/gigabit-fiber-managed-converter-modules.shtml	Media Converter Module: CM-1000MM
05062400	CM-1000MM-S1SC80U - Managed Gigabit Fiber to Fiber Converter Module: 1000BASE-SX 850nm multimode (SC) [550 m/1804 ft.] to 1000BASE-BX 1510nm TX / 1590nm RX single strand fiber, single mode (SC) [80 km/50 miles]. Managed or unmanaged operation.	https://www.perle.com/products/gigabit-fiber-managed-converter-modules.shtml	Media Converter Module: CM-1000MM
05062410	CM-1000MM-S1SC80D - Managed Gigabit Fiber to Fiber Converter Module: 1000BASE-SX 850nm multimode (SC) [550 m/1804 ft.] to 1000BASE-BX 1490nm TX / 1310nm RX single strand fiber, single mode (SC) [80 km/50 miles]. Managed or unmanaged operation.	https://www.perle.com/products/gigabit-fiber-managed-converter-modules.shtml	Media Converter Module: CM-1000MM

Part #	Description	Product Datasheet	Product Group
05062420	CM-1000MM-S1SC120U - Managed Gigabit Fiber to Fiber Converter Module: 1000BASE-SX 850nm multimode (SC) [550 m/1804 ft.] to 1000BASE-BX 1510nm TX / 1590nm RX single strand fiber, single mode (SC) [120 km/75 miles]. Managed or unmanaged operation.	https://www.perle.com/products/gigabit-fiber-managed-converter-modules.shtml	Media Converter Module: CM-1000MM
05062430	CM-1000MM-S1SC120D - Managed Gigabit Fiber to Fiber Converter Module: 1000BASE-SX 850nm multimode (SC) [550 m/1804 ft.] to 1000BASE-BX 1490nm TX / 1310nm RX single strand fiber, single mode (SC) [120 km/75 miles]. Managed or unmanaged operation.	https://www.perle.com/products/gigabit-fiber-managed-converter-modules.shtml	Media Converter Module: CM-1000MM
05062440	CM-1000MM-S2SC160 - Managed Gigabit Fiber to Fiber Converter Module: 1000BASE-SX 850nm multimode (SC) [550 m/1804 ft.] to 1000BASE-ZX 1550 nm single mode (SC) [160 km/100 miles]. Managed or unmanaged operation.	https://www.perle.com/products/gigabit-fiber-managed-converter-modules.shtml	Media Converter Module: CM-1000MM
05062450	CM-1000MM-S2LC160 - Managed Gigabit Fiber to Fiber Converter Module: 1000BASE-SX 850nm multimode (LC) [550 m/1804 ft.] to 1000BASE-ZX 1550 nm single mode (LC) [160 km/100 miles]. Managed or unmanaged operation.	https://www.perle.com/products/gigabit-fiber-managed-converter-modules.shtml	Media Converter Module: CM-1000MM
05062460	CM-1000MM-S2ST160 - Managed Gigabit Fiber to Fiber Converter Module: 1000BASE-SX 850nm multimode (ST) [550 m/1804 ft.] to 1000BASE-ZX 1550 nm single mode (ST) [160 km/100 miles]. Managed or unmanaged operation.	https://www.perle.com/products/gigabit-fiber-managed-converter-modules.shtml	Media Converter Module: CM-1000MM
05062470	CM-1000MM-M2SC2 - Managed Gigabit Fiber to Fiber Converter Module: 1000BASE-SX 850nm multimode (SC) [550 m/1804 ft.] to 1000BASE-LX 1310nm Extended multimode (SC) [2km /6562 ft.] Managed or unmanaged operation.	https://www.perle.com/products/gigabit-fiber-managed-converter-modules.shtml	Media Converter Module: CM-1000MM
05062480	CM-1000MM-M2LC2 - Managed Gigabit Fiber to Fiber Converter Module: 1000BASE-SX 850nm multimode (LC) [550 m/1804 ft.] to 1000BASE-LX 1310nm Extended multimode (LC) [2km /6562 ft.] Managed or unmanaged operation.	https://www.perle.com/products/gigabit-fiber-managed-converter-modules.shtml	Media Converter Module: CM-1000MM
05062490	CM-1000MM-M2ST2 - Managed Gigabit Fiber to Fiber Converter Module: 1000BASE-SX 850nm multimode (ST) [550 m/1804 ft.] to 1000BASE-LX 1310nm Extended multimode (ST) [2km /6562 ft.] Managed or unmanaged operation.	https://www.perle.com/products/gigabit-fiber-managed-converter-modules.shtml	Media Converter Module: CM-1000MM
05062500	CM-10G-ST5 - Managed 10 Gigabit Media Converter Module with dual SFP+ slots (empty).	https://www.perle.com/products/media-converters/10-gigabit-managed-media-converter-modules.shtml	Media Converter Module: CM-10G

Part #	Description	Product Datasheet	Product Group
05062510	CM-10G-XTS - Managed 10 Gigabit Media Converter Module with one XFP slot (empty) and one SFP+ slot (empty).	https://www.perle.com/products/media-converters/10-gigabit-managed-media-converter-modules.shtml	Media Converter Module: CM-10G
05062520	CM-10G-XTSH - Managed 10 Gigabit Media Converter Module with one XFP slot (empty) and one SFP+ slot (empty). Supports Power Level 4 XFPs.	https://www.perle.com/products/media-converters/10-gigabit-managed-media-converter-modules.shtml	Media Converter Module: CM-10G
05062530	CM-10G-XTX - Managed 10 Gigabit Media Converter Module with dual XFP slots (empty).	https://www.perle.com/products/media-converters/10-gigabit-managed-media-converter-modules.shtml	Media Converter Module: CM-10G
05062540	CM-10G-XTXH - Managed 10 Gigabit Media Converter Module with dual XFP slots (empty). Supports Power Level 4 XFPs.	https://www.perle.com/products/media-converters/10-gigabit-managed-media-converter-modules.shtml	Media Converter Module: CM-10G
05062560	CM-10GT-XFPH - Managed 10 Gigabit Media Converter Module: 10GBASE-T (RJ-45) [100 m/328 ft.] (CAT6A or better) to fiber 10GBase-X or copper 10GBase-CX4 XFP. XFP slot (empty). Supports Power Level 4 XFPs. Managed or unmanaged operation.	https://www.perle.com/products/media-converters/10gbase-t-managed-media-converter-modules.shtml	Media Converter Module: CM-10G
05062570	CM-4GPT-DSFP - Protocol Transparent Managed Media Converter module with dual SFP slots (empty). Supports two SFPs with identical speeds up to 4.25 Gbps.	https://www.perle.com/products/sfp-to-sfp-managed-media-converter-module.shtml	Media Converter Module: CM-4GPT
05062590	CM-100MM-S1ST20U Managed Fast Ethernet Fiber to Fiber Converter Module: 100BASE-FX 1310nm multimode (ST) [2 km/1.2 miles] to 100Base-BX 1310nm TX / 1550nm RX single strand fiber, single mode (ST) [20 km/12.4 miles]. Managed or unmanaged operation.	https://www.perle.com/products/fast-ethernet-fiber-managed-converter-module.shtml	Media Converter Module: CM-100MM
05062600	CM-100MM-S1ST20D Managed Fast Ethernet Fiber to Fiber Converter Module: 100BASE-FX 1310nm multimode (ST) [2 km/1.2 miles] to 100Base-BX 1550nm TX / 1310nm RX single strand fiber, single mode (ST) [20 km/12.4 miles]. Managed or unmanaged operation.	https://www.perle.com/products/fast-ethernet-fiber-managed-converter-module.shtml	Media Converter Module: CM-100MM
05062610	CM-10GRT-SFP - Managed 10 Gigabit Media and Rate Converter Module: 10/100/1000/2.5G/10GBase-T (RJ-45) [100 m/328 ft.] (CAT6A or better) to SFP+ slot (empty). Managed or unmanaged operation.	https://www.perle.com/products/media-converters/10gbase-t-managed-rate-converter-module.shtml	Media Converter Module: CM-10GR
05062620	CM-10GR-STS - Managed 10 Gigabit Media and Rate Converter Module with dual SFP+ slots (empty).	https://www.perle.com/products/media-converters/10-gigabit-managed-rate-converter-module.shtml	Media Converter Module: CM-10GR

Part #	Description	Product Datasheet	Product Group
05070002	SMI-1000-M2SC05 - Managed Gigabit Media Converter: 1000BASE-T (RJ-45) [100 m/328 ft.] to 1000BASE-SX 850nm multimode (SC) [550 m/1804 ft.] - EU Power Cord	https://www.perle.com/products/gigabit-managed-media-converters.shtml	Media Converter: SMI-1000
05070012	SMI-1000-M2ST05 - Managed Gigabit Media Converter: 1000BASE-T (RJ-45) [100 m/328 ft.] to 1000BASE-SX 850nm multimode (ST) [550 m/1804 ft.] - EU Power Cord	https://www.perle.com/products/gigabit-managed-media-converters.shtml	Media Converter: SMI-1000
05070022	SMI-1000-M2LC05 - Managed Gigabit Media Converter: 1000BASE-T (RJ-45) [100 m/328 ft.] to 1000BASE-SX 850nm multimode (LC) [550 m/1804 ft.] - EU Power Cord	https://www.perle.com/products/gigabit-managed-media-converters.shtml	Media Converter: SMI-1000
05070032	SMI-1000-S2SC10 - Managed Gigabit Media Converter: 1000BASE-T (RJ-45) [100 m/328 ft.] to 1000BASE-LX/LH 1310 nm single mode (SC) [10 km/6.2 miles] or multimode (SC) [550 m/1804 ft.] using the optional mode conditioning cable - EU Power Cord	https://www.perle.com/products/gigabit-managed-media-converters.shtml	Media Converter: SMI-1000
05070042	SMI-1000-S2ST10 - Managed Gigabit Media Converter: 1000BASE-T (RJ-45) [100 m/328 ft.] to 1000BASE-LX/LH 1310 nm single mode (ST) [10 km/6.2 miles] or multimode (ST) [550 m/1804 ft.] using a mode conditioning cable - EU Power Cord	https://www.perle.com/products/gigabit-managed-media-converters.shtml	Media Converter: SMI-1000
05070052	SMI-1000-S2LC10 - Managed Gigabit Media Converter: 1000BASE-T (RJ-45) [100 m/328 ft.] to 1000BASE-LX/LH 1310 nm single mode (LC) [10 km/6.2 miles] or multimode (LC) [550 m/1804 ft.] using a mode conditioning cable - EU Power Cord	https://www.perle.com/products/gigabit-managed-media-converters.shtml	Media Converter: SMI-1000
05070062	SMI-1000-S2SC40 - Managed Gigabit Media Converter: 1000BASE-T (RJ-45) [100 m/328 ft.] to 1000BASE-EX 1310 nm single mode (SC) [40 km/24.9 miles] - EU Power Cord	https://www.perle.com/products/gigabit-managed-media-converters.shtml	Media Converter: SMI-1000
05070072	SMI-1000-S2ST40 - Managed Gigabit Media Converter: 1000BASE-T (RJ-45) [100 m/328 ft.] to 1000BASE-EX 1310 nm single mode (ST) [40 km/24.9 miles] - EU Power Cord	https://www.perle.com/products/gigabit-managed-media-converters.shtml	Media Converter: SMI-1000
05070082	SMI-1000-S2LC40 - Managed Gigabit Media Converter: 1000BASE-T (RJ-45) [100 m/328 ft.] to 1000BASE-EX 1310 nm single mode (LC) [40 km/24.9 miles] - EU Power Cord	https://www.perle.com/products/gigabit-managed-media-converters.shtml	Media Converter: SMI-1000
05070092	SMI-1000-S2SC70 - Managed Gigabit Media Converter: 1000BASE-T (RJ-45) [100 m/328 ft.] to 1000BASE-ZX 1550 nm single mode (SC) [70 km/43.5 miles] - EU Power Cord	https://www.perle.com/products/gigabit-managed-media-converters.shtml	Media Converter: SMI-1000

Part #	Description	Product Datasheet	Product Group
05070102	SMI-1000-S2ST70 - Managed Gigabit Media Converter: 1000BASE-T (RJ-45) [100 m/328 ft.] to 1000BASE-ZX 1550 nm single mode (ST) [70 km/43.5 miles] - EU Power Cord	https://www.perle.com/products/gigabit-managed-media-converters.shtml	Media Converter: SMI-1000
05070112	SMI-1000-S2LC70 - Managed Gigabit Media Converter: 1000BASE-T (RJ-45) [100 m/328 ft.] to 1000BASE-ZX 1550 nm single mode (LC) [70 km/43.5 miles] - EU Power Cord	https://www.perle.com/products/gigabit-managed-media-converters.shtml	Media Converter: SMI-1000
05070122	SMI-1000-S2SC120 - Managed Gigabit Media Converter: 1000BASE-T (RJ-45) [100 m/328 ft.] to 1000BASE-EZX 1550 nm single mode (SC) [120 km/74.6 miles] - EU Power Cord	https://www.perle.com/products/gigabit-managed-media-converters.shtml	Media Converter: SMI-1000
05070132	SMI-1000-S2ST120 - Managed Gigabit Media Converter: 1000BASE-T (RJ-45) [100 m/328 ft.] to 1000BASE-EZX 1550 nm single mode (ST) [120 km/74.6 miles] - EU Power Cord	https://www.perle.com/products/gigabit-managed-media-converters.shtml	Media Converter: SMI-1000
05070142	SMI-1000-S2LC120 - Managed Gigabit Media Converter: 1000BASE-T (RJ-45) [100 m/328 ft.] to 1000BASE-EZX 1550 nm single mode (LC) [120 km/74.6 miles] - EU Power Cord	https://www.perle.com/products/gigabit-managed-media-converters.shtml	Media Converter: SMI-1000
05070152	SMI-1000-S1SC10U - Managed Gigabit Media Converter: 1000BASE-T (RJ-45) [100 m/328 ft.] to 1000BASE-BX 1310nm TX / 1490nm RX single fiber single mode (SC) [10 km/6.2 miles] - EU Power Cord	https://www.perle.com/products/gigabit-managed-media-converters.shtml	Media Converter: SMI-1000
05070162	SMI-1000-S1SC10D - Managed Gigabit Media Converter: 1000BASE-T (RJ-45) [100 m/328 ft.] to 1000BASE-BX 1490nm TX / 1310nm RX single fiber single mode (SC) [10 km/6.2 miles] - EU Power Cord	https://www.perle.com/products/gigabit-managed-media-converters.shtml	Media Converter: SMI-1000
05070172	SMI-1000-SFP - Managed Gigabit Media Converter: 1000BASE-T (RJ-45) [100 m/328 ft.] to 1000BASE-X - SFP slot (empty). Managed or unmanaged operation - EU Power Cord	https://www.perle.com/products/gigabit-sfp-managed-media-converters.shtml	Media Converter: SMI-1000
05070182	SMI-1000-S2SC160 - Managed Gigabit Media Converter: 1000BASE-T (RJ-45) [100 m/328 ft.] to 1000BASE-ZX 1550 nm single mode (SC) [160 km/100 miles] - EU Power Cord	https://www.perle.com/products/gigabit-managed-media-converters.shtml	Media Converter: SMI-1000
05070192	SMI-1000-S2ST160 - Managed Gigabit Media Converter: 1000BASE-T (RJ-45) [100 m/328 ft.] to 1000BASE-ZX 1550 nm single mode (ST) [160 km/100 miles] - EU Power Cord	https://www.perle.com/products/gigabit-managed-media-converters.shtml	Media Converter: SMI-1000
05070202	SMI-1000-S2LC160 - Managed Gigabit Media Converter: 1000BASE-T (RJ-45) [100 m/328 ft.] to 1000BASE-ZX 1550 nm single mode (LC) [160 km/100 miles] - EU Power Cord	https://www.perle.com/products/gigabit-managed-media-converters.shtml	Media Converter: SMI-1000

Part #	Description	Product Datasheet	Product Group
05070212	SMI-1000-S1SC20U - Managed Gigabit Media Converter: 1000BASE-T (RJ-45) [100 m/328 ft.] to 1000BASE-BX 1310nm TX / 1490nm RX single fiber single mode (SC) [20 km/12.4 miles] - EU Power Cord	https://www.perle.com/products/gigabit-managed-media-converters.shtml	Media Converter: SMI-1000
05070222	SMI-1000-S1SC20D - Managed Gigabit Media Converter: 1000BASE-T (RJ-45) [100 m/328 ft.] to 1000BASE-BX 1490nm TX / 1310nm RX single fiber single mode (SC) [20 km/12.4 miles] - EU Power Cord	https://www.perle.com/products/gigabit-managed-media-converters.shtml	Media Converter: SMI-1000
05070232	SMI-1000-S1SC40U - Managed Gigabit Media Converter: 1000BASE-T (RJ-45) [100 m/328 ft.] to 1000BASE-BX 1310nm TX / 1490nm RX single fiber single mode (SC) [40 km/25 miles] - EU Power Cord	https://www.perle.com/products/gigabit-managed-media-converters.shtml	Media Converter: SMI-1000
05070242	SMI-1000-S1SC40D - Managed Gigabit Media Converter: 1000BASE-T (RJ-45) [100 m/328 ft.] to 1000BASE-BX 1490nm TX / 1310nm RX single fiber single mode (SC) [40 km/25 miles] - EU Power Cord	https://www.perle.com/products/gigabit-managed-media-converters.shtml	Media Converter: SMI-1000
05070252	SMI-1000-S1SC80U - Managed Gigabit Media Converter: 1000BASE-T (RJ-45) [100 m/328 ft.] to 1000BASE-BX 1510nm TX / 1590nm RX single fiber single mode (SC) [80 km/50 miles] - EU Power Cord	https://www.perle.com/products/gigabit-managed-media-converters.shtml	Media Converter: SMI-1000
05070262	SMI-1000-S1SC80D - Managed Gigabit Media Converter: 1000BASE-T (RJ-45) [100 m/328 ft.] to 1000BASE-BX 1590nm TX / 1510nm RX single fiber single mode (SC) [80 km/50miles] - EU Power Cord	https://www.perle.com/products/gigabit-managed-media-converters.shtml	Media Converter: SMI-1000
05070272	SMI-1000-S1SC120U - Managed Gigabit Media Converter: 1000BASE-T (RJ-45) [100 m/328 ft.] to 1000BASE-BX 1510nm TX / 1590nm RX single fiber single mode (SC) [120 km/75 miles] - EU Power Cord	https://www.perle.com/products/gigabit-managed-media-converters.shtml	Media Converter: SMI-1000
05070282	SMI-1000-S1SC120D - Managed Gigabit Media Converter: 1000BASE-T (RJ-45) [100 m/328 ft.] to 1000BASE-BX 1590nm TX / 1510nm RX single fiber single mode (SC) [120 km/75miles] - EU Power Cord	https://www.perle.com/products/gigabit-managed-media-converters.shtml	Media Converter: SMI-1000
05070302	SMI-100-M2C2 - Managed Fast Ethernet Media Converter.100BASE-TX (RJ-45) [100 m/328 ft.] to 100BASE-FX 1310nm multimode (SC) [2 km/1.2 miles] - EU Power Cord	https://www.perle.com/products/fast-ethernet-managed-media-converters.shtml	Media Converter: SMI-100
05070312	SMI-100-M2ST2 - Managed Fast Ethernet Media Converter: 100BASE-TX (RJ-45) [100 m/328 ft.] to 100BASE-FX 1310nm multimode (ST) [2 km/1.2 miles] - EU Power Cord	https://www.perle.com/products/fast-ethernet-managed-media-converters.shtml	Media Converter: SMI-100
05070322	SMI-100-M2LC2 - Managed Fast Ethernet Media Converter: 100BASE-TX (RJ-45) [100 m/328 ft.] to 100BASE-FX 1310nm multimode (LC) [2 km/1.2 miles] - EU Power Cord	https://www.perle.com/products/fast-ethernet-managed-media-converters.shtml	Media Converter: SMI-100

Part #	Description	Product Datasheet	Product Group
05070332	SMI-100-S2SC20 - Managed Fast Ethernet Media Converter: 100BASE-TX (RJ-45) [100 m/328 ft.] to 100BASE-LX 1310nm single mode (SC) [20 km/12.4 miles] - EU Power Cord	https://www.perle.com/products/fast-ethernet-managed-media-converters.shtml	Media Converter: SMI-100
05070342	SMI-100-S2ST20 - Managed Fast Ethernet Media Converter: 100BASE-TX (RJ-45) [100 m/328 ft.] to 100BASE-LX 1310nm single mode (ST) [20 km/12.4 miles] - EU Power Cord	https://www.perle.com/products/fast-ethernet-managed-media-converters.shtml	Media Converter: SMI-100
05070352	SMI-100-S2LC20 - Managed Fast Ethernet Media Converter: 100BASE-TX (RJ-45) [100 m/328 ft.] to 100BASE-LX 1310nm single mode (LC) [20 km/12.4 miles] - EU Power Cord	https://www.perle.com/products/fast-ethernet-managed-media-converters.shtml	Media Converter: SMI-100
05070362	SMI-100-S2SC40 - Managed Fast Ethernet Media Converter: 100BASE-TX (RJ-45) [100 m/328 ft.] to 100BASE-EX 1310nm single mode (SC) [40 km/24.9 miles] - EU Power Cord	https://www.perle.com/products/fast-ethernet-managed-media-converters.shtml	Media Converter: SMI-100
05070372	SMI-100-S2ST40 - Managed Fast Ethernet Media Converter: 100BASE-TX (RJ-45) [100 m/328 ft.] to 100BASE-EX 1310nm single mode (ST) [40 km/24.9 miles] - EU Power Cord	https://www.perle.com/products/fast-ethernet-managed-media-converters.shtml	Media Converter: SMI-100
05070382	SMI-100-S2LC40 - Managed Fast Ethernet Media Converter: 100BASE-TX (RJ-45) [100 m/328 ft.] to 100BASE-EX 1310nm single mode (LC) [40 km/24.9 miles] - EU Power Cord	https://www.perle.com/products/fast-ethernet-managed-media-converters.shtml	Media Converter: SMI-100
05070392	SMI-100-S2SC80 - Managed Fast Ethernet Media Converter: 100BASE-TX (RJ-45) [100 m/328 ft.] to 100BASE-ZX 1550nm single mode (SC) [80 km/49.7 miles] - EU Power Cord	https://www.perle.com/products/fast-ethernet-managed-media-converters.shtml	Media Converter: SMI-100
05070402	SMI-100-S2ST80 - Managed Fast Ethernet Media Converter: 100BASE-TX (RJ-45) [100 m/328 ft.] to 100BASE-ZX 1550nm single mode (ST) [80 km/49.7 miles] - EU Power Cord	https://www.perle.com/products/fast-ethernet-managed-media-converters.shtml	Media Converter: SMI-100
05070412	SMI-100-S2LC80 - Managed Fast Ethernet Media Converter: 100BASE-TX (RJ-45) [100 m/328 ft.] to 100BASE-ZX 1550nm single mode (LC) [80 km/49.7 miles] - EU Power Cord	https://www.perle.com/products/fast-ethernet-managed-media-converters.shtml	Media Converter: SMI-100
05070422	SMI-100-S2SC120 - Managed Fast Ethernet Media Converter: 100BASE-TX (RJ-45) [100 m/328 ft.] to 100BASE-ZX 1550nm single mode (SC) [120 km/74.6 miles] - EU Power Cord	https://www.perle.com/products/fast-ethernet-managed-media-converters.shtml	Media Converter: SMI-100
05070432	SMI-100-S2ST120 - Managed Fast Ethernet Media Converter: 100BASE-TX (RJ-45) [100 m/328 ft.] to 100BASE-ZX 1550nm single mode (ST) [120 km/74.6 miles] - EU Power Cord	https://www.perle.com/products/fast-ethernet-managed-media-converters.shtml	Media Converter: SMI-100

Part #	Description	Product Datasheet	Product Group
05070442	SMI-100-S2LC120 - Managed Fast Ethernet Media Converter: 100BASE-TX (RJ-45) [100 m/328 ft.] to 100BASE-ZX 1550nm single mode (LC) [120 km/74.6 miles] - EU Power Cord	https://www.perle.com/products/fast-ethernet-managed-media-converters.shtml	Media Converter: SMI-100
05070452	SMI-100-S1SC20U - Managed Fast Ethernet Media Converter: 100BASE-BX 1310nm TX / 1550nm RX single fiber single mode (SC) [20 km/12.4 miles] - EU Power Cord	https://www.perle.com/products/fast-ethernet-managed-media-converters.shtml	Media Converter: SMI-100
05070462	SMI-100-S1SC20D - Managed Fast Ethernet Media Converter: 100BASE-BX 1550nm TX / 1310nm RX single fiber single mode (SC) [20 km/12.4 miles] - EU Power Cord	https://www.perle.com/products/fast-ethernet-managed-media-converters.shtml	Media Converter: SMI-100
05070472	SMI-100-S1SC40U - Managed Fast Ethernet Media Converter: 100BASE-BX 1310nm TX / 1550nm RX single fiber single mode (SC) [40 km/24.9 miles] - EU Power Cord	https://www.perle.com/products/fast-ethernet-managed-media-converters.shtml	Media Converter: SMI-100
05070482	SMI-100-S1SC40D - Managed Fast Ethernet Media Converter: 100BASE-BX 1550nm TX / 1310nm RX single fiber single mode (SC) [40 km/24.9 miles] - EU Power Cord	https://www.perle.com/products/fast-ethernet-managed-media-converters.shtml	Media Converter: SMI-100
05070492	SMI-1000-M2SC2 - Managed Gigabit Media Converter: 1000BASE-T (RJ-45) [100 m/328 ft.] to 1000BASE-LX 1310nm Extended multimode (SC) [2km /6562 ft.] - EU Power Cord	https://www.perle.com/products/gigabit-managed-media-converters.shtml	Media Converter: SMI-1000
05070502	SMI-1000-M2ST2 - Managed Gigabit Media Converter: 1000BASE-T (RJ-45) [100 m/328 ft.] to 1000BASE-LX 1310nm Extended multimode (ST) [2km /6562 ft.] - EU Power Cord	https://www.perle.com/products/gigabit-managed-media-converters.shtml	Media Converter: SMI-1000
05070512	SMI-1000-M2LC2 - Managed Gigabit Media Converter: 1000BASE-T (RJ-45) [100 m/328 ft.] to 1000BASE-LX 1310nm Extended multimode (LC) [2km /6562 ft.] - EU Power Cord	https://www.perle.com/products/gigabit-managed-media-converters.shtml	Media Converter: SMI-1000
05070522	SMI-1110-M2SC2 - Managed 10/100/1000Base-T Media and Rate Converter: 10/100/1000BASE-T (RJ-45) [100 m/328 ft.] to 1000BASE-LX 1310nm Extended multimode (SC) [2km /6562 ft.] - EU Power Cord	https://www.perle.com/products/10-100-1000-managed-media-converters.shtml	Media Converter: SMI-1110
05070532	SMI-1110-M2ST2 - Managed 10/100/1000Base-T Media and Rate Converter: 10/100/1000BASE-T (RJ-45) [100 m/328 ft.] to 1000BASE-LX 1310nm Extended multimode (ST) [2km /6562 ft.] - EU Power Cord	https://www.perle.com/products/10-100-1000-managed-media-converters.shtml	Media Converter: SMI-1110
05070542	SMI-1110-M2LC2 - Managed 10/100/1000Base-T Media and Rate Converter: 10/100/1000BASE-T (RJ-45) [100 m/328 ft.] to 1000BASE-LX 1310nm Extended multimode (LC) [2km /6562 ft.] - EU Power Cord	https://www.perle.com/products/10-100-1000-managed-media-converters.shtml	Media Converter: SMI-1110

Part #	Description	Product Datasheet	Product Group
05070602	SMI-1110-M2SC05 - Managed 10/100/1000Base-T Media and Rate Converter: 10/100/1000BASE-T (RJ-45) [100 m/328 ft.] to 1000BASE-SX 850nm multimode (SC) [550 m/1804 ft.] - EU Power Cord	https://www.perle.com/products/10-100-1000-managed-media-converters.shtml	Media Converter: SMI-1110
05070612	SMI-1110-M2ST05 - Managed 10/100/1000Base-T Media and Rate Converter: 10/100/1000BASE-T (RJ-45) [100 m/328 ft.] to 1000BASE-SX 850nm multimode (ST) [550 m/1804 ft.] - EU Power Cord	https://www.perle.com/products/10-100-1000-managed-media-converters.shtml	Media Converter: SMI-1110
05070622	SMI-1110-M2LC05 - Managed 10/100/1000Base-T Media and Rate Converter: 10/100/1000BASE-T (RJ-45) [100 m/328 ft.] to 1000BASE-SX 850nm multimode (LC) [550 m/1804 ft.] - EU Power Cord	https://www.perle.com/products/10-100-1000-managed-media-converters.shtml	Media Converter: SMI-1110
05070632	SMI-1110-S2SC10 - Managed 10/100/1000Base-T Media and Rate Converter: 10/100/1000BASE-T (RJ-45) [100 m/328 ft.] to 1000BASE-LX/LH 1310 nm single mode (SC) [10 km/6.2 miles] or multimode (SC) [550 m/1804 ft.] using the optional mode conditioning cable - EU Power Cord	https://www.perle.com/products/10-100-1000-managed-media-converters.shtml	Media Converter: SMI-1110
05070642	SMI-1110-S2ST10 - Managed 10/100/1000Base-T Media and Rate Converter: 10/100/1000BASE-T (RJ-45) [100 m/328 ft.] to 1000BASE-LX/LH 1310 nm single mode (ST) [10 km/6.2 miles] or multimode (ST) [550 m/1804 ft.] using a mode conditioning cable - EU Power Cord	https://www.perle.com/products/10-100-1000-managed-media-converters.shtml	Media Converter: SMI-1110
05070652	SMI-1110-S2LC10 - Managed 10/100/1000Base-T Media and Rate Converter: 10/100/1000BASE-T (RJ-45) [100 m/328 ft.] to 1000BASE-LX/LH 1310 nm single mode (LC) [10 km/6.2 miles] or multimode (LC) [550 m/1804 ft.] using a mode conditioning cable - EU Power Cord	https://www.perle.com/products/10-100-1000-managed-media-converters.shtml	Media Converter: SMI-1110
05070662	SMI-1110-S2SC40 - Managed 10/100/1000Base-T Media and Rate Converter: 10/100/1000BASE-T (RJ-45) [100 m/328 ft.] to 1000BASE-EX 1310 nm single mode (SC) [40 km/24.9 miles] - EU Power Cord	https://www.perle.com/products/10-100-1000-managed-media-converters.shtml	Media Converter: SMI-1110
05070672	SMI-1110-S2ST40 - Managed 10/100/1000Base-T Media and Rate Converter: 10/100/1000BASE-T (RJ-45) [100 m/328 ft.] to 1000BASE-EX 1310 nm single mode (ST) [40 km/24.9 miles] - EU Power Cord	https://www.perle.com/products/10-100-1000-managed-media-converters.shtml	Media Converter: SMI-1110
05070682	SMI-1110-S2LC40 - Managed 10/100/1000Base-T Media and Rate Converter: 10/100/1000BASE-T (RJ-45) [100 m/328 ft.] to 1000BASE-EX 1310 nm single mode (LC) [40 km/24.9 miles] - EU Power Cord	https://www.perle.com/products/10-100-1000-managed-media-converters.shtml	Media Converter: SMI-1110
05070692	SMI-1110-S2SC70 - Managed 10/100/1000Base-T Media and Rate Converter: 10/100/1000BASE-T (RJ-45) [100 m/328 ft.] to 1000BASE-ZX 1550 nm single mode (SC) [70 km/43.5 miles] - EU Power Cord	https://www.perle.com/products/10-100-1000-managed-media-converters.shtml	Media Converter: SMI-1110

Part #	Description	Product Datasheet	Product Group
05070702	SMI-1110-S2ST70 - Managed 10/100/1000Base-T Media and Rate Converter: 10/100/1000BASE-T (RJ-45) [100 m/328 ft.] to 1000BASE-ZX 1550 nm single mode (ST) [70 km/43.5 miles] - EU Power Cord	https://www.perle.com/products/10-100-1000-managed-media-converters.shtml	Media Converter: SMI-1110
05070712	SMI-1110-S2LC70 - Managed 10/100/1000Base-T Media and Rate Converter: 10/100/1000BASE-T (RJ-45) [100 m/328 ft.] to 1000BASE-ZX 1550 nm single mode (LC) [70 km/43.5 miles] - EU Power Cord	https://www.perle.com/products/10-100-1000-managed-media-converters.shtml	Media Converter: SMI-1110
05070722	SMI-1110-S2SC120 - Managed 10/100/1000Base-T Media and Rate Converter: 10/100/1000BASE-T (RJ-45) [100 m/328 ft.] to 1000BASE-EZX 1550 nm single mode (SC) [120 km/74.6 miles] - EU Power Cord	https://www.perle.com/products/10-100-1000-managed-media-converters.shtml	Media Converter: SMI-1110
05070732	SMI-1110-S2ST120 - Managed 10/100/1000Base-T Media and Rate Converter: 10/100/1000BASE-T (RJ-45) [100 m/328 ft.] to 1000BASE-EZX 1550 nm single mode (ST) [120 km/74.6 miles] - EU Power Cord	https://www.perle.com/products/10-100-1000-managed-media-converters.shtml	Media Converter: SMI-1110
05070742	SMI-1110-S2LC120 - Managed 10/100/1000Base-T Media and Rate Converter: 10/100/1000BASE-T (RJ-45) [100 m/328 ft.] to 1000BASE-EZX 1550 nm single mode (LC) [120 km/74.6 miles] - EU Power Cord	https://www.perle.com/products/10-100-1000-managed-media-converters.shtml	Media Converter: SMI-1110
05070752	SMI-1110-S1SC10U - Managed 10/100/1000Base-T Media and Rate Converter: 10/100/1000BASE-T (RJ-45) [100 m/328 ft.] to 1000BASE-BX 1310nm TX / 1490nm RX single fiber single mode (SC) [10 km/6.2 miles] - EU Power Cord	https://www.perle.com/products/10-100-1000-managed-media-converters.shtml	Media Converter: SMI-1110
05070762	SMI-1110-S1SC10D - Managed 10/100/1000Base-T Media and Rate Converter: 10/100/1000BASE-T (RJ-45) [100 m/328 ft.] to 1000BASE-BX 1490nm TX / 1310nm RX single fiber single mode (SC) [10 km/6.2 miles] - EU Power Cord	https://www.perle.com/products/10-100-1000-managed-media-converters.shtml	Media Converter: SMI-1110
05070772	SMI-1110-SFP - Managed 10/100/1000Base-T Media and Rate Converter: 10/100/1000BASE-T (RJ-45) [100 m/328 ft.] to 1000BASE-X - SFP slot (empty). - EU Power Cord	https://www.perle.com/products/10-100-1000-sfp-managed-media-converters.shtml	Media Converter: SMI-1110
05070782	SMI-1110-S2SC160 - Managed 10/100/1000Base-T Media and Rate Converter: 10/100/1000BASE-T (RJ-45) [100 m/328 ft.] to 1000BASE-ZX 1550 nm single mode (SC) [160 km/100 miles] - EU Power Cord	https://www.perle.com/products/10-100-1000-managed-media-converters.shtml	Media Converter: SMI-1110
05070792	SMI-1110-S2LC160 - Managed 10/100/1000Base-T Media and Rate Converter: 10/100/1000BASE-T (RJ-45) [100 m/328 ft.] to 1000BASE-ZX 1550 nm single mode (LC) [160 km/100 miles] - EU Power Cord	https://www.perle.com/products/10-100-1000-managed-media-converters.shtml	Media Converter: SMI-1110
05070802	SMI-1110-S2ST160 - Managed 10/100/1000Base-T Media and Rate Converter: 10/100/1000BASE-T (RJ-45) [100 m/328 ft.] to 1000BASE-ZX 1550 nm single mode (ST) [160 km/100 miles] - EU Power Cord	https://www.perle.com/products/10-100-1000-managed-media-converters.shtml	Media Converter: SMI-1110

Part #	Description	Product Datasheet	Product Group
05070812	SMI-1110-S1SC20U - Managed 10/100/1000Base-T Media and Rate Converter: 10/100/1000BASE-T (RJ-45) [100 m/328 ft.] to 1000BASE-BX 1310nm TX / 1490nm RX single fiber single mode (SC) [20 km/12.4 miles] - EU Power Cord	https://www.perle.com/products/10-100-1000-managed-media-converters.shtml	Media Converter: SMI-1110
05070822	SMI-1110-S1SC20D - Managed 10/100/1000Base-T Media and Rate Converter: 10/100/1000BASE-T (RJ-45) [100 m/328 ft.] to 1000BASE-BX 1490nm TX / 1310nm RX single fiber single mode (SC) [20 km/12.4 miles] - EU Power Cord	https://www.perle.com/products/10-100-1000-managed-media-converters.shtml	Media Converter: SMI-1110
05070832	SMI-1110-S1SC40U - Managed 10/100/1000Base-T Media and Rate Converter: 10/100/1000BASE-T (RJ-45) [100 m/328 ft.] to 1000BASE-BX 1310nm TX / 1490nm RX single fiber single mode (SC) [40 km/25 miles] - EU Power Cord	https://www.perle.com/products/10-100-1000-managed-media-converters.shtml	Media Converter: SMI-1110
05070842	SMI-1110-S1SC40D - Managed 10/100/1000Base-T Media and Rate Converter: 10/100/1000BASE-T (RJ-45) [100 m/328 ft.] to 1000BASE-BX 1490nm TX / 1310nm RX single fiber single mode (SC) [40 km/25 miles] - EU Power Cord	https://www.perle.com/products/10-100-1000-managed-media-converters.shtml	Media Converter: SMI-1110
05070852	SMI-1110-S1SC80U - Managed 10/100/1000Base-T Media and Rate Converter: 10/100/1000BASE-T (RJ-45) [100 m/328 ft.] to 1000BASE-BX 1510nm TX / 1590nm RX single fiber single mode (SC) [80 km/50 miles] - EU Power Cord	https://www.perle.com/products/10-100-1000-managed-media-converters.shtml	Media Converter: SMI-1110
05070862	SMI-1110-S1SC80D - Managed 10/100/1000Base-T Media and Rate Converter: 10/100/1000BASE-T (RJ-45) [100 m/328 ft.] to 1000BASE-BX 1590nm TX / 1510nm RX single fiber single mode (SC) [80 km/50 miles] - EU Power Cord	https://www.perle.com/products/10-100-1000-managed-media-converters.shtml	Media Converter: SMI-1110
05070872	SMI-1110-S1SC120U - Managed 10/100/1000Base-T Media and Rate Converter: 10/100/1000BASE-T (RJ-45) [100 m/328 ft.] to 1000BASE-BX 1510nm TX / 1590nm RX single fiber single mode (SC) [120 km/75 miles] - EU Power Cord	https://www.perle.com/products/10-100-1000-managed-media-converters.shtml	Media Converter: SMI-1110
05070882	SMI-1110-S1SC120D - Managed 10/100/1000Base-T Media and Rate Converter: 10/100/1000BASE-T (RJ-45) [100 m/328 ft.] to 1000BASE-BX 1590nm TX / 1510nm RX single fiber single mode (SC) [120 km/75 miles] - EU Power Cord	https://www.perle.com/products/10-100-1000-managed-media-converters.shtml	Media Converter: SMI-1110
05070902	SMI-110-M2C2 - Managed 10/100Base-TX Media and Rate Converter. 10/100BASE-TX (RJ-45) [100 m/328 ft.] to 100BASE-FX 1310nm multimode (SC) [2 km/1.2 miles] - EU Power Cord	https://www.perle.com/products/10-100-managed-media-converters.shtml	Media Converter: SMI-110

Part #	Description	Product Datasheet	Product Group
05070912	SMI-110-M2ST2 - Managed 10/100Base-TX Media and Rate Converter: 10/100BASE-TX (RJ-45) [100 m/328 ft.] to 100BASE-FX 1310nm multimode (ST) [2 km/1.2 miles] - EU Power Cord	https://www.perle.com/products/10-100-managed-media-converters.shtml	Media Converter: SMI-110
05070922	SMI-110-M2LC2 - Managed 10/100Base-TX Media and Rate Converter: 10/100BASE-TX (RJ-45) [100 m/328 ft.] to 100BASE-FX 1310nm multimode (LC) [2 km/1.2 miles] - EU Power Cord	https://www.perle.com/products/10-100-managed-media-converters.shtml	Media Converter: SMI-110
05070932	SMI-110-S2SC20 - Managed 10/100Base-TX Media and Rate Converter: 10/100BASE-TX (RJ-45) [100 m/328 ft.] to 100BASE-FX 1310nm single mode (SC) [20 km/12.4 miles] - EU Power Cord	https://www.perle.com/products/10-100-managed-media-converters.shtml	Media Converter: SMI-110
05070942	SMI-110-S2ST20 - Managed 10/100Base-TX Media and Rate Converter: 10/100BASE-TX (RJ-45) [100 m/328 ft.] to 100BASE-LX 1310nm single mode (ST) [20 km/12.4 miles] - EU Power Cord	https://www.perle.com/products/10-100-managed-media-converters.shtml	Media Converter: SMI-110
05070952	SMI-110-S2LC20 - Managed 10/100Base-TX Media and Rate Converter: 10/100BASE-TX (RJ-45) [100 m/328 ft.] to 100BASE-LX 1310nm single mode (LC) [20 km/12.4 miles] - EU Power Cord	https://www.perle.com/products/10-100-managed-media-converters.shtml	Media Converter: SMI-110
05070962	SMI-110-S2SC40 - Managed 10/100Base-TX Media and Rate Converter: 10/100BASE-TX (RJ-45) [100 m/328 ft.] to 100BASE-EX 1310nm single mode (SC) [40 km/24.9 miles] - EU Power Cord	https://www.perle.com/products/10-100-managed-media-converters.shtml	Media Converter: SMI-110
05070972	SMI-110-S2ST40 - Managed 10/100Base-TX Media and Rate Converter: 10/100BASE-TX (RJ-45) [100 m/328 ft.] to 100BASE-EX 1310nm single mode (ST) [40 km/24.9 miles] - EU Power Cord	https://www.perle.com/products/10-100-managed-media-converters.shtml	Media Converter: SMI-110
05070982	SMI-110-S2LC40 - Managed 10/100Base-TX Media and Rate Converter: 10/100BASE-TX (RJ-45) [100 m/328 ft.] to 100BASE-EX 1310nm single mode (LC) [40 km/24.9 miles] - EU Power Cord	https://www.perle.com/products/10-100-managed-media-converters.shtml	Media Converter: SMI-110
05070992	SMI-110-S2SC80 - Managed 10/100Base-TX Media and Rate Converter: 10/100BASE-TX (RJ-45) [100 m/328 ft.] to 100BASE-ZX 1550nm single mode (SC) [80 km/49.7 miles] - EU Power Cord	https://www.perle.com/products/10-100-managed-media-converters.shtml	Media Converter: SMI-110
05071002	SMI-110-S2ST80 - Managed 10/100Base-TX Media and Rate Converter: 10/100BASE-TX (RJ-45) [100 m/328 ft.] to 100BASE-ZX 1550nm single mode (ST) [80 km/49.7 miles] - EU Power Cord	https://www.perle.com/products/10-100-managed-media-converters.shtml	Media Converter: SMI-110
05071012	SMI-110-S2LC80 - Managed 10/100Base-TX Media and Rate Converter: 10/100BASE-TX (RJ-45) [100 m/328 ft.] to 100BASE-ZX 1550nm single mode (LC) [80 km/49.7 miles] - EU Power Cord	https://www.perle.com/products/10-100-managed-media-converters.shtml	Media Converter: SMI-110

Part #	Description	Product Datasheet	Product Group
05071022	SMI-110-S2SC120 - Managed 10/100Base-TX Media and Rate Converter: 10/100BASE-TX (RJ-45) [100 m/328 ft.] to 100BASE-ZX 1550nm single mode (SC) [120 km/74.6 miles] - EU Power Cord	https://www.perle.com/products/10-100-managed-media-converters.shtml	Media Converter: SMI-110
05071032	SMI-110-S2ST120 - Managed 10/100Base-TX Media and Rate Converter: 10/100BASE-TX (RJ-45) [100 m/328 ft.] to 100BASE-ZX 1550nm single mode (ST) [120 km/74.6 miles] - EU Power Cord	https://www.perle.com/products/10-100-managed-media-converters.shtml	Media Converter: SMI-110
05071042	SMI-110-S2LC120 - Managed 10/100Base-TX Media and Rate Converter: 10/100BASE-TX (RJ-45) [100 m/328 ft.] to 100BASE-ZX 1550nm single mode (LC) [120 km/74.6 miles] - EU Power Cord	https://www.perle.com/products/10-100-managed-media-converters.shtml	Media Converter: SMI-110
05071052	SMI-110-S1SC20U - Managed 10/100Base-TX Media and Rate Converter: 10/100BASE-TX (RJ-45) [100 m/328 ft.] to 100BASE-BX 1310nm TX / 1550nm RX single fiber single mode (SC) [20 km/12.4 miles] - EU Power Cord	https://www.perle.com/products/10-100-managed-media-converters.shtml	Media Converter: SMI-110
05071062	SMI-110-S1SC20D - Managed 10/100Base-TX Media and Rate Converter: 10/100BASE-TX (RJ-45) [100 m/328 ft.] to 100BASE-BX 1550nm TX / 1310nm RX single fiber single mode (SC) [20 km/12.4 miles] - EU Power Cord	https://www.perle.com/products/10-100-managed-media-converters.shtml	Media Converter: SMI-110
05071072	SMI-110-S1SC40U - Managed 10/100Base-TX Media and Rate Converter: 10/100BASE-TX (RJ-45) [100 m/328 ft.] to 100BASE-BX 1310nm TX / 1550nm RX single fiber single mode (SC) [40 km/24.9 miles] - EU Power Cord	https://www.perle.com/products/10-100-managed-media-converters.shtml	Media Converter: SMI-110
05071082	SMI-110-S1SC40D - Managed 10/100Base-TX Media and Rate Converter: 10/100BASE-TX (RJ-45) [100 m/328 ft.] to 100BASE-BX 1550nm TX / 1310nm RX single fiber single mode (SC) [40 km/24.9 miles] - EU Power Cord	https://www.perle.com/products/10-100-managed-media-converters.shtml	Media Converter: SMI-110
05071102	SMI-10G-STs - Managed 10 Gigabit Media Converter with dual SFP+ slots (empty). Includes AC power Adapter - EU Power Cord	https://www.perle.com/products/media-converters/10-gigabit-managed-media-converters.shtml	Media Converter: SMI-10G
05071112	SMI-10G-XTs - Managed 10 Gigabit Media Converter with one XFP slot (empty) and one SFP+ slot (empty). AC adapter included - EU Power Cord	https://www.perle.com/products/media-converters/10-gigabit-managed-media-converters.shtml	Media Converter: SMI-10G
05071122	SMI-10G-XTSH - Managed 10 Gigabit Media Converter with one XFP slot (empty) and one SFP+ slot (empty). Supports Power Level 4 XFPs. AC adapter included - EU Power Cord	https://www.perle.com/products/media-converters/10-gigabit-managed-media-converters.shtml	Media Converter: SMI-10G

Part #	Description	Product Datasheet	Product Group
05071142	SMI-10GT-XFPH - Managed 10 Gigabit Media Converter: 10GBASE-T (RJ-45) [100 m/328 ft.] (CAT6A or better) to fiber 10GBase-X or copper 10GBase-CX4 XFP. XFP slot (empty). Supports Power Level 4 XFPs. AC Adapter included - EU Power Cord	https://www.perle.com/products/media-converters/10gbase-t-managed-media-converters.shtml	Media Converter: SMI-10G
05071152	SMI-4GPT-DSFP - Managed Protocol Transparent Media Converter with dual SFP slots (empty). Supports two SFPs with identical speeds up to 4.25 Gbps. AC adapter included - EU Power Cord	https://www.perle.com/products/sfp-to-sfp-managed-media-converter.shtml	Media Converter: SMI-4GPT
05071172	SMI-10G-XTX - Managed 10 Gigabit Media Converter with dual XFP slots (empty). AC adapter included - EU Power Cord	https://www.perle.com/products/media-converters/10-gigabit-managed-media-converters.shtml	Media Converter: SMI-10G
05071182	SMI-10G-XTXH - Managed 10 Gigabit Media Converter with dual XFP slots (empty). Support Power Level 4 XFPs. AC adapter included - EU Power Cord	https://www.perle.com/products/media-converters/10-gigabit-managed-media-converters.shtml	Media Converter: SMI-10G
05071192	SMI-100-M1SC2U - Managed Fast Ethernet Media Converter: 100BASE-TX (RJ-45) [100 m/328 ft.] to 100BASE-BX 1310nm TX / 1550nm RX single fiber multimode (SC) [2 km/1.2 miles] - EU Power Cord	https://www.perle.com/products/fast-ethernet-managed-media-converters.shtml	Media Converter: SMI-100
05071202	SMI-100-M1SC2D - Managed Fast Ethernet Media Converter: 100BASE-TX (RJ-45) [100 m/328 ft.] to 100BASE-BX 1550nm TX / 1310nm RX single fiber multimode (SC) [2 km/1.2 miles] - EU Power Cord	https://www.perle.com/products/fast-ethernet-managed-media-converters.shtml	Media Converter: SMI-100
05071212	SMI-110-M1SC2U - Managed 10/100Base-TX Media and Rate Converter: 10/100BASE-TX (RJ-45) [100 m/328 ft.] to 100BASE-BX 1310nm TX / 1550nm RX single fiber multimode (SC) [2 km/1.2 miles] - EU Power Cord	https://www.perle.com/products/10-100-managed-media-converters.shtml	Media Converter: SMI-110
05071222	SMI-110-M1SC2D - Managed 10/100Base-TX Media and Rate Converter: 10/100BASE-TX (RJ-45) [100 m/328 ft.] to 100BASE-BX 1550nm TX / 1310nm RX single fiber multimode (SC) [2 km/1.2 miles] - EU Power Cord	https://www.perle.com/products/10-100-managed-media-converters.shtml	Media Converter: SMI-110
05071232	SMI-1000-M1SC05U - Managed Gigabit Media Converter: 1000BASE-T (RJ-45) [100 m/328 ft.] to 1000BASE-BX 1310nm TX / 1550nm RX single fiber multimode (SC) [500 m/1640 ft] - EU Power Cord	https://www.perle.com/products/gigabit-managed-media-converters.shtml	Media Converter: SMI-1000
05071242	SMI-1000-M1SC05D - Managed Gigabit Media Converter: 1000BASE-T (RJ-45) [100 m/328 ft.] to 1000BASE-BX 1550nm TX / 1310nm RX single fiber multimode (SC) [500 m/1640 ft] - EU Power Cord	https://www.perle.com/products/gigabit-managed-media-converters.shtml	Media Converter: SMI-1000
05071252	SMI-1110-M1SC05U - Managed 10/100/1000Base-T Media and Rate Converter: 10/100/1000BASE-T (RJ-45) [100 m/328 ft.] to 1000BASE-BX 1310nm TX / 1550nm RX single fiber multimode (SC) [500 m/1640 ft] - EU Power Cord	https://www.perle.com/products/10-100-1000-managed-media-converters.shtml	Media Converter: SMI-1110

Part #	Description	Product Datasheet	Product Group
05071262	SMI-1110-M1SC05D - Managed 10/100/1000Base-T Media and Rate Converter: 10/100/1000BASE-T (RJ-45) [100 m/328 ft.] to 1000BASE-BX 1550nm TX / 1310nm RX single fiber multimode (SC) [500 m/1640 ft] - EU Power Cord	https://www.perle.com/products/10-100-1000-managed-media-converters.shtml	Media Converter: SMI-1110
05071272	SMI-100-S1ST20U - Managed Fast Ethernet Media Converter: 100BASE-TX (RJ-45) [100 m/328 ft.] to 100BASE-BX 1310nm TX / 1550nm RX single fiber single mode (ST) [20 km/12.4 miles] - EU Power Cord	https://www.perle.com/products/fast-ethernet-managed-media-converters.shtml	Media Converter: SMI-100
05071282	SMI-100-S1ST20D - Managed Fast Ethernet Media Converter: 100BASE-TX (RJ-45) [100 m/328 ft.] to 100BASE-BX 1550nm TX / 1310nm RX single fiber single mode (ST) [20 km/12.4 miles] - EU Power Cord	https://www.perle.com/products/fast-ethernet-managed-media-converters.shtml	Media Converter: SMI-100
05071292	SMI-100-M1ST2U - Managed Fast Ethernet Media Converter: 100BASE-TX (RJ-45) [100 m/328 ft.] to 100BASE-BX 1310nm TX / 1550nm RX single fiber multimode (ST) [2 km/1.2 miles] - EU Power Cord	https://www.perle.com/products/fast-ethernet-managed-media-converters.shtml	Media Converter: SMI-100
05071302	SMI-100-M1ST2D - Managed Fast Ethernet Media Converter: 100BASE-TX (RJ-45) [100 m/328 ft.] to 100BASE-BX 1550nm TX / 1310nm RX single fiber multimode (ST) [2 km/1.2 miles] - EU Power Cord	https://www.perle.com/products/fast-ethernet-managed-media-converters.shtml	Media Converter: SMI-100
05071312	SMI-110-S1ST20D - Managed 10/100Base-TX Media and Rate Converter: 10/100BASE-TX (RJ-45) [100 m/328 ft.] to 100BASE-BX 1550nm TX / 1310nm RX single fiber single mode (ST) [20 km/12.4 miles] - EU Power Cord	https://www.perle.com/products/10-100-managed-media-converters.shtml	Media Converter: SMI-110
05071322	SMI-110-S1ST20U - Managed 10/100Base-TX Media and Rate Converter: 10/100BASE-TX (RJ-45) [100 m/328 ft.] to 100BASE-BX 1310nm TX / 1550nm RX single fiber single mode (ST) [20 km/12.4 miles] - EU Power Cord	https://www.perle.com/products/10-100-managed-media-converters.shtml	Media Converter: SMI-110
05071332	SMI-110-M1ST2U - Managed 10/100Base-TX Media and Rate Converter: 10/100BASE-TX (RJ-45) [100 m/328 ft.] to 100BASE-BX 1310nm TX / 1550nm RX single fiber multimode (ST) [2 km/1.2 miles] - EU Power Cord	https://www.perle.com/products/10-100-managed-media-converters.shtml	Media Converter: SMI-110
05071342	SMI-110-M1ST2D - Managed 10/100Base-TX Media and Rate Converter: 10/100BASE-TX (RJ-45) [100 m/328 ft.] to 100BASE-BX 1550nm TX / 1310nm RX single fiber multimode (ST) [2 km/1.2 miles] - EU Power Cord	https://www.perle.com/products/10-100-managed-media-converters.shtml	Media Converter: SMI-110
05071352	SMI-10GRT-SFP - Managed 10 Gigabit Media and Rate Converter: 10/100/1000/2.5G/10GBase-T (RJ-45) [100 m/328 ft.] (CAT6A or better) to SFP+ slot (empty). AC Adapter included - EU Power Cord	https://www.perle.com/products/media-converters/10gbase-t-managed-rate-converter.shtml	Media Converter: SMI-10GR

Part #	Description	Product Datasheet	Product Group
05071362	SMI-10GR-STS - Managed 10 Gigabit Media and Rate Converter with dual SFP+ slots (empty). Includes AC power Adapter - EU Power Cord	https://www.perle.com/products/media-converters/10-gigabit-managed-rate-converter.shtml	Media Converter: SMI-10GR
05079280	S-1110DHP-SC05-XT - Gigabit Industrial Temperature Media and Rate Converter with Type 4 High-Power PoE PSE (up to 100W/port): Dual 10/100/1000Base-T (RJ45) [100 m/328 ft] to 1000Base-SX 850nm multimode (SC) [550 m/1804 ft]. -40F to +167F (-40C to +75C) operating temperature support. Terminal block power connector for external power source.	https://www.perle.com/products/media-converters/s-1110hp-xt-hi-poe-media-converters.shtml	Media Converter: S-1110HP
05079290	S-1110DHP-ST05-XT - Gigabit Industrial Temperature Media and Rate Converter with Type 4 High-Power PoE PSE (up to 100W/port): Dual 10/100/1000Base-T (RJ45) [100 m/328 ft] to 1000Base-SX 850nm multimode (ST) [550 m/1804 ft]. -40F to +167F (-40C to +75C) operating temperature support. Terminal block power connector for external power source.	https://www.perle.com/products/media-converters/s-1110hp-xt-hi-poe-media-converters.shtml	Media Converter: S-1110HP
05079300	S-1110DHP-SC10-XT - Gigabit Industrial Temperature Media and Rate Converter with Type 4 High-Power PoE PSE (up to 100W/port): Dual 10/100/1000Base-T (RJ45) [100 m/328 ft] to 1000Base-LX/LH 1310nm single mode (SC) [10 km/6.2 miles]. -40F to +167F (-40C to +75C) operating temperature support. Terminal block power connector for external power source.	https://www.perle.com/products/media-converters/s-1110hp-xt-hi-poe-media-converters.shtml	Media Converter: S-1110HP
05079310	S-1110DHP-ST10-XT - Gigabit Industrial Temperature Media and Rate Converter with Type 4 High-Power PoE PSE (up to 100W/port): Dual 10/100/1000Base-T (RJ45) [100 m/328 ft] to 1000Base-LX/LH 1310nm single mode (ST) [10 km/6.2 miles]. -40F to +167F (-40C to +75C) operating temperature support. Terminal block power connector for external power source.	https://www.perle.com/products/media-converters/s-1110hp-xt-hi-poe-media-converters.shtml	Media Converter: S-1110HP
05079320	S-1110HP-DSFP-XT - Gigabit Industrial Temperature Media and Rate Converter with Type 4 High-Power PoE PSE (up to 100W/port): 10/100/1000Base-T (RJ45) [100 m/328 ft] to 1000Base-X or 100Base-X. Dual SFP Slots (empty). -40F to +167F (-40C to +75C) operating temperature support.	https://www.perle.com/products/media-converters/s-1110hp-sfp-xt-hi-poe-media-converters.shtml	Media Converter: S-1110HP

Part #	Description	Product Datasheet	Product Group
05079330	S-1110DHP-SFP-XT - Gigabit Industrial Temperature Media and Rate Converter with Type 4 High-Power PoE PSE (up to 100W/port): Dual 10/100/1000Base-T (RJ45) [100 m/328 ft] to 1000Base-X or 100Base-X - SFP Slot (empty). -40F to +167F (-40C to +75C) operating temperature support. Terminal block power connector for external power source	https://www.perle.com/products/media-converters/s-1110hp-sfp-xt-hi-poe-media-converters.shtml	Media Converter: S-1110HP
05079342	S-1110HP-SFP - Gigabit Media and Rate Converter with Type 4 High-Power PoE PSE (up to 100W/port): 10/100/1000Base-T (RJ45) [100 m/328 ft] to 1000Base-X or 100Base-X. SFP Slot (empty). Includes EU AC Power Adapter	https://www.perle.com/products/media-converters/s-1110hp-sfp-hi-poe-media-converters.shtml	Media Converter: S-1110HP
05079352	S-1110HP-DSFP - Gigabit Media and Rate Converter with Type 4 High-Power PoE PSE (up to 100W/port): 10/100/1000Base-T (RJ45) [100 m/328 ft] to 1000Base-X or 100Base-X. Dual SFP Slots (empty). Includes EU AC Power Adapter	https://www.perle.com/products/media-converters/s-1110hp-sfp-hi-poe-media-converters.shtml	Media Converter: S-1110HP
05079362	S-1110HP-SC05 - Gigabit Media and Rate Converter with Type 4 High-Power PoE PSE (up to 100W/port): 10/100/1000Base-T (RJ45) [100 m/328 ft] to 1000Base-SX 850nm multimode (SC) [550 m/1804 ft]. Includes EU AC Power Adapter	https://www.perle.com/products/media-converters/s-1110hp-hi-poe-media-converters.shtml	Media Converter: S-1110HP
05079372	S-1110HP-ST05 - Gigabit Media and Rate Converter with Type 4 High-Power PoE PSE (up to 100W/port): 10/100/1000Base-T (RJ45) [100 m/328 ft] to 1000Base-SX 850nm multimode (ST) [550 m/1804 ft]. Includes EU AC Power Adapter	https://www.perle.com/products/media-converters/s-1110hp-hi-poe-media-converters.shtml	Media Converter: S-1110HP
05079382	S-1110HP-SC2 - Gigabit Media and Rate Converter with Type 4 High-Power PoE PSE (up to 100W/port): 10/100/1000Base-T (RJ45) [100 m/328 ft] to 1000Base-LX 1310nm Extended multimode (SC) [2km /6562 ft]. Includes EU AC Power Adapter	https://www.perle.com/products/media-converters/s-1110hp-hi-poe-media-converters.shtml	Media Converter: S-1110HP
05079392	S-1110HP-ST2 - Gigabit Media and Rate Converter with Type 4 High-Power PoE PSE (up to 100W/port): 10/100/1000Base-T (RJ45) [100 m/328 ft] to 1000Base-LX 1310nm Extended multimode (ST) [2km /6562 ft]. Includes EU AC Power Adapter	https://www.perle.com/products/media-converters/s-1110hp-hi-poe-media-converters.shtml	Media Converter: S-1110HP
05079402	S-1110HP-SC10 - Gigabit Media and Rate Converter with Type 4 High-Power PoE PSE (up to 100W/port): 10/100/1000Base-T (RJ45) [100 m/328 ft] to 1000Base-LX/LH 1310nm single mode (SC) [10 km/6.2 miles]. Includes EU AC Power Adapter	https://www.perle.com/products/media-converters/s-1110hp-hi-poe-media-converters.shtml	Media Converter: S-1110HP

Part #	Description	Product Datasheet	Product Group
05079412	S-1110HP-ST10 - Gigabit Media and Rate Converter with Type 4 High-Power PoE PSE (up to 100W/port): 10/100/1000Base-T (RJ45) [100 m/328 ft] to 1000Base-LX/LH 1310nm single mode (ST) [10 km/6.2 miles]. Includes EU AC Power Adapter	https://www.perle.com/products/media-converters/s-1110hp-hi-poe-media-converters.shtml	Media Converter: S-1110HP
05079422	S-1110HP-SC40 - Gigabit Media and Rate Converter with Type 4 High-Power PoE PSE (up to 100W/port): 10/100/1000Base-T (RJ45) [100 m/328 ft] to 1000Base-EX 1310nm single mode (SC) [40 km/24.9 miles]. Includes EU AC Power Adapter	https://www.perle.com/products/media-converters/s-1110hp-hi-poe-media-converters.shtml	Media Converter: S-1110HP
05079432	S-1110HP-ST40 - Gigabit Media and Rate Converter with Type 4 High-Power PoE PSE (up to 100W/port): 10/100/1000Base-T (RJ45) [100 m/328 ft] to 1000Base-EX 1310nm single mode (ST) [40 km/24.9 miles]. Includes EU AC Power Adapter	https://www.perle.com/products/media-converters/s-1110hp-hi-poe-media-converters.shtml	Media Converter: S-1110HP
05079442	S-1110HP-SC70 - Gigabit Media and Rate Converter with Type 4 High-Power PoE PSE (up to 100W/port): 10/100/1000Base-T (RJ45) [100 m/328 ft] to 1000Base-ZX 1550nm single mode (SC) [70 km/43.5 miles]. Includes EU AC Power Adapter	https://www.perle.com/products/media-converters/s-1110hp-hi-poe-media-converters.shtml	Media Converter: S-1110HP
05079452	S-1110HP-ST70 - Gigabit Media and Rate Converter with Type 4 High-Power PoE PSE (up to 100W/port): 10/100/1000Base-T (RJ45) [100 m/328 ft] to 1000Base-ZX 1550nm single mode (ST) [70 km/43.5 miles]. Includes EU AC Power Adapter	https://www.perle.com/products/media-converters/s-1110hp-hi-poe-media-converters.shtml	Media Converter: S-1110HP
05079462	S-1110HP-SC120 - Gigabit Media and Rate Converter with Type 4 High-Power PoE PSE (up to 100W/port): 10/100/1000Base-T (RJ45) [100 m/328 ft] to 1000Base-ZX 1550nm single mode (SC) [120 km/74.6 miles]. Includes EU AC Power Adapter	https://www.perle.com/products/media-converters/s-1110hp-hi-poe-media-converters.shtml	Media Converter: S-1110HP
05079472	S-1110HP-ST120 - Gigabit Media and Rate Converter with Type 4 High-Power PoE PSE: 10/100/1000Base-T (RJ45) [100 m/328 ft] to 1000Base-ZX 1550nm single mode (ST) [120 km/74.6 miles]. Includes EU AC Power Adapter	https://www.perle.com/products/media-converters/s-1110hp-hi-poe-media-converters.shtml	Media Converter: S-1110HP
05079482	S-1110HP-SC160 - Gigabit Media and Rate Converter with Type 4 High-Power PoE PSE (up to 100W/port): 10/100/1000Base-T (RJ45) [100 m/328 ft] to 1000Base-ZX 1550nm single mode (SC) [160 km/100 miles]. Includes EU AC Power Adapter	https://www.perle.com/products/media-converters/s-1110hp-hi-poe-media-converters.shtml	Media Converter: S-1110HP

Part #	Description	Product Datasheet	Product Group
05079492	S-1110HP-ST160 - Gigabit Media and Rate Converter with Type 4 High-Power PoE PSE (up to 100W/port): 10/100/1000Base-T (RJ45) [100 m/328 ft] to 1000Base-ZX 1550nm single mode (ST) [160 km/100 miles]. Includes EU AC Power Adapter	https://www.perle.com/products/media-converters/s-1110hp-hi-poe-media-converters.shtml	Media Converter: S-1110HP
05079502	S-1110HP-SC05U - 10/100/1000 Gigabit Ethernet Media and Rate Converter with Type 4 High-Power PoE PSE (up to 100W/port): 10/100/1000BASE-T (RJ45) [100 m/328 ft] to 1000Base-BX 1310nm TX / 1550nm RX single strand fiber, multimode (SC) [550 m/1804 ft]. Includes EU AC Power Adapter	https://www.perle.com/products/media-converters/s-1110hp-hi-poe-media-converters.shtml	Media Converter: S-1110HP
05079512	S-1110HP-SC05D - 10/100/1000 Gigabit Ethernet Media and Rate Converter with Type 4 High-Power PoE PSE (up to 100W/port): 10/100/1000BASE-T (RJ45) [100 m/328 ft] to 1000Base-BX 1550nm TX / 1310nm RX single strand fiber, multimode (SC) [550 m/1804 ft]. Includes EU AC Power Adapter	https://www.perle.com/products/media-converters/s-1110hp-hi-poe-media-converters.shtml	Media Converter: S-1110HP
05079522	S-1110HP-SC10U - Gigabit Media and Rate Converter with Type 4 High-Power PoE PSE (up to 100W/port): 10/100/1000Base-T (RJ45) [100 m/328 ft] to 1000Base-BX 1310nm TX / 1490nm RX single strand fiber, single mode (SC) [10 km/6.2 miles]. Includes EU AC Power Adapter	https://www.perle.com/products/media-converters/s-1110hp-hi-poe-media-converters.shtml	Media Converter: S-1110HP
05079532	S-1110HP-SC10D - Gigabit Media and Rate Converter with Type 4 High-Power PoE PSE (up to 100W/port): 10/100/1000Base-T (RJ45) [100 m/328 ft] to 1000Base-BX 1490nm TX / 1310nm RX single strand fiber, single mode (SC) [10 km/6.2 miles]. Includes EU AC Power Adapter	https://www.perle.com/products/media-converters/s-1110hp-hi-poe-media-converters.shtml	Media Converter: S-1110HP
05079542	S-1110HP-SC20U - Gigabit Media and Rate Converter with Type 4 High-Power PoE PSE (up to 100W/port): 10/100/1000Base-T (RJ45) [100 m/328 ft] to 1000Base-BX 1310nm TX / 1490nm RX single strand fiber, single mode (SC) [20 km/12.4 miles]. Includes EU AC Power Adapter	https://www.perle.com/products/media-converters/s-1110hp-hi-poe-media-converters.shtml	Media Converter: S-1110HP
05079552	S-1110HP-SC20D - Gigabit Media and Rate Converter with Type 4 High-Power PoE PSE (up to 100W/port): 10/100/1000Base-T (RJ45) [100 m/328 ft] to 1000Base-BX 1490nm TX / 1310nm RX single strand fiber, single mode (SC) [20 km/12.4 miles]. Includes EU AC Power Adapter	https://www.perle.com/products/media-converters/s-1110hp-hi-poe-media-converters.shtml	Media Converter: S-1110HP
05079562	S-1110HP-SC40U - Gigabit Media and Rate Converter with Type 4 High-Power PoE PSE (up to 100W/port): 10/100/1000Base-T (RJ45) [100 m/328 ft] to 1000Base-BX 1310nm TX / 1490nm RX single strand fiber, single mode (SC) [40 km/25 miles]. Includes EU AC Power Adapter	https://www.perle.com/products/media-converters/s-1110hp-hi-poe-media-converters.shtml	Media Converter: S-1110HP

Part #	Description	Product Datasheet	Product Group
05079572	S-1110HP-SC40D - Gigabit Media and Rate Converter with Type 4 High-Power PoE PSE (up to 100W/port): 10/100/1000Base-T (RJ45) [100 m/328 ft] to 1000Base-BX 1490nm TX / 1310nm RX single strand fiber, single mode (SC) [40 km/25 miles]. Includes EU AC Power Adapter	https://www.perle.com/products/media-converters/s-1110hp-hi-poe-media-converters.shtml	Media Converter: S-1110HP
05079582	S-1110HP-SC80U - Gigabit Media and Rate Converter with Type 4 High-Power PoE PSE (up to 100W/port): 10/100/1000Base-T (RJ45) [100 m/328 ft] to 1000Base-BX 1510nm TX / 1590nm RX single strand fiber, single mode (SC) [80 km/50 miles]. Includes EU AC Power Adapter	https://www.perle.com/products/media-converters/s-1110hp-hi-poe-media-converters.shtml	Media Converter: S-1110HP
05079592	S-1110HP-SC80D - Gigabit Media and Rate Converter with Type 4 High-Power PoE PSE (up to 100W/port): 10/100/1000Base-T (RJ45) [100 m/328 ft] to 1000Base-BX 1590nm TX / 1510nm RX single strand fiber, single mode (SC) [80 km/50 miles]. Includes EU AC Power Adapter	https://www.perle.com/products/media-converters/s-1110hp-hi-poe-media-converters.shtml	Media Converter: S-1110HP
05079602	S-1110HP-SC120U - Gigabit Media and Rate Converter with Type 4 High-Power PoE PSE (up to 100W/port): 10/100/1000Base-T (RJ45) [100 m/328 ft] to 1000Base-BX 1510nm TX / 1590nm RX single strand fiber, single mode (SC) [120 km/75 miles]. Includes EU AC Power Adapter	https://www.perle.com/products/media-converters/s-1110hp-hi-poe-media-converters.shtml	Media Converter: S-1110HP
05079612	S-1110HP-SC120D - Gigabit Media and Rate Converter with Type 4 High-Power PoE PSE (up to 100W/port): 10/100/1000Base-T (RJ45) [100 m/328 ft] to 1000Base-BX 1590nm TX / 1510nm RX single strand fiber, single mode (SC) [120 km/75 miles]. Includes EU AC Power Adapter	https://www.perle.com/products/media-converters/s-1110hp-hi-poe-media-converters.shtml	Media Converter: S-1110HP
05079622	S-1110DHP-SFP - Gigabit Media and Rate Converter with Type 4 High-Power PoE PSE (up to 100W/port): Dual 10/100/1000Base-T (RJ45) [100 m/328 ft] to 1000Base-X or 100Base-X. SFP Slot (empty). Includes EU AC Power Adapter	https://www.perle.com/products/media-converters/s-1110hp-sfp-hi-poe-media-converters.shtml	Media Converter: S-1110HP
05079632	S-1110DHP-DSFP - Gigabit Media and Rate Converter with Type 4 High-Power PoE PSE (up to 100W/port): Dual 10/100/1000Base-T (RJ45) [100 m/328 ft] to 1000Base-X or 100Base-X. Dual SFP Slots (empty). Includes EU AC Power Adapter	https://www.perle.com/products/media-converters/s-1110hp-sfp-hi-poe-media-converters.shtml	Media Converter: S-1110HP
05079642	S-1110DHP-SC05 - Gigabit Media and Rate Converter with Type 4 High-Power PoE PSE (up to 100W/port): Dual 10/100/1000Base-T (RJ45) [100 m/328 ft] to 1000Base-SX 850nm multimode (SC) [550 m/1804 ft]. Includes EU AC Power Adapter	https://www.perle.com/products/media-converters/s-1110hp-hi-poe-media-converters.shtml	Media Converter: S-1110HP

Part #	Description	Product Datasheet	Product Group
05079652	S-1110DHP-ST05 - Gigabit Media and Rate Converter with Type 4 High-Power PoE PSE (up to 100W/port): Dual 10/100/1000Base-T (RJ45) [100 m/328 ft] to 1000Base-SX 850nm multimode (ST) [550 m/1804 ft]. Includes EU AC Power Adapter	https://www.perle.com/products/media-converters/s-1110hp-hi-poe-media-converters.shtml	Media Converter: S-1110HP
05079662	S-1110DHP-SC2 - Gigabit Media and Rate Converter with Type 4 High-Power PoE PSE (up to 100W/port): Dual 10/100/1000Base-T (RJ45) [100 m/328 ft] to 1000Base-LX 1310nm Extended multimode (SC) [2km /6562 ft]. Includes EU AC Power Adapter	https://www.perle.com/products/media-converters/s-1110hp-hi-poe-media-converters.shtml	Media Converter: S-1110HP
05079672	S-1110DHP-ST2 - Gigabit Media and Rate Converter with Type 4 High-Power PoE PSE (up to 100W/port): Dual 10/100/1000Base-T (RJ45) [100 m/328 ft] to 1000Base-LX 1310nm Extended multimode (ST) [2km /6562 ft]. Includes EU AC Power Adapter	https://www.perle.com/products/media-converters/s-1110hp-hi-poe-media-converters.shtml	Media Converter: S-1110HP
05079682	S-1110DHP-SC10 - Gigabit Media and Rate Converter with Type 4 High-Power PoE PSE (up to 100W/port): Dual 10/100/1000Base-T (RJ45) [100 m/328 ft] to 1000Base-LX/LH 1310nm single mode (SC) [10 km/6.2 miles]. Includes EU AC Power Adapter	https://www.perle.com/products/media-converters/s-1110hp-hi-poe-media-converters.shtml	Media Converter: S-1110HP
05079692	S-1110DHP-ST10 - Gigabit Media and Rate Converter with Type 4 High-Power PoE PSE (up to 100W/port): Dual 10/100/1000Base-T (RJ45) [100 m/328 ft] to 1000Base-LX/LH 1310nm single mode (ST) [10 km/6.2 miles]. Includes EU AC Power Adapter	https://www.perle.com/products/media-converters/s-1110hp-hi-poe-media-converters.shtml	Media Converter: S-1110HP
05079702	S-1110DHP-SC40 - Gigabit Media and Rate Converter with Type 4 High-Power PoE PSE (up to 100W/port): Dual 10/100/1000Base-T (RJ45) [100 m/328 ft] to 1000Base-EX 1310nm single mode (SC) [40 km/24.9 miles]. Includes EU AC Power Adapter	https://www.perle.com/products/media-converters/s-1110hp-hi-poe-media-converters.shtml	Media Converter: S-1110HP
05079712	S-1110DHP-ST40 - Gigabit Media and Rate Converter with Type 4 High-Power PoE PSE (up to 100W/port): Dual 10/100/1000Base-T (RJ45) [100 m/328 ft] to 1000Base-EX 1310nm single mode (ST) [40 km/24.9 miles]. Includes EU AC Power Adapter	https://www.perle.com/products/media-converters/s-1110hp-hi-poe-media-converters.shtml	Media Converter: S-1110HP
05079722	S-1110DHP-SC70 - Gigabit Media and Rate Converter with Type 4 High-Power PoE PSE (up to 100W/port): Dual 10/100/1000Base-T (RJ45) [100 m/328 ft] to 1000Base-ZX 1550nm single mode (SC) [70 km/43.5 miles]. Includes EU AC Power Adapter	https://www.perle.com/products/media-converters/s-1110hp-hi-poe-media-converters.shtml	Media Converter: S-1110HP

Part #	Description	Product Datasheet	Product Group
05079732	S-1110DHP-ST70 - Gigabit Media and Rate Converter with Type 4 High-Power PoE PSE (up to 100W/port): Dual 10/100/1000Base-T (RJ45) [100 m/328 ft] to 1000Base-ZX 1550nm single mode (ST) [70 km/43.5 miles]. Includes EU AC Power Adapter	https://www.perle.com/products/media-converters/s-1110hp-hi-poe-media-converters.shtml	Media Converter: S-1110HP
05079742	S-1110DHP-SC120 - Gigabit Media and Rate Converter with Type 4 High-Power PoE PSE (up to 100W/port): Dual 10/100/1000Base-T (RJ45) [100 m/328 ft] to 1000Base-ZX 1550nm single mode (SC) [120 km/74.6 miles]. Includes EU AC Power Adapter	https://www.perle.com/products/media-converters/s-1110hp-hi-poe-media-converters.shtml	Media Converter: S-1110HP
05079752	S-1110DHP-ST120 - Gigabit Media and Rate Converter with Type 4 High-Power PoE PSE (up to 100W/port): Dual 10/100/1000Base-T (RJ45) [100 m/328 ft] to 1000Base-ZX 1550nm single mode (ST) [120 km/74.6 miles]. Includes EU AC Power Adapter	https://www.perle.com/products/media-converters/s-1110hp-hi-poe-media-converters.shtml	Media Converter: S-1110HP
05079762	S-1110DHP-SC160 - Gigabit Media and Rate Converter with Type 4 High-Power PoE PSE (up to 100W/port): Dual 10/100/1000Base-T (RJ45) [100 m/328 ft] to 1000Base-ZX 1550nm single mode (SC) [160 km/100 miles]. Includes EU AC Power Adapter	https://www.perle.com/products/media-converters/s-1110hp-hi-poe-media-converters.shtml	Media Converter: S-1110HP
05079772	S-1110DHP-ST160 - Gigabit Media and Rate Converter with Type 4 High-Power PoE PSE (up to 100W/port): Dual 10/100/1000Base-T (RJ45) [100 m/328 ft] to 1000Base-ZX 1550nm single mode (ST) [160 km/100 miles]. Includes EU AC Power Adapter	https://www.perle.com/products/media-converters/s-1110hp-hi-poe-media-converters.shtml	Media Converter: S-1110HP
05079782	S-1110DHP-SC05U - 10/100/1000 Gigabit Ethernet Media and Rate Converter with Type 4 High-Power PoE PSE (up to 100W/port): Dual 10/100/1000BASE-T (RJ45) [100 m/328 ft] to 1000Base-BX 1310nm TX / 1550nm RX single strand fiber, multimode (SC) [500 m/1640 ft]. Includes EU AC Power Adapter	https://www.perle.com/products/media-converters/s-1110hp-hi-poe-media-converters.shtml	Media Converter: S-1110HP
05079792	S-1110DHP-SC05D - 10/100/1000 Gigabit Ethernet Media and Rate Converter with Type 4 High-Power PoE PSE (up to 100W/port): Dual 10/100/1000BASE-T (RJ45) [100 m/328 ft] to 1000Base-BX 1550nm TX / 1310nm RX single strand fiber, multimode (SC) [500 m/1640 ft]. Includes EU AC Power Adapter	https://www.perle.com/products/media-converters/s-1110hp-hi-poe-media-converters.shtml	Media Converter: S-1110HP
05079802	S-1110DHP-SC10U - Gigabit Media and Rate Converter with Type 4 High-Power PoE PSE (up to 100W/port): Dual 10/100/1000Base-T (RJ45) [100 m/328 ft] to 1000Base-BX 1310nm TX / 1490nm RX single strand fiber, single mode (SC) [10 km/6.2 miles]. Includes EU AC Power Adapter	https://www.perle.com/products/media-converters/s-1110hp-hi-poe-media-converters.shtml	Media Converter: S-1110HP

Part #	Description	Product Datasheet	Product Group
05079812	S-1110DHP-SC10D - Gigabit Media and Rate Converter with Type 4 High-Power PoE PSE (up to 100W/port): Dual 10/100/1000Base-T (RJ45) [100 m/328 ft] to 1000Base-BX 1490nm TX / 1310nm RX single strand fiber, single mode (SC) [10 km/6.2 miles]. Includes EU AC Power Adapter	https://www.perle.com/products/media-converters/s-1110hp-hi-poe-media-converters.shtml	Media Converter: S-1110HP
05079822	S-1110DHP-SC20U - Gigabit Media and Rate Converter with Type 4 High-Power PoE PSE (up to 100W/port): Dual 10/100/1000Base-T (RJ45) [100 m/328 ft] to 1000Base-BX 1310nm TX / 1490nm RX single strand fiber, single mode (SC) [20 km/12.4 miles]. Includes EU AC Power Adapter	https://www.perle.com/products/media-converters/s-1110hp-hi-poe-media-converters.shtml	Media Converter: S-1110HP
05079832	S-1110DHP-SC20D - Gigabit Media and Rate Converter with Type 4 High-Power PoE PSE (up to 100W/port): Dual 10/100/1000Base-T (RJ45) [100 m/328 ft] to 1000Base-BX 1490nm TX / 1310nm RX single strand fiber, single mode (SC) [20 km/12.4 miles]. Includes EU AC Power Adapter	https://www.perle.com/products/media-converters/s-1110hp-hi-poe-media-converters.shtml	Media Converter: S-1110HP
05079842	S-1110DHP-SC40U - Gigabit Media and Rate Converter with Type 4 High-Power PoE PSE (up to 100W/port): Dual 10/100/1000Base-T (RJ45) [100 m/328 ft] to 1000Base-BX 1310nm TX / 1490nm RX single strand fiber, single mode (SC) [40 km/25 miles]. Includes EU AC Power Adapter	https://www.perle.com/products/media-converters/s-1110hp-hi-poe-media-converters.shtml	Media Converter: S-1110HP
05079852	S-1110DHP-SC40D - Gigabit Media and Rate Converter with Type 4 High-Power PoE PSE (up to 100W/port): Dual 10/100/1000Base-T (RJ45) [100 m/328 ft] to 1000Base-BX 1490nm TX / 1310nm RX single strand fiber, single mode (SC) [40 km/25 miles]. Includes EU AC Power Adapter	https://www.perle.com/products/media-converters/s-1110hp-hi-poe-media-converters.shtml	Media Converter: S-1110HP
05079862	S-1110DHP-SC80U - Gigabit Media and Rate Converter with Type 4 High-Power PoE PSE (up to 100W/port): Dual 10/100/1000Base-T (RJ45) [100 m/328 ft] to 1000Base-BX 1510nm TX / 1590nm RX single strand fiber, single mode (SC) [80 km/50 miles]. Includes EU AC Power Adapter	https://www.perle.com/products/media-converters/s-1110hp-hi-poe-media-converters.shtml	Media Converter: S-1110HP
05079872	S-1110DHP-SC80D - Gigabit Media and Rate Converter with Type 4 High-Power PoE PSE (up to 100W/port): Dual 10/100/1000Base-T (RJ45) [100 m/328 ft] to 1000Base-BX 1590nm TX / 1510nm RX single strand fiber, single mode (SC) [80 km/50 miles]. Includes EU AC Power Adapter	https://www.perle.com/products/media-converters/s-1110hp-hi-poe-media-converters.shtml	Media Converter: S-1110HP
05079882	S-1110DHP-SC120U - Gigabit Media and Rate Converter with Type 4 High-Power PoE PSE (up to 100W/port): Dual 10/100/1000Base-T (RJ45) [100 m/328 ft] to 1000Base-BX 1510nm TX / 1590nm RX single strand fiber, single mode (SC) [120 km/75 miles]. Includes EU AC Power Adapter	https://www.perle.com/products/media-converters/s-1110hp-hi-poe-media-converters.shtml	Media Converter: S-1110HP

Part #	Description	Product Datasheet	Product Group
05079892	S-1110DHP-SC120D - Gigabit Media and Rate Converter with Type 4 High-Power PoE PSE (up to 100W/port): Dual 10/100/1000Base-T (RJ45) [100 m/328 ft] to 1000Base-BX 1590nm TX / 1510nm RX single strand fiber, single mode (SC) [120 km/75 miles]. Includes EU AC Power Adapter	https://www.perle.com/products/media-converters/s-1110hp-hi-poe-media-converters.shtml	Media Converter: S-1110HP
05079900	S-1110HP-SFP-XT - Gigabit Industrial Temperature Media and Rate Converter with Type 4 High-Power PoE PSE (up to 100W/port): 10/100/1000Base-T (RJ45) [100 m/328 ft] to 1000Base-X or 100Base-X - SFP Slot (empty). -40F to +167F (-40C to +75C) operating temperature support.	https://www.perle.com/products/media-converters/s-1110hp-sfp-xt-hi-poe-media-converters.shtml	Media Converter: S-1110HP
05079910	S-1110HP-SC05-XT - Gigabit Industrial Temperature Media and Rate Converter with Type 4 High-Power PoE PSE (up to 100W/port): 10/100/1000Base-T (RJ45) [100 m/328 ft] to 1000Base-SX 850nm multimode (SC) [550 m/1804 ft]. -40F to +167F (-40C to +75C) operating temperature support. Terminal block power connector for external power source.	https://www.perle.com/products/media-converters/s-1110hp-xt-hi-poe-media-converters.shtml	Media Converter: S-1110HP
05079920	S-1110HP-ST05-XT - Gigabit Industrial Temperature Media and Rate Converter with Type 4 High-Power PoE PSE (up to 100W/port): 10/100/1000Base-T (RJ45) [100 m/328 ft] to 1000Base-SX 850nm multimode (ST) [550 m/1804 ft]. -40F to +167F (-40C to +75C) operating temperature support. Terminal block power connector for external power source.	https://www.perle.com/products/media-converters/s-1110hp-xt-hi-poe-media-converters.shtml	Media Converter: S-1110HP
05079930	S-1110HP-SC10-XT - Gigabit Industrial Temperature Media and Rate Converter with Type 4 High-Power PoE PSE (up to 100W/port): 10/100/1000Base-T (RJ45) [100 m/328 ft] to 1000Base-LX/LH 1310nm single mode (SC) [10 km/6.2 miles]. -40F to +167F (-40C to +75C) operating temperature support. Terminal block power connector for external power source.	https://www.perle.com/products/media-converters/s-1110hp-xt-hi-poe-media-converters.shtml	Media Converter: S-1110HP
05079940	S-1110HP-ST10-XT - Gigabit Industrial Temperature Media and Rate Converter with Type 4 High-Power PoE PSE (up to 100W/port): 10/100/1000Base-T (RJ45) [100 m/328 ft] to 1000Base-LX/LH 1310nm single mode (ST) [10 km/6.2 miles]. -40F to +167F (-40C to +75C) operating temperature support. Terminal block power connector for external power source.	https://www.perle.com/products/media-converters/s-1110hp-xt-hi-poe-media-converters.shtml	Media Converter: S-1110HP

Part #	Description	Product Datasheet	Product Group
05079950	S-1110HP-SC10U-XT - Gigabit Industrial Temperature Media and Rate Converter with Type 4 High-Power PoE PSE (up to 100W/port): 10/100/1000Base-T (RJ45) [100 m/328 ft] to 1000Base-BX 1310nm TX / 1490nm RX single strand fiber, single mode (SC) [10 km/6.2 miles]. -40F to +167F (-40C to +75C) operating temperature support. Terminal block power connector for external power source.	https://www.perle.com/products/media-converters/s-1110hp-xt-hi-poe-media-converters.shtml	Media Converter: S-1110HP
05079960	S-1110HP-SC10D-XT - Gigabit Industrial Temperature Media and Rate Converter with Type 4 High-Power PoE PSE (up to 100W/port): 10/100/1000Base-T (RJ45) [100 m/328 ft] to 1000Base-BX 1490nm TX / 1310nm RX single strand fiber, single mode (SC) [10 km/6.2 miles]. -40F to +167F (-40C to +75C) operating temperature support. Terminal block power connector for external power source.	https://www.perle.com/products/media-converters/s-1110hp-xt-hi-poe-media-converters.shtml	Media Converter: S-1110HP
05079970	S-1110DHP-DSFP-XT - Gigabit Industrial Temperature Media and Rate Converter with Type 4 High-Power PoE PSE (up to 100W/port): Dual 10/100/1000Base-T (RJ45) [100 m/328 ft] to 1000Base-X or 100Base-X. Dual SFP Slots (empty). -40F to +167F (-40C to +75C) operating temperature support. Terminal block power connector for external power source	https://www.perle.com/products/media-converters/s-1110hp-sfp-xt-hi-poe-media-converters.shtml	Media Converter: S-1110HP
05079980	S-1110DHP-SC10U-XT - Gigabit Industrial Temperature Media and Rate Converter with Type 4 High-Power PoE PSE (up to 100W/port): Dual 10/100/1000Base-T (RJ45) [100 m/328 ft] to 1000Base-BX 1310nm TX / 1490nm RX single strand fiber, single mode (SC) [10 km/6.2 miles]. -40F to +167F (-40C to +75C) operating temperature support. Terminal block power connector for external power source.	https://www.perle.com/products/media-converters/s-1110hp-xt-hi-poe-media-converters.shtml	Media Converter: S-1110HP
05079990	S-1110DHP-SC10D-XT - Gigabit Industrial Temperature Media and Rate Converter with Type 4 High-Power PoE PSE (up to 100W/port): Dual 10/100/1000Base-T (RJ45) [100 m/328 ft] to 1000Base-BX 1490nm TX / 1310nm RX single strand fiber, single mode (SC) [10 km/6.2 miles]. -40F to +167F (-40C to +75C) operating temperature support. Terminal block power connector for external power source.	https://www.perle.com/products/media-converters/s-1110hp-xt-hi-poe-media-converters.shtml	Media Converter: S-1110HP
05080002	S-1110P-SFP - 10/100/1000Base-T Media and Rate Converter with PoE Power Sourcing: 10/100/1000BASE-T (RJ-45) [100 m/328 ft.] to 1000BASE-X or 100BASE-X - SFP Slot (empty) Includes AC Power Adapter - EU Power Cord	https://www.perle.com/products/10-100-1000-poe-media-converters.shtml	Media Converter: S-1110P

Part #	Description	Product Datasheet	Product Group
05080012	S-1110P-DSFP - 10/100/1000Base-T Media and Rate Converter with PoE Power Sourcing: 10/100/1000BASE-T (RJ-45) [100 m/328 ft.] to 1000BASE-X or 100BASE-X - Dual SFP Slot (empty) Includes AC Power Adapter - EU Power Cord	https://www.perle.com/products/10-100-1000-poe-media-converters.shtml	Media Converter: S-1110P
05080022	S-1110P-M2SC05 - 10/100/1000Base-T Media and Rate Converter with PoE Power Sourcing: 10/100/1000BASE-T (RJ-45) [100 m/328 ft.] to 1000BASE-SX 850nm multimode (SC) [550 m/1804 ft.] Includes AC Power Adapter - EU Power Cord	https://www.perle.com/products/10-100-1000-poe-media-converters.shtml	Media Converter: S-1110P
05080032	S-1110P-M2ST05 - 10/100/1000Base-T Media and Rate Converter with PoE Power Sourcing: 10/100/1000BASE-T (RJ-45) [100 m/328 ft.] to 1000BASE-SX 850nm multimode (ST) [550 m/1804 ft.] Includes AC Power Adapter - EU Power Cord	https://www.perle.com/products/10-100-1000-poe-media-converters.shtml	Media Converter: S-1110P
05080042	S-1110P-S2SC10 - 10/100/1000Base-T Media and Rate Converter with PoE Power Sourcing: 10/100/1000BASE-T (RJ-45) [100 m/328 ft.] to 1000BASE-LX/LH 1310 nm single mode (SC) [10 km/6.2 miles] or multimode (SC) [550 m/1804 ft.] using a mode conditioning adapter. Includes AC Power Adapter - EU Power Cord	https://www.perle.com/products/10-100-1000-poe-media-converters.shtml	Media Converter: S-1110P
05080052	S-1110P-S2ST10 - 10/100/1000Base-T Media and Rate Converter with PoE Power Sourcing: 10/100/1000BASE-T (RJ-45) [100 m/328 ft.] to 1000BASE-LX/LH 1310 nm single mode (ST) [10 km/6.2 miles] Includes AC Power Adapter - EU Power Cord	https://www.perle.com/products/10-100-1000-poe-media-converters.shtml	Media Converter: S-1110P
05080062	S-1110P-S2SC40 - 10/100/1000Base-T Media and Rate Converter with PoE Power Sourcing: 10/100/1000BASE-T (RJ-45) [100 m/328 ft.] to 1000BASE-EX 1310 nm single mode (SC) [40 km/24.9 miles] Includes AC Power Adapter - EU Power Cord	https://www.perle.com/products/10-100-1000-poe-media-converters.shtml	Media Converter: S-1110P
05080072	S-1110P-S2ST40 - 10/100/1000Base-T Media and Rate Converter with PoE Power Sourcing: 10/100/1000BASE-T (RJ-45) [100 m/328 ft.] to 1000BASE-EX 1310 nm single mode (ST) [40 km/24.9 miles] Includes AC Power Adapter - EU Power Cord	https://www.perle.com/products/10-100-1000-poe-media-converters.shtml	Media Converter: S-1110P
05080082	S-1110P-S2SC70 - 10/100/1000Base-T Media and Rate Converter with PoE Power Sourcing: 10/100/1000BASE-T (RJ-45) [100 m/328 ft.] to 1000BASE-ZX 1550 nm single mode (SC) [70 km/43.5 miles] Includes AC Power Adapter - EU Power Cord	https://www.perle.com/products/10-100-1000-poe-media-converters.shtml	Media Converter: S-1110P

Part #	Description	Product Datasheet	Product Group
05080092	S-1110P-S2ST70 - 10/100/1000Base-T Media and Rate Converter with PoE Power Sourcing: 10/100/1000BASE-T (RJ-45) [100 m/328 ft.] to 1000BASE-ZX 1550 nm single mode (ST) [70 km/43.5 miles] Includes AC Power Adapter - EU Power Cord	https://www.perle.com/products/10-100-1000-poe-media-converters.shtml	Media Converter: S-1110P
05080102	S-1110P-S2SC120 - 10/100/1000Base-T Media and Rate Converter with PoE Power Sourcing: 10/100/1000BASE-T (RJ-45) [100 m/328 ft.] to 1000BASE-EZX 1550 nm single mode (SC) [120 km/74.6 miles] Includes AC Power Adapter - EU Power Cord	https://www.perle.com/products/10-100-1000-poe-media-converters.shtml	Media Converter: S-1110P
05080112	S-1110P-S2ST120 - 10/100/1000Base-T Media and Rate Converter with PoE Power Sourcing: 10/100/1000BASE-T (RJ-45) [100 m/328 ft.] to 1000BASE-ZX 1550 nm single mode (ST) [120 km/74.6 miles] Includes AC Power Adapter - EU Power Cord	https://www.perle.com/products/10-100-1000-poe-media-converters.shtml	Media Converter: S-1110P
05080122	S-1110P-S2SC160 - 10/100/1000Base-T Media and Rate Converter with PoE Power Sourcing: 10/100/1000BASE-T (RJ-45) [100 m/328 ft.] to 1000BASE-EZX 1550 nm single mode (SC) [160 km/100 miles] Includes AC Power Adapter - EU Power Cord	https://www.perle.com/products/10-100-1000-poe-media-converters.shtml	Media Converter: S-1110P
05080132	S-1110P-S2ST160 - 10/100/1000Base-T Media and Rate Converter with PoE Power Sourcing: 10/100/1000BASE-T (RJ-45) [100 m/328 ft.] to 1000BASE-ZX 1550 nm single mode (ST) [160 km/100 miles] Includes AC Power Adapter - EU Power Cord	https://www.perle.com/products/10-100-1000-poe-media-converters.shtml	Media Converter: S-1110P
05080142	S-1110P-S1SC10U - 10/100/1000Base-T Media and Rate Converter with PoE Power Sourcing: 10/100/1000BASE-T (RJ-45) [100 m/328 ft.] to 1000BASE-BX 1310nm TX / 1490nm RX single strand fiber, single mode (SC) [10 km/6.2 miles] Includes AC Power Adapter - EU Power Cord	https://www.perle.com/products/10-100-1000-poe-media-converters.shtml	Media Converter: S-1110P
05080152	S-1110P-S1SC10D - 10/100/1000Base-T Media and Rate Converter with PoE Power Sourcing: 10/100/1000BASE-T (RJ-45) [100 m/328 ft.] to 1000BASE-BX 1490nm TX / 1310nm RX single strand fiber, single mode (SC) [10 km/6.2 miles] Includes AC Power Adapter - EU Power Cord	https://www.perle.com/products/10-100-1000-poe-media-converters.shtml	Media Converter: S-1110P
05080162	S-1110P-S1SC20U - 10/100/1000Base-T Media and Rate Converter with PoE Power Sourcing: 10/100/1000BASE-T (RJ-45) [100 m/328 ft.] to 1000BASE-BX 1310nm TX / 1490nm RX single strand fiber, single mode (SC) [20 km/12.4 miles] Includes AC Power Adapter - EU Power Cord	https://www.perle.com/products/10-100-1000-poe-media-converters.shtml	Media Converter: S-1110P

Part #	Description	Product Datasheet	Product Group
05080172	S-1110P-S1SC20D - 10/100/1000Base-T Media and Rate Converter with PoE Power Sourcing: 10/100/1000BASE-T (RJ-45) [100 m/328 ft.] to 1000BASE-BX 1490nm TX / 1310nm RX single strand fiber, single mode (SC) [20 km/12.4 miles] Includes AC Power Adapter - EU Power Cord	https://www.perle.com/products/10-100-1000-poe-media-converters.shtml	Media Converter: S-1110P
05080182	S-1110P-S1SC40U - 10/100/1000Base-T Media and Rate Converter with PoE Power Sourcing: 10/100/1000BASE-T (RJ-45) [100 m/328 ft.] to 1000BASE-BX 1310nm TX / 1490nm RX single strand fiber, single mode (SC) [40 km/25 miles] Includes AC Power Adapter - EU Power Cord	https://www.perle.com/products/10-100-1000-poe-media-converters.shtml	Media Converter: S-1110P
05080192	S-1110P-S1SC40D - 10/100/1000Base-T Media and Rate Converter with PoE Power Sourcing: 10/100/1000BASE-T (RJ-45) [100 m/328 ft.] to 1000BASE-BX 1490nm TX / 1310nm RX single strand fiber, single mode (SC) [40 km/25 miles] Includes AC Power Adapter - EU Power Cord	https://www.perle.com/products/10-100-1000-poe-media-converters.shtml	Media Converter: S-1110P
05080202	S-1110P-S1SC80U - 10/100/1000Base-T Media and Rate Converter with PoE Power Sourcing: 10/100/1000BASE-T (RJ-45) [100 m/328 ft.] to 1000BASE-BX 1510nm TX / 1590nm RX single strand fiber, single mode (SC) [80 km/50 miles] Includes AC Power Adapter - EU Power Cord	https://www.perle.com/products/10-100-1000-poe-media-converters.shtml	Media Converter: S-1110P
05080212	S-1110P-S1SC80D - 10/100/1000Base-T Media and Rate Converter with PoE Power Sourcing: 10/100/1000BASE-T (RJ-45) [100 m/328 ft.] to 1000BASE-BX 1590nm TX / 1510nm RX single strand fiber, single mode (SC) [80 km/50 miles] Includes AC Power Adapter - EU Power Cord	https://www.perle.com/products/10-100-1000-poe-media-converters.shtml	Media Converter: S-1110P
05080222	S-1110P-S1SC120U - 10/100/1000Base-T Media and Rate Converter with PoE Power Sourcing: 10/100/1000BASE-T (RJ-45) [100 m/328 ft.] to 1000BASE-BX 1510nm TX / 1590nm RX single strand fiber, single mode (SC) [120 km/75 miles] Includes AC Power Adapter - EU Power Cord	https://www.perle.com/products/10-100-1000-poe-media-converters.shtml	Media Converter: S-1110P
05080232	S-1110P-S1SC120D - 10/100/1000Base-T Media and Rate Converter with PoE Power Sourcing: 10/100/1000BASE-T (RJ-45) [100 m/328 ft.] to 1000BASE-BX 1590nm TX / 1510nm RX single strand fiber, single mode (SC) [120 km/75 miles] Includes AC Power Adapter - EU Power Cord	https://www.perle.com/products/10-100-1000-poe-media-converters.shtml	Media Converter: S-1110P
05080242	S-1110P-M2SC2 - 10/100/1000Base-T Media and Rate Converter with PoE Power Sourcing: 10/100/1000BASE-T (RJ-45) [100 m/328 ft.] to 1000BASE-LX 1310nm Extended multimode (SC) [2km /6562 ft.]. Includes AC Power Adapter - EU Power Cord	https://www.perle.com/products/10-100-1000-poe-media-converters.shtml	Media Converter: S-1110P

Part #	Description	Product Datasheet	Product Group
05080252	S-1110P-M2ST2 - 10/100/1000Base-T Media and Rate Converter with PoE Power Sourcing: 10/100/1000BASE-T (RJ-45) [100 m/328 ft.] to 1000BASE-LX 1310nm Extended multimode (ST) [2km /6562 ft.]. Includes AC Power Adapter - EU Power Cord	https://www.perle.com/products/10-100-1000-poe-media-converters.shtml	Media Converter: S-1110P
05080262	S-1110P-M1SC05U - 10/100/1000Base-T Media and Rate Converter with PoE Power Sourcing: 10/100/1000BASE-T (RJ-45) [100 m/328 ft.] to 1000BASE-BX 1310nm TX / 1550nm RX single strand fiber, multimode (SC) [550 m/1804 ft] Includes AC Power Adapter - EU Power Cord	https://www.perle.com/products/10-100-1000-poe-media-converters.shtml	Media Converter: S-1110P
05080272	S-1110P-M1SC05D - 10/100/1000Base-T Media and Rate Converter with PoE Power Sourcing: 10/100/1000BASE-T (RJ-45) [100 m/328 ft.] to 1000BASE-BX 1550nm TX / 1310nm RX single strand fiber, multimode (SC) [550 m/1804 ft] Includes AC Power Adapter - EU Power Cord	https://www.perle.com/products/10-100-1000-poe-media-converters.shtml	Media Converter: S-1110P
05080282	S-110P-S1ST20U - 10/100Base-TX Media and Rate Converter with PoE Power Sourcing: 10/100Base-TX (RJ-45) [100 m/328 ft.] to 100Base-BX 1310nm TX / 1550nm RX single strand fiber, single mode (ST) [20 km/12.4 miles] includes AC Power Adapter - EU Power Cord	https://www.perle.com/products/10-100-poe-media-converters.shtml	Media Converter: S-110P
05080292	S-110P-S1ST20D - 10/100Base-TX Media and Rate Converter with PoE Power Sourcing: 10/100Base-TX (RJ-45) [100 m/328 ft.] to 100Base-BX 1550nm TX / 1310nm RX single strand fiber, single mode (ST) [20 km/12.4 miles] includes AC Power Adapter - EU Power Cord	https://www.perle.com/products/10-100-poe-media-converters.shtml	Media Converter: S-110P
05080302	S-110P-M1ST2U - 10/100Base-TX Media and Rate Converter with PoE Power Sourcing: 10/100Base-TX (RJ-45) [100 m/328 ft.] to 100Base-BX 1310nm TX / 1550nm RX single strand fiber, multimode (ST) [2 km/1.2 miles] includes AC Power Adapter - EU Power Cord	https://www.perle.com/products/10-100-poe-media-converters.shtml	Media Converter: S-110P
05080312	S-110P-M1ST2D - 10/100Base-TX Media and Rate Converter with PoE Power Sourcing: 10/100Base-TX (RJ-45) [100 m/328 ft.] to 100Base-BX 1550nm TX / 1310nm RX single strand fiber, multimode (ST) [2 km/1.2 miles] includes AC Power Adapter - EU Power Cord	https://www.perle.com/products/10-100-poe-media-converters.shtml	Media Converter: S-110P
05081002	S-1110PP-SFP - 10/100/1000Base-T Media and Rate Converter with PoE+ (PoEP) Power Sourcing: 10/100/1000BASE-T (RJ-45) [100 m/328 ft.] to 1000BASE-X or 100BASE-X - SFP Slot (empty) Includes AC Power Adapter - EU Power Cord	https://www.perle.com/products/10-100-1000-poe-media-converters.shtml	Media Converter: S-1110PP

Part #	Description	Product Datasheet	Product Group
05081012	S-1110PP-DSFP - 10/100/1000Base-T Media and Rate Converter with PoE+ (PoEP) Power Sourcing: 10/100/1000BASE-T (RJ-45) [100 m/328 ft.] to 1000BASE-X or 100BASE-X - Dual SFP Slot (empty) Includes AC Power Adapter - EU Power Cord	https://www.perle.com/products/10-100-1000-poe-media-converters.shtml	Media Converter: S-1110PP
05081022	S-1110PP-M2SC05 - 10/100/1000Base-T Media and Rate Converter with PoE+ (PoEP) Power Sourcing: 10/100/1000BASE-T (RJ-45) [100 m/328 ft.] to 1000BASE-SX 850nm multimode (SC) [550 m/1804 ft.] Includes AC Power Adapter - EU Power Cord	https://www.perle.com/products/10-100-1000-poe-media-converters.shtml	Media Converter: S-1110PP
05081032	S-1110PP-M2ST05 - 10/100/1000Base-T Media and Rate Converter with PoE+ (PoEP) Power Sourcing: 10/100/1000BASE-T (RJ-45) [100 m/328 ft.] to 1000BASE-SX 850nm multimode (ST) [550 m/1804 ft.] Includes AC Power Adapter - EU Power Cord	https://www.perle.com/products/10-100-1000-poe-media-converters.shtml	Media Converter: S-1110PP
05081042	S-1110PP-S2SC10 - 10/100/1000Base-T Media and Rate Converter with PoE+ (PoEP) Power Sourcing: 10/100/1000BASE-T (RJ-45) [100 m/328 ft.] to 1000BASE-LX/LH 1310 nm single mode (SC) [10 km/6.2 miles] or multimode (SC) [550 m/1804 ft.] using a mode conditioning adapter. Includes AC Power Adapter - EU Power Cord	https://www.perle.com/products/10-100-1000-poe-media-converters.shtml	Media Converter: S-1110PP
05081052	S-1110PP-S2ST10 - 10/100/1000Base-T Media and Rate Converter with PoE+ (PoEP) Power Sourcing: 10/100/1000BASE-T (RJ-45) [100 m/328 ft.] to 1000BASE-LX/LH 1310 nm single mode (ST) [10 km/6.2 miles] Includes AC Power Adapter - EU Power Cord	https://www.perle.com/products/10-100-1000-poe-media-converters.shtml	Media Converter: S-1110PP
05081062	S-1110PP-S2SC40 - 10/100/1000Base-T Media and Rate Converter with PoE+ (PoEP) Power Sourcing: 10/100/1000BASE-T (RJ-45) [100 m/328 ft.] to 1000BASE-EX 1310 nm single mode (SC) [40 km/24.9 miles] Includes AC Power Adapter - EU Power Cord	https://www.perle.com/products/10-100-1000-poe-media-converters.shtml	Media Converter: S-1110PP
05081072	S-1110PP-S2ST40 - 10/100/1000Base-T Media and Rate Converter with PoE+ (PoEP) Power Sourcing: 10/100/1000BASE-T (RJ-45) [100 m/328 ft.] to 1000BASE-EX 1310 nm single mode (ST) [40 km/24.9 miles] Includes AC Power Adapter - EU Power Cord	https://www.perle.com/products/10-100-1000-poe-media-converters.shtml	Media Converter: S-1110PP
05081082	S-1110PP-S2SC70 - 10/100/1000Base-T Media and Rate Converter with PoE+ (PoEP) Power Sourcing: 10/100/1000BASE-T (RJ-45) [100 m/328 ft.] to 1000BASE-ZX 1550 nm single mode (SC) [70 km/43.5 miles] Includes AC Power Adapter - EU Power Cord	https://www.perle.com/products/10-100-1000-poe-media-converters.shtml	Media Converter: S-1110PP

Part #	Description	Product Datasheet	Product Group
05081092	S-1110PP-S2ST70 - 10/100/1000Base-T Media and Rate Converter with PoE+ (PoEP) Power Sourcing: 10/100/1000BASE-T (RJ-45) [100 m/328 ft.] to 1000BASE-ZX 1550 nm single mode (ST) [70 km/43.5 miles] Includes AC Power Adapter - EU Power Cord	https://www.perle.com/products/10-100-1000-poe-media-converters.shtml	Media Converter: S-1110PP
05081102	S-1110PP-S2SC120 - 10/100/1000Base-T Media and Rate Converter with PoE+ (PoEP) Power Sourcing: 10/100/1000BASE-T (RJ-45) [100 m/328 ft.] to 1000BASE-EZX 1550 nm single mode (SC) [120 km/74.6 miles] Includes AC Power Adapter - EU Power Cord	https://www.perle.com/products/10-100-1000-poe-media-converters.shtml	Media Converter: S-1110PP
05081112	S-1110PP-S2ST120 - 10/100/1000Base-T Media and Rate Converter with PoE+ (PoEP) Power Sourcing: 10/100/1000BASE-T (RJ-45) [100 m/328 ft.] to 1000BASE-ZX 1550 nm single mode (ST) [120 km/74.6 miles] Includes AC Power Adapter - EU Power Cord	https://www.perle.com/products/10-100-1000-poe-media-converters.shtml	Media Converter: S-1110PP
05081122	S-1110PP-S2SC160 - 10/100/1000Base-T Media and Rate Converter with PoE+ (PoEP) Power Sourcing: 10/100/1000BASE-T (RJ-45) [100 m/328 ft.] to 1000BASE-EZX 1550 nm single mode (SC) [160 km/100 miles] Includes AC Power Adapter - EU Power Cord	https://www.perle.com/products/10-100-1000-poe-media-converters.shtml	Media Converter: S-1110PP
05081132	S-1110PP-S2ST160 - 10/100/1000Base-T Media and Rate Converter with PoE+ (PoEP) Power Sourcing: 10/100/1000BASE-T (RJ-45) [100 m/328 ft.] to 1000BASE-ZX 1550 nm single mode (ST) [160 km/100 miles] Includes AC Power Adapter - EU Power Cord	https://www.perle.com/products/10-100-1000-poe-media-converters.shtml	Media Converter: S-1110PP
05081142	S-1110PP-S1SC10U - 10/100/1000Base-T Media and Rate Converter with PoE+ (PoEP) Power Sourcing: 10/100/1000BASE-T (RJ-45) [100 m/328 ft.] to 1000BASE-BX 1310nm TX / 1490nm RX single strand fiber, single mode (SC) [10 km/6.2 miles] Includes AC Power Adapter - EU Power Cord	https://www.perle.com/products/10-100-1000-poe-media-converters.shtml	Media Converter: S-1110PP
05081152	S-1110PP-S1SC10D - 10/100/1000Base-T Media and Rate Converter with PoE+ (PoEP) Power Sourcing: 10/100/1000BASE-T (RJ-45) [100 m/328 ft.] to 1000BASE-BX 1490nm TX / 1310nm RX single strand fiber, single mode (SC) [10 km/6.2 miles] Includes AC Power Adapter - EU Power Cord	https://www.perle.com/products/10-100-1000-poe-media-converters.shtml	Media Converter: S-1110PP
05081162	S-1110PP-S1SC20U - 10/100/1000Base-T Media and Rate Converter with PoE+ (PoEP) Power Sourcing: 10/100/1000BASE-T (RJ-45) [100 m/328 ft.] to 1000BASE-BX 1310nm TX / 1490nm RX single strand fiber, single mode (SC) [20 km/12.4 miles] Includes AC Power Adapter - EU Power Cord	https://www.perle.com/products/10-100-1000-poe-media-converters.shtml	Media Converter: S-1110PP

Part #	Description	Product Datasheet	Product Group
05081172	S-1110PP-S1SC20D - 10/100/1000Base-T Media and Rate Converter with PoE+ (PoEP) Power Sourcing: 10/100/1000BASE-T (RJ-45) [100 m/328 ft.] to 1000BASE-BX 1490nm TX / 1310nm RX single strand fiber, single mode (SC) [20 km/12.4 miles] Includes AC Power Adapter - EU Power Cord	https://www.perle.com/products/10-100-1000-poe-media-converters.shtml	Media Converter: S-1110PP
05081182	S-1110PP-S1SC40U - 10/100/1000Base-T Media and Rate Converter with PoE+ (PoEP) Power Sourcing: 10/100/1000BASE-T (RJ-45) [100 m/328 ft.] to 1000BASE-BX 1310nm TX / 1490nm RX single strand fiber, single mode (SC) [40 km/25 miles] Includes AC Power Adapter - EU Power Cord	https://www.perle.com/products/10-100-1000-poe-media-converters.shtml	Media Converter: S-1110PP
05081192	S-1110PP-S1SC40D - 10/100/1000Base-T Media and Rate Converter with PoE+ (PoEP) Power Sourcing: 10/100/1000BASE-T (RJ-45) [100 m/328 ft.] to 1000BASE-BX 1490nm TX / 1310nm RX single strand fiber, single mode (SC) [40 km/25 miles] Includes AC Power Adapter - EU Power Cord	https://www.perle.com/products/10-100-1000-poe-media-converters.shtml	Media Converter: S-1110PP
05081202	S-1110PP-S1SC80U - 10/100/1000Base-T Media and Rate Converter with PoE+ (PoEP) Power Sourcing: 10/100/1000BASE-T (RJ-45) [100 m/328 ft.] to 1000BASE-BX 1510nm TX / 1590nm RX single strand fiber, single mode (SC) [80 km/50 miles] Includes AC Power Adapter - EU Power Cord	https://www.perle.com/products/10-100-1000-poe-media-converters.shtml	Media Converter: S-1110PP
05081212	S-1110PP-S1SC80D - 10/100/1000Base-T Media and Rate Converter with PoE+ (PoEP) Power Sourcing: 10/100/1000BASE-T (RJ-45) [100 m/328 ft.] to 1000BASE-BX 1590nm TX / 1510nm RX single strand fiber, single mode (SC) [80 km/50 miles] Includes AC Power Adapter - EU Power Cord	https://www.perle.com/products/10-100-1000-poe-media-converters.shtml	Media Converter: S-1110PP
05081222	S-1110PP-S1SC120U - 10/100/1000Base-T Media and Rate Converter with PoE+ (PoEP) Power Sourcing: 10/100/1000BASE-T (RJ-45) [100 m/328 ft.] to 1000BASE-BX 1510nm TX / 1590nm RX single strand fiber, single mode (SC) [120 km/75 miles] Includes AC Power Adapter - EU Power Cord	https://www.perle.com/products/10-100-1000-poe-media-converters.shtml	Media Converter: S-1110PP
05081232	S-1110PP-S1SC120D - 10/100/1000Base-T Media and Rate Converter with PoE+ (PoEP) Power Sourcing: 10/100/1000BASE-T (RJ-45) [100 m/328 ft.] to 1000BASE-BX 1590nm TX / 1510nm RX single strand fiber, single mode (SC) [120 km/75 miles] Includes AC Power Adapter - EU Power Cord	https://www.perle.com/products/10-100-1000-poe-media-converters.shtml	Media Converter: S-1110PP
05081242	S-1110PP-M2SC2 - 10/100/1000Base-T Media and Rate Converter with PoE+ (PoEP) Power Sourcing: 10/100/1000BASE-T (RJ-45) [100 m/328 ft.] to 1000BASE-LX 1310nm Extended multimode (SC) [2km /6562 ft.]. Includes AC Power Adapter - EU Power Cord	https://www.perle.com/products/10-100-1000-poe-media-converters.shtml	Media Converter: S-1110PP

Part #	Description	Product Datasheet	Product Group
05081252	S-1110PP-M2ST2 - 10/100/1000Base-T Media and Rate Converter with PoE+ (PoEP) Power Sourcing: 10/100/1000BASE-T (RJ-45) [100 m/328 ft.] to 1000BASE-LX 1310nm Extended multimode (ST) [2km /6562 ft.]. Includes AC Power Adapter - EU Power Cord	https://www.perle.com/products/10-100-1000-poe-media-converters.shtml	Media Converter: S-1110PP
05081262	S-1110PP-M1SC05U - 10/100/1000Base-T Media and Rate Converter with PoE+ (PoEP) Power Sourcing: 10/100/1000BASE-T (RJ-45) [100 m/328 ft.] to 1000BASE-BX 1310nm TX / 1550nm RX single strand fiber, multimode (SC) [500 m/1640 ft] Includes AC Power Adapter - EU Power Cord	https://www.perle.com/products/10-100-1000-poe-media-converters.shtml	Media Converter: S-1110PP
05081272	S-1110PP-M1SC05D - 10/100/1000Base-T Media and Rate Converter with PoE+ (PoEP) Power Sourcing: 10/100/1000BASE-T (RJ-45) [100 m/328 ft.] to 1000BASE-BX 1550nm TX / 1310nm RX single strand fiber, multimode (SC) [500 m/1640 ft] Includes AC Power Adapter - EU Power Cord	https://www.perle.com/products/10-100-1000-poe-media-converters.shtml	Media Converter: S-1110PP
05081282	S-110PP-S1ST20U - 10/100Base-TX Media and Rate Converter with PoE+ (PoEP) Power Sourcing: 10/100Base-TX (RJ-45) [100 m/328 ft.] to 100Base-BX 1310nm TX / 1550nm RX single strand fiber, single mode (ST) [20 km/12.4 miles] includes AC Power Adapter - EU Power Cord	https://www.perle.com/products/10-100-poe-media-converters.shtml	Media Converter: S-110PP
05081292	S-110PP-S1ST20D - 10/100Base-TX Media and Rate Converter with PoE+ (PoEP) Power Sourcing: 10/100Base-TX (RJ-45) [100 m/328 ft.] to 100Base-BX 1550nm TX / 1310nm RX single strand fiber, single mode (ST) [20 km/12.4 miles] includes AC Power Adapter - EU Power Cord	https://www.perle.com/products/10-100-poe-media-converters.shtml	Media Converter: S-110PP
05081302	S-110PP-M1ST2U - 10/100Base-TX Media and Rate Converter with PoE+ (PoEP) Power Sourcing: 10/100Base-TX (RJ-45) [100 m/328 ft.] to 100Base-BX 1310nm TX / 1550nm RX single strand fiber, multimode (ST) [2 km/1.2 miles] includes AC Power Adapter - EU Power Cord	https://www.perle.com/products/10-100-poe-media-converters.shtml	Media Converter: S-110PP
05081312	S-110PP-M1ST2D - 10/100Base-TX Media and Rate Converter with PoE+ (PoEP) Power Sourcing: 10/100Base-TX (RJ-45) [100 m/328 ft.] to 100Base-BX 1550nm TX / 1310nm RX single strand fiber, multimode (ST) [2 km/1.2 miles] includes AC Power Adapter - EU Power Cord	https://www.perle.com/products/10-100-poe-media-converters.shtml	Media Converter: S-110PP
05082002	S-1110DP-SFP - 10/100/1000Base-T Media and Rate Converter with PoE Power Sourcing: Dual 10/100/1000BASE-T (RJ-45) [100 m/328 ft.] to 1000BASE-X or 100BASE-X - SFP Slot (empty) Includes AC Power Adapter - EU Power Cord	https://www.perle.com/products/10-100-1000-poe-media-converters.shtml	Media Converter: S-1110P

Part #	Description	Product Datasheet	Product Group
05082012	S-1110DP-DSFP - 10/100/1000Base-T Media and Rate Converter with PoE Power Sourcing: Dual 10/100/1000BASE-T (RJ-45) [100 m/328 ft.] to 1000BASE-X or 100BASE-X - Dual SFP Slot (empty) Includes AC Power Adapter - EU Power Cord	https://www.perle.com/products/10-100-1000-poe-media-converters.shtml	Media Converter: S-1110P
05082022	S-1110DP-M2SC05 - 10/100/1000Base-T Media and Rate Converter with PoE Power Sourcing: Dual 10/100/1000BASE-T (RJ-45) [100 m/328 ft.] to 1000BASE-SX 850nm multimode (SC) [550 m/1804 ft.] Includes AC Power Adapter - EU Power Cord	https://www.perle.com/products/10-100-1000-poe-media-converters.shtml	Media Converter: S-1110P
05082032	S-1110DP-M2ST05 - 10/100/1000Base-T Media and Rate Converter with PoE Power Sourcing: Dual 10/100/1000BASE-T (RJ-45) [100 m/328 ft.] to 1000BASE-SX 850nm multimode (ST) [550 m/1804 ft.] Includes AC Power Adapter - EU Power Cord	https://www.perle.com/products/10-100-1000-poe-media-converters.shtml	Media Converter: S-1110P
05082042	S-1110DP-S2SC10 - 10/100/1000Base-T Media and Rate Converter with PoE Power Sourcing: Dual 10/100/1000BASE-T (RJ-45) [100 m/328 ft.] to 1000BASE-LX/LH 1310 nm single mode (SC) [10 km/6.2 miles] or multimode (SC) [550 m/1804 ft.] using a mode conditioning adapter. Includes AC Power Adapter - EU Power Cord	https://www.perle.com/products/10-100-1000-poe-media-converters.shtml	Media Converter: S-1110P
05082052	S-1110DP-S2ST10 - 10/100/1000Base-T Media and Rate Converter with PoE Power Sourcing: Dual 10/100/1000BASE-T (RJ-45) [100 m/328 ft.] to 1000BASE-LX/LH 1310 nm single mode (ST) [10 km/6.2 miles] Includes AC Power Adapter - EU Power Cord	https://www.perle.com/products/10-100-1000-poe-media-converters.shtml	Media Converter: S-1110P
05082062	S-1110DP-S2SC40 - 10/100/1000Base-T Media and Rate Converter with PoE Power Sourcing: Dual 10/100/1000BASE-T (RJ-45) [100 m/328 ft.] to 1000BASE-EX 1310 nm single mode (SC) [40 km/24.9 miles] Includes AC Power Adapter - EU Power Cord	https://www.perle.com/products/10-100-1000-poe-media-converters.shtml	Media Converter: S-1110P
05082072	S-1110DP-S2ST40 - 10/100/1000Base-T Media and Rate Converter with PoE Power Sourcing: Dual 10/100/1000BASE-T (RJ-45) [100 m/328 ft.] to 1000BASE-EX 1310 nm single mode (ST) [40 km/24.9 miles] Includes AC Power Adapter - EU Power Cord	https://www.perle.com/products/10-100-1000-poe-media-converters.shtml	Media Converter: S-1110P
05082082	S-1110DP-S2SC70 - 10/100/1000Base-T Media and Rate Converter with PoE Power Sourcing: Dual 10/100/1000BASE-T (RJ-45) [100 m/328 ft.] to 1000BASE-ZX 1550 nm single mode (SC) [70 km/43.5 miles] Includes AC Power Adapter - EU Power Cord	https://www.perle.com/products/10-100-1000-poe-media-converters.shtml	Media Converter: S-1110P

Part #	Description	Product Datasheet	Product Group
05082092	S-1110DP-S2ST70 - 10/100/1000Base-T Media and Rate Converter with PoE Power Sourcing: Dual 10/100/1000BASE-T (RJ-45) [100 m/328 ft.] to 1000BASE-ZX 1550 nm single mode (ST) [70 km/43.5 miles] Includes AC Power Adapter - EU Power Cord	https://www.perle.com/products/10-100-1000-poe-media-converters.shtml	Media Converter: S-1110P
05082102	S-1110DP-S2SC120 - 10/100/1000Base-T Media and Rate Converter with PoE Power Sourcing: Dual 10/100/1000BASE-T (RJ-45) [100 m/328 ft.] to 1000BASE-EZX 1550 nm single mode (SC) [120 km/74.6 miles] Includes AC Power Adapter - EU Power Cord	https://www.perle.com/products/10-100-1000-poe-media-converters.shtml	Media Converter: S-1110P
05082112	S-1110DP-S2ST120 - 10/100/1000Base-T Media and Rate Converter with PoE Power Sourcing: Dual 10/100/1000BASE-T (RJ-45) [100 m/328 ft.] to 1000BASE-ZX 1550 nm single mode (ST) [120 km/74.6 miles] Includes AC Power Adapter - EU Power Cord	https://www.perle.com/products/10-100-1000-poe-media-converters.shtml	Media Converter: S-1110P
05082122	S-1110DP-S2SC160 - 10/100/1000Base-T Media and Rate Converter with PoE Power Sourcing: Dual 10/100/1000BASE-T (RJ-45) [100 m/328 ft.] to 1000BASE-EZX 1550 nm single mode (SC) [160 km/100 miles] Includes AC Power Adapter - EU Power Cord	https://www.perle.com/products/10-100-1000-poe-media-converters.shtml	Media Converter: S-1110P
05082132	S-1110DP-S2ST160 - 10/100/1000Base-T Media and Rate Converter with PoE Power Sourcing: Dual 10/100/1000BASE-T (RJ-45) [100 m/328 ft.] to 1000BASE-ZX 1550 nm single mode (ST) [160 km/100 miles] Includes AC Power Adapter - EU Power Cord	https://www.perle.com/products/10-100-1000-poe-media-converters.shtml	Media Converter: S-1110P
05082142	S-1110DP-S1SC10U - 10/100/1000Base-T Media and Rate Converter with PoE Power Sourcing: Dual 10/100/1000BASE-T (RJ-45) [100 m/328 ft.] to 1000BASE-BX 1310nm TX / 1490nm RX single strand fiber, single mode (SC) [10 km/6.2 miles] Includes AC Power Adapter - EU Power Cord	https://www.perle.com/products/10-100-1000-poe-media-converters.shtml	Media Converter: S-1110P
05082152	S-1110DP-S1SC10D - 10/100/1000Base-T Media and Rate Converter with PoE Power Sourcing: Dual 10/100/1000BASE-T (RJ-45) [100 m/328 ft.] to 1000BASE-BX 1490nm TX / 1310nm RX single strand fiber, single mode (SC) [10 km/6.2 miles] Includes AC Power Adapter - EU Power Cord	https://www.perle.com/products/10-100-1000-poe-media-converters.shtml	Media Converter: S-1110P
05082162	S-1110DP-S1SC20U - 10/100/1000Base-T Media and Rate Converter with PoE Power Sourcing: Dual 10/100/1000BASE-T (RJ-45) [100 m/328 ft.] to 1000BASE-BX 1310nm TX / 1490nm RX single strand fiber, single mode (SC) [20 km/12.4 miles] Includes AC Power Adapter - EU Power Cord	https://www.perle.com/products/10-100-1000-poe-media-converters.shtml	Media Converter: S-1110P

Part #	Description	Product Datasheet	Product Group
05082172	S-1110DP-S1SC20D - 10/100/1000Base-T Media and Rate Converter with PoE Power Sourcing: Dual 10/100/1000BASE-T (RJ-45) [100 m/328 ft.] to 1000BASE-BX 1490nm TX / 1310nm RX single strand fiber, single mode (SC) [20 km/12.4 miles] Includes AC Power Adapter - EU Power Cord	https://www.perle.com/products/10-100-1000-poe-media-converters.shtml	Media Converter: S-1110P
05082182	S-1110DP-S1SC40U - 10/100/1000Base-T Media and Rate Converter with PoE Power Sourcing: Dual 10/100/1000BASE-T (RJ-45) [100 m/328 ft.] to 1000BASE-BX 1310nm TX / 1490nm RX single strand fiber, single mode (SC) [40 km/25 miles] Includes AC Power Adapter - EU Power Cord	https://www.perle.com/products/10-100-1000-poe-media-converters.shtml	Media Converter: S-1110P
05082192	S-1110DP-S1SC40D - 10/100/1000Base-T Media and Rate Converter with PoE Power Sourcing: Dual 10/100/1000BASE-T (RJ-45) [100 m/328 ft.] to 1000BASE-BX 1490nm TX / 1310nm RX single strand fiber, single mode (SC) [40 km/25 miles] Includes AC Power Adapter - EU Power Cord	https://www.perle.com/products/10-100-1000-poe-media-converters.shtml	Media Converter: S-1110P
05082202	S-1110DP-S1SC80U - 10/100/1000Base-T Media and Rate Converter with PoE Power Sourcing: Dual 10/100/1000BASE-T (RJ-45) [100 m/328 ft.] to 1000BASE-BX 1510nm TX / 1590nm RX single strand fiber, single mode (SC) [80 km/50 miles] Includes AC Power Adapter - EU Power Cord	https://www.perle.com/products/10-100-1000-poe-media-converters.shtml	Media Converter: S-1110P
05082212	S-1110DP-S1SC80D - 10/100/1000Base-T Media and Rate Converter with PoE Power Sourcing: Dual 10/100/1000BASE-T (RJ-45) [100 m/328 ft.] to 1000BASE-BX 1590nm TX / 1510nm RX single strand fiber, single mode (SC) [80 km/50 miles] Includes AC Power Adapter - EU Power Cord	https://www.perle.com/products/10-100-1000-poe-media-converters.shtml	Media Converter: S-1110P
05082222	S-1110DP-S1SC120U - 10/100/1000Base-T Media and Rate Converter with PoE Power Sourcing: Dual 10/100/1000BASE-T (RJ-45) [100 m/328 ft.] to 1000BASE-BX 1510nm TX / 1590nm RX single strand fiber, single mode (SC) [120 km/75 miles] Includes AC Power Adapter - EU Power Cord	https://www.perle.com/products/10-100-1000-poe-media-converters.shtml	Media Converter: S-1110P
05082232	S-1110DP-S1SC120D - 10/100/1000Base-T Media and Rate Converter with PoE Power Sourcing: Dual 10/100/1000BASE-T (RJ-45) [100 m/328 ft.] to 1000BASE-BX 1590nm TX / 1510nm RX single strand fiber, single mode (SC) [120 km/75 miles] Includes AC Power Adapter - EU Power Cord	https://www.perle.com/products/10-100-1000-poe-media-converters.shtml	Media Converter: S-1110P
05082242	S-1110DP-M2SC2 - 10/100/1000Base-T Media and Rate Converter with PoE Power Sourcing: Dual 10/100/1000BASE-T (RJ-45) [100 m/328 ft.] to 1000BASE-LX 1310nm Extended multimode (SC) [2km /6562 ft.]. Includes AC Power Adapter - EU Power Cord	https://www.perle.com/products/10-100-1000-poe-media-converters.shtml	Media Converter: S-1110P

Part #	Description	Product Datasheet	Product Group
05082252	S-1110DP-M2ST2 - 10/100/1000Base-T Media and Rate Converter with PoE Power Sourcing: Dual 10/100/1000BASE-T (RJ-45) [100 m/328 ft.] to 1000BASE-LX 1310nm Extended multimode (ST) [2km /6562 ft.]. Includes AC Power Adapter - EU Power Cord	https://www.perle.com/products/10-100-1000-poe-media-converters.shtml	Media Converter: S-1110P
05082262	S-1110DP-M1SC05U - 10/100/1000Base-T Media and Rate Converter with PoE Power Sourcing: Dual 10/100/1000BASE-T (RJ-45) [100 m/328 ft.] to 1000BASE-BX 1310nm TX / 1550nm RX single strand fiber, multimode (SC) [500 m/1640 ft] Includes AC Power Adapter - EU Power Cord	https://www.perle.com/products/10-100-1000-poe-media-converters.shtml	Media Converter: S-1110P
05082272	S-1110DP-M1SC05D - 10/100/1000Base-T Media and Rate Converter with PoE Power Sourcing: Dual 10/100/1000BASE-T (RJ-45) [100 m/328 ft.] to 1000BASE-BX 1550nm TX / 1310nm RX single strand fiber, multimode (SC) [500 m/1640 ft] Includes AC Power Adapter - EU Power Cord	https://www.perle.com/products/10-100-1000-poe-media-converters.shtml	Media Converter: S-1110P
05083002	S-1110DPP-SFP - 10/100/1000BaseT Media and Rate Converter with PoE+ (PoEP) Power Sourcing: Dual 10/100/1000BASE-T (RJ-45) [100 m/328 ft.] to 1000BASE-X or 100BASE-X - SFP Slot (empty) Includes AC Power Adapter - EU Power Cord	https://www.perle.com/products/10-100-1000-poe-media-converters.shtml	Media Converter: S-1110PP
05083012	S-1110DPP-DSFP - 10/100/1000BaseT Media and Rate Converter with PoE+ (PoEP) Power Sourcing: Dual 10/100/1000BASE-T (RJ-45) [100 m/328 ft.] to 1000BASE-X or 100BASE-X - Dual SFP Slot (empty) Includes AC Power Adapter - EU Power Cord	https://www.perle.com/products/10-100-1000-poe-media-converters.shtml	Media Converter: S-1110PP
05083022	S-1110DPP-M2SC05 - 10/100/1000BaseT Media and Rate Converter with PoE+ (PoEP) Power Sourcing: Dual 10/100/1000BASE-T (RJ-45) [100 m/328 ft.] to 1000BASE-SX 850nm multimode (SC) [550 m/1804 ft.] Includes AC Power Adapter - EU Power Cord	https://www.perle.com/products/10-100-1000-poe-media-converters.shtml	Media Converter: S-1110PP
05083032	S-1110DPP-M2ST05 - 10/100/1000BaseT Media and Rate Converter with PoE+ (PoEP) Power Sourcing: Dual 10/100/1000BASE-T (RJ-45) [100 m/328 ft.] to 1000BASE-SX 850nm multimode (ST) [550 m/1804 ft.] Includes AC Power Adapter - EU Power Cord	https://www.perle.com/products/10-100-1000-poe-media-converters.shtml	Media Converter: S-1110PP
05083042	S-1110DPP-S2SC10 - 10/100/1000BaseT Media and Rate Converter with PoE+ (PoEP) Power Sourcing: Dual 10/100/1000BASE-T (RJ-45) [100 m/328 ft.] to 1000BASE-LX/LH 1310 nm single mode (SC) [10 km/6.2 miles] or multimode (SC) [550 m/1804 ft.] using a mode conditioning adapter. Includes AC Power Adapter - EU Power Cord	https://www.perle.com/products/10-100-1000-poe-media-converters.shtml	Media Converter: S-1110PP

Part #	Description	Product Datasheet	Product Group
05083052	S-1110DPP-S2ST10 - 10/100/1000BaseT Media and Rate Converter with PoE+ (PoEP) Power Sourcing: Dual 10/100/1000BASE-T (RJ-45) [100 m/328 ft.] to 1000BASE-LX/LH 1310 nm single mode (ST) [10 km/6.2 miles] Includes AC Power Adapter - EU Power Cord	https://www.perle.com/products/10-100-1000-poe-media-converters.shtml	Media Converter: S-1110PP
05083062	S-1110DPP-S2SC40 - 10/100/1000BaseT Media and Rate Converter with PoE+ (PoEP) Power Sourcing: Dual 10/100/1000BASE-T (RJ-45) [100 m/328 ft.] to 1000BASE-EX 1310 nm single mode (SC) [40 km/24.9 miles] Includes AC Power Adapter - EU Power Cord	https://www.perle.com/products/10-100-1000-poe-media-converters.shtml	Media Converter: S-1110PP
05083072	S-1110DPP-S2ST40 - 10/100/1000BaseT Media and Rate Converter with PoE+ (PoEP) Power Sourcing: Dual 10/100/1000BASE-T (RJ-45) [100 m/328 ft.] to 1000BASE-EX 1310 nm single mode (ST) [40 km/24.9 miles] Includes AC Power Adapter - EU Power Cord	https://www.perle.com/products/10-100-1000-poe-media-converters.shtml	Media Converter: S-1110PP
05083082	S-1110DPP-S2SC70 - 10/100/1000BaseT Media and Rate Converter with PoE+ (PoEP) Power Sourcing: Dual 10/100/1000BASE-T (RJ-45) [100 m/328 ft.] to 1000BASE-ZX 1550 nm single mode (SC) [70 km/43.5 miles] Includes AC Power Adapter - EU Power Cord	https://www.perle.com/products/10-100-1000-poe-media-converters.shtml	Media Converter: S-1110PP
05083092	S-1110DPP-S2ST70 - 10/100/1000BaseT Media and Rate Converter with PoE+ (PoEP) Power Sourcing: Dual 10/100/1000BASE-T (RJ-45) [100 m/328 ft.] to 1000BASE-ZX 1550 nm single mode (ST) [70 km/43.5 miles] Includes AC Power Adapter - EU Power Cord	https://www.perle.com/products/10-100-1000-poe-media-converters.shtml	Media Converter: S-1110PP
05083102	S-1110DPP-S2SC120 - 10/100/1000BaseT Media and Rate Converter with PoE+ (PoEP) Power Sourcing: Dual 10/100/1000BASE-T (RJ-45) [100 m/328 ft.] to 1000BASE-EZX 1550 nm single mode (SC) [120 km/74.6 miles] Includes AC Power Adapter - EU Power Cord	https://www.perle.com/products/10-100-1000-poe-media-converters.shtml	Media Converter: S-1110PP
05083112	S-1110DPP-S2ST120 - 10/100/1000BaseT Media and Rate Converter with PoE+ (PoEP) Power Sourcing: Dual 10/100/1000BASE-T (RJ-45) [100 m/328 ft.] to 1000BASE-ZX 1550 nm single mode (ST) [120 km/74.6 miles] Includes AC Power Adapter - EU Power Cord	https://www.perle.com/products/10-100-1000-poe-media-converters.shtml	Media Converter: S-1110PP
05083122	S-1110DPP-S2SC160 - 10/100/1000BaseT Media and Rate Converter with PoE+ (PoEP) Power Sourcing: Dual 10/100/1000BASE-T (RJ-45) [100 m/328 ft.] to 1000BASE-EZX 1550 nm single mode (SC) [160 km/100 miles] Includes AC Power Adapter - EU Power Cord	https://www.perle.com/products/10-100-1000-poe-media-converters.shtml	Media Converter: S-1110PP

Part #	Description	Product Datasheet	Product Group
05083132	S-1110DPP-S2ST160 - 10/100/1000BaseT Media and Rate Converter with PoE+ (PoEP) Power Sourcing: Dual 10/100/1000BASE-T (RJ-45) [100 m/328 ft.] to 1000BASE-ZX 1550 nm single mode (ST) [160 km/100 miles] Includes AC Power Adapter - EU Power Cord	https://www.perle.com/products/10-100-1000-poe-media-converters.shtml	Media Converter: S-1110PP
05083142	S-1110DPP-S1SC10U - 10/100/1000BaseT Media and Rate Converter with PoE+ (PoEP) Power Sourcing: Dual 10/100/1000BASE-T (RJ-45) [100 m/328 ft.] to 1000BASE-BX 1310nm TX / 1490nm RX single strand fiber, single mode (SC) [10 km/6.2 miles] Includes AC Power Adapter - EU Power Cord	https://www.perle.com/products/10-100-1000-poe-media-converters.shtml	Media Converter: S-1110PP
05083152	S-1110DPP-S1SC10D - 10/100/1000BaseT Media and Rate Converter with PoE+ (PoEP) Power Sourcing: Dual 10/100/1000BASE-T (RJ-45) [100 m/328 ft.] to 1000BASE-BX 1490nm TX / 1310nm RX single strand fiber, single mode (SC) [10 km/6.2 miles] Includes AC Power Adapter - EU Power Cord	https://www.perle.com/products/10-100-1000-poe-media-converters.shtml	Media Converter: S-1110PP
05083162	S-1110DPP-S1SC20U - 10/100/1000BaseT Media and Rate Converter with PoE+ (PoEP) Power Sourcing: Dual 10/100/1000BASE-T (RJ-45) [100 m/328 ft.] to 1000BASE-BX 1310nm TX / 1490nm RX single strand fiber, single mode (SC) [20 km/12.4 miles] Includes AC Power Adapter - EU Power Cord	https://www.perle.com/products/10-100-1000-poe-media-converters.shtml	Media Converter: S-1110PP
05083172	S-1110DPP-S1SC20D - 10/100/1000BaseT Media and Rate Converter with PoE+ (PoEP) Power Sourcing: Dual 10/100/1000BASE-T (RJ-45) [100 m/328 ft.] to 1000BASE-BX 1490nm TX / 1310nm RX single strand fiber, single mode (SC) [20 km/12.4 miles] Includes AC Power Adapter - EU Power Cord	https://www.perle.com/products/10-100-1000-poe-media-converters.shtml	Media Converter: S-1110PP
05083182	S-1110DPP-S1SC40U - 10/100/1000BaseT Media and Rate Converter with PoE+ (PoEP) Power Sourcing: Dual 10/100/1000BASE-T (RJ-45) [100 m/328 ft.] to 1000BASE-BX 1310nm TX / 1490nm RX single strand fiber, single mode (SC) [40 km/25 miles] Includes AC Power Adapter - EU Power Cord	https://www.perle.com/products/10-100-1000-poe-media-converters.shtml	Media Converter: S-1110PP
05083192	S-1110DPP-S1SC40D - 10/100/1000BaseT Media and Rate Converter with PoE+ (PoEP) Power Sourcing: Dual 10/100/1000BASE-T (RJ-45) [100 m/328 ft.] to 1000BASE-BX 1490nm TX / 1310nm RX single strand fiber, single mode (SC) [40 km/25 miles] Includes AC Power Adapter - EU Power Cord	https://www.perle.com/products/10-100-1000-poe-media-converters.shtml	Media Converter: S-1110PP

Part #	Description	Product Datasheet	Product Group
05083202	S-1110DPP-S1SC80U - 10/100/1000BaseT Media and Rate Converter with PoE+ (PoEP) Power Sourcing: Dual 10/100/1000BASE-T (RJ-45) [100 m/328 ft.] to 1000BASE-BX 1510nm TX / 1590nm RX single strand fiber, single mode (SC) [80 km/50 miles] Includes AC Power Adapter - EU Power Cord	https://www.perle.com/products/10-100-1000-poe-media-converters.shtml	Media Converter: S-1110PP
05083212	S-1110DPP-S1SC80D - 10/100/1000BaseT Media and Rate Converter with PoE+ (PoEP) Power Sourcing: Dual 10/100/1000BASE-T (RJ-45) [100 m/328 ft.] to 1000BASE-BX 1590nm TX / 1510nm RX single strand fiber, single mode (SC) [80 km/50 miles] Includes AC Power Adapter - EU Power Cord	https://www.perle.com/products/10-100-1000-poe-media-converters.shtml	Media Converter: S-1110PP
05083222	S-1110DPP-S1SC120U - 10/100/1000BaseT Media and Rate Converter with PoE+ (PoEP) Power Sourcing: Dual 10/100/1000BASE-T (RJ-45) [100 m/328 ft.] to 1000BASE-BX 1510nm TX / 1590nm RX single strand fiber, single mode (SC) [120 km/75 miles] Includes AC Power Adapter - EU Power Cord	https://www.perle.com/products/10-100-1000-poe-media-converters.shtml	Media Converter: S-1110PP
05083232	S-1110DPP-S1SC120D - 10/100/1000BaseT Media and Rate Converter with PoE+ (PoEP) Power Sourcing: Dual 10/100/1000BASE-T (RJ-45) [100 m/328 ft.] to 1000BASE-BX 1590nm TX / 1510nm RX single strand fiber, single mode (SC) [120 km/75 miles] Includes AC Power Adapter - EU Power Cord	https://www.perle.com/products/10-100-1000-poe-media-converters.shtml	Media Converter: S-1110PP
05083242	S-1110DPP-M2SC2 - 10/100/1000BaseT Media and Rate Converter with PoE+ (PoEP) Power Sourcing: Dual 10/100/1000BASE-T (RJ-45) [100 m/328 ft.] to 1000BASE-LX 1310nm Extended multimode (SC) [2km /6562 ft.]. Includes AC Power Adapter - EU Power Cord	https://www.perle.com/products/10-100-1000-poe-media-converters.shtml	Media Converter: S-1110PP
05083252	S-1110DPP-M2ST2 - 10/100/1000BaseT Media and Rate Converter with PoE+ (PoEP) Power Sourcing: Dual 10/100/1000BASE-T (RJ-45) [100 m/328 ft.] to 1000BASE-LX 1310nm Extended multimode (ST) [2km /6562 ft.]. Includes AC Power Adapter - EU Power Cord	https://www.perle.com/products/10-100-1000-poe-media-converters.shtml	Media Converter: S-1110PP
05083262	S-1110DPP-M1SC05U - 10/100/1000BaseT Media and Rate Converter with PoE+ (PoEP) Power Sourcing: Dual 10/100/1000BASE-T (RJ-45) [100 m/328 ft.] to 1000BASE-BX 1310nm TX / 1550nm RX single strand fiber, multimode (SC) [500 m/1640 ft] Includes AC Power Adapter - EU Power Cord	https://www.perle.com/products/10-100-1000-poe-media-converters.shtml	Media Converter: S-1110PP

Part #	Description	Product Datasheet	Product Group
05083272	S-1110DPP-M1SC05D - 10/100/1000BaseT Media and Rate Converter with PoE+ (PoEP) Power Sourcing: Dual 10/100/1000BASE-T (RJ-45) [100 m/328 ft.] to 1000BASE-BX 1550nm TX / 1310nm RX single strand fiber, multimode (SC) [500 m/1640 ft] Includes AC Power Adapter - EU Power Cord	https://www.perle.com/products/10-100-1000-poe-media-converters.shtml	Media Converter: S-1110PP
05084002	S-110P-SFP - 10/100Base-TX Media Rate Converter with PoE Power Sourcing: 10/100BASE-TX (RJ-45) [100 m/328 ft.] to 100BASE-X - SFP Slot (empty) Includes AC Power Adapter - EU Power Cord	https://www.perle.com/products/10-100-poe-media-converters.shtml	Media Converter: S-110P
05084012	S-110P-M2SC2 - 10/100Base-TX Media and Rate Converter with PoE Power Sourcing: 10/100Base-TX (RJ-45) [100 m/328 ft.] to 100BASE-FX 1310nm multimode (SC) [2 km/1.2 miles] includes AC Power Adapter - EU Power Cord	https://www.perle.com/products/10-100-poe-media-converters.shtml	Media Converter: S-110P
05084022	S-110P-M2ST2 - 10/100Base-TX Media and Rate Converter with PoE Power Sourcing: 10/100Base-TX (RJ-45) [100 m/328 ft.] to 100BASE-FX 1310nm multimode (ST) [2 km/1.2 miles] includes AC Power Adapter - EU Power Cord	https://www.perle.com/products/10-100-poe-media-converters.shtml	Media Converter: S-110P
05084032	S-110P-S2SC20 - 10/100Base-TX Media and Rate Converter with PoE Power Sourcing: 10/100Base-TX (RJ-45) [100 m/328 ft.] to 100Base-LX 1310nm single mode (SC) [20 km/12.4 miles] includes AC Power Adapter - EU Power Cord	https://www.perle.com/products/10-100-poe-media-converters.shtml	Media Converter: S-110P
05084042	S-110P-S2ST20 - 10/100Base-TX Media and Rate Converter with PoE Power Sourcing: 10/100Base-TX (RJ-45) [100 m/328 ft.] to 100Base-LX 1310nm single mode (ST) [20 km/12.4 miles] includes AC Power Adapter - EU Power Cord	https://www.perle.com/products/10-100-poe-media-converters.shtml	Media Converter: S-110P
05084052	S-110P-S2SC40 - 10/100Base-TX Media and Rate Converter with PoE Power Sourcing: 10/100Base-TX (RJ-45) [100 m/328 ft.] to 100Base-EX 1310nm single mode (SC) [40 km/24.9 miles] includes AC Power Adapter - EU Power Cord	https://www.perle.com/products/10-100-poe-media-converters.shtml	Media Converter: S-110P
05084062	S-110P-S2ST40 - 10/100Base-TX Media and Rate Converter with PoE Power Sourcing: 10/100Base-TX (RJ-45) [100 m/328 ft.] to 100Base-EX 1310nm single mode (ST) [40 km/24.9 miles] includes AC Power Adapter - EU Power Cord	https://www.perle.com/products/10-100-poe-media-converters.shtml	Media Converter: S-110P

Part #	Description	Product Datasheet	Product Group
05084072	S-110P-S2SC80 - 10/100Base-TX Media and Rate Converter with PoE Power Sourcing: 10/100Base-TX (RJ-45) [100 m/328 ft.] to 100Base-ZX 1550nm single mode (SC) [80 km/49.7 miles] includes AC Power Adapter - EU Power Cord	https://www.perle.com/products/10-100-poe-media-converters.shtml	Media Converter: S-110P
05084082	S-110P-S2ST80 - 10/100Base-TX Media and Rate Converter with PoE Power Sourcing: 10/100Base-TX (RJ-45) [100 m/328 ft.] to 100Base-ZX 1550nm single mode (ST) [80 km/49.7 miles] includes AC Power Adapter - EU Power Cord	https://www.perle.com/products/10-100-poe-media-converters.shtml	Media Converter: S-110P
05084092	S-110P-S2SC120 - 10/100Base-TX Media and Rate Converter with PoE Power Sourcing: 10/100Base-TX (RJ-45) [100 m/328 ft.] to 100Base-ZX 1550nm single mode (SC) [120 km/74.6 miles] includes AC Power Adapter - EU Power Cord	https://www.perle.com/products/10-100-poe-media-converters.shtml	Media Converter: S-110P
05084102	S-110P-S2ST120 - 10/100Base-TX Media and Rate Converter with PoE Power Sourcing: 10/100Base-TX (RJ-45) [100 m/328 ft.] to 100Base-ZX 1550nm single mode (ST) [120 km/74.6 miles] includes AC Power Adapter - EU Power Cord	https://www.perle.com/products/10-100-poe-media-converters.shtml	Media Converter: S-110P
05084112	S-110P-S1SC20U - 10/100Base-TX Media and Rate Converter with PoE Power Sourcing: 10/100Base-TX (RJ-45) [100 m/328 ft.] to 100Base-BX 1310nm TX / 1550nm RX single strand fiber, single mode (SC) [20 km/12.4 miles] includes AC Power Adapter - EU Power Cord	https://www.perle.com/products/10-100-poe-media-converters.shtml	Media Converter: S-110P
05084122	S-110P-S1SC20D - 10/100Base-TX Media and Rate Converter with PoE Power Sourcing: 10/100Base-TX (RJ-45) [100 m/328 ft.] to 100Base-BX 1550nm TX / 1310nm RX single strand fiber, single mode (SC) [20 km/12.4 miles] includes AC Power Adapter - EU Power Cord	https://www.perle.com/products/10-100-poe-media-converters.shtml	Media Converter: S-110P
05084132	S-110P-S1SC40U - 10/100Base-TX Media and Rate Converter with PoE Power Sourcing: 10/100Base-TX (RJ-45) [100 m/328 ft.] to 100Base-BX 1310nm TX / 1550nm RX single strand fiber, single mode (SC) [40 km/24.9 miles] includes AC Power Adapter - EU Power Cord	https://www.perle.com/products/10-100-poe-media-converters.shtml	Media Converter: S-110P
05084142	S-110P-S1SC40D - 10/100Base-TX Media and Rate Converter with PoE Power Sourcing: 10/100Base-TX (RJ-45) [100 m/328 ft.] to 100Base-BX 1550nm TX / 1310nm RX single strand fiber, single mode (SC) [40 km/24.9 miles] includes AC Power Adapter - EU Power Cord	https://www.perle.com/products/10-100-poe-media-converters.shtml	Media Converter: S-110P

Part #	Description	Product Datasheet	Product Group
05084152	S-110P-M1SC2U - 10/100Base-TX Media and Rate Converter with PoE Power Sourcing: 10/100Base-TX (RJ-45) [100 m/328 ft.] to 100Base-BX 1310nm TX / 1550nm RX single strand fiber, multimode (SC) [2 km/1.2 miles] includes AC Power Adapter - EU Power Cord	https://www.perle.com/products/10-100-poe-media-converters.shtml	Media Converter: S-110P
05084162	S-110P-M1SC2D - 10/100Base-TX Media and Rate Converter with PoE Power Sourcing: 10/100Base-TX (RJ-45) [100 m/328 ft.] to 100Base-BX 1550nm TX / 1310nm RX single strand fiber, multimode (SC) [2 km/1.2 miles] includes AC Power Adapter - EU Power Cord	https://www.perle.com/products/10-100-poe-media-converters.shtml	Media Converter: S-110P
05085002	S-110PP-SFP - 10/100Base-TX Media and Rate Converter with PoE+ (PoEP) Power Sourcing: 10/100BASE-TX (RJ-45) [100 m/328 ft.] to 100BASE-X - SFP Slot (empty) Includes AC Power Adapter - EU Power Cord	https://www.perle.com/products/10-100-poe-media-converters.shtml	Media Converter: S-110PP
05085012	S-110PP-M2SC2 - 10/100Base-TX Media and Rate Converter with PoE+ (PoEP) Power Sourcing: 10/100Base-TX (RJ-45) [100 m/328 ft.] to 100BASE-FX 1310nm multimode (SC) [2 km/1.2 miles] includes AC Power Adapter - EU Power Cord	https://www.perle.com/products/10-100-poe-media-converters.shtml	Media Converter: S-110PP
05085022	S-110PP-M2ST2 - 10/100Base-TX Media and Rate Converter with PoE+ (PoEP) Power Sourcing: 10/100Base-TX (RJ-45) [100 m/328 ft.] to 100BASE-FX 1310nm multimode (ST) [2 km/1.2 miles] includes AC Power Adapter - EU Power Cord	https://www.perle.com/products/10-100-poe-media-converters.shtml	Media Converter: S-110PP
05085032	S-110PP-S2SC20 - 10/100Base-TX Media and Rate Converter with PoE+ (PoEP) Power Sourcing: 10/100Base-TX (RJ-45) [100 m/328 ft.] to 100Base-LX 1310nm single mode (SC) [20 km/12.4 miles] includes AC Power Adapter - EU Power Cord	https://www.perle.com/products/10-100-poe-media-converters.shtml	Media Converter: S-110PP
05085042	S-110PP-S2ST20 - 10/100Base-TX Media and Rate Converter with PoE+ (PoEP) Power Sourcing: 10/100Base-TX (RJ-45) [100 m/328 ft.] to 100Base-LX 1310nm single mode (ST) [20 km/12.4 miles] includes AC Power Adapter - EU Power Cord	https://www.perle.com/products/10-100-poe-media-converters.shtml	Media Converter: S-110PP
05085052	S-110PP-S2SC40 - 10/100Base-TX Media and Rate Converter with PoE+ (PoEP) Power Sourcing: 10/100Base-TX (RJ-45) [100 m/328 ft.] to 100Base-EX 1310nm single mode (SC) [40 km/24.9 miles] includes AC Power Adapter - EU Power Cord	https://www.perle.com/products/10-100-poe-media-converters.shtml	Media Converter: S-110PP
05085062	S-110PP-S2ST40 - 10/100Base-TX Media and Rate Converter with PoE+ (PoEP) Power Sourcing: 10/100Base-TX (RJ-45) [100 m/328 ft.] to 100Base-EX 1310nm single mode (ST) [40 km/24.9 miles] includes AC Power Adapter - EU Power Cord	https://www.perle.com/products/10-100-poe-media-converters.shtml	Media Converter: S-110PP

Part #	Description	Product Datasheet	Product Group
05085072	S-110PP-S2SC80 - 10/100Base-TX Media and Rate Converter with PoE+ (PoEP) Power Sourcing: 10/100Base-TX (RJ-45) [100 m/328 ft.] to 100Base-ZX 1550nm single mode (SC) [80 km/49.7 miles] includes AC Power Adapter - EU Power Cord	https://www.perle.com/products/10-100-poe-media-converters.shtml	Media Converter: S-110PP
05085082	S-110PP-S2ST80 - 10/100Base-TX Media and Rate Converter with PoE+ (PoEP) Power Sourcing: 10/100Base-TX (RJ-45) [100 m/328 ft.] to 100Base-ZX 1550nm single mode (ST) [80 km/49.7 miles] includes AC Power Adapter - EU Power Cord	https://www.perle.com/products/10-100-poe-media-converters.shtml	Media Converter: S-110PP
05085092	S-110PP-S2SC120 - 10/100Base-TX Media and Rate Converter with PoE+ (PoEP) Power Sourcing: 10/100Base-TX (RJ-45) [100 m/328 ft.] to 100Base-ZX 1550nm single mode (SC) [120 km/74.6 miles] includes AC Power Adapter - EU Power Cord	https://www.perle.com/products/10-100-poe-media-converters.shtml	Media Converter: S-110PP
05085102	S-110PP-S2ST120 - 10/100Base-TX Media and Rate Converter with PoE+ (PoEP) Power Sourcing: 10/100Base-TX (RJ-45) [100 m/328 ft.] to 100Base-ZX 1550nm single mode (ST) [120 km/74.6 miles] includes AC Power Adapter - EU Power Cord	https://www.perle.com/products/10-100-poe-media-converters.shtml	Media Converter: S-110PP
05085112	S-110PP-S1SC20U - 10/100Base-TX Media and Rate Converter with PoE+ (PoEP) Power Sourcing: 10/100Base-TX (RJ-45) [100 m/328 ft.] to 100Base-BX 1310nm TX / 1550nm RX single strand fiber, single mode (SC) [20 km/12.4 miles] includes AC Power Adapter - EU Power Cord	https://www.perle.com/products/10-100-poe-media-converters.shtml	Media Converter: S-110PP
05085122	S-110PP-S1SC20D - 10/100Base-TX Media and Rate Converter with PoE+ (PoEP) Power Sourcing: 10/100Base-TX (RJ-45) [100 m/328 ft.] to 100Base-BX 1550nm TX / 1310nm RX single strand fiber, single mode (SC) [20 km/12.4 miles] includes AC Power Adapter - EU Power Cord	https://www.perle.com/products/10-100-poe-media-converters.shtml	Media Converter: S-110PP
05085132	S-110PP-S1SC40U - 10/100Base-TX Media and Rate Converter with PoE+ (PoEP) Power Sourcing: 10/100Base-TX (RJ-45) [100 m/328 ft.] to 100Base-BX 1310nm TX / 1550nm RX single strand fiber, single mode (SC) [40 km/24.9 miles] includes AC Power Adapter - EU Power Cord	https://www.perle.com/products/10-100-poe-media-converters.shtml	Media Converter: S-110PP
05085142	S-110PP-S1SC40D - 10/100Base-TX Media and Rate Converter with PoE+ (PoEP) Power Sourcing: 10/100Base-TX (RJ-45) [100 m/328 ft.] to 100Base-BX 1550nm TX / 1310nm RX single strand fiber, single mode (SC) [40 km/24.9 miles] includes AC Power Adapter - EU Power Cord	https://www.perle.com/products/10-100-poe-media-converters.shtml	Media Converter: S-110PP

Part #	Description	Product Datasheet	Product Group
05085152	S-110PP-M1SC2U - 10/100Base-TX Media and Rate Converter with PoE+ (PoEP) Power Sourcing: 10/100Base-TX (RJ-45) [100 m/328 ft.] to 100Base-BX 1310nm TX / 1550nm RX single strand fiber, multimode (SC) [2 km/1.2 miles] includes AC Power Adapter - EU Power Cord	https://www.perle.com/products/10-100-poe-media-converters.shtml	Media Converter: S-110PP
05085162	S-110PP-M1SC2D - 10/100Base-TX Media and Rate Converter with PoE+ (PoEP) Power Sourcing: 10/100Base-TX (RJ-45) [100 m/328 ft.] to 100Base-BX 1550nm TX / 1310nm RX single strand fiber, multimode (SC) [2 km/1.2 miles] includes AC Power Adapter - EU Power Cord	https://www.perle.com/products/10-100-poe-media-converters.shtml	Media Converter: S-110PP
05090000	S-110-M2SC2-XT - 10/100Base-TX Industrial Temperature Media Rate Converter: 10/100Base-TX (RJ-45) [100 m/328 ft.] to 100BASE-FX 1310nm multimode (SC) [2 km/1.2 miles]. Extended Temperature, terminal block power connector for external power source	https://www.perle.com/products/10-100-industrial-converters.shtml	Media Converter: S-110
05090010	S-110-M2ST2-XT - 10/100Base-TX Industrial Temperature Media Rate Converter: 10/100Base-TX (RJ-45) [100 m/328 ft.] to 100BASE-FX 1310nm multimode (ST) [2 km/1.2 miles]. Extended Temperature, terminal block power connector for external power source	https://www.perle.com/products/10-100-industrial-converters.shtml	Media Converter: S-110
05090020	S-110-M2LC2-XT - 10/100Base-TX Industrial Temperature Media Rate Converter: 10/100Base-TX (RJ-45) [100 m/328 ft.] to 100BASE-FX 1310nm multimode (LC) [2 km/1.2 miles]. Extended Temperature, terminal block power connector for external power source	https://www.perle.com/products/10-100-industrial-converters.shtml	Media Converter: S-110
05090030	S-110-S2SC20-XT 10/100Base-TX Industrial Temperature Media and Rate Converter: 10/100Base-TX (RJ-45) [100 m/328 ft.] to 100Base-LX 1310nm single mode (SC) [20 km/12.4 miles]. Extended Temperature, terminal block power connector for external power source.	https://www.perle.com/products/10-100-industrial-converters.shtml	Media Converter: S-110
05090040	S-110-S2ST20-XT 10/100Base-TX Industrial Temperature Media and Rate Converter: 10/100Base-TX (RJ-45) [100 m/328 ft.] to 100Base-LX 1310nm single mode (ST) [20 km/12.4 miles]. Extended Temperature, terminal block power connector for external power source.	https://www.perle.com/products/10-100-industrial-converters.shtml	Media Converter: S-110
05090050	S-110-S2LC20-XT 10/100Base-TX Industrial Temperature Media and Rate Converter: 10/100Base-TX (RJ-45) [100 m/328 ft.] to 100Base-LX 1310nm single mode (LC) [20 km/12.4 miles]. Extended Temperature, terminal block power connector for external power source.	https://www.perle.com/products/10-100-industrial-converters.shtml	Media Converter: S-110

Part #	Description	Product Datasheet	Product Group
05090060	S-110-S1SC20U-XT 10/100Base-TX Industrial Temperature Media and Rate Converter: 10/100Base-TX (RJ-45) [100 m/328 ft.] to 100Base-BX 1310nm TX / 1550nm RX single strand fiber, single mode (SC) [20 km/12.4 miles]. Extended Temperature, terminal block power connector for external power source.	https://www.perle.com/products/10-100-industrial-converters.shtml	Media Converter: S-110
05090070	S-110-S1SC20D-XT 10/100Base-TX Industrial Temperature Media and Rate Converter: 10/100Base-TX (RJ-45) [100 m/328 ft.] to 100Base-BX 1550nm TX / 1310nm RX single strand fiber, single mode (SC) [20 km/12.4 miles]. Extended Temperature, terminal block power connector for external power source.	https://www.perle.com/products/10-100-industrial-converters.shtml	Media Converter: S-110
05090200	S-110P-M2SC2-XT - 10/100Base-TX Industrial Temperature Media and Rate Converter with PoE Power Sourcing: 10/100Base-TX (RJ-45) [100 m/328 ft.] to 100BASE-FX 1310nm multimode (SC) [2 km/1.2 miles]. Extended Temperature, terminal block power connector for external power source.	https://www.perle.com/products/10-100-poe-industrial-converters.shtml	Media Converter: S-110P
05090210	S-110P-M2ST2-XT - 10/100Base-TX Industrial Temperature Media and Rate Converter with PoE Power Sourcing: 10/100Base-TX (RJ-45) [100 m/328 ft.] to 100BASE-FX 1310nm multimode (ST) [2 km/1.2 miles]. Extended Temperature, terminal block power connector for external power source.	https://www.perle.com/products/10-100-poe-industrial-converters.shtml	Media Converter: S-110P
05090220	S-110P-S2SC20-XT - 10/100Base-TX Industrial Temperature Media Rate Converter with PoE Power Sourcing: 10/100Base-TX (RJ-45) [100 m/328 ft.] to 100Base-LX 1310nm single mode (SC) [20 km/12.4 miles]. Extended Temperature, terminal block power connector for external power source.	https://www.perle.com/products/10-100-poe-industrial-converters.shtml	Media Converter: S-110P
05090230	S-110P-S2ST20-XT - 10/100Base-TX Industrial Temperature Media Rate Converter with PoE Power Sourcing: 10/100Base-TX (RJ-45) [100 m/328 ft.] to 100Base-LX 1310nm single mode (ST) [20 km/12.4 miles]. Extended Temperature, terminal block power connector for external power source.	https://www.perle.com/products/10-100-poe-industrial-converters.shtml	Media Converter: S-110P
05090240	S-110P-S1SC20U-XT - 10/100Base-TX Industrial Temperature Media Rate Converter with PoE Power Sourcing: 10/100Base-TX (RJ-45) [100 m/328 ft.] to 100Base-BX 1310nm TX / 1550nm RX single strand fiber, single mode (SC) [20 km/12.4 miles]. Extended Temperature, terminal block power connector for external power source.	https://www.perle.com/products/10-100-poe-industrial-converters.shtml	Media Converter: S-110P

Part #	Description	Product Datasheet	Product Group
05090250	S-110P-S1SC20D-XT - 10/100Base-TX Industrial Temperature Media Rate Converter with PoE Power Sourcing: 10/100Base-TX (RJ-45) [100 m/328 ft.] to 100Base-BX 1550nm TX / 1310nm RX single strand fiber, single mode (SC) [20 km/12.4 miles]. Extended Temperature, terminal block power connector for external power source.	https://www.perle.com/products/10-100-poe-industrial-converters.shtml	Media Converter: S-110P
05090260	S-110P-SFP-XT - 10/100Base-TX Industrial Temperature Media Rate Converter with PoE Power Sourcing: 10/100BASE-TX (RJ-45) [100 m/328 ft.] to 100BASE-X - SFP Slot (empty). Extended Temperature, terminal block power connector for external power source	https://www.perle.com/products/10-100-poe-industrial-converters.shtml	Media Converter: S-110P
05090300	S-110PP-M2SC2-XT - 10/100Base-TX Industrial Temperature Media Rate Converter with PoE+ (PoEP) Power Sourcing: 10/100Base-TX (RJ-45) [100 m/328 ft.] to 100BASE-FX 1310nm multimode (SC) [2 km/1.2 miles]. Extended Temperature, terminal block power connector for external power source.	https://www.perle.com/products/10-100-poe-industrial-converters.shtml	Media Converter: S-110PP
05090310	S-110PP-M2ST2-XT - 10/100Base-TX Industrial Temperature Media Rate Converter with PoE+ (PoEP) Power Sourcing: 10/100Base-TX (RJ-45) [100 m/328 ft.] to 100BASE-FX 1310nm multimode (ST) [2 km/1.2 miles]. Extended Temperature, terminal block power connector for external power source.	https://www.perle.com/products/10-100-poe-industrial-converters.shtml	Media Converter: S-110PP
05090320	S-110PP-S2SC20-XT - 10/100Base-TX Industrial Temperature Media Rate Converter with PoE+ (PoEP) Power Sourcing: 10/100Base-TX (RJ-45) [100 m/328 ft.] to 100Base-LX 1310nm single mode (SC) [20 km/12.4 miles]. Extended Temperature, terminal block power connector for external power source.	https://www.perle.com/products/10-100-poe-industrial-converters.shtml	Media Converter: S-110PP
05090330	S-110PP-S2ST20-XT - 10/100Base-TX Industrial Temperature Media Rate Converter with PoE+ (PoEP) Power Sourcing: 10/100Base-TX (RJ-45) [100 m/328 ft.] to 100Base-LX 1310nm single mode (ST) [20 km/12.4 miles]. Extended Temperature, terminal block power connector for external power source.	https://www.perle.com/products/10-100-poe-industrial-converters.shtml	Media Converter: S-110PP
05090340	S-110PP-S1SC20U-XT - 10/100Base-TX Industrial Temperature Media Rate Converter with PoE+ (PoEP) Power Sourcing: 10/100Base-TX (RJ-45) [100 m/328 ft.] to 100Base-BX 1310nm TX / 1550nm RX single strand fiber, single mode (SC) [20 km/12.4 miles]. Extended Temperature, terminal block power connector for external power source.	https://www.perle.com/products/10-100-poe-industrial-converters.shtml	Media Converter: S-110PP

Part #	Description	Product Datasheet	Product Group
05090350	S-110PP-S1SC20D-XT - 10/100Base-TX Industrial Temperature Media Rate Converter with PoE+ (PoEP) Power Sourcing: 10/100Base-TX (RJ-45) [100 m/328 ft.] to 100Base-BX 1550nm TX / 1310nm RX single strand fiber, single mode (SC) [20 km/12.4 miles]. Extended Temperature, terminal block power connector for external power source.	https://www.perle.com/products/10-100-poe-industrial-converters.shtml	Media Converter: S-110PP
05090360	S-110PP-SFP-XT - 10/100Base-TX Industrial Temperature Media and Rate Converter with PoE+ (PoEP) Power Sourcing: 10/100BASE-TX (RJ-45) [100 m/328 ft.] to 100BASE-X - SFP Slot (empty). Extended Temperature, terminal block power connector for external power source	https://www.perle.com/products/10-100-poe-industrial-converters.shtml	Media Converter: S-110PP
05090500	S-1110P-M2SC05-XT - 10/100/1000Base-T Industrial Temperature Media and Rate Converter with PoE Power Sourcing: 10/100/1000BASE-T (RJ-45) [100 m/328 ft.] to 1000BASE-SX 850nm multimode (SC) [550 m/1804 ft.]. Extended Temperature, terminal block power connector for external power source.	https://www.perle.com/products/10-100-1000-poe-industrial-converters.shtml	Media Converter: S-1110P
05090510	S-1110P-M2ST05-XT - 10/100/1000Base-T Industrial Temperature Media and Rate Converter with PoE Power Sourcing: 10/100/1000BASE-T (RJ-45) [100 m/328 ft.] to 1000BASE-SX 850nm multimode (ST) [550 m/1804 ft.]. Extended Temperature, terminal block power connector for external power source.	https://www.perle.com/products/10-100-1000-poe-industrial-converters.shtml	Media Converter: S-1110P
05090520	S-1110P-S2SC10-XT - Industrial Temperature 10/100/1000Base-T Media and Rate Converter with PoE Power Sourcing: 10/100/1000BASE-T (RJ-45) [100 m/328 ft.] to 1000BASE-LX/LH 1310 nm single mode (SC) [10 km/6.2 miles] or multimode (SC) [550 m/1804 ft.] using a mode conditioning adapter. Extended Temperature, terminal block power connector for external power source.	https://www.perle.com/products/10-100-1000-poe-industrial-converters.shtml	Media Converter: S-1110P
05090530	S-1110P-S2ST10-XT - Industrial Temperature 10/100/1000Base-T Media and Rate Converter with PoE Power Sourcing: 10/100/1000BASE-T (RJ-45) [100 m/328 ft.] to 1000BASE-LX/LH 1310 nm single mode (ST) [10 km/6.2 miles]. Extended Temperature, terminal block power connector for external power source.	https://www.perle.com/products/10-100-1000-poe-industrial-converters.shtml	Media Converter: S-1110P
05090540	S-1110P-S1SC10U-XT - Industrial Temperature 10/100/1000Base-T Media and Rate Converter with PoE Power Sourcing: 10/100/1000BASE-T (RJ-45) [100 m/328 ft.] to 1000BASE-BX 1310nm TX / 1490nm RX single strand fiber, single mode (SC) [10 km/6.2 miles]. Extended Temperature, terminal block power connector for external power source.	https://www.perle.com/products/10-100-1000-poe-industrial-converters.shtml	Media Converter: S-1110P

Part #	Description	Product Datasheet	Product Group
05090550	S-1110P-S1SC10D-XT - Industrial Temperature 10/100/1000Base-T Media and Rate Converter with PoE Power Sourcing: 10/100/1000BASE-T (RJ-45) [100 m/328 ft.] to 1000BASE-BX 1490nm TX / 1310nm RX single strand fiber, single mode (SC) [10 km/6.2 miles]. Extended Temperature, terminal block power connector for external power source.	https://www.perle.com/products/10-100-1000-poe-industrial-converters.shtml	Media Converter: S-1110P
05090560	S-1110P-SFP-XT - Industrial Temperature 10/100/1000Base-T Media and Rate Converter with PoE Power Sourcing: 10/100/1000BASE-T (RJ-45) [100 m/328 ft.] to 1000BASE-X or 100BASE-X - SFP Slot (empty). Extended Temperature, terminal block power connector for external power source.	https://www.perle.com/products/10-100-1000-poe-industrial-converters.shtml	Media Converter: S-1110P
05090600	S-1110PP-M2SC05-XT - 10/100/1000Base-T Industrial Temperature Media and Rate Converter with PoE+ (PoEP) Power Sourcing: 10/100/1000BASE-T (RJ-45) [100 m/328 ft.] to 1000BASE-SX 850nm multimode (SC) [550 m/1804 ft.]. Extended Temperature, terminal block power connector for external power source.	https://www.perle.com/products/10-100-1000-poe-industrial-converters.shtml	Media Converter: S-1110PP
05090610	S-1110PP-M2ST05-XT - 10/100/1000Base-T Industrial Temperature Media and Rate Converter with PoE+ (PoEP) Power Sourcing: 10/100/1000BASE-T (RJ-45) [100 m/328 ft.] to 1000BASE-SX 850nm multimode (ST) [550 m/1804 ft.]. Extended Temperature, terminal block power connector for external power source.	https://www.perle.com/products/10-100-1000-poe-industrial-converters.shtml	Media Converter: S-1110PP
05090620	S-1110PP-S2SC10-XT - 10/100/1000Base-T Industrial Temperature Media and Rate Converter with PoE+ (PoEP) Power Sourcing: 10/100/1000BASE-T (RJ-45) [100 m/328 ft.] to 1000BASE-LX/LH 1310 nm single mode (SC) [10 km/6.2 miles] or multimode (SC) [550 m/1804 ft.] using a mode conditioning adapter. Extended Temperature, terminal block power connector for external power source.	https://www.perle.com/products/10-100-1000-poe-industrial-converters.shtml	Media Converter: S-1110PP
05090630	S-1110PP-S2ST10-XT - 10/100/1000Base-T Industrial Temperature Media and Rate Converter with PoE+ (PoEP) Power Sourcing: 10/100/1000BASE-T (RJ-45) [100 m/328 ft.] to 1000BASE-LX/LH 1310 nm single mode (ST) [10 km/6.2 miles]. Extended Temperature, terminal block power connector for external power source.	https://www.perle.com/products/10-100-1000-poe-industrial-converters.shtml	Media Converter: S-1110PP

Part #	Description	Product Datasheet	Product Group
05090640	S-1110PP-S1SC10U-XT - 10/100/1000Base-T Industrial Temperature Media and Rate Converter with PoE+ (PoEP) Power Sourcing: 10/100/1000BASE-T (RJ-45) [100 m/328 ft.] to 1000BASE-BX 1310nm TX / 1490nm RX single strand fiber, single mode (SC) [10 km/6.2 miles]. Extended Temperature, terminal block power connector for external power source.	https://www.perle.com/products/10-100-1000-poe-industrial-converters.shtml	Media Converter: S-1110PP
05090650	S-1110PP-S1SC10D-XT - 10/100/1000Base-T Industrial Temperature Media and Rate Converter with PoE+ (PoEP) Power Sourcing: 10/100/1000BASE-T (RJ-45) [100 m/328 ft.] to 1000BASE-BX 1490nm TX / 1310nm RX single strand fiber, single mode (SC) [10 km/6.2 miles]. Extended Temperature, terminal block power connector for external power source.	https://www.perle.com/products/10-100-1000-poe-industrial-converters.shtml	Media Converter: S-1110PP
05090660	S-1110PP-SFP-XT - 10/100/1000Base-T Industrial Temperature Media and Rate Converter with PoE+ (PoEP) Power Sourcing: 10/100/1000BASE-T (RJ-45) [100 m/328 ft.] to 1000BASE-X or 100BASE-X - SFP Slot (empty).	https://www.perle.com/products/10-100-1000-poe-industrial-converters.shtml	Media Converter: S-1110PP
05090670	S-1110-M2SC05-XT - 10/100/1000Base-T Industrial Temperature Media and Rate Converter: 10/100/1000BASE-T (RJ-45) [100 m/328 ft.] to 1000BASE-SX 850nm multimode (SC) [550 m/1804 ft.]. Extended Temperature, terminal block power connector for external power source.	https://www.perle.com/products/10-100-1000-industrial-converters.shtml	Media Converter: S-1110
05090680	S-1110-M2ST05-XT - 10/100/1000Base-T Industrial Temperature Media and Rate Converter: 10/100/1000BASE-T (RJ-45) [100 m/328 ft.] to 1000BASE-SX 850nm multimode (ST) [550 m/1804 ft.]. Extended Temperature, terminal block power connector for external power source.	https://www.perle.com/products/10-100-1000-industrial-converters.shtml	Media Converter: S-1110
05090690	S-1110-M2LC05-XT - 10/100/1000Base-T Industrial Temperature Media and Rate Converter: 10/100/1000BASE-T (RJ-45) [100 m/328 ft.] to 1000BASE-SX 850nm multimode (LC) [550 m/1804 ft.]. Extended Temperature, terminal block power connector for external power source.	https://www.perle.com/products/10-100-1000-industrial-converters.shtml	Media Converter: S-1110
05090700	S-1110-S2SC10-XT - Industrial Temperature 10/100/1000Base-T Media and Rate Converter: 10/100/1000BASE-T (RJ-45) [100 m/328 ft.] to 1000BASE-LX/LH 1310 nm single mode (SC) [10 km/6.2 miles] or multimode (SC) [550 m/1804 ft.] using a mode conditioning adapter. Extended Temperature, terminal block power connector for external power source.	https://www.perle.com/products/10-100-1000-industrial-converters.shtml	Media Converter: S-1110

Part #	Description	Product Datasheet	Product Group
05090710	S-1110-S2ST10-XT - Industrial Temperature 10/100/1000Base-T Media and Rate Converter: 10/100/1000BASE-T (RJ-45) [100 m/328 ft.] to 1000BASE-LX/LH 1310 nm single mode (ST) [10 km/6.2 miles]. Extended Temperature, terminal block power connector for external power source	https://www.perle.com/products/10-100-1000-industrial-converters.shtml	Media Converter: S-1110
05090720	S-1110-S2LC10-XT - Industrial Temperature 10/100/1000Base-T Media and Rate Converter: 10/100/1000BASE-T (RJ-45) [100 m/328 ft.] to 1000BASE-LX/LH 1310 nm single mode (LC) [10 km/6.2 miles] or multimode (SC) [550 m/1804 ft.] using a mode conditioning adapter. Extended Temperature, terminal block power connector for external power source.	https://www.perle.com/products/10-100-1000-industrial-converters.shtml	Media Converter: S-1110
05090730	S-1110-S1SC10U-XT - Industrial Temperature 10/100/1000Base-T Media and Rate Converter: 10/100/1000BASE-T (RJ-45) [100 m/328 ft.] to 1000BASE-BX 1310nm TX / 1490nm RX single strand fiber, single mode (SC) [10 km/6.2 miles]. Extended Temperature, terminal block power connector for external power source	https://www.perle.com/products/10-100-1000-industrial-converters.shtml	Media Converter: S-1110
05090740	S-1110-S1SC10D-XT - Industrial Temperature 10/100/1000Base-T Media and Rate Converter: 10/100/1000BASE-T (RJ-45) [100 m/328 ft.] to 1000BASE-BX 1490nm TX / 1310nm RX single strand fiber, single mode (SC) [10 km/6.2 miles]. Extended Temperature, terminal block power connector for external power source	https://www.perle.com/products/10-100-1000-industrial-converters.shtml	Media Converter: S-1110
05090750	S-1110-SFP-XT - Industrial Temperature 10/100/1000Base-T Media and Rate Converter: 10/100/1000BASE-T (RJ-45) [100 m/328 ft.] to 1000BASE-X or 100BASE-X - SFP Slot (empty). Extended Temperature, terminal block power connector for external power source.	https://www.perle.com/products/10-100-1000-sfp-industrial-converters.shtml	Media Converter: S-1110
05091000	SR-100-ST2 - Fast Ethernet Industrial Media Converter: 100BASE-TX (RJ-45) [100 m/328 ft] to 100BASE-FX 1310nm multimode (ST) [2 km/1.2 miles]. DIN Rail case, terminal block (Combicon) power connector for external power source	https://www.perle.com/products/media-converters/sr-100-din-rail-copper-fiber-converters.shtml	Media Converter: SR-100
05091010	SR-100-SC2 - Fast Ethernet Industrial Media Converter: 100BASE-TX (RJ-45) [100 m/328 ft] to 100BASE-FX 1310nm multimode (SC) [2 km/1.2 miles]. DIN Rail case, terminal block (Combicon) power connector for external power source	https://www.perle.com/products/media-converters/sr-100-din-rail-copper-fiber-converters.shtml	Media Converter: SR-100

Part #	Description	Product Datasheet	Product Group
05091020	SR-100-SC20 - Fast Ethernet Industrial Media Converter: 100BASE-TX (RJ-45) [100 m/328 ft] to 100Base-LX 1310nm single mode (SC) [20 km/12.4 miles]. DIN Rail case, terminal block (Combicon) power connector for external power source	https://www.perle.com/products/media-converters/sr-100-din-rail-copper-fiber-converters.shtml	Media Converter: SR-100
05091030	SR-100-ST20 - Fast Ethernet Industrial Media Converter: 100BASE-TX (RJ-45) [100 m/328 ft] to 100Base-LX 1310nm single mode (ST) [20 km/12.4 miles]. DIN Rail case, terminal block (Combicon) power connector for external power source	https://www.perle.com/products/media-converters/sr-100-din-rail-copper-fiber-converters.shtml	Media Converter: SR-100
05091040	SR-100-SC40 - Fast Ethernet Industrial Media Converter: 100BASE-TX (RJ-45) [100 m/328 ft] to 100Base-EX 1310nm single mode (SC) [40 km/24.9 miles]. DIN Rail case, terminal block (Combicon) power connector for external power source	https://www.perle.com/products/media-converters/sr-100-din-rail-copper-fiber-converters.shtml	Media Converter: SR-100
05091050	SR-100-ST40 - Fast Ethernet Industrial Media Converter: 100BASE-TX (RJ-45) [100 m/328 ft] to 100Base-EX 1310nm single mode (ST) [40 km/24.9 miles]. DIN Rail case, terminal block (Combicon) power connector for external power source	https://www.perle.com/products/media-converters/sr-100-din-rail-copper-fiber-converters.shtml	Media Converter: SR-100
05091060	SR-100-SC80 - Fast Ethernet Industrial Media Converter: 100BASE-TX (RJ-45) [100 m/328 ft] to 100Base-ZX 1550nm single mode (SC) [80 km/49.7 miles]. DIN Rail case, terminal block (Combicon) power connector for external power source	https://www.perle.com/products/media-converters/sr-100-din-rail-copper-fiber-converters.shtml	Media Converter: SR-100
05091070	SR-100-ST80 - Fast Ethernet Industrial Media Converter: 100BASE-TX (RJ-45) [100 m/328 ft] to 100Base-ZX 1550nm single mode (ST) [80 km/49.7 miles]. DIN Rail case, terminal block (Combicon) power connector for external power source	https://www.perle.com/products/media-converters/sr-100-din-rail-copper-fiber-converters.shtml	Media Converter: SR-100
05091080	SR-100-SC120 - Fast Ethernet Industrial Media Converter: 100BASE-TX (RJ-45) [100 m/328 ft] to 100Base-ZX 1550nm single mode (SC) [120 km/74.6 miles]. DIN Rail case, terminal block (Combicon) power connector for external power source	https://www.perle.com/products/media-converters/sr-100-din-rail-copper-fiber-converters.shtml	Media Converter: SR-100
05091090	SR-100-ST120 - Fast Ethernet Industrial Media Converter: 100BASE-TX (RJ-45) [100 m/328 ft] to 100Base-ZX 1550nm single mode (ST) [120 km/74.6 miles]. DIN Rail case, terminal block (Combicon) power connector for external power source	https://www.perle.com/products/media-converters/sr-100-din-rail-copper-fiber-converters.shtml	Media Converter: SR-100

Part #	Description	Product Datasheet	Product Group
05091100	SR-100-SC20U - Fast Ethernet Industrial Media Converter: 100Base-TX (RJ-45) [100 m/328 ft] to 100Base-BX 1310nm TX / 1550nm RX single strand fiber, single mode (SC) [20 km/12.4 miles]. DIN Rail case, terminal block (Combicon) power connector for external power source	https://www.perle.com/products/media-converters/sr-100-din-rail-copper-fiber-converters.shtml	Media Converter: SR-100
05091110	SR-100-SC20D - Fast Ethernet Industrial Media Converter: 100Base-TX (RJ-45) [100 m/328 ft] to 100Base-BX 1550nm TX / 1310nm RX single strand fiber, single mode (SC) [20 km/12.4 miles]. DIN Rail case, terminal block (Combicon) power connector for external power source	https://www.perle.com/products/media-converters/sr-100-din-rail-copper-fiber-converters.shtml	Media Converter: SR-100
05091120	SR-100-SC40U - Fast Ethernet Industrial Media Converter: 100Base-TX (RJ-45) [100 m/328 ft] to 100Base-BX 1310nm TX / 1550nm RX single strand fiber, single mode (SC) [40 km/24.9 miles]. DIN Rail case, terminal block (Combicon) power connector for external power source	https://www.perle.com/products/media-converters/sr-100-din-rail-copper-fiber-converters.shtml	Media Converter: SR-100
05091130	SR-100-SC40D - Fast Ethernet Industrial Media Converter: 100Base-TX (RJ-45) [100 m/328 ft] to 100Base-BX 1550nm TX / 1310nm RX single strand fiber, single mode (SC) [40 km/24.9 miles]. DIN Rail case, terminal block (Combicon) power connector for external power source	https://www.perle.com/products/media-converters/sr-100-din-rail-copper-fiber-converters.shtml	Media Converter: SR-100
05091140	SR-100-SC2D - Fast Ethernet Industrial Media Converter: 100Base-TX (RJ-45) [100 m/328 ft] to 100Base-BX 1550nm TX / 1310nm RX single strand fiber, multimode (SC) [2 km/1.2 miles]. DIN Rail case, terminal block (Combicon) power connector for external power source	https://www.perle.com/products/media-converters/sr-100-din-rail-copper-fiber-converters.shtml	Media Converter: SR-100
05091150	SR-100-SC2U - Fast Ethernet Industrial Media Converter: 100Base-TX (RJ-45) [100 m/328 ft] to 100Base-BX 1310nm TX / 1550nm RX single strand fiber, multimode (SC) [2 km/1.2 miles]. DIN Rail case, terminal block (Combicon) power connector for external power source	https://www.perle.com/products/media-converters/sr-100-din-rail-copper-fiber-converters.shtml	Media Converter: SR-100
05091160	SR-100-ST20U - Fast Ethernet Industrial Media Converter: 100Base-TX (RJ-45) [100 m/328 ft] to 100Base-BX 1310nm TX / 1550nm RX single strand fiber, single mode (ST) [20 km/12.4 miles]. DIN Rail case, terminal block (Combicon) power connector for external power source	https://www.perle.com/products/media-converters/sr-100-din-rail-copper-fiber-converters.shtml	Media Converter: SR-100
05091170	SR-100-ST20D - Fast Ethernet Industrial Media Converter: 100Base-TX (RJ-45) [100 m/328 ft] to 100Base-BX 1550nm TX / 1310nm RX single strand fiber, single mode (ST) [20 km/12.4 miles]. DIN Rail case, terminal block (Combicon) power connector for external power source	https://www.perle.com/products/media-converters/sr-100-din-rail-copper-fiber-converters.shtml	Media Converter: SR-100

Part #	Description	Product Datasheet	Product Group
05091180	SR-100-ST2D - Fast Ethernet Industrial Media Converter: 100Base-TX (RJ-45) [100 m/328 ft] to 100Base-BX 1550nm TX / 1310nm RX single strand fiber, multimode (ST) [2 km/1.2 miles]. DIN Rail case, terminal block (Combicon) power connector for external power source	https://www.perle.com/products/media-converters/sr-100-din-rail-copper-fiber-converters.shtml	Media Converter: SR-100
05091190	SR-100-ST2U - Fast Ethernet Industrial Media Converter: 100Base-TX (RJ-45) [100 m/328 ft] to 100Base-BX 1310nm TX / 1550nm RX single strand fiber, multimode (ST) [2 km/1.2 miles]. DIN Rail case, terminal block (Combicon) power connector for external power source	https://www.perle.com/products/media-converters/sr-100-din-rail-copper-fiber-converters.shtml	Media Converter: SR-100
05091200	SR-100-SC2-XT - Fast Ethernet Industrial Media Converter: 100Base-TX (RJ-45) [100 m/328 ft] to 100BASE-FX 1310nm multimode (SC) [2 km/1.2 miles], -40F to +167F (-40C to +75C) extended operating temperature support. DIN Rail case, terminal block (Combicon) power connector for external power source	https://www.perle.com/products/media-converters/sr-100xt-din-rail-copper-fiber-converters.shtml	Media Converter: SR-100
05091210	SR-100-ST2-XT - Fast Ethernet Industrial Media Converter: 100Base-TX (RJ-45) [100 m/328 ft] to 100BASE-FX 1310nm multimode (ST) [2 km/1.2 miles], -40F to +167F (-40C to +75C) extended operating temperature support. DIN Rail case, terminal block (Combicon) power connector for external power source	https://www.perle.com/products/media-converters/sr-100xt-din-rail-copper-fiber-converters.shtml	Media Converter: SR-100
05091220	SR-100-SC20-XT - Fast Ethernet Industrial Media Converter: 100Base-TX (RJ-45) [100 m/328 ft] to 100Base-LX 1310nm single mode (SC) [20 km/12.4 miles], -40F to +167F (-40C to +75C) extended operating temperature support. DIN Rail case, terminal block (Combicon) power connector for external power source	https://www.perle.com/products/media-converters/sr-100xt-din-rail-copper-fiber-converters.shtml	Media Converter: SR-100
05091230	SR-100-ST20-XT - Fast Ethernet Industrial Media Converter: 100Base-TX (RJ-45) [100 m/328 ft] to 100Base-LX 1310nm single mode (ST) [20 km/12.4 miles], -40F to +167F (-40C to +75C) extended operating temperature support. DIN Rail case, terminal block (Combicon) power connector for external power source	https://www.perle.com/products/media-converters/sr-100xt-din-rail-copper-fiber-converters.shtml	Media Converter: SR-100
05091240	SR-100-SC40-XT - Fast Ethernet Industrial Media Converter: 100Base-TX (RJ-45) [100 m/328 ft] to 100Base-LX 1310nm single mode (SC) [40 km/24.9 miles], -40F to +167F (-40C to +75C) extended operating temperature support. DIN Rail case, terminal block (Combicon) power connector for external power source	https://www.perle.com/products/media-converters/sr-100xt-din-rail-copper-fiber-converters.shtml	Media Converter: SR-100

Part #	Description	Product Datasheet	Product Group
05091250	SR-100-ST40-XT - Fast Ethernet Industrial Media Converter: 100Base-TX (RJ-45) [100 m/328 ft] to 100Base-LX 1310nm single mode (ST) [40 km/24.9 miles], -40F to +167F (-40C to +75C) extended operating temperature support. DIN Rail case, terminal block (Combicon) power connector for external power source	https://www.perle.com/products/media-converters/sr-100xt-din-rail-copper-fiber-converters.shtml	Media Converter: SR-100
05091260	SR-100-SC20U-XT - Fast Ethernet Industrial Media Converter: 100Base-TX (RJ-45) [100 m/328 ft] to 100Base-BX 1310nm TX / 1550nm RX single strand fiber, single mode (SC) [20 km/12.4 miles], -40F to +167F (-40C to +75C) extended operating temperature support. DIN Rail case, terminal block (Combicon) power connector for external power source	https://www.perle.com/products/media-converters/sr-100xt-din-rail-copper-fiber-converters.shtml	Media Converter: SR-100
05091270	SR-100-SC20D-XT - Fast Ethernet Industrial Media Converter: 100Base-TX (RJ-45) [100 m/328 ft] to 100Base-BX 1550nm TX / 1310nm RX single strand fiber, single mode (SC) [20 km/12.4 miles], -40F to +167F (-40C to +75C) extended operating temperature support. DIN Rail case, terminal block (Combicon) power connector for external power source	https://www.perle.com/products/media-converters/sr-100xt-din-rail-copper-fiber-converters.shtml	Media Converter: SR-100
05091280	SR-100-SFP - Fast Ethernet Industrial Media Converter: 100BASE-TX (RJ-45) [100 m/328 ft] to 100BASE-X SFP Slot (empty). DIN Rail case, terminal block (Combicon) power connector for external power source	https://www.perle.com/products/media-converters/sr-100-sfp-din-rail-copper-fiber-converter.shtml	Media Converter: SR-100
05091290	SR-100-SFP-XT - Fast Ethernet Industrial Media Converter: 100BASE-T (RJ-45) [100 m/328 ft] to 100BASE-X SFP Slot (empty), -40F to +167F (-40C to +75C) extended operating temperature support. DIN Rail case, terminal block (Combicon) power connector for external power source	https://www.perle.com/products/media-converters/sr-100-sfp-xt-din-rail-copper-fiber-converter.shtml	Media Converter: SR-100
05091300	SR-1000-SC05 - Gigabit Industrial Media Converter: 1000BASE-T (RJ-45) [100 m/328 ft] to 1000BASE-SX 850nm multimode (SC) [550 m/1804 ft]. DIN Rail case, terminal block (Combicon) power connector for external power source	https://www.perle.com/products/media-converters/sr-1000-din-rail-copper-fiber-converters.shtml	Media Converter: SR-1000
05091310	SR-1000-ST05 - Gigabit Industrial Media Converter: 1000BASE-T (RJ-45) [100 m/328 ft] to 1000BASE-SX 850nm multimode (ST) [550 m/1804 ft]. DIN Rail case, terminal block (Combicon) power connector for external power source	https://www.perle.com/products/media-converters/sr-1000-din-rail-copper-fiber-converters.shtml	Media Converter: SR-1000
05091320	SR-1000-SC2 - Gigabit Industrial Media Converter: 1000BASE-T (RJ-45) [100 m/328 ft] to 1000BASE-LX 1310nm extended multimode (SC) [2km /6562 ft]. DIN Rail case, terminal block (Combicon) power connector for external power source	https://www.perle.com/products/media-converters/sr-1000-din-rail-copper-fiber-converters.shtml	Media Converter: SR-1000

Part #	Description	Product Datasheet	Product Group
05091330	SR-1000-ST2 - Gigabit Industrial Media Converter: 1000BASE-T (RJ-45) [100 m/328 ft] to 1000BASE-LX 1310nm extended multimode (ST) [2km /6562 ft]. DIN Rail case, terminal block (Combicon) power connector for external power source	https://www.perle.com/products/media-converters/sr-1000-din-rail-copper-fiber-converters.shtml	Media Converter: SR-1000
05091340	SR-1000-SC10 - Gigabit Industrial Media Converter: 1000BASE-T (RJ-45) [100 m/328 ft] to 1000BASE-LX/LH 1310 nm single mode (SC) [10 km/6.2 miles]. DIN Rail case, terminal block (Combicon) power connector for external power source	https://www.perle.com/products/media-converters/sr-1000-din-rail-copper-fiber-converters.shtml	Media Converter: SR-1000
05091350	SR-1000-ST10 - Gigabit Industrial Media Converter: 1000BASE-T (RJ-45) [100 m/328 ft] to 1000BASE-LX/LH 1310 nm single mode (ST) [10 km/6.2 miles]. DIN Rail case, terminal block (Combicon) power connector for external power source	https://www.perle.com/products/media-converters/sr-1000-din-rail-copper-fiber-converters.shtml	Media Converter: SR-1000
05091360	SR-1000-SC40 - Gigabit Industrial Media Converter: 1000BASE-T (RJ-45) [100 m/328 ft] to 1000BASE-EX 1310 nm single mode (SC) [40 km/24.9 miles]. DIN Rail case, terminal block (Combicon) power connector for external power source	https://www.perle.com/products/media-converters/sr-1000-din-rail-copper-fiber-converters.shtml	Media Converter: SR-1000
05091370	SR-1000-ST40 - Gigabit Industrial Media Converter: 1000BASE-T (RJ-45) [100 m/328 ft] to 1000BASE-EX 1310 nm single mode (ST) [40 km/24.9 miles]. DIN Rail case, terminal block (Combicon) power connector for external power source	https://www.perle.com/products/media-converters/sr-1000-din-rail-copper-fiber-converters.shtml	Media Converter: SR-1000
05091380	SR-1000-SC70 - Gigabit Industrial Media Converter: 1000BASE-T (RJ-45) [100 m/328 ft] to 1000BASE-ZX 1550 nm single mode (SC) [70 km/43.5 miles]. DIN Rail case, terminal block (Combicon) power connector for external power source	https://www.perle.com/products/media-converters/sr-1000-din-rail-copper-fiber-converters.shtml	Media Converter: SR-1000
05091390	SR-1000-ST70 - Gigabit Industrial Media Converter: 1000BASE-T (RJ-45) [100 m/328 ft] to 1000BASE-ZX 1550 nm single mode (ST) [70 km/43.5 miles]. DIN Rail case, terminal block (Combicon) power connector for external power source	https://www.perle.com/products/media-converters/sr-1000-din-rail-copper-fiber-converters.shtml	Media Converter: SR-1000
05091400	SR-1000-ST120 - Gigabit Industrial Media Converter: 1000BASE-T (RJ-45) [100 m/328 ft] to 1000BASE-ZX 1550 nm single mode (ST) [120 km/74.6 miles]. DIN Rail case, terminal block (Combicon) power connector for external power source	https://www.perle.com/products/media-converters/sr-1000-din-rail-copper-fiber-converters.shtml	Media Converter: SR-1000

Part #	Description	Product Datasheet	Product Group
05091410	SR-1000-SC120 - Gigabit Industrial Media Converter: 1000BASE-T (RJ-45) [100 m/328 ft] to 1000BASE-ZX 1550 nm single mode (SC) [120 km/74.6 miles]. DIN Rail case, terminal block (Combicon) power connector for external power source	https://www.perle.com/products/media-converters/sr-1000-din-rail-copper-fiber-converters.shtml	Media Converter: SR-1000
05091420	SR-1000-SC160 - Gigabit Industrial Media Converter: 1000BASE-T (RJ-45) [100 m/328 ft] to 1000BASE-ZX 1550 nm single mode (SC) [160 km/100 miles]. DIN Rail case, terminal block (Combicon) power connector for external power source	https://www.perle.com/products/media-converters/sr-1000-din-rail-copper-fiber-converters.shtml	Media Converter: SR-1000
05091430	SR-1000-ST160 - Gigabit Industrial Media Converter: 1000BASE-T (RJ-45) [100 m/328 ft] to 1000BASE-ZX 1550 nm single mode (ST) [160 km/100 miles]. DIN Rail case, terminal block (Combicon) power connector for external power source	https://www.perle.com/products/media-converters/sr-1000-din-rail-copper-fiber-converters.shtml	Media Converter: SR-1000
05091440	SR-1000-SC10U - Gigabit Industrial Media Converter: 1000BASE-T (RJ-45) [100 m/328 ft] to 1000BASE-BX 1310nm TX / 1490nm RX single strand fiber, single mode (SC) [10 km/6.2 miles]. DIN Rail case, terminal block (Combicon) power connector for external power source	https://www.perle.com/products/media-converters/sr-1000-din-rail-copper-fiber-converters.shtml	Media Converter: SR-1000
05091450	SR-1000-SC10D - Gigabit Industrial Media Converter: 1000BASE-T (RJ-45) [100 m/328 ft] to 1000BASE-BX 1490nm TX / 1310nm RX single strand fiber, single mode (SC) [10 km/6.2 miles]. DIN Rail case, terminal block (Combicon) power connector for external power source	https://www.perle.com/products/media-converters/sr-1000-din-rail-copper-fiber-converters.shtml	Media Converter: SR-1000
05091460	SR-1000-SC20U - Gigabit Industrial Media Converter: 1000BASE-T (RJ-45) [100 m/328 ft] to 1000BASE-BX 1310nm TX / 1490nm RX single strand fiber, single mode (SC) [20 km/12.4 miles]. DIN Rail case, terminal block (Combicon) power connector for external power source	https://www.perle.com/products/media-converters/sr-1000-din-rail-copper-fiber-converters.shtml	Media Converter: SR-1000
05091470	SR-1000-SC20D - Gigabit Industrial Media Converter: 1000BASE-T (RJ-45) [100 m/328 ft] to 1000BASE-BX 1490nm TX / 1310nm RX single strand fiber, single mode (SC) [20 km/12.4 miles]. DIN Rail case, terminal block (Combicon) power connector for external power source	https://www.perle.com/products/media-converters/sr-1000-din-rail-copper-fiber-converters.shtml	Media Converter: SR-1000
05091480	SR-1000-SC40U - Gigabit Industrial Media Converter: 1000BASE-T (RJ-45) [100 m/328 ft] to 1000BASE-BX 1310nm TX / 1490nm RX single strand fiber, single mode (SC) [40 km/25 miles]. DIN Rail case, terminal block (Combicon) power connector for external power source	https://www.perle.com/products/media-converters/sr-1000-din-rail-copper-fiber-converters.shtml	Media Converter: SR-1000

Part #	Description	Product Datasheet	Product Group
05091490	SR-1000-SC40D - Gigabit Industrial Media Converter: 1000BASE-T (RJ-45) [100 m/328 ft] to 1000BASE-BX 1490nm TX / 1310nm RX single strand fiber, single mode (SC) [40 km/25 miles]. DIN Rail case, terminal block (Combicon) power connector for external power source	https://www.perle.com/products/media-converters/sr-1000-din-rail-copper-fiber-converters.shtml	Media Converter: SR-1000
05091500	SR-1000-SC80U - Gigabit Industrial Media Converter: 1000BASE-T (RJ-45) [100 m/328 ft] to 1000BASE-BX 1510nm TX / 1590nm RX single strand fiber, single mode (SC) [80 km/50 miles]. DIN Rail case, terminal block (Combicon) power connector for external power source	https://www.perle.com/products/media-converters/sr-1000-din-rail-copper-fiber-converters.shtml	Media Converter: SR-1000
05091510	SR-1000-SC80D - Gigabit Industrial Media Converter: 1000BASE-T (RJ-45) [100 m/328 ft] to 1000BASE-BX 1590nm TX / 1510nm RX single strand fiber, single mode (SC) [80 km/50 miles]. DIN Rail case, terminal block (Combicon) power connector for external power source	https://www.perle.com/products/media-converters/sr-1000-din-rail-copper-fiber-converters.shtml	Media Converter: SR-1000
05091520	SR-1000-SC120U - Gigabit Industrial Media Converter: 1000BASE-T (RJ-45) [100 m/328 ft] to 1000BASE-BX 1510nm TX / 1590nm RX single strand fiber, single mode (SC) [120 km/75 miles]. DIN Rail case, terminal block (Combicon) power connector for external power source	https://www.perle.com/products/media-converters/sr-1000-din-rail-copper-fiber-converters.shtml	Media Converter: SR-1000
05091530	SR-1000-SC120D - Gigabit Industrial Media Converter: 1000BASE-T (RJ-45) [100 m/328 ft] to 1000BASE-BX 1590nm TX / 1510nm RX single strand fiber, single mode (SC) [120 km/75 miles]. DIN Rail case, terminal block (Combicon) power connector for external power source	https://www.perle.com/products/media-converters/sr-1000-din-rail-copper-fiber-converters.shtml	Media Converter: SR-1000
05091540	SR-1000-SC05D - Gigabit Industrial Media Converter: 1000BASE-T (RJ-45) [100 m/328 ft] to 1000BASE-BX 1550nm TX / 1310nm RX single strand fiber, multimode (SC) [500 m/1640 ft]. DIN Rail case, terminal block (Combicon) power connector for external power source	https://www.perle.com/products/media-converters/sr-1000-din-rail-copper-fiber-converters.shtml	Media Converter: SR-1000
05091550	SR-1000-SC05U - Gigabit Industrial Media Converter: 1000BASE-T (RJ-45) [100 m/328 ft] to 1000BASE-BX 1310nm TX / 1550nm RX single strand fiber, multimode (SC) [500 m/1640 ft]. DIN Rail case, terminal block (Combicon) power connector for external power source	https://www.perle.com/products/media-converters/sr-1000-din-rail-copper-fiber-converters.shtml	Media Converter: SR-1000
05091560	SR-1000-SC05-XT - Gigabit Industrial Media Rate Converter: 1000Base-T (RJ-45) [100 m/328 ft] to 1000BASE-SX 850nm multimode (SC) [550 m/1804 ft], -40F to +167F (-40C to +75C) extended operating temperature support. DIN Rail case, terminal block (Combicon) power connector for external power source .	https://www.perle.com/products/media-converters/sr-1000xt-din-rail-copper-fiber-converters.shtml	Media Converter: SR-1000

Part #	Description	Product Datasheet	Product Group
05091570	SR-1000-ST05-XT - Gigabit Industrial Media Rate Converter: 1000Base-T (RJ-45) [100 m/328 ft] to 1000BASE-SX 850nm multimode (ST) [550 m/1804 ft], -40F to +167F (-40C to +75C) extended operating temperature support. DIN Rail case, terminal block (Combicon) power connector for external power source .	https://www.perle.com/products/media-converters/sr-1000xt-din-rail-copper-fiber-converters.shtml	Media Converter: SR-1000
05091580	SR-1000-SC10-XT - Gigabit Industrial Media Rate Converter: 1000Base-T (RJ-45) [100 m/328 ft] to 1000BASE-LX/LH 1310 nm single mode (SC) [10 km/6.2 miles], -40F to +167F (-40C to +75C) extended operating temperature support. DIN Rail case, terminal block (Combicon) power connector for external power source .	https://www.perle.com/products/media-converters/sr-1000xt-din-rail-copper-fiber-converters.shtml	Media Converter: SR-1000
05091590	SR-1000-ST10-XT - Gigabit Industrial Media Rate Converter: 1000Base-T (RJ-45) [100 m/328 ft] to 1000BASE-LX/LH 1310 nm single mode (ST) [10 km/6.2 miles], -40F to +167F (-40C to +75C) extended operating temperature support. DIN Rail case, terminal block (Combicon) power connector for external power source	https://www.perle.com/products/media-converters/sr-1000xt-din-rail-copper-fiber-converters.shtml	Media Converter: SR-1000
05091600	SR-1000-SC10U-XT - Gigabit Industrial Media Rate Converter: 1000Base-T (RJ-45) [100 m/328 ft] to 1000BASE-BX 1310nm TX / 1490nm RX single strand fiber, single mode (SC) [10 km/6.2 miles], -40F to +167F (-40C to +75C) extended operating temperature support. DIN Rail case, terminal block (Combicon) power connector for external power source	https://www.perle.com/products/media-converters/sr-1000xt-din-rail-copper-fiber-converters.shtml	Media Converter: SR-1000
05091610	SR-1000-SC10D-XT - Gigabit Industrial Media Rate Converter: 1000Base-T (RJ-45) [100 m/328 ft] to 1000BASE-BX 1490nm TX / 1310nm RX single strand fiber, single mode (SC) [10 km/6.2 miles], -40F to +167F (-40C to +75C) extended operating temperature support. DIN Rail case, terminal block (Combicon) power connector for external power source	https://www.perle.com/products/media-converters/sr-1000xt-din-rail-copper-fiber-converters.shtml	Media Converter: SR-1000
05091620	SR-1000-SFP - Gigabit Industrial Media Converter: 1000BASE-T (RJ-45) [100 m/328 ft] to 1000BASE-X SFP Slot (empty). DIN Rail case, terminal block (Combicon) power connector for external power source	https://www.perle.com/products/media-converters/sr-1000-sfp-din-rail-copper-fiber-converter.shtml	Media Converter: SR-1000
05091630	SR-1000-SFP-XT - Gigabit Industrial Media Converter: 1000BASE-T (RJ-45) [100 m/328 ft] to 1000BASE-X SFP Slot (empty), -40F to +167F (-40C to +75C) extended operating temperature support. DIN Rail case, terminal block (Combicon) power connector for external power source	https://www.perle.com/products/media-converters/sr-1000-sfp-xt-din-rail-copper-fiber-converter.shtml	Media Converter: SR-1000

Part #	Description	Product Datasheet	Product Group
05091640	SR-1110-SC05 - 10/100/1000 Industrial Media and Rate Converter: 10/100/1000BASE-T (RJ-45) [100 m/328 ft] to 1000BASE-SX 850nm multimode (SC) [550 m/1804 ft]. DIN Rail case, terminal block (Combicon) power connector for external power source	https://www.perle.com/products/media-converters/sr-1110-din-rail-copper-fiber-converters.shtml	Media Converter: SR-1110
05091650	SR-1110-ST05 - 10/100/1000 Industrial Media and Rate Converter: 10/100/1000BASE-T (RJ-45) [100 m/328 ft] to 1000BASE-SX 850nm multimode (ST) [550 m/1804 ft]. DIN Rail case, terminal block (Combicon) power connector for external power source	https://www.perle.com/products/media-converters/sr-1110-din-rail-copper-fiber-converters.shtml	Media Converter: SR-1110
05091660	SR-1110-SC2 - 10/100/1000 Industrial Media and Rate Converter: 10/100/1000BASE-T (RJ-45) [100 m/328 ft] to 1000BASE-LX 1310nm Extended multimode (SC) [2km /6562 ft]. DIN Rail case, terminal block (Combicon) power connector for external power source	https://www.perle.com/products/media-converters/sr-1110-din-rail-copper-fiber-converters.shtml	Media Converter: SR-1110
05091670	SR-1110-ST2 - 10/100/1000 Industrial Media and Rate Converter: 10/100/1000BASE-T (RJ-45) [100 m/328 ft] to 1000BASE-LX 1310nm Extended multimode (ST) [2km /6562 ft]. DIN Rail case, terminal block (Combicon) power connector for external power source	https://www.perle.com/products/media-converters/sr-1110-din-rail-copper-fiber-converters.shtml	Media Converter: SR-1110
05091680	SR-1110-SC10 - 10/100/1000 Industrial Media and Rate Converter: 10/100/1000BASE-T (RJ-45) [100 m/328 ft] to 1000BASE-LX/LH 1310 nm single mode (SC) [10 km/6.2 miles]. DIN Rail case, terminal block (Combicon) power connector for external power source	https://www.perle.com/products/media-converters/sr-1110-din-rail-copper-fiber-converters.shtml	Media Converter: SR-1110
05091690	SR-1110-ST10 - 10/100/1000 Industrial Media and Rate Converter: 10/100/1000BASE-T (RJ-45) [100 m/328 ft] to 1000BASE-LX/LH 1310 nm single mode (ST) [10 km/6.2 miles]. DIN Rail case, terminal block (Combicon) power connector for external power source	https://www.perle.com/products/media-converters/sr-1110-din-rail-copper-fiber-converters.shtml	Media Converter: SR-1110
05091700	SR-1110-SC40 - 10/100/1000 Industrial Media and Rate Converter: 10/100/1000BASE-T (RJ-45) [100 m/328 ft] to 1000BASE-EX 1310 nm single mode (SC) [40 km/24.9 miles]. DIN Rail case, terminal block (Combicon) power connector for external power source	https://www.perle.com/products/media-converters/sr-1110-din-rail-copper-fiber-converters.shtml	Media Converter: SR-1110
05091710	SR-1110-ST40 - 10/100/1000 Industrial Media and Rate Converter: 10/100/1000BASE-T (RJ-45) [100 m/328 ft] to 1000BASE-EX 1310 nm single mode (ST) [40 km/24.9 miles]. DIN Rail case, terminal block (Combicon) power connector for external power source	https://www.perle.com/products/media-converters/sr-1110-din-rail-copper-fiber-converters.shtml	Media Converter: SR-1110

Part #	Description	Product Datasheet	Product Group
05091720	SR-1110-SC70 - 10/100/1000 Industrial Media and Rate Converter: 10/100/1000BASE-T (RJ-45) [100 m/328 ft] to 1000BASE-ZX 1550 nm single mode (SC) [70 km/43.5 miles]. DIN Rail case, terminal block (Combicon) power connector for external power source	https://www.perle.com/products/media-converters/sr-1110-din-rail-copper-fiber-converters.shtml	Media Converter: SR-1110
05091730	SR-1110-ST70 - 10/100/1000 Industrial Media and Rate Converter: 10/100/1000BASE-T (RJ-45) [100 m/328 ft] to 1000BASE-ZX 1550 nm single mode (ST) [70 km/43.5 miles]. DIN Rail case, terminal block (Combicon) power connector for external power source	https://www.perle.com/products/media-converters/sr-1110-din-rail-copper-fiber-converters.shtml	Media Converter: SR-1110
05091740	SR-1110-ST120 - 10/100/1000 Industrial Media and Rate Converter: 10/100/1000BASE-T (RJ-45) [100 m/328 ft] to 1000BASE-ZX 1550 nm single mode (ST) [120 km/74.6 miles]. DIN Rail case, terminal block (Combicon) power connector for external power source	https://www.perle.com/products/media-converters/sr-1110-din-rail-copper-fiber-converters.shtml	Media Converter: SR-1110
05091750	SR-1110-SC120 - 10/100/1000 Industrial Media and Rate Converter: 10/100/1000BASE-T (RJ-45) [100 m/328 ft] to 1000BASE-ZX 1550 nm single mode (SC) [120 km/74.6 miles]. DIN Rail case, terminal block (Combicon) power connector for external power source	https://www.perle.com/products/media-converters/sr-1110-din-rail-copper-fiber-converters.shtml	Media Converter: SR-1110
05091760	SR-1110-SC160 - 10/100/1000 Industrial Media and Rate Converter: 10/100/1000BASE-T (RJ-45) [100 m/328 ft] to 1000BASE-ZX 1550 nm single mode (SC) [160 km/100 miles]. DIN Rail case, terminal block (Combicon) power connector for external power source	https://www.perle.com/products/media-converters/sr-1110-din-rail-copper-fiber-converters.shtml	Media Converter: SR-1110
05091770	SR-1110-ST160 - 10/100/1000 Industrial Media and Rate Converter: 10/100/1000BASE-T (RJ-45) [100 m/328 ft] to 1000BASE-ZX 1550 nm single mode (ST) [160 km/100 miles]. DIN Rail case, terminal block (Combicon) power connector for external power source	https://www.perle.com/products/media-converters/sr-1110-din-rail-copper-fiber-converters.shtml	Media Converter: SR-1110
05091780	SR-1110-SC10U - 10/100/1000 Industrial Media and Rate Converter: 10/100/1000BASE-T (RJ-45) [100 m/328 ft] to 1000BASE-BX 1310nm TX / 1490nm RX single strand fiber, single mode (SC) [10 km/6.2 miles]. DIN Rail case, terminal block (Combicon) power connector for external power source	https://www.perle.com/products/media-converters/sr-1110-din-rail-copper-fiber-converters.shtml	Media Converter: SR-1110
05091790	SR-1110-SC10D - 10/100/1000 Industrial Media and Rate Converter: 10/100/1000BASE-T (RJ-45) [100 m/328 ft] to 1000BASE-BX 1490nm TX / 1310nm RX single strand fiber, single mode (SC) [10 km/6.2 miles]. DIN Rail case, terminal block (Combicon) power connector for external power source	https://www.perle.com/products/media-converters/sr-1110-din-rail-copper-fiber-converters.shtml	Media Converter: SR-1110

Part #	Description	Product Datasheet	Product Group
05091800	SR-1110-SC20U - 10/100/1000 Industrial Media and Rate Converter: 10/100/1000BASE-T (RJ-45) [100 m/328 ft] to 1000BASE-BX 1310nm TX / 1490nm RX single strand fiber, single mode (SC) [20 km/12.4 miles]. DIN Rail case, terminal block (Combicon) power connector for external power source	https://www.perle.com/products/media-converters/sr-1110-din-rail-copper-fiber-converters.shtml	Media Converter: SR-1110
05091810	SR-1110-SC20D - 10/100/1000 Industrial Media and Rate Converter: 10/100/1000BASE-T (RJ-45) [100 m/328 ft] to 1000BASE-BX 1490nm TX / 1310nm RX single strand fiber, single mode (SC) [20 km/12.4 miles]. DIN Rail case, terminal block (Combicon) power connector for external power source	https://www.perle.com/products/media-converters/sr-1110-din-rail-copper-fiber-converters.shtml	Media Converter: SR-1110
05091820	SR-1110-SC40U - 10/100/1000 Industrial Media and Rate Converter: 10/100/1000BASE-T (RJ-45) [100 m/328 ft] to 1000BASE-BX 1310nm TX / 1490nm RX single strand fiber, single mode (SC) [40 km/25 miles]. DIN Rail case, terminal block (Combicon) power connector for external power source	https://www.perle.com/products/media-converters/sr-1110-din-rail-copper-fiber-converters.shtml	Media Converter: SR-1110
05091830	SR-1110-SC40D - 10/100/1000 Industrial Media and Rate Converter: 10/100/1000BASE-T (RJ-45) [100 m/328 ft] to 1000BASE-BX 1490nm TX / 1310nm RX single strand fiber, single mode (SC) [40 km/25 miles]. DIN Rail case, terminal block (Combicon) power connector for external power source	https://www.perle.com/products/media-converters/sr-1110-din-rail-copper-fiber-converters.shtml	Media Converter: SR-1110
05091840	SR-1110-SC80U - 10/100/1000 Industrial Media and Rate Converter: 10/100/1000BASE-T (RJ-45) [100 m/328 ft] to 1000BASE-BX 1510nm TX / 1590nm RX single strand fiber, single mode (SC) [80 km/50 miles]. DIN Rail case, terminal block (Combicon) power connector for external power source	https://www.perle.com/products/media-converters/sr-1110-din-rail-copper-fiber-converters.shtml	Media Converter: SR-1110
05091850	SR-1110-SC80D - 10/100/1000 Industrial Media and Rate Converter: 10/100/1000BASE-T (RJ-45) [100 m/328 ft] to 1000BASE-BX 1590nm TX / 1510nm RX single strand fiber, single mode (SC) [80 km/50 miles]. DIN Rail case, terminal block (Combicon) power connector for external power source	https://www.perle.com/products/media-converters/sr-1110-din-rail-copper-fiber-converters.shtml	Media Converter: SR-1110
05091860	SR-1110-SC120U - 10/100/1000 Industrial Media and Rate Converter: 10/100/1000BASE-T (RJ-45) [100 m/328 ft] to 1000BASE-BX 1510nm TX / 1590nm RX single strand fiber, single mode (SC) [120 km/75 miles]. DIN Rail case, terminal block (Combicon) power connector for external power source	https://www.perle.com/products/media-converters/sr-1110-din-rail-copper-fiber-converters.shtml	Media Converter: SR-1110

Part #	Description	Product Datasheet	Product Group
05091870	SR-1110-SC120D - 10/100/1000 Industrial Media and Rate Converter: 10/100/1000BASE-T (RJ-45) [100 m/328 ft] to 1000BASE-BX 1590nm TX / 1510nm RX single strand fiber, single mode (SC) [120 km/75 miles]. DIN Rail case, terminal block (Combicon) power connector for external power source	https://www.perle.com/products/media-converters/sr-1110-din-rail-copper-fiber-converters.shtml	Media Converter: SR-1110
05091880	SR-1110-SC05D - 10/100/1000 Industrial Media and Rate Converter: 10/100/1000BASE-T (RJ-45) [100 m/328 ft] to 1000BASE-BX 1550nm TX / 1310nm RX single strand fiber, multimode (SC) [500 m/1640 ft]. DIN Rail case, terminal block (Combicon) power connector for external power source	https://www.perle.com/products/media-converters/sr-1110-din-rail-copper-fiber-converters.shtml	Media Converter: SR-1110
05091890	SR-1110-SC05U - 10/100/1000 Industrial Media and Rate Converter: 10/100/1000BASE-T (RJ-45) [100 m/328 ft] to 1000BASE-BX 1310nm TX / 1550nm RX single strand fiber, multimode (SC) [500 m/1640 ft]. DIN Rail case, terminal block (Combicon) power connector for external power source	https://www.perle.com/products/media-converters/sr-1110-din-rail-copper-fiber-converters.shtml	Media Converter: SR-1110
05091900	SR-1110-SC05-XT - 10/100/1000 Industrial Media Rate Converter: 10/100/1000BASE-T (RJ-45) [100 m/328 ft] to 1000BASE-SX 850nm multimode (SC) [550 m/1804 ft], -40F to +167F (-40C to +75C) extended operating temperature support. DIN Rail case, terminal block (Combicon) power connector for external power source .	https://www.perle.com/products/media-converters/sr-1110xt-din-rail-copper-fiber-converters.shtml	Media Converter: SR-1110
05091910	SR-1110-ST05-XT - 10/100/1000 Industrial Media Rate Converter: 10/100/1000BASE-T (RJ-45) [100 m/328 ft] to 1000BASE-SX 850nm multimode (ST) [550 m/1804 ft], -40F to +167F (-40C to +75C) extended operating temperature support. DIN Rail case, terminal block (Combicon) power connector for external power source .	https://www.perle.com/products/media-converters/sr-1110xt-din-rail-copper-fiber-converters.shtml	Media Converter: SR-1110
05091920	SR-1110-SC10-XT - 10/100/1000 Industrial Media Rate Converter: 10/100/1000BASE-T (RJ-45) [100 m/328 ft] to 1000BASE-LX/LH 1310 nm single mode (SC) [10 km/6.2 miles], -40F to +167F (-40C to +75C) extended operating temperature support. DIN Rail case, terminal block (Combicon) power connector for external power source .	https://www.perle.com/products/media-converters/sr-1110xt-din-rail-copper-fiber-converters.shtml	Media Converter: SR-1110
05091930	SR-1110-ST10-XT - 10/100/1000 Industrial Media Rate Converter: 10/100/1000BASE-T (RJ-45) [100 m/328 ft] to 1000BASE-LX/LH 1310 nm single mode (ST) [10 km/6.2 miles], -40F to +167F (-40C to +75C) extended operating temperature support. DIN Rail case, terminal block (Combicon) power connector for external power source	https://www.perle.com/products/media-converters/sr-1110xt-din-rail-copper-fiber-converters.shtml	Media Converter: SR-1110

Part #	Description	Product Datasheet	Product Group
05091940	SR-1110-SC10U-XT - 10/100/1000 Industrial Media Rate Converter: 10/100/1000BASE-T (RJ-45) [100 m/328 ft] to 1000BASE-BX 1310nm TX / 1490nm RX single strand fiber, single mode (SC) [10 km/6.2 miles], -40F to +167F (-40C to +75C) extended operating temperature support. DIN Rail case, terminal block (Combicon) power connector for external power source	https://www.perle.com/products/media-converters/sr-1110xt-din-rail-copper-fiber-converters.shtml	Media Converter: SR-1110
05091950	SR-1110-SC10D-XT - 10/100/1000 Industrial Media Rate Converter: 10/100/1000BASE-T (RJ-45) [100 m/328 ft] to 1000BASE-BX 1490nm TX / 1310nm RX single strand fiber, single mode (SC) [10 km/6.2 miles], -40F to +167F (-40C to +75C) extended operating temperature support. DIN Rail case, terminal block (Combicon) power connector for external power source	https://www.perle.com/products/media-converters/sr-1110xt-din-rail-copper-fiber-converters.shtml	Media Converter: SR-1110
05091960	SR-1110-SFP - 10/100/1000 Industrial Media and Rate Converter: 10/100/1000BASE-T (RJ-45) [100 m/328 ft] to 1000BASE-X or 100BASE-X - SFP Slot (empty). DIN Rail case, terminal block (Combicon) power connector for external power source	https://www.perle.com/products/media-converters/sr-1110-sfp-din-rail-copper-fiber-converter.shtml	Media Converter: SR-1110
05091970	SR-1110-SFP-XT - 10/100/1000 Standalone Media Rate Converter: 10/100/1000BASE-T (RJ-45) [100 m/328 ft] to 1000BASE-X or 100BASE-X - SFP Slot (empty), -40F to +167F (-40C to +75C) extended operating temperature support. DIN Rail case, terminal block (Combicon) power connector for external power source .	https://www.perle.com/products/media-converters/sr-1110-sfp-xt-din-rail-copper-fiber-converter.shtml	Media Converter: SR-1110
05092000	SRS-1110-FSC2 - 10/100/1000 Industrial Media and Rate Converter: 10/100/1000BASE-T (RJ-45) [100 m/328 ft] to 100BASE-FX 1310nm multimode (SC) [2 km/1.2 miles]. Ruggedized to IEC 61850-3/IEEE 1613, -40F to +167F (-40C to +75C) extended operating temperature support. DIN Rail case, terminal block (Combicon) power connector for external power source	https://www.perle.com/products/media-converters/srs-1110f-din-rail-copper-fiber-converters.shtml	Media Converter: SRS-1110
05092010	SRS-1110-FST2 - 10/100/1000 Industrial Media and Rate Converter: 10/100/1000BASE-T (RJ-45) [100 m/328 ft] to 100BASE-FX 1310nm multimode (ST) [2 km/1.2 miles]. Ruggedized to IEC 61850-3/IEEE 1613, -40F to +167F (-40C to +75C) extended operating temperature support. DIN Rail case, terminal block (Combicon) power connector for external power source	https://www.perle.com/products/media-converters/srs-1110f-din-rail-copper-fiber-converters.shtml	Media Converter: SRS-1110

Part #	Description	Product Datasheet	Product Group
05092020	SRS-1110-FSC20 - 10/100/1000 Industrial Media and Rate Converter: 10/100/1000BASE-T (RJ-45) [100 m/328 ft] to 100Base-LX 1310nm single mode (SC) [20 km/12.4 miles]. Ruggedized to IEC 61850-3/IEEE 1613, -40F to +167F (-40C to +75C) extended operating temperature support. DIN Rail case, terminal block (Combicon) power connector for external power source	https://www.perle.com/products/media-converters/srs-1110f-din-rail-copper-fiber-converters.shtml	Media Converter: SRS-1110
05092030	SRS-1110-FST20 - 10/100/1000 Industrial Media and Rate Converter: 10/100/1000BASE-T (RJ-45) [100 m/328 ft] to 100Base-LX 1310nm single mode (ST) [20 km/12.4 miles]. Ruggedized to IEC 61850-3/IEEE 1613, -40F to +167F (-40C to +75C) extended operating temperature support. DIN Rail case, terminal block (Combicon) power connector for external power source	https://www.perle.com/products/media-converters/srs-1110f-din-rail-copper-fiber-converters.shtml	Media Converter: SRS-1110
05092040	SRS-1110-FSC40 - 10/100/1000 Industrial Media and Rate Converter: 10/100/1000BASE-T (RJ-45) [100 m/328 ft] to 100Base-LX 1310nm single mode (SC) [40 km/24.9 miles]. Ruggedized to IEC 61850-3/IEEE 1613, -40F to +167F (-40C to +75C) extended operating temperature support. DIN Rail case, terminal block (Combicon) power connector for external power source	https://www.perle.com/products/media-converters/srs-1110f-din-rail-copper-fiber-converters.shtml	Media Converter: SRS-1110
05092050	SRS-1110-FST40 - 10/100/1000 Industrial Media and Rate Converter: 10/100/1000BASE-T (RJ-45) [100 m/328 ft] to 100Base-LX 1310nm single mode (ST) [40 km/24.9 miles]. Ruggedized to IEC 61850-3/IEEE 1613, -40F to +167F (-40C to +75C) extended operating temperature support. DIN Rail case, terminal block (Combicon) power connector for external power source	https://www.perle.com/products/media-converters/srs-1110f-din-rail-copper-fiber-converters.shtml	Media Converter: SRS-1110
05092060	SRS-1110-FSC20U - 10/100/1000 Industrial Media and Rate Converter: 10/100/1000BASE-T (RJ-45) [100 m/328 ft] to 100Base-BX 1310nm TX / 1550nm RX single strand fiber, single mode (SC) [20 km/12.4 miles]. Ruggedized to IEC 61850-3/IEEE 1613, -40F to +167F (-40C to +75C) extended operating temperature support. DIN Rail case, terminal block (Combicon) power connector for external power source	https://www.perle.com/products/media-converters/srs-1110f-din-rail-copper-fiber-converters.shtml	Media Converter: SRS-1110

Part #	Description	Product Datasheet	Product Group
05092070	SRS-1110-FSC20D - 10/100/1000 Industrial Media and Rate Converter: 10/100/1000BASE-T (RJ-45) [100 m/328 ft] to 100Base-BX 1550nm TX / 1310nm RX single strand fiber, single mode (SC) [20 km/12.4 miles]. Ruggedized to IEC 61850-3/IEEE 1613, -40F to +167F (-40C to +75C) extended operating temperature support. DIN Rail case, terminal block (Combicon) power connector for external power source	https://www.perle.com/products/media-converters/srs-1110-sfp-din-rail-copper-fiber-converter.shtml	Media Converter: SRS-1110
05092080	SRS-1110-SFP - 10/100/1000 Industrial Media and Rate Converter: 10/100/1000BASE-T (RJ-45) [100 m/328 ft] to 1000BASE-X or 100BASE-X - SFP Slot (empty) - Ruggedized to IEC 61850-3/IEEE 1613, -40F to +167F (-40C to +75C) extended operating temperature support. DIN Rail case, terminal block (Combicon) power connector for external power source	https://www.perle.com/products/media-converters/srs-1110g-din-rail-copper-fiber-converters.shtml	Media Converter: SRS-1110
05092090	SRS-1110-GSC05 - 10/100/1000 Industrial Media Rate Converter: 10/100/1000BASE-T (RJ-45) [100 m/328 ft] to 1000BASE-SX 850nm multimode (SC) [550 m/1804 ft]. Ruggedized to IEC 61850-3/IEEE 1613, -40F to +167F (-40C to +75C) extended operating temperature support. DIN Rail case, terminal block (Combicon) power connector for external power source .	https://www.perle.com/products/media-converters/srs-1110g-din-rail-copper-fiber-converters.shtml	Media Converter: SRS-1110
05092100	SRS-1110-GST05 - 10/100/1000 Industrial Media Rate Converter: 10/100/1000BASE-T (RJ-45) [100 m/328 ft] to 1000BASE-SX 850nm multimode (ST) [550 m/1804 ft]. Ruggedized to IEC 61850-3/IEEE 1613, -40F to +167F (-40C to +75C) extended operating temperature support. DIN Rail case, terminal block (Combicon) power connector for external power source .	https://www.perle.com/products/media-converters/srs-1110g-din-rail-copper-fiber-converters.shtml	Media Converter: SRS-1110
05092110	SRS-1110-GSC10 - 10/100/1000 Industrial Media Rate Converter: 10/100/1000BASE-T (RJ-45) [100 m/328 ft] to 1000BASE-LX/LH 1310 nm single mode (SC) [10 km/6.2 miles]. Ruggedized to IEC 61850-3/IEEE 1613, -40F to +167F (-40C to +75C) extended operating temperature support. DIN Rail case, terminal block (Combicon) power connector for external power source .	https://www.perle.com/products/media-converters/srs-1110g-din-rail-copper-fiber-converters.shtml	Media Converter: SRS-1110
05092120	SRS-1110-GST10 - 10/100/1000 Industrial Media Rate Converter: 10/100/1000BASE-T (RJ-45) [100 m/328 ft] to 1000BASE-LX/LH 1310 nm single mode (ST) [10 km/6.2 miles]. Ruggedized to IEC 61850-3/IEEE 1613, -40F to +167F (-40C to +75C) extended operating temperature support. DIN Rail case, terminal block (Combicon) power connector for external power source	https://www.perle.com/products/media-converters/srs-1110g-din-rail-copper-fiber-converters.shtml	Media Converter: SRS-1110

Part #	Description	Product Datasheet	Product Group
05092130	SRS-1110-GSC10U - 10/100/1000 Industrial Media Rate Converter: 10/100/1000BASE-T (RJ-45) [100 m/328 ft] to 1000BASE-BX 1310nm TX / 1490nm RX single strand fiber, single mode (SC) [10 km/6.2 miles]. Ruggedized to IEC 61850-3/IEEE 1613, -40F to +167F (-40C to +75C) extended operating temperature support. DIN Rail case, terminal block (Combicon) power connector for external power source	https://www.perle.com/products/media-converters/srs-1110g-din-rail-copper-fiber-converters.shtml	Media Converter: SRS-1110
05092140	SRS-1110-GSC10D - 10/100/1000 Industrial Media Rate Converter: 10/100/1000BASE-T (RJ-45) [100 m/328 ft] to 1000BASE-BX 1490nm TX / 1310nm RX single strand fiber, single mode (SC) [10 km/6.2 miles]. Ruggedized to IEC 61850-3/IEEE 1613, -40F to +167F (-40C to +75C) extended operating temperature support. DIN Rail case, terminal block (Combicon) power connector for external power source	https://www.perle.com/products/media-converters/srs-1110g-din-rail-copper-fiber-converters.shtml	Media Converter: SRS-1110
06003502	eX-1S110-RJ - Fast Ethernet Extender: 1 port 10/100Base-TX (RJ-45). RJ45 Interlink (VDSL2) connector - EU Power Cord	https://www.perle.com/products/10-100-ethernet-extender.shtml	Ethernet Extender: eX-S110
06003512	eX-1S110-BNC - Fast Ethernet Extender: 1 port 10/100Base-TX (RJ-45). BNC (Coax) Interlink (VDSL2) connector - EU Power Cord	https://www.perle.com/products/10-100-ethernet-extender.shtml	Ethernet Extender: eX-S110
06003522	eX-1S110-TB - Fast Ethernet Extender: 1 port 10/100Base-TX (RJ-45). 2-pin Terminal Block Interlink (VDSL2) connector - EU Power Cord	https://www.perle.com/products/10-100-ethernet-extender.shtml	Ethernet Extender: eX-S110
06003532	eX-1S1110-RJ - Gigabit Ethernet Extender: 1 port 10/100/1000Base-T (RJ-45). RJ45 Interlink (VDSL2) connector - EU Power Cord	https://www.perle.com/products/10-100-managed-ethernet-extender.shtml	Ethernet Extender: eX-S1110
06003542	eX-1S1110-BNC - Gigabit Ethernet Extender: 1 port 10/100/1000Base-T (RJ-45). BNC (Coax) Interlink (VDSL2) connector - EU Power Cord	https://www.perle.com/products/10-100-managed-ethernet-extender.shtml	Ethernet Extender: eX-S1110
06003552	eX-1S1110-TB - Gigabit Ethernet Extender: 1 port 10/100/1000Base-T (RJ-45). 2-pin Terminal Block Interlink (VDSL2) connector - EU Power Cord	https://www.perle.com/products/10-100-managed-ethernet-extender.shtml	Ethernet Extender: eX-S1110
06003560	eX-1C110-RJ Fast Ethernet Extender Module: 1 port 10/100Base-TX (RJ-45). RJ45 Interlink (VDSL2) connector.	https://www.perle.com/products/10-100-ethernet-extender-module.shtml	Ethernet Extender Module: eX-C110
06003570	eX-1C110-BNC Fast Ethernet Extender Module: 1 port 10/100Base-TX (RJ-45). BNC (Coax) Interlink (VDSL2) connector.	https://www.perle.com/products/10-100-ethernet-extender-module.shtml	Ethernet Extender Module: eX-C110
06003580	eX-1C110-TB Fast Ethernet Extender Module: 1 port 10/100Base-TX (RJ-45). 2-pin Terminal Block Interlink (VDSL2) connector.	https://www.perle.com/products/10-100-ethernet-extender-module.shtml	Ethernet Extender Module: eX-C110
06003590	eX-1C1110-RJ Gigabit Ethernet Extender Module: 1 port 10/100/1000Base-T (RJ-45). RJ45 Interlink (VDSL2) connector.	https://www.perle.com/products/10-100-1000-ethernet-extender-module.shtml	Ethernet Extender Module: eX-C1110
06003600	eX-1C1110-BNC Gigabit Ethernet Extender Module: 1 port 10/100/1000Base-T (RJ-45). BNC (Coax) Interlink (VDSL2) connector.	https://www.perle.com/products/10-100-1000-ethernet-extender-module.shtml	Ethernet Extender Module: eX-C1110

Part #	Description	Product Datasheet	Product Group
06003610	eX-1C1110-TB Gigabit Ethernet Extender Module: 1 port 10/100/1000Base-T (RJ-45), 2-pin Terminal Block Interlink (VDSL2) connector.	https://www.perle.com/products/10-100-1000-ethernet-extender-module.shtml	Ethernet Extender Module: eX-C1110
06003620	eX-1S110-RJ-XT - Industrial Temperature Fast Ethernet Extender: 1 port 10/100Base-TX (RJ-45), RJ45 Interlink (VDSL2) connector. -40C to 75C (-40F to 167F) operating temperature	https://www.perle.com/products/10-100-industrial-ethernet-extender.shtml	Ethernet Extender: eX-S110
06003630	eX-1S110-BNC-XT - Industrial Temperature Fast Ethernet Extender: 1 port 10/100Base-TX (RJ-45), BNC (Coax) Interlink (VDSL2) connector. -40C to 75C (-40F to 167F) operating temperature	https://www.perle.com/products/10-100-industrial-ethernet-extender.shtml	Ethernet Extender: eX-S110
06003640	eX-1S110-TB-XT - Industrial Temperature Fast Ethernet Extender: 1 port 10/100Base-TX (RJ-45), 2-pin Terminal Block Interlink (VDSL2) connector. -40C to 75C (-40F to 167F) operating temperature	https://www.perle.com/products/10-100-industrial-ethernet-extender.shtml	Ethernet Extender: eX-S110
06003650	eX-1S1110-RJ-XT - Industrial Temperature Gigabit Ethernet Extender: 1 port 10/100/1000Base-T (RJ-45), RJ45 Interlink (VDSL2) connector. -40C to 75C (-40F to 167F) operating temperature	https://www.perle.com/products/10-100-1000-industrial-ethernet-extender.shtml	Ethernet Extender: eX-S1110
06003660	eX-1S1110-BNC-XT - Industrial Temperature Gigabit Ethernet Extender: 1 port 10/100/1000Base-T (RJ-45), BNC (Coax) Interlink (VDSL2) connector. -40C to 75C (-40F to 167F) operating temperature	https://www.perle.com/products/10-100-1000-industrial-ethernet-extender.shtml	Ethernet Extender: eX-S1110
06003670	eX-1S1110-TB-XT - Industrial Temperature Gigabit Ethernet Extender: 1 port 10/100/1000Base-T (RJ-45), 2-pin Terminal Block Interlink (VDSL2) connector. -40C to 75C (-40F to 167F) operating temperature	https://www.perle.com/products/10-100-1000-industrial-ethernet-extender.shtml	Ethernet Extender: eX-S1110
06003682	eX-4S110-RJ - Fast Ethernet Extender: 4 port 10/100Base-TX (RJ-45), RJ45 Interlink (VDSL2) connector - EU Power Cord	https://www.perle.com/products/10-100-ethernet-extender.shtml	Ethernet Extender: eX-S110
06003692	eX-4S110-BNC - Fast Ethernet Extender: 4 port 10/100Base-TX (RJ-45), BNC (Coax) Interlink (VDSL2) connector - EU Power Cord	https://www.perle.com/products/10-100-ethernet-extender.shtml	Ethernet Extender: eX-S110
06003702	eX-4S110-TB - Fast Ethernet Extender: 4 port 10/100Base-TX (RJ-45), 2-pin Terminal Block Interlink (VDSL2) connector - EU Power Cord	https://www.perle.com/products/10-100-ethernet-extender.shtml	Ethernet Extender: eX-S110
06003712	eX-4S1110-RJ - Gigabit Ethernet Extender: 4 port 10/100/1000Base-T (RJ-45), RJ45 Interlink (VDSL2) connector - EU Power Cord	https://www.perle.com/products/10-100-managed-ethernet-extender.shtml	Ethernet Extender: eX-S1110
06003722	eX-4S1110-BNC - Gigabit Ethernet Extender: 4 port 10/100/1000Base-T (RJ-45), BNC (Coax) Interlink (VDSL2) connector - EU Power Cord	https://www.perle.com/products/10-100-managed-ethernet-extender.shtml	Ethernet Extender: eX-S1110
06003732	eX-4S1110-TB - Gigabit Ethernet Extender: 4 port 10/100/1000Base-T (RJ-45), 2-pin Terminal Block Interlink (VDSL2) connector - EU Power Cord	https://www.perle.com/products/10-100-managed-ethernet-extender.shtml	Ethernet Extender: eX-S1110

Part #	Description	Product Datasheet	Product Group
06003740	eX-4S110-RJ-XT - Industrial Temperature Fast Ethernet Extender: 4 port 10/100Base-TX (RJ-45). RJ45 Interlink (VDSL2) connector. -40C to 75C (-40F to 167F) operating temperature	https://www.perle.com/products/10-100-industrial-ethernet-extender.shtml	Ethernet Extender: eX-S110
06003750	eX-4S110-BNC-XT - Industrial Temperature Fast Ethernet Extender: 4 port 10/100Base-TX (RJ-45). BNC (Coax) Interlink (VDSL2) connector. -40C to 75C (-40F to 167F) operating temperature	https://www.perle.com/products/10-100-industrial-ethernet-extender.shtml	Ethernet Extender: eX-S110
06003760	eX-4S110-TB-XT - Industrial Temperature Fast Ethernet Extender: 4 port 10/100Base-TX (RJ-45). 2-pin Terminal Block Interlink (VDSL2) connector. -40C to 75C (-40F to 167F) operating temperature	https://www.perle.com/products/10-100-industrial-ethernet-extender.shtml	Ethernet Extender: eX-S110
06003770	eX-4S1110-RJ-XT - Industrial Temperature Gigabit Ethernet Extender: 4 port 10/100/1000Base-T (RJ-45). RJ45 Interlink (VDSL2) connector. -40C to 75C (-40F to 167F) operating temperature	https://www.perle.com/products/10-100-1000-industrial-ethernet-extender.shtml	Ethernet Extender: eX-S1110
06003780	eX-4S1110-BNC-XT - Industrial Temperature Gigabit Ethernet Extender: 4 port 10/100/1000Base-T (RJ-45). BNC (Coax) Interlink (VDSL2) connector. -40C to 75C (-40F to 167F) operating temperature	https://www.perle.com/products/10-100-1000-industrial-ethernet-extender.shtml	Ethernet Extender: eX-S1110
06003790	eX-4S1110-TB-XT - Industrial Temperature Gigabit Ethernet Extender: 4 port 10/100/1000Base-T (RJ-45). 2-pin Terminal Block Interlink (VDSL2) connector. -40C to 75C (-40F to 167F) operating temperature	https://www.perle.com/products/10-100-1000-industrial-ethernet-extender.shtml	Ethernet Extender: eX-S1110
06003802	eX-KIT11-S110-RJ - Fast Ethernet Extender Kit. 1 pair of 1 port eX-1S110-RJ Ethernet Extenders - EU Power Cord	https://www.perle.com/products/10-100-ethernet-extender.shtml	Ethernet Extender: eX-S110
06003812	eX-KIT11-S110-BNC - Fast Ethernet Extender Kit. 1 pair of 1 port eX-1S110-BNC Ethernet Extenders - EU Power Cord	https://www.perle.com/products/10-100-ethernet-extender.shtml	Ethernet Extender: eX-S110
06003822	eX-KIT11-S110-TB - Fast Ethernet Extender Kit. 1 pair of 1 port eX-1S110-TB Ethernet Extenders - EU Power Cord	https://www.perle.com/products/10-100-ethernet-extender.shtml	Ethernet Extender: eX-S110
06003832	eX-KIT11-S1110-RJ - Gigabit Extender Kit. 1 pair of 1 port eX-1S1110-RJ Ethernet Extenders - EU Power Cord	https://www.perle.com/products/10-100-managed-ethernet-extender.shtml	Ethernet Extender: eX-S1110
06003842	eX-KIT11-S1110-BNC - Gigabit Extender Kit. 1 pair of 1 port eX-1S1110-BNC Ethernet Extenders - EU Power Cord	https://www.perle.com/products/10-100-managed-ethernet-extender.shtml	Ethernet Extender: eX-S1110
06003852	eX-KIT11-S1110-TB - Gigabit Extender Kit. 1 pair of 1 port eX-1S1110-TB Ethernet Extenders - EU Power Cord	https://www.perle.com/products/10-100-managed-ethernet-extender.shtml	Ethernet Extender: eX-S1110
06003862	eX-KIT44-S110-RJ - Fast Ethernet Extender Kit. 1 pair of 4 port eX-4S110-RJ Ethernet Extenders - EU Power Cord	https://www.perle.com/products/10-100-ethernet-extender.shtml	Ethernet Extender: eX-S110
06003872	eX-KIT44-S110-BNC - Fast Ethernet Extender Kit. 1 pair of 4 port eX-4S110-BNC Ethernet Extenders - EU Power Cord	https://www.perle.com/products/10-100-ethernet-extender.shtml	Ethernet Extender: eX-S110

Part #	Description	Product Datasheet	Product Group
06003882	eX-KIT44-S110-TB - Fast Ethernet Extender Kit. 1 pair of 4 port eX-4S110-TB Ethernet Extenders - EU Power Cord	https://www.perle.com/products/10-100-ethernet-extender.shtml	Ethernet Extender: eX-S110
06003892	eX-KIT44-S1110-RJ - Gigabit Extender Kit. 1 pair of 4 port eX-4S1110-RJ Ethernet Extenders - EU Power Cord	https://www.perle.com/products/10-100-managed-ethernet-extender.shtml	Ethernet Extender: eX-S1110
06003902	eX-KIT44-S1110-BNC - Gigabit Extender Kit. 1 pair of 4 port eX-4S1110-BNC Ethernet Extenders - EU Power Cord	https://www.perle.com/products/10-100-managed-ethernet-extender.shtml	Ethernet Extender: eX-S1110
06003912	eX-KIT44-S1110-TB - Gigabit Extender Kit. 1 pair of 4 port eX-4S1110-TB Ethernet Extenders - EU Power Cord	https://www.perle.com/products/10-100-managed-ethernet-extender.shtml	Ethernet Extender: eX-S1110
06003920	eX-1CM110-RJ Managed Fast Ethernet Extender Module: 1 port 10/100Base-TX (RJ-45). RJ45 Interlink (VDSL2) connector.	https://www.perle.com/products/10-100-managed-ethernet-extender-module.shtml	Ethernet Extender Module: eX-CM110
06003930	eX-1CM110-BNC Managed Fast Ethernet Extender Module: 1 port 10/100Base-TX (RJ-45). BNC (Coax) Interlink (VDSL2) connector.	https://www.perle.com/products/10-100-managed-ethernet-extender-module.shtml	Ethernet Extender Module: eX-CM110
06003940	eX-1CM110-TB Managed Fast Ethernet Extender Module: 1 port 10/100Base-TX (RJ-45). 2-pin Terminal Block Interlink (VDSL2) connector.	https://www.perle.com/products/10-100-managed-ethernet-extender-module.shtml	Ethernet Extender Module: eX-CM110
06003950	eX-1CM1110-RJ Managed Gigabit Ethernet Extender Module: 1 port 10/100/1000Base-T (RJ-45). RJ45 Interlink (VDSL2) connector.	https://www.perle.com/products/10-100-1000-managed-ethernet-extender-module.shtml	Ethernet Extender Module: eX-CM1110
06003960	eX-1CM1110-BNC Managed Gigabit Ethernet Extender Module: 1 port 10/100/1000Base-T (RJ-45). BNC (Coax) Interlink (VDSL2) connector.	https://www.perle.com/products/10-100-1000-managed-ethernet-extender-module.shtml	Ethernet Extender Module: eX-CM1110
06003970	eX-1CM1110-TB Managed Gigabit Ethernet Extender Module: 1 port 10/100/1000Base-T (RJ-45). 2-pin Terminal Block Interlink (VDSL2) connector.	https://www.perle.com/products/10-100-1000-managed-ethernet-extender-module.shtml	Ethernet Extender Module: eX-CM1110
06004102	eX-1SM110-RJ - Managed Fast Ethernet Extender: 1 port 10/100Base-TX (RJ-45). RJ45 Interlink (VDSL2) connector - EU Power Cord	https://www.perle.com/products/10-100-managed-ethernet-extender.shtml	Ethernet Extender: eX-SM110
06004112	eX-1SM110-BNC - Managed Fast Ethernet Extender: 1 port 10/100Base-TX (RJ-45). BNC (Coax) Interlink (VDSL2) connector - EU Power Cord	https://www.perle.com/products/10-100-managed-ethernet-extender.shtml	Ethernet Extender: eX-SM110
06004122	eX-1SM110-TB - Managed Fast Ethernet Extender: 1 port 10/100Base-TX (RJ-45). 2-pin Terminal Block Interlink (VDSL2) connector - EU Power Cord	https://www.perle.com/products/10-100-managed-ethernet-extender.shtml	Ethernet Extender: eX-SM110
06004132	eX-1SM1110-RJ - Managed Gigabit Ethernet Extender: 1 port 10/100/1000Base-T (RJ-45). RJ45 Interlink (VDSL2) connector - EU Power Cord	https://www.perle.com/products/10-100-1000-managed-ethernet-extender.shtml	Ethernet Extender: eX-SM1110
06004142	eX-1SM1110-BNC - Managed Gigabit Ethernet Extender: 1 port 10/100/1000Base-T (RJ-45). BNC (Coax) Interlink (VDSL2) connector - EU Power Cord	https://www.perle.com/products/10-100-1000-managed-ethernet-extender.shtml	Ethernet Extender: eX-SM1110

Part #	Description	Product Datasheet	Product Group
06004152	eX-1SM1110-TB - Managed Gigabit Ethernet Extender: 1 port 10/100/1000Base-T (RJ-45). 2-pin Terminal Block Interlink (VDSL2) connector - EU Power Cord	https://www.perle.com/products/10-100-1000-managed-ethernet-extender.shtml	Ethernet Extender: eX-SM1110
06004222	eXP-1S110L-RJ - PoE Fast Ethernet Extender: 1 port 10/100Base-TX (RJ-45). RJ45 Interlink (VDSL2) connector. Provides power over VDSL Link. 48V 65W adapter included - EU Power Cord	https://www.perle.com/products/10-100-poe-ethernet-extender.shtml	Ethernet Extender: eXP-S110
06004232	eXP-1S110L-BNC - PoE Fast Ethernet Extender: 1 port 10/100Base-TX (RJ-45). BNC Interlink (VDSL2) connector. Provides power over VDSL Link. 48V 65W adapter included - EU Power Cord	https://www.perle.com/products/10-100-poe-ethernet-extender.shtml	Ethernet Extender: eXP-S110
06004242	eXP-1S110L-TB - PoE Fast Ethernet Extender: 1 port 10/100Base-TX (RJ-45). Terminal Block Interlink (VDSL2) connector. Provides power over VDSL Link. 48V 65W adapter included - EU Power Cord	https://www.perle.com/products/10-100-poe-ethernet-extender.shtml	Ethernet Extender: eXP-S110
06004252	eXP-1S110L-RJ - PoE Gigabit Ethernet Extender: 1 port 10/100/1000Base-T (RJ-45). RJ45 Interlink (VDSL2) connector. Provides power over VDSL Link. 48V 65W adapter included - EU Power Cord	https://www.perle.com/products/10-100-1000-poe-ethernet-extender.shtml	Ethernet Extender: eXP-S110
06004262	eXP-1S110L-BNC - PoE Gigabit Ethernet Extender: 1 port 10/100/1000Base-T (RJ-45). BNC Interlink (VDSL2) connector. Provides power over VDSL Link. 48V 65W adapter included - EU Power Cord	https://www.perle.com/products/10-100-1000-poe-ethernet-extender.shtml	Ethernet Extender: eXP-S110
06004272	eXP-1S110L-TB - PoE Gigabit Ethernet Extender: 1 port 10/100/1000Base-T (RJ-45). Terminal Block Interlink (VDSL2) connector. Provides power over VDSL Link. 48V 65W adapter included - EU Power Cord	https://www.perle.com/products/10-100-1000-poe-ethernet-extender.shtml	Ethernet Extender: eXP-S110
06004280	eXP-1S110L-RJ-XT - Industrial Temperature PoE Fast Ethernet Extender: 1 port 10/100Base-TX (RJ-45). RJ45 Interlink (VDSL2) connector. Provides power over VDSL Link. -40C to 75C (-40F to 167F) operating temperature	https://www.perle.com/products/10-100-industrial-poe-ethernet-extender.shtml	Ethernet Extender: eXP-S110
06004290	eXP-1S110L-BNC-XT - Industrial Temperature PoE Fast Ethernet Extender: 1 port 10/100Base-TX (RJ-45). BNC Interlink (VDSL2) connector. Provides power over VDSL Link. -40C to 75C (-40F to 167F) operating temperature	https://www.perle.com/products/10-100-industrial-poe-ethernet-extender.shtml	Ethernet Extender: eXP-S110
06004300	eXP-1S110L-TB-XT - Industrial Temperature PoE Fast Ethernet Extender: 1 port 10/100Base-TX (RJ-45). Terminal Block Interlink (VDSL2) connector. Provides power over VDSL Link. -40C to 75C (-40F to 167F) operating temperature	https://www.perle.com/products/10-100-industrial-poe-ethernet-extender.shtml	Ethernet Extender: eXP-S110

Part #	Description	Product Datasheet	Product Group
06004310	eXP-1S1110L-RJ-XT - Industrial Temperature PoE Gigabit Ethernet Extender: 1 port 10/100/1000Base-T (RJ-45). RJ45 Interlink (VDSL2) connector. Provides power over VDSL Link. -40C to 75C (-40F to 167F) operating temperature	https://www.perle.com/products/10-100-1000-industrial-poe-ethernet-extender.shtml	Ethernet Extender: eXP-S1110
06004320	eXP-1S1110L-BNC-XT - Industrial Temperature PoE Gigabit Ethernet Extender: 1 port 10/100/1000Base-T (RJ-45). BNC Interlink (VDSL2) connector. Provides power over VDSL Link. -40C to 75C (-40F to 167F) operating temperature	https://www.perle.com/products/10-100-1000-industrial-poe-ethernet-extender.shtml	Ethernet Extender: eXP-S1110
06004330	eXP-1S1110L-TB-XT - Industrial Temperature PoE Gigabit Ethernet Extender: 1 port 10/100/1000Base-T (RJ-45). Terminal Block Interlink (VDSL2) connector. Provides power over VDSL Link. -40C to 75C (-40F to 167F) operating temperature	https://www.perle.com/products/10-100-1000-industrial-poe-ethernet-extender.shtml	Ethernet Extender: eXP-S1110
06004462	eXP-4S1110L-RJ - PoE Fast Ethernet Extender: 4 port 10/100Base-TX (RJ-45). RJ45 Interlink (VDSL2) connector. Provides power over VDSL Link. 48V 65W adapter included - EU Power Cord	https://www.perle.com/products/10-100-poe-ethernet-extender.shtml	Ethernet Extender: eXP-S110
06004472	eXP-4S1110L-BNC - PoE Fast Ethernet Extender: 4 port 10/100Base-TX (RJ-45). BNC Interlink (VDSL2) connector. Provides power over VDSL Link. 48V 65W adapter included - EU Power Cord	https://www.perle.com/products/10-100-poe-ethernet-extender.shtml	Ethernet Extender: eXP-S110
06004482	eXP-4S1110L-TB - PoE Fast Ethernet Extender: 4 port 10/100Base-TX (RJ-45). Terminal Block Interlink (VDSL2) connector. Provides power over VDSL Link. 48V 65W adapter included - EU Power Cord	https://www.perle.com/products/10-100-poe-ethernet-extender.shtml	Ethernet Extender: eXP-S110
06004492	eXP-4S1110L-RJ - PoE Gigabit Ethernet Extender: 4 port 10/100/1000Base-T (RJ-45). RJ45 Interlink (VDSL2) connector. Provides power over VDSL Link. 48V 65W adapter included - EU Power Cord	https://www.perle.com/products/10-100-1000-poe-ethernet-extender.shtml	Ethernet Extender: eXP-S1110
06004502	eXP-4S1110L-BNC - PoE Gigabit Ethernet Extender: 4 port 10/100/1000Base-T (RJ-45). BNC Interlink (VDSL2) connector. Provides power over VDSL Link. 48V 65W adapter included - EU Power Cord	https://www.perle.com/products/10-100-1000-poe-ethernet-extender.shtml	Ethernet Extender: eXP-S1110
06004512	eXP-4S1110L-TB - PoE Gigabit Ethernet Extender: 4 port 10/100/1000Base-T (RJ-45). Terminal Block Interlink (VDSL2) connector. Provides power over VDSL Link. 48V 65W adapter included - EU Power Cord	https://www.perle.com/products/10-100-1000-poe-ethernet-extender.shtml	Ethernet Extender: eXP-S1110
06004520	eXP-4S1110L-RJ-XT - Industrial Temperature PoE Fast Ethernet Extender: 4 port 10/100Base-TX (RJ-45). RJ45 Interlink (VDSL2) connector. Provides power over VDSL Link. -40C to 75C (-40F to 167F) operating temperature	https://www.perle.com/products/10-100-industrial-poe-ethernet-extender.shtml	Ethernet Extender: eXP-S110

Part #	Description	Product Datasheet	Product Group
06004530	eXP-4S110L-BNC-XT - Industrial Temperature PoE Fast Ethernet Extender: 4 port 10/100Base-TX (RJ-45). BNC Interlink (VDSL2) connector. Provides power over VDSL Link. -40C to 75C (-40F to 167F) operating temperature	https://www.perle.com/products/10-100-industrial-poe-ethernet-extender.shtml	Ethernet Extender: eXP-S110
06004540	eXP-4S110L-TB-XT - Industrial Temperature PoE Fast Ethernet Extender: 4 port 10/100Base-TX (RJ-45). Terminal Block Interlink (VDSL2) connector. Provides power over VDSL Link. -40C to 75C (-40F to 167F) operating temperature	https://www.perle.com/products/10-100-industrial-poe-ethernet-extender.shtml	Ethernet Extender: eXP-S110
06004550	eXP-4S1110L-RJ-XT - Industrial Temperature PoE Gigabit Ethernet Extender.- 4 port 10/100/1000Base-T (RJ-45). RJ45 Interlink (VDSL2) connector. Provides power over VDSL Link. -40C to 75C (-40F to 167F) operating temperature	https://www.perle.com/products/10-100-1000-industrial-poe-ethernet-extender.shtml	Ethernet Extender: eXP-S1110
06004560	eXP-4S1110L-BNC-XT - Industrial Temperature PoE Gigabit Extender: 4 port 10/100/1000Base-T (RJ-45). BNC Interlink (VDSL2) connector. Provides power over VDSL Link. -40C to 75C (-40F to 167F) operating temperature	https://www.perle.com/products/10-100-1000-industrial-poe-ethernet-extender.shtml	Ethernet Extender: eXP-S1110
06004570	eXP-4S1110L-TB-XT - Industrial Temperature PoE Gigabit Ethernet Extender.- 4 port 10/100/1000Base-T (RJ-45). Terminal Block Interlink (VDSL2) connector. Provides power over VDSL Link. -40C to 75C (-40F to 167F) operating temperature	https://www.perle.com/products/10-100-1000-industrial-poe-ethernet-extender.shtml	Ethernet Extender: eXP-S1110
06004582	eXP-1S110E-RJ - PoE Fast Ethernet Extender: 1 port 10/100Base-TX (RJ-45). RJ45 Interlink (VDSL2) connector. Provides power over Ethernet as a PSE. 48V 65W adapter included - EU Power Cord	https://www.perle.com/products/10-100-poe-ethernet-extender.shtml	Ethernet Extender: eXP-S110
06004592	eXP-1S110E-BNC - PoE Fast Ethernet Extender: 1 port 10/100Base-TX (RJ-45). BNC Interlink (VDSL2) connector. Provides power over Ethernet as a PSE. 48V 65W adapter included - EU Power Cord	https://www.perle.com/products/10-100-poe-ethernet-extender.shtml	Ethernet Extender: eXP-S110
06004602	eXP-1S110E-TB - PoE Fast Ethernet Extender: 1 port 10/100Base-TX (RJ-45). Terminal Block Interlink (VDSL2) connector. Provides power over Ethernet as a PSE. 48V 65W adapter included - EU Power Cord	https://www.perle.com/products/10-100-poe-ethernet-extender.shtml	Ethernet Extender: eXP-S110
06004612	eXP-1S1110E-RJ - PoE Gigabit Ethernet Extender: 1 port 10/100/1000Base-T (RJ-45). RJ45 Interlink (VDSL2) connector. Provides power over Ethernet as a PSE. 48V 65W adapter included - EU Power Cord	https://www.perle.com/products/10-100-1000-poe-ethernet-extender.shtml	Ethernet Extender: eXP-S1110
06004622	eXP-1S1110E-BNC - PoE Gigabit Ethernet Extender: 1 port 10/100/1000Base-T (RJ-45). BNC Interlink (VDSL2) connector. Provides power over Ethernet as a PSE. 48V 65W adapter included - EU Power Cord	https://www.perle.com/products/10-100-1000-poe-ethernet-extender.shtml	Ethernet Extender: eXP-S1110

Part #	Description	Product Datasheet	Product Group
06004632	eXP-1S1110E-TB - PoE Gigabit Ethernet Extender: 1 port 10/100/1000Base-T (RJ-45). Terminal Block Interlink (VDSL2) connector. Provides power over Ethernet as a PSE. 48V 65W adapter included - EU Power Cord	https://www.perle.com/products/10-100-1000-poe-ethernet-extender.shtml	Ethernet Extender: eXP-S1110
06004702	eXP-4S1110E-RJ - PoE Fast Ethernet Extender: 4 port 10/100Base-TX (RJ-45). RJ45 Interlink (VDSL2) connector. Provides power over Ethernet as a PSE. 48V 65W adapter included - EU Power Cord	https://www.perle.com/products/10-100-poe-ethernet-extender.shtml	Ethernet Extender: eXP-S110
06004712	eXP-4S1110E-BNC - PoE Fast Ethernet Extender: 4 port 10/100Base-TX (RJ-45). BNC Interlink (VDSL2) connector. Provides power over Ethernet as a PSE. 48V 65W adapter included - EU Power Cord	https://www.perle.com/products/10-100-poe-ethernet-extender.shtml	Ethernet Extender: eXP-S110
06004722	eXP-4S1110E-TB - PoE Fast Ethernet Extender: 4 port 10/100Base-TX (RJ-45). Terminal Block Interlink (VDSL2) connector. Provides power over Ethernet as a PSE. 48V 65W adapter included - EU Power Cord	https://www.perle.com/products/10-100-poe-ethernet-extender.shtml	Ethernet Extender: eXP-S110
06004732	eXP-4S1110E-RJ - PoE Gigabit Ethernet Extender: 4 port 10/100/1000Base-T (RJ-45). RJ45 Interlink (VDSL2) connector. Provides power over Ethernet as a PSE. 48V 65W adapter included - EU Power Cord	https://www.perle.com/products/10-100-1000-poe-ethernet-extender.shtml	Ethernet Extender: eXP-S1110
06004742	eXP-4S1110E-BNC - PoE Gigabit Ethernet Extender: 4 port 10/100/1000Base-T (RJ-45). BNC Interlink (VDSL2) connector. Provides power over Ethernet as a PSE. 48V 65W adapter included - EU Power Cord	https://www.perle.com/products/10-100-1000-poe-ethernet-extender.shtml	Ethernet Extender: eXP-S1110
06004752	eXP-4S1110E-TB - PoE Gigabit Ethernet Extender: 4 port 10/100/1000Base-T (RJ-45). Terminal Block Interlink (VDSL2) connector. Provides power over Ethernet as a PSE. 48V 65W adapter included - EU Power Cord	https://www.perle.com/products/10-100-1000-poe-ethernet-extender.shtml	Ethernet Extender: eXP-S1110
06004760	eXP-1S1110E-RJ-XT - Industrial Temperature PoE Fast Ethernet Extender: 1 port 10/100Base-TX (RJ-45). RJ45 Interlink (VDSL2) connector. Provides power over Ethernet as a PSE. -40C to 75C (-40F to 167F) operating temperature	https://www.perle.com/products/10-100-industrial-poe-ethernet-extender.shtml	Ethernet Extender: eXP-S110
06004770	eXP-1S1110E-BNC-XT - Industrial Temperature PoE Fast Ethernet Extender: 1 port 10/100Base-TX (RJ-45). BNC Interlink (VDSL2) connector. Provides power over Ethernet as a PSE. -40C to 75C (-40F to 167F) operating temperature	https://www.perle.com/products/10-100-industrial-poe-ethernet-extender.shtml	Ethernet Extender: eXP-S110
06004780	eXP-1S1110E-TB-XT - Industrial Temperature PoE Fast Ethernet Extender: 1 port 10/100Base-TX (RJ-45). Terminal Block Interlink (VDSL2) connector. Provides power over Ethernet as a PSE. -40C to 75C (-40F to 167F) operating temperature	https://www.perle.com/products/10-100-industrial-poe-ethernet-extender.shtml	Ethernet Extender: eXP-S110

Part #	Description	Product Datasheet	Product Group
06004790	eXP-1S1110PE-RJ-XT - Industrial Temperature PoE+ Gigabit Ethernet Extender: 1 port 10/100/1000Base-T (RJ-45). RJ45 Interlink (VDSL2) connector. Provides power over Ethernet as a PSE. -40C to 75C (-40F to 167F) operating temperature	https://www.perle.com/products/10-100-1000-industrial-poe-ethernet-extender.shtml	Ethernet Extender: eXP-S1110
06004800	eXP-1S1110PE-BNC-XT - Industrial Temperature PoE+ Gigabit Ethernet Extender: 1 port 10/100/1000Base-T (RJ-45). BNC Interlink (VDSL2) connector. Provides power over Ethernet as a PSE. -40C to 75C (-40F to 167F) operating temperature	https://www.perle.com/products/10-100-1000-industrial-poe-ethernet-extender.shtml	Ethernet Extender: eXP-S1110
06004810	eXP-1S1110PE-TB-XT - Industrial Temperature PoE+ Gigabit Ethernet Extender: 1 port 10/100/1000Base-T (RJ-45). Terminal Block Interlink (VDSL2) connector. Provides power over Ethernet as a PSE. -40C to 75C (-40F to 167F) operating temperature	https://www.perle.com/products/10-100-1000-industrial-poe-ethernet-extender.shtml	Ethernet Extender: eXP-S1110
06004880	eXP-4S110E-RJ-XT - Industrial Temperature PoE Fast Ethernet Extender: 4 port 10/100Base-TX (RJ-45). RJ45 Interlink (VDSL2) connector. Provides power over Ethernet as a PSE. -40C to 75C (-40F to 167F) operating temperature	https://www.perle.com/products/10-100-industrial-poe-ethernet-extender.shtml	Ethernet Extender: eXP-S110
06004890	eXP-4S110E-BNC-XT - Industrial Temperature PoE Fast Ethernet Extender: 4 port 10/100Base-TX (RJ-45). BNC Interlink (VDSL2) connector. Provides power over Ethernet as a PSE. -40C to 75C (-40F to 167F) operating temperature	https://www.perle.com/products/10-100-industrial-poe-ethernet-extender.shtml	Ethernet Extender: eXP-S110
06004900	eXP-4S110E-TB-XT - Industrial Temperature PoE Fast Ethernet Extender: 4 port 10/100Base-TX (RJ-45). Terminal Block Interlink (VDSL2) connector. Provides power over Ethernet as a PSE. -40C to 75C (-40F to 167F) operating temperature	https://www.perle.com/products/10-100-industrial-poe-ethernet-extender.shtml	Ethernet Extender: eXP-S110
06004910	eXP-4S1110PE-RJ-XT - Industrial Temperature PoE+ Gigabit Ethernet Extender: 4 port 10/100/1000Base-T (RJ-45). RJ45 Interlink (VDSL2) connector. Provides power over Ethernet as a PSE. -40C to 75C (-40F to 167F) operating temperature	https://www.perle.com/products/10-100-1000-industrial-poe-ethernet-extender.shtml	Ethernet Extender: eXP-S1110
06004920	eXP-4S1110PE-BNC-XT - Industrial Temperature PoE+ Gigabit Ethernet Extender: 4 port 10/100/1000Base-T (RJ-45). BNC Interlink (VDSL2) connector. Provides power over Ethernet as a PSE. -40C to 75C (-40F to 167F) operating temperature	https://www.perle.com/products/10-100-1000-industrial-poe-ethernet-extender.shtml	Ethernet Extender: eXP-S1110

Part #	Description	Product Datasheet	Product Group
06004930	eXP-4S1110PE-TB-XT - Industrial Temperature PoE+ Gigabit Ethernet Extender: 4 port 10/100/1000Base-T (RJ-45). Terminal Block Interlink (VDSL2) connector. Provides power over Ethernet as a PSE. -40C to 75C (-40F to 167F) operating temperature	https://www.perle.com/products/10-100-1000-industrial-poe-ethernet-extender.shtml	Ethernet Extender: eXP-S1110
06004942	eXP-KIT11-S110-RJ PoE Fast Ethernet Extender Kit. 1 x eXP-1S110L-RJ PoE ethernet extender and 1 x eXP-1S110E-RJ PoE ethernet Extender: One 48V 65W Adapter included - EU Power Cord	https://www.perle.com/products/10-100-poe-ethernet-extender.shtml	Ethernet Extender: eXP-S110
06004952	eXP-KIT11-S110-BNC Extender Kit. PoE Fast Ethernet Extender Kit. 1 x eXP-1S110L-BNC PoE ethernet extender and 1 x eXP-1S110E-BNC PoE ethernet Extender: One 48V 65W Adapter included - EU Power Cord	https://www.perle.com/products/10-100-poe-ethernet-extender.shtml	Ethernet Extender: eXP-S110
06004962	eXP-KIT11-S110-TB PoE Fast Ethernet Extender Kit. 1 x eXP-1S110L-TB PoE ethernet extender and 1 x eXP-1S110E-TB PoE ethernet Extender: One 48V 65W Adapter included - EU Power Cord	https://www.perle.com/products/10-100-poe-ethernet-extender.shtml	Ethernet Extender: eXP-S110
06004972	eXP-KIT11-S1110-RJ PoE Gigabit Ethernet Extender Kit. 1 x eXP-1S1110L-RJ PoE ethernet extender and 1 x eXP-1S1110E-RJ PoE ethernet Extender: One 48V 65W Adapter included - EU Power Cord	https://www.perle.com/products/10-100-1000-poe-ethernet-extender.shtml	Ethernet Extender: eXP-S1110
06004982	eXP-KIT11-S1110-BNC PoE Gigabit Ethernet Extender Kit. 1 x eXP-1S1110L-BNC PoE ethernet extender and 1 x eXP-1S1110E-BNC PoE ethernet Extender: One 48V 65W Adapter included - EU Power Cord	https://www.perle.com/products/10-100-1000-poe-ethernet-extender.shtml	Ethernet Extender: eXP-S1110
06004992	eXP-KIT11-S1110-TB PoE Gigabit Ethernet Extender Kit. 1 x eXP-1S1110L-TB PoE ethernet extender and 1 x eXP-1S1110E-TB PoE ethernet Extender: One 48V 65W Adapter included - EU Power Cord	https://www.perle.com/products/10-100-1000-poe-ethernet-extender.shtml	Ethernet Extender: eXP-S1110
06005062	eXP-KIT44-S110-RJ PoE Fast Ethernet Extender Kit. 1 x eXP-4S110L-RJ PoE ethernet extender and 1 x eXP-4S110E-RJ PoE ethernet Extender: One 48V 65W Adapter included - EU Power Cord	https://www.perle.com/products/10-100-poe-ethernet-extender.shtml	Ethernet Extender: eXP-S110
06005072	eXP-KIT44-S110-BNC PoE Fast Ethernet Extender Kit. 1 x eXP-4S110L-BNC PoE ethernet extender and 1 x eXP-4S110E-BNC PoE ethernet Extender: One 48V 65W Adapter included - EU Power Cord	https://www.perle.com/products/10-100-poe-ethernet-extender.shtml	Ethernet Extender: eXP-S110
06005082	eXP-KIT44-S110-TB PoE Fast Ethernet Extender Kit. 1 x eXP-4S110L-TB PoE ethernet extender and 1 x eXP-4S110E-TB PoE ethernet Extender: One 48V 65W Adapter included - EU Power Cord	https://www.perle.com/products/10-100-poe-ethernet-extender.shtml	Ethernet Extender: eXP-S110
06005092	eXP-KIT44-S1110-RJ PoE Gigabit Ethernet Extender Kit. 1 x eXP-4S1110L-RJ PoE ethernet extender and 1 x eXP-4S1110E-RJ PoE ethernet Extender: One 48V 65W Adapter included - EU Power Cord	https://www.perle.com/products/10-100-1000-poe-ethernet-extender.shtml	Ethernet Extender: eXP-S1110

Part #	Description	Product Datasheet	Product Group
06005102	eXP-KIT44-S1110-BNC PoE Gigabit Ethernet Extender Kit. 1 x eXP-4S1110L-BNC PoE ethernet extender and 1 x eXP-4S1110E-BNC PoE ethernet Extender: One 48V 65W Adapter included - EU Power Cord	https://www.perle.com/products/10-100-1000-poe-ethernet-extender.shtml	Ethernet Extender: eXP-S1110
06005112	eXP-KIT44-S1110-TB PoE Gigabit Ethernet Extender Kit. 1 x eXP-4S1110L-TB PoE ethernet extender and 1 x eXP-4S1110E-TB PoE ethernet Extender: One 48V 65W Adapter included - EU Power Cord	https://www.perle.com/products/10-100-1000-poe-ethernet-extender.shtml	Ethernet Extender: eXP-S1110
06005152	eXP-1S1110PE-RJ - PoE+ Gigabit Ethernet Extender: 1 port 10/100/1000Base-T (RJ-45). RJ45 Interlink (VDSL2) connector. Provides power over Ethernet as a PSE. 57V 75W PoE+ power adapter included - EU Power Cord	https://www.perle.com/products/10-100-1000-poe+ethernet-extender.shtml	Ethernet Extender: eXP-S1110
06005162	eXP-1S1110PE-BNC - PoE+ Gigabit Ethernet Extender: 1 port 10/100/1000Base-T (RJ-45). BNC Interlink (VDSL2) connector. Provides power over Ethernet as a PSE. 57V 75W PoE+ power adapter included - EU Power Cord	https://www.perle.com/products/10-100-1000-poe+ethernet-extender.shtml	Ethernet Extender: eXP-S1110
06005172	eXP-1S1110PE-TB - PoE+ Gigabit Ethernet Extender: 1 port 10/100/1000Base-T (RJ-45). Terminal Block Interlink (VDSL2) connector. Provides power over Ethernet as a PSE. 57V 75W PoE+ power adapter included - EU Power Cord	https://www.perle.com/products/10-100-1000-poe+ethernet-extender.shtml	Ethernet Extender: eXP-S1110
06005272	eXP-4S1110PE-RJ - PoE+ Gigabit Ethernet Extender: 4 port 10/100/1000Base-T (RJ-45). RJ45 Interlink (VDSL2) connector. Provides power over Ethernet as a PSE. 57V 75W PoE+ power adapter included - EU Power Cord	https://www.perle.com/products/10-100-1000-poe+ethernet-extender.shtml	Ethernet Extender: eXP-S1110
06005282	eXP-4S1110PE-BNC - PoE+ Gigabit Ethernet Extender: 4 port 10/100/1000Base-T (RJ-45). BNC Interlink (VDSL2) connector. Provides power over Ethernet as a PSE. 57V 75W PoE+ power adapter included - EU Power Cord	https://www.perle.com/products/10-100-1000-poe+ethernet-extender.shtml	Ethernet Extender: eXP-S1110
06005292	eXP-4S1110PE-TB - PoE+ Gigabit Ethernet Extender: 4 port 10/100/1000Base-T (RJ-45). Terminal Block Interlink (VDSL2) connector. Provides power over Ethernet as a PSE. 57V 75W PoE+ power adapter included - EU Power Cord	https://www.perle.com/products/10-100-1000-poe+ethernet-extender.shtml	Ethernet Extender: eXP-S1110
06005322	eR-S1110 – Gigabit Ethernet Repeater and Rate Converter – 2 x 10/100/1000Base-T (RJ45) ports. Auto-sensing and rate converting. Extend existing Ethernet cable length by 100m (300ft). 802.3af Power over Ethernet (PoE) compliant PD. Power supply included.	https://www.perle.com/products/ethernet-extenders/er-s1110-ethernet-repeater.shtml	Ethernet Repeater: eR-S1110

Part #	Description	Product Datasheet	Product Group
07009800	IDS-105F-M1ST2U Industrial Switch: 4 x 10/100Base-TX RJ-45 ports and 1 x 100Base-BX, 1310nm TX / 1550nm RX single strand multimode port with simplex (BIDI) ST connector [up to 5km/3.1 miles]. 0 to 60C operating temperature.	https://www.perle.com/products/5-port-industrial-ethernet-switch.shtml	Industrial Switch: IDS-105F
07009810	IDS-105F-M1ST2D Industrial Switch: 4 x 10/100Base-TX RJ-45 ports and 1 x 100Base-BX, 1550nm TX / 1310nm RX single strand multimode port with simplex (BIDI) ST connector [up to 5km/3.1 miles]. 0 to 60C operating temperature.	https://www.perle.com/products/5-port-industrial-ethernet-switch.shtml	Industrial Switch: IDS-105F
07009820	IDS-105F-S1ST20U Industrial Switch: 4 x 10/100Base-TX RJ-45 ports and 1 x 100Base-BX, 1310nm TX / 1550nm RX single strand single mode port with simplex (BIDI) ST connector [20km/12.4 miles]. 0 to 60C operating temperature.	https://www.perle.com/products/5-port-industrial-ethernet-switch.shtml	Industrial Switch: IDS-105F
07009830	IDS-105F-S1ST20D Industrial Switch: 4 x 10/100Base-TX RJ-45 ports and 1 x 100Base-BX, 1550nm TX / 1310nm RX single strand single mode port with simplex (BIDI) ST connector [20km/12.4 miles]. 0 to 60C operating temperature.	https://www.perle.com/products/5-port-industrial-ethernet-switch.shtml	Industrial Switch: IDS-105F
07009840	IDS-108F-M1ST2U Industrial Switch: 8 x 10/100Base-TX RJ-45 ports and 1 x 100Base-BX, 1310nm TX / 1550nm RX single strand multimode port with simplex (BIDI) ST connector [up to 5km/3.1 miles]. 0 to 60C operating temperature.	https://www.perle.com/products/8-port-industrial-ethernet-switch.shtml	Industrial Switch: IDS-108F
07009850	IDS-108F-M1ST2D Industrial Switch: 8 x 10/100Base-TX RJ-45 ports and 1 x 100Base-BX, 1550nm TX / 1310nm RX single strand multimode port with simplex (BIDI) ST connector [up to 5km/3.1 miles]. 0 to 60C operating temperature.	https://www.perle.com/products/8-port-industrial-ethernet-switch.shtml	Industrial Switch: IDS-108F
07009860	IDS-108F-S1ST20U Industrial Switch: 8 x 10/100Base-TX RJ-45 ports and 1 x 100Base-BX, 1310nm TX / 1550nm RX single strand single mode port with simplex (BIDI) ST connector [20km/12.4 miles]. 0 to 60C operating temperature.	https://www.perle.com/products/8-port-industrial-ethernet-switch.shtml	Industrial Switch: IDS-108F
07009870	IDS-108F-S1ST20D Industrial Switch: 8 x 10/100Base-TX RJ-45 ports and 1 x 100Base-BX, 1550nm TX / 1310nm RX single strand single mode port with simplex (BIDI) ST connector [20km/12.4 miles]. 0 to 60C operating temperature.	https://www.perle.com/products/8-port-industrial-ethernet-switch.shtml	Industrial Switch: IDS-108F

Part #	Description	Product Datasheet	Product Group
07009880	IDS-108F-DM1ST2U Industrial Switch: 8 x 10/100Base-TX RJ-45 ports and 2 x 100Base-BX, 1310nm TX / 1550nm RX single strand multimode port with simplex (BIDI) ST connectors [up to 5km/3.1 miles]. 0 to 60C operating temperature.	https://www.perle.com/products/8-port-industrial-ethernet-switch.shtml	Industrial Switch: IDS-108F
07009890	IDS-108F-DM1ST2D Industrial Switch: 8 x 10/100Base-TX RJ-45 ports and 2 x 100Base-BX, 1550nm TX / 1310nm RX single strand multimode port with simplex (BIDI) ST connectors [up to 5km/3.1 miles]. 0 to 60C operating temperature.	https://www.perle.com/products/8-port-industrial-ethernet-switch.shtml	Industrial Switch: IDS-108F
07009900	IDS-108F-DS1ST20U Industrial Switch: 8 x 10/100Base-TX RJ-45 ports and 2 x 100Base-BX, 1310nm TX / 1550nm RX single strand single mode port with simplex (BIDI) ST connectors [20km/12.4 miles]. 0 to 60C operating temperature.	https://www.perle.com/products/8-port-industrial-ethernet-switch.shtml	Industrial Switch: IDS-108F
07009910	IDS-108F-DS1ST20D Industrial Switch: 8 x 10/100Base-TX RJ-45 ports and 2 x 100Base-BX, 1550nm TX / 1310nm RX single strand single mode port with simplex (BIDI) ST connectors [20km/12.4 miles]. 0 to 60C operating temperature.	https://www.perle.com/products/8-port-industrial-ethernet-switch.shtml	Industrial Switch: IDS-108F
07009920	IDS-108FPP-M1ST2U Industrial PoE Switch: 8 x 10/100Base-TX RJ45 ports, 4 of which support PoE/PoE+ and 1 x 100Base-BX, 1310nm TX / 1550nm RX single strand multimode port with simplex (BIDI) ST connector [up to 5km/3.1 miles]. 0 to 60C operating temperature.	https://www.perle.com/products/8-port-industrial-poe-switch.shtml	Industrial Switch: IDS-108FPP
07009930	IDS-108FPP-M1ST2D Industrial PoE Switch: 8 x 10/100Base-TX RJ45 ports, 4 of which support PoE/PoE+ and 1 x 100Base-BX, 1550nm TX / 1310nm RX single strand multimode port with simplex (BIDI) ST connector [up to 5km/3.1 miles]. 0 to 60C operating temperature.	https://www.perle.com/products/8-port-industrial-poe-switch.shtml	Industrial Switch: IDS-108FPP
07009940	IDS-108FPP-S1ST20U Industrial PoE Switch: 8 x 10/100Base-TX RJ45 ports, 4 of which support PoE/PoE+ and 1 x 100Base-BX, 1310nm TX / 1550nm RX single strand single mode port with simplex (BIDI) ST connector [20km/12.4 miles]. 0 to 60C operating temperature.	https://www.perle.com/products/8-port-industrial-poe-switch.shtml	Industrial Switch: IDS-108FPP
07009950	IDS-108FPP-S1ST20D Industrial PoE Switch: 8 x 10/100Base-TX RJ45 ports, 4 of which support PoE/PoE+ and 1 x 100Base-BX, 1550nm TX / 1310nm RX single strand single mode port with simplex (BIDI) ST connector [20km/12.4 miles]. 0 to 60C operating temperature.	https://www.perle.com/products/8-port-industrial-poe-switch.shtml	Industrial Switch: IDS-108FPP

Part #	Description	Product Datasheet	Product Group
07009960	IDS-108FPP-DM1ST2U Industrial PoE Switch: 8 x 10/100Base-TX RJ45 ports, 4 of which support PoE/PoE+ and 2 x 100Base-BX, 1310nm TX / 1550nm RX single strand multimode port with simplex (BIDI) ST connectors [up to 5km/3.1 miles]. 0 to 60C operating temperature.	https://www.perle.com/products/8-port-industrial-poe-switch.shtml	Industrial Switch: IDS-108FPP
07009970	IDS-108FPP-DM1ST2D Industrial PoE Switch: 8 x 10/100Base-TX RJ45 ports, 4 of which support PoE/PoE+ and 2 x 100Base-BX, 1550nm TX / 1310nm RX single strand multimode port with simplex (BIDI) ST connectors [up to 5km/3.1 miles]. 0 to 60C operating temperature.	https://www.perle.com/products/8-port-industrial-poe-switch.shtml	Industrial Switch: IDS-108FPP
07009980	IDS-108FPP-DS1ST20U Industrial PoE Switch: 8 x 10/100Base-TX RJ45 ports, 4 of which support PoE/PoE+ and 2 x 100Base-BX, 1310nm TX / 1550nm RX single strand single mode port with simplex (BIDI) ST connectors [20km/12.4 miles]. 0 to 60C operating temperature.	https://www.perle.com/products/8-port-industrial-poe-switch.shtml	Industrial Switch: IDS-108FPP
07009990	IDS-108FPP-DS1ST20D Industrial PoE Switch: 8 x 10/100Base-TX RJ45 ports, 4 of which support PoE/PoE+ and 2 x 100Base-BX, 1550nm TX / 1310nm RX single strand single mode port with simplex (BIDI) ST connectors [20km/12.4 miles]. 0 to 60C operating temperature.	https://www.perle.com/products/8-port-industrial-poe-switch.shtml	Industrial Switch: IDS-108FPP
07010000	IDS-105F Industrial Switch: 5 x 10/100Base-TX RJ-45 ports. 0 to 60C operating temperature.	https://www.perle.com/products/5-port-industrial-ethernet-switch.shtml	Industrial Switch: IDS-105F
07010010	IDS-105F-M2SC2 Industrial Switch: 4 x 10/100Base-TX RJ-45 ports and 1 x 100Base-FX, 1310nm multimode port with duplex SC connector [up to 5km/3.1 miles]. 0 to 60C operating temperature.	https://www.perle.com/products/5-port-industrial-ethernet-switch.shtml	Industrial Switch: IDS-105F
07010020	IDS-105F-M2ST2 Industrial Switch: 4 x 10/100Base-TX RJ-45 ports and 1 x 100Base-FX, 1310nm multimode port with duplex ST connector [up to 5km/3.1 miles]. 0 to 60C operating temperature.	https://www.perle.com/products/5-port-industrial-ethernet-switch.shtml	Industrial Switch: IDS-105F
07010030	IDS-105F-S2SC20 Industrial Switch: 4 x 10/100Base-TX RJ-45 ports and 1 x 100Base-LX, 1310nm single mode port with duplex SC connector [20 km/ 12.4 miles]. 0 to 60C operating temperature.	https://www.perle.com/products/5-port-industrial-ethernet-switch.shtml	Industrial Switch: IDS-105F
07010040	IDS-105F-S2ST20 Industrial Switch: 4 x 10/100Base-TX RJ-45 ports and 1 x 100Base-LX, 1310nm single mode port with duplex ST connector [20 km/ 12.4 miles]. 0 to 60C operating temperature.	https://www.perle.com/products/5-port-industrial-ethernet-switch.shtml	Industrial Switch: IDS-105F
07010050	IDS-105F-S2SC40 Industrial Switch: 4 x 10/100Base-TX RJ-45 ports and 1 x 100Base-LX, 1310nm single mode port with duplex SC connector [40 km/ 24.9 miles]. 0 to 60C operating temperature.	https://www.perle.com/products/5-port-industrial-ethernet-switch.shtml	Industrial Switch: IDS-105F

Part #	Description	Product Datasheet	Product Group
07010060	IDS-105F-S2ST40 Industrial Switch: 4 x 10/100Base-TX RJ-45 ports and 1 x 100Base-LX, 1310nm single mode port with duplex ST connector [40 km/ 24.9 miles]. 0 to 60C operating temperature.	https://www.perle.com/products/5-port-industrial-ethernet-switch.shtml	Industrial Switch: IDS-105F
07010070	IDS-105F-S2SC80 Industrial Switch: 4 x 10/100Base-TX RJ-45 ports and 1 x 100Base-EX, 1550nm single mode port with duplex SC connector [80 km/ 49.7 miles]. 0 to 60C operating temperature.	https://www.perle.com/products/5-port-industrial-ethernet-switch.shtml	Industrial Switch: IDS-105F
07010080	IDS-105F-S2ST80 Industrial Switch: 4 x 10/100Base-TX RJ-45 ports and 1 x 100Base-EX, 1550nm single mode port with duplex ST connector [80 km/ 49.7 miles]. 0 to 60C operating temperature.	https://www.perle.com/products/5-port-industrial-ethernet-switch.shtml	Industrial Switch: IDS-105F
07010090	IDS-105F-S2SC120 Industrial Switch: 4 x 10/100Base-TX RJ-45 ports and 1 x 100Base-ZX, 1550nm single mode port with duplex SC connector [120 km/ 74.6 miles]. 0 to 60C operating temperature.	https://www.perle.com/products/5-port-industrial-ethernet-switch.shtml	Industrial Switch: IDS-105F
07010100	IDS-105F-S2ST120 Industrial Switch: 4 x 10/100Base-TX RJ-45 ports and 1 x 100Base-ZX, 1550nm single mode port with duplex ST connector [120 km/ 74.6 miles]. 0 to 60C operating temperature.	https://www.perle.com/products/5-port-industrial-ethernet-switch.shtml	Industrial Switch: IDS-105F
07010110	IDS-105F-M1SC2U Industrial Switch: 4 x 10/100Base-TX RJ-45 ports and 1 x 100Base-BX, 1310nm TX / 1550nm RX single strand multimode port with simplex (BIDI) SC connector [up to 5km/3.1 miles]. 0 to 60C operating temperature.	https://www.perle.com/products/5-port-industrial-ethernet-switch.shtml	Industrial Switch: IDS-105F
07010120	IDS-105F-M1SC2D Industrial Switch: 4 x 10/100Base-TX RJ-45 ports and 1 x 100Base-BX, 1550nm TX / 1310nm RX single strand multimode port with simplex (BIDI) SC connector [up to 5km/3.1 miles]. 0 to 60C operating temperature.	https://www.perle.com/products/5-port-industrial-ethernet-switch.shtml	Industrial Switch: IDS-105F
07010150	IDS-105F-S1SC20U Industrial Switch: 4 x 10/100Base-TX RJ-45 ports and 1 x 100Base-BX, 1310nm TX / 1550nm RX single strand single mode port with simplex (BIDI) SC connector [20km/12.4 miles]. 0 to 60C operating temperature.	https://www.perle.com/products/5-port-industrial-ethernet-switch.shtml	Industrial Switch: IDS-105F
07010160	IDS-105F-S1SC20D Industrial Switch: 4 x 10/100Base-TX RJ-45 ports and 1 x 100Base-BX, 1550nm TX / 1310nm RX single strand single mode port with simplex (BIDI) SC connector [20km/12.4 miles]. 0 to 60C operating temperature.	https://www.perle.com/products/5-port-industrial-ethernet-switch.shtml	Industrial Switch: IDS-105F
07010170	IDS-105F-S1SC40U Industrial Switch: 4 x 10/100Base-TX RJ-45 ports and 1 x 100Base-BX, 1310nm TX / 1550nm RX single strand single mode port with simplex (BIDI) SC connector [40km/24.9 miles]. 0 to 60C operating temperature.	https://www.perle.com/products/5-port-industrial-ethernet-switch.shtml	Industrial Switch: IDS-105F

Part #	Description	Product Datasheet	Product Group
07010180	IDS-105F-S1SC40D Industrial Switch: 4 x 10/100Base-TX RJ-45 ports and 1 x 100Base-BX, 1550nm TX / 1310nm RX single strand single mode port with simplex (BIDI) SC connector [40km/24.9 miles]. 0 to 60C operating temperature.	https://www.perle.com/products/5-port-industrial-ethernet-switch.shtml	Industrial Switch: IDS-105F
07010190	IDS-105F-XT Industrial Switch: 5 x 10/100Base-TX RJ-45 ports. -40 to 75C industrial extended operating temperature.	https://www.perle.com/products/5-port-industrial-ethernet-switch.shtml	Industrial Switch: IDS-105F
07010200	IDS-105F-M2SC2-XT Industrial Switch: 4 x 10/100Base-TX RJ-45 ports and 1 x 100Base-FX, 1310nm multimode port with duplex SC connector [up to 5km/3.1 miles]. -40 to 75C industrial extended operating temperature.	https://www.perle.com/products/5-port-industrial-ethernet-switch.shtml	Industrial Switch: IDS-105F
07010210	IDS-105F-M2ST2-XT Industrial Switch: 4 x 10/100Base-TX RJ-45 ports and 1 x 100Base-FX, 1310nm multimode port with duplex ST connector [up to 5km/3.1 miles].-40 to 75C industrial extended operating temperature.	https://www.perle.com/products/5-port-industrial-ethernet-switch.shtml	Industrial Switch: IDS-105F
07010220	IDS-105F-S2SC20-XT Industrial Switch: 4 x 10/100Base-TX RJ-45 ports and 1 x 100Base-LX, 1310nm single mode port with duplex SC connector [20 km/ 12.4 miles]. -40 to 75C industrial extended operating temperature.	https://www.perle.com/products/5-port-industrial-ethernet-switch.shtml	Industrial Switch: IDS-105F
07010230	IDS-105F-S2ST20-XT Industrial Switch: 4 x 10/100Base-TX RJ-45 ports and 1 x 100Base-LX, 1310nm single mode port with duplex ST connector [20 km/ 12.4 miles].-40 to 75C industrial extended operating temperature.	https://www.perle.com/products/5-port-industrial-ethernet-switch.shtml	Industrial Switch: IDS-105F
07010240	IDS-105F-S2SC40-XT Industrial Switch: 4 x 10/100Base-TX RJ-45 ports and 1 x 100Base-LX, 1310nm single mode port with duplex SC connector [40 km/ 24.9 miles]. -40 to 75C industrial extended operating temperature.	https://www.perle.com/products/5-port-industrial-ethernet-switch.shtml	Industrial Switch: IDS-105F
07010250	IDS-105F-S2ST40-XT Industrial Switch: 4 x 10/100Base-TX RJ-45 ports and 1 x 100Base-LX, 1310nm single mode port with duplex ST connector [40 km/ 24.9 miles]. -40 to 75C industrial extended operating temperature.	https://www.perle.com/products/5-port-industrial-ethernet-switch.shtml	Industrial Switch: IDS-105F
07010260	IDS-105F-S1SC20U-XT Industrial Switch: 4 x 10/100Base-TX RJ-45 ports and 1 x 100Base-BX, 1310nm TX / 1550nm RX single strand single mode port with simplex (BIDI) SC connector [20km/12.4 miles]. -40 to 75C industrial extended operating temperature.	https://www.perle.com/products/5-port-industrial-ethernet-switch.shtml	Industrial Switch: IDS-105F
07010270	IDS-105F-S1SC20D-XT Industrial Switch: 4 x 10/100Base-TX RJ-45 ports and 1 x 100Base-BX, 1550nm TX / 1310nm RX single strand single mode port with simplex (BIDI) SC connector [20km/12.4 miles]. -40 to 75C industrial extended operating temperature.	https://www.perle.com/products/5-port-industrial-ethernet-switch.shtml	Industrial Switch: IDS-105F
07010290	Panel Mount kit PM3 - Brackets for wall or panel mounting Perle IDS industrial switches.	https://www.perle.com/products/product_detail.asp?a=4&i=07010290&c=1249	Accessories: Mounting Kits

Part #	Description	Product Datasheet	Product Group
07010300	Rack Mount kit PM4U - 4U Rack mount for mounting DIN Rail products to a 19 inch rack.	https://www.perle.com/products/product_detail.asp?a=4&i=07010300&c=1249	Accessories: Mounting Kits
07010310	IDS-108F Industrial Switch: 8 x 10/100Base-TX RJ-45 ports. 0 to 60C operating temperature.	https://www.perle.com/products/8-port-industrial-ethernet-switch.shtml	Industrial Switch: IDS-108F
07010320	IDS-108F-M2SC2 Industrial Switch: 8 x 10/100Base-TX RJ-45 ports and 1 x 100Base-FX, 1310nm multimode port with duplex SC connector [up to 5km/3.1 miles]. 0 to 60C operating temperature.	https://www.perle.com/products/8-port-industrial-ethernet-switch.shtml	Industrial Switch: IDS-108F
07010330	IDS-108F-M2ST2 Industrial Switch: 8 x 10/100Base-TX RJ-45 ports and 1 x 100Base-FX, 1310nm multimode port with duplex ST connector [up to 5km/3.1 miles]. 0 to 60C operating temperature.	https://www.perle.com/products/8-port-industrial-ethernet-switch.shtml	Industrial Switch: IDS-108F
07010340	IDS-108F-S2SC20 Industrial Switch: 8 x 10/100Base-TX RJ-45 ports and 1 x 100Base-LX, 1310nm single mode port with duplex SC connector [20 km/ 12.4 miles]. 0 to 60C operating temperature.	https://www.perle.com/products/8-port-industrial-ethernet-switch.shtml	Industrial Switch: IDS-108F
07010350	IDS-108F-S2ST20 Industrial Switch: 8 x 10/100Base-TX RJ-45 ports and 1 x 100Base-LX, 1310nm single mode port with duplex ST connector [20 km/ 12.4 miles]. 0 to 60C operating temperature.	https://www.perle.com/products/8-port-industrial-ethernet-switch.shtml	Industrial Switch: IDS-108F
07010360	IDS-108F-S2SC40 Industrial Switch: 8 x 10/100Base-TX RJ-45 ports and 1 x 100Base-LX, 1310nm single mode port with duplex SC connector [40 km/ 24.9 miles]. 0 to 60C operating temperature.	https://www.perle.com/products/8-port-industrial-ethernet-switch.shtml	Industrial Switch: IDS-108F
07010370	IDS-108F-S2ST40 Industrial Switch: 8 x 10/100Base-TX RJ-45 ports and 1 x 100Base-LX, 1310nm single mode port with duplex ST connector [40 km/ 24.9 miles]. 0 to 60C operating temperature.	https://www.perle.com/products/8-port-industrial-ethernet-switch.shtml	Industrial Switch: IDS-108F
07010380	IDS-108F-S2SC80 Industrial Switch: 8 x 10/100Base-TX RJ-45 ports and 1 x 100Base-EX, 1550nm single mode port with duplex SC connector [80 km/ 49.7 miles]. 0 to 60C operating temperature.	https://www.perle.com/products/8-port-industrial-ethernet-switch.shtml	Industrial Switch: IDS-108F
07010390	IDS-108F-S2ST80 Industrial Switch: 8 x 10/100Base-TX RJ-45 ports and 1 x 100Base-EX, 1550nm single mode port with duplex ST connector [80 km/ 49.7 miles]. 0 to 60C operating temperature.	https://www.perle.com/products/8-port-industrial-ethernet-switch.shtml	Industrial Switch: IDS-108F
07010400	IDS-108F-S2SC120 Industrial Switch: 8 x 10/100Base-TX RJ-45 ports and 1 x 100Base-ZX, 1550nm single mode port with duplex SC connector [120 km/ 74.6 miles]. 0 to 60C operating temperature.	https://www.perle.com/products/8-port-industrial-ethernet-switch.shtml	Industrial Switch: IDS-108F
07010410	IDS-108F-S2ST120 Industrial Switch: 8 x 10/100Base-TX RJ-45 ports and 1 x 100Base-ZX, 1550nm single mode port with duplex ST connector [120 km/ 74.6 miles]. 0 to 60C operating temperature.	https://www.perle.com/products/8-port-industrial-ethernet-switch.shtml	Industrial Switch: IDS-108F

Part #	Description	Product Datasheet	Product Group
07010420	IDS-108F-M1SC2U Industrial Switch: 8 x 10/100Base-TX RJ-45 ports and 1 x 100Base-BX, 1310nm TX / 1550nm RX single strand multimode port with simplex (BIDI) SC connector [up to 5km/3.1 miles]. 0 to 60C operating temperature.	https://www.perle.com/products/8-port-industrial-ethernet-switch.shtml	Industrial Switch: IDS-108F
07010430	IDS-108F-M1SC2D Industrial Switch: 8 x 10/100Base-TX RJ-45 ports and 1 x 100Base-BX, 1550nm TX / 1310nm RX single strand multimode port with simplex (BIDI) SC connector [up to 5km/3.1 miles]. 0 to 60C operating temperature.	https://www.perle.com/products/8-port-industrial-ethernet-switch.shtml	Industrial Switch: IDS-108F
07010440	IDS-108F-S1SC20U Industrial Switch: 8 x 10/100Base-TX RJ-45 ports and 1 x 100Base-BX, 1310nm TX / 1550nm RX single strand single mode port with simplex (BIDI) SC connector [20km/12.4 miles]. 0 to 60C operating temperature.	https://www.perle.com/products/8-port-industrial-ethernet-switch.shtml	Industrial Switch: IDS-108F
07010450	IDS-108F-S1SC20D Industrial Switch: 8 x 10/100Base-TX RJ-45 ports and 1 x 100Base-BX, 1550nm TX / 1310nm RX single strand single mode port with simplex (BIDI) SC connector [20km/12.4 miles]. 0 to 60C operating temperature.	https://www.perle.com/products/8-port-industrial-ethernet-switch.shtml	Industrial Switch: IDS-108F
07010460	IDS-108F-S1SC40U Industrial Switch: 8 x 10/100Base-TX RJ-45 ports and 1 x 100Base-BX, 1310nm TX / 1550nm RX single strand single mode port with simplex (BIDI) SC connector [40km/24.9 miles]. 0 to 60C operating temperature.	https://www.perle.com/products/8-port-industrial-ethernet-switch.shtml	Industrial Switch: IDS-108F
07010470	IDS-108F-S1SC40D Industrial Switch: 8 x 10/100Base-TX RJ-45 ports and 1 x 100Base-BX, 1550nm TX / 1310nm RX single strand single mode port with simplex (BIDI) SC connector [40km/24.9 miles]. 0 to 60C operating temperature.	https://www.perle.com/products/8-port-industrial-ethernet-switch.shtml	Industrial Switch: IDS-108F
07010480	IDS-108F-DM2SC2 Industrial Switch: 8 x 10/100Base-TX RJ-45 ports and 2 x 100Base-FX, 1310nm multimode port with duplex SC connectors [up to 5km/3.1 miles]. 0 to 60C operating temperature.	https://www.perle.com/products/8-port-industrial-ethernet-switch.shtml	Industrial Switch: IDS-108F
07010490	IDS-108F-DM2ST2 Industrial Switch: 8 x 10/100Base-TX RJ-45 ports and 2 x 100Base-FX, 1310nm multimode port with duplex ST connectors [up to 5km/3.1 miles]. 0 to 60C operating temperature.	https://www.perle.com/products/8-port-industrial-ethernet-switch.shtml	Industrial Switch: IDS-108F
07010500	IDS-108F-DS2SC20 Industrial Switch: 8 x 10/100Base-TX RJ-45 ports and 2 x 100Base-LX, 1310nm single mode port with duplex SC connectors [20 km/ 12.4 miles]. 0 to 60C operating temperature.	https://www.perle.com/products/8-port-industrial-ethernet-switch.shtml	Industrial Switch: IDS-108F

Part #	Description	Product Datasheet	Product Group
07010510	IDS-108F-DS2ST20 Industrial Switch: 8 x 10/100Base-TX RJ-45 ports and 2 x 100Base-LX, 1310nm single mode port with duplex ST connectors [20 km/ 12.4 miles]. 0 to 60C operating temperature.	https://www.perle.com/products/8-port-industrial-ethernet-switch.shtml	Industrial Switch: IDS-108F
07010520	IDS-108F-DS2SC40 Industrial Switch: 8 x 10/100Base-TX RJ-45 ports and 2 x 100Base-LX, 1310nm single mode port with duplex SC connectors [40 km/ 24.9 miles]. 0 to 60C operating temperature.	https://www.perle.com/products/8-port-industrial-ethernet-switch.shtml	Industrial Switch: IDS-108F
07010530	IDS-108F-DS2ST40 Industrial Switch: 8 x 10/100Base-TX RJ-45 ports and 2 x 100Base-LX, 1310nm single mode port with duplex ST connectors [40 km/ 24.9 miles]. 0 to 60C operating temperature.	https://www.perle.com/products/8-port-industrial-ethernet-switch.shtml	Industrial Switch: IDS-108F
07010540	IDS-108F-DS2SC80 Industrial Switch: 8 x 10/100Base-TX RJ-45 ports and 2 x 100Base-EX, 1550nm single mode port with duplex SC connectors [80 km/ 49.7 miles]. 0 to 60C operating temperature.	https://www.perle.com/products/8-port-industrial-ethernet-switch.shtml	Industrial Switch: IDS-108F
07010550	IDS-108F-DS2ST80 Industrial Switch: 8 x 10/100Base-TX RJ-45 ports and 2 x 100Base-EX, 1550nm single mode port with duplex ST connectors [80 km/ 49.7 miles]. 0 to 60C operating temperature.	https://www.perle.com/products/8-port-industrial-ethernet-switch.shtml	Industrial Switch: IDS-108F
07010560	IDS-108F-DS2SC120 Industrial Switch: 8 x 10/100Base-TX RJ-45 ports and 2 x 100Base-ZX, 1550nm single mode port with duplex SC connectors [120 km/ 74.6 miles]. 0 to 60C operating temperature.	https://www.perle.com/products/8-port-industrial-ethernet-switch.shtml	Industrial Switch: IDS-108F
07010570	IDS-108F-DS2ST120 Industrial Switch: 8 x 10/100Base-TX RJ-45 ports and 2 x 100Base-ZX, 1550nm single mode port with duplex ST connectors [120 km/ 74.6 miles]. 0 to 60C operating temperature.	https://www.perle.com/products/8-port-industrial-ethernet-switch.shtml	Industrial Switch: IDS-108F
07010580	IDS-108F-DM1SC2U Industrial Switch: 8 x 10/100Base-TX RJ-45 ports and 2 x 100Base-BX, 1310nm TX / 1550nm RX single strand multimode port with simplex (BIDI) SC connectors [up to 5km/3.1 miles]. 0 to 60C operating temperature.	https://www.perle.com/products/8-port-industrial-ethernet-switch.shtml	Industrial Switch: IDS-108F
07010590	IDS-108F-DM1SC2D Industrial Switch: 8 x 10/100Base-TX RJ-45 ports and 2 x 100Base-BX, 1550nm TX / 1310nm RX single strand multimode port with simplex (BIDI) SC connectors [up to 5km/3.1 miles]. 0 to 60C operating temperature.	https://www.perle.com/products/8-port-industrial-ethernet-switch.shtml	Industrial Switch: IDS-108F
07010600	IDS-108F-DS1SC20U Industrial Switch: 8 x 10/100Base-TX RJ-45 ports and 2 x 100Base-BX, 1310nm TX / 1550nm RX single strand single mode port with simplex (BIDI) SC connectors [20km/12.4 miles]. 0 to 60C operating temperature.	https://www.perle.com/products/8-port-industrial-ethernet-switch.shtml	Industrial Switch: IDS-108F

Part #	Description	Product Datasheet	Product Group
07010610	IDS-108F-DS1SC20D Industrial Switch: 8 x 10/100Base-TX RJ-45 ports and 2 x 100Base-BX, 1550nm TX / 1310nm RX single strand single mode port with simplex (BIDI) SC connectors [20km/12.4 miles]. 0 to 60C operating temperature.	https://www.perle.com/products/8-port-industrial-ethernet-switch.shtml	Industrial Switch: IDS-108F
07010620	IDS-108F-DS1SC40U Industrial Switch: 8 x 10/100Base-TX RJ-45 ports and 2 x 100Base-BX, 1310nm TX / 1550nm RX single strand single mode port with simplex (BIDI) SC connectors [40km/24.9 miles]. 0 to 60C operating temperature.	https://www.perle.com/products/8-port-industrial-ethernet-switch.shtml	Industrial Switch: IDS-108F
07010630	IDS-108F-DS1SC40D Industrial Switch: 8 x 10/100Base-TX RJ-45 ports and 2 x 100Base-BX, 1550nm TX / 1310nm RX single strand single mode port with simplex (BIDI) SC connectors [40km/24.9 miles]. 0 to 60C operating temperature.	https://www.perle.com/products/8-port-industrial-ethernet-switch.shtml	Industrial Switch: IDS-108F
07010640	IDS-108F-XT Industrial Switch: 8 x 10/100Base-TX RJ-45 ports. -40 to 75C industrial extended operating temperature.	https://www.perle.com/products/8-port-industrial-ethernet-switch.shtml	Industrial Switch: IDS-108F
07010650	IDS-108F-M2SC2-XT Industrial Switch: 8 x 10/100Base-TX RJ-45 ports and 1 x 100Base-FX, 1310nm multimode port with duplex SC connector [up to 5km/3.1 miles]. -40 to 75C industrial extended operating temperature.	https://www.perle.com/products/8-port-industrial-ethernet-switch.shtml	Industrial Switch: IDS-108F
07010660	IDS-108F-M2ST2-XT Industrial Switch: 8 x 10/100Base-TX RJ-45 ports and 1 x 100Base-FX, 1310nm multimode port with duplex ST connector [up to 5km/3.1 miles]. -40 to 75C industrial extended operating temperature.	https://www.perle.com/products/8-port-industrial-ethernet-switch.shtml	Industrial Switch: IDS-108F
07010670	IDS-108F-S2SC20-XT Industrial Switch: 8 x 10/100Base-TX RJ-45 ports and 1 x 100Base-LX, 1310nm single mode port with duplex SC connector [20 km/ 12.4 miles]. -40 to 75C industrial extended operating temperature.	https://www.perle.com/products/8-port-industrial-ethernet-switch.shtml	Industrial Switch: IDS-108F
07010680	IDS-108F-S2ST20-XT Industrial Switch: 8 x 10/100Base-TX RJ-45 ports and 1 x 100Base-LX, 1310nm single mode port with duplex ST connector [20 km/ 12.4 miles]. -40 to 75C industrial extended operating temperature.	https://www.perle.com/products/8-port-industrial-ethernet-switch.shtml	Industrial Switch: IDS-108F
07010690	IDS-108F-S2SC40-XT Industrial Switch: 8 x 10/100Base-TX RJ-45 ports and 1 x 100Base-LX, 1310nm single mode port with duplex SC connector [40 km/ 24.9 miles]. -40 to 75C industrial extended operating temperature.	https://www.perle.com/products/8-port-industrial-ethernet-switch.shtml	Industrial Switch: IDS-108F
07010700	IDS-108F-S2ST40-XT Industrial Switch: 8 x 10/100Base-TX RJ-45 ports and 1 x 100Base-LX, 1310nm single mode port with duplex ST connector [40 km/ 24.9 miles]. -40 to 75C industrial extended operating temperature.	https://www.perle.com/products/8-port-industrial-ethernet-switch.shtml	Industrial Switch: IDS-108F

Part #	Description	Product Datasheet	Product Group
07010710	IDS-108F-S1SC20U-XT Industrial Switch: 8 x 10/100Base-TX RJ-45 ports and 1 x 100Base-BX, 1310nm TX / 1550nm RX single strand single mode port with simplex (BIDI) SC connector [20km/12.4 miles]. -40 to 75C industrial extended operating temperature.	https://www.perle.com/products/8-port-industrial-ethernet-switch.shtml	Industrial Switch: IDS-108F
07010720	IDS-108F-S1SC20D-XT Industrial Switch: 8 x 10/100Base-TX RJ-45 ports and 1 x 100Base-BX, 1550nm TX / 1310nm RX single strand single mode port with simplex (BIDI) SC connector [20km/12.4 miles]. -40 to 75C industrial extended operating temperature.	https://www.perle.com/products/8-port-industrial-ethernet-switch.shtml	Industrial Switch: IDS-108F
07010730	IDS-108F-DM2SC2-XT Industrial Switch: 8 x 10/100Base-TX RJ-45 ports and 2 x 100Base-FX, 1310nm multimode port with duplex SC connectors [up to 5km/3.1 miles]. -40 to 75C industrial extended operating temperature.	https://www.perle.com/products/8-port-industrial-ethernet-switch.shtml	Industrial Switch: IDS-108F
07010740	IDS-108F-DM2ST2-XT Industrial Switch: 8 x 10/100Base-TX RJ-45 ports and 2 x 100Base-FX, 1310nm multimode port with duplex ST connectors [up to 5km/3.1 miles].-40 to 75C industrial extended operating temperature.	https://www.perle.com/products/8-port-industrial-ethernet-switch.shtml	Industrial Switch: IDS-108F
07010750	IDS-108F-DS2SC20-XT Industrial Switch: 8 x 10/100Base-TX RJ-45 ports and 2 x 100Base-LX, 1310nm single mode port with duplex SC connectors [20 km/ 12.4 miles]. -40 to 75C industrial extended operating temperature.	https://www.perle.com/products/8-port-industrial-ethernet-switch.shtml	Industrial Switch: IDS-108F
07010760	IDS-108F-DS2ST20-XT Industrial Switch: 8 x 10/100Base-TX RJ-45 ports and 2 x 100Base-LX, 1310nm single mode port with duplex ST connectors [20 km/ 12.4 miles]. -40 to 75C industrial extended operating temperature.	https://www.perle.com/products/8-port-industrial-ethernet-switch.shtml	Industrial Switch: IDS-108F
07010770	IDS-108F-DS2SC40-XT Industrial Switch: 8 x 10/100Base-TX RJ-45 ports and 2 x 100Base-LX, 1310nm single mode port with duplex SC connectors [40 km/ 24.9 miles]. -40 to 75C industrial extended operating temperature.	https://www.perle.com/products/8-port-industrial-ethernet-switch.shtml	Industrial Switch: IDS-108F
07010780	IDS-108F-DS2ST40-XT Industrial Switch: 8 x 10/100Base-TX RJ-45 ports and 2 x 100Base-LX, 1310nm single mode port with duplex ST connectors [40 km/ 24.9 miles]. -40 to 75C industrial extended operating temperature.	https://www.perle.com/products/8-port-industrial-ethernet-switch.shtml	Industrial Switch: IDS-108F

Part #	Description	Product Datasheet	Product Group
07010790	IDS-108F-DS1SC20U-XT Industrial Switch: 8 x 10/100Base-TX RJ-45 ports and 2 x 100Base-BX, 1310nm TX / 1550nm RX single strand single mode port with simplex (BIDI) SC connectors [20km/12.4 miles]. -40 to 75C industrial extended operating temperature.	https://www.perle.com/products/8-port-industrial-ethernet-switch.shtml	Industrial Switch: IDS-108F
07010800	IDS-108F-DS1SC20D-XT Industrial Switch: 8 x 10/100Base-TX RJ-45 ports and 2 x 100Base-BX, 1550nm TX / 1310nm RX single strand single mode port with simplex (BIDI) SC connectors [20km/12.4 miles]. -40 to 75C industrial extended operating temperature.	https://www.perle.com/products/8-port-industrial-ethernet-switch.shtml	Industrial Switch: IDS-108F
07010810	IDS-105G Industrial Gigabit Switch: 5 x 10/100/1000Base-T Base-T RJ-45 ports. 0 to 60C operating temperature.	https://www.perle.com/products/5-port-industrial-gigabit-ethernet-switch.shtml	Industrial Switch: IDS-105G
07010820	IDS-105G-M2SC05 Industrial Gigabit Switch: 5 x 10/100/1000Base-T Base-T RJ-45 ports and 1 x 1000Base-SX, 850nm multimode port with duplex SC connector [550m/1804 ft]. 0 to 60C operating temperature.	https://www.perle.com/products/5-port-industrial-gigabit-ethernet-switch.shtml	Industrial Switch: IDS-105G
07010830	IDS-105G-M2ST05 Industrial Gigabit Switch: 5 x 10/100/1000Base-T Base-T RJ-45 ports and 1 x 1000Base-SX, 850nm multimode port with duplex ST connector [550m/1804 ft]. 0 to 60C operating temperature.	https://www.perle.com/products/5-port-industrial-gigabit-ethernet-switch.shtml	Industrial Switch: IDS-105G
07010840	IDS-105G-M2SC2 Industrial Gigabit Switch: 5 x 10/100/1000Base-T Base-T RJ-45 ports and 1 x 1000Base-SX, 1310nm extended multimode port with duplex SC connector [2km/1.2 miles]. 0 to 60C operating temperature.	https://www.perle.com/products/5-port-industrial-gigabit-ethernet-switch.shtml	Industrial Switch: IDS-105G
07010850	IDS-105G-M2ST2 Industrial Gigabit Switch: 5 x 10/100/1000Base-T Base-T RJ-45 ports and 1 x 1000Base-SX, 1310nm extended multimode port with duplex ST connector [2km/1.2 miles]. 0 to 60C operating temperature.	https://www.perle.com/products/5-port-industrial-gigabit-ethernet-switch.shtml	Industrial Switch: IDS-105G
07010860	IDS-105G-S2SC10 Industrial Gigabit Switch: 5 x 10/100/1000Base-T Base-T RJ-45 ports and 1 x 1000Base-LX/LH, 1310nm single mode port with duplex SC connector [10 km/ 6.2 miles]. 0 to 60C operating temperature.	https://www.perle.com/products/5-port-industrial-gigabit-ethernet-switch.shtml	Industrial Switch: IDS-105G
07010870	IDS-105G-S2ST10 Industrial Gigabit Switch: 5 x 10/100/1000Base-T Base-T RJ-45 ports and 1 x 1000Base-LX/LH, 1310nm single mode port with duplex ST connector [10 km/ 6.2 miles]. 0 to 60C operating temperature.	https://www.perle.com/products/5-port-industrial-gigabit-ethernet-switch.shtml	Industrial Switch: IDS-105G
07010880	IDS-105G-S2SC40 Industrial Gigabit Switch: 5 x 10/100/1000Base-T Base-T RJ-45 ports and 1 x 1000Base-EX, 1310nm single mode port with duplex SC connector [40 km/ 24.9 miles]. 0 to 60C operating temperature.	https://www.perle.com/products/5-port-industrial-gigabit-ethernet-switch.shtml	Industrial Switch: IDS-105G
07010890	IDS-105G-S2ST40 Industrial Gigabit Switch: 5 x 10/100/1000Base-T Base-T RJ-45 ports and 1 x 1000Base-EX, 1310nm single mode port with duplex ST connector [40 km/ 24.9 miles]. 0 to 60C operating temperature.	https://www.perle.com/products/5-port-industrial-gigabit-ethernet-switch.shtml	Industrial Switch: IDS-105G

Part #	Description	Product Datasheet	Product Group
07010900	IDS-105G-S2SC70 Industrial Gigabit Switch: 5 x 10/100/1000Base-T Base-T RJ-45 ports and 1 x 1000Base-ZX, 1550nm single mode port with duplex SC connector [70 km/ 43.5 miles]. 0 to 60C operating temperature.	https://www.perle.com/products/5-port-industrial-gigabit-ethernet-switch.shtml	Industrial Switch: IDS-105G
07010910	IDS-105G-S2ST70 Industrial Gigabit Switch: 5 x 10/100/1000Base-T Base-T RJ-45 ports and 1 x 1000Base-ZX, 1550nm single mode port with duplex ST connector [70 km/ 43.5 miles]. 0 to 60C operating temperature.	https://www.perle.com/products/5-port-industrial-gigabit-ethernet-switch.shtml	Industrial Switch: IDS-105G
07010920	IDS-105G-S2SC120 Industrial Gigabit Switch: 5 x 10/100/1000Base-T Base-T RJ-45 ports and 1 x 1000Base-ZX, 1550nm single mode port with duplex SC connector [120 km/ 74.6 miles]. 0 to 60C operating temperature.	https://www.perle.com/products/5-port-industrial-gigabit-ethernet-switch.shtml	Industrial Switch: IDS-105G
07010930	IDS-105G-S2ST120 Industrial Gigabit Switch: 5 x 10/100/1000Base-T Base-T RJ-45 ports and 1 x 1000Base-ZX, 1550nm single mode port with duplex ST connector [120 km/ 74.6 miles]. 0 to 60C operating temperature.	https://www.perle.com/products/5-port-industrial-gigabit-ethernet-switch.shtml	Industrial Switch: IDS-105G
07010940	IDS-105G-S2SC160 Industrial Gigabit Switch: 5 x 10/100/1000Base-T Base-T RJ-45 ports and 1 x 1000Base-ZX, 1550nm single mode port with duplex SC connector [160 km/ 100 miles]. 0 to 60C operating temperature.	https://www.perle.com/products/5-port-industrial-gigabit-ethernet-switch.shtml	Industrial Switch: IDS-105G
07010950	IDS-105G-S2ST160 Industrial Gigabit Switch: 5 x 10/100/1000Base-T Base-T RJ-45 ports and 1 x 1000Base-ZX, 1550nm single mode port with duplex ST connector [160 km/ 100 miles]. 0 to 60C operating temperature.	https://www.perle.com/products/5-port-industrial-gigabit-ethernet-switch.shtml	Industrial Switch: IDS-105G
07010960	IDS-105G-S1SC10U Industrial Gigabit Switch: 5 x 10/100/1000Base-T Base-T RJ-45 ports and 1 x 1000Base-BX, 1310nm TX / 1490nm RX single strand single mode port with simplex (BIDI) SC connector [10km/6.2 miles]. 0 to 60C operating temperature.	https://www.perle.com/products/5-port-industrial-gigabit-ethernet-switch.shtml	Industrial Switch: IDS-105G
07010970	IDS-105G-S1SC10D Industrial Gigabit Switch: 5 x 10/100/1000Base-T Base-T RJ-45 ports and 1 x 1000Base-BX, 1490nm TX / 1310nm RX single strand single mode port with simplex (BIDI) SC connector [10km/6.2 miles]. 0 to 60C operating temperature.	https://www.perle.com/products/5-port-industrial-gigabit-ethernet-switch.shtml	Industrial Switch: IDS-105G
07010980	IDS-105G-S1SC20U Industrial Gigabit Switch: 5 x 10/100/1000Base-T Base-T RJ-45 ports and 1 x 1000Base-BX, 1310nm TX / 1490nm RX single strand single mode port with simplex (BIDI) SC connector [20km/12.4 miles]. 0 to 60C operating temperature.	https://www.perle.com/products/5-port-industrial-gigabit-ethernet-switch.shtml	Industrial Switch: IDS-105G
07010990	IDS-105G-S1SC20D Industrial Gigabit Switch: 5 x 10/100/1000Base-T Base-T RJ-45 ports and 1 x 1000Base-BX, 1490nm TX / 1310nm RX single strand single mode port with simplex (BIDI) SC connector [20km/12.4 miles]. 0 to 60C operating temperature.	https://www.perle.com/products/5-port-industrial-gigabit-ethernet-switch.shtml	Industrial Switch: IDS-105G

Part #	Description	Product Datasheet	Product Group
07011000	IDS-105G-S1SC40U Industrial Gigabit Switch: 5 x 10/100/1000Base-T Base-T RJ-45 ports and 1 x 1000Base-BX, 1310nm TX / 1490nm RX single strand single mode port with simplex (BIDI) SC connector [40km/24.9 miles]. 0 to 60C operating temperature.	https://www.perle.com/products/5-port-industrial-gigabit-ethernet-switch.shtml	Industrial Switch: IDS-105G
07011010	IDS-105G-S1SC40D Industrial Gigabit Switch: 5 x 10/100/1000Base-T Base-T RJ-45 ports and 1 x 1000Base-BX, 1490nm TX / 1310nm RX single strand single mode port with simplex (BIDI) SC connector [40km/24.9 miles]. 0 to 60C operating temperature.	https://www.perle.com/products/5-port-industrial-gigabit-ethernet-switch.shtml	Industrial Switch: IDS-105G
07011020	IDS-105G-S1SC80U Industrial Gigabit Switch: 5 x 10/100/1000Base-T Base-T RJ-45 ports and 1 x 1000Base-BX, 1310nm TX / 1490nm RX single strand single mode port with simplex (BIDI) SC connector [80km/49.7 miles]. 0 to 60C operating temperature.	https://www.perle.com/products/5-port-industrial-gigabit-ethernet-switch.shtml	Industrial Switch: IDS-105G
07011030	IDS-105G-S1SC80D Industrial Gigabit Switch: 5 x 10/100/1000Base-T Base-T RJ-45 ports and 1 x 1000Base-BX, 1590nm TX / 1510nm RX single strand single mode port with simplex (BIDI) SC connector [80km/49.7miles]. 0 to 60C operating temperature.	https://www.perle.com/products/5-port-industrial-gigabit-ethernet-switch.shtml	Industrial Switch: IDS-105G
07011040	IDS-105G-S1SC120U Industrial Gigabit Switch: 5 x 10/100/1000Base-T Base-T RJ-45 ports and 1 x 1000Base-BX, 1510nm TX / 1590nm RX single strand single mode port with simplex (BIDI) SC connector [120km/74.6 miles]. 0 to 60C operating temperature.	https://www.perle.com/products/5-port-industrial-gigabit-ethernet-switch.shtml	Industrial Switch: IDS-105G
07011050	IDS-105G-S1SC120D Industrial Gigabit Switch: 5 x 10/100/1000Base-T Base-T RJ-45 ports and 1 x 1000Base-BX, 1590nm TX / 1510nm RX single strand single mode port with simplex (BIDI) SC connector [120km/74.6 miles]. 0 to 60C operating temperature.	https://www.perle.com/products/5-port-industrial-gigabit-ethernet-switch.shtml	Industrial Switch: IDS-105G
07011060	IDS-105G-XT Industrial Gigabit Switch: 5 x 10/100/1000Base-T Base-T RJ-45 ports. -40 to 75C industrial extended operating temperature.	https://www.perle.com/products/5-port-industrial-gigabit-ethernet-switch.shtml	Industrial Switch: IDS-105G
07011070	IDS-105G-M2SC05-XT Industrial Gigabit Switch: 5 x 10/100/1000Base-T Base-T RJ-45 ports and 1 x 1000Base-SX, 850nm multimode port with duplex SC connector [550m/1804 ft].-40 to 75C industrial extended operating temperature.	https://www.perle.com/products/5-port-industrial-gigabit-ethernet-switch.shtml	Industrial Switch: IDS-105G
07011080	IDS-105G-M2ST05-XT Industrial Gigabit Switch: 5 x 10/100/1000Base-T Base-T RJ-45 ports and 1 x 1000Base-SX, 850nm multimode port with duplex ST connector [550m/1804 ft]. -40 to 75C industrial extended operating temperature.	https://www.perle.com/products/5-port-industrial-gigabit-ethernet-switch.shtml	Industrial Switch: IDS-105G

Part #	Description	Product Datasheet	Product Group
07011090	IDS-105G-S2SC10-XT Industrial Gigabit Switch: 5 x 10/100/1000Base-T Base-T RJ-45 ports and 1 x 1000Base-LX/LH, 1310nm single mode port with duplex SC connector [10 km/ 6.2 miles]. -40 to 75C industrial extended operating temperature.	https://www.perle.com/products/5-port-industrial-gigabit-ethernet-switch.shtml	Industrial Switch: IDS-105G
07011100	IDS-105G-S2ST10-XT Industrial Gigabit Switch: 5 x 10/100/1000Base-T Base-T RJ-45 ports and 1 x 1000Base-LX/LH, 1310nm single mode port with duplex ST connector [10 km/ 6.2 miles]. -40 to 75C industrial extended operating temperature.	https://www.perle.com/products/5-port-industrial-gigabit-ethernet-switch.shtml	Industrial Switch: IDS-105G
07011110	IDS-105G-S1SC10U-XT Industrial Gigabit Switch: 5 x 10/100/1000Base-T Base-T RJ-45 ports and 1 x 1000Base-BX, 1310nm TX / 1490nm RX single strand single mode port with simplex (BIDI) SC connector [10km/6.2 miles]. -40 to 75C industrial extended operating temperature.	https://www.perle.com/products/5-port-industrial-gigabit-ethernet-switch.shtml	Industrial Switch: IDS-105G
07011120	IDS-105G-S1SC10D-XT Industrial Gigabit Switch: 5 x 10/100/1000Base-T Base-T RJ-45 ports and 1 x 1000Base-BX, 1490nm TX / 1310nm RX single strand single mode port with simplex (BIDI) SC connector [10km/6.2 miles]. -40 to 75C industrial extended operating temperature.	https://www.perle.com/products/5-port-industrial-gigabit-ethernet-switch.shtml	Industrial Switch: IDS-105G
07011130	IDS-105G-SFP Industrial Gigabit Switch: 5 x 10/100/1000Base-T Base-T RJ-45 ports and 1 x 1000BASE-X SFP slot (empty). 0 to 60C operating temperature.	https://www.perle.com/products/5-port-industrial-gigabit-ethernet-switch.shtml	Industrial Switch: IDS-105G
07011140	IDS-105G-DSFP Industrial Gigabit Switch: 5 x 10/100/1000Base-T Base-T RJ-45 ports and 2 x 1000BASE-X SFP slots (empty). 0 to 60C operating temperature.	https://www.perle.com/products/5-port-industrial-gigabit-ethernet-switch.shtml	Industrial Switch: IDS-105G
07011150	IDS-105G-SFP-XT Industrial Gigabit Switch: 5 x 10/100/1000Base-T Base-T RJ-45 ports and 1 x 1000BASE-X SFP slot (empty). -40 to 75C industrial extended operating temperature.	https://www.perle.com/products/5-port-industrial-gigabit-ethernet-switch.shtml	Industrial Switch: IDS-105G
07011160	IDS-105G-DSFP-XT Industrial Switch: 5 x 10/100/1000Base-T Base-T RJ-45 ports and 2 x 1000BASE-X SFP slots (empty). -40 to 75C industrial extended operating temperature.	https://www.perle.com/products/5-port-industrial-gigabit-ethernet-switch.shtml	Industrial Switch: IDS-105G
07011170	IDS-108FPP Industrial PoE Switch: 8 x 10/100Base-TX RJ45 ports, 4 of which support PoE/PoE+. 0 to 60C operating temperature.	https://www.perle.com/products/8-port-industrial-poe-switch.shtml	Industrial Switch: IDS-108FPP
07011180	IDS-108FPP-M2SC2 Industrial PoE Switch: 8 x 10/100Base-TX RJ45 ports, 4 of which support PoE/PoE+ and 1 x 100Base-FX, 1310nm multimode port with duplex SC connector [up to 5km/3.1 miles]. 0 to 60C operating temperature.	https://www.perle.com/products/8-port-industrial-poe-switch.shtml	Industrial Switch: IDS-108FPP

Part #	Description	Product Datasheet	Product Group
07011190	IDS-108FPP-M2ST2 Industrial PoE Switch: 8 x 10/100Base-TX RJ45 ports, 4 of which support PoE/PoE+ and 1 x 100Base-FX, 1310nm multimode port with duplex ST connector [up to 5km/3.1 miles]. 0 to 60C operating temperature.	https://www.perle.com/products/8-port-industrial-poe-switch.shtml	Industrial Switch: IDS-108FPP
07011200	IDS-108FPP-S2SC20 Industrial PoE Switch: 8 x 10/100Base-TX RJ45 ports, 4 of which support PoE/PoE+ and 1 x 100Base-LX, 1310nm single mode port with duplex SC connector [20 km/ 12.4 miles]. 0 to 60C operating temperature.	https://www.perle.com/products/8-port-industrial-poe-switch.shtml	Industrial Switch: IDS-108FPP
07011210	IDS-108FPP-S2ST20 Industrial PoE Switch: 8 x 10/100Base-TX RJ45 ports, 4 of which support PoE/PoE+ and 1 x 100Base-LX, 1310nm single mode port with duplex ST connector [20 km/ 12.4 miles]. 0 to 60C operating temperature.	https://www.perle.com/products/8-port-industrial-poe-switch.shtml	Industrial Switch: IDS-108FPP
07011220	IDS-108FPP-S2SC40 Industrial PoE Switch: 8 x 10/100Base-TX RJ45 ports, 4 of which support PoE/PoE+ and 1 x 100Base-LX, 1310nm single mode port with duplex SC connector [40 km/ 24.9 miles]. 0 to 60C operating temperature.	https://www.perle.com/products/8-port-industrial-poe-switch.shtml	Industrial Switch: IDS-108FPP
07011230	IDS-108FPP-S2ST40 Industrial PoE Switch: 8 x 10/100Base-TX RJ45 ports, 4 of which support PoE/PoE+ and 1 x 100Base-LX, 1310nm single mode port with duplex ST connector [40 km/ 24.9 miles]. 0 to 60C operating temperature.	https://www.perle.com/products/8-port-industrial-poe-switch.shtml	Industrial Switch: IDS-108FPP
07011240	IDS-108FPP-S2SC80 Industrial PoE Switch: 8 x 10/100Base-TX RJ45 ports, 4 of which support PoE/PoE+ and 1 x 100Base-EX, 1550nm single mode port with duplex SC connector [80 km/ 49.7 miles]. 0 to 60C operating temperature.	https://www.perle.com/products/8-port-industrial-poe-switch.shtml	Industrial Switch: IDS-108FPP
07011250	IDS-108FPP-S2ST80 Industrial PoE Switch: 8 x 10/100Base-TX RJ45 ports, 4 of which support PoE/PoE+ and 1 x 100Base-EX, 1550nm single mode port with duplex ST connector [80 km/ 49.7 miles]. 0 to 60C operating temperature.	https://www.perle.com/products/8-port-industrial-poe-switch.shtml	Industrial Switch: IDS-108FPP
07011260	IDS-108FPP-S2SC120 Industrial PoE Switch: 8 x 10/100Base-TX RJ45 ports, 4 of which support PoE/PoE+ and 1 x 100Base-ZX, 1550nm single mode port with duplex SC connector [120 km/ 74.6 miles]. 0 to 60C operating temperature.	https://www.perle.com/products/8-port-industrial-poe-switch.shtml	Industrial Switch: IDS-108FPP

Part #	Description	Product Datasheet	Product Group
07011270	IDS-108FPP-S2ST120 Industrial PoE Switch: 8 x 10/100Base-TX RJ45 ports, 4 of which support PoE/PoE+ and 1 x 100Base-ZX, 1550nm single mode port with duplex ST connector [120 km/ 74.6 miles]. 0 to 60C operating temperature.	https://www.perle.com/products/8-port-industrial-poe-switch.shtml	Industrial Switch: IDS-108FPP
07011280	IDS-108FPP-M1SC2U Industrial PoE Switch: 8 x 10/100Base-TX RJ45 ports, 4 of which support PoE/PoE+ and 1 x 100Base-BX, 1310nm TX / 1550nm RX single strand multimode port with simplex (BIDI) SC connector [up to 5km/3.1 miles]. 0 to 60C operating temperature.	https://www.perle.com/products/8-port-industrial-poe-switch.shtml	Industrial Switch: IDS-108FPP
07011290	IDS-108FPP-M1SC2D Industrial PoE Switch: 8 x 10/100Base-TX RJ45 ports, 4 of which support PoE/PoE+ and 1 x 100Base-BX, 1550nm TX / 1310nm RX single strand multimode port with simplex (BIDI) SC connector [up to 5km/3.1 miles]. 0 to 60C operating temperature.	https://www.perle.com/products/8-port-industrial-poe-switch.shtml	Industrial Switch: IDS-108FPP
07011300	IDS-108FPP-S1SC20U Industrial PoE Switch: 8 x 10/100Base-TX RJ45 ports, 4 of which support PoE/PoE+ and 1 x 100Base-BX, 1310nm TX / 1550nm RX single strand single mode port with simplex (BIDI) SC connector [20km/12.4 miles]. 0 to 60C operating temperature.	https://www.perle.com/products/8-port-industrial-poe-switch.shtml	Industrial Switch: IDS-108FPP
07011310	IDS-108FPP-S1SC20D Industrial PoE Switch: 8 x 10/100Base-TX RJ45 ports, 4 of which support PoE/PoE+ and 1 x 100Base-BX, 1550nm TX / 1310nm RX single strand single mode port with simplex (BIDI) SC connector [20km/12.4 miles]. 0 to 60C operating temperature.	https://www.perle.com/products/8-port-industrial-poe-switch.shtml	Industrial Switch: IDS-108FPP
07011320	IDS-108FPP-S1SC40U Industrial PoE Switch: 8 x 10/100Base-TX RJ45 ports, 4 of which support PoE/PoE+ and 1 x 100Base-BX, 1310nm TX / 1550nm RX single strand single mode port with simplex (BIDI) SC connector [40km/24.9 miles]. 0 to 60C operating temperature.	https://www.perle.com/products/8-port-industrial-poe-switch.shtml	Industrial Switch: IDS-108FPP
07011330	IDS-108FPP-S1SC40D Industrial PoE Switch: 8 x 10/100Base-TX RJ45 ports, 4 of which support PoE/PoE+ and 1 x 100Base-BX, 1550nm TX / 1310nm RX single strand single mode port with simplex (BIDI) SC connector [40km/24.9 miles]. 0 to 60C operating temperature.	https://www.perle.com/products/8-port-industrial-poe-switch.shtml	Industrial Switch: IDS-108FPP
07011340	IDS-108FPP-DM2SC2 Industrial PoE Switch: 8 x 10/100Base-TX RJ45 ports, 4 of which support PoE/PoE+ and 2 x 100Base-FX, 1310nm multimode port with duplex SC connectors [up to 5km/3.1 miles]. 0 to 60C operating temperature.	https://www.perle.com/products/8-port-industrial-poe-switch.shtml	Industrial Switch: IDS-108FPP

Part #	Description	Product Datasheet	Product Group
07011350	IDS-108FPP-DM2ST2 Industrial PoE Switch: 8 x 10/100Base-TX RJ45 ports, 4 of which support PoE/PoE+ and 2 x 100Base-FX, 1310nm multimode port with duplex ST connectors [up to 5km/3.1 miles]. 0 to 60C operating temperature.	https://www.perle.com/products/8-port-industrial-poe-switch.shtml	Industrial Switch: IDS-108FPP
07011360	IDS-108FPP-DS2SC20 Industrial PoE Switch: 8 x 10/100Base-TX RJ45 ports, 4 of which support PoE/PoE+ and 2 x 100Base-LX, 1310nm single mode port with duplex SC connectors [20 km/ 12.4 miles]. 0 to 60C operating temperature.	https://www.perle.com/products/8-port-industrial-poe-switch.shtml	Industrial Switch: IDS-108FPP
07011370	IDS-108FPP-DS2ST20 Industrial PoE Switch: 8 x 10/100Base-TX RJ45 ports, 4 of which support PoE/PoE+ and 2 x 100Base-LX, 1310nm single mode port with duplex ST connectors [20 km/ 12.4 miles]. 0 to 60C operating temperature.	https://www.perle.com/products/8-port-industrial-poe-switch.shtml	Industrial Switch: IDS-108FPP
07011380	IDS-108FPP-DS2SC40 Industrial PoE Switch: 8 x 10/100Base-TX RJ45 ports, 4 of which support PoE/PoE+ and 2 x 100Base-LX, 1310nm single mode port with duplex SC connectors [40 km/ 24.9 miles]. 0 to 60C operating temperature.	https://www.perle.com/products/8-port-industrial-poe-switch.shtml	Industrial Switch: IDS-108FPP
07011390	IDS-108FPP-DS2ST40 Industrial PoE Switch: 8 x 10/100Base-TX RJ45 ports, 4 of which support PoE/PoE+ and 2 x 100Base-LX, 1310nm single mode port with duplex ST connectors [40 km/ 24.9 miles]. 0 to 60C operating temperature.	https://www.perle.com/products/8-port-industrial-poe-switch.shtml	Industrial Switch: IDS-108FPP
07011400	IDS-108FPP-DS2SC80 Industrial PoE Switch: 8 x 10/100Base-TX RJ45 ports, 4 of which support PoE/PoE+ and 2 x 100Base-EX, 1550nm single mode port with duplex SC connectors [80 km/ 49.7 miles]. 0 to 60C operating temperature.	https://www.perle.com/products/8-port-industrial-poe-switch.shtml	Industrial Switch: IDS-108FPP
07011410	IDS-108FPP-DS2ST80 Industrial PoE Switch: 8 x 10/100Base-TX RJ45 ports, 4 of which support PoE/PoE+ and 2 x 100Base-EX, 1550nm single mode port with duplex ST connectors [80 km/ 49.7 miles]. 0 to 60C operating temperature.	https://www.perle.com/products/8-port-industrial-poe-switch.shtml	Industrial Switch: IDS-108FPP
07011420	IDS-108FPP-DS2SC120 Industrial PoE Switch: 8 x 10/100Base-TX RJ45 ports, 4 of which support PoE/PoE+ and 2 x 100Base-ZX, 1550nm single mode port with duplex SC connectors [120 km/ 74.6 miles]. 0 to 60C operating temperature.	https://www.perle.com/products/8-port-industrial-poe-switch.shtml	Industrial Switch: IDS-108FPP

Part #	Description	Product Datasheet	Product Group
07011430	IDS-108FPP-DS2ST120 Industrial PoE Switch: 8 x 10/100Base-TX RJ45 ports, 4 of which support PoE/PoE+ and 2 x 100Base-ZX, 1550nm single mode port with duplex ST connectors [120 km/ 74.6 miles]. 0 to 60C operating temperature.	https://www.perle.com/products/8-port-industrial-poe-switch.shtml	Industrial Switch: IDS-108FPP
07011440	IDS-108FPP-DM1SC2U Industrial PoE Switch: 8 x 10/100Base-TX RJ45 ports, 4 of which support PoE/PoE+ and 2 x 100Base-BX, 1310nm TX / 1550nm RX single strand multimode port with simplex (BIDI) SC connectors [up to 5km/3.1 miles]. 0 to 60C operating temperature.	https://www.perle.com/products/8-port-industrial-poe-switch.shtml	Industrial Switch: IDS-108FPP
07011450	IDS-108FPP-DM1SC2D Industrial PoE Switch: 8 x 10/100Base-TX RJ45 ports, 4 of which support PoE/PoE+ and 2 x 100Base-BX, 1550nm TX / 1310nm RX single strand multimode port with simplex (BIDI) SC connectors [up to 5km/3.1 miles]. 0 to 60C operating temperature.	https://www.perle.com/products/8-port-industrial-poe-switch.shtml	Industrial Switch: IDS-108FPP
07011460	IDS-108FPP-DS1SC20U Industrial PoE Switch: 8 x 10/100Base-TX RJ45 ports, 4 of which support PoE/PoE+ and 2 x 100Base-BX, 1310nm TX / 1550nm RX single strand single mode port with simplex (BIDI) SC connectors [20km/12.4 miles]. 0 to 60C operating temperature.	https://www.perle.com/products/8-port-industrial-poe-switch.shtml	Industrial Switch: IDS-108FPP
07011470	IDS-108FPP-DS1SC20D Industrial PoE Switch: 8 x 10/100Base-TX RJ45 ports, 4 of which support PoE/PoE+ and 2 x 100Base-BX, 1550nm TX / 1310nm RX single strand single mode port with simplex (BIDI) SC connectors [20km/12.4 miles]. 0 to 60C operating temperature.	https://www.perle.com/products/8-port-industrial-poe-switch.shtml	Industrial Switch: IDS-108FPP
07011480	IDS-108FPP-DS1SC40U Industrial PoE Switch: 8 x 10/100Base-TX RJ45 ports, 4 of which support PoE/PoE+ and 2 x 100Base-BX, 1310nm TX / 1550nm RX single strand single mode port with simplex (BIDI) SC connectors [40km/24.9 miles]. 0 to 60C operating temperature.	https://www.perle.com/products/8-port-industrial-poe-switch.shtml	Industrial Switch: IDS-108FPP
07011490	IDS-108FPP-DS1SC40D Industrial PoE Switch: 8 x 10/100Base-TX RJ45 ports, 4 of which support PoE/PoE+ and 2 x 100Base-BX, 1550nm TX / 1310nm RX single strand single mode port with simplex (BIDI) SC connectors [40km/24.9 miles]. 0 to 60C operating temperature.	https://www.perle.com/products/8-port-industrial-poe-switch.shtml	Industrial Switch: IDS-108FPP
07011500	IDS-108FPP-XT Industrial PoE Switch: 8 x 10/100Base-TX RJ45 ports, 4 of which support PoE/PoE+. -40 to 75C Industrial extended operating temperature.	https://www.perle.com/products/8-port-industrial-poe-switch.shtml	Industrial Switch: IDS-108FPP
07011510	IDS-108FPP-M2SC2-XT Industrial PoE Switch: 8 x 10/100Base-TX RJ45 ports, 4 of which support PoE/PoE+ and 1 x 100Base-FX, 1310nm multimode port with duplex SC connector [up to 5km/3.1 miles]. -40 to 75C Industrial extended operating temperature.	https://www.perle.com/products/8-port-industrial-poe-switch.shtml	Industrial Switch: IDS-108FPP

Part #	Description	Product Datasheet	Product Group
07011520	IDS-108FPP-M2ST2-XT Industrial PoE Switch: 8 x 10/100Base-TX RJ45 ports, 4 of which support PoE/PoE+ and 1 x 100Base-FX, 1310nm multimode port with duplex ST connector [up to 5km/3.1 miles]. -40 to 75C Industrial extended operating temperature.	https://www.perle.com/products/8-port-industrial-poe-switch.shtml	Industrial Switch: IDS-108FPP
07011530	IDS-108FPP-S2SC20-XT Industrial PoE Switch: 8 x 10/100Base-TX RJ45 ports, 4 of which support PoE/PoE+ and 1 x 100Base-LX, 1310nm single mode port with duplex SC connector [20 km/ 12.4 miles]. -40 to 75C Industrial extended operating temperature.	https://www.perle.com/products/8-port-industrial-poe-switch.shtml	Industrial Switch: IDS-108FPP
07011540	IDS-108FPP-S2ST20-XT Industrial PoE Switch: 8 x 10/100Base-TX RJ45 ports, 4 of which support PoE/PoE+ and 1 x 100Base-LX, 1310nm single mode port with duplex ST connector [20 km/ 12.4 miles]. -40 to 75C Industrial extended operating temperature.	https://www.perle.com/products/8-port-industrial-poe-switch.shtml	Industrial Switch: IDS-108FPP
07011550	IDS-108FPP-S2SC40-XT Industrial PoE Switch: 8 x 10/100Base-TX RJ45 ports, 4 of which support PoE/PoE+ and 1 x 100Base-LX, 1310nm single mode port with duplex SC connector [40 km/ 24.9 miles]. -40 to 75C Industrial extended operating temperature.	https://www.perle.com/products/8-port-industrial-poe-switch.shtml	Industrial Switch: IDS-108FPP
07011560	IDS-108FPP-S2ST40-XT Industrial PoE Switch: 8 x 10/100Base-TX RJ45 ports, 4 of which support PoE/PoE+ and 1 x 100Base-LX, 1310nm single mode port with duplex ST connector [40 km/ 24.9 miles]. -40 to 75C Industrial extended operating temperature.	https://www.perle.com/products/8-port-industrial-poe-switch.shtml	Industrial Switch: IDS-108FPP
07011570	IDS-108FPP-S1SC20U-XT Industrial PoE Switch: 8 x 10/100Base-TX RJ45 ports, 4 of which support PoE/PoE+ and 1 x 100Base-BX, 1310nm TX / 1550nm RX single strand single mode port with simplex (BIDI) SC connector [20km/12.4 miles]. -40 to 75C Industrial extended operating temperature.	https://www.perle.com/products/8-port-industrial-poe-switch.shtml	Industrial Switch: IDS-108FPP
07011580	IDS-108FPP-S1SC20D-XT Industrial PoE Switch: 8 x 10/100Base-TX RJ45 ports, 4 of which support PoE/PoE+ and 1 x 100Base-BX, 1550nm TX / 1310nm RX single strand single mode port with simplex (BIDI) SC connector [20km/12.4 miles]. -40 to 75C Industrial extended operating temperature.	https://www.perle.com/products/8-port-industrial-poe-switch.shtml	Industrial Switch: IDS-108FPP
07011590	IDS-108FPP-DM2SC2-XT Industrial PoE Switch: 8 x 10/100Base-TX RJ45 ports, 4 of which support PoE/PoE+ and 2 x 100Base-FX, 1310nm multimode port with duplex SC connectors [up to 5km/3.1 miles]. -40 to 75C Industrial extended operating temperature.	https://www.perle.com/products/8-port-industrial-poe-switch.shtml	Industrial Switch: IDS-108FPP

Part #	Description	Product Datasheet	Product Group
07011600	IDS-108FPP-DM2ST2-XT Industrial PoE Switch: 8 x 10/100Base-TX RJ45 ports, 4 of which support PoE/PoE+ and 2 x 100Base-FX, 1310nm multimode port with duplex ST connectors [up to 5km/3.1 miles].-40 to 75C Industrial extended operating temperature.	https://www.perle.com/products/8-port-industrial-poe-switch.shtml	Industrial Switch: IDS-108FPP
07011610	IDS-108FPP-DS2SC20-XT Industrial PoE Switch: 8 x 10/100Base-TX RJ45 ports, 4 of which support PoE/PoE+ and 2 x 100Base-LX, 1310nm single mode port with duplex SC connectors [20 km/ 12.4 miles]. -40 to 75C Industrial extended operating temperature.	https://www.perle.com/products/8-port-industrial-poe-switch.shtml	Industrial Switch: IDS-108FPP
07011620	IDS-108FPP-DS2ST20-XT Industrial PoE Switch: 8 x 10/100Base-TX RJ45 ports, 4 of which support PoE/PoE+ and 2 x 100Base-LX, 1310nm single mode port with duplex ST connectors [20 km/ 12.4 miles]. -40 to 75C Industrial extended operating temperature.	https://www.perle.com/products/8-port-industrial-poe-switch.shtml	Industrial Switch: IDS-108FPP
07011630	IDS-108FPP-DS2SC40-XT Industrial PoE Switch: 8 x 10/100Base-TX RJ45 ports, 4 of which support PoE/PoE+ and 2 x 100Base-LX, 1310nm single mode port with duplex SC connectors [40 km/ 24.9 miles]. -40 to 75C Industrial extended operating temperature.	https://www.perle.com/products/8-port-industrial-poe-switch.shtml	Industrial Switch: IDS-108FPP
07011640	IDS-108FPP-DS2ST40-XT Industrial PoE Switch: 8 x 10/100Base-TX RJ45 ports, 4 of which support PoE/PoE+ and 2 x 100Base-LX, 1310nm single mode port with duplex ST connectors [40 km/ 24.9 miles]. -40 to 75C Industrial extended operating temperature.	https://www.perle.com/products/8-port-industrial-poe-switch.shtml	Industrial Switch: IDS-108FPP
07011650	IDS-108FPP-DS1SC20U-XT Industrial PoE Switch: 8 x 10/100Base-TX RJ45 ports, 4 of which support PoE/PoE+ and 2 x 100Base-BX, 1310nm TX / 1550nm RX single strand single mode port with simplex (BIDI) SC connectors [20km/12.4 miles]. -40 to 75C Industrial extended operating temperature.	https://www.perle.com/products/8-port-industrial-poe-switch.shtml	Industrial Switch: IDS-108FPP
07011660	IDS-108FPP-DS1SC20D-XT Industrial PoE Switch: 8 x 10/100Base-TX RJ45 ports, 4 of which support PoE/PoE+ and 2 x 100Base-BX, 1550nm TX / 1310nm RX single strand single mode port with simplex (BIDI) SC connectors [20km/12.4 miles]. -40 to 75C Industrial extended operating temperature.	https://www.perle.com/products/8-port-industrial-poe-switch.shtml	Industrial Switch: IDS-108FPP
07011670	IDS-105GPP Industrial PoE Switch: 5 x 10/100/1000Base-T Base-T RJ-45 ports, 4 of which are PoE/PoE+ capable. 0 to 60C operating temperature.	https://www.perle.com/products/5-port-industrial-gigabit-poe-switch.shtml	Industrial Switch: IDS-105GPP
07011680	IDS-105GPP-SFP Industrial PoE Switch: 5 x 10/100/1000Base-T Base-T RJ-45 ports, 4 of which are PoE/PoE+ capable and 1 x 1000BASE-X SFP slot (empty). 0 to 60C operating temperature.	https://www.perle.com/products/5-port-industrial-gigabit-poe-switch.shtml	Industrial Switch: IDS-105GPP

Part #	Description	Product Datasheet	Product Group
07011690	IDS-105GPP-DSFP Industrial PoE Switch: 5 x 10/100/1000Base-T Base-T RJ-45 ports, 4 of which are PoE/PoE+ capable and 2 x 1000BASE-X SFP slot (empty). 0 to 60C operating temperature.	https://www.perle.com/products/5-port-industrial-gigabit-poe-switch.shtml	Industrial Switch: IDS-105GPP
07011700	IDS-105GPP-M2SC05 Industrial PoE Switch: 5 x 10/100/1000Base-T Base-T RJ-45 ports, 4 of which are PoE/PoE+ capable and 1 x 1000Base-SX, 850nm multimode port with duplex SC connector [550m/1804 ft]. 0 to 60C operating temperature.	https://www.perle.com/products/5-port-industrial-gigabit-poe-switch.shtml	Industrial Switch: IDS-105GPP
07011710	IDS-105GPP-M2ST05 Industrial PoE Switch: 5 x 10/100/1000Base-T Base-T RJ-45 ports, 4 of which are PoE/PoE+ capable and 1 x 1000Base-SX, 850nm multimode port with duplex ST connector [550m/1804 ft]. 0 to 60C operating temperature.	https://www.perle.com/products/5-port-industrial-gigabit-poe-switch.shtml	Industrial Switch: IDS-105GPP
07011720	IDS-105GPP-M2SC2 Industrial PoE Switch: 5 x 10/100/1000Base-T Base-T RJ-45 ports, 4 of which are PoE/PoE+ capable and 1 x 1000Base-SX, 1310nm extended multimode port with duplex SC connector [2km/1.2 miles]. 0 to 60C operating temperature.	https://www.perle.com/products/5-port-industrial-gigabit-poe-switch.shtml	Industrial Switch: IDS-105GPP
07011730	IDS-105GPP-M2ST2 Industrial PoE Switch: 5 x 10/100/1000Base-T Base-T RJ-45 ports, 4 of which are PoE/PoE+ capable and 1 x 1000Base-SX, 1310nm extended multimode port with duplex ST connector [2km/1.2 miles]. 0 to 60C operating temperature.	https://www.perle.com/products/5-port-industrial-gigabit-poe-switch.shtml	Industrial Switch: IDS-105GPP
07011740	IDS-105GPP-S2SC10 Industrial PoE Switch: 5 x 10/100/1000Base-T Base-T RJ-45 ports, 4 of which are PoE/PoE+ capable and 1 x 1000Base-LX/LH, 1310nm single mode port with duplex SC connector [10 km/ 6.2 miles]. 0 to 60C operating temperature.	https://www.perle.com/products/5-port-industrial-gigabit-poe-switch.shtml	Industrial Switch: IDS-105GPP
07011750	IDS-105GPP-S2ST10 Industrial PoE Switch: 5 x 10/100/1000Base-T Base-T RJ-45 ports, 4 of which are PoE/PoE+ capable and 1 x 1000Base-LX/LH, 1310nm single mode port with duplex ST connector [10 km/ 6.2 miles]. 0 to 60C operating temperature.	https://www.perle.com/products/5-port-industrial-gigabit-poe-switch.shtml	Industrial Switch: IDS-105GPP
07011760	IDS-105GPP-S2SC40 Industrial PoE Switch: 5 x 10/100/1000Base-T Base-T RJ-45 ports, 4 of which are PoE/PoE+ capable and 1 x 1000Base-EX, 1310nm single mode port with duplex SC connector [40 km/ 24.9 miles]. 0 to 60C operating temperature.	https://www.perle.com/products/5-port-industrial-gigabit-poe-switch.shtml	Industrial Switch: IDS-105GPP
07011770	IDS-105GPP-S2ST40 Industrial PoE Switch: 5 x 10/100/1000Base-T Base-T RJ-45 ports, 4 of which are PoE/PoE+ capable and 1 x 1000Base-EX, 1310nm single mode port with duplex ST connector [40 km/ 24.9 miles]. 0 to 60C operating temperature.	https://www.perle.com/products/5-port-industrial-gigabit-poe-switch.shtml	Industrial Switch: IDS-105GPP

Part #	Description	Product Datasheet	Product Group
07011780	IDS-105GPP-S2SC70 Industrial PoE Switch: 5 x 10/100/1000Base-T Base-T RJ-45 ports, 4 of which are PoE/PoE+ capable and 1 x 1000Base-ZX, 1550nm single mode port with duplex SC connector [70 km/ 43.5 miles]. 0 to 60C operating temperature.	https://www.perle.com/products/5-port-industrial-gigabit-poe-switch.shtml	Industrial Switch: IDS-105GPP
07011790	IDS-105GPP-S2ST70 Industrial PoE Switch: 5 x 10/100/1000Base-T Base-T RJ-45 ports, 4 of which are PoE/PoE+ capable and 1 x 1000Base-ZX, 1550nm single mode port with duplex ST connector [70 km/ 43.5 miles]. 0 to 60C operating temperature.	https://www.perle.com/products/5-port-industrial-gigabit-poe-switch.shtml	Industrial Switch: IDS-105GPP
07011800	IDS-105GPP-S2SC120 Industrial PoE Switch: 5 x 10/100/1000Base-T Base-T RJ-45 ports, 4 of which are PoE/PoE+ capable and 1 x 1000Base-ZX, 1550nm single mode port with duplex SC connector [120 km/ 74.6 miles]. 0 to 60C operating temperature.	https://www.perle.com/products/5-port-industrial-gigabit-poe-switch.shtml	Industrial Switch: IDS-105GPP
07011810	IDS-105GPP-S2ST120 Industrial PoE Switch: 5 x 10/100/1000Base-T Base-T RJ-45 ports, 4 of which are PoE/PoE+ capable and 1 x 1000Base-ZX, 1550nm single mode port with duplex ST connector [120 km/ 74.6 miles]. 0 to 60C operating temperature.	https://www.perle.com/products/5-port-industrial-gigabit-poe-switch.shtml	Industrial Switch: IDS-105GPP
07011820	IDS-105GPP-S2SC160 Industrial PoE Switch: 5 x 10/100/1000Base-T Base-T RJ-45 ports, 4 of which are PoE/PoE+ capable and 1 x 1000Base-ZX, 1550nm single mode port with duplex SC connector [160 km/ 100 miles]. 0 to 60C operating temperature.	https://www.perle.com/products/5-port-industrial-gigabit-poe-switch.shtml	Industrial Switch: IDS-105GPP
07011830	IDS-105GPP-S2ST160 Industrial PoE Switch: 5 x 10/100/1000Base-T Base-T RJ-45 ports, 4 of which are PoE/PoE+ capable and 1 x 1000Base-ZX, 1550nm single mode port with duplex ST connector [160 km/ 100 miles]. 0 to 60C operating temperature.	https://www.perle.com/products/5-port-industrial-gigabit-poe-switch.shtml	Industrial Switch: IDS-105GPP
07011840	IDS-105GPP-S1SC10U Industrial PoE Switch: 5 x 10/100/1000Base-T Base-T RJ-45 ports, 4 of which are PoE/PoE+ capable and 1 x 1000Base-BX, 1310nm TX / 1490nm RX single strand single mode port with simplex (BIDI) SC connector [10km/6.2 miles]. 0 to 60C operating temperature.	https://www.perle.com/products/5-port-industrial-gigabit-poe-switch.shtml	Industrial Switch: IDS-105GPP
07011850	IDS-105GPP-S1SC10D Industrial PoE Switch: 5 x 10/100/1000Base-T Base-T RJ-45 ports, 4 of which are PoE/PoE+ capable and 1 x 1000Base-BX, 1490nm TX / 1310nm RX single strand single mode port with simplex (BIDI) SC connector [10km/6.2 miles]. 0 to 60C operating temperature.	https://www.perle.com/products/5-port-industrial-gigabit-poe-switch.shtml	Industrial Switch: IDS-105GPP

Part #	Description	Product Datasheet	Product Group
07011860	IDS-105GPP-S1SC20U Industrial PoE Switch: 5 x 10/100/1000Base-T Base-T RJ-45 ports, 4 of which are PoE/PoE+ capable and 1 x 1000Base-BX, 1310nm TX / 1490nm RX single strand single mode port with simplex (BIDI) SC connector [20km/12.4 miles]. 0 to 60C operating temperature.	https://www.perle.com/products/5-port-industrial-gigabit-poe-switch.shtml	Industrial Switch: IDS-105GPP
07011870	IDS-105GPP-S1SC20D Industrial PoE Switch: 5 x 10/100/1000Base-T Base-T RJ-45 ports, 4 of which are PoE/PoE+ capable and 1 x 1000Base-BX, 1490nm TX / 1310nm RX single strand single mode port with simplex (BIDI) SC connector [20km/12.4 miles]. 0 to 60C operating temperature.	https://www.perle.com/products/5-port-industrial-gigabit-poe-switch.shtml	Industrial Switch: IDS-105GPP
07011880	IDS-105GPP-S1SC40U Industrial PoE Switch: 5 x 10/100/1000Base-T Base-T RJ-45 ports, 4 of which are PoE/PoE+ capable and 1 x 1000Base-BX, 1310nm TX / 1490nm RX single strand single mode port with simplex (BIDI) SC connector [40km/24.9 miles]. 0 to 60C operating temperature.	https://www.perle.com/products/5-port-industrial-gigabit-poe-switch.shtml	Industrial Switch: IDS-105GPP
07011890	IDS-105GPP-S1SC40D Industrial PoE Switch: 5 x 10/100/1000Base-T Base-T RJ-45 ports, 4 of which are PoE/PoE+ capable and 1 x 1000Base-BX, 1490nm TX / 1310nm RX single strand single mode port with simplex (BIDI) SC connector [40km/24.9 miles]. 0 to 60C operating temperature.	https://www.perle.com/products/5-port-industrial-gigabit-poe-switch.shtml	Industrial Switch: IDS-105GPP
07011900	IDS-105GPP-S1SC80U Industrial PoE Switch: 5 x 10/100/1000Base-T Base-T RJ-45 ports, 4 of which are PoE/PoE+ capable and 1 x 1000Base-BX, 1510nm TX / 1590nm RX single strand single mode port with simplex (BIDI) SC connector [80km/49.7 miles]. 0 to 60C operating temperature.	https://www.perle.com/products/5-port-industrial-gigabit-poe-switch.shtml	Industrial Switch: IDS-105GPP
07011910	IDS-105GPP-S1SC80D Industrial PoE Switch: 5 x 10/100/1000Base-T Base-T RJ-45 ports, 4 of which are PoE/PoE+ capable and 1 x 1000Base-BX, 1590nm TX / 1510nm RX single strand single mode port with simplex (BIDI) SC connector [80km/49.7miles]. 0 to 60C operating temperature.	https://www.perle.com/products/5-port-industrial-gigabit-poe-switch.shtml	Industrial Switch: IDS-105GPP
07011920	IDS-105GPP-S1SC120U Industrial PoE Switch: 5 x 10/100/1000Base-T Base-T RJ-45 ports, 4 of which are PoE/PoE+ capable and 1 x 1000Base-BX, 1510nm TX / 1590nm RX single strand single mode port with simplex (BIDI) SC connector [120km/74.6 miles]. 0 to 60C operating temperature.	https://www.perle.com/products/5-port-industrial-gigabit-poe-switch.shtml	Industrial Switch: IDS-105GPP
07011930	IDS-105GPP-S1SC120D Industrial PoE Switch: 5 x 10/100/1000Base-T Base-T RJ-45 ports, 4 of which are PoE/PoE+ capable and 1 x 1000Base-BX, 1590nm TX / 1510nm RX single strand single mode port with simplex (BIDI) SC connector [120km/74.6 miles]. 0 to 60C operating temperature.	https://www.perle.com/products/5-port-industrial-gigabit-poe-switch.shtml	Industrial Switch: IDS-105GPP
07011940	IDS-105GPP-XT Industrial PoE Switch: 5 x 10/100/1000Base-T Base-T RJ-45 ports, 4 of which are PoE/PoE+ capable. -40 to 75C industrial extended operating temperature.	https://www.perle.com/products/5-port-industrial-gigabit-poe-switch.shtml	Industrial Switch: IDS-105GPP

Part #	Description	Product Datasheet	Product Group
07011950	IDS-105GPP-SFP-XT Industrial PoE Switch: 5 x 10/100/1000Base-T Base-T RJ-45 ports, 4 of which are PoE/PoE+ capable and 1 x 1000BASE-X SFP slot (empty). -40 to 75C industrial extended operating temperature.	https://www.perle.com/products/5-port-industrial-gigabit-poe-switch.shtml	Industrial Switch: IDS-105GPP
07011960	IDS-105GPP-DSFP-XT Industrial PoE Switch: 5 x 10/100/1000Base-T Base-T RJ-45 ports, 4 of which are PoE/PoE+ capable and 2 x 1000BASE-X SFP slot (empty). -40 to 75C industrial extended operating temperature.	https://www.perle.com/products/5-port-industrial-gigabit-poe-switch.shtml	Industrial Switch: IDS-105GPP
07011970	IDS-105GPP-M2SC05-XT Industrial PoE Switch: 5 x 10/100/1000Base-T Base-T RJ-45 ports, 4 of which are PoE/PoE+ capable and 1 x 1000Base-SX, 850nm multimode port with duplex SC connector [550m/1804 ft].-40 to 75C industrial extended operating temperature.	https://www.perle.com/products/5-port-industrial-gigabit-poe-switch.shtml	Industrial Switch: IDS-105GPP
07011980	IDS-105GPP-M2ST05-XT Industrial PoE Switch: 5 x 10/100/1000Base-T Base-T RJ-45 ports, 4 of which are PoE/PoE+ capable and 1 x 1000Base-SX, 850nm multimode port with duplex ST connector [550m/1804 ft]. -40 to 75C industrial extended operating temperature.	https://www.perle.com/products/5-port-industrial-gigabit-poe-switch.shtml	Industrial Switch: IDS-105GPP
07011990	IDS-105GPP-S2SC10-XT Industrial PoE Switch: 5 x 10/100/1000Base-T Base-T RJ-45 ports, 4 of which are PoE/PoE+ capable and 1 x 1000Base-LX/LH, 1310nm single mode port with duplex SC connector [10 km/ 6.2 miles]. -40 to 75C industrial extended operating temperature.	https://www.perle.com/products/5-port-industrial-gigabit-poe-switch.shtml	Industrial Switch: IDS-105GPP
07012000	IDS-105GPP-S2ST10-XT Industrial PoE Switch: 5 x 10/100/1000Base-T Base-T RJ-45 ports, 4 of which are PoE/PoE+ capable and 1 x 1000Base-LX/LH, 1310nm single mode port with duplex ST connector [10 km/ 6.2 miles]. -40 to 75C industrial extended operating temperature.	https://www.perle.com/products/5-port-industrial-gigabit-poe-switch.shtml	Industrial Switch: IDS-105GPP
07012010	IDS-105GPP-S1SC10U-XT Industrial PoE Switch: 5 x 10/100/1000Base-T Base-T RJ-45 ports, 4 of which are PoE/PoE+ capable and 1 x 1000Base-BX, 1310nm TX / 1490nm RX single strand single mode port with simplex (BIDI) SC connector [10km/6.2 miles]. -40 to 75C industrial extended operating temperature.	https://www.perle.com/products/5-port-industrial-gigabit-poe-switch.shtml	Industrial Switch: IDS-105GPP
07012020	IDS-105GPP-S1SC10D-XT Industrial PoE Switch: 5 x 10/100/1000Base-T Base-T RJ-45 ports, 4 of which are PoE/PoE+ capable and 1 x 1000Base-BX, 1490nm TX / 1310nm RX single strand single mode port with simplex (BIDI) SC connector [10km/6.2 miles]. -40 to 75C industrial extended operating temperature.	https://www.perle.com/products/5-port-industrial-gigabit-poe-switch.shtml	Industrial Switch: IDS-105GPP

Part #	Description	Product Datasheet	Product Group
07012050	IDS-205F-CMD2 Industrial Managed Switch, 5 ports: 4 x 10/100/1000Base-T Base-T RJ-45 ports and 1 x 100Base-FX, 1310nm multimode port with duplex SC connector [up to 5km/3.1 miles]. -10 to 60C operating temperature.	https://www.perle.com/products/switches/ids-205f-industrial-managed-ethernet-switch.shtml	Industrial Switch: IDS-205F
07012060	IDS-205F-TMD2 Industrial Managed Switch, 5 ports: 4 x 10/100/1000Base-T Base-T RJ-45 ports and 1 x 100Base-FX, 1310nm multimode port with duplex ST connector [up to 5km/3.1 miles]. -10 to 60C operating temperature.	https://www.perle.com/products/switches/ids-205f-industrial-managed-ethernet-switch.shtml	Industrial Switch: IDS-205F
07012070	IDS-205F-CSD20 Industrial Managed Switch, 5 ports: 4 x 10/100/1000Base-T Base-T RJ-45 ports and 1 x 100Base-LX, 1310nm single mode port with duplex SC connector [20 km/ 12.4 miles]. -10 to 60C operating temperature.	https://www.perle.com/products/switches/ids-205f-industrial-managed-ethernet-switch.shtml	Industrial Switch: IDS-205F
07012080	IDS-205F-TSD20 Industrial Managed Switch, 5 ports: 4 x 10/100/1000Base-T Base-T RJ-45 ports and 1 x 100Base-LX, 1310nm single mode port with duplex ST connector [20 km/ 12.4 miles]. -10 to 60C operating temperature.	https://www.perle.com/products/switches/ids-205f-industrial-managed-ethernet-switch.shtml	Industrial Switch: IDS-205F
07012090	IDS-205F-CSD40 Industrial Managed Switch, 5 ports: 4 x 10/100/1000Base-T Base-T RJ-45 ports and 1 x 100Base-LX, 1310nm single mode port with duplex SC connector [40 km/ 24.9 miles]. -10 to 60C operating temperature.	https://www.perle.com/products/switches/ids-205f-industrial-managed-ethernet-switch.shtml	Industrial Switch: IDS-205F
07012100	IDS-205F-TSD40 Industrial Managed Switch, 5 ports: 4 x 10/100/1000Base-T Base-T RJ-45 ports and 1 x 100Base-LX, 1310nm single mode port with duplex ST connector [40 km/ 24.9 miles]. -10 to 60C operating temperature.	https://www.perle.com/products/switches/ids-205f-industrial-managed-ethernet-switch.shtml	Industrial Switch: IDS-205F
07012110	IDS-205F-CSD80 Industrial Managed Switch, 5 ports: 4 x 10/100/1000Base-T Base-T RJ-45 ports and 1 x 100Base-EX, 1550nm single mode port with duplex SC connector [80 km/ 49.7 miles]. -10 to 60C operating temperature.	https://www.perle.com/products/switches/ids-205f-industrial-managed-ethernet-switch.shtml	Industrial Switch: IDS-205F
07012120	IDS-205F-TSD80 Industrial Managed Switch, 5 ports: 4 x 10/100/1000Base-T Base-T RJ-45 ports and 1 x 100Base-EX, 1550nm single mode port with duplex ST connector [80 km/ 49.7 miles]. -10 to 60C operating temperature.	https://www.perle.com/products/switches/ids-205f-industrial-managed-ethernet-switch.shtml	Industrial Switch: IDS-205F

Part #	Description	Product Datasheet	Product Group
07012130	IDS-205F-CSD120 Industrial Managed Switch, 5 ports: 4 x 10/100/1000Base-T Base-T RJ-45 ports and 1 x 100Base-ZX, 1550nm single mode port with duplex SC connector [120 km/ 74.6 miles]. -10 to 60C operating temperature.	https://www.perle.com/products/switches/ids-205f-industrial-managed-ethernet-switch.shtml	Industrial Switch: IDS-205F
07012140	IDS-205F-TSD120 Industrial Managed Switch, 5 ports: 4 x 10/100/1000Base-T Base-T RJ-45 ports and 1 x 100Base-ZX, 1550nm single mode port with duplex ST connector [120 km/ 74.6 miles]. -10 to 60C operating temperature.	https://www.perle.com/products/switches/ids-205f-industrial-managed-ethernet-switch.shtml	Industrial Switch: IDS-205F
07012150	IDS-205F-CMS2U Industrial Managed Switch, 5 ports: 4 x 10/100/1000Base-T Base-T RJ-45 ports and 1 x 100Base-BX, 1310nm TX / 1550nm RX single strand multimode port with simplex (BIDI) SC connector [up to 5km/3.1 miles]. -10 to 60C operating temperature.	https://www.perle.com/products/switches/ids-205f-industrial-managed-ethernet-switch.shtml	Industrial Switch: IDS-205F
07012160	IDS-205F-CMS2D Industrial Managed Switch, 5 ports: 4 x 10/100/1000Base-T Base-T RJ-45 ports and 1 x 100Base-BX, 1550nm TX / 1310nm RX single strand multimode port with simplex (BIDI) SC connector [up to 5km/3.1 miles]. -10 to 60C operating temperature.	https://www.perle.com/products/switches/ids-205f-industrial-managed-ethernet-switch.shtml	Industrial Switch: IDS-205F
07012170	IDS-205F-TMS2U Industrial Managed Switch, 5 ports: 4 x 10/100/1000Base-T Base-T RJ-45 ports and 1 x 100Base-BX, 1310nm TX / 1550nm RX single strand multimode port with simplex (BIDI) ST connector [up to 5km/3.1 miles]. -10 to 60C operating temperature.	https://www.perle.com/products/switches/ids-205f-industrial-managed-ethernet-switch.shtml	Industrial Switch: IDS-205F
07012180	IDS-205F-TMS2D Industrial Managed Switch, 5 ports: 4 x 10/100/1000Base-T Base-T RJ-45 ports and 1 x 100Base-BX, 1550nm TX / 1310nm RX single strand multimode port with simplex (BIDI) ST connector [up to 5km/3.1 miles]. -10 to 60C operating temperature.	https://www.perle.com/products/switches/ids-205f-industrial-managed-ethernet-switch.shtml	Industrial Switch: IDS-205F
07012190	IDS-205F-CSS20U Industrial Managed Switch, 5 ports: 4 x 10/100/1000Base-T Base-T RJ-45 ports and 1 x 100Base-BX, 1310nm TX / 1550nm RX single strand single mode port with simplex (BIDI) SC connector [20km/12.4 miles]. -10 to 60C operating temperature.	https://www.perle.com/products/switches/ids-205f-industrial-managed-ethernet-switch.shtml	Industrial Switch: IDS-205F
07012200	IDS-205F-CSS20D Industrial Managed Switch, 5 ports: 4 x 10/100/1000Base-T Base-T RJ-45 ports and 1 x 100Base-BX, 1550nm TX / 1310nm RX single strand single mode port with simplex (BIDI) SC connector [20km/12.4 miles]. -10 to 60C operating temperature.	https://www.perle.com/products/switches/ids-205f-industrial-managed-ethernet-switch.shtml	Industrial Switch: IDS-205F

Part #	Description	Product Datasheet	Product Group
07012210	IDS-205F-TSS20U Industrial Managed Switch, 5 ports: 4 x 10/100/1000Base-T Base-T RJ-45 ports and 1 x 100Base-BX, 1310nm TX / 1550nm RX single strand single mode port with simplex (BIDI) ST connector [20km/12.4 miles]. -10 to 60C operating temperature.	https://www.perle.com/products/switches/ids-205f-industrial-managed-ethernet-switch.shtml	Industrial Switch: IDS-205F
07012220	IDS-205F-TSS20D Industrial Managed Switch, 5 ports: 4 x 10/100/1000Base-T Base-T RJ-45 ports and 1 x 100Base-BX, 1550nm TX / 1310nm RX single strand single mode port with simplex (BIDI) ST connector [20km/12.4 miles]. -10 to 60C operating temperature.	https://www.perle.com/products/switches/ids-205f-industrial-managed-ethernet-switch.shtml	Industrial Switch: IDS-205F
07012230	IDS-205F-CSS40U Industrial Managed Switch, 5 ports: 4 x 10/100/1000Base-T Base-T RJ-45 ports and 1 x 100Base-BX, 1310nm TX / 1550nm RX single strand single mode port with simplex (BIDI) SC connector [40km/24.9 miles]. -10 to 60C operating temperature	https://www.perle.com/products/switches/ids-205f-industrial-managed-ethernet-switch.shtml	Industrial Switch: IDS-205F
07012240	IDS-205F-CSS40D Industrial Managed Switch, 5 ports: 4 x 10/100/1000Base-T Base-T RJ-45 ports and 1 x 100Base-BX, 1550nm TX / 1310nm RX single strand single mode port with simplex (BIDI) SC connector [40km/24.9 miles]. -10 to 60C operating temperature.	https://www.perle.com/products/switches/ids-205f-industrial-managed-ethernet-switch.shtml	Industrial Switch: IDS-205F
07012250	IDS-205F-CMD2-XT Industrial Managed Switch, 5 ports: 4 x 10/100/1000Base-T Base-T RJ-45 ports and 1 x 100Base-FX, 1310nm multimode port with duplex SC connector [up to 5km/3.1 miles]. -40 to 75C Industrial extended operating temperature.	https://www.perle.com/products/switches/ids-205f-industrial-managed-ethernet-switch.shtml	Industrial Switch: IDS-205F
07012260	IDS-205F-TMD2-XT Industrial Managed Switch, 5 ports: 4 x 10/100/1000Base-T Base-T RJ-45 ports and 1 x 100Base-FX, 1310nm multimode port with duplex ST connector [up to 5km/3.1 miles]. -40 to 75C Industrial extended operating temperature.	https://www.perle.com/products/switches/ids-205f-industrial-managed-ethernet-switch.shtml	Industrial Switch: IDS-205F
07012270	IDS-205F-CSD20-XT Industrial Managed Switch, 5 ports: 4 x 10/100/1000Base-T Base-T RJ-45 ports and 1 x 100Base-LX, 1310nm single mode port with duplex SC connector [20 km/ 12.4 miles]. -40 to 75C Industrial extended operating temperature.	https://www.perle.com/products/switches/ids-205f-industrial-managed-ethernet-switch.shtml	Industrial Switch: IDS-205F
07012280	IDS-205F-TSD20-XT Industrial Managed Switch, 5 ports: 4 x 10/100/1000Base-T Base-T RJ-45 ports and 1 x 100Base-LX, 1310nm single mode port with duplex ST connector [20 km/ 12.4 miles]. -40 to 75C Industrial extended operating temperature.	https://www.perle.com/products/switches/ids-205f-industrial-managed-ethernet-switch.shtml	Industrial Switch: IDS-205F

Part #	Description	Product Datasheet	Product Group
07012290	IDS-205F-CSD40-XT Industrial Managed Switch, 5 ports: 4 x 10/100/1000Base-T Base-T RJ-45 ports and 1 x 100Base-LX, 1310nm single mode port with duplex SC connector [40 km/ 24.9 miles]. -40 to 75C Industrial extended operating temperature.	https://www.perle.com/products/switches/ids-205f-industrial-managed-ethernet-switch.shtml	Industrial Switch: IDS-205F
07012300	IDS-205F-TSD40-XT Industrial Managed Switch, 5 ports: 4 x 10/100/1000Base-T Base-T RJ-45 ports and 1 x 100Base-LX, 1310nm single mode port with duplex ST connector [40 km/ 24.9 miles]. -40 to 75C Industrial extended operating temperature.	https://www.perle.com/products/switches/ids-205f-industrial-managed-ethernet-switch.shtml	Industrial Switch: IDS-205F
07012310	IDS-205F-CSS20U-XT Industrial Managed Switch, 5 ports: 4 x 10/100/1000Base-T Base-T RJ-45 ports and 1 x 100Base-BX, 1310nm TX / 1550nm RX single strand single mode port with simplex (BIDI) SC connector [20km/12.4 miles]. -40 to 75C Industrial extended operating temperature.	https://www.perle.com/products/switches/ids-205f-industrial-managed-ethernet-switch.shtml	Industrial Switch: IDS-205F
07012320	IDS-205F-CSS20D-XT Industrial Managed Switch, 5 ports: 4 x 10/100/1000Base-T Base-T RJ-45 ports and 1 x 100Base-BX, 1550nm TX / 1310nm RX single strand single mode port with simplex (BIDI) SC connector [20km/12.4 miles]. -40 to 75C Industrial extended operating temperature.	https://www.perle.com/products/switches/ids-205f-industrial-managed-ethernet-switch.shtml	Industrial Switch: IDS-205F
07012330	IDS-305F-CMD2 Industrial Managed Switch, 5 ports: 4 x 10/100/1000Base-T Base-T RJ-45 ports and 1 x 100Base-FX, 1310nm multimode port with duplex SC connector [up to 5km/3.1 miles]. -10 to 60C operating temperature. PRO software feature set.	https://www.perle.com/products/switches/ids-305f-industrial-managed-ethernet-switch.shtml	Industrial Switch: IDS-305F
07012340	IDS-305F-TMD2 Industrial Managed Switch, 5 ports: 4 x 10/100/1000Base-T Base-T RJ-45 ports and 1 x 100Base-FX, 1310nm multimode port with duplex ST connector [up to 5km/3.1 miles]. -10 to 60C operating temperature. PRO software feature set.	https://www.perle.com/products/switches/ids-305f-industrial-managed-ethernet-switch.shtml	Industrial Switch: IDS-305F
07012350	IDS-305F-CSD20 Industrial Managed Switch, 5 ports: 4 x 10/100/1000Base-T Base-T RJ-45 ports and 1 x 100Base-LX, 1310nm single mode port with duplex SC connector [20 km/ 12.4 miles]. -10 to 60C operating temperature. PRO software feature set.	https://www.perle.com/products/switches/ids-305f-industrial-managed-ethernet-switch.shtml	Industrial Switch: IDS-305F
07012360	IDS-305F-TSD20 Industrial Managed Switch, 5 ports: 4 x 10/100/1000Base-T Base-T RJ-45 ports and 1 x 100Base-LX, 1310nm single mode port with duplex ST connector [20 km/ 12.4 miles]. -10 to 60C operating temperature. PRO software feature set.	https://www.perle.com/products/switches/ids-305f-industrial-managed-ethernet-switch.shtml	Industrial Switch: IDS-305F

Part #	Description	Product Datasheet	Product Group
07012370	IDS-305F-CSD40 Industrial Managed Switch, 5 ports: 4 x 10/100/1000Base-T Base-T RJ-45 ports and 1 x 100Base-LX, 1310nm single mode port with duplex SC connector [40 km/ 24.9 miles]. -10 to 60C operating temperature. PRO software feature set.	https://www.perle.com/products/switches/ids-305f-industrial-managed-ethernet-switch.shtml	Industrial Switch: IDS-305F
07012380	IDS-305F-TSD40 Industrial Managed Switch, 5 ports: 4 x 10/100/1000Base-T Base-T RJ-45 ports and 1 x 100Base-LX, 1310nm single mode port with duplex ST connector [40 km/ 24.9 miles]. -10 to 60C operating temperature. PRO software feature set.	https://www.perle.com/products/switches/ids-305f-industrial-managed-ethernet-switch.shtml	Industrial Switch: IDS-305F
07012390	IDS-305F-CSD80 Industrial Managed Switch, 5 ports: 4 x 10/100/1000Base-T Base-T RJ-45 ports and 1 x 100Base-EX, 1550nm single mode port with duplex SC connector [80 km/ 49.7 miles]. -10 to 60C operating temperature. PRO software feature set.	https://www.perle.com/products/switches/ids-305f-industrial-managed-ethernet-switch.shtml	Industrial Switch: IDS-305F
07012400	IDS-305F-TSD80 Industrial Managed Switch, 5 ports: 4 x 10/100/1000Base-T Base-T RJ-45 ports and 1 x 100Base-EX, 1550nm single mode port with duplex ST connector [80 km/ 49.7 miles]. -10 to 60C operating temperature. PRO software feature set.	https://www.perle.com/products/switches/ids-305f-industrial-managed-ethernet-switch.shtml	Industrial Switch: IDS-305F
07012410	IDS-305F-CSD120 Industrial Managed Switch, 5 ports: 4 x 10/100/1000Base-T Base-T RJ-45 ports and 1 x 100Base-ZX, 1550nm single mode port with duplex SC connector [120 km/ 74.6 miles]. -10 to 60C operating temperature. PRO software feature set.	https://www.perle.com/products/switches/ids-305f-industrial-managed-ethernet-switch.shtml	Industrial Switch: IDS-305F
07012420	IDS-305F-TSD120 Industrial Managed Switch, 5 ports: 4 x 10/100/1000Base-T Base-T RJ-45 ports and 1 x 100Base-ZX, 1550nm single mode port with duplex ST connector [120 km/ 74.6 miles]. -10 to 60C operating temperature. PRO software feature set.	https://www.perle.com/products/switches/ids-305f-industrial-managed-ethernet-switch.shtml	Industrial Switch: IDS-305F
07012430	IDS-305F-CMS2U Industrial Managed Switch, 5 ports: 4 x 10/100/1000Base-T Base-T RJ-45 ports and 1 x 100Base-BX, 1310nm TX / 1550nm RX single strand multimode port with simplex (BIDI) SC connector [up to 5km/3.1 miles]. -10 to 60C operating temperature. PRO software feature set.	https://www.perle.com/products/switches/ids-305f-industrial-managed-ethernet-switch.shtml	Industrial Switch: IDS-305F
07012440	IDS-305F-CMS2D Industrial Managed Switch, 5 ports: 4 x 10/100/1000Base-T Base-T RJ-45 ports and 1 x 100Base-BX, 1550nm TX / 1310nm RX single strand multimode port with simplex (BIDI) SC connector [up to 5km/3.1 miles]. -10 to 60C operating temperature. PRO software feature set.	https://www.perle.com/products/switches/ids-305f-industrial-managed-ethernet-switch.shtml	Industrial Switch: IDS-305F

Part #	Description	Product Datasheet	Product Group
07012450	IDS-305F-TMS2U Industrial Managed Switch, 5 ports: 4 x 10/100/1000Base-T Base-T RJ-45 ports and 1 x 100Base-BX, 1310nm TX / 1550nm RX single strand multimode port with simplex (BIDI) ST connector [up to 5km/3.1 miles]. -10 to 60C operating temperature. PRO software feature set.	https://www.perle.com/products/switches/ids-305f-industrial-managed-ethernet-switch.shtml	Industrial Switch: IDS-305F
07012460	IDS-305F-TMS2D Industrial Managed Switch, 5 ports: 4 x 10/100/1000Base-T Base-T RJ-45 ports and 1 x 100Base-BX, 1550nm TX / 1310nm RX single strand multimode port with simplex (BIDI) ST connector [up to 5km/3.1 miles]. -10 to 60C operating temperature. PRO software feature set.	https://www.perle.com/products/switches/ids-305f-industrial-managed-ethernet-switch.shtml	Industrial Switch: IDS-305F
07012470	IDS-305F-CSS20U Industrial Managed Switch, 5 ports: 4 x 10/100/1000Base-T Base-T RJ-45 ports and 1 x 100Base-BX, 1310nm TX / 1550nm RX single strand single mode port with simplex (BIDI) SC connector [20km/12.4 miles]. -10 to 60C operating temperature. PRO software feature set.	https://www.perle.com/products/switches/ids-305f-industrial-managed-ethernet-switch.shtml	Industrial Switch: IDS-305F
07012480	IDS-305F-CSS20D Industrial Managed Switch, 5 ports: 4 x 10/100/1000Base-T Base-T RJ-45 ports and 1 x 100Base-BX, 1550nm TX / 1310nm RX single strand single mode port with simplex (BIDI) SC connector [20km/12.4 miles]. -10 to 60C operating temperature. PRO software feature set.	https://www.perle.com/products/switches/ids-305f-industrial-managed-ethernet-switch.shtml	Industrial Switch: IDS-305F
07012490	IDS-305F-TSS20U Industrial Managed Switch, 5 ports: 4 x 10/100/1000Base-T Base-T RJ-45 ports and 1 x 100Base-BX, 1310nm TX / 1550nm RX single strand single mode port with simplex (BIDI) ST connector [20km/12.4 miles]. -10 to 60C operating temperature. PRO software feature set.	https://www.perle.com/products/switches/ids-305f-industrial-managed-ethernet-switch.shtml	Industrial Switch: IDS-305F
07012500	IDS-305F-TSS20D Industrial Managed Switch, 5 ports: 4 x 10/100/1000Base-T Base-T RJ-45 ports and 1 x 100Base-BX, 1550nm TX / 1310nm RX single strand single mode port with simplex (BIDI) ST connector [20km/12.4 miles]. -10 to 60C operating temperature. PRO software feature set.	https://www.perle.com/products/switches/ids-305f-industrial-managed-ethernet-switch.shtml	Industrial Switch: IDS-305F
07012510	IDS-305F-CSS40U Industrial Managed Switch, 5 ports: 4 x 10/100/1000Base-T Base-T RJ-45 ports and 1 x 100Base-BX, 1310nm TX / 1550nm RX single strand single mode port with simplex (BIDI) SC connector [40km/24.9 miles]. -10 to 60C operating temperature. PRO software feature set.	https://www.perle.com/products/switches/ids-305f-industrial-managed-ethernet-switch.shtml	Industrial Switch: IDS-305F

Part #	Description	Product Datasheet	Product Group
07012520	IDS-305F-CSS40D Industrial Managed Switch, 5 ports: 4 x 10/100/1000Base-T Base-T RJ-45 ports and 1 x 100Base-BX, 1550nm TX / 1310nm RX single strand single mode port with simplex (BIDI) SC connector [40km/24.9 miles]. -10 to 60C operating temperature. PRO software feature set.	https://www.perle.com/products/switches/ids-305f-industrial-managed-ethernet-switch.shtml	Industrial Switch: IDS-305F
07012530	IDS-305F-CMD2-XT Industrial Managed Switch, 5 ports: 4 x 10/100/1000Base-T Base-T RJ-45 ports and 1 x 100Base-FX, 1310nm multimode port with duplex SC connector [up to 5km/3.1 miles]. -40 to 75C Industrial extended operating temperature. PRO software feature set.	https://www.perle.com/products/switches/ids-305f-industrial-managed-ethernet-switch.shtml	Industrial Switch: IDS-305F
07012540	IDS-305F-TMD2-XT Industrial Managed Switch, 5 ports: 4 x 10/100/1000Base-T Base-T RJ-45 ports and 1 x 100Base-FX, 1310nm multimode port with duplex ST connector [up to 5km/3.1 miles]. -40 to 75C Industrial extended operating temperature. PRO software feature set.	https://www.perle.com/products/switches/ids-305f-industrial-managed-ethernet-switch.shtml	Industrial Switch: IDS-305F
07012550	IDS-305F-CSD20-XT Industrial Managed Switch, 5 ports: 4 x 10/100/1000Base-T Base-T RJ-45 ports and 1 x 100Base-LX, 1310nm single mode port with duplex SC connector [20 km/ 12.4 miles]. -40 to 75C Industrial extended operating temperature. PRO software feature set.	https://www.perle.com/products/switches/ids-305f-industrial-managed-ethernet-switch.shtml	Industrial Switch: IDS-305F
07012560	IDS-305F-TSD20-XT Industrial Managed Switch, 5 ports: 4 x 10/100/1000Base-T Base-T RJ-45 ports and 1 x 100Base-LX, 1310nm single mode port with duplex ST connector [20 km/ 12.4 miles]. -40 to 75C Industrial extended operating temperature. PRO software feature set.	https://www.perle.com/products/switches/ids-305f-industrial-managed-ethernet-switch.shtml	Industrial Switch: IDS-305F
07012570	IDS-305F-CSD40-XT Industrial Managed Switch, 5 ports: 4 x 10/100/1000Base-T Base-T RJ-45 ports and 1 x 100Base-LX, 1310nm single mode port with duplex SC connector [40 km/ 24.9 miles]. -40 to 75C Industrial extended operating temperature. PRO software feature set.	https://www.perle.com/products/switches/ids-305f-industrial-managed-ethernet-switch.shtml	Industrial Switch: IDS-305F
07012580	IDS-305F-TSD40-XT Industrial Managed Switch, 5 ports: 4 x 10/100/1000Base-T Base-T RJ-45 ports and 1 x 100Base-LX, 1310nm single mode port with duplex ST connector [40 km/ 24.9 miles]. -40 to 75C Industrial extended operating temperature. PRO software feature set.	https://www.perle.com/products/switches/ids-305f-industrial-managed-ethernet-switch.shtml	Industrial Switch: IDS-305F
07012590	IDS-305F-CSS20U-XT Industrial Managed Switch, 5 ports: 4 x 10/100/1000Base-T Base-T RJ-45 ports and 1 x 100Base-BX, 1310nm TX / 1550nm RX single strand single mode port with simplex (BIDI) SC connector [20km/12.4 miles]. -40 to 75C Industrial extended operating temperature. PRO software feature set.	https://www.perle.com/products/switches/ids-305f-industrial-managed-ethernet-switch.shtml	Industrial Switch: IDS-305F

Part #	Description	Product Datasheet	Product Group
07012600	IDS-305F-CSS20D-XT Industrial Managed Switch, 5 ports: 4 x 10/100/1000Base-T Base-T RJ-45 ports and 1 x 100Base-BX, 1550nm TX / 1310nm RX single strand single mode port with simplex (BIDI) SC connector [20km/12.4 miles]. -40 to 75C Industrial extended operating temperature. PRO software feature set.	https://www.perle.com/products/switches/ids-305f-industrial-managed-ethernet-switch.shtml	Industrial Switch: IDS-305F
07012610	IDS-205G-CMD05 Industrial Managed Switch, 5 ports: 4 x 10/100/1000Base-T Base-T RJ-45 ports and 1 x 1000Base-SX, 850nm multimode port with duplex SC connector [550m/1804 ft]. -10 to 60C operating temperature.	https://www.perle.com/products/switches/ids-205g-industrial-managed-gigabit-switch.shtml	Industrial Switch: IDS-205G
07012620	IDS-205G-TMD05 Industrial Managed Switch, 5 ports: 4 x 10/100/1000Base-T Base-T RJ-45 ports and 1 x 1000Base-SX, 850nm multimode port with duplex ST connector [550m/1804 ft]. -10 to 60C operating temperature.	https://www.perle.com/products/switches/ids-205g-industrial-managed-gigabit-switch.shtml	Industrial Switch: IDS-205G
07012630	IDS-205G-CMD2 Industrial Managed Switch, 5 ports: 4 x 10/100/1000Base-T Base-T RJ-45 ports and 1 x 1000Base-LX, 1310nm extended multimode port with duplex SC connector [2km/1.2 miles]. -10 to 60C operating temperature.	https://www.perle.com/products/switches/ids-205g-industrial-managed-gigabit-switch.shtml	Industrial Switch: IDS-205G
07012640	IDS-205G-TMD2 Industrial Managed Switch, 5 ports: 4 x 10/100/1000Base-T Base-T RJ-45 ports and 1 x 1000Base-LX, 1310nm extended multimode port with duplex ST connector [2km/1.2 miles]. -10 to 60C operating temperature.	https://www.perle.com/products/switches/ids-205g-industrial-managed-gigabit-switch.shtml	Industrial Switch: IDS-205G
07012650	IDS-205G-CSD10 Industrial Managed Switch, 5 ports: 4 x 10/100/1000Base-T Base-T RJ-45 ports and 1 x 1000Base-LX/LH, 1310nm single mode port with duplex SC connector [10 km/ 6.2 miles]. -10 to 60C operating temperature.	https://www.perle.com/products/switches/ids-205g-industrial-managed-gigabit-switch.shtml	Industrial Switch: IDS-205G
07012660	IDS-205G-TSD10 Industrial Managed Switch, 5 ports: 4 x 10/100/1000Base-T Base-T RJ-45 ports and 1 x 1000Base-LX/LH, 1310nm single mode port with duplex ST connector [10 km/ 6.2 miles]. -10 to 60C operating temperature.	https://www.perle.com/products/switches/ids-205g-industrial-managed-gigabit-switch.shtml	Industrial Switch: IDS-205G
07012670	IDS-205G-CSD40 Industrial Managed Switch, 5 ports: 4 x 10/100/1000Base-T Base-T RJ-45 ports and 1 x 1000Base-EX, 1310nm single mode port with duplex SC connector [40 km/ 24.9 miles]. -10 to 60C operating temperature.	https://www.perle.com/products/switches/ids-205g-industrial-managed-gigabit-switch.shtml	Industrial Switch: IDS-205G

Part #	Description	Product Datasheet	Product Group
07012680	IDS-205G-TSD40 Industrial Managed Switch, 5 ports: 4 x 10/100/1000Base-T Base-T RJ-45 ports and 1 x 1000Base-EX, 1310nm single mode port with duplex ST connector [40 km/ 24.9 miles]. -10 to 60C operating temperature.	https://www.perle.com/products/switches/ids-205g-industrial-managed-gigabit-switch.shtml	Industrial Switch: IDS-205G
07012690	IDS-205G-CSD70 Industrial Managed Switch, 5 ports: 4 x 10/100/1000Base-T Base-T RJ-45 ports and 1 x 1000Base-ZX, 1550nm single mode port with duplex SC connector [70 km/ 43.5 miles]. -10 to 60C operating temperature.	https://www.perle.com/products/switches/ids-205g-industrial-managed-gigabit-switch.shtml	Industrial Switch: IDS-205G
07012700	IDS-205G-TSD70 Industrial Managed Switch, 5 ports: 4 x 10/100/1000Base-T Base-T RJ-45 ports and 1 x 1000Base-ZX, 1550nm single mode port with duplex ST connector [70 km/ 43.5 miles]. -10 to 60C operating temperature.	https://www.perle.com/products/switches/ids-205g-industrial-managed-gigabit-switch.shtml	Industrial Switch: IDS-205G
07012710	IDS-205G-CSD120 Industrial Managed Switch, 5 ports: 4 x 10/100/1000Base-T Base-T RJ-45 ports and 1 x 1000Base-ZX, 1550nm single mode port with duplex SC connector [120 km/ 74.6 miles]. -10 to 60C operating temperature.	https://www.perle.com/products/switches/ids-205g-industrial-managed-gigabit-switch.shtml	Industrial Switch: IDS-205G
07012720	IDS-205G-TSD120 Industrial Managed Switch, 5 ports: 4 x 10/100/1000Base-T Base-T RJ-45 ports and 1 x 1000Base-ZX, 1550nm single mode port with duplex ST connector [120 km/ 74.6 miles]. -10 to 60C operating temperature.	https://www.perle.com/products/switches/ids-205g-industrial-managed-gigabit-switch.shtml	Industrial Switch: IDS-205G
07012730	IDS-205G-CSD160 Industrial Managed Switch, 5 ports: 4 x 10/100/1000Base-T Base-T RJ-45 ports and 1 x 1000Base-ZX, 1550nm single mode port with duplex SC connector [160 km/ 100 miles]. -10 to 60C operating temperature.	https://www.perle.com/products/switches/ids-205g-industrial-managed-gigabit-switch.shtml	Industrial Switch: IDS-205G
07012740	IDS-205G-TSD160 Industrial Managed Switch, 5 ports: 4 x 10/100/1000Base-T Base-T RJ-45 ports and 1 x 1000Base-ZX, 1550nm single mode port with duplex ST connector [160 km/ 100 miles]. -10 to 60C operating temperature.	https://www.perle.com/products/switches/ids-205g-industrial-managed-gigabit-switch.shtml	Industrial Switch: IDS-205G
07012750	IDS-205G-CMS05U Industrial Managed Switch, 5 ports: 4 x 10/100/1000Base-T Base-T RJ-45 ports and 1 x 1000BASE-BX 1310nm TX / 1550nm RX single strand fiber, multimode (SC) [500 m/1640 ft]. -10 to 60C operating temperature.	https://www.perle.com/products/switches/ids-205g-industrial-managed-gigabit-switch.shtml	Industrial Switch: IDS-205G

Part #	Description	Product Datasheet	Product Group
07012760	IDS-205G-CMS05D Industrial Managed Switch, 5 ports: 4 x 10/100/1000Base-T Base-T RJ-45 ports and 1 x 1000BASE-BX 1550nm TX / 1310nm RX single strand fiber, multimode (SC) [500 m/1640 ft] -10 to 60C operating temperature.	https://www.perle.com/products/switches/ids-205g-industrial-managed-gigabit-switch.shtml	Industrial Switch: IDS-205G
07012770	IDS-205G-CSS10U Industrial Managed Switch, 5 ports: 4 x 10/100/1000Base-T Base-T RJ-45 ports and 1 x 1000Base-BX, 1310nm TX / 1490nm RX single strand single mode port with simplex (BIDI) SC connector [10km/6.2 miles]. -10 to 60C operating temperature.	https://www.perle.com/products/switches/ids-205g-industrial-managed-gigabit-switch.shtml	Industrial Switch: IDS-205G
07012780	IDS-205G-CSS10D Industrial Managed Switch, 5 ports: 4 x 10/100/1000Base-T Base-T RJ-45 ports and 1 x 1000Base-BX, 1490nm TX / 1310nm RX single strand single mode port with simplex (BIDI) SC connector [10km/6.2 miles]. -10 to 60C operating temperature.	https://www.perle.com/products/switches/ids-205g-industrial-managed-gigabit-switch.shtml	Industrial Switch: IDS-205G
07012790	IDS-205G-CSS20U Industrial Managed Switch, 5 ports: 4 x 10/100/1000Base-T Base-T RJ-45 ports and 1 x 1000Base-BX, 1310nm TX / 1490nm RX single strand single mode port with simplex (BIDI) SC connector [20km/12.4 miles]. -10 to 60C operating temperature.	https://www.perle.com/products/switches/ids-205g-industrial-managed-gigabit-switch.shtml	Industrial Switch: IDS-205G
07012800	IDS-205G-CSS20D Industrial Managed Switch, 5 ports: 4 x 10/100/1000Base-T Base-T RJ-45 ports and 1 x 1000Base-BX, 1490nm TX / 1310nm RX single strand single mode port with simplex (BIDI) SC connector [20km/12.4 miles]. -10 to 60C operating temperature.	https://www.perle.com/products/switches/ids-205g-industrial-managed-gigabit-switch.shtml	Industrial Switch: IDS-205G
07012810	IDS-205G-CSS40U Industrial Managed Switch, 5 ports: 4 x 10/100/1000Base-T Base-T RJ-45 ports and 1 x 1000Base-BX, 1310nm TX / 1490nm RX single strand single mode port with simplex (BIDI) SC connector [40km/24.9 miles]. -10 to 60C operating temperature.	https://www.perle.com/products/switches/ids-205g-industrial-managed-gigabit-switch.shtml	Industrial Switch: IDS-205G
07012820	IDS-205G-CSS40D Industrial Managed Switch, 5 ports: 4 x 10/100/1000Base-T Base-T RJ-45 ports and 1 x 1000Base-BX, 1490nm TX / 1310nm RX single strand single mode port with simplex (BIDI) SC connector [40km/24.9 miles]. -10 to 60C operating temperature.	https://www.perle.com/products/switches/ids-205g-industrial-managed-gigabit-switch.shtml	Industrial Switch: IDS-205G
07012830	IDS-205G-CSS80U Industrial Managed Switch, 5 ports: 4 x 10/100/1000Base-T Base-T RJ-45 ports and 1 x 1000Base-BX, 1310nm TX / 1550nm RX single strand single mode port with simplex (BIDI) SC connector [80km/49.7 miles]. -10 to 60C operating temperature.	https://www.perle.com/products/switches/ids-205g-industrial-managed-gigabit-switch.shtml	Industrial Switch: IDS-205G

Part #	Description	Product Datasheet	Product Group
07012840	IDS-205G-CSS80D Industrial Managed Switch, 5 ports: 4 x 10/100/1000Base-T Base-T RJ-45 ports and 1 x 1000Base-BX, 1550nm TX / 1310nm RX single strand single mode port with simplex (BIDI) SC connector [80km/49.7miles]. -10 to 60C operating temperature.	https://www.perle.com/products/switches/ids-205g-industrial-managed-gigabit-switch.shtml	Industrial Switch: IDS-205G
07012850	IDS-205G-CSS120U Industrial Managed Switch, 5 ports: 4 x 10/100/1000Base-T Base-T RJ-45 ports and 1 x 1000Base-BX, 1310nm TX / 1550nm RX single strand single mode port with simplex (BIDI) SC connector [120km/74.6 miles]. -10 to 60C operating temperature.	https://www.perle.com/products/switches/ids-205g-industrial-managed-gigabit-switch.shtml	Industrial Switch: IDS-205G
07012860	IDS-205G-CSS120D Industrial Managed Switch, 5 ports: 4 x 10/100/1000Base-T Base-T RJ-45 ports and 1 x 1000Base-BX, 1550nm TX / 1310nm RX single strand single mode port with simplex (BIDI) SC connector [120km/74.6 miles]. -10 to 60C operating temperature.	https://www.perle.com/products/switches/ids-205g-industrial-managed-gigabit-switch.shtml	Industrial Switch: IDS-205G
07012870	IDS-205G-CMD05-XT Industrial Managed Switch, 5 ports: 4 x 10/100/1000Base-T Base-T RJ-45 ports and 1 x 1000Base-SX, 850nm multimode port with duplex SC connector [550m/1804 ft]. -40 to 75C Industrial extended operating temperature.	https://www.perle.com/products/switches/ids-205g-industrial-managed-gigabit-switch.shtml	Industrial Switch: IDS-205G
07012880	IDS-205G-TMD05-XT Industrial Managed Switch, 5 ports: 4 x 10/100/1000Base-T Base-T RJ-45 ports and 1 x 1000Base-SX, 850nm multimode port with duplex ST connector [550m/1804 ft]. -40 to 75C Industrial extended operating temperature.	https://www.perle.com/products/switches/ids-205g-industrial-managed-gigabit-switch.shtml	Industrial Switch: IDS-205G
07012890	IDS-205G-CSD10-XT Industrial Managed Switch, 5 ports: 4 x 10/100/1000Base-T Base-T RJ-45 ports and 1 x 1000Base-LX/LH, 1310nm single mode port with duplex SC connector [10 km/ 6.2 miles]. -40 to 75C Industrial extended operating temperature.	https://www.perle.com/products/switches/ids-205g-industrial-managed-gigabit-switch.shtml	Industrial Switch: IDS-205G
07012900	IDS-205G-TSD10-XT Industrial Managed Switch, 5 ports: 4 x 10/100/1000Base-T Base-T RJ-45 ports and 1 x 1000Base-LX/LH, 1310nm single mode port with duplex ST connector [10 km/ 6.2 miles]. -40 to 75C Industrial extended operating temperature.	https://www.perle.com/products/switches/ids-205g-industrial-managed-gigabit-switch.shtml	Industrial Switch: IDS-205G
07012910	IDS-205G-CSS10U-XT Industrial Managed Switch, 5 ports: 4 x 10/100/1000Base-T Base-T RJ-45 ports and 1 x 1000Base-BX, 1310nm TX / 1490nm RX single strand single mode port with simplex (BIDI) SC connector [10km/6.2 miles]. -40 to 75C industrial extended operating temperature.	https://www.perle.com/products/switches/ids-205g-industrial-managed-gigabit-switch.shtml	Industrial Switch: IDS-205G

Part #	Description	Product Datasheet	Product Group
07012920	IDS-205G-CSS10D-XT Industrial Managed Switch, 5 ports: 4 x 10/100/1000Base-T Base-T RJ-45 ports and 1 x 1000Base-BX, 1490nm TX / 1310nm RX single strand single mode port with simplex (BIDI) SC connector [10km/6.2 miles]. -40 to 75C industrial extended operating temperature.	https://www.perle.com/products/switches/ids-205g-industrial-managed-gigabit-switch.shtml	Industrial Switch: IDS-205G
07012930	IDS-305G-CMD05 Industrial Managed Switch, 5 ports: 4 x 10/100/1000Base-T Base-T RJ-45 ports and 1 x 1000Base-SX, 850nm multimode port with duplex SC connector [550m/1804 ft]. -10 to 60C operating temperature. PRO software feature set.	https://www.perle.com/products/switches/ids-305g-industrial-managed-gigabit-switch.shtml	Industrial Switch: IDS-305G
07012940	IDS-305G-TMD05 Industrial Managed Switch, 5 ports: 4 x 10/100/1000Base-T Base-T RJ-45 ports and 1 x 1000Base-SX, 850nm multimode port with duplex ST connector [550m/1804 ft]. -10 to 60C operating temperature. PRO software feature set.	https://www.perle.com/products/switches/ids-305g-industrial-managed-gigabit-switch.shtml	Industrial Switch: IDS-305G
07012950	IDS-305G-CMD2 Industrial Managed Switch, 5 ports: 4 x 10/100/1000Base-T Base-T RJ-45 ports and 1 x 1000Base-LX, 1310nm extended multimode port with duplex SC connector [2km/1.2 miles]. -10 to 60C operating temperature. PRO software feature set.	https://www.perle.com/products/switches/ids-305g-industrial-managed-gigabit-switch.shtml	Industrial Switch: IDS-305G
07012960	IDS-305G-TMD2 Industrial Managed Switch, 5 ports: 4 x 10/100/1000Base-T Base-T RJ-45 ports and 1 x 1000Base-LX, 1310nm extended multimode port with duplex ST connector [2km/1.2 miles]. -10 to 60C operating temperature. PRO software feature set.	https://www.perle.com/products/switches/ids-305g-industrial-managed-gigabit-switch.shtml	Industrial Switch: IDS-305G
07012970	IDS-305G-CSD10 Industrial Managed Switch, 5 ports: 4 x 10/100/1000Base-T Base-T RJ-45 ports and 1 x 1000Base-LX/LH, 1310nm single mode port with duplex SC connector [10 km/ 6.2 miles]. -10 to 60C operating temperature. PRO software feature set.	https://www.perle.com/products/switches/ids-305g-industrial-managed-gigabit-switch.shtml	Industrial Switch: IDS-305G
07012980	IDS-305G-TSD10 Industrial Managed Switch, 5 ports: 4 x 10/100/1000Base-T Base-T RJ-45 ports and 1 x 1000Base-LX/LH, 1310nm single mode port with duplex ST connector [10 km/ 6.2 miles]. -10 to 60C operating temperature. PRO software feature set.	https://www.perle.com/products/switches/ids-305g-industrial-managed-gigabit-switch.shtml	Industrial Switch: IDS-305G
07012990	IDS-305G-CSD40 Industrial Managed Switch, 5 ports: 4 x 10/100/1000Base-T Base-T RJ-45 ports and 1 x 1000Base-EX, 1310nm single mode port with duplex SC connector [40 km/ 24.9 miles]. -10 to 60C operating temperature. PRO software feature set.	https://www.perle.com/products/switches/ids-305g-industrial-managed-gigabit-switch.shtml	Industrial Switch: IDS-305G

Part #	Description	Product Datasheet	Product Group
07013000	IDS-305G-TSD40 Industrial Managed Switch, 5 ports: 4 x 10/100/1000Base-T Base-T RJ-45 ports and 1 x 1000Base-EX, 1310nm single mode port with duplex ST connector [40 km/ 24.9 miles]. -10 to 60C operating temperature. PRO software feature set.	https://www.perle.com/products/switches/ids-305g-industrial-managed-gigabit-switch.shtml	Industrial Switch: IDS-305G
07013010	IDS-305G-CSD70 Industrial Managed Switch, 5 ports: 4 x 10/100/1000Base-T Base-T RJ-45 ports and 1 x 1000Base-ZX, 1550nm single mode port with duplex SC connector [70 km/ 43.5 miles]. -10 to 60C operating temperature. PRO software feature set.	https://www.perle.com/products/switches/ids-305g-industrial-managed-gigabit-switch.shtml	Industrial Switch: IDS-305G
07013020	IDS-305G-TSD70 Industrial Managed Switch, 5 ports: 4 x 10/100/1000Base-T Base-T RJ-45 ports and 1 x 1000Base-ZX, 1550nm single mode port with duplex ST connector [70 km/ 43.5 miles]. -10 to 60C operating temperature. PRO software feature set.	https://www.perle.com/products/switches/ids-305g-industrial-managed-gigabit-switch.shtml	Industrial Switch: IDS-305G
07013030	IDS-305G-CSD120 Industrial Managed Switch, 5 ports: 4 x 10/100/1000Base-T Base-T RJ-45 ports and 1 x 1000Base-ZX, 1550nm single mode port with duplex SC connector [120 km/ 74.6 miles]. -10 to 60C operating temperature. PRO software feature set.	https://www.perle.com/products/switches/ids-305g-industrial-managed-gigabit-switch.shtml	Industrial Switch: IDS-305G
07013040	IDS-305G-TSD120 Industrial Managed Switch, 5 ports: 4 x 10/100/1000Base-T Base-T RJ-45 ports and 1 x 1000Base-ZX, 1550nm single mode port with duplex ST connector [120 km/ 74.6 miles]. -10 to 60C operating temperature. PRO software feature set.	https://www.perle.com/products/switches/ids-305g-industrial-managed-gigabit-switch.shtml	Industrial Switch: IDS-305G
07013050	IDS-305G-CSD160 Industrial Managed Switch, 5 ports: 4 x 10/100/1000Base-T Base-T RJ-45 ports and 1 x 1000Base-ZX, 1550nm single mode port with duplex SC connector [160 km/ 100 miles]. -10 to 60C operating temperature. PRO software feature set.	https://www.perle.com/products/switches/ids-305g-industrial-managed-gigabit-switch.shtml	Industrial Switch: IDS-305G
07013060	IDS-305G-TSD160 Industrial Managed Switch, 5 ports: 4 x 10/100/1000Base-T Base-T RJ-45 ports and 1 x 1000Base-ZX, 1550nm single mode port with duplex ST connector [160 km/ 100 miles]. -10 to 60C operating temperature. PRO software feature set.	https://www.perle.com/products/switches/ids-305g-industrial-managed-gigabit-switch.shtml	Industrial Switch: IDS-305G
07013070	IDS-305G-CMS05U Industrial Managed Switch, 5 ports: 4 x 10/100/1000Base-T Base-T RJ-45 ports and 1000BASE-BX 1310nm TX / 1550nm RX single strand fiber, multimode (SC) [500 m/1640 ft]. -10 to 60C operating temperature. PRO software feature set.	https://www.perle.com/products/switches/ids-305g-industrial-managed-gigabit-switch.shtml	Industrial Switch: IDS-305G

Part #	Description	Product Datasheet	Product Group
07013080	IDS-305G-CMS05D Industrial Managed Switch, 5 ports: 4 x 10/100/1000Base-T Base-T RJ-45 ports and 1000BASE-BX 1550nm TX / 1310nm RX single strand fiber, multimode (SC) [500 m/1640 ft] -10 to 60C operating temperature. PRO software feature set.	https://www.perle.com/products/switches/ids-305g-industrial-managed-gigabit-switch.shtml	Industrial Switch: IDS-305G
07013090	IDS-305G-CSS10U Industrial Managed Switch, 5 ports: 4 x 10/100/1000Base-T Base-T RJ-45 ports and 1 x 1000Base-BX, 1310nm TX / 1490nm RX single strand single mode port with simplex (BIDI) SC connector [10km/6.2 miles]. -10 to 60C operating temperature. PRO software feature set.	https://www.perle.com/products/switches/ids-305g-industrial-managed-gigabit-switch.shtml	Industrial Switch: IDS-305G
07013100	IDS-305G-CSS10D Industrial Managed Switch, 5 ports: 4 x 10/100/1000Base-T Base-T RJ-45 ports and 1 x 1000Base-BX, 1490nm TX / 1310nm RX single strand single mode port with simplex (BIDI) SC connector [10km/6.2 miles]. -10 to 60C operating temperature. PRO software feature set.	https://www.perle.com/products/switches/ids-305g-industrial-managed-gigabit-switch.shtml	Industrial Switch: IDS-305G
07013110	IDS-305G-CSS20U Industrial Managed Switch, 5 ports: 4 x 10/100/1000Base-T Base-T RJ-45 ports and 1 x 1000Base-BX, 1310nm TX / 1490nm RX single strand single mode port with simplex (BIDI) SC connector [20km/12.4 miles]. -10 to 60C operating temperature. PRO software feature set.	https://www.perle.com/products/switches/ids-305g-industrial-managed-gigabit-switch.shtml	Industrial Switch: IDS-305G
07013120	IDS-305G-CSS20D Industrial Managed Switch, 5 ports: 4 x 10/100/1000Base-T Base-T RJ-45 ports and 1 x 1000Base-BX, 1490nm TX / 1310nm RX single strand single mode port with simplex (BIDI) SC connector [20km/12.4 miles]. -10 to 60C operating temperature. PRO software feature set.	https://www.perle.com/products/switches/ids-305g-industrial-managed-gigabit-switch.shtml	Industrial Switch: IDS-305G
07013130	IDS-305G-CSS40U Industrial Managed Switch, 5 ports: 4 x 10/100/1000Base-T Base-T RJ-45 ports and 1 x 1000Base-BX, 1310nm TX / 1490nm RX single strand single mode port with simplex (BIDI) SC connector [40km/24.9 miles]. -10 to 60C operating temperature. PRO software feature set.	https://www.perle.com/products/switches/ids-305g-industrial-managed-gigabit-switch.shtml	Industrial Switch: IDS-305G
07013140	IDS-305G-CSS40D Industrial Managed Switch, 5 ports: 4 x 10/100/1000Base-T Base-T RJ-45 ports and 1 x 1000Base-BX, 1490nm TX / 1310nm RX single strand single mode port with simplex (BIDI) SC connector [40km/24.9 miles]. -10 to 60C operating temperature. PRO software feature set.	https://www.perle.com/products/switches/ids-305g-industrial-managed-gigabit-switch.shtml	Industrial Switch: IDS-305G

Part #	Description	Product Datasheet	Product Group
07013150	IDS-305G-CSS80U Industrial Managed Switch, 5 ports: 4 x 10/100/1000Base-T Base-T RJ-45 ports and 1 x 1000Base-BX, 1310nm TX / 1550nm RX single strand single mode port with simplex (BIDI) SC connector [80km/49.7 miles]. -10 to 60C operating temperature. PRO software feature set.	https://www.perle.com/products/switches/ids-305g-industrial-managed-gigabit-switch.shtml	Industrial Switch: IDS-305G
07013160	IDS-305G-CSS80D Industrial Managed Switch, 5 ports: 4 x 10/100/1000Base-T Base-T RJ-45 ports and 1 x 1000Base-BX, 1550nm TX / 1310nm RX single strand single mode port with simplex (BIDI) SC connector [80km/49.7miles]. -10 to 60C operating temperature. PRO software feature set.	https://www.perle.com/products/switches/ids-305g-industrial-managed-gigabit-switch.shtml	Industrial Switch: IDS-305G
07013170	IDS-305G-CSS120U Industrial Managed Switch, 5 ports: 4 x 10/100/1000Base-T Base-T RJ-45 ports and 1 x 1000Base-BX, 1310nm TX / 1550nm RX single strand single mode port with simplex (BIDI) SC connector [120km/74.6 miles]. -10 to 60C operating temperature. PRO software feature set.	https://www.perle.com/products/switches/ids-305g-industrial-managed-gigabit-switch.shtml	Industrial Switch: IDS-305G
07013180	IDS-305G-CSS120D Industrial Managed Switch, 5 ports: 4 x 10/100/1000Base-T Base-T RJ-45 ports and 1 x 1000Base-BX, 1550nm TX / 1310nm RX single strand single mode port with simplex (BIDI) SC connector [120km/74.6 miles]. -10 to 60C operating temperature. PRO software feature set.	https://www.perle.com/products/switches/ids-305g-industrial-managed-gigabit-switch.shtml	Industrial Switch: IDS-305G
07013190	IDS-305G-CMD05-XT Industrial Managed Switch, 5 ports: 4 x 10/100/1000Base-T Base-T RJ-45 ports and 1 x 1000Base-SX, 850nm multimode port with duplex SC connector [550m/1804 ft]. -40 to 75C Industrial extended operating temperature. PRO software feature set.	https://www.perle.com/products/switches/ids-305g-industrial-managed-gigabit-switch.shtml	Industrial Switch: IDS-305G
07013200	IDS-305G-TMD05-XT Industrial Managed Switch, 5 ports: 4 x 10/100/1000Base-T Base-T RJ-45 ports and 1 x 1000Base-SX, 850nm multimode port with duplex ST connector [550m/1804 ft]. -40 to 75C Industrial extended operating temperature. PRO software feature set.	https://www.perle.com/products/switches/ids-305g-industrial-managed-gigabit-switch.shtml	Industrial Switch: IDS-305G
07013210	IDS-305G-CSD10-XT Industrial Managed Switch, 5 ports: 4 x 10/100/1000Base-T Base-T RJ-45 ports and 1 x 1000Base-LX/LH, 1310nm single mode port with duplex SC connector [10 km/ 6.2 miles]. -40 to 75C Industrial extended operating temperature. PRO software feature set.	https://www.perle.com/products/switches/ids-305g-industrial-managed-gigabit-switch.shtml	Industrial Switch: IDS-305G

Part #	Description	Product Datasheet	Product Group
07013220	IDS-305G-TSD10-XT Industrial Managed Switch, 5 ports: 4 x 10/100/1000Base-T Base-T RJ-45 ports and 1 x 1000Base-LX/LH, 1310nm single mode port with duplex ST connector [10 km/ 6.2 miles]. -40 to 75C Industrial extended operating temperature. PRO software feature set.	https://www.perle.com/products/switches/ids-305g-industrial-managed-gigabit-switch.shtml	Industrial Switch: IDS-305G
07013230	IDS-305G-CSS10U-XT Industrial Managed Switch, 5 ports: 4 x 10/100/1000Base-T Base-T RJ-45 ports and 1 x 1000Base-BX, 1310nm TX / 1490nm RX single strand single mode port with simplex (BIDI) SC connector [10km/6.2 miles]. -40 to 75C industrial extended operating temperature. PRO software feature set.	https://www.perle.com/products/switches/ids-305g-industrial-managed-gigabit-switch.shtml	Industrial Switch: IDS-305G
07013240	IDS-305G-CSS10D-XT Industrial Managed Switch, 5 ports: 4 x 10/100/1000Base-T Base-T RJ-45 ports and 1 x 1000Base-BX, 1490nm TX / 1310nm RX single strand single mode port with simplex (BIDI) SC connector [10km/6.2 miles]. -40 to 75C industrial extended operating temperature. PRO software feature set.	https://www.perle.com/products/switches/ids-305g-industrial-managed-gigabit-switch.shtml	Industrial Switch: IDS-305G
07013250	IDS-205 Industrial Managed Switch: 5 x 10/100/1000Base-T Base-T RJ-45 ports. -10 to 60C operating temperature.	https://www.perle.com/products/switches/ids-205-industrial-managed-ethernet-switch.shtml	Industrial Switch: IDS-205
07013260	IDS-205-XT Industrial Managed Switch: 5 x 10/100/1000Base-T Base-T RJ-45 ports. -40 to 75C industrial extended operating temperature.	https://www.perle.com/products/switches/ids-205-industrial-managed-ethernet-switch.shtml	Industrial Switch: IDS-205
07013270	IDS-305 Industrial Managed Switch: 5 x 10/100/1000Base-T Base-T RJ-45 ports. -10 to 60C operating temperature. PRO software feature set.	https://www.perle.com/products/switches/ids-305-industrial-managed-ethernet-switch.shtml	Industrial Switch: IDS-305
07013280	IDS-305-XT Industrial Managed Switch: 5 x 10/100/1000Base-T Base-T RJ-45 ports. -40 to 75C industrial extended operating temperature. PRO software feature set.	https://www.perle.com/products/switches/ids-305-industrial-managed-ethernet-switch.shtml	Industrial Switch: IDS-305
07013290	IDS-206 Industrial Managed Switch, 6 ports: 5 x 10/100/1000Base-T Base-T RJ-45 ports and 1 x 100/1000Base-X SFP slot (empty). -10 to 60C operating temperature.	https://www.perle.com/products/switches/ids-206-industrial-managed-gigabit-switch.shtml	Industrial Switch: IDS-206
07013300	IDS-206-XT Industrial Managed Switch, 6 ports: 5 x 10/100/1000Base-T Base-T RJ-45 ports and 1 x 100/1000Base-X SFP slot (empty). -40 to 75C industrial extended operating temperature.	https://www.perle.com/products/switches/ids-206-industrial-managed-gigabit-switch.shtml	Industrial Switch: IDS-206
07013310	IDS-306 Industrial Managed Switch, 6 ports: 5 x 10/100/1000Base-T Base-T RJ-45 ports and 1 x 100/1000Base-X SFP slot (empty). -10 to 60C operating temperature. PRO software feature set.	https://www.perle.com/products/switches/ids-306-industrial-managed-gigabit-switch.shtml	Industrial Switch: IDS-306

Part #	Description	Product Datasheet	Product Group
07013320	IDS-306-XT Industrial Managed Switch, 6 ports: 5 x 10/100/1000Base-T Base-T RJ-45 ports and 1 x 100/1000Base-X SFP slot (empty). -40 to 75C industrial extended operating temperature. PRO software feature set.	https://www.perle.com/products/switches/ids-306-industrial-managed-gigabit-switch.shtml	Industrial Switch: IDS-306
07013330	IDS-409C Industrial Managed Switch, 9 ports: 5 x 10/100/1000Base-T Base-T RJ-45 ports and 4 x (100 Mbps and 1 Gbps) dual-purpose Combo ports (SFP or RJ45). -10 to 60C operating temperature.	https://www.perle.com/products/switches/ids-409c-industrial-managed-gigabit-switch.shtml	Industrial Switch: IDS-409C
07013340	IDS-409C-XT Industrial Managed Switch, 9 ports: 5 x 10/100/1000Base-T Base-T RJ-45 ports and 4 x (100 Mbps and 1 Gbps) dual-purpose Combo ports (SFP or RJ45). -40 to 75C Industrial extended operating temperature.	https://www.perle.com/products/switches/ids-409c-industrial-managed-gigabit-switch.shtml	Industrial Switch: IDS-409C
07013350	IDS-509C Industrial Managed Switch, 9 ports: 5 x 10/100/1000Base-T Base-T RJ-45 ports and 4 x (100 Mbps and 1 Gbps) dual-purpose Combo ports (SFP or RJ45). -10 to 60C operating temperature. PRO software feature set.	https://www.perle.com/products/switches/ids-509c-industrial-managed-gigabit-switch.shtml	Industrial Switch: IDS-509C
07013360	IDS-509C-XT Industrial Managed Switch, 9 ports: 5 x 10/100/1000Base-T Base-T RJ-45 ports and 4 x (100 Mbps and 1 Gbps) dual-purpose Combo ports (SFP or RJ45). -40 to 75C Industrial extended operating temperature. PRO software feature set.	https://www.perle.com/products/switches/ids-509c-industrial-managed-gigabit-switch.shtml	Industrial Switch: IDS-509C
07013370	IDS-409-3SFP Industrial Managed Switch, 9 ports: 6 x 10/100/1000Base-T Base-T RJ-45 ports and 3 x 100/1000BASE-X SFP slots (empty). -10 to 60C operating temperature.	https://www.perle.com/products/switches/ids-409-sfp-industrial-managed-gigabit-switch.shtml	Industrial Switch: IDS-409
07013380	IDS-409-3SFP-XT Industrial Managed Switch, 9 ports: 6 x 10/100/1000Base-T Base-T RJ-45 ports and 3 x 100/1000BASE-X SFP slots (empty). -40 to 75C Industrial extended operating temperature.	https://www.perle.com/products/switches/ids-409-sfp-industrial-managed-gigabit-switch.shtml	Industrial Switch: IDS-409
07013390	IDS-509-3SFP Industrial Managed Switch, 9 ports: 6 x 10/100/1000Base-T Base-T RJ-45 ports and 3 x 100/1000BASE-X SFP slots (empty). -10 to 60C operating temperature. PRO software feature set.	https://www.perle.com/products/switches/ids-509-sfp-industrial-managed-gigabit-switch.shtml	Industrial Switch: IDS-509
07013400	IDS-509-3SFP-XT Industrial Managed Switch, 9 ports: 6 x 10/100/1000Base-T Base-T RJ-45 ports and 3 x 100/1000BASE-X SFP slots (empty). -40 to 75C Industrial extended operating temperature. PRO software feature set.	https://www.perle.com/products/switches/ids-509-sfp-industrial-managed-gigabit-switch.shtml	Industrial Switch: IDS-509
07013410	IDS-409-2SFP Industrial Managed Switch, 9 ports: 7 x 10/100/1000Base-T Base-T RJ-45 ports and 2 x 100/1000BASE-X SFP slots (empty). -10 to 60C operating temperature.	https://www.perle.com/products/switches/ids-409-sfp-industrial-managed-gigabit-switch.shtml	Industrial Switch: IDS-409

Part #	Description	Product Datasheet	Product Group
07013420	IDS-409-2SFP-XT Industrial Managed Switch, 9 ports: 7 x 10/100/1000Base-T Base-T RJ-45 ports and 2 x 100/1000BASE-X SFP slots (empty). -40 to 75C Industrial extended operating temperature.	https://www.perle.com/products/switches/ids-409-sfp-industrial-managed-gigabit-switch.shtml	Industrial Switch: IDS-409
07013430	IDS-509-2SFP Industrial Managed Switch, 9 ports: 7 x 10/100/1000Base-T Base-T RJ-45 ports and 2 x 100/1000BASE-X SFP slots (empty). -10 to 60C operating temperature. PRO software feature set.	https://www.perle.com/products/switches/ids-509-sfp-industrial-managed-gigabit-switch.shtml	Industrial Switch: IDS-509
07013440	IDS-509-2SFP-XT Industrial Managed Switch, 9 ports: 7 x 10/100/1000Base-T Base-T RJ-45 ports and 2 x 100/1000BASE-X SFP slots (empty). -40 to 75C Industrial extended operating temperature. PRO software feature set.	https://www.perle.com/products/switches/ids-509-sfp-industrial-managed-gigabit-switch.shtml	Industrial Switch: IDS-509
07013450	IDS-409-1SFP Industrial Managed Switch, 9 ports: 8 x 10/100/1000Base-T Base-T RJ-45 ports and 1 x 100/1000BASE-X SFP slot (empty). -10 to 60C operating temperature.	https://www.perle.com/products/switches/ids-409-sfp-industrial-managed-gigabit-switch.shtml	Industrial Switch: IDS-409
07013460	IDS-409-1SFP-XT Industrial Managed Switch, 9 ports: 8 x 10/100/1000Base-T Base-T RJ-45 ports and 1 x 100/1000BASE-X SFP slot (empty). -40 to 75C Industrial extended operating temperature.	https://www.perle.com/products/switches/ids-409-sfp-industrial-managed-gigabit-switch.shtml	Industrial Switch: IDS-409
07013470	IDS-509-1SFP Industrial Managed Switch, 9 ports: 8 x 10/100/1000Base-T Base-T RJ-45 ports and 1 x 100/1000BASE-X SFP slot (empty). -10 to 60C operating temperature. PRO software feature set.	https://www.perle.com/products/switches/ids-509-sfp-industrial-managed-gigabit-switch.shtml	Industrial Switch: IDS-509
07013480	IDS-509-1SFP-XT Industrial Managed Switch, 9 ports: 8 x 10/100/1000Base-T Base-T RJ-45 ports and 1 x 100/1000BASE-X SFP slot (empty). -40 to 75C Industrial extended operating temperature. PRO software feature set.	https://www.perle.com/products/switches/ids-509-sfp-industrial-managed-gigabit-switch.shtml	Industrial Switch: IDS-509
07013490	IDS-409 Industrial Managed Switch: 9 x 10/100/1000Base-T Base-T RJ-45 ports. -10 to 60C operating temperature.	https://www.perle.com/products/switches/ids-409-industrial-managed-ethernet-switch.shtml	Industrial Switch: IDS-409
07013500	IDS-409-XT Industrial Managed Switch: 9 x 10/100/1000Base-T Base-T RJ-45 ports. -40 to 75C Industrial extended operating temperature.	https://www.perle.com/products/switches/ids-409-industrial-managed-ethernet-switch.shtml	Industrial Switch: IDS-409
07013510	IDS-509 Industrial Managed Switch: 9 x 10/100/1000Base-T Base-T RJ-45 ports. -10 to 60C operating temperature. PRO software feature set.	https://www.perle.com/products/switches/ids-509-industrial-managed-ethernet-switch.shtml	Industrial Switch: IDS-509
07013520	IDS-509-XT Industrial Managed Switch: 9 x 10/100/1000Base-T Base-T RJ-45 ports. -40 to 75C Industrial extended operating temperature. PRO software feature set.	https://www.perle.com/products/switches/ids-509-industrial-managed-ethernet-switch.shtml	Industrial Switch: IDS-509

Part #	Description	Product Datasheet	Product Group
07013530	IDS-409-5SFP Industrial Managed Switch, 9 ports: 4 x 10/100/1000Base-T Base-T RJ-45 ports and 5 x 100/1000BASE-X SFP slots (empty). -10 to 60C operating temperature.	https://www.perle.com/products/switches/ids-409-sfp-industrial-managed-gigabit-switch.shtml	Industrial Switch: IDS-409
07013540	IDS-409-5SFP-XT Industrial Managed Switch, 9 ports: 4 x 10/100/1000Base-T Base-T RJ-45 ports and 5 x 100/1000BASE-X SFP slots (empty). -40 to 75C Industrial extended operating temperature.	https://www.perle.com/products/switches/ids-409-sfp-industrial-managed-gigabit-switch.shtml	Industrial Switch: IDS-409
07013550	IDS-509-5SFP Industrial Managed Switch, 9 ports: 4 x 10/100/1000Base-T Base-T RJ-45 ports and 5 x 100/1000BASE-X SFP slots (empty). -10 to 60C operating temperature. PRO software feature set.	https://www.perle.com/products/switches/ids-509-sfp-industrial-managed-gigabit-switch.shtml	Industrial Switch: IDS-509
07013560	IDS-509-5SFP-XT Industrial Managed Switch, 9 ports: 4 x 10/100/1000Base-T Base-T RJ-45 ports and 5 x 100/1000BASE-X SFP slots (empty). -40 to 75C Industrial extended operating temperature. PRO software feature set.	https://www.perle.com/products/switches/ids-509-sfp-industrial-managed-gigabit-switch.shtml	Industrial Switch: IDS-509
07013570	IDS-409F3-C2MD2-SD20 Industrial Managed Switch, 9 ports: 6 x 10/100/1000Base-T Base-T RJ-45 ports and 2 x 100Base-FX, 1310nm multimode port with duplex SC connector [up to 5km/3.1 miles] and 1 x 100Base-LX, 1310nm single mode port with duplex SC connector [20 km/ 12.4 miles]. -10 to 60C operating temperature.	https://www.perle.com/products/switches/ids-409f-industrial-managed-ethernet-switch.shtml	Industrial Switch: IDS-409F
07013580	IDS-409F3-T2MD2-SD20 Industrial Managed Switch, 9 ports: 6 x 10/100/1000Base-T Base-T RJ-45 ports and 2 x 100Base-FX, 1310nm multimode port with duplex ST connector [up to 5km/3.1 miles] and 1 x 100Base-LX, 1310nm single mode port with duplex ST connector [20 km/ 12.4 miles]. -10 to 60C operating temperature.	https://www.perle.com/products/switches/ids-409f-industrial-managed-ethernet-switch.shtml	Industrial Switch: IDS-409F
07013590	IDS-409F3-C2MD2-SD40 Industrial Managed Switch, 9 ports: 6 x 10/100/1000Base-T Base-T RJ-45 ports and 2 x 100Base-FX, 1310nm multimode port with duplex SC connector [up to 5km/3.1 miles] and 1 x 100Base-LX, 1310nm single mode port with duplex SC connector [40 km/ 24.9 miles]. -10 to 60C operating temperature.	https://www.perle.com/products/switches/ids-409f-industrial-managed-ethernet-switch.shtml	Industrial Switch: IDS-409F
07013600	IDS-409F3-T2MD2-SD40 Industrial Managed Switch, 9 ports: 6 x 10/100/1000Base-T Base-T RJ-45 ports and 2 x 100Base-FX, 1310nm multimode port with duplex ST connector [up to 5km/3.1 miles] and 1 x 100Base-LX, 1310nm single mode port with duplex ST connector [40 km/ 24.9 miles]. -10 to 60C operating temperature.	https://www.perle.com/products/switches/ids-409f-industrial-managed-ethernet-switch.shtml	Industrial Switch: IDS-409F

Part #	Description	Product Datasheet	Product Group
07013610	IDS-409F3-C2MD2-SD80 Industrial Managed Switch, 9 ports: 6 x 10/100/1000Base-T Base-T RJ-45 ports and 2 x 100Base-FX, 1310nm multimode port with duplex SC connector [up to 5km/3.1 miles] and 1 x 100Base-EX, 1550nm single mode port with duplex SC connector [80 km/ 49.7 miles]. -10 to 60C operating temperature.	https://www.perle.com/products/switches/ids-409f-industrial-managed-ethernet-switch.shtml	Industrial Switch: IDS-409F
07013620	IDS-409F3-T2MD2-SD80 Industrial Managed Switch, 9 ports: 6 x 10/100/1000Base-T Base-T RJ-45 ports and 2 x 100Base-FX, 1310nm multimode port with duplex ST connector [up to 5km/3.1 miles] and 1 x 100Base-EX, 1550nm single mode port with duplex ST connector [80 km/ 49.7 miles]. -10 to 60C operating temperature.	https://www.perle.com/products/switches/ids-409f-industrial-managed-ethernet-switch.shtml	Industrial Switch: IDS-409F
07013630	IDS-409F3-C2MD2-SD120 Industrial Managed Switch, 9 ports: 6 x 10/100/1000Base-T Base-T RJ-45 ports and 2 x 100Base-FX, 1310nm multimode port with duplex SC connector [up to 5km/3.1 miles] and 1 x 100Base-ZX, 1550nm single mode port with duplex SC connector [120 km/ 74.6 miles]. -10 to 60C operating temperature.	https://www.perle.com/products/switches/ids-409f-industrial-managed-ethernet-switch.shtml	Industrial Switch: IDS-409F
07013640	IDS-409F3-T2MD2-SD120 Industrial Managed Switch, 9 ports: 6 x 10/100/1000Base-T Base-T RJ-45 ports and 2 x 100Base-FX, 1310nm multimode port with duplex ST connector [up to 5km/3.1 miles] and 1 x 100Base-ZX, 1550nm single mode port with duplex STconnector [120 km/ 74.6 miles]. -10 to 60C operating temperature.	https://www.perle.com/products/switches/ids-409f-industrial-managed-ethernet-switch.shtml	Industrial Switch: IDS-409F
07013650	IDS-409F3-C2SD20-MD2 Industrial Managed Switch, 9 ports: 6 x 10/100/1000Base-T Base-T RJ-45 ports and 2 x 100Base-LX, 1310nm single mode port with duplex SC connector [20 km/ 12.4 miles] and 1 x 100Base-FX, 1310nm multimode port with duplex SC connector [up to 5km/3.1 miles] and. -10 to 60C operating temperature.	https://www.perle.com/products/switches/ids-409f-industrial-managed-ethernet-switch.shtml	Industrial Switch: IDS-409F
07013660	IDS-409F3-T2SD20-MD2 Industrial Managed Switch, 9 ports: 6 x 10/100/1000Base-T Base-T RJ-45 ports and 2 x 100Base-LX, 1310nm single mode port with duplex ST connector [20 km/ 12.4 miles] and 1 x 100Base-FX, 1310nm multimode port with duplex ST connector [up to 5km/3.1 miles] and. -10 to 60C operating temperature.	https://www.perle.com/products/switches/ids-409f-industrial-managed-ethernet-switch.shtml	Industrial Switch: IDS-409F
07013670	IDS-409F3-C2SD20-SD40 Industrial Managed Switch, 9 ports: 6 x 10/100/1000Base-T Base-T RJ-45 ports and 2 x 100Base-LX, 1310nm single mode port with duplex SC connector [20 km/ 12.4 miles] and 1 x 100Base-LX, 1310nm single mode port with duplex SC connector [40 km/ 24.9 miles]. -10 to 60C operating temperature.	https://www.perle.com/products/switches/ids-409f-industrial-managed-ethernet-switch.shtml	Industrial Switch: IDS-409F

Part #	Description	Product Datasheet	Product Group
07013680	IDS-409F3-T2SD20-SD40 Industrial Managed Switch, 9 ports: 6 x 10/100/1000Base-T Base-T RJ-45 ports and 2 x 100Base-LX, 1310nm single mode port with duplex ST connector [20 km/ 12.4 miles] and 1 x 100Base-LX, 1310nm single mode port with duplex ST connector [40 km/ 24.9 miles]. -10 to 60C operating temperature.	https://www.perle.com/products/switches/ids-409f-industrial-managed-ethernet-switch.shtml	Industrial Switch: IDS-409F
07013690	IDS-409F3-C2SD20-SD80 Industrial Managed Switch, 9 ports: 6 x 10/100/1000Base-T Base-T RJ-45 ports and 2 x 100Base-LX, 1310nm single mode port with duplex SC connector [20 km/ 12.4 miles] and 1 x 100Base-EX, 1550nm single mode port with duplex SC connector [80 km/ 49.7 miles]. -10 to 60C operating temperature.	https://www.perle.com/products/switches/ids-409f-industrial-managed-ethernet-switch.shtml	Industrial Switch: IDS-409F
07013700	IDS-409F3-T2SD20-SD80 Industrial Managed Switch, 9 ports: 6 x 10/100/1000Base-T Base-T RJ-45 ports and 2 x 100Base-LX, 1310nm single mode port with duplex ST connector [20 km/ 12.4 miles] and 1 x 100Base-EX, 1550nm single mode port with duplex ST connector [80 km/ 49.7 miles]. -10 to 60C operating temperature.	https://www.perle.com/products/switches/ids-409f-industrial-managed-ethernet-switch.shtml	Industrial Switch: IDS-409F
07013710	IDS-409F3-C2SD20-SD120 Industrial Managed Switch, 9 ports: 6 x 10/100/1000Base-T Base-T RJ-45 ports and 2 x 100Base-LX, 1310nm single mode port with duplex SC connector [20 km/ 12.4 miles] and 1 x 100Base-ZX, 1550nm single mode port with duplex SC connector [120 km/ 74.6 miles]. -10 to 60C operating temperature.	https://www.perle.com/products/switches/ids-409f-industrial-managed-ethernet-switch.shtml	Industrial Switch: IDS-409F
07013720	IDS-409F3-T2SD20-SD120 Industrial Managed Switch, 9 ports: 6 x 10/100/1000Base-T Base-T RJ-45 ports and 2 x 100Base-LX, 1310nm single mode ports with duplex ST connector [20 km/ 12.4 miles] and 1 x 100Base-ZX, 1550nm single mode port with duplex ST connector [120 km/ 74.6 miles]. -10 to 60C operating temperature.	https://www.perle.com/products/switches/ids-409f-industrial-managed-ethernet-switch.shtml	Industrial Switch: IDS-409F
07013730	IDS-409F3-C2SD40-MD2 Industrial Managed Switch, 9 ports: 6 x 10/100/1000Base-T Base-T RJ-45 ports and 2 x 100Base-LX, 1310nm single mode port with duplex SC connector [40 km/ 24.9 miles] and 1 x 100Base-FX, 1310nm multimode port with duplex SC connector [up to 5km/3.1 miles]. -10 to 60C operating temperature.	https://www.perle.com/products/switches/ids-409f-industrial-managed-ethernet-switch.shtml	Industrial Switch: IDS-409F
07013740	IDS-409F3-T2SD40-MD2 Industrial Managed Switch, 9 ports: 6 x 10/100/1000Base-T Base-T RJ-45 ports and 2 x 100Base-LX, 1310nm single mode port with duplex ST connector [40 km/ 24.9 miles] and 1 x 100Base-FX, 1310nm multimode port with duplex ST connector [up to 5km/3.1 miles]. -10 to 60C operating temperature.	https://www.perle.com/products/switches/ids-409f-industrial-managed-ethernet-switch.shtml	Industrial Switch: IDS-409F

Part #	Description	Product Datasheet	Product Group
07013750	IDS-409F3-C2SD40-SD20 Industrial Managed Switch, 9 ports: 6 x 10/100/1000Base-T Base-T RJ-45 ports and 2 x 100Base-LX, 1310nm single mode port with duplex SC connector [40 km/ 24.9 miles] and 1 x 100Base-LX, 1310nm single mode port with duplex SC connector [20 km/ 12.4 miles]. -10 to 60C operating temperature.	https://www.perle.com/products/switches/ids-409f-industrial-managed-ethernet-switch.shtml	Industrial Switch: IDS-409F
07013760	IDS-409F3-T2SD40-SD20 Industrial Managed Switch, 9 ports: 6 x 10/100/1000Base-T Base-T RJ-45 ports and 2 x 100Base-LX, 1310nm single mode port with duplex ST connector [40 km/ 24.9 miles] and 1 x 100Base-LX, 1310nm single mode port with duplex ST connector [20 km/ 12.4 miles]. -10 to 60C operating temperature.	https://www.perle.com/products/switches/ids-409f-industrial-managed-ethernet-switch.shtml	Industrial Switch: IDS-409F
07013770	IDS-409F3-C2SD40-SD80 Industrial Managed Switch, 9 ports: 6 x 10/100/1000Base-T Base-T RJ-45 ports and 2 x 100Base-LX, 1310nm single mode port with duplex SC connector [40 km/ 24.9 miles] and 1 x 100Base-EX, 1550nm single mode port with duplex SC connector [80 km/ 49.7 miles]. -10 to 60C operating temperature.	https://www.perle.com/products/switches/ids-409f-industrial-managed-ethernet-switch.shtml	Industrial Switch: IDS-409F
07013780	IDS-409F3-T2SD40-SD80 Industrial Managed Switch, 9 ports: 6 x 10/100/1000Base-T Base-T RJ-45 ports and 2 x 100Base-LX, 1310nm single mode port with duplex ST connector [40 km/ 24.9 miles] and 1 x 100Base-EX, 1550nm single mode port with duplex ST connector [80 km/ 49.7 miles]. -10 to 60C operating temperature.	https://www.perle.com/products/switches/ids-409f-industrial-managed-ethernet-switch.shtml	Industrial Switch: IDS-409F
07013790	IDS-409F3-C2SD40-SD120 Industrial Managed Switch, 9 ports: 6 x 10/100/1000Base-T Base-T RJ-45 ports and 2 x 100Base-LX, 1310nm single mode port with duplex SC connector [40 km/ 24.9 miles] and 1 x 100Base-ZX, 1550nm single mode port with duplex SC connector [120 km/ 74.6 miles]. -10 to 60C operating temperature.	https://www.perle.com/products/switches/ids-409f-industrial-managed-ethernet-switch.shtml	Industrial Switch: IDS-409F
07013800	IDS-409F3-T2SD40-SD120 Industrial Managed Switch, 9 ports: 6 x 10/100/1000Base-T Base-T RJ-45 ports and 2 x 100Base-LX, 1310nm single mode port with duplex ST connector [40 km/ 24.9 miles] and 1 x 100Base-ZX, 1550nm single mode port with duplex ST connector [120 km/ 74.6 miles]. -10 to 60C operating temperature.	https://www.perle.com/products/switches/ids-409f-industrial-managed-ethernet-switch.shtml	Industrial Switch: IDS-409F
07013810	IDS-409F3-C2MD2-SD20-XT Industrial Managed Switch, 9 ports: 6 x 10/100/1000Base-T Base-T RJ-45 ports and 2 x 100Base-FX, 1310nm multimode port with duplex SC connector [up to 5km/3.1 miles] and 1 x 100Base-LX, 1310nm single mode port with duplex SC connector [20 km/ 12.4 miles]. -40 to 75C Industrial extended operating temperature.	https://www.perle.com/products/switches/ids-409f-industrial-managed-ethernet-switch.shtml	Industrial Switch: IDS-409F

Part #	Description	Product Datasheet	Product Group
07013820	IDS-409F3-T2MD2-SD20-XT Industrial Managed Switch, 9 ports: 6 x 10/100/1000Base-T Base-T RJ-45 ports and 2 x 100Base-FX, 1310nm multimode port with duplex ST connector [up to 5km/3.1 miles] and 1 x 100Base-LX, 1310nm single mode port with duplex ST connector [20 km/ 12.4 miles]. -40 to 75C Industrial extended operating temperature.	https://www.perle.com/products/switches/ids-409f-industrial-managed-ethernet-switch.shtml	Industrial Switch: IDS-409F
07013830	IDS-409F3-C2MD2-SD40-XT Industrial Managed Switch, 9 ports: 6 x 10/100/1000Base-T Base-T RJ-45 ports and 2 x 100Base-FX, 1310nm multimode port with duplex SC connector [up to 5km/3.1 miles] and 1 x 100Base-LX, 1310nm single mode port with duplex SC connector [40 km/ 24.9 miles]. -40 to 75C Industrial extended operating temperature.	https://www.perle.com/products/switches/ids-409f-industrial-managed-ethernet-switch.shtml	Industrial Switch: IDS-409F
07013840	IDS-409F3-T2MD2-SD40-XT Industrial Managed Switch, 9 ports: 6 x 10/100/1000Base-T Base-T RJ-45 ports and 2 x 100Base-FX, 1310nm multimode port with duplex ST connector [up to 5km/3.1 miles] and 1 x 100Base-LX, 1310nm single mode port with duplex ST connector [40 km/ 24.9 miles]. -40 to 75C Industrial extended operating temperature.	https://www.perle.com/products/switches/ids-409f-industrial-managed-ethernet-switch.shtml	Industrial Switch: IDS-409F
07013850	IDS-409F3-C2SD20-SD40-XT Industrial Managed Switch, 9 ports: 6 x 10/100/1000Base-T Base-T RJ-45 ports and 2 x 100Base-LX, 1310nm single mode port with duplex SC connector [20 km/ 12.4 miles] and 1 x 100Base-LX, 1310nm single mode port with duplex SC connector [40 km/ 24.9 miles]. -40 to 75C Industrial extended operating temperature.	https://www.perle.com/products/switches/ids-409f-industrial-managed-ethernet-switch.shtml	Industrial Switch: IDS-409F
07013860	IDS-409F3-T2SD20-SD40-XT Industrial Managed Switch, 9 ports: 6 x 10/100/1000Base-T Base-T RJ-45 ports and 2 x 100Base-LX, 1310nm single mode port with duplex ST connector [20 km/ 12.4 miles] and 1 x 100Base-LX, 1310nm single mode port with duplex ST connector [40 km/ 24.9 miles]. -40 to 75C Industrial extended operating temperature.	https://www.perle.com/products/switches/ids-409f-industrial-managed-ethernet-switch.shtml	Industrial Switch: IDS-409F
07013870	IDS-409F3-C2SD40-MD2-XT Industrial Managed Switch, 9 ports: 6 x 10/100/1000Base-T Base-T RJ-45 ports and 2 x 100Base-LX, 1310nm single mode port with duplex SC connector [40 km/ 24.9 miles] and 1 x 100Base-FX, 1310nm multimode port with duplex SC connector [up to 5km/3.1 miles]. -40 to 75C Industrial extended operating temperature.	https://www.perle.com/products/switches/ids-409f-industrial-managed-ethernet-switch.shtml	Industrial Switch: IDS-409F
07013880	IDS-409F3-T2SD40-MD2-XT Industrial Managed Switch, 9 ports: 6 x 10/100/1000Base-T Base-T RJ-45 ports and 2 x 100Base-LX, 1310nm single mode port with duplex ST connector [40 km/ 24.9 miles] and 1 x 100Base-FX, 1310nm multimode port with duplex ST connector [up to 5km/3.1 miles]. -40 to 75C Industrial extended operating temperature.	https://www.perle.com/products/switches/ids-409f-industrial-managed-ethernet-switch.shtml	Industrial Switch: IDS-409F

Part #	Description	Product Datasheet	Product Group
07013890	IDS-409F3-C2SD40-SD20-XT Industrial Managed Switch, 9 ports: 6 x 10/100/1000Base-T Base-T RJ-45 ports and 2 x 100Base-LX, 1310nm single mode port with duplex SC connector [40 km/ 24.9 miles] and 1 x 100Base-LX, 1310nm single mode port with duplex SC connector [20 km/ 12.4 miles]. -40 to 75C Industrial extended operating temperature.	https://www.perle.com/products/switches/ids-409f-industrial-managed-ethernet-switch.shtml	Industrial Switch: IDS-409F
07013900	IDS-409F3-T2SD40-SD20-XT Industrial Managed Switch, 9 ports: 6 x 10/100/1000Base-T Base-T RJ-45 ports and 2 x 100Base-LX, 1310nm single mode port with duplex ST connector [40 km/ 24.9 miles] and 1 x 100Base-LX, 1310nm single mode port with duplex ST connector [20 km/ 12.4 miles]. -40 to 75C Industrial extended operating temperature.	https://www.perle.com/products/switches/ids-409f-industrial-managed-ethernet-switch.shtml	Industrial Switch: IDS-409F
07013910	IDS-509F3-C2MD2-SD20 Industrial Managed Switch, 9 ports: 6 x 10/100/1000Base-T Base-T RJ-45 ports and 2 x 100Base-FX, 1310nm multimode port with duplex SC connector [up to 5km/3.1 miles] and 1 x 100Base-LX, 1310nm single mode port with duplex SC connector [20 km/ 12.4 miles]. -10 to 60C operating temperature. PRO Software feature set.	https://www.perle.com/products/switches/ids-509f-industrial-managed-ethernet-switch.shtml	Industrial Switch: IDS-509F
07013920	IDS-509F3-T2MD2-SD20 Industrial Managed Switch, 9 ports: 6 x 10/100/1000Base-T Base-T RJ-45 ports and 2 x 100Base-FX, 1310nm multimode port with duplex ST connector [up to 5km/3.1 miles] and 1 x 100Base-LX, 1310nm single mode port with duplex ST connector [20 km/ 12.4 miles]. -10 to 60C operating temperature. PRO Software feature set.	https://www.perle.com/products/switches/ids-509f-industrial-managed-ethernet-switch.shtml	Industrial Switch: IDS-509F
07013930	IDS-509F3-C2MD2-SD40 Industrial Managed Switch, 9 ports: 6 x 10/100/1000Base-T Base-T RJ-45 ports and 2 x 100Base-FX, 1310nm multimode port with duplex SC connector [up to 5km/3.1 miles] and 1 x 100Base-LX, 1310nm single mode port with duplex SC connector [40 km/ 24.9 miles]. -10 to 60C operating temperature. PRO Software feature set.	https://www.perle.com/products/switches/ids-509f-industrial-managed-ethernet-switch.shtml	Industrial Switch: IDS-509F
07013940	IDS-509F3-T2MD2-SD40 Industrial Managed Switch, 9 ports: 6 x 10/100/1000Base-T Base-T RJ-45 ports and 2 x 100Base-FX, 1310nm multimode port with duplex ST connector [up to 5km/3.1 miles] and 1 x 100Base-LX, 1310nm single mode port with duplex ST connector [40 km/ 24.9 miles]. -10 to 60C operating temperature. PRO Software feature set.	https://www.perle.com/products/switches/ids-509f-industrial-managed-ethernet-switch.shtml	Industrial Switch: IDS-509F
07013950	IDS-509F3-C2MD2-SD80 Industrial Managed Switch, 9 ports: 6 x 10/100/1000Base-T Base-T RJ-45 ports and 2 x 100Base-FX, 1310nm multimode port with duplex SC connector [up to 5km/3.1 miles] and 1 x 100Base-EX, 1550nm single mode port with duplex SC connector [80 km/ 49.7 miles]. -10 to 60C operating temperature. PRO Software feature set.	https://www.perle.com/products/switches/ids-509f-industrial-managed-ethernet-switch.shtml	Industrial Switch: IDS-509F

Part #	Description	Product Datasheet	Product Group
07013960	IDS-509F3-T2MD2-SD80 Industrial Managed Switch, 9 ports: 6 x 10/100/1000Base-T Base-T RJ-45 ports and 2 x 100Base-FX, 1310nm multimode port with duplex ST connector [up to 5km/3.1 miles] and 1 x 100Base-EX, 1550nm single mode port with duplex ST connector [80 km/ 49.7 miles]. -10 to 60C operating temperature. PRO Software feature set.	https://www.perle.com/products/switches/ids-509f-industrial-managed-ethernet-switch.shtml	Industrial Switch: IDS-509F
07013970	IDS-509F3-C2MD2-SD120 Industrial Managed Switch, 9 ports: 6 x 10/100/1000Base-T Base-T RJ-45 ports and 2 x 100Base-FX, 1310nm multimode port with duplex SC connector [up to 5km/3.1 miles] and 1 x 100Base-ZX, 1550nm single mode port with duplex SC connector [120 km/ 74.6 miles]. -10 to 60C operating temperature. PRO Software feature set.	https://www.perle.com/products/switches/ids-509f-industrial-managed-ethernet-switch.shtml	Industrial Switch: IDS-509F
07013980	IDS-509F3-T2MD2-SD120 Industrial Managed Switch, 9 ports: 6 x 10/100/1000Base-T Base-T RJ-45 ports and 2 x 100Base-FX, 1310nm multimode port with duplex ST connector [up to 5km/3.1 miles] and 1 x 100Base-ZX, 1550nm single mode port with duplex ST connector [120 km/ 74.6 miles]. -10 to 60C operating temperature. PRO Software feature set.	https://www.perle.com/products/switches/ids-509f-industrial-managed-ethernet-switch.shtml	Industrial Switch: IDS-509F
07013990	IDS-509F3-C2SD20-MD2 Industrial Managed Switch, 9 ports: 6 x 10/100/1000Base-T Base-T RJ-45 ports and 2 x 100Base-LX, 1310nm single mode port with duplex SC connector [20 km/ 12.4 miles] and 1 x 100Base-FX, 1310nm multimode port with duplex SC connector [up to 5km/3.1 miles] and. -10 to 60C operating temperature. PRO Software feature set.	https://www.perle.com/products/switches/ids-509f-industrial-managed-ethernet-switch.shtml	Industrial Switch: IDS-509F
07014000	IDS-509F3-T2SD20-MD2 Industrial Managed Switch, 9 ports: 6 x 10/100/1000Base-T Base-T RJ-45 ports and 2 x 100Base-LX, 1310nm single mode port with duplex ST connector [20 km/ 12.4 miles] and 1 x 100Base-FX, 1310nm multimode port with duplex ST connector [up to 5km/3.1 miles] and. -10 to 60C operating temperature. PRO Software feature set.	https://www.perle.com/products/switches/ids-509f-industrial-managed-ethernet-switch.shtml	Industrial Switch: IDS-509F
07014010	IDS-509F3-C2SD20-SD40 Industrial Managed Switch, 9 ports: 6 x 10/100/1000Base-T Base-T RJ-45 ports and 2 x 100Base-LX, 1310nm single mode port with duplex SC connector [20 km/ 12.4 miles] and 1 x 100Base-LX, 1310nm single mode port with duplex SC connector [40 km/ 24.9 miles]. -10 to 60C operating temperature. PRO Software feature set.	https://www.perle.com/products/switches/ids-509f-industrial-managed-ethernet-switch.shtml	Industrial Switch: IDS-509F

Part #	Description	Product Datasheet	Product Group
07014020	IDS-509F3-T2SD20-SD40 Industrial Managed Switch, 9 ports: 6 x 10/100/1000Base-T Base-T RJ-45 ports and 2 x 100Base-LX, 1310nm single mode port with duplex ST connector [20 km/ 12.4 miles] and 1 x 100Base-LX, 1310nm single mode port with duplex ST connector [40 km/ 24.9 miles]. -10 to 60C operating temperature. PRO Software feature set.	https://www.perle.com/products/switches/ids-509f-industrial-managed-ethernet-switch.shtml	Industrial Switch: IDS-509F
07014030	IDS-509F3-C2SD20-SD80 Industrial Managed Switch, 9 ports: 6 x 10/100/1000Base-T Base-T RJ-45 ports and 2 x 100Base-LX, 1310nm single mode port with duplex SC connector [20 km/ 12.4 miles] and 1 x 100Base-EX, 1550nm single mode port with duplex SC connector [80 km/ 49.7 miles]. -10 to 60C operating temperature. PRO Software feature set.	https://www.perle.com/products/switches/ids-509f-industrial-managed-ethernet-switch.shtml	Industrial Switch: IDS-509F
07014040	IDS-509F3-T2SD20-SD80 Industrial Managed Switch, 9 ports: 6 x 10/100/1000Base-T Base-T RJ-45 ports and 2 x 100Base-LX, 1310nm single mode port with duplex ST connector [20 km/ 12.4 miles] and 1 x 100Base-EX, 1550nm single mode port with duplex ST connector [80 km/ 49.7 miles]. -10 to 60C operating temperature. PRO Software feature set.	https://www.perle.com/products/switches/ids-509f-industrial-managed-ethernet-switch.shtml	Industrial Switch: IDS-509F
07014050	IDS-509F3-C2SD20-SD120 Industrial Managed Switch, 9 ports: 6 x 10/100/1000Base-T Base-T RJ-45 ports and 2 x 100Base-LX, 1310nm single mode port with duplex SC connector [20 km/ 12.4 miles] and 1 x 100Base-ZX, 1550nm single mode port with duplex SC connector [120 km/ 74.6 miles]. -10 to 60C operating temperature. PRO Software feature set.	https://www.perle.com/products/switches/ids-509f-industrial-managed-ethernet-switch.shtml	Industrial Switch: IDS-509F
07014060	IDS-509F3-T2SD20-SD120 Industrial Managed Switch, 9 ports: 6 x 10/100/1000Base-T Base-T RJ-45 ports and 2 x 100Base-LX, 1310nm single mode ports with duplex ST connector [20 km/ 12.4 miles] and 1 x 100Base-ZX, 1550nm single mode port with duplex ST connector [120 km/ 74.6 miles]. -10 to 60C operating temperature. PRO Software feature set.	https://www.perle.com/products/switches/ids-509f-industrial-managed-ethernet-switch.shtml	Industrial Switch: IDS-509F
07014070	IDS-509F3-C2SD40-MD2 Industrial Managed Switch, 9 ports: 6 x 10/100/1000Base-T Base-T RJ-45 ports and 2 x 100Base-LX, 1310nm single mode port with duplex SC connector [40 km/ 24.9 miles] and 1 x 100Base-FX, 1310nm multimode port with duplex SC connector [up to 5km/3.1 miles]. -10 to 60C operating temperature. PRO Software feature set.	https://www.perle.com/products/switches/ids-509f-industrial-managed-ethernet-switch.shtml	Industrial Switch: IDS-509F

Part #	Description	Product Datasheet	Product Group
07014080	IDS-509F3-T2SD40-MD2 Industrial Managed Switch, 9 ports: 6 x 10/100/1000Base-T Base-T RJ-45 ports and 2 x 100Base-LX, 1310nm single mode port with duplex ST connector [40 km/ 24.9 miles] and 1 x 100Base-FX, 1310nm multimode port with duplex ST connector [up to 5km/3.1 miles]. -10 to 60C operating temperature. PRO Software feature set.	https://www.perle.com/products/switches/ids-509f-industrial-managed-ethernet-switch.shtml	Industrial Switch: IDS-509F
07014090	IDS-509F3-C2SD40-SD20 Industrial Managed Switch, 9 ports: 6 x 10/100/1000Base-T Base-T RJ-45 ports and 2 x 100Base-LX, 1310nm single mode port with duplex SC connector [40 km/ 24.9 miles] and 1 x 100Base-LX, 1310nm single mode port with duplex SC connector [20 km/ 12.4 miles]. -10 to 60C operating temperature. PRO Software feature set.	https://www.perle.com/products/switches/ids-509f-industrial-managed-ethernet-switch.shtml	Industrial Switch: IDS-509F
07014100	IDS-509F3-T2SD40-SD20 Industrial Managed Switch, 9 ports: 6 x 10/100/1000Base-T Base-T RJ-45 ports and 2 x 100Base-LX, 1310nm single mode port with duplex ST connector [40 km/ 24.9 miles] and 1 x 100Base-LX, 1310nm single mode port with duplex ST connector [20 km/ 12.4 miles]. -10 to 60C operating temperature. PRO Software feature set.	https://www.perle.com/products/switches/ids-509f-industrial-managed-ethernet-switch.shtml	Industrial Switch: IDS-509F
07014110	IDS-509F3-C2SD40-SD80 Industrial Managed Switch, 9 ports: 6 x 10/100/1000Base-T Base-T RJ-45 ports and 2 x 100Base-LX, 1310nm single mode port with duplex SC connector [40 km/ 24.9 miles] and 1 x 100Base-EX, 1550nm single mode port with duplex SC connector [80 km/ 49.7 miles]. -10 to 60C operating temperature. PRO Software feature set.	https://www.perle.com/products/switches/ids-509f-industrial-managed-ethernet-switch.shtml	Industrial Switch: IDS-509F
07014120	IDS-509F3-T2SD40-SD80 Industrial Managed Switch, 9 ports: 6 x 10/100/1000Base-T Base-T RJ-45 ports and 2 x 100Base-LX, 1310nm single mode port with duplex ST connector [40 km/ 24.9 miles] and 1 x 100Base-EX, 1550nm single mode port with duplex ST connector [80 km/ 49.7 miles]. -10 to 60C operating temperature. PRO Software feature set.	https://www.perle.com/products/switches/ids-509f-industrial-managed-ethernet-switch.shtml	Industrial Switch: IDS-509F
07014130	IDS-509F3-C2SD40-SD120 Industrial Managed Switch, 9 ports: 6 x 10/100/1000Base-T Base-T RJ-45 ports and 2 x 100Base-LX, 1310nm single mode port with duplex SC connector [40 km/ 24.9 miles] and 1 x 100Base-ZX, 1550nm single mode port with duplex SC connector [120 km/ 74.6 miles]. -10 to 60C operating temperature. PRO Software feature set.	https://www.perle.com/products/switches/ids-509f-industrial-managed-ethernet-switch.shtml	Industrial Switch: IDS-509F

Part #	Description	Product Datasheet	Product Group
07014140	IDS-509F3-T2SD40-SD120 Industrial Managed Switch, 9 ports: 6 x 10/100/1000Base-T Base-T RJ-45 ports and 2 x 100Base-LX, 1310nm single mode port with duplex ST connector [40 km/ 24.9 miles] and 1 x 100Base-ZX, 1550nm single mode port with duplex ST connector [120 km/ 74.6 miles]. -10 to 60C operating temperature. PRO Software feature set.	https://www.perle.com/products/switches/ids-509f-industrial-managed-ethernet-switch.shtml	Industrial Switch: IDS-509F
07014150	IDS-509F3-C2MD2-SD20-XT Industrial Managed Switch, 9 ports: 6 x 10/100/1000Base-T Base-T RJ-45 ports and 2 x 100Base-FX, 1310nm multimode port with duplex SC connector [up to 5km/3.1 miles] and 1 x 100Base-LX, 1310nm single mode port with duplex SC connector [20 km/ 12.4 miles]. -40 to 75C Industrial extended operating temperature. PRO Software feature set.	https://www.perle.com/products/switches/ids-509f-industrial-managed-ethernet-switch.shtml	Industrial Switch: IDS-509F
07014160	IDS-509F3-T2MD2-SD20-XT Industrial Managed Switch, 9 ports: 6 x 10/100/1000Base-T Base-T RJ-45 ports and 2 x 100Base-FX, 1310nm multimode port with duplex ST connector [up to 5km/3.1 miles] and 1 x 100Base-LX, 1310nm single mode port with duplex ST connector [20 km/ 12.4 miles]. -40 to 75C Industrial extended operating temperature. PRO Software feature set.	https://www.perle.com/products/switches/ids-509f-industrial-managed-ethernet-switch.shtml	Industrial Switch: IDS-509F
07014170	IDS-509F3-C2MD2-SD40-XT Industrial Managed Switch, 9 ports: 6 x 10/100/1000Base-T Base-T RJ-45 ports and 2 x 100Base-FX, 1310nm multimode port with duplex SC connector [up to 5km/3.1 miles] and 1 x 100Base-LX, 1310nm single mode port with duplex SC connector [40 km/ 24.9 miles]. -40 to 75C Industrial extended operating temperature. PRO Software feature set.	https://www.perle.com/products/switches/ids-509f-industrial-managed-ethernet-switch.shtml	Industrial Switch: IDS-509F
07014180	IDS-509F3-T2MD2-SD40-XT Industrial Managed Switch, 9 ports: 6 x 10/100/1000Base-T Base-T RJ-45 ports and 2 x 100Base-FX, 1310nm multimode port with duplex ST connector [up to 5km/3.1 miles] and 1 x 100Base-LX, 1310nm single mode port with duplex SC connector [40 km/ 24.9 miles]. -40 to 75C Industrial extended operating temperature. PRO Software feature set.	https://www.perle.com/products/switches/ids-509f-industrial-managed-ethernet-switch.shtml	Industrial Switch: IDS-509F

Part #	Description	Product Datasheet	Product Group
07014190	IDS-509F3-C2SD20-SD40-XT Industrial Managed Switch, 9 ports: 6 x 10/100/1000Base-T Base-T RJ-45 ports and 2 x 100Base-LX, 1310nm single mode port with duplex SC connector [20 km/ 12.4 miles] and 1 x 100Base-LX, 1310nm single mode port with duplex SC connector [40 km/ 24.9 miles]. -40 to 75C Industrial extended operating temperature. PRO Software feature set.	https://www.perle.com/products/switches/ids-509f-industrial-managed-ethernet-switch.shtml	Industrial Switch: IDS-509F
07014200	IDS-509F3-T2SD20-SD40-XT Industrial Managed Switch, 9 ports: 6 x 10/100/1000Base-T Base-T RJ-45 ports and 2 x 100Base-LX, 1310nm single mode port with duplex ST connector [20 km/ 12.4 miles] and 1 x 100Base-LX, 1310nm single mode port with duplex ST connector [40 km/ 24.9 miles]. -40 to 75C Industrial extended operating temperature. PRO Software feature set.	https://www.perle.com/products/switches/ids-509f-industrial-managed-ethernet-switch.shtml	Industrial Switch: IDS-509F
07014210	IDS-509F3-C2SD40-MD2-XT Industrial Managed Switch, 9 ports: 6 x 10/100/1000Base-T Base-T RJ-45 ports and 2 x 100Base-LX, 1310nm single mode port with duplex SC connector [40 km/ 24.9 miles] and 1 x 100Base-FX, 1310nm multimode port with duplex SC connector [up to 5km/3.1 miles]. -40 to 75C Industrial extended operating temperature. PRO Software feature set.	https://www.perle.com/products/switches/ids-509f-industrial-managed-ethernet-switch.shtml	Industrial Switch: IDS-509F
07014220	IDS-509F3-T2SD40-MD2-XT Industrial Managed Switch, 9 ports: 6 x 10/100/1000Base-T Base-T RJ-45 ports and 2 x 100Base-LX, 1310nm single mode port with duplex ST connector [40 km/ 24.9 miles] and 1 x 100Base-FX, 1310nm multimode port with duplex ST connector [up to 5km/3.1 miles]. -40 to 75C Industrial extended operating temperature. PRO Software feature set.	https://www.perle.com/products/switches/ids-509f-industrial-managed-ethernet-switch.shtml	Industrial Switch: IDS-509F
07014230	IDS-509F3-C2SD40-SD20-XT Industrial Managed Switch, 9 ports: 6 x 10/100/1000Base-T Base-T RJ-45 ports and 2 x 100Base-LX, 1310nm single mode port with duplex SC connector [40 km/ 24.9 miles] and 1 x 100Base-LX, 1310nm single mode port with duplex SC connector [20 km/ 12.4 miles]. -40 to 75C Industrial extended operating temperature. PRO Software feature set.	https://www.perle.com/products/switches/ids-509f-industrial-managed-ethernet-switch.shtml	Industrial Switch: IDS-509F

Part #	Description	Product Datasheet	Product Group
07014240	IDS-509F3-T2SD40-SD20-XT Industrial Managed Switch, 9 ports: 6 x 10/100/1000Base-T Base-T RJ-45 ports and 2 x 100Base-LX, 1310nm single mode port with duplex ST connector [40 km/ 24.9 miles] and 1 x 100Base-LX, 1310nm single mode port with duplex ST connector [20 km/ 12.4 miles]. -40 to 75C Industrial extended operating temperature. PRO Software feature set.	https://www.perle.com/products/switches/ids-509f-industrial-managed-ethernet-switch.shtml	Industrial Switch: IDS-509F
07014250	IDS-409G3-C2MD05-SD10 Industrial Managed Switch, 9 ports: 6 x 10/100/1000Base-T Base-T RJ-45 ports and 2 x 1000Base-SX, 850nm multimode port with duplex SC connector [550m/1804 ft] and 1 x 1000Base-LX/LH, 1310nm single mode port with duplex SC connector [10 km/ 6.2 miles]. -10 to 60C operating temperature.	https://www.perle.com/products/switches/ids-409g-industrial-managed-gigabit-switch.shtml	Industrial Switch: IDS-409G
07014260	IDS-409G3-T2MD05-SD10 Industrial Managed Switch, 9 ports: 6 x 10/100/1000Base-T Base-T RJ-45 ports and 2 x 1000Base-SX, 850nm multimode port with duplex ST connector [550m/1804 ft] and 1 x 1000Base-LX/LH, 1310nm single mode port with duplex ST connector [10 km/ 6.2 miles]. -10 to 60C operating temperature.	https://www.perle.com/products/switches/ids-409g-industrial-managed-gigabit-switch.shtml	Industrial Switch: IDS-409G
07014270	IDS-409G3-C2MD05-SD40 Industrial Managed Switch, 9 ports: 6 x 10/100/1000Base-T Base-T RJ-45 ports and 2 x 1000Base-SX, 850nm multimode port with duplex SC connector [550m/1804 ft] and 1 x 1000Base-EX, 1310nm single mode port with duplex SC connector [40 km/ 24.9 miles]. -10 to 60C operating temperature.	https://www.perle.com/products/switches/ids-409g-industrial-managed-gigabit-switch.shtml	Industrial Switch: IDS-409G
07014280	IDS-409G3-T2MD05-SD40 Industrial Managed Switch, 9 ports: 6 x 10/100/1000Base-T Base-T RJ-45 ports and 2 x 1000Base-SX, 850nm multimode port with duplex ST connector [550m/1804 ft] and 1 x 1000Base-EX, 1310nm single mode port with duplex ST connector [40 km/ 24.9 miles]. -10 to 60C operating temperature.	https://www.perle.com/products/switches/ids-409g-industrial-managed-gigabit-switch.shtml	Industrial Switch: IDS-409G
07014290	IDS-409G3-C2MD05-SD70 Industrial Managed Switch, 9 ports: 6 x 10/100/1000Base-T Base-T RJ-45 ports and 2 x 1000Base-SX, 850nm multimode port with duplex SC connector [550m/1804 ft] and 1 x 1000Base-ZX, 1550nm single mode port with duplex SC connector [70 km/ 43.5 miles]. -10 to 60C operating temperature.	https://www.perle.com/products/switches/ids-409g-industrial-managed-gigabit-switch.shtml	Industrial Switch: IDS-409G

Part #	Description	Product Datasheet	Product Group
07014300	IDS-409G3-T2MD05-SD70 Industrial Managed Switch, 9 ports: 6 x 10/100/1000Base-T Base-T RJ-45 ports and 2 x 1000Base-SX, 850nm multimode port with duplex ST connector [550m/1804 ft] and 1 x 1000Base-ZX, 1550nm single mode port with duplex ST connector [70 km/ 43.5 miles]. -10 to 60C operating temperature.	https://www.perle.com/products/switches/ids-409g-industrial-managed-gigabit-switch.shtml	Industrial Switch: IDS-409G
07014310	IDS-409G3-C2MD05-SD120 Industrial Managed Switch, 9 ports: 6 x 10/100/1000Base-T Base-T RJ-45 ports and 2 x 1000Base-SX, 850nm multimode port with duplex SC connector [550m/1804 ft] and 1 x 1000Base-ZX, 1550nm single mode port with duplex SC connector [120 km/ 74.6 miles]. -10 to 60C operating temperature.	https://www.perle.com/products/switches/ids-409g-industrial-managed-gigabit-switch.shtml	Industrial Switch: IDS-409G
07014320	IDS-409G3-T2MD05-SD120 Industrial Managed Switch, 9 ports: 6 x 10/100/1000Base-T Base-T RJ-45 ports and 2 x 1000Base-SX, 850nm multimode port with duplex ST connector [550m/1804 ft] and 1 x 1000Base-ZX, 1550nm single mode port with duplex ST connector [120 km/ 74.6 miles]. -10 to 60C operating temperature.	https://www.perle.com/products/switches/ids-409g-industrial-managed-gigabit-switch.shtml	Industrial Switch: IDS-409G
07014330	IDS-409G3-C2MD05-SD160 Industrial Managed Switch, 9 ports: 6 x 10/100/1000Base-T Base-T RJ-45 ports and 2 x 1000Base-SX, 850nm multimode port with duplex SC connector [550m/1804 ft] and 1 x 1000Base-ZX, 1550nm single mode port with duplex SC connector [160 km/ 100 miles]. -10 to 60C operating temperature.	https://www.perle.com/products/switches/ids-409g-industrial-managed-gigabit-switch.shtml	Industrial Switch: IDS-409G
07014340	IDS-409G3-T2MD05-SD160 Industrial Managed Switch, 9 ports: 6 x 10/100/1000Base-T Base-T RJ-45 ports and 2 x 1000Base-SX, 850nm multimode port with duplex ST connector [550m/1804 ft] and 1 x 1000Base-ZX, 1550nm single mode port with duplex ST connector [160 km/ 100 miles]. -10 to 60C operating temperature.	https://www.perle.com/products/switches/ids-409g-industrial-managed-gigabit-switch.shtml	Industrial Switch: IDS-409G
07014350	IDS-409G3-C2SD10-MD05 Industrial Managed Switch, 9 ports: 6 x 10/100/1000Base-T Base-T RJ-45 ports and 1 x 1000Base-SX, 850nm multimode port with duplex SC connector [550m/1804 ft] and 2 x 1000Base-LX/LH, 1310nm single mode port with duplex SC connector [10 km/ 6.2 miles]. -10 to 60C operating temperature.	https://www.perle.com/products/switches/ids-409g-industrial-managed-gigabit-switch.shtml	Industrial Switch: IDS-409G
07014360	IDS-409G3-T2SD10-MD05 Industrial Managed Switch, 9 ports: 6 x 10/100/1000Base-T Base-T RJ-45 ports and 1 x 1000Base-SX, 850nm multimode port with duplex ST connector [550m/1804 ft] and 2 x 1000Base-LX/LH, 1310nm single mode port with duplex ST connector [10 km/ 6.2 miles]. -10 to 60C operating temperature.	https://www.perle.com/products/switches/ids-409g-industrial-managed-gigabit-switch.shtml	Industrial Switch: IDS-409G

Part #	Description	Product Datasheet	Product Group
07014370	IDS-409G3-C2SD10-SD40 Industrial Managed Switch, 9 ports: 6 x 10/100/1000Base-T Base-T RJ-45 ports and 2 x 1000Base-LX/LH, 1310nm single mode port with duplex SC connector [10 km/ 6.2 miles] and 1 x 1000Base-EX, 1310nm single mode port with duplex SC connector [40 km/ 24.9 miles]. -10 to 60C operating temperature.	https://www.perle.com/products/switches/ids-409g-industrial-managed-gigabit-switch.shtml	Industrial Switch: IDS-409G
07014380	IDS-409G3-T2SD10-SD40 Industrial Managed Switch, 9 ports: 6 x 10/100/1000Base-T Base-T RJ-45 ports and 2 x 1000Base-LX/LH, 1310nm single mode port with duplex ST connector [10 km/ 6.2 miles] and 1 x 1000Base-EX, 1310nm single mode port with duplex ST connector [40 km/ 24.9 miles]. -10 to 60C operating temperature.	https://www.perle.com/products/switches/ids-409g-industrial-managed-gigabit-switch.shtml	Industrial Switch: IDS-409G
07014390	IDS-409G3-C2SD10-SD70 Industrial Managed Switch, 9 ports: 6 x 10/100/1000Base-T Base-T RJ-45 ports and 2 x 1000Base-LX/LH, 1310nm single mode port with duplex SC connector [10 km/ 6.2 miles] and 1 x 1000Base-ZX, 1550nm single mode port with duplex SC connector [70 km/ 43.5 miles]. -10 to 60C operating temperature.	https://www.perle.com/products/switches/ids-409g-industrial-managed-gigabit-switch.shtml	Industrial Switch: IDS-409G
07014400	IDS-409G3-T2SD10-SD70 Industrial Managed Switch, 9 ports: 6 x 10/100/1000Base-T Base-T RJ-45 ports and 2 x 1000Base-LX/LH, 1310nm single mode port with duplex ST connector [10 km/ 6.2 miles] and 1 x 1000Base-ZX, 1550nm single mode port with duplex ST connector [70 km/ 43.5 miles]. -10 to 60C operating temperature.	https://www.perle.com/products/switches/ids-409g-industrial-managed-gigabit-switch.shtml	Industrial Switch: IDS-409G
07014410	IDS-409G3-C2SD10-SD120 Industrial Managed Switch, 9 ports: 6 x 10/100/1000Base-T Base-T RJ-45 ports and 2 x 1000Base-LX/LH, 1310nm single mode port with duplex SC connector [10 km/ 6.2 miles] and 1 x 1000Base-ZX, 1550nm single mode port with duplex SC connector [120 km/ 74.6 miles]. -10 to 60C operating temperature.	https://www.perle.com/products/switches/ids-409g-industrial-managed-gigabit-switch.shtml	Industrial Switch: IDS-409G
07014420	IDS-409G3-T2SD10-SD120 Industrial Managed Switch, 9 ports: 6 x 10/100/1000Base-T Base-T RJ-45 ports and 2 x 1000Base-LX/LH, 1310nm single mode port with duplex ST connector [10 km/ 6.2 miles] and 1 x 1000Base-ZX, 1550nm single mode port with duplex ST connector [120 km/ 74.6 miles]. -10 to 60C operating temperature.	https://www.perle.com/products/switches/ids-409g-industrial-managed-gigabit-switch.shtml	Industrial Switch: IDS-409G
07014430	IDS-409G3-C2SD10-SD160 Industrial Managed Switch, 9 ports: 6 x 10/100/1000Base-T Base-T RJ-45 ports and 2 x 1000Base-LX/LH, 1310nm single mode port with duplex SC connector [10 km/ 6.2 miles] and 1 x 1000Base-ZX, 1550nm single mode port with duplex SC connector [160 km/ 100 miles]. -10 to 60C operating temperature.	https://www.perle.com/products/switches/ids-409g-industrial-managed-gigabit-switch.shtml	Industrial Switch: IDS-409G

Part #	Description	Product Datasheet	Product Group
07014440	IDS-409G3-T2SD10-SD160 Industrial Managed Switch, 9 ports: 6 x 10/100/1000Base-T Base-T RJ-45 ports and 2 x 1000Base-LX/LH, 1310nm single mode port with duplex ST connector [10 km/ 6.2 miles] and 1 x 1000Base-ZX, 1550nm single mode port with duplex ST connector [160 km/ 100 miles]. -10 to 60C operating temperature.	https://www.perle.com/products/switches/ids-409g-industrial-managed-gigabit-switch.shtml	Industrial Switch: IDS-409G
07014450	IDS-409G3-C2MD05-SD10-XT Industrial Managed Switch, 9 ports: 6 x 10/100/1000Base-T Base-T RJ-45 ports and 2 x 1000Base-SX, 850nm multimode port with duplex SC connector [550m/1804 ft] and 1 x 1000Base-LX/LH, 1310nm single mode port with duplex SC connector [10 km/ 6.2 miles]. -40 to 75C Industrial extended operating temperature.	https://www.perle.com/products/switches/ids-409g-industrial-managed-gigabit-switch.shtml	Industrial Switch: IDS-409G
07014460	IDS-409G3-T2MD05-SD10-XT Industrial Managed Switch, 9 ports: 6 x 10/100/1000Base-T Base-T RJ-45 ports and 2 x 1000Base-SX, 850nm multimode port with duplex ST connector [550m/1804 ft] and 1 x 1000Base-LX/LH, 1310nm single mode port with duplex ST connector [10 km/ 6.2 miles]. -40 to 75C Industrial extended operating temperature.	https://www.perle.com/products/switches/ids-409g-industrial-managed-gigabit-switch.shtml	Industrial Switch: IDS-409G
07014470	IDS-409G3-C2SD10-MD05-XT Industrial Managed Switch, 9 ports: 6 x 10/100/1000Base-T Base-T RJ-45 ports and 1 x 1000Base-SX, 850nm multimode port with duplex SC connector [550m/1804 ft] and 2 x 1000Base-LX/LH, 1310nm single mode port with duplex SC connector [10 km/ 6.2 miles].-40 to 75C Industrial extended operating temperature.	https://www.perle.com/products/switches/ids-409g-industrial-managed-gigabit-switch.shtml	Industrial Switch: IDS-409G
07014480	IDS-409G3-T2SD10-MD05-XT Industrial Managed Switch, 9 ports: 6 x 10/100/1000Base-T Base-T RJ-45 ports and 1 x 1000Base-SX, 850nm multimode port with duplex ST connector [550m/1804 ft] and 2 x 1000Base-LX/LH, 1310nm single mode port with duplex ST connector [10 km/ 6.2 miles].-40 to 75C Industrial extended operating temperature.	https://www.perle.com/products/switches/ids-409g-industrial-managed-gigabit-switch.shtml	Industrial Switch: IDS-409G
07014490	IDS-509G3-C2MD05-SD10 Industrial Managed Switch, 9 ports: 6 x 10/100/1000Base-T Base-T RJ-45 ports and 2 x 1000Base-SX, 850nm multimode port with duplex SC connector [550m/1804 ft] and 1 x 1000Base-LX/LH, 1310nm single mode port with duplex SC connector [10 km/ 6.2 miles]. -10 to 60C operating temperature. PRO software feature set.	https://www.perle.com/products/switches/ids-509g-industrial-managed-gigabit-switch.shtml	Industrial Switch: IDS-509G

Part #	Description	Product Datasheet	Product Group
07014500	IDS-509G3-T2MD05-SD10 Industrial Managed Switch, 9 ports: 6 x 10/100/1000Base-T Base-T RJ-45 ports and 2 x 1000Base-SX, 850nm multimode port with duplex ST connector [550m/1804 ft] and 1 x 1000Base-LX/LH, 1310nm single mode port with duplex ST connector [10 km/ 6.2 miles]. -10 to 60C operating temperature. PRO software feature set.	https://www.perle.com/products/switches/ids-509g-industrial-managed-gigabit-switch.shtml	Industrial Switch: IDS-509G
07014510	IDS-509G3-C2MD05-SD40 Industrial Managed Switch, 9 ports: 6 x 10/100/1000Base-T Base-T RJ-45 ports and 2 x 1000Base-SX, 850nm multimode port with duplex SC connector [550m/1804 ft] and 1 x 1000Base-EX, 1310nm single mode port with duplex SC connector [40 km/ 24.9 miles]. -10 to 60C operating temperature. PRO software feature set.	https://www.perle.com/products/switches/ids-509g-industrial-managed-gigabit-switch.shtml	Industrial Switch: IDS-509G
07014520	IDS-509G3-T2MD05-SD40 Industrial Managed Switch, 9 ports: 6 x 10/100/1000Base-T Base-T RJ-45 ports and 2 x 1000Base-SX, 850nm multimode port with duplex ST connector [550m/1804 ft] and 1 x 1000Base-EX, 1310nm single mode port with duplex ST connector [40 km/ 24.9 miles]. -10 to 60C operating temperature. PRO software feature set.	https://www.perle.com/products/switches/ids-509g-industrial-managed-gigabit-switch.shtml	Industrial Switch: IDS-509G
07014530	IDS-509G3-C2MD05-SD70 Industrial Managed Switch, 9 ports: 6 x 10/100/1000Base-T Base-T RJ-45 ports and 2 x 1000Base-SX, 850nm multimode port with duplex SC connector [550m/1804 ft] and 1 x 1000Base-ZX, 1550nm single mode port with duplex SC connector [70 km/ 43.5 miles]. -10 to 60C operating temperature. PRO software feature set.	https://www.perle.com/products/switches/ids-509g-industrial-managed-gigabit-switch.shtml	Industrial Switch: IDS-509G
07014540	IDS-509G3-T2MD05-SD70 Industrial Managed Switch, 9 ports: 6 x 10/100/1000Base-T Base-T RJ-45 ports and 2 x 1000Base-SX, 850nm multimode port with duplex ST connector [550m/1804 ft] and 1 x 1000Base-ZX, 1550nm single mode port with duplex ST connector [70 km/ 43.5 miles]. -10 to 60C operating temperature. PRO software feature set.	https://www.perle.com/products/switches/ids-509g-industrial-managed-gigabit-switch.shtml	Industrial Switch: IDS-509G

Part #	Description	Product Datasheet	Product Group
07014550	IDS-509G3-C2MD05-SD120 Industrial Managed Switch, 9 ports: 6 x 10/100/1000Base-T Base-T RJ-45 ports and 2 x 1000Base-SX, 850nm multimode port with duplex SC connector [550m/1804 ft] and 1 x 1000Base-ZX, 1550nm single mode port with duplex SC connector [120 km/ 74.6 miles]. -10 to 60C operating temperature. PRO software feature set.	https://www.perle.com/products/switches/ids-509g-industrial-managed-gigabit-switch.shtml	Industrial Switch: IDS-509G
07014560	IDS-509G3-T2MD05-SD120 Industrial Managed Switch, 9 ports: 6 x 10/100/1000Base-T Base-T RJ-45 ports and 2 x 1000Base-SX, 850nm multimode port with duplex ST connector [550m/1804 ft] and 1 x 1000Base-ZX, 1550nm single mode port with duplex ST connector [120 km/ 74.6 miles]. -10 to 60C operating temperature. PRO software feature set.	https://www.perle.com/products/switches/ids-509g-industrial-managed-gigabit-switch.shtml	Industrial Switch: IDS-509G
07014570	IDS-509G3-C2MD05-SD160 Industrial Managed Switch, 9 ports: 6 x 10/100/1000Base-T Base-T RJ-45 ports and 2 x 1000Base-SX, 850nm multimode port with duplex SC connector [550m/1804 ft] and 1 x 1000Base-ZX, 1550nm single mode port with duplex SC connector [160 km/ 100 miles]. -10 to 60C operating temperature. PRO software feature set.	https://www.perle.com/products/switches/ids-509g-industrial-managed-gigabit-switch.shtml	Industrial Switch: IDS-509G
07014580	IDS-509G3-T2MD05-SD160 Industrial Managed Switch, 9 ports: 6 x 10/100/1000Base-T Base-T RJ-45 ports and 2 x 1000Base-SX, 850nm multimode port with duplex ST connector [550m/1804 ft] and 1 x 1000Base-ZX, 1550nm single mode port with duplex ST connector [160 km/ 100 miles]. -10 to 60C operating temperature. PRO software feature set.	https://www.perle.com/products/switches/ids-509g-industrial-managed-gigabit-switch.shtml	Industrial Switch: IDS-509G
07014590	IDS-509G3-C2SD10-MD05 Industrial Managed Switch, 9 ports: 6 x 10/100/1000Base-T Base-T RJ-45 ports and 1 x 1000Base-SX, 850nm multimode port with duplex SC connector [550m/1804 ft] and 2 x 1000Base-LX/LH, 1310nm single mode port with duplex SC connector [10 km/ 6.2 miles]. -10 to 60C operating temperature. PRO software feature set.	https://www.perle.com/products/switches/ids-509g-industrial-managed-gigabit-switch.shtml	Industrial Switch: IDS-509G

Part #	Description	Product Datasheet	Product Group
07014600	IDS-509G3-T2SD10-MD05 Industrial Managed Switch, 9 ports: 6 x 10/100/1000Base-T Base-T RJ-45 ports and 1 x 1000Base-SX, 850nm multimode port with duplex ST connector [550m/1804 ft] and 2 x 1000Base-LX/LH, 1310nm single mode port with duplex ST connector [10 km/ 6.2 miles]. -10 to 60C operating temperature. PRO software feature set.	https://www.perle.com/products/switches/ids-509g-industrial-managed-gigabit-switch.shtml	Industrial Switch: IDS-509G
07014610	IDS-509G3-C2SD10-SD40 Industrial Managed Switch, 9 ports: 6 x 10/100/1000Base-T Base-T RJ-45 ports and 2 x 1000Base-LX/LH, 1310nm single mode port with duplex SC connector [10 km/ 6.2 miles] and 1 x 1000Base-EX, 1310nm single mode port with duplex SC connector [40 km/ 24.9 miles]. -10 to 60C operating temperature. PRO software feature set.	https://www.perle.com/products/switches/ids-509g-industrial-managed-gigabit-switch.shtml	Industrial Switch: IDS-509G
07014620	IDS-509G3-T2SD10-SD40 Industrial Managed Switch, 9 ports: 6 x 10/100/1000Base-T Base-T RJ-45 ports and 2 x 1000Base-LX/LH, 1310nm single mode port with duplex ST connector [10 km/ 6.2 miles] and 1 x 1000Base-EX, 1310nm single mode port with duplex ST connector [40 km/ 24.9 miles]. -10 to 60C operating temperature. PRO software feature set.	https://www.perle.com/products/switches/ids-509g-industrial-managed-gigabit-switch.shtml	Industrial Switch: IDS-509G
07014630	IDS-509G3-C2SD10-SD70 Industrial Managed Switch, 9 ports: 6 x 10/100/1000Base-T Base-T RJ-45 ports and 2 x 1000Base-LX/LH, 1310nm single mode port with duplex SC connector [10 km/ 6.2 miles] and 1 x 1000Base-ZX, 1550nm single mode port with duplex SC connector [70 km/ 43.5 miles]. -10 to 60C operating temperature. PRO software feature set.	https://www.perle.com/products/switches/ids-509g-industrial-managed-gigabit-switch.shtml	Industrial Switch: IDS-509G
07014640	IDS-509G3-T2SD10-SD70 Industrial Managed Switch, 9 ports: 6 x 10/100/1000Base-T Base-T RJ-45 ports and 2 x 1000Base-LX/LH, 1310nm single mode port with duplex ST connector [10 km/ 6.2 miles] and 1 x 1000Base-ZX, 1550nm single mode port with duplex ST connector [70 km/ 43.5 miles]. -10 to 60C operating temperature. PRO software feature set.	https://www.perle.com/products/switches/ids-509g-industrial-managed-gigabit-switch.shtml	Industrial Switch: IDS-509G

Part #	Description	Product Datasheet	Product Group
07014650	IDS-509G3-C2SD10-SD120 Industrial Managed Switch, 9 ports: 6 x 10/100/1000Base-T Base-T RJ-45 ports and 2 x 1000Base-LX/LH, 1310nm single mode port with duplex SC connector [10 km/ 6.2 miles] and 1 x 1000Base-ZX, 1550nm single mode port with duplex SC connector [120 km/ 74.6 miles]. -10 to 60C operating temperature. PRO software feature set.	https://www.perle.com/products/switches/ids-509g-industrial-managed-gigabit-switch.shtml	Industrial Switch: IDS-509G
07014660	IDS-509G3-T2SD10-SD120 Industrial Managed Switch, 9 ports: 6 x 10/100/1000Base-T Base-T RJ-45 ports and 2 x 1000Base-LX/LH, 1310nm single mode port with duplex ST connector [10 km/ 6.2 miles] and 1 x 1000Base-ZX, 1550nm single mode port with duplex ST connector [120 km/ 74.6 miles]. -10 to 60C operating temperature. PRO software feature set.	https://www.perle.com/products/switches/ids-509g-industrial-managed-gigabit-switch.shtml	Industrial Switch: IDS-509G
07014670	IDS-509G3-C2SD10-SD160 Industrial Managed Switch, 9 ports: 6 x 10/100/1000Base-T Base-T RJ-45 ports and 2 x 1000Base-LX/LH, 1310nm single mode port with duplex SC connector [10 km/ 6.2 miles] and 1 x 1000Base-ZX, 1550nm single mode port with duplex SC connector [160 km/ 100 miles]. -10 to 60C operating temperature. PRO software feature set.	https://www.perle.com/products/switches/ids-509g-industrial-managed-gigabit-switch.shtml	Industrial Switch: IDS-509G
07014680	IDS-509G3-T2SD10-SD160 Industrial Managed Switch, 9 ports: 6 x 10/100/1000Base-T Base-T RJ-45 ports and 2 x 1000Base-LX/LH, 1310nm single mode port with duplex ST connector [10 km/ 6.2 miles] and 1 x 1000Base-ZX, 1550nm single mode port with duplex ST connector [160 km/ 100 miles]. -10 to 60C operating temperature. PRO software feature set.	https://www.perle.com/products/switches/ids-509g-industrial-managed-gigabit-switch.shtml	Industrial Switch: IDS-509G
07014690	IDS-509G3-C2MD05-SD10-XT Industrial Managed Switch, 9 ports: 6 x 10/100/1000Base-T Base-T RJ-45 ports and 2 x 1000Base-SX, 850nm multimode port with duplex SC connector [550m/1804 ft] and 1 x 1000Base-LX/LH, 1310nm single mode port with duplex SC connector [10 km/ 6.2 miles]. -40 to 75C Industrial extended operating temperature. PRO Software feature set.	https://www.perle.com/products/switches/ids-509g-industrial-managed-gigabit-switch.shtml	Industrial Switch: IDS-509G

Part #	Description	Product Datasheet	Product Group
07014700	IDS-509G3-T2MD05-SD10-XT Industrial Managed Switch, 9 ports: 6 x 10/100/1000Base-T Base-T RJ-45 ports and 2 x 1000Base-SX, 850nm multimode port with duplex ST connector [550m/1804 ft] and 1 x 1000Base-LX/LH, 1310nm single mode port with duplex ST connector [10 km/ 6.2 miles]. -40 to 75C Industrial extended operating temperature. PRO Software feature set.	https://www.perle.com/products/switches/ids-509g-industrial-managed-gigabit-switch.shtml	Industrial Switch: IDS-509G
07014710	IDS-509G3-C2SD10-MD05-XT Industrial Managed Switch, 9 ports: 6 x 10/100/1000Base-T Base-T RJ-45 ports and 1 x 1000Base-SX, 850nm multimode port with duplex SC connector [550m/1804 ft] and 2 x 1000Base-LX/LH, 1310nm single mode port with duplex SC connector [10 km/ 6.2 miles]. -40 to 75C Industrial extended operating temperature. PRO Software feature set.	https://www.perle.com/products/switches/ids-509g-industrial-managed-gigabit-switch.shtml	Industrial Switch: IDS-509G
07014720	IDS-509G3-T2SD10-MD05-XT Industrial Managed Switch, 9 ports: 6 x 10/100/1000Base-T Base-T RJ-45 ports and 1 x 1000Base-SX, 850nm multimode port with duplex ST connector [550m/1804 ft] and 2 x 1000Base-LX/LH, 1310nm single mode port with duplex ST connector [10 km/ 6.2 miles]. -40 to 75C Industrial extended operating temperature. PRO Software feature set.	https://www.perle.com/products/switches/ids-509g-industrial-managed-gigabit-switch.shtml	Industrial Switch: IDS-509G
07014730	IDS-409F2-C2MD2 Industrial Managed Switch, 9 ports: 7 x 10/100/1000Base-T Base-T RJ-45 ports and 2 x 100Base-FX, 1310nm multimode port with duplex SC connector [up to 5km/3.1 miles]. -10 to 60C operating temperature.	https://www.perle.com/products/switches/ids-409f-industrial-managed-ethernet-switch.shtml	Industrial Switch: IDS-409F
07014740	IDS-409F2-T2MD2 Industrial Managed Switch, 9 ports: 7 x 10/100/1000Base-T Base-T RJ-45 ports and 2 x 100Base-FX, 1310nm multimode port with duplex ST connector [up to 5km/3.1 miles]. -10 to 60C operating temperature.	https://www.perle.com/products/switches/ids-409f-industrial-managed-ethernet-switch.shtml	Industrial Switch: IDS-409F
07014750	IDS-409F2-C2SD20 Industrial Managed Switch, 9 ports: 7 x 10/100/1000Base-T Base-T RJ-45 ports and 2 x 100Base-LX, 1310nm single mode port with duplex SC connector [20 km/ 12.4 miles]. -10 to 60C operating temperature.	https://www.perle.com/products/switches/ids-409f-industrial-managed-ethernet-switch.shtml	Industrial Switch: IDS-409F
07014760	IDS-409F2-T2SD20 Industrial Managed Switch, 9 ports: 7 x 10/100/1000Base-T Base-T RJ-45 ports and 2 x 100Base-LX, 1310nm single mode port with duplex ST connector [20 km/ 12.4 miles]. -10 to 60C operating temperature.	https://www.perle.com/products/switches/ids-409f-industrial-managed-ethernet-switch.shtml	Industrial Switch: IDS-409F

Part #	Description	Product Datasheet	Product Group
07014770	IDS-409F2-C2SD40 Industrial Managed Switch, 9 ports: 7 x 10/100/1000Base-T Base-T RJ-45 ports and 2 x 100Base-LX, 1310nm single mode port with duplex SC connector [40 km/ 24.9 miles]. -10 to 60C operating temperature.	https://www.perle.com/products/switches/ids-409f-industrial-managed-ethernet-switch.shtml	Industrial Switch: IDS-409F
07014780	IDS-409F2-T2SD40 Industrial Managed Switch, 9 ports: 7 x 10/100/1000Base-T Base-T RJ-45 ports and 2 x 100Base-LX, 1310nm single mode port with duplex ST connector [40 km/ 24.9 miles]. -10 to 60C operating temperature.	https://www.perle.com/products/switches/ids-409f-industrial-managed-ethernet-switch.shtml	Industrial Switch: IDS-409F
07014790	IDS-409F2-C2MD2-XT Industrial Managed Switch, 9 ports: 7 x 10/100/1000Base-T Base-T RJ-45 ports and 2 x 100Base-FX, 1310nm multimode port with duplex SC connector [up to 5km/3.1 miles]. -40 to 75C Industrial extended operating temperature.	https://www.perle.com/products/switches/ids-409f-industrial-managed-ethernet-switch.shtml	Industrial Switch: IDS-409F
07014800	IDS-409F2-T2MD2-XT Industrial Managed Switch, 9 ports: 7 x 10/100/1000Base-T Base-T RJ-45 ports and 2 x 100Base-FX, 1310nm multimode port with duplex ST connector [up to 5km/3.1 miles]. -40 to 75C Industrial extended operating temperature.	https://www.perle.com/products/switches/ids-409f-industrial-managed-ethernet-switch.shtml	Industrial Switch: IDS-409F
07014810	IDS-409F2-C2SD20-XT Industrial Managed Switch, 9 ports: 7 x 10/100/1000Base-T Base-T RJ-45 ports and 2 x 100Base-LX, 1310nm single mode port with duplex SC connector [20 km/ 12.4 miles]. -40 to 75C Industrial extended operating temperature.	https://www.perle.com/products/switches/ids-409f-industrial-managed-ethernet-switch.shtml	Industrial Switch: IDS-409F
07014820	IDS-409F2-T2SD20-XT Industrial Managed Switch, 9 ports: 7 x 10/100/1000Base-T Base-T RJ-45 ports and 2 x 100Base-LX, 1310nm single mode port with duplex ST connector [20 km/ 12.4 miles]. -40 to 75C Industrial extended operating temperature.	https://www.perle.com/products/switches/ids-409f-industrial-managed-ethernet-switch.shtml	Industrial Switch: IDS-409F
07014830	IDS-409F2-C2SD40-XT Industrial Managed Switch, 9 ports: 7 x 10/100/1000Base-T Base-T RJ-45 ports and 2 x 100Base-LX, 1310nm single mode port with duplex SC connector [40 km/ 24.9 miles]. -40 to 75C Industrial extended operating temperature.	https://www.perle.com/products/switches/ids-409f-industrial-managed-ethernet-switch.shtml	Industrial Switch: IDS-409F
07014840	IDS-409F2-T2SD40-XT Industrial Managed Switch, 9 ports: 7 x 10/100/1000Base-T Base-T RJ-45 ports and 2 x 100Base-LX, 1310nm single mode port with duplex ST connector [40 km/ 24.9 miles]. -40 to 75C Industrial extended operating temperature.	https://www.perle.com/products/switches/ids-409f-industrial-managed-ethernet-switch.shtml	Industrial Switch: IDS-409F

Part #	Description	Product Datasheet	Product Group
07014850	IDS-509F2-C2MD2 Industrial Managed Switch, 9 ports: 7 x 10/100/1000Base-T Base-T RJ-45 ports and 2 x 100Base-FX, 1310nm multimode port with duplex SC connector [up to 5km/3.1 miles]. -10 to 60C operating temperature. PRO software feature set.	https://www.perle.com/products/switches/ids-509f-industrial-managed-ethernet-switch.shtml	Industrial Switch: IDS-509F
07014860	IDS-509F2-T2MD2 Industrial Managed Switch, 9 ports: 7 x 10/100/1000Base-T Base-T RJ-45 ports and 2 x 100Base-FX, 1310nm multimode port with duplex ST connector [up to 5km/3.1 miles]. -10 to 60C operating temperature. PRO software feature set.	https://www.perle.com/products/switches/ids-509f-industrial-managed-ethernet-switch.shtml	Industrial Switch: IDS-509F
07014870	IDS-509F2-C2SD20 Industrial Managed Switch, 9 ports: 7 x 10/100/1000Base-T Base-T RJ-45 ports and 2 x 100Base-LX, 1310nm single mode port with duplex SC connector [20 km/ 12.4 miles]. -10 to 60C operating temperature. PRO software feature set.	https://www.perle.com/products/switches/ids-509f-industrial-managed-ethernet-switch.shtml	Industrial Switch: IDS-509F
07014880	IDS-509F2-T2SD20 Industrial Managed Switch, 9 ports: 7 x 10/100/1000Base-T Base-T RJ-45 ports and 2 x 100Base-LX, 1310nm single mode port with duplex ST connector [20 km/ 12.4 miles]. -10 to 60C operating temperature. PRO software feature set.	https://www.perle.com/products/switches/ids-509f-industrial-managed-ethernet-switch.shtml	Industrial Switch: IDS-509F
07014890	IDS-509F2-C2SD40 Industrial Managed Switch, 9 ports: 7 x 10/100/1000Base-T Base-T RJ-45 ports and 2 x 100Base-LX, 1310nm single mode port with duplex SC connector [40 km/ 24.9 miles]. -10 to 60C operating temperature. PRO software feature set.	https://www.perle.com/products/switches/ids-509f-industrial-managed-ethernet-switch.shtml	Industrial Switch: IDS-509F
07014900	IDS-509F2-T2SD40 Industrial Managed Switch, 9 ports: 7 x 10/100/1000Base-T Base-T RJ-45 ports and 2 x 100Base-LX, 1310nm single mode port with duplex ST connector [40 km/ 24.9 miles]. -10 to 60C operating temperature. PRO software feature set.	https://www.perle.com/products/switches/ids-509f-industrial-managed-ethernet-switch.shtml	Industrial Switch: IDS-509F
07014910	IDS-509F2-C2MD2-XT Industrial Managed Switch, 9 ports: 7 x 10/100/1000Base-T Base-T RJ-45 ports and 2 x 100Base-FX, 1310nm multimode port with duplex SC connector [up to 5km/3.1 miles]. -40 to 75C Industrial extended operating temperature. PRO software feature set.	https://www.perle.com/products/switches/ids-509f-industrial-managed-ethernet-switch.shtml	Industrial Switch: IDS-509F
07014920	IDS-509F2-T2MD2-XT Industrial Managed Switch, 9 ports: 7 x 10/100/1000Base-T Base-T RJ-45 ports and 2 x 100Base-FX, 1310nm multimode port with duplex ST connector [up to 5km/3.1 miles]. -40 to 75C Industrial extended operating temperature. PRO software feature set.	https://www.perle.com/products/switches/ids-509f-industrial-managed-ethernet-switch.shtml	Industrial Switch: IDS-509F

Part #	Description	Product Datasheet	Product Group
07014930	IDS-509F2-C2SD20-XT Industrial Managed Switch, 9 ports: 7 x 10/100/1000Base-T Base-T RJ-45 ports and 2 x 100Base-LX, 1310nm single mode port with duplex SC connector [20 km/ 12.4 miles]. -40 to 75C Industrial extended operating temperature. PRO software feature set.	https://www.perle.com/products/switches/ids-509f-industrial-managed-ethernet-switch.shtml	Industrial Switch: IDS-509F
07014940	IDS-509F2-T2SD20-XT Industrial Managed Switch, 9 ports: 7 x 10/100/1000Base-T Base-T RJ-45 ports and 2 x 100Base-LX, 1310nm single mode port with duplex ST connector [20 km/ 12.4 miles]. -40 to 75C Industrial extended operating temperature. PRO software feature set.	https://www.perle.com/products/switches/ids-509f-industrial-managed-ethernet-switch.shtml	Industrial Switch: IDS-509F
07014950	IDS-509F2-C2SD40-XT Industrial Managed Switch, 9 ports: 7 x 10/100/1000Base-T Base-T RJ-45 ports and 2 x 100Base-LX, 1310nm single mode port with duplex SC connector [40 km/ 24.9 miles]. -40 to 75C Industrial extended operating temperature. PRO software feature set.	https://www.perle.com/products/switches/ids-509f-industrial-managed-ethernet-switch.shtml	Industrial Switch: IDS-509F
07014960	IDS-509F2-T2SD40-XT Industrial Managed Switch, 9 ports: 7 x 10/100/1000Base-T Base-T RJ-45 ports and 2 x 100Base-LX, 1310nm single mode port with duplex ST connector [40 km/ 24.9 miles]. -40 to 75C Industrial extended operating temperature. PRO software feature set.	https://www.perle.com/products/switches/ids-509f-industrial-managed-ethernet-switch.shtml	Industrial Switch: IDS-509F
07014970	IDS-409G2-C2MD05 Industrial Managed Switch, 9 ports: 7 x 10/100/1000Base-T Base-T RJ-45 ports and 2 x 1000Base-SX, 850nm multimode port with duplex SC connector [550m/1804 ft]. -10 to 60C operating temperature.	https://www.perle.com/products/switches/ids-409g-industrial-managed-gigabit-switch.shtml	Industrial Switch: IDS-409G
07014980	IDS-409G2-T2MD05 Industrial Managed Switch, 9 ports: 7 x 10/100/1000Base-T Base-T RJ-45 ports and 2 x 1000Base-SX, 850nm multimode port with duplex ST connector [550m/1804 ft]. -10 to 60C operating temperature.	https://www.perle.com/products/switches/ids-409g-industrial-managed-gigabit-switch.shtml	Industrial Switch: IDS-409G
07014990	IDS-409G2-C2MD2 Industrial Managed Switch, 9 ports: 7 x 10/100/1000Base-T Base-T RJ-45 ports and 2 x 1000Base-LX, 1310nm extended multimode port with duplex SC connector [2km/1.2 miles]. -10 to 60C operating temperature.	https://www.perle.com/products/switches/ids-409g-industrial-managed-gigabit-switch.shtml	Industrial Switch: IDS-409G
07015000	IDS-409G2-T2MD2 Industrial Managed Switch, 9 ports: 7 x 10/100/1000Base-T Base-T RJ-45 ports and 2 x 1000Base-LX, 1310nm extended multimode port with duplex ST connector [2km/1.2 miles]. -10 to 60C operating temperature.	https://www.perle.com/products/switches/ids-409g-industrial-managed-gigabit-switch.shtml	Industrial Switch: IDS-409G

Part #	Description	Product Datasheet	Product Group
07015010	IDS-409G2-C2SD10 Industrial Managed Switch, 9 ports: 7 x 10/100/1000Base-T Base-T RJ-45 ports and 2 x 1000Base-LX/LH, 1310nm single mode port with duplex SC connector [10 km/ 6.2 miles]. -10 to 60C operating temperature.	https://www.perle.com/products/switches/ids-409g-industrial-managed-gigabit-switch.shtml	Industrial Switch: IDS-409G
07015020	IDS-409G2-T2SD10 Industrial Managed Switch, 9 ports: 7 x 10/100/1000Base-T Base-T RJ-45 ports and 2 x 1000Base-LX/LH, 1310nm single mode port with duplex ST connector [10 km/ 6.2 miles]. -10 to 60C operating temperature.	https://www.perle.com/products/switches/ids-409g-industrial-managed-gigabit-switch.shtml	Industrial Switch: IDS-409G
07015030	IDS-409G2-C2MD05-XT Industrial Managed Switch, 9 ports: 7 x 10/100/1000Base-T Base-T RJ-45 ports and 2 x 1000Base-SX, 850nm multimode port with duplex SC connector [550m/1804 ft]. -40 to 75C Industrial extended operating temperature.	https://www.perle.com/products/switches/ids-409g-industrial-managed-gigabit-switch.shtml	Industrial Switch: IDS-409G
07015040	IDS-409G2-T2MD05-XT Industrial Managed Switch, 9 ports: 7 x 10/100/1000Base-T Base-T RJ-45 ports and 2 x 1000Base-SX, 850nm multimode port with duplex ST connector [550m/1804 ft]. -40 to 75C Industrial extended operating temperature.	https://www.perle.com/products/switches/ids-409g-industrial-managed-gigabit-switch.shtml	Industrial Switch: IDS-409G
07015050	IDS-409G2-C2SD10-XT Industrial Managed Switch, 9 ports: 7 x 10/100/1000Base-T Base-T RJ-45 ports and 2 x 1000Base-LX/LH, 1310nm single mode port with duplex SC connector [10 km/ 6.2 miles]. -40 to 75C Industrial extended operating temperature.	https://www.perle.com/products/switches/ids-409g-industrial-managed-gigabit-switch.shtml	Industrial Switch: IDS-409G
07015060	IDS-409G2-T2SD10-XT Industrial Managed Switch, 9 ports: 7 x 10/100/1000Base-T Base-T RJ-45 ports and 2 x 1000Base-LX/LH, 1310nm single mode port with duplex ST connector [10 km/ 6.2 miles]. -40 to 75C Industrial extended operating temperature.	https://www.perle.com/products/switches/ids-409g-industrial-managed-gigabit-switch.shtml	Industrial Switch: IDS-409G
07015070	IDS-509G2-C2MD05 Industrial Managed Switch, 9 ports: 7 x 10/100/1000Base-T Base-T RJ-45 ports and 2 x 1000Base-SX, 850nm multimode port with duplex SC connector [550m/1804 ft]. -10 to 60C operating temperature. PRO software feature set.	https://www.perle.com/products/switches/ids-509g-industrial-managed-gigabit-switch.shtml	Industrial Switch: IDS-509G
07015080	IDS-509G2-T2MD05 Industrial Managed Switch, 9 ports: 7 x 10/100/1000Base-T Base-T RJ-45 ports and 2 x 1000Base-SX, 850nm multimode port with duplex ST connector [550m/1804 ft]. -10 to 60C operating temperature. PRO software feature set.	https://www.perle.com/products/switches/ids-509g-industrial-managed-gigabit-switch.shtml	Industrial Switch: IDS-509G

Part #	Description	Product Datasheet	Product Group
07015090	IDS-509G2-C2MD2 Industrial Managed Switch, 9 ports: 7 x 10/100/1000Base-T Base-T RJ-45 ports and 2 x 1000Base-LX, 1310nm extended multimode port with duplex SC connector [2km/1.2 miles]. -10 to 60C operating temperature. PRO software feature set.	https://www.perle.com/products/switches/ids-509g-industrial-managed-gigabit-switch.shtml	Industrial Switch: IDS-509G
07015100	IDS-509G2-T2MD2 Industrial Managed Switch, 9 ports: 7 x 10/100/1000Base-T Base-T RJ-45 ports and 2 x 1000Base-LX, 1310nm extended multimode port with duplex ST connector [2km/1.2 miles]. -10 to 60C operating temperature. PRO software feature set.	https://www.perle.com/products/switches/ids-509g-industrial-managed-gigabit-switch.shtml	Industrial Switch: IDS-509G
07015110	IDS-509G2-C2SD10 Industrial Managed Switch, 9 ports: 7 x 10/100/1000Base-T Base-T RJ-45 ports and 2 x 1000Base-LX/LH, 1310nm single mode port with duplex SC connector [10 km/ 6.2 miles]. -10 to 60C operating temperature. PRO software feature set.	https://www.perle.com/products/switches/ids-509g-industrial-managed-gigabit-switch.shtml	Industrial Switch: IDS-509G
07015120	IDS-509G2-T2SD10 Industrial Managed Switch, 9 ports: 7 x 10/100/1000Base-T Base-T RJ-45 ports and 2 x 1000Base-LX/LH, 1310nm single mode port with duplex ST connector [10 km/ 6.2 miles]. -10 to 60C operating temperature. PRO software feature set.	https://www.perle.com/products/switches/ids-509g-industrial-managed-gigabit-switch.shtml	Industrial Switch: IDS-509G
07015130	IDS-509G2-C2MD05-XT Industrial Managed Switch, 9 ports: 7 x 10/100/1000Base-T Base-T RJ-45 ports and 2 x 1000Base-SX, 850nm multimode port with duplex SC connector [550m/1804 ft]. -40 to 75C Industrial extended operating temperature. PRO software feature set.	https://www.perle.com/products/switches/ids-509g-industrial-managed-gigabit-switch.shtml	Industrial Switch: IDS-509G
07015140	IDS-509G2-T2MD05-XT Industrial Managed Switch, 9 ports: 7 x 10/100/1000Base-T Base-T RJ-45 ports and 2 x 1000Base-SX, 850nm multimode port with duplex ST connector [550m/1804 ft]. -40 to 75C Industrial extended operating temperature. PRO software feature set.	https://www.perle.com/products/switches/ids-509g-industrial-managed-gigabit-switch.shtml	Industrial Switch: IDS-509G
07015150	IDS-509G2-C2SD10-XT Industrial Managed Switch, 9 ports: 7 x 10/100/1000Base-T Base-T RJ-45 ports and 2 x 1000Base-LX/LH, 1310nm single mode port with duplex SC connector [10 km/ 6.2 miles]. -40 to 75C Industrial extended operating temperature. PRO software feature set.	https://www.perle.com/products/switches/ids-509g-industrial-managed-gigabit-switch.shtml	Industrial Switch: IDS-509G
07015160	IDS-509G2-T2SD10-XT Industrial Managed Switch, 9 ports: 7 x 10/100/1000Base-T Base-T RJ-45 ports and 2 x 1000Base-LX/LH, 1310nm single mode port with duplex ST connector [10 km/ 6.2 miles]. -40 to 75C Industrial extended operating temperature. PRO software feature set.	https://www.perle.com/products/switches/ids-509g-industrial-managed-gigabit-switch.shtml	Industrial Switch: IDS-509G

Part #	Description	Product Datasheet	Product Group
07015170	IDS-409F-CMD2 Industrial Managed Switch, 9 ports: 8 x 10/100/1000Base-T Base-T RJ-45 ports and 1 x 100Base-FX, 1310nm multimode port with duplex SC connector [up to 5km/3.1 miles]. -10 to 60C operating temperature.	https://www.perle.com/products/switches/ids-409f-industrial-managed-ethernet-switch.shtml	Industrial Switch: IDS-409F
07015180	IDS-409F-TMD2 Industrial Managed Switch, 9 ports: 8 x 10/100/1000Base-T Base-T RJ-45 ports and 1 x 100Base-FX, 1310nm multimode port with duplex ST connector [up to 5km/3.1 miles]. -10 to 60C operating temperature.	https://www.perle.com/products/switches/ids-409f-industrial-managed-ethernet-switch.shtml	Industrial Switch: IDS-409F
07015190	IDS-409F-CSD20 Industrial Managed Switch, 9 ports: 8 x 10/100/1000Base-T Base-T RJ-45 ports and 1 x 100Base-LX, 1310nm single mode port with duplex SC connector [20 km/ 12.4 miles]. -10 to 60C operating temperature.	https://www.perle.com/products/switches/ids-409f-industrial-managed-ethernet-switch.shtml	Industrial Switch: IDS-409F
07015200	IDS-409F-TSD20 Industrial Managed Switch, 9 ports: 8 x 10/100/1000Base-T Base-T RJ-45 ports and 1 x 100Base-LX, 1310nm single mode port with duplex ST connector [20 km/ 12.4 miles]. -10 to 60C operating temperature.	https://www.perle.com/products/switches/ids-409f-industrial-managed-ethernet-switch.shtml	Industrial Switch: IDS-409F
07015210	IDS-409F-CSD40 Industrial Managed Switch, 9 ports: 8 x 10/100/1000Base-T Base-T RJ-45 ports and 1 x 100Base-LX, 1310nm single mode port with duplex SC connector [40 km/ 24.9 miles]. -10 to 60C operating temperature.	https://www.perle.com/products/switches/ids-409f-industrial-managed-ethernet-switch.shtml	Industrial Switch: IDS-409F
07015220	IDS-409F-TSD40 Industrial Managed Switch, 9 ports: 8 x 10/100/1000Base-T Base-T RJ-45 ports and 1 x 100Base-LX, 1310nm single mode port with duplex ST connector [40 km/ 24.9 miles]. -10 to 60C operating temperature.	https://www.perle.com/products/switches/ids-409f-industrial-managed-ethernet-switch.shtml	Industrial Switch: IDS-409F
07015230	IDS-409F-CSD80 Industrial Managed Switch, 9 ports: 8 x 10/100/1000Base-T Base-T RJ-45 ports and 1 x 100Base-EX, 1550nm single mode port with duplex SC connector [80 km/ 49.7 miles]. -10 to 60C operating temperature.	https://www.perle.com/products/switches/ids-409f-industrial-managed-ethernet-switch.shtml	Industrial Switch: IDS-409F
07015240	IDS-409F-TSD80 Industrial Managed Switch, 9 ports: 8 x 10/100/1000Base-T Base-T RJ-45 ports and 1 x 100Base-EX, 1550nm single mode port with duplex ST connector [80 km/ 49.7 miles]. -10 to 60C operating temperature.	https://www.perle.com/products/switches/ids-409f-industrial-managed-ethernet-switch.shtml	Industrial Switch: IDS-409F

Part #	Description	Product Datasheet	Product Group
07015250	IDS-409F-CSD120 Industrial Managed Switch, 9 ports: 8 x 10/100/1000Base-T Base-T RJ-45 ports and 1 x 100Base-ZX, 1550nm single mode port with duplex SC connector [120 km/ 74.6 miles]. -10 to 60C operating temperature.	https://www.perle.com/products/switches/ids-409f-industrial-managed-ethernet-switch.shtml	Industrial Switch: IDS-409F
07015260	IDS-409F-TSD120 Industrial Managed Switch, 9 ports: 8 x 10/100/1000Base-T Base-T RJ-45 ports and 1 x 100Base-ZX, 1550nm single mode port with duplex ST connector [120 km/ 74.6 miles]. -10 to 60C operating temperature.	https://www.perle.com/products/switches/ids-409f-industrial-managed-ethernet-switch.shtml	Industrial Switch: IDS-409F
07015270	IDS-409F-CMS2U Industrial Managed Switch, 9 ports: 8 x 10/100/1000Base-T Base-T RJ-45 ports and 1 x 100Base-BX, 1310nm TX / 1550nm RX single strand multimode port with simplex (BIDI) SC connector [up to 5km/3.1 miles]. -10 to 60C operating temperature.	https://www.perle.com/products/switches/ids-409f-industrial-managed-ethernet-switch.shtml	Industrial Switch: IDS-409F
07015280	IDS-409F-CMS2D Industrial Managed Switch, 9 ports: 8 x 10/100/1000Base-T Base-T RJ-45 ports and 1 x 100Base-BX, 1550nm TX / 1310nm RX single strand multimode port with simplex (BIDI) SC connector [up to 5km/3.1 miles]. -10 to 60C operating temperature.	https://www.perle.com/products/switches/ids-409f-industrial-managed-ethernet-switch.shtml	Industrial Switch: IDS-409F
07015290	IDS-409F-TMS2U Industrial Managed Switch, 9 ports: 8 x 10/100/1000Base-T Base-T RJ-45 ports and 1 x 100Base-BX, 1310nm TX / 1550nm RX single strand multimode port with simplex (BIDI) ST connector [up to 5km/3.1 miles]. -10 to 60C operating temperature.	https://www.perle.com/products/switches/ids-409f-industrial-managed-ethernet-switch.shtml	Industrial Switch: IDS-409F
07015300	IDS-409F-TMS2D Industrial Managed Switch, 9 ports: 8 x 10/100/1000Base-T Base-T RJ-45 ports and 1 x 100Base-BX, 1550nm TX / 1310nm RX single strand multimode port with simplex (BIDI) ST connector [up to 5km/3.1 miles]. -10 to 60C operating temperature.	https://www.perle.com/products/switches/ids-409f-industrial-managed-ethernet-switch.shtml	Industrial Switch: IDS-409F
07015310	IDS-409F-CSS20U Industrial Managed Switch, 9 ports: 8 x 10/100/1000Base-T Base-T RJ-45 ports and 1 x 100Base-BX, 1310nm TX / 1550nm RX single strand single mode port with simplex (BIDI) SC connector [20km/12.4 miles]. -10 to 60C operating temperature.	https://www.perle.com/products/switches/ids-409f-industrial-managed-ethernet-switch.shtml	Industrial Switch: IDS-409F
07015320	IDS-409F-CSS20D Industrial Managed Switch, 9 ports: 8 x 10/100/1000Base-T Base-T RJ-45 ports and 1 x 100Base-BX, 1550nm TX / 1310nm RX single strand single mode port with simplex (BIDI) SC connector [20km/12.4 miles]. -10 to 60C operating temperature.	https://www.perle.com/products/switches/ids-409f-industrial-managed-ethernet-switch.shtml	Industrial Switch: IDS-409F

Part #	Description	Product Datasheet	Product Group
07015330	IDS-409F-TSS20U Industrial Managed Switch, 9 ports: 8 x 10/100/1000Base-T Base-T RJ-45 ports and 1 x 100Base-BX, 1310nm TX / 1550nm RX single strand single mode port with simplex (BIDI) ST connector [20km/12.4 miles]. -10 to 60C operating temperature.	https://www.perle.com/products/switches/ids-409f-industrial-managed-ethernet-switch.shtml	Industrial Switch: IDS-409F
07015340	IDS-409F-TSS20D Industrial Managed Switch, 9 ports: 8 x 10/100/1000Base-T Base-T RJ-45 ports and 1 x 100Base-BX, 1550nm TX / 1310nm RX single strand single mode port with simplex (BIDI) ST connector [20km/12.4 miles]. -10 to 60C operating temperature.	https://www.perle.com/products/switches/ids-409f-industrial-managed-ethernet-switch.shtml	Industrial Switch: IDS-409F
07015350	IDS-409F-CSS40U Industrial Managed Switch, 9 ports: 8 x 10/100/1000Base-T Base-T RJ-45 ports and 1 x 100Base-BX, 1310nm TX / 1550nm RX single strand single mode port with simplex (BIDI) SC connector [40km/24.9 miles]. -10 to 60C operating temperature.	https://www.perle.com/products/switches/ids-409f-industrial-managed-ethernet-switch.shtml	Industrial Switch: IDS-409F
07015360	IDS-409F-CSS40D Industrial Managed Switch, 9 ports: 8 x 10/100/1000Base-T Base-T RJ-45 ports and 1 x 100Base-BX, 1550nm TX / 1310nm RX single strand single mode port with simplex (BIDI) SC connector [40km/24.9 miles]. -10 to 60C operating temperature.	https://www.perle.com/products/switches/ids-409f-industrial-managed-ethernet-switch.shtml	Industrial Switch: IDS-409F
07015370	IDS-409F-CMD2-XT Industrial Managed Switch, 9 ports: 8 x 10/100/1000Base-T Base-T RJ-45 ports and 1 x 100Base-FX, 1310nm multimode port with duplex SC connector [up to 5km/3.1 miles]. -40 to 75C Industrial extended operating temperature.	https://www.perle.com/products/switches/ids-409f-industrial-managed-ethernet-switch.shtml	Industrial Switch: IDS-409F
07015380	IDS-409F-TMD2-XT Industrial Managed Switch, 9 ports: 8 x 10/100/1000Base-T Base-T RJ-45 ports and 1 x 100Base-FX, 1310nm multimode port with duplex ST connector [up to 5km/3.1 miles]. -40 to 75C Industrial extended operating temperature.	https://www.perle.com/products/switches/ids-409f-industrial-managed-ethernet-switch.shtml	Industrial Switch: IDS-409F
07015390	IDS-409F-CSD20-XT Industrial Managed Switch, 9 ports: 8 x 10/100/1000Base-T Base-T RJ-45 ports and 1 x 100Base-LX, 1310nm single mode port with duplex SC connector [20 km/ 12.4 miles]. -40 to 75C Industrial extended operating temperature.	https://www.perle.com/products/switches/ids-409f-industrial-managed-ethernet-switch.shtml	Industrial Switch: IDS-409F
07015400	IDS-409F-TSD20-XT Industrial Managed Switch, 9 ports: 8 x 10/100/1000Base-T Base-T RJ-45 ports and 1 x 100Base-LX, 1310nm single mode port with duplex ST connector [20 km/ 12.4 miles]. -40 to 75C Industrial extended operating temperature.	https://www.perle.com/products/switches/ids-409f-industrial-managed-ethernet-switch.shtml	Industrial Switch: IDS-409F

Part #	Description	Product Datasheet	Product Group
07015410	IDS-409F-CSD40-XT Industrial Managed Switch, 9 ports: 8 x 10/100/1000Base-T Base-T RJ-45 ports and 1 x 100Base-LX, 1310nm single mode port with duplex SC connector [40 km/ 24.9 miles]. -40 to 75C Industrial extended operating temperature.	https://www.perle.com/products/switches/ids-409f-industrial-managed-ethernet-switch.shtml	Industrial Switch: IDS-409F
07015420	IDS-409F-TSD40-XT Industrial Managed Switch, 9 ports: 8 x 10/100/1000Base-T Base-T RJ-45 ports and 1 x 100Base-LX, 1310nm single mode port with duplex ST connector [40 km/ 24.9 miles]. -40 to 75C Industrial extended operating temperature.	https://www.perle.com/products/switches/ids-409f-industrial-managed-ethernet-switch.shtml	Industrial Switch: IDS-409F
07015430	IDS-409F-CSS20U-XT Industrial Managed Switch, 9 ports: 8 x 10/100/1000Base-T Base-T RJ-45 ports and 1 x 100Base-BX, 1310nm TX / 1550nm RX single strand single mode port with simplex (BIDI) SC connector [20km/12.4 miles]. -40 to 75C Industrial extended operating temperature.	https://www.perle.com/products/switches/ids-409f-industrial-managed-ethernet-switch.shtml	Industrial Switch: IDS-409F
07015440	IDS-409F-CSS20D-XT Industrial Managed Switch, 9 ports: 8 x 10/100/1000Base-T Base-T RJ-45 ports and 1 x 100Base-BX, 1550nm TX / 1310nm RX single strand single mode port with simplex (BIDI) SC connector [20km/12.4 miles]. -40 to 75C Industrial extended operating temperature.	https://www.perle.com/products/switches/ids-409f-industrial-managed-ethernet-switch.shtml	Industrial Switch: IDS-409F
07015450	IDS-509F-CMD2 Industrial Managed Switch, 9 ports: 8 x 10/100/1000Base-T Base-T RJ-45 ports and 1 x 100Base-FX, 1310nm multimode port with duplex SC connector [up to 5km/3.1 miles]. -10 to 60C operating temperature. PRO software set.	https://www.perle.com/products/switches/ids-509f-industrial-managed-ethernet-switch.shtml	Industrial Switch: IDS-509F
07015460	IDS-509F-TMD2 Industrial Managed Switch, 9 ports: 8 x 10/100/1000Base-T Base-T RJ-45 ports and 1 x 100Base-FX, 1310nm multimode port with duplex ST connector [up to 5km/3.1 miles]. -10 to 60C operating temperature. PRO software set.	https://www.perle.com/products/switches/ids-509f-industrial-managed-ethernet-switch.shtml	Industrial Switch: IDS-509F
07015470	IDS-509F-CSD20 Industrial Managed Switch, 9 ports: 8 x 10/100/1000Base-T Base-T RJ-45 ports and 1 x 100Base-LX, 1310nm single mode port with duplex SC connector [20 km/ 12.4 miles]. -10 to 60C operating temperature. PRO software set.	https://www.perle.com/products/switches/ids-509f-industrial-managed-ethernet-switch.shtml	Industrial Switch: IDS-509F
07015480	IDS-509F-TSD20 Industrial Managed Switch, 9 ports: 8 x 10/100/1000Base-T Base-T RJ-45 ports and 1 x 100Base-LX, 1310nm single mode port with duplex ST connector [20 km/ 12.4 miles]. -10 to 60C operating temperature. PRO software set.	https://www.perle.com/products/switches/ids-509f-industrial-managed-ethernet-switch.shtml	Industrial Switch: IDS-509F

Part #	Description	Product Datasheet	Product Group
07015490	IDS-509F-CSD40 Industrial Managed Switch, 9 ports: 8 x 10/100/1000Base-T Base-T RJ-45 ports and 1 x 100Base-LX, 1310nm single mode port with duplex SC connector [40 km/ 24.9 miles]. -10 to 60C operating temperature. PRO software set.	https://www.perle.com/products/switches/ids-509f-industrial-managed-ethernet-switch.shtml	Industrial Switch: IDS-509F
07015500	IDS-509F-TSD40 Industrial Managed Switch, 9 ports: 8 x 10/100/1000Base-T Base-T RJ-45 ports and 1 x 100Base-LX, 1310nm single mode port with duplex ST connector [40 km/ 24.9 miles]. -10 to 60C operating temperature. PRO software set.	https://www.perle.com/products/switches/ids-509f-industrial-managed-ethernet-switch.shtml	Industrial Switch: IDS-509F
07015510	IDS-509F-CSD80 Industrial Managed Switch, 9 ports: 8 x 10/100/1000Base-T Base-T RJ-45 ports and 1 x 100Base-EX, 1550nm single mode port with duplex SC connector [80 km/ 49.7 miles]. -10 to 60C operating temperature. PRO software set.	https://www.perle.com/products/switches/ids-509f-industrial-managed-ethernet-switch.shtml	Industrial Switch: IDS-509F
07015520	IDS-509F-TSD80 Industrial Managed Switch, 9 ports: 8 x 10/100/1000Base-T Base-T RJ-45 ports and 1 x 100Base-EX, 1550nm single mode port with duplex ST connector [80 km/ 49.7 miles]. -10 to 60C operating temperature. PRO software set.	https://www.perle.com/products/switches/ids-509f-industrial-managed-ethernet-switch.shtml	Industrial Switch: IDS-509F
07015530	IDS-509F-CSD120 Industrial Managed Switch, 9 ports: 8 x 10/100/1000Base-T Base-T RJ-45 ports and 1 x 100Base-ZX, 1550nm single mode port with duplex SC connector [120 km/ 74.6 miles]. -10 to 60C operating temperature. PRO software set.	https://www.perle.com/products/switches/ids-509f-industrial-managed-ethernet-switch.shtml	Industrial Switch: IDS-509F
07015540	IDS-509F-TSD120 Industrial Managed Switch, 9 ports: 8 x 10/100/1000Base-T Base-T RJ-45 ports and 1 x 100Base-ZX, 1550nm single mode port with duplex ST connector [120 km/ 74.6 miles]. -10 to 60C operating temperature. PRO software set.	https://www.perle.com/products/switches/ids-509f-industrial-managed-ethernet-switch.shtml	Industrial Switch: IDS-509F
07015550	IDS-509F-CMS2U Industrial Managed Switch, 9 ports: 8 x 10/100/1000Base-T Base-T RJ-45 ports and 1 x 100Base-BX, 1310nm TX / 1550nm RX single strand multimode port with simplex (BIDI) SC connector [up to 5km/3.1 miles]. -10 to 60C operating temperature. PRO software set.	https://www.perle.com/products/switches/ids-509f-industrial-managed-ethernet-switch.shtml	Industrial Switch: IDS-509F
07015560	IDS-509F-CMS2D Industrial Managed Switch, 9 ports: 8 x 10/100/1000Base-T Base-T RJ-45 ports and 1 x 100Base-BX, 1550nm TX / 1310nm RX single strand multimode port with simplex (BIDI) SC connector [up to 5km/3.1 miles]. -10 to 60C operating temperature. PRO software set.	https://www.perle.com/products/switches/ids-509f-industrial-managed-ethernet-switch.shtml	Industrial Switch: IDS-509F

Part #	Description	Product Datasheet	Product Group
07015570	IDS-509F-TMS2U Industrial Managed Switch, 9 ports: 8 x 10/100/1000Base-T Base-T RJ-45 ports and 1 x 100Base-BX, 1310nm TX / 1550nm RX single strand multimode port with simplex (BIDI) ST connector [up to 5km/3.1 miles]. -10 to 60C operating temperature. PRO software set.	https://www.perle.com/products/switches/ids-509f-industrial-managed-ethernet-switch.shtml	Industrial Switch: IDS-509F
07015580	IDS-509F-TMS2D Industrial Managed Switch, 9 ports: 8 x 10/100/1000Base-T Base-T RJ-45 ports and 1 x 100Base-BX, 1550nm TX / 1310nm RX single strand multimode port with simplex (BIDI) ST connector [up to 5km/3.1 miles]. -10 to 60C operating temperature. PRO software set.	https://www.perle.com/products/switches/ids-509f-industrial-managed-ethernet-switch.shtml	Industrial Switch: IDS-509F
07015590	IDS-509F-CSS20U Industrial Managed Switch, 9 ports: 8 x 10/100/1000Base-T Base-T RJ-45 ports and 1 x 100Base-BX, 1310nm TX / 1550nm RX single strand single mode port with simplex (BIDI) SC connector [20km/12.4 miles]. -10 to 60C operating temperature. PRO software set.	https://www.perle.com/products/switches/ids-509f-industrial-managed-ethernet-switch.shtml	Industrial Switch: IDS-509F
07015600	IDS-509F-CSS20D Industrial Managed Switch, 9 ports: 8 x 10/100/1000Base-T Base-T RJ-45 ports and 1 x 100Base-BX, 1550nm TX / 1310nm RX single strand single mode port with simplex (BIDI) SC connector [20km/12.4 miles]. -10 to 60C operating temperature. PRO software set.	https://www.perle.com/products/switches/ids-509f-industrial-managed-ethernet-switch.shtml	Industrial Switch: IDS-509F
07015610	IDS-509F-TSS20U Industrial Managed Switch, 9 ports: 8 x 10/100/1000Base-T Base-T RJ-45 ports and 1 x 100Base-BX, 1310nm TX / 1550nm RX single strand single mode port with simplex (BIDI) ST connector [20km/12.4 miles]. -10 to 60C operating temperature. PRO software set.	https://www.perle.com/products/switches/ids-509f-industrial-managed-ethernet-switch.shtml	Industrial Switch: IDS-509F
07015620	IDS-509F-TSS20D Industrial Managed Switch, 9 ports: 8 x 10/100/1000Base-T Base-T RJ-45 ports and 1 x 100Base-BX, 1550nm TX / 1310nm RX single strand single mode port with simplex (BIDI) ST connector [20km/12.4 miles]. -10 to 60C operating temperature. PRO software set.	https://www.perle.com/products/switches/ids-509f-industrial-managed-ethernet-switch.shtml	Industrial Switch: IDS-509F
07015630	IDS-509F-CSS40U Industrial Managed Switch, 9 ports: 8 x 10/100/1000Base-T Base-T RJ-45 ports and 1 x 100Base-BX, 1310nm TX / 1550nm RX single strand single mode port with simplex (BIDI) SC connector [40km/24.9 miles]. -10 to 60C operating temperature. PRO software set.	https://www.perle.com/products/switches/ids-509f-industrial-managed-ethernet-switch.shtml	Industrial Switch: IDS-509F

Part #	Description	Product Datasheet	Product Group
07015640	IDS-509F-CSS40D Industrial Managed Switch, 9 ports: 8 x 10/100/1000Base-T Base-T RJ-45 ports and 1 x 100Base-BX, 1550nm TX / 1310nm RX single strand single mode port with simplex (BIDI) SC connector [40km/24.9 miles]. -10 to 60C operating temperature. PRO software set.	https://www.perle.com/products/switches/ids-509f-industrial-managed-ethernet-switch.shtml	Industrial Switch: IDS-509F
07015650	IDS-509F-CMD2-XT Industrial Managed Switch, 9 ports: 8 x 10/100/1000Base-T Base-T RJ-45 ports and 1 x 100Base-FX, 1310nm multimode port with duplex SC connector [up to 5km/3.1 miles]. -40 to 75C Industrial extended operating temperature. PRO software set.	https://www.perle.com/products/switches/ids-509f-industrial-managed-ethernet-switch.shtml	Industrial Switch: IDS-509F
07015660	IDS-509F-TMD2-XT Industrial Managed Switch, 9 ports: 8 x 10/100/1000Base-T Base-T RJ-45 ports and 1 x 100Base-FX, 1310nm multimode port with duplex ST connector [up to 5km/3.1 miles]. -40 to 75C Industrial extended operating temperature. PRO software set.	https://www.perle.com/products/switches/ids-509f-industrial-managed-ethernet-switch.shtml	Industrial Switch: IDS-509F
07015670	IDS-509F-CSD20-XT Industrial Managed Switch, 9 ports: 8 x 10/100/1000Base-T Base-T RJ-45 ports and 1 x 100Base-LX, 1310nm single mode port with duplex SC connector [20 km/ 12.4 miles]. -40 to 75C Industrial extended operating temperature. PRO software set.	https://www.perle.com/products/switches/ids-509f-industrial-managed-ethernet-switch.shtml	Industrial Switch: IDS-509F
07015680	IDS-509F-TSD20-XT Industrial Managed Switch, 9 ports: 8 x 10/100/1000Base-T Base-T RJ-45 ports and 1 x 100Base-LX, 1310nm single mode port with duplex ST connector [20 km/ 12.4 miles]. -40 to 75C Industrial extended operating temperature. PRO software set.	https://www.perle.com/products/switches/ids-509f-industrial-managed-ethernet-switch.shtml	Industrial Switch: IDS-509F
07015690	IDS-509F-CSD40-XT Industrial Managed Switch, 9 ports: 8 x 10/100/1000Base-T Base-T RJ-45 ports and 1 x 100Base-LX, 1310nm single mode port with duplex SC connector [40 km/ 24.9 miles]. -40 to 75C Industrial extended operating temperature. PRO software set.	https://www.perle.com/products/switches/ids-509f-industrial-managed-ethernet-switch.shtml	Industrial Switch: IDS-509F
07015700	IDS-509F-TSD40-XT Industrial Managed Switch, 9 ports: 8 x 10/100/1000Base-T Base-T RJ-45 ports and 1 x 100Base-LX, 1310nm single mode port with duplex ST connector [40 km/ 24.9 miles]. -40 to 75C Industrial extended operating temperature. PRO software set.	https://www.perle.com/products/switches/ids-509f-industrial-managed-ethernet-switch.shtml	Industrial Switch: IDS-509F
07015710	IDS-509F-CSS20U-XT Industrial Managed Switch, 9 ports: 8 x 10/100/1000Base-T Base-T RJ-45 ports and 1 x 100Base-BX, 1310nm TX / 1550nm RX single strand single mode port with simplex (BIDI) SC connector [20km/12.4 miles]. -40 to 75C Industrial extended operating temperature. PRO software set.	https://www.perle.com/products/switches/ids-509f-industrial-managed-ethernet-switch.shtml	Industrial Switch: IDS-509F

Part #	Description	Product Datasheet	Product Group
07015720	IDS-509F-CSS20D-XT Industrial Managed Switch, 9 ports: 8 x 10/100/1000Base-T Base-T RJ-45 ports and 1 x 100Base-BX, 1550nm TX / 1310nm RX single strand single mode port with simplex (BIDI) SC connector [20km/12.4 miles]. -40 to 75C Industrial extended operating temperature. PRO software set.	https://www.perle.com/products/switches/ids-509f-industrial-managed-ethernet-switch.shtml	Industrial Switch: IDS-509F
07015730	IDS-409G-CMD05 Industrial Managed Switch, 9 ports: 8 x 10/100/1000Base-T Base-T RJ-45 ports and 1 x 1000Base-SX, 850nm multimode port with duplex SC connector [550m/1804 ft]. -10 to 60C operating temperature.	https://www.perle.com/products/switches/ids-409g-industrial-managed-gigabit-switch.shtml	Industrial Switch: IDS-409G
07015740	IDS-409G-TMD05 Industrial Managed Switch, 9 ports: 8 x 10/100/1000Base-T Base-T RJ-45 ports and 1 x 1000Base-SX, 850nm multimode port with duplex ST connector [550m/1804 ft]. -10 to 60C operating temperature.	https://www.perle.com/products/switches/ids-409g-industrial-managed-gigabit-switch.shtml	Industrial Switch: IDS-409G
07015750	IDS-409G-CMD2 Industrial Managed Switch, 9 ports: 8 x 10/100/1000Base-T Base-T RJ-45 ports and 1 x 1000Base-LX, 1310nm extended multimode port with duplex SC connector [2km/1.2 miles]. -10 to 60C operating temperature.	https://www.perle.com/products/switches/ids-409g-industrial-managed-gigabit-switch.shtml	Industrial Switch: IDS-409G
07015760	IDS-409G-TMD2 Industrial Managed Switch, 9 ports: 8 x 10/100/1000Base-T Base-T RJ-45 ports and 1 x 1000Base-LX, 1310nm extended multimode port with duplex ST connector [2km/1.2 miles]. -10 to 60C operating temperature.	https://www.perle.com/products/switches/ids-409g-industrial-managed-gigabit-switch.shtml	Industrial Switch: IDS-409G
07015770	IDS-409G-CSD10 Industrial Managed Switch, 9 ports: 8 x 10/100/1000Base-T Base-T RJ-45 ports and 1 x 1000Base-LX/LH, 1310nm single mode port with duplex SC connector [10 km/ 6.2 miles]. -10 to 60C operating temperature.	https://www.perle.com/products/switches/ids-409g-industrial-managed-gigabit-switch.shtml	Industrial Switch: IDS-409G
07015780	IDS-409G-TSD10 Industrial Managed Switch, 9 ports: 8 x 10/100/1000Base-T Base-T RJ-45 ports and 1 x 1000Base-LX/LH, 1310nm single mode port with duplex ST connector [10 km/ 6.2 miles]. -10 to 60C operating temperature.	https://www.perle.com/products/switches/ids-409g-industrial-managed-gigabit-switch.shtml	Industrial Switch: IDS-409G
07015790	IDS-409G-CSD40 Industrial Managed Switch, 9 ports: 8 x 10/100/1000Base-T Base-T RJ-45 ports and 1 x 1000Base-EX, 1310nm single mode port with duplex SC connector [40 km/ 24.9 miles]. -10 to 60C operating temperature.	https://www.perle.com/products/switches/ids-409g-industrial-managed-gigabit-switch.shtml	Industrial Switch: IDS-409G

Part #	Description	Product Datasheet	Product Group
07015800	IDS-409G-TSD40 Industrial Managed Switch, 9 ports: 8 x 10/100/1000Base-T Base-T RJ-45 ports and 1 x 1000Base-EX, 1310nm single mode port with duplex ST connector [40 km/ 24.9 miles]. -10 to 60C operating temperature.	https://www.perle.com/products/switches/ids-409g-industrial-managed-gigabit-switch.shtml	Industrial Switch: IDS-409G
07015810	IDS-409G-CSD70 Industrial Managed Switch, 9 ports: 8 x 10/100/1000Base-T Base-T RJ-45 ports and 1 x 1000Base-ZX, 1550nm single mode port with duplex SC connector [70 km/ 43.5 miles]. -10 to 60C operating temperature.	https://www.perle.com/products/switches/ids-409g-industrial-managed-gigabit-switch.shtml	Industrial Switch: IDS-409G
07015820	IDS-409G-TSD70 Industrial Managed Switch, 9 ports: 8 x 10/100/1000Base-T Base-T RJ-45 ports and 1 x 1000Base-ZX, 1550nm single mode port with duplex ST connector [70 km/ 43.5 miles]. -10 to 60C operating temperature.	https://www.perle.com/products/switches/ids-409g-industrial-managed-gigabit-switch.shtml	Industrial Switch: IDS-409G
07015830	IDS-409G-CSD120 Industrial Managed Switch, 9 ports: 8 x 10/100/1000Base-T Base-T RJ-45 ports and 1 x 1000Base-ZX, 1550nm single mode port with duplex SC connector [120 km/ 74.6 miles]. -10 to 60C operating temperature.	https://www.perle.com/products/switches/ids-409g-industrial-managed-gigabit-switch.shtml	Industrial Switch: IDS-409G
07015840	IDS-409G-TSD120 Industrial Managed Switch, 9 ports: 8 x 10/100/1000Base-T Base-T RJ-45 ports and 1 x 1000Base-ZX, 1550nm single mode port with duplex ST connector [120 km/ 74.6 miles]. -10 to 60C operating temperature.	https://www.perle.com/products/switches/ids-409g-industrial-managed-gigabit-switch.shtml	Industrial Switch: IDS-409G
07015850	IDS-409G-CSD160 Industrial Managed Switch, 9 ports: 8 x 10/100/1000Base-T Base-T RJ-45 ports and 1 x 1000Base-ZX, 1550nm single mode port with duplex SC connector [160 km/ 100 miles]. -10 to 60C operating temperature.	https://www.perle.com/products/switches/ids-409g-industrial-managed-gigabit-switch.shtml	Industrial Switch: IDS-409G
07015860	IDS-409G-TSD160 Industrial Managed Switch, 9 ports: 8 x 10/100/1000Base-T Base-T RJ-45 ports and 1 x 1000Base-ZX, 1550nm single mode port with duplex ST connector [160 km/ 100 miles]. -10 to 60C operating temperature.	https://www.perle.com/products/switches/ids-409g-industrial-managed-gigabit-switch.shtml	Industrial Switch: IDS-409G
07015870	IDS-409G-CMS05U Industrial Managed Switch, 9 ports: 8 x 10/100/1000Base-T Base-T RJ-45 ports and 1 x 1000BASE-BX 1310nm TX / 1550nm RX single strand fiber, multimode (SC) [550 m/1804 ft]. -10 to 60C operating temperature.	https://www.perle.com/products/switches/ids-409g-industrial-managed-gigabit-switch.shtml	Industrial Switch: IDS-409G

Part #	Description	Product Datasheet	Product Group
07015880	IDS-409G-CMS05D Industrial Managed Switch, 9 ports: 8 x 10/100/1000Base-T Base-T RJ-45 ports and 1 x 1000BASE-BX 1550nm TX / 1310nm RX single strand fiber, multimode (SC) [550 m/1804 ft]. -10 to 60C operating temperature.	https://www.perle.com/products/switches/ids-409g-industrial-managed-gigabit-switch.shtml	Industrial Switch: IDS-409G
07015890	IDS-409G-CSS10U Industrial Managed Switch, 9 ports: 8 x 10/100/1000Base-T Base-T RJ-45 ports and 1 x 1000Base-BX, 1310nm TX / 1490nm RX single strand single mode port with simplex (BIDI) SC connector [10km/6.2 miles]. -10 to 60C operating temperature.	https://www.perle.com/products/switches/ids-409g-industrial-managed-gigabit-switch.shtml	Industrial Switch: IDS-409G
07015900	IDS-409G-CSS10D Industrial Managed Switch, 9 ports: 8 x 10/100/1000Base-T Base-T RJ-45 ports and 1 x 1000Base-BX, 1490nm TX / 1310nm RX single strand single mode port with simplex (BIDI) SC connector [10km/6.2 miles]. -10 to 60C operating temperature.	https://www.perle.com/products/switches/ids-409g-industrial-managed-gigabit-switch.shtml	Industrial Switch: IDS-409G
07015910	IDS-409G-CSS20U Industrial Managed Switch, 9 ports: 8 x 10/100/1000Base-T Base-T RJ-45 ports and 1 x 1000Base-BX, 1310nm TX / 1490nm RX single strand single mode port with simplex (BIDI) SC connector [20km/12.4 miles]. -10 to 60C operating temperature.	https://www.perle.com/products/switches/ids-409g-industrial-managed-gigabit-switch.shtml	Industrial Switch: IDS-409G
07015920	IDS-409G-CSS20D Industrial Managed Switch, 9 ports: 8 x 10/100/1000Base-T Base-T RJ-45 ports and 1 x 1000Base-BX, 1490nm TX / 1310nm RX single strand single mode port with simplex (BIDI) SC connector [20km/12.4 miles]. -10 to 60C operating temperature.	https://www.perle.com/products/switches/ids-409g-industrial-managed-gigabit-switch.shtml	Industrial Switch: IDS-409G
07015930	IDS-409G-CSS40U Industrial Managed Switch, 9 ports: 8 x 10/100/1000Base-T Base-T RJ-45 ports and 1 x 1000Base-BX, 1310nm TX / 1490nm RX single strand single mode port with simplex (BIDI) SC connector [40km/24.9 miles]. -10 to 60C operating temperature.	https://www.perle.com/products/switches/ids-409g-industrial-managed-gigabit-switch.shtml	Industrial Switch: IDS-409G
07015940	IDS-409G-CSS40D Industrial Managed Switch, 9 ports: 8 x 10/100/1000Base-T Base-T RJ-45 ports and 1 x 1000Base-BX, 1490nm TX / 1310nm RX single strand single mode port with simplex (BIDI) SC connector [40km/24.9 miles]. -10 to 60C operating temperature.	https://www.perle.com/products/switches/ids-409g-industrial-managed-gigabit-switch.shtml	Industrial Switch: IDS-409G
07015950	IDS-409G-CSS80U Industrial Managed Switch, 9 ports: 8 x 10/100/1000Base-T Base-T RJ-45 ports and 1 x 1000Base-BX, 1310nm TX / 1550nm RX single strand single mode port with simplex (BIDI) SC connector [80km/49.7 miles]. -10 to 60C operating temperature.	https://www.perle.com/products/switches/ids-409g-industrial-managed-gigabit-switch.shtml	Industrial Switch: IDS-409G

Part #	Description	Product Datasheet	Product Group
07015960	IDS-409G-CSS80D Industrial Managed Switch, 9 ports: 8 x 10/100/1000Base-T Base-T RJ-45 ports and 1 x 1000Base-BX, 1550nm TX / 1310nm RX single strand single mode port with simplex (BIDI) SC connector [80km/49.7miles]. -10 to 60C operating temperature.	https://www.perle.com/products/switches/ids-409g-industrial-managed-gigabit-switch.shtml	Industrial Switch: IDS-409G
07015970	IDS-409G-CSS120U Industrial Managed Switch, 9 ports: 8 x 10/100/1000Base-T Base-T RJ-45 ports and 1 x 1000Base-BX, 1310nm TX / 1550nm RX single strand single mode port with simplex (BIDI) SC connector [120km/74.6 miles]. -10 to 60C operating temperature.	https://www.perle.com/products/switches/ids-409g-industrial-managed-gigabit-switch.shtml	Industrial Switch: IDS-409G
07015980	IDS-409G-CSS120D Industrial Managed Switch, 9 ports: 8 x 10/100/1000Base-T Base-T RJ-45 ports and 1 x 1000Base-BX, 1550nm TX / 1310nm RX single strand single mode port with simplex (BIDI) SC connector [120km/74.6 miles]. -10 to 60C operating temperature.	https://www.perle.com/products/switches/ids-409g-industrial-managed-gigabit-switch.shtml	Industrial Switch: IDS-409G
07015990	IDS-409G-CMD05-XT Industrial Managed Switch, 9 ports: 8 x 10/100/1000Base-T Base-T RJ-45 ports and 1 x 1000Base-SX, 850nm multimode port with duplex SC connector [550m/1804 ft]. -40 to 75C Industrial extended operating temperature.	https://www.perle.com/products/switches/ids-409g-industrial-managed-gigabit-switch.shtml	Industrial Switch: IDS-409G
07016000	IDS-409G-TMD05-XT Industrial Managed Switch, 9 ports: 8 x 10/100/1000Base-T Base-T RJ-45 ports and 1 x 1000Base-SX, 850nm multimode port with duplex ST connector [550m/1804 ft]. -40 to 75C Industrial extended operating temperature.	https://www.perle.com/products/switches/ids-409g-industrial-managed-gigabit-switch.shtml	Industrial Switch: IDS-409G
07016010	IDS-409G-CSD10-XT Industrial Managed Switch, 9 ports: 8 x 10/100/1000Base-T Base-T RJ-45 ports and 1 x 1000Base-LX/LH, 1310nm single mode port with duplex SC connector [10 km/ 6.2 miles]. -40 to 75C Industrial extended operating temperature.	https://www.perle.com/products/switches/ids-409g-industrial-managed-gigabit-switch.shtml	Industrial Switch: IDS-409G
07016020	IDS-409G-TSD10-XT Industrial Managed Switch, 9 ports: 8 x 10/100/1000Base-T Base-T RJ-45 ports and 1 x 1000Base-LX/LH, 1310nm single mode port with duplex ST connector [10 km/ 6.2 miles]. -40 to 75C Industrial extended operating temperature.	https://www.perle.com/products/switches/ids-409g-industrial-managed-gigabit-switch.shtml	Industrial Switch: IDS-409G
07016030	IDS-409G-CSS10U-XT Industrial Managed Switch, 9 ports: 8 x 10/100/1000Base-T Base-T RJ-45 ports and 1 x 1000Base-BX, 1310nm TX / 1490nm RX single strand single mode port with simplex (BIDI) SC connector [10km/6.2 miles]. -40 to 75C Industrial extended operating temperature.	https://www.perle.com/products/switches/ids-409g-industrial-managed-gigabit-switch.shtml	Industrial Switch: IDS-409G

Part #	Description	Product Datasheet	Product Group
07016040	IDS-409G-CSS10D-XT Industrial Managed Switch, 9 ports: 8 x 10/100/1000Base-T Base-T RJ-45 ports and 1 x 1000Base-BX, 1490nm TX / 1310nm RX single strand single mode port with simplex (BIDI) SC connector [10km/6.2 miles]. -40 to 75C Industrial extended operating temperature.	https://www.perle.com/products/switches/ids-409g-industrial-managed-gigabit-switch.shtml	Industrial Switch: IDS-409G
07016050	IDS-509G-CMD05 Industrial Managed Switch, 9 ports: 8 x 10/100/1000Base-T Base-T RJ-45 ports and 1 x 1000Base-SX, 850nm multimode port with duplex SC connector [550m/1804 ft]. -10 to 60C operating temperature. PRO software feature set.	https://www.perle.com/products/switches/ids-509g-industrial-managed-gigabit-switch.shtml	Industrial Switch: IDS-509G
07016060	IDS-509G-TMD05 Industrial Managed Switch, 9 ports: 8 x 10/100/1000Base-T Base-T RJ-45 ports and 1 x 1000Base-SX, 850nm multimode port with duplex ST connector [550m/1804 ft]. -10 to 60C operating temperature. PRO software feature set.	https://www.perle.com/products/switches/ids-509g-industrial-managed-gigabit-switch.shtml	Industrial Switch: IDS-509G
07016070	IDS-509G-CMD2 Industrial Managed Switch, 9 ports: 8 x 10/100/1000Base-T Base-T RJ-45 ports and 1 x 1000Base-LX, 1310nm extended multimode port with duplex SC connector [2km/1.2 miles]. -10 to 60C operating temperature. PRO software feature set.	https://www.perle.com/products/switches/ids-509g-industrial-managed-gigabit-switch.shtml	Industrial Switch: IDS-509G
07016080	IDS-509G-TMD2 Industrial Managed Switch, 9 ports: 8 x 10/100/1000Base-T Base-T RJ-45 ports and 1 x 1000Base-LX, 1310nm extended multimode port with duplex ST connector [2km/1.2 miles]. -10 to 60C operating temperature. PRO software feature set.	https://www.perle.com/products/switches/ids-509g-industrial-managed-gigabit-switch.shtml	Industrial Switch: IDS-509G
07016090	IDS-509G-CSD10 Industrial Managed Switch, 9 ports: 8 x 10/100/1000Base-T Base-T RJ-45 ports and 1 x 1000Base-LX/LH, 1310nm single mode port with duplex SC connector [10 km/ 6.2 miles]. -10 to 60C operating temperature. PRO software feature set.	https://www.perle.com/products/switches/ids-509g-industrial-managed-gigabit-switch.shtml	Industrial Switch: IDS-509G
07016100	IDS-509G-TSD10 Industrial Managed Switch, 9 ports: 8 x 10/100/1000Base-T Base-T RJ-45 ports and 1 x 1000Base-LX/LH, 1310nm single mode port with duplex ST connector [10 km/ 6.2 miles]. -10 to 60C operating temperature. PRO software feature set.	https://www.perle.com/products/switches/ids-509g-industrial-managed-gigabit-switch.shtml	Industrial Switch: IDS-509G
07016110	IDS-509G-CSD40 Industrial Managed Switch, 9 ports: 8 x 10/100/1000Base-T Base-T RJ-45 ports and 1 x 1000Base-EX, 1310nm single mode port with duplex SC connector [40 km/ 24.9 miles]. -10 to 60C operating temperature. PRO software feature set.	https://www.perle.com/products/switches/ids-509g-industrial-managed-gigabit-switch.shtml	Industrial Switch: IDS-509G

Part #	Description	Product Datasheet	Product Group
07016120	IDS-509G-TSD40 Industrial Managed Switch, 9 ports: 8 x 10/100/1000Base-T Base-T RJ-45 ports and 1 x 1000Base-EX, 1310nm single mode port with duplex ST connector [40 km/ 24.9 miles]. -10 to 60C operating temperature. PRO software feature set.	https://www.perle.com/products/switches/ids-509g-industrial-managed-gigabit-switch.shtml	Industrial Switch: IDS-509G
07016130	IDS-509G-CSD70 Industrial Managed Switch, 9 ports: 8 x 10/100/1000Base-T Base-T RJ-45 ports and 1 x 1000Base-ZX, 1550nm single mode port with duplex SC connector [70 km/ 43.5 miles]. -10 to 60C operating temperature. PRO software feature set.	https://www.perle.com/products/switches/ids-509g-industrial-managed-gigabit-switch.shtml	Industrial Switch: IDS-509G
07016140	IDS-509G-TSD70 Industrial Managed Switch, 9 ports: 8 x 10/100/1000Base-T Base-T RJ-45 ports and 1 x 1000Base-ZX, 1550nm single mode port with duplex ST connector [70 km/ 43.5 miles]. -10 to 60C operating temperature. PRO software feature set.	https://www.perle.com/products/switches/ids-509g-industrial-managed-gigabit-switch.shtml	Industrial Switch: IDS-509G
07016150	IDS-509G-CSD120 Industrial Managed Switch, 9 ports: 8 x 10/100/1000Base-T Base-T RJ-45 ports and 1 x 1000Base-ZX, 1550nm single mode port with duplex SC connector [120 km/ 74.6 miles]. -10 to 60C operating temperature. PRO software feature set.	https://www.perle.com/products/switches/ids-509g-industrial-managed-gigabit-switch.shtml	Industrial Switch: IDS-509G
07016160	IDS-509G-TSD120 Industrial Managed Switch, 9 ports: 8 x 10/100/1000Base-T Base-T RJ-45 ports and 1 x 1000Base-ZX, 1550nm single mode port with duplex ST connector [120 km/ 74.6 miles]. -10 to 60C operating temperature. PRO software feature set.	https://www.perle.com/products/switches/ids-509g-industrial-managed-gigabit-switch.shtml	Industrial Switch: IDS-509G
07016170	IDS-509G-CSD160 Industrial Managed Switch, 9 ports: 8 x 10/100/1000Base-T Base-T RJ-45 ports and 1 x 1000Base-ZX, 1550nm single mode port with duplex SC connector [160 km/ 100 miles]. -10 to 60C operating temperature. PRO software feature set.	https://www.perle.com/products/switches/ids-509g-industrial-managed-gigabit-switch.shtml	Industrial Switch: IDS-509G
07016180	IDS-509G-TSD160 Industrial Managed Switch, 9 ports: 8 x 10/100/1000Base-T Base-T RJ-45 ports and 1 x 1000Base-ZX, 1550nm single mode port with duplex ST connector [160 km/ 100 miles]. -10 to 60C operating temperature. PRO software feature set.	https://www.perle.com/products/switches/ids-509g-industrial-managed-gigabit-switch.shtml	Industrial Switch: IDS-509G
07016190	IDS-509G-CMS05U Industrial Managed Switch, 9 ports: 8 x 10/100/1000Base-T Base-T RJ-45 ports and 1 x 1000BASE-BX 1310nm TX / 1550nm RX single strand fiber, multimode (SC) [550 m/1804 ft]. -10 to 60C operating temperature. PRO software feature set.	https://www.perle.com/products/switches/ids-509g-industrial-managed-gigabit-switch.shtml	Industrial Switch: IDS-509G

Part #	Description	Product Datasheet	Product Group
07016200	IDS-509G-CMS05D Industrial Managed Switch, 9 ports: 8 x 10/100/1000Base-T Base-T RJ-45 ports and 1 x 1000BASE-BX 1550nm TX / 1310nm RX single strand fiber, multimode (SC) [550 m/1804 ft]. -10 to 60C operating temperature. PRO software feature set.	https://www.perle.com/products/switches/ids-509g-industrial-managed-gigabit-switch.shtml	Industrial Switch: IDS-509G
07016210	IDS-509G-CSS10U Industrial Managed Switch, 9 ports: 8 x 10/100/1000Base-T Base-T RJ-45 ports and 1 x 1000Base-BX, 1310nm TX / 1490nm RX single strand single mode port with simplex (BIDI) SC connector [10km/6.2 miles]. -10 to 60C operating temperature. PRO software feature set.	https://www.perle.com/products/switches/ids-509g-industrial-managed-gigabit-switch.shtml	Industrial Switch: IDS-509G
07016220	IDS-509G-CSS10D Industrial Managed Switch, 9 ports: 8 x 10/100/1000Base-T Base-T RJ-45 ports and 1 x 1000Base-BX, 1490nm TX / 1310nm RX single strand single mode port with simplex (BIDI) SC connector [10km/6.2 miles]. -10 to 60C operating temperature. PRO software feature set.	https://www.perle.com/products/switches/ids-509g-industrial-managed-gigabit-switch.shtml	Industrial Switch: IDS-509G
07016230	IDS-509G-CSS20U Industrial Managed Switch, 9 ports: 8 x 10/100/1000Base-T Base-T RJ-45 ports and 1 x 1000Base-BX, 1310nm TX / 1490nm RX single strand single mode port with simplex (BIDI) SC connector [20km/12.4 miles]. -10 to 60C operating temperature. PRO software feature set.	https://www.perle.com/products/switches/ids-509g-industrial-managed-gigabit-switch.shtml	Industrial Switch: IDS-509G
07016240	IDS-509G-CSS20D Industrial Managed Switch, 9 ports: 8 x 10/100/1000Base-T Base-T RJ-45 ports and 1 x 1000Base-BX, 1490nm TX / 1310nm RX single strand single mode port with simplex (BIDI) SC connector [20km/12.4 miles]. -10 to 60C operating temperature. PRO software feature set.	https://www.perle.com/products/switches/ids-509g-industrial-managed-gigabit-switch.shtml	Industrial Switch: IDS-509G
07016250	IDS-509G-CSS40U Industrial Managed Switch, 9 ports: 8 x 10/100/1000Base-T Base-T RJ-45 ports and 1 x 1000Base-BX, 1310nm TX / 1490nm RX single strand single mode port with simplex (BIDI) SC connector [40km/24.9 miles]. -10 to 60C operating temperature. PRO software feature set.	https://www.perle.com/products/switches/ids-509g-industrial-managed-gigabit-switch.shtml	Industrial Switch: IDS-509G
07016260	IDS-509G-CSS40D Industrial Managed Switch, 9 ports: 8 x 10/100/1000Base-T Base-T RJ-45 ports and 1 x 1000Base-BX, 1490nm TX / 1310nm RX single strand single mode port with simplex (BIDI) SC connector [40km/24.9 miles]. -10 to 60C operating temperature. PRO software feature set.	https://www.perle.com/products/switches/ids-509g-industrial-managed-gigabit-switch.shtml	Industrial Switch: IDS-509G

Part #	Description	Product Datasheet	Product Group
07016270	IDS-509G-CSS80U Industrial Managed Switch, 9 ports: 8 x 10/100/1000Base-T Base-T RJ-45 ports and 1 x 1000Base-BX, 1310nm TX / 1550nm RX single strand single mode port with simplex (BIDI) SC connector [80km/49.7 miles]. -10 to 60C operating temperature. PRO software feature set.	https://www.perle.com/products/switches/ids-509g-industrial-managed-gigabit-switch.shtml	Industrial Switch: IDS-509G
07016280	IDS-509G-CSS80D Industrial Managed Switch, 9 ports: 8 x 10/100/1000Base-T Base-T RJ-45 ports and 1 x 1000Base-BX, 1550nm TX / 1310nm RX single strand single mode port with simplex (BIDI) SC connector [80km/49.7miles]. -10 to 60C operating temperature. PRO software feature set.	https://www.perle.com/products/switches/ids-509g-industrial-managed-gigabit-switch.shtml	Industrial Switch: IDS-509G
07016290	IDS-509G-CSS120U Industrial Managed Switch, 9 ports: 8 x 10/100/1000Base-T Base-T RJ-45 ports and 1 x 1000Base-BX, 1310nm TX / 1550nm RX single strand single mode port with simplex (BIDI) SC connector [120km/74.6 miles]. -10 to 60C operating temperature. PRO software feature set.	https://www.perle.com/products/switches/ids-509g-industrial-managed-gigabit-switch.shtml	Industrial Switch: IDS-509G
07016300	IDS-509G-CSS120D Industrial Managed Switch, 9 ports: 8 x 10/100/1000Base-T Base-T RJ-45 ports and 1 x 1000Base-BX, 1550nm TX / 1310nm RX single strand single mode port with simplex (BIDI) SC connector [120km/74.6 miles]. -10 to 60C operating temperature. PRO software feature set.	https://www.perle.com/products/switches/ids-509g-industrial-managed-gigabit-switch.shtml	Industrial Switch: IDS-509G
07016310	IDS-509G-CMD05-XT Industrial Managed Switch, 9 ports: 8 x 10/100/1000Base-T Base-T RJ-45 ports and 1 x 1000Base-SX, 850nm multimode port with duplex SC connector [550m/1804 ft]. -40 to 75C Industrial extended operating temperature. PRO software feature set.	https://www.perle.com/products/switches/ids-509g-industrial-managed-gigabit-switch.shtml	Industrial Switch: IDS-509G
07016320	IDS-509G-TMD05-XT Industrial Managed Switch, 9 ports: 8 x 10/100/1000Base-T Base-T RJ-45 ports and 1 x 1000Base-SX, 850nm multimode port with duplex ST connector [550m/1804 ft]. -40 to 75C Industrial extended operating temperature. PRO software feature set.	https://www.perle.com/products/switches/ids-509g-industrial-managed-gigabit-switch.shtml	Industrial Switch: IDS-509G
07016330	IDS-509G-CSD10-XT Industrial Managed Switch, 9 ports: 8 x 10/100/1000Base-T Base-T RJ-45 ports and 1 x 1000Base-LX/LH, 1310nm single mode port with duplex SC connector [10 km/ 6.2 miles]. -40 to 75C Industrial extended operating temperature. PRO software feature set.	https://www.perle.com/products/switches/ids-509g-industrial-managed-gigabit-switch.shtml	Industrial Switch: IDS-509G

Part #	Description	Product Datasheet	Product Group
07016340	IDS-509G-TSD10-XT Industrial Managed Switch, 9 ports: 8 x 10/100/1000Base-T Base-T RJ-45 ports and 1 x 1000Base-LX/LH, 1310nm single mode port with duplex ST connector [10 km/ 6.2 miles]. -40 to 75C Industrial extended operating temperature. PRO software feature set.	https://www.perle.com/products/switches/ids-509g-industrial-managed-gigabit-switch.shtml	Industrial Switch: IDS-509G
07016350	IDS-509G-CMS10U-XT Industrial Managed Switch, 9 ports: 8 x 10/100/1000Base-T Base-T RJ-45 ports and 1 x 1000Base-BX, 1310nm TX / 1490nm RX single strand single mode port with simplex (BIDI) SC connector [10km/6.2 miles]. -40 to 75C industrial extended operating temperature. PRO software feature set.	https://www.perle.com/products/switches/ids-509g-industrial-managed-gigabit-switch.shtml	Industrial Switch: IDS-509G
07016360	IDS-509G-CSS10D-XT Industrial Managed Switch, 9 ports: 8 x 10/100/1000Base-T Base-T RJ-45 ports and 1 x 1000Base-BX, 1490nm TX / 1310nm RX single strand single mode port with simplex (BIDI) SC connector [10km/6.2 miles]. -40 to 75C industrial extended operating temperature. PRO software feature set.	https://www.perle.com/products/switches/ids-509g-industrial-managed-gigabit-switch.shtml	Industrial Switch: IDS-509G
07016370	IDS-509PP8 Industrial Managed PoE Switch: 9 x 10/100/1000Base-T Base-T RJ-45 ports, 8 of which are PoE/PoE+ capable. -10 to 60C operating temperature. PRO software feature set.	https://www.perle.com/products/switches/ids-509pp-industrial-managed-poe-switch.shtml	Industrial Switch: IDS-509PP
07016380	IDS-509PP8-XT Industrial Managed PoE Switch: 9 x 10/100/1000Base-T Base-T RJ-45 ports, 8 of which are PoE/PoE+ capable. -40 to 75C operating temperature. PRO software feature set.	https://www.perle.com/products/switches/ids-509pp-industrial-managed-poe-switch.shtml	Industrial Switch: IDS-509PP
07016390	IDS-509F2PP6-C2MD2 Industrial Managed PoE Switch, 9 ports: 7 x 10/100/1000Base-T Base-T RJ-45 ports, of which 6 are PoE/PoE+ capable and 2 x 100Base-FX, 1310nm multimode port with duplex SC connector [up to 5km/3.1 miles]. -10 to 60C operating temperature. PRO software feature set.	https://www.perle.com/products/switches/ids-509fpp-industrial-managed-poe-switch.shtml	Industrial Switch: IDS-509FPP
07016400	IDS-509F2PP6-T2MD2 Industrial Managed PoE Switch, 9 ports: 7 x 10/100/1000Base-T Base-T RJ-45 ports, of which 6 are PoE/PoE+ capable and 2 x 100Base-FX, 1310nm multimode port with duplex ST connector [up to 5km/3.1 miles]. -10 to 60C operating temperature. PRO software feature set.	https://www.perle.com/products/switches/ids-509fpp-industrial-managed-poe-switch.shtml	Industrial Switch: IDS-509FPP
07016410	IDS-509F2PP6-C2SD20 Industrial Managed PoE Switch, 9 ports: 7 x 10/100/1000Base-T Base-T RJ-45 ports, of which 6 are PoE/PoE+ capable and 2 x 100Base-LX, 1310nm single mode port with duplex SC connector [20 km/ 12.4 miles]. -10 to 60C operating temperature. PRO software set.	https://www.perle.com/products/switches/ids-509fpp-industrial-managed-poe-switch.shtml	Industrial Switch: IDS-509FPP

Part #	Description	Product Datasheet	Product Group
07016420	IDS-509F2PP6-T2SD20 Industrial Managed PoE Switch, 9 ports: 7 x 10/100/1000Base-T Base-T RJ-45 ports, of which 6 are PoE/PoE+ capable and 2 x 100Base-LX, 1310nm single mode port with duplex ST connector [20 km/ 12.4 miles]. -10 to 60C operating temperature. PRO software set.	https://www.perle.com/products/switches/ids-509fpp-industrial-managed-poe-switch.shtml	Industrial Switch: IDS-509FPP
07016430	IDS-509F2PP6-C2SD40 Industrial Managed PoE Switch, 9 ports: 7 x 10/100/1000Base-T Base-T RJ-45 ports, of which 6 are PoE/PoE+ capable and 2 x 100Base-LX, 1310nm single mode port with duplex SC connector [40 km/ 24.9 miles]. -10 to 60C operating temperature. PRO software set.	https://www.perle.com/products/switches/ids-509fpp-industrial-managed-poe-switch.shtml	Industrial Switch: IDS-509FPP
07016440	IDS-509F2PP6-T2SD40 Industrial Managed PoE Switch, 9 ports: 7 x 10/100/1000Base-T Base-T RJ-45 ports, of which 6 are PoE/PoE+ capable and 2 x 100Base-LX, 1310nm single mode port with duplex ST connector [40 km/ 24.9 miles]. -10 to 60C operating temperature. PRO software set.	https://www.perle.com/products/switches/ids-509fpp-industrial-managed-poe-switch.shtml	Industrial Switch: IDS-509FPP
07016450	IDS-509F2PP6-C2MD2-XT Industrial Managed PoE Switch, 9 ports: 7 x 10/100/1000Base-T Base-T RJ-45 ports, of which 6 are PoE/PoE+ capable and 2 x 100Base-FX, 1310nm multimode port with duplex SC connector [up to 5km/3.1 miles]. -40 to 75C Industrial extended operating temperature. PRO software feature set.	https://www.perle.com/products/switches/ids-509fpp-industrial-managed-poe-switch.shtml	Industrial Switch: IDS-509FPP
07016460	IDS-509F2PP6-T2MD2-XT Industrial Managed PoE Switch, 9 ports: 7 x 10/100/1000Base-T Base-T RJ-45 ports, of which 6 are PoE/PoE+ capable and 2 x 100Base-FX, 1310nm multimode port with duplex ST connector [up to 5km/3.1 miles]. -40 to 75C Industrial extended operating temperature. PRO software feature set.	https://www.perle.com/products/switches/ids-509fpp-industrial-managed-poe-switch.shtml	Industrial Switch: IDS-509FPP
07016470	IDS-509F2PP6-C2SD20-XT Industrial Managed PoE Switch, 9 ports: 7 x 10/100/1000Base-T Base-T RJ-45 ports, of which 6 are PoE/PoE+ capable and 2 x 100Base-LX, 1310nm single mode port with duplex SC connector [20 km/ 12.4 miles]. -40 to 75C Industrial extended operating temperature. PRO software set.	https://www.perle.com/products/switches/ids-509fpp-industrial-managed-poe-switch.shtml	Industrial Switch: IDS-509FPP
07016480	IDS-509F2PP6-T2SD20-XT Industrial Managed PoE Switch, 9 ports: 7 x 10/100/1000Base-T Base-T RJ-45 ports, of which 6 are PoE/PoE+ capable and 2 x 100Base-LX, 1310nm single mode port with duplex ST connector [20 km/ 12.4 miles]. -40 to 75C Industrial extended operating temperature. PRO software set.	https://www.perle.com/products/switches/ids-509fpp-industrial-managed-poe-switch.shtml	Industrial Switch: IDS-509FPP

Part #	Description	Product Datasheet	Product Group
07016490	IDS-509F2PP6-C2SD40-XT Industrial Managed PoE Switch, 9 ports: 7 x 10/100/1000Base-T Base-T RJ-45 ports, of which 6 are PoE/PoE+ capable and 2 x 100Base-LX, 1310nm single mode port with duplex SC connector [40 km/ 24.9 miles]. -40 to 75C Industrial extended operating temperature. PRO software set.	https://www.perle.com/products/switches/ids-509fpp-industrial-managed-poe-switch.shtml	Industrial Switch: IDS-509FPP
07016500	IDS-509F2PP6-T2SD40-XT Industrial Managed PoE Switch, 9 ports: 7 x 10/100/1000Base-T Base-T RJ-45 ports, of which 6 are PoE/PoE+ capable and 2 x 100Base-LX, 1310nm single mode port with duplex ST connector [40 km/ 24.9 miles]. -40 to 75C Industrial extended operating temperature. PRO software set.	https://www.perle.com/products/switches/ids-509fpp-industrial-managed-poe-switch.shtml	Industrial Switch: IDS-509FPP
07016510	IDS-509G2PP6-C2MD05 Industrial Managed PoE Switch, 9 ports: 7 x 10/100/1000Base-T Base-T RJ-45 ports, of which 6 are PoE/PoE+ capable and 2 x 1000Base-SX, 850nm multimode port with duplex SC connector [550m/1804 ft]. -10 to 60C operating temperature. PRO software feature set.	https://www.perle.com/products/switches/ids-509gpp-industrial-managed-poe-switch.shtml	Industrial Switch: IDS-509GPP
07016520	IDS-509G2PP6-T2MD05 Industrial Managed PoE Switch, 9 ports: 7 x 10/100/1000Base-T Base-T RJ-45 ports, of which 6 are PoE/PoE+ capable and 2 x 1000Base-SX, 850nm multimode port with duplex ST connector [550m/1804 ft]. -10 to 60C operating temperature. PRO software feature set.	https://www.perle.com/products/switches/ids-509gpp-industrial-managed-poe-switch.shtml	Industrial Switch: IDS-509GPP
07016530	IDS-509G2PP6-C2MD2 Industrial Managed PoE Switch, 9 ports: 7 x 10/100/1000Base-T Base-T RJ-45 ports, of which 6 are PoE/PoE+ capable and 2 x 1000Base-LX, 1310nm extended multimode port with duplex SC connector [2km/1.2 miles]. -10 to 60C operating temperature. PRO software feature set.	https://www.perle.com/products/switches/ids-509gpp-industrial-managed-poe-switch.shtml	Industrial Switch: IDS-509GPP
07016540	IDS-509G2PP6-T2MD2 Industrial Managed PoE Switch, 9 ports: 7 x 10/100/1000Base-T Base-T RJ-45 ports, of which 6 are PoE/PoE+ capable and 2 x 1000Base-LX, 1310nm extended multimode port with duplex ST connector [10 km/ 6.2 miles]. -10 to 60C operating temperature. PRO software feature set.	https://www.perle.com/products/switches/ids-509gpp-industrial-managed-poe-switch.shtml	Industrial Switch: IDS-509GPP
07016550	IDS-509G2PP6-C2SD10 Industrial Managed PoE Switch, 9 ports: 7 x 10/100/1000Base-T Base-T RJ-45 ports, of which 6 are PoE/PoE+ capable and 2 x 1000Base-LX/LH, 1310nm single mode port with duplex SC connector [10 km/ 6.2 miles]. -10 to 60C operating temperature. PRO software feature set.	https://www.perle.com/products/switches/ids-509gpp-industrial-managed-poe-switch.shtml	Industrial Switch: IDS-509GPP

Part #	Description	Product Datasheet	Product Group
07016560	IDS-509G2PP6-T2SD10 Industrial Managed PoE Switch, 9 ports: 7 x 10/100/1000Base-T Base-T RJ-45 ports, of which 6 are PoE/PoE+ capable and 2 x 1000Base-LX/LH, 1310nm single mode port with duplex ST connector [10 km/ 6.2 miles]. -10 to 60C operating temperature. PRO software feature set.	https://www.perle.com/products/switches/ids-509gpp-industrial-managed-poe-switch.shtml	Industrial Switch: IDS-509GPP
07016570	IDS-509G2PP6-C2MD05-XT Industrial Managed PoE Switch, 9 ports: 7 x 10/100/1000Base-T Base-T RJ-45 ports, of which 6 are PoE/PoE+ capable and 2 x 1000Base-SX, 850nm multimode port with duplex SC connector [550m/1804 ft]. -40 to 75C Industrial extended operating temperature. PRO software feature set.	https://www.perle.com/products/switches/ids-509gpp-industrial-managed-poe-switch.shtml	Industrial Switch: IDS-509GPP
07016580	IDS-509G2PP6-T2MD05-XT Industrial Managed PoE Switch, 9 ports: 7 x 10/100/1000Base-T Base-T RJ-45 ports, of which 6 are PoE/PoE+ capable and 2 x 1000Base-SX, 850nm multimode port with duplex ST connector [550m/1804 ft]. -40 to 75C Industrial extended operating temperature. PRO software feature set.	https://www.perle.com/products/switches/ids-509gpp-industrial-managed-poe-switch.shtml	Industrial Switch: IDS-509GPP
07016590	IDS-509G2PP6-C2SD10-XT Industrial Managed PoE Switch, 9 ports: 7 x 10/100/1000Base-T Base-T RJ-45 ports, of which 6 are PoE/PoE+ capable and 2 x 1000Base-LX/LH, 1310nm single mode port with duplex SC connector [10 km/ 6.2 miles]. -40 to 75C Industrial extended operating temperature. PRO software feature set.	https://www.perle.com/products/switches/ids-509gpp-industrial-managed-poe-switch.shtml	Industrial Switch: IDS-509GPP
07016600	IDS-509G2PP6-T2SD10-XT Industrial Managed PoE Switch, 9 ports: 7 x 10/100/1000Base-T Base-T RJ-45 ports, of which 6 are PoE/PoE+ capable and 2 x 1000Base-EX, 1310nm single mode port with duplex ST connector [40 km/ 24.9 miles]. -40 to 75C industrial extended operating temperature. PRO software feature set.	https://www.perle.com/products/switches/ids-509gpp-industrial-managed-poe-switch.shtml	Industrial Switch: IDS-509GPP
07016610	IDS-509F3PP6-C2MD2-SD20 Industrial Managed PoE Switch, 9 ports: 6 x 10/100/1000Base-T Base-T RJ-45 ports, all of which are PoE/PoE+ capable and 2 x 100Base-FX, 1310nm multimode port with duplex SC connector [up to 5km/3.1 miles] and 1 x 100Base-LX, 1310nm single mode port with duplex SC connector [20 km/ 12.4 miles]. -10 to 60C operating temperature. PRO software feature set.	https://www.perle.com/products/switches/ids-509fpp-industrial-managed-poe-switch.shtml	Industrial Switch: IDS-509FPP

Part #	Description	Product Datasheet	Product Group
07016620	IDS-509F3PP6-T2MD2-SD20 Industrial Managed PoE Switch, 9 ports: 6 x 10/100/1000Base-T Base-T RJ-45 ports, all of which are PoE/PoE+ capable and 2 x 100Base-FX, 1310nm multimode port with duplex ST connector [up to 5km/3.1 miles] and 1 x 100Base-LX, 1310nm single mode port with duplex ST connector [20 km/ 12.4 miles]. -10 to 60C operating temperature. PRO software feature set.	https://www.perle.com/products/switches/ids-509fpp-industrial-managed-poe-switch.shtml	Industrial Switch: IDS-509FPP
07016630	IDS-509F3PP6-C2MD2-SD40 Industrial Managed PoE Switch, 9 ports: 6 x 10/100/1000Base-T Base-T RJ-45 ports, all of which are PoE/PoE+ capable and 2 x 100Base-FX, 1310nm multimode port with duplex SC connector [up to 5km/3.1 miles] and 1 x 100Base-LX, 1310nm single mode port with duplex SC connector [40 km/ 24.9 miles]. -10 to 60C operating temperature. PRO software feature set.	https://www.perle.com/products/switches/ids-509fpp-industrial-managed-poe-switch.shtml	Industrial Switch: IDS-509FPP
07016640	IDS-509F3PP6-T2MD2-SD40 Industrial Managed PoE Switch, 9 ports: 6 x 10/100/1000Base-T Base-T RJ-45 ports, all of which are PoE/PoE+ capable and 2 x 100Base-FX, 1310nm multimode port with duplex ST connector [up to 5km/3.1 miles] and 1 x 100Base-LX, 1310nm single mode port with duplex ST connector [40 km/ 24.9 miles]. -10 to 60C operating temperature. PRO software feature set.	https://www.perle.com/products/switches/ids-509fpp-industrial-managed-poe-switch.shtml	Industrial Switch: IDS-509FPP
07016650	IDS-509F3PP6-C2MD2-SD80 Industrial Managed PoE Switch, 9 ports: 6 x 10/100/1000Base-T Base-T RJ-45 ports, all of which are PoE/PoE+ capable and 2 x 100Base-FX, 1310nm multimode port with duplex SC connector [up to 5km/3.1 miles] and 1 x 100Base-EX, 1550nm single mode port with duplex SC connector [80 km/ 49.7 miles]. -10 to 60C operating temperature. PRO software feature set.	https://www.perle.com/products/switches/ids-509fpp-industrial-managed-poe-switch.shtml	Industrial Switch: IDS-509FPP
07016660	IDS-509F3PP6-T2MD2-SD80 Industrial Managed PoE Switch, 9 ports: 6 x 10/100/1000Base-T Base-T RJ-45 ports, all of which are PoE/PoE+ capable and 2 x 100Base-FX, 1310nm multimode port with duplex ST connector [up to 5km/3.1 miles] and 1 x 100Base-EX, 1550nm single mode port with duplex ST connector [80 km/ 49.7 miles]. -10 to 60C operating temperature. PRO software feature set.	https://www.perle.com/products/switches/ids-509fpp-industrial-managed-poe-switch.shtml	Industrial Switch: IDS-509FPP

Part #	Description	Product Datasheet	Product Group
07016670	IDS-509F3PP6-C2MD2-SD120 Industrial Managed PoE Switch, 9 ports: 6 x 10/100/1000Base-T Base-T RJ-45 ports, all of which are PoE/PoE+ capable and 2 x 100Base-FX, 1310nm multimode port with duplex SC connector [up to 5km/3.1 miles] and 1 x 100Base-ZX, 1550nm single mode port with duplex SC connector [120 km/ 74.6 miles]. -10 to 60C operating temperature. PRO software feature set.	https://www.perle.com/products/switches/ids-509fpp-industrial-managed-poe-switch.shtml	Industrial Switch: IDS-509FPP
07016680	IDS-509F3PP6-T2MD2-SD120 Industrial Managed PoE Switch, 9 ports: 6 x 10/100/1000Base-T Base-T RJ-45 ports, all of which are PoE/PoE+ capable and 2 x 100Base-FX, 1310nm multimode port with duplex ST connector [up to 5km/3.1 miles] and 1 x 100Base-ZX, 1550nm single mode port with duplex ST connector [120 km/ 74.6 miles]. -10 to 60C operating temperature. PRO software feature set.	https://www.perle.com/products/switches/ids-509fpp-industrial-managed-poe-switch.shtml	Industrial Switch: IDS-509FPP
07016690	IDS-509F3PP6-C2SD20-MD2 Industrial Managed PoE Switch, 9 ports: 6 x 10/100/1000Base-T Base-T RJ-45 ports, all of which are PoE/PoE+ capable and 2 x 100Base-LX, 1310nm single mode port with duplex SC connector [20 km/ 12.4 miles] and 1 x 100Base-FX, 1310nm multimode port with duplex SC connector [up to 5km/3.1 miles]. -10 to 60C operating temperature. PRO software feature set.	https://www.perle.com/products/switches/ids-509fpp-industrial-managed-poe-switch.shtml	Industrial Switch: IDS-509FPP
07016700	IDS-509F3PP6-T2SD20-MD2 Industrial Managed PoE Switch, 9 ports: 6 x 10/100/1000Base-T Base-T RJ-45 ports, all of which are PoE/PoE+ capable and 2 x 100Base-LX, 1310nm single mode port with duplex ST connector [20 km/ 12.4 miles] and 1 x 100Base-FX, 1310nm multimode port with duplex ST connector [up to 5km/3.1 miles]. -10 to 60C operating temperature. PRO software feature set.	https://www.perle.com/products/switches/ids-509fpp-industrial-managed-poe-switch.shtml	Industrial Switch: IDS-509FPP
07016710	IDS-509F3PP6-C2SD20-SD40 Industrial Managed PoE Switch, 9 ports: 6 x 10/100/1000Base-T Base-T RJ-45 ports, all of which are PoE/PoE+ capable and 2 x 100Base-LX, 1310nm single mode port with duplex SC connector [20 km/ 12.4 miles] and 1 x 100Base-LX, 1310nm single mode port with duplex SC connector [40 km/ 24.9 miles]. -10 to 60C operating temperature. PRO software feature set.	https://www.perle.com/products/switches/ids-509fpp-industrial-managed-poe-switch.shtml	Industrial Switch: IDS-509FPP

Part #	Description	Product Datasheet	Product Group
07016720	IDS-509F3PP6-T2SD20-SD40 Industrial Managed PoE Switch, 9 ports: 6 x 10/100/1000Base-T Base-T RJ-45 ports, all of which are PoE/PoE+ capable and 2 x 100Base-LX, 1310nm single mode port with duplex ST connector [20 km/ 12.4 miles] and 1 x 100Base-LX, 1310nm single mode port with duplex ST connector [40 km/ 24.9 miles]. -10 to 60C operating temperature. PRO software feature set.	https://www.perle.com/products/switches/ids-509fpp-industrial-managed-poe-switch.shtml	Industrial Switch: IDS-509FPP
07016730	IDS-509F3PP6-C2SD20-SD80 Industrial Managed PoE Switch, 9 ports: 6 x 10/100/1000Base-T Base-T RJ-45 ports, all of which are PoE/PoE+ capable and 2 x 100Base-LX, 1310nm single mode port with duplex SC connector [20 km/ 12.4 miles] and 1 x 100Base-EX, 1550nm single mode port with duplex SC connector [80 km/ 49.7 miles]. -10 to 60C operating temperature. PRO software feature set.	https://www.perle.com/products/switches/ids-509fpp-industrial-managed-poe-switch.shtml	Industrial Switch: IDS-509FPP
07016740	IDS-509F3PP6-T2SD20-SD80 Industrial Managed PoE Switch, 9 ports: 6 x 10/100/1000Base-T Base-T RJ-45 ports, all of which are PoE/PoE+ capable and 2 x 100Base-LX, 1310nm single mode port with duplex ST connector [20 km/ 12.4 miles] and 1 x 100Base-EX, 1550nm single mode port with duplex ST connector [80 km/ 49.7 miles]. -10 to 60C operating temperature. PRO software feature set.	https://www.perle.com/products/switches/ids-509fpp-industrial-managed-poe-switch.shtml	Industrial Switch: IDS-509FPP
07016750	IDS-509F3PP6-C2SD20-SD120 Industrial Managed PoE Switch, 9 ports: 6 x 10/100/1000Base-T Base-T RJ-45 ports, all of which are PoE/PoE+ capable and 2 x 100Base-LX, 1310nm single mode port with duplex SC connector [20 km/ 12.4 miles] and 1 x 100Base-ZX, 1550nm single mode port with duplex SC connector [120 km/ 74.6 miles]. -10 to 60C operating temperature. PRO software feature set.	https://www.perle.com/products/switches/ids-509fpp-industrial-managed-poe-switch.shtml	Industrial Switch: IDS-509FPP
07016760	IDS-509F3PP6-T2SD20-SD120 Industrial Managed PoE Switch, 9 ports: 6 x 10/100/1000Base-T Base-T RJ-45 ports, all of which are PoE/PoE+ capable and 2 x 100Base-LX, 1310nm single mode port with duplex ST connector [20 km/ 12.4 miles] and 1 x 100Base-ZX, 1550nm single mode port with duplex ST connector [120 km/ 74.6 miles]. -10 to 60C operating temperature. PRO software feature set.	https://www.perle.com/products/switches/ids-509fpp-industrial-managed-poe-switch.shtml	Industrial Switch: IDS-509FPP

Part #	Description	Product Datasheet	Product Group
07016770	IDS-509F3PP6-C2SD40-MD2 Industrial Managed PoE Switch, 9 ports: 6 x 10/100/1000Base-T Base-T RJ-45 ports, all of which are PoE/PoE+ capable and 2 x 100Base-LX, 1310nm single mode port with duplex SC connector [40 km/ 24.9 miles] and 1 x 100Base-FX, 1310nm multimode port with duplex SC connector [up to 5km/3.1 miles]. -10 to 60C operating temperature. PRO software feature set.	https://www.perle.com/products/switches/ids-509fpp-industrial-managed-poe-switch.shtml	Industrial Switch: IDS-509FPP
07016780	IDS-509F3PP6-T2SD40-MD2 Industrial Managed PoE Switch, 9 ports: 6 x 10/100/1000Base-T Base-T RJ-45 ports, all of which are PoE/PoE+ capable and 2 x 100Base-LX, 1310nm single mode port with duplex ST connector [40 km/ 24.9 miles] and 1 x 100Base-FX, 1310nm multimode port with duplex ST connector [up to 5km/3.1 miles]. -10 to 60C operating temperature. PRO software feature set.	https://www.perle.com/products/switches/ids-509fpp-industrial-managed-poe-switch.shtml	Industrial Switch: IDS-509FPP
07016790	IDS-509F3PP6-C2SD40-SD20 Industrial Managed PoE Switch, 9 ports: 6 x 10/100/1000Base-T Base-T RJ-45 ports, all of which are PoE/PoE+ capable and 2 x 100Base-LX, 1310nm single mode port with duplex SC connector [40 km/ 24.9 miles] and 1 x 100Base-LX, 1310nm single mode port with duplex SC connector [20 km/ 12.4 miles]. -10 to 60C operating temperature. PRO software feature set.	https://www.perle.com/products/switches/ids-509fpp-industrial-managed-poe-switch.shtml	Industrial Switch: IDS-509FPP
07016800	IDS-509F3PP6-T2SD40-SD20 Industrial Managed PoE Switch, 9 ports: 6 x 10/100/1000Base-T Base-T RJ-45 ports, all of which are PoE/PoE+ capable and 2 x 100Base-LX, 1310nm single mode port with duplex ST connector [40 km/ 24.9 miles] and 1 x 100Base-LX, 1310nm single mode port with duplex ST connector [20 km/ 12.4 miles]. -10 to 60C operating temperature. PRO software feature set.	https://www.perle.com/products/switches/ids-509fpp-industrial-managed-poe-switch.shtml	Industrial Switch: IDS-509FPP
07016810	IDS-509F3PP6-C2SD40-SD80 Industrial Managed PoE Switch, 9 ports: 6 x 10/100/1000Base-T Base-T RJ-45 ports, all of which are PoE/PoE+ capable and 2 x 100Base-LX, 1310nm single mode port with duplex SC connector [40 km/ 24.9 miles] and 1 x 100Base-EX, 1550nm single mode port with duplex SC connector [80 km/ 49.7 miles]. -10 to 60C operating temperature. PRO software feature set.	https://www.perle.com/products/switches/ids-509fpp-industrial-managed-poe-switch.shtml	Industrial Switch: IDS-509FPP

Part #	Description	Product Datasheet	Product Group
07016820	IDS-509F3PP6-T2SD40-SD80 Industrial Managed PoE Switch, 9 ports: 6 x 10/100/1000Base-T Base-T RJ-45 ports, all of which are PoE/PoE+ capable and 2 x 100Base-LX, 1310nm single mode port with duplex ST connector [40 km/ 24.9 miles] and 1 x 100Base-EX, 1550nm single mode port with duplex ST connector [80 km/ 49.7 miles]. -10 to 60C operating temperature. PRO software feature set.	https://www.perle.com/products/switches/ids-509fpp-industrial-managed-poe-switch.shtml	Industrial Switch: IDS-509FPP
07016830	IDS-509F3PP6-C2SD40-SD120 Industrial Managed PoE Switch, 9 ports: 6 x 10/100/1000Base-T Base-T RJ-45 ports, all of which are PoE/PoE+ capable and 2 x 100Base-LX, 1310nm single mode port with duplex SC connector [40 km/ 24.9 miles] and 1 x 100Base-ZX, 1550nm single mode port with duplex SC connector [120 km/ 74.6 miles]. -10 to 60C operating temperature. PRO software feature set.	https://www.perle.com/products/switches/ids-509fpp-industrial-managed-poe-switch.shtml	Industrial Switch: IDS-509FPP
07016840	IDS-509F3PP6-T2SD40-SD120 Industrial Managed PoE Switch, 9 ports: 6 x 10/100/1000Base-T Base-T RJ-45 ports, all of which are PoE/PoE+ capable and 2 x 100Base-LX, 1310nm single mode port with duplex ST connector [40 km/ 24.9 miles] and 1 x 100Base-ZX, 1550nm single mode port with duplex ST connector [120 km/ 74.6 miles]. -10 to 60C operating temperature. PRO software feature set.	https://www.perle.com/products/switches/ids-509fpp-industrial-managed-poe-switch.shtml	Industrial Switch: IDS-509FPP
07016850	IDS-509F3PP6-C2MD2-SD20-XT Industrial Managed PoE Switch, 9 ports: 6 x 10/100/1000Base-T Base-T RJ-45 ports, all of which are PoE/PoE+ capable and 2 x 100Base-FX, 1310nm multimode port with duplex SC connector [up to 5km/3.1 miles] and 1 x 100Base-LX, 1310nm single mode port with duplex SC connector [20 km/ 12.4 miles]. -40 to 75C Industrial extended operating temperature. PRO software feature set.	https://www.perle.com/products/switches/ids-509fpp-industrial-managed-poe-switch.shtml	Industrial Switch: IDS-509FPP
07016860	IDS-509F3PP6-T2MD2-SD20-XT Industrial Managed PoE Switch, 9 ports: 6 x 10/100/1000Base-T Base-T RJ-45 ports, all of which are PoE/PoE+ capable and 2 x 100Base-FX, 1310nm multimode port with duplex ST connector [up to 5km/3.1 miles] and 1 x 100Base-LX, 1310nm single mode port with duplex ST connector [20 km/ 12.4 miles]. -40 to 75C Industrial extended operating temperature. PRO software feature set.	https://www.perle.com/products/switches/ids-509fpp-industrial-managed-poe-switch.shtml	Industrial Switch: IDS-509FPP

Part #	Description	Product Datasheet	Product Group
07016870	IDS-509F3PP6-C2MD2-SD40-XT Industrial Managed PoE Switch, 9 ports: 6 x 10/100/1000Base-T Base-T RJ-45 ports, all of which are PoE/PoE+ capable and 2 x 100Base-FX, 1310nm multimode port with duplex SC connector [up to 5km/3.1 miles] and 1 x 100Base-LX, 1310nm single mode port with duplex SC connector [40 km/ 24.9 miles]. -40 to 75C Industrial extended operating temperature. PRO software feature set.	https://www.perle.com/products/switches/ids-509fpp-industrial-managed-poe-switch.shtml	Industrial Switch: IDS-509FPP
07016880	IDS-509F3PP6-T2MD2-SD40-XT Industrial Managed PoE Switch, 9 ports: 6 x 10/100/1000Base-T Base-T RJ-45 ports, all of which are PoE/PoE+ capable and 2 x 100Base-FX, 1310nm multimode port with duplex ST connector [up to 5km/3.1 miles] and 1 x 100Base-LX, 1310nm single mode port with duplex ST connector [40 km/ 24.9 miles]. -40 to 75C Industrial extended operating temperature. PRO software feature set.	https://www.perle.com/products/switches/ids-509fpp-industrial-managed-poe-switch.shtml	Industrial Switch: IDS-509FPP
07016890	IDS-509F3PP6-C2SD20-SD40-XT Industrial Managed PoE Switch, 9 ports: 6 x 10/100/1000Base-T Base-T RJ-45 ports, all of which are PoE/PoE+ capable and 2 x 100Base-LX, 1310nm single mode port with duplex SC connector [20 km/ 12.4 miles] and 1 x 100Base-LX, 1310nm single mode port with duplex SC connector [40 km/ 24.9 miles]. -40 to 75C Industrial extended operating temperature. PRO software feature set.	https://www.perle.com/products/switches/ids-509fpp-industrial-managed-poe-switch.shtml	Industrial Switch: IDS-509FPP
07016900	IDS-509F3PP6-T2SD20-SD40-XT Industrial Managed PoE Switch, 9 ports: 6 x 10/100/1000Base-T Base-T RJ-45 ports, all of which are PoE/PoE+ capable and 2 x 100Base-LX, 1310nm single mode port with duplex ST connector [20 km/ 12.4 miles] and 1 x 100Base-LX, 1310nm single mode port with duplex ST connector [40 km/ 24.9 miles]. -40 to 75C Industrial extended operating temperature. PRO software feature set.	https://www.perle.com/products/switches/ids-509fpp-industrial-managed-poe-switch.shtml	Industrial Switch: IDS-509FPP
07016910	IDS-509F3PP6-C2SD40-MD2-XT Industrial Managed PoE Switch, 9 ports: 6 x 10/100/1000Base-T Base-T RJ-45 ports, all of which are PoE/PoE+ capable and 2 x 100Base-LX, 1310nm single mode port with duplex SC connector [40 km/ 24.9 miles] and 1 x 100Base-FX, 1310nm multimode port with duplex SC connector [up to 5km/3.1 miles]. -40 to 75C Industrial extended operating temperature. PRO software feature set.	https://www.perle.com/products/switches/ids-509fpp-industrial-managed-poe-switch.shtml	Industrial Switch: IDS-509FPP

Part #	Description	Product Datasheet	Product Group
07016920	IDS-509F3PP6-T2SD40-MD2-XT Industrial Managed PoE Switch, 9 ports: 6 x 10/100/1000Base-T Base-T RJ-45 ports, all of which are PoE/PoE+ capable and 2 x 100Base-LX, 1310nm single mode port with duplex ST connector [40 km/ 24.9 miles] and 1 x 100Base-FX, 1310nm multimode port with duplex ST connector [up to 5km/3.1 miles]. -40 to 75C Industrial extended operating temperature. PRO software feature set.	https://www.perle.com/products/switches/ids-509fpp-industrial-managed-poe-switch.shtml	Industrial Switch: IDS-509FPP
07016930	IDS-509F3PP6-C2SD40-SD20-XT Industrial Managed PoE Switch, 9 ports: 6 x 10/100/1000Base-T Base-T RJ-45 ports, all of which are PoE/PoE+ capable and 2 x 100Base-LX, 1310nm single mode port with duplex SC connector [40 km/ 24.9 miles] and 1 x 100Base-LX, 1310nm single mode port with duplex SC connector [20 km/ 12.4 miles]. -40 to 75C Industrial extended operating temperature. PRO software feature set.	https://www.perle.com/products/switches/ids-509fpp-industrial-managed-poe-switch.shtml	Industrial Switch: IDS-509FPP
07016940	IDS-509F3PP6-T2SD40-SD20-XT Industrial Managed PoE Switch, 9 ports: 6 x 10/100/1000Base-T Base-T RJ-45 ports, all of which are PoE/PoE+ capable and 2 x 100Base-LX, 1310nm single mode port with duplex ST connector [40 km/ 24.9 miles] and 1 x 100Base-LX, 1310nm single mode port with duplex ST connector [20 km/ 12.4 miles]. -40 to 75C Industrial extended operating temperature. PRO software feature set.	https://www.perle.com/products/switches/ids-509fpp-industrial-managed-poe-switch.shtml	Industrial Switch: IDS-509FPP
07016950	IDS-509G3PP6-C2MD05-SD10 Industrial Managed PoE Switch, 9 ports: 6 x 10/100/1000Base-T Base-T RJ-45 ports, all of which are PoE/PoE+ capable and 2 x 1000Base-SX, 850nm multimode port with duplex SC connector [550m/1804 ft] and 1 x 1000Base-LX/LH, 1310nm single mode port with duplex SC connector [10 km/ 6.2 miles]. -10 to 60C operating temperature. PRO software feature set.	https://www.perle.com/products/switches/ids-509gpp-industrial-managed-poe-switch.shtml	Industrial Switch: IDS-509GPP
07016960	IDS-509G3PP6-T2MD05-SD10 Industrial Managed PoE Switch, 9 ports: 6 x 10/100/1000Base-T Base-T RJ-45 ports, all of which are PoE/PoE+ capable and 2 x 1000Base-SX, 850nm multimode port with duplex ST connector [550m/1804 ft] and 1 x 1000Base-LX/LH, 1310nm single mode port with duplex ST connector [10 km/ 6.2 miles]. -10 to 60C operating temperature. PRO software feature set.	https://www.perle.com/products/switches/ids-509gpp-industrial-managed-poe-switch.shtml	Industrial Switch: IDS-509GPP

Part #	Description	Product Datasheet	Product Group
07016970	IDS-509G3PP6-C2MD05-SD40 Industrial Managed PoE Switch, 9 ports: 6 x 10/100/1000Base-T Base-T RJ-45 ports, all of which are PoE/PoE+ capable and 2 x 1000Base-SX, 850nm multimode port with duplex SC connector [550m/1804 ft] and 1 x 1000Base-EX, 1310nm single mode port with duplex SC connector [40 km/ 24.9 miles]. -10 to 60C operating temperature. PRO software feature set.	https://www.perle.com/products/switches/ids-509gpp-industrial-managed-poe-switch.shtml	Industrial Switch: IDS-509GPP
07016980	IDS-509G3PP6-T2MD05-SD40 Industrial Managed PoE Switch, 9 ports: 6 x 10/100/1000Base-T Base-T RJ-45 ports, all of which are PoE/PoE+ capable and 2 x 1000Base-SX, 850nm multimode port with duplex ST connector [550m/1804 ft] and 1 x 1000Base-EX, 1310nm single mode port with duplex ST connector [40 km/ 24.9 miles]. -10 to 60C operating temperature. PRO software feature set.	https://www.perle.com/products/switches/ids-509gpp-industrial-managed-poe-switch.shtml	Industrial Switch: IDS-509GPP
07016990	IDS-509G3PP6-C2MD05-SD70 Industrial Managed PoE Switch, 9 ports: 6 x 10/100/1000Base-T Base-T RJ-45 ports, all of which are PoE/PoE+ capable and 2 x 1000Base-SX, 850nm multimode port with duplex SC connector [550m/1804 ft] and 1 x 1000Base-ZX, 1550nm single mode port with duplex SC connector [70 km/ 43.5 miles]. -10 to 60C operating temperature. PRO software feature set.	https://www.perle.com/products/switches/ids-509gpp-industrial-managed-poe-switch.shtml	Industrial Switch: IDS-509GPP
07017000	IDS-509G3PP6-T2MD05-SD70 Industrial Managed PoE Switch, 9 ports: 6 x 10/100/1000Base-T Base-T RJ-45 ports, all of which are PoE/PoE+ capable and 2 x 1000Base-SX, 850nm multimode port with duplex ST connector [550m/1804 ft] and 1 x 1000Base-ZX, 1550nm single mode port with duplex ST connector [70 km/ 43.5 miles]. -10 to 60C operating temperature. PRO software feature set.	https://www.perle.com/products/switches/ids-509gpp-industrial-managed-poe-switch.shtml	Industrial Switch: IDS-509GPP
07017010	IDS-509G3PP6-C2MD05-SD120 Industrial Managed PoE Switch, 9 ports: 6 x 10/100/1000Base-T Base-T RJ-45 ports, all of which are PoE/PoE+ capable and 2 x 1000Base-SX, 850nm multimode port with duplex SC connector [550m/1804 ft] and 1 x 1000Base-ZX, 1550nm single mode port with duplex SC connector [120 km/ 74.6 miles]. -10 to 60C operating temperature. PRO software feature set.	https://www.perle.com/products/switches/ids-509gpp-industrial-managed-poe-switch.shtml	Industrial Switch: IDS-509GPP

Part #	Description	Product Datasheet	Product Group
07017020	IDS-509G3PP6-T2MD05-SD120 Industrial Managed PoE Switch, 9 ports: 6 x 10/100/1000Base-T Base-T RJ-45 ports, all of which are PoE/PoE+ capable and 2 x 1000Base-SX, 850nm multimode port with duplex ST connector [550m/1804 ft] and 1 x 1000Base-ZX, 1550nm single mode port with duplex ST connector [120 km/ 74.6 miles]. -10 to 60C operating temperature. PRO software feature set.	https://www.perle.com/products/switches/ids-509gpp-industrial-managed-poe-switch.shtml	Industrial Switch: IDS-509GPP
07017030	IDS-509G3PP6-C2MD05-SD160 Industrial Managed PoE Switch, 9 ports: 6 x 10/100/1000Base-T Base-T RJ-45 ports, all of which are PoE/PoE+ capable and 2 x 1000Base-SX, 850nm multimode port with duplex SC connector [550m/1804 ft] and 1 x 1000Base-ZX, 1550nm single mode port with duplex SC connector [160 km/ 100 miles]. -10 to 60C operating temperature. PRO software feature set.	https://www.perle.com/products/switches/ids-509gpp-industrial-managed-poe-switch.shtml	Industrial Switch: IDS-509GPP
07017040	IDS-509G3PP6-T2MD05-SD160 Industrial Managed PoE Switch, 9 ports: 6 x 10/100/1000Base-T Base-T RJ-45 ports, all of which are PoE/PoE+ capable and 2 x 1000Base-SX, 850nm multimode port with duplex ST connector [550m/1804 ft] and 1 x 1000Base-ZX, 1550nm single mode port with duplex ST connector [160 km/ 100 miles]. -10 to 60C operating temperature. PRO software feature set.	https://www.perle.com/products/switches/ids-509gpp-industrial-managed-poe-switch.shtml	Industrial Switch: IDS-509GPP
07017050	IDS-509G3PP6-C2SD10-MD05 Industrial Managed PoE Switch, 9 ports: 6 x 10/100/1000Base-T Base-T RJ-45 ports, all of which are PoE/PoE+ capable and 2 x 1000Base-LX/LH, 1310nm single mode port with duplex SC connector [10 km/ 6.2 miles] and 1 x 1000Base-SX, 850nm multimode port with duplex SC connector [550m/1804 ft]. -10 to 60C operating temperature. PRO software feature set.	https://www.perle.com/products/switches/ids-509gpp-industrial-managed-poe-switch.shtml	Industrial Switch: IDS-509GPP
07017060	IDS-509G3PP6-T2SD10-MD05 Industrial Managed PoE Switch, 9 ports: 6 x 10/100/1000Base-T Base-T RJ-45 ports, all of which are PoE/PoE+ capable and 2 x 1000Base-LX/LH, 1310nm single mode port with duplex ST connector [10 km/ 6.2 miles] and 1 x 1000Base-SX, 850nm multimode port with duplex ST connector [550m/1804 ft]. -10 to 60C operating temperature. PRO software feature set.	https://www.perle.com/products/switches/ids-509gpp-industrial-managed-poe-switch.shtml	Industrial Switch: IDS-509GPP

Part #	Description	Product Datasheet	Product Group
07017070	IDS-509G3PP6-C2SD10-SD40 Industrial Managed PoE Switch, 9 ports: 6 x 10/100/1000Base-T Base-T RJ-45 ports, all of which are PoE/PoE+ capable and 2 x 1000Base-LX/LH, 1310nm single mode port with duplex SC connector [10 km/ 6.2 miles] and 1 x 1000Base-EX, 1310nm single mode port with duplex SC connector [40 km/ 24.9 miles]. -10 to 60C operating temperature. PRO software feature set.	https://www.perle.com/products/switches/ids-509gpp-industrial-managed-poe-switch.shtml	Industrial Switch: IDS-509GPP
07017080	IDS-509G3PP6-T2SD10-SD40 Industrial Managed PoE Switch, 9 ports: 6 x 10/100/1000Base-T Base-T RJ-45 ports, all of which are PoE/PoE+ capable and 2 x 1000Base-LX/LH, 1310nm single mode port with duplex ST connector [10 km/ 6.2 miles] and 1 x 1000Base-EX, 1310nm single mode port with duplex ST connector [40 km/ 24.9 miles]. -10 to 60C operating temperature. PRO software feature set.	https://www.perle.com/products/switches/ids-509gpp-industrial-managed-poe-switch.shtml	Industrial Switch: IDS-509GPP
07017090	IDS-509G3PP6-C2SD10-SD70 Industrial Managed PoE Switch, 9 ports: 6 x 10/100/1000Base-T Base-T RJ-45 ports, all of which are PoE/PoE+ capable and 2 x 1000Base-LX/LH, 1310nm single mode port with duplex SC connector [10 km/ 6.2 miles] and 1 x 1000Base-ZX, 1550nm single mode port with duplex SC connector [70 km/ 43.5 miles]. -10 to 60C operating temperature. PRO software feature set.	https://www.perle.com/products/switches/ids-509gpp-industrial-managed-poe-switch.shtml	Industrial Switch: IDS-509GPP
07017100	IDS-509G3PP6-T2SD10-SD70 Industrial Managed PoE Switch, 9 ports: 6 x 10/100/1000Base-T Base-T RJ-45 ports, all of which are PoE/PoE+ capable and 2 x 1000Base-LX/LH, 1310nm single mode port with duplex ST connector [10 km/ 6.2 miles] and 1 x 1000Base-ZX, 1550nm single mode port with duplex ST connector [70 km/ 43.5 miles]. -10 to 60C operating temperature. PRO software feature set.	https://www.perle.com/products/switches/ids-509gpp-industrial-managed-poe-switch.shtml	Industrial Switch: IDS-509GPP
07017110	IDS-509G3PP6-C2SD10-SD120 Industrial Managed PoE Switch, 9 ports: 6 x 10/100/1000Base-T Base-T RJ-45 ports, all of which are PoE/PoE+ capable and 2 x 1000Base-LX/LH, 1310nm single mode port with duplex SC connector [10 km/ 6.2 miles] and 1 x 1000Base-ZX, 1550nm single mode port with duplex SC connector [120 km/ 74.6 miles]. -10 to 60C operating temperature. PRO software feature set.	https://www.perle.com/products/switches/ids-509gpp-industrial-managed-poe-switch.shtml	Industrial Switch: IDS-509GPP

Part #	Description	Product Datasheet	Product Group
07017120	IDS-509G3PP6-T2SD10-SD120 Industrial Managed PoE Switch, 9 ports: 6 x 10/100/1000Base-T Base-T RJ-45 ports, all of which are PoE/PoE+ capable and 2 x 1000Base-LX/LH, 1310nm single mode port with duplex ST connector [10 km/ 6.2 miles] and 1 x 1000Base-ZX, 1550nm single mode port with duplex ST connector [120 km/ 74.6 miles]. -10 to 60C operating temperature. PRO software feature set.	https://www.perle.com/products/switches/ids-509gpp-industrial-managed-poe-switch.shtml	Industrial Switch: IDS-509GPP
07017130	IDS-509G3PP6-C2SD10-SD160 Industrial Managed PoE Switch, 9 ports: 6 x 10/100/1000Base-T Base-T RJ-45 ports, all of which are PoE/PoE+ capable and 2 x 1000Base-LX/LH, 1310nm single mode port with duplex SC connector [10 km/ 6.2 miles] and 1 x 1000Base-ZX, 1550nm single mode port with duplex SC connector [160 km/ 100 miles]. -10 to 60C operating temperature. PRO software feature set.	https://www.perle.com/products/switches/ids-509gpp-industrial-managed-poe-switch.shtml	Industrial Switch: IDS-509GPP
07017140	IDS-509G3PP6-T2SD10-SD160 Industrial Managed PoE Switch, 9 ports: 6 x 10/100/1000Base-T Base-T RJ-45 ports, all of which are PoE/PoE+ capable and 2 x 1000Base-LX/LH, 1310nm single mode port with duplex ST connector [10 km/ 6.2 miles] and 1 x 1000Base-ZX, 1550nm single mode port with duplex ST connector [160 km/ 100 miles]. -10 to 60C operating temperature. PRO software feature set.	https://www.perle.com/products/switches/ids-509gpp-industrial-managed-poe-switch.shtml	Industrial Switch: IDS-509GPP
07017150	IDS-509G3PP6-C2MD05-SD10-XT Industrial Managed PoE Switch, 9 ports: 6 x 10/100/1000Base-T Base-T RJ-45 ports, all of which are PoE/PoE+ capable and 2 x 1000Base-SX, 850nm multimode port with duplex SC connector [550m/1804 ft] and 1 x 1000Base-LX/LH, 1310nm single mode port with duplex SC connector [10 km/ 6.2 miles]. -40 to 75C Industrial extended operating temperature. PRO software feature set.	https://www.perle.com/products/switches/ids-509gpp-industrial-managed-poe-switch.shtml	Industrial Switch: IDS-509GPP
07017160	IDS-509G3PP6-T2MD05-SD10-XT Industrial Managed PoE Switch, 9 ports: 6 x 10/100/1000Base-T Base-T RJ-45 ports, all of which are PoE/PoE+ capable and 2 x 1000Base-SX, 850nm multimode port with duplex ST connector [550m/1804 ft] and 1 x 1000Base-LX/LH, 1310nm single mode port with duplex ST connector [10 km/ 6.2 miles]. -40 to 75C Industrial extended operating temperature. PRO software feature set.	https://www.perle.com/products/switches/ids-509gpp-industrial-managed-poe-switch.shtml	Industrial Switch: IDS-509GPP

Part #	Description	Product Datasheet	Product Group
07017170	IDS-509G3PP6-C2SD10-MD05-XT Industrial Managed PoE Switch, 9 ports: 6 x 10/100/1000Base-T Base-T RJ-45 ports, all of which are PoE/PoE+ capable and 2 x 1000Base-LX/LH, 1310nm single mode port with duplex SC connector [10 km/ 6.2 miles] and 1 x 1000Base-SX, 850nm multimode port with duplex SC connector [550m/1804 ft]. -40 to 75C Industrial extended operating temperature. PRO software feature set.	https://www.perle.com/products/switches/ids-509gpp-industrial-managed-poe-switch.shtml	Industrial Switch: IDS-509GPP
07017180	IDS-509G3PP6-T2SD10-MD05-XT Industrial Managed PoE Switch, 9 ports: 6 x 10/100/1000Base-T Base-T RJ-45 ports, all of which are PoE/PoE+ capable and 2 x 1000Base-LX/LH, 1310nm single mode port with duplex ST connector [10 km/ 6.2 miles] and 1 x 1000Base-SX, 850nm multimode port with duplex ST connector [550m/1804 ft]. -40 to 75C Industrial extended operating temperature. PRO software feature set.	https://www.perle.com/products/switches/ids-509gpp-industrial-managed-poe-switch.shtml	Industrial Switch: IDS-509GPP
07017190	IDS-509CPP Industrial Managed Switch, 9 ports: 8 x 10/100/1000Base-T Base-T RJ-45 ports, 8 of which are all PoE/PoE+ capable, 3 of which are (100 Mbps and 1 Gbps) dual-purpose Combo ports (SFP or RJ45 PoE) plus 1 x dedicated (100 and 1000 Gbps) SFP slot. -10 to 60C operating temperature. PRO software feature set.	https://www.perle.com/products/switches/ids-509cpp-industrial-managed-poe-switch.shtml	Industrial Switch: IDS-509CPP
07017200	IDS-509CPP-XT Industrial Managed Switch, 9 ports: 8 x 10/100/1000Base-T Base-T RJ-45 ports, 8 of which are all PoE/PoE+ capable, 3 of which are (100 Mbps and 1 Gbps) dual-purpose Combo ports (SFP or RJ45 PoE) plus 1 x dedicated (100 and 1000 Gbps) SFP slot. -40 to 75C Industrial extended operating temperature. PRO software feature set.	https://www.perle.com/products/switches/ids-509cpp-industrial-managed-poe-switch.shtml	Industrial Switch: IDS-509CPP
10040658	INJ 2103-T DIN Rail PoE+ Injector with surge protection: 30 W PoE+ compliant, 1 x RJ45 socket, 1 x Push-in terminal block, 10/100/1000 Mbps, IP20, potential separation, shield contacting with strain relief, shield current monitoring	https://www.perle.com/products/poe-injectors/din-rail-inj-2100-t.shtml	PoE Injector
10040668	INJ 2113-T DIN Rail Hi-PoE Injector with surge protection: 60 W Type 3 Hi-PoE compliant, 1 x RJ45 socket, 1 x Push-in terminal block, 10/100/1000 Mbps, IP20, potential separation, shield contacting with strain relief, shield current monitoring	https://www.perle.com/products/poe-injectors/din-rail-inj-2100-t.shtml	PoE Injector
22038528	DIN rail connector, UL 8A / cUL 6A, 150 V, Data & Power Pin positions: 4P+1S, width 22.5, color: black - Pack of 5 TBUS connectors	https://www.perle.com/products/product_detail.asp?a=4&i=22038528&c=1335	Accessories: DIN Rail
2300236	AC EU WALL MOUNT ADAPT TL 24VDC, 18W wall power adapter with tinned leads - 0 to 60C. For use with TC EXTENDER, PSI-MOS Converters, PSM-ME Isolator, PSM-ME Converter and PSM-ME Repeater	https://www.perle.com/products/product_detail.asp?a=4&i=2300236&c=1295	Power Supplies

Part #	Description	Product Datasheet	Product Group
23136692	PSI-MODEM-SHDSL/SERIAL - Long Range Serial Extender: RS-232 DB9M, RS422/485 terminal block. Dual (SHDSL) connectors on 2-pin terminal blocks. Links up to 20km – 24VDC EU wall power adapter included	https://www.perle.com/products/serial-extenders/psi-modem-shdsl-serial-extender.shtml	Serial Extender: PSI-MODEM-SHDSL
23136698	PSI-MODEM-SHDSL/SERIAL - Long Range Serial Extender - RS-232 DB9M, RS-422/485 terminal block. Dual (SHDSL) connectors on 2-pin terminal blocks. Links up to 20km	https://www.perle.com/products/serial-extenders/psi-modem-shdsl-serial-extender.shtml	Serial Extender: PSI-MODEM-SHDSL
23200348	QUINT-PS/24DC/24DC/5 Power Supply - QUINT DC/DC converter for DIN rail mounting with SFB (Selective Fuse Breaking) Technology, input: 24 V DC, output: 24 V DC/5 A	https://www.perle.com/products/industrial-power-supply/quint-ps-24dc-24dc-5-23200348.shtml	Power Supplies
23200928	QUINT-PS/24DC/24DC/10 Power Supply - QUINT DC/DC converter for DIN rail mounting with SFB (Selective Fuse Breaking) Technology, input: 24 V DC, output: 24 V DC/10 A	https://www.perle.com/products/industrial-power-supply/quint-ps-24dc-24dc-10-23200928.shtml	Power Supplies
23201028	QUINT-PS/24DC/24DC/20 Power Supply - QUINT DC/DC converter for DIN rail mounting with SFB (Selective Fuse Breaking) Technology, input: 24 V DC, output: 24 V DC/20 A	https://www.perle.com/products/industrial-power-supply/quint-ps-24dc-24dc-20-23201028.shtml	Power Supplies
23201158	QUINT-PS/24DC/12DC/8 Power Supply - QUINT DC/DC converter for DIN rail mounting with SFB (Selective Fuse Breaking) Technology, input: 24 V DC, output: 12 V DC/8 A	https://www.perle.com/products/industrial-power-supply/quint-ps-24dc-12dc-8-23201158.shtml	Power Supplies
23201288	QUINT-PS/24DC/48DC/5 Power Supply - QUINT DC/DC converter for DIN rail mounting with SFB (Selective Fuse Breaking) Technology, input: 24 V DC, output: 48 V DC/5 A	https://www.perle.com/products/industrial-power-supply/quint-ps-24dc-48dc-5-23201288.shtml	Power Supplies
23201318	QUINT-PS/12DC/24DC/5 Power Supply - QUINT DC/DC converter for DIN rail mounting with SFB (Selective Fuse Breaking) Technology, input: 12 V DC, output: 24 V DC/5 A	https://www.perle.com/products/industrial-power-supply/quint-ps-12dc-24dc-5-23201318.shtml	Power Supplies
23201448	QUINT-PS/48DC/24DC/5 Power Supply - QUINT DC/DC converter for DIN rail mounting with SFB (Selective Fuse Breaking) Technology, input: 48 V DC, output: 24 V DC/5 A	https://www.perle.com/products/industrial-power-supply/quint-ps-48dc-24dc-5-23201448.shtml	Power Supplies
23205138	STEP-PS/1AC/5DC/2 Power Supply - STEP power supply for DIN rail mounting, input: 1-phase, output: 5 V DC/2 A	https://www.perle.com/products/industrial-power-supply/step-ps-1ac-5dc-2-23205138.shtml	Power Supplies
23205428	QUINT-PS/24DC/24DC/5/CO Power Supply - QUINT DC/DC converter for DIN rail mounting with SFB (Selective Fuse Breaking) Technology, with protective coating, input: 24 V DC, output: 24 V DC/5 A	https://www.perle.com/products/industrial-power-supply/quint-ps-24dc-24dc-5-co-23205428.shtml	Power Supplies

Part #	Description	Product Datasheet	Product Group
23205558	QUINT-PS/24DC/24DC/10/CO Power Supply - QUINT DC/DC converter for DIN rail mounting with SFB (Selective Fuse Breaking) Technology, with protective coating, input: 24 V DC, output: 24 V DC/10 A	https://www.perle.com/products/industrial-power-supply/quint-ps-24dc-24dc-10-co-23205558.shtml	Power Supplies
23205688	QUINT-PS/24DC/24DC/20/CO Power Supply - QUINT DC/DC converter for DIN rail mounting with SFB (Selective Fuse Breaking) Technology, with protective coating, input: 24 V DC, output: 24 V DC/20 A	https://www.perle.com/products/industrial-power-supply/quint-ps-24dc-24dc-20-co-23205688.shtml	Power Supplies
23208278	QUINT-PS/3AC/48DC/20 Power Supply - QUINT power supply for DIN rail mounting with SFB (Selective Fuse Breaking) Technology, input: 3-phase, output: 48 V DC/20 A	https://www.perle.com/products/industrial-power-supply/quint-3-phase.shtml	Power Supplies
23208308	QUINT-PS/2AC/1DC/24DC/20 Power Supply - QUINT power supply DIN Rail unit. AC input: suitable for operation between two phases (400 V AC). DC input: suitable for operation in an FI intermediate circuit. Output: 24 V DC/20 A	https://www.perle.com/products/industrial-power-supply/quint-high-input.shtml	Power Supplies
23208988	QUINT-PS/1AC/24DC/20/CO Power Supply - QUINT power supply for DIN rail mounting with SFB (Selective Fuse Breaking) Technology, with protective coating, input: 1-phase, output: 24 V DC/20 A	https://www.perle.com/products/industrial-power-supply/quint-1-phase-xt.shtml	Power Supplies
23209088	QUINT-PS/1AC/24DC/5/CO Power Supply - QUINT power supply for DIN rail mounting with SFB (Selective Fuse Breaking) Technology, with protective coating, input: 1-phase, output: 24 V DC/5 A	https://www.perle.com/products/industrial-power-supply/quint-1-phase-xt.shtml	Power Supplies
23209118	QUINT-PS/1AC/24DC/10/CO Power Supply - QUINT power supply for DIN rail mounting with SFB (Selective Fuse Breaking) Technology, with protective coating, input: 1-phase, output: 24 V DC/10 A	https://www.perle.com/products/industrial-power-supply/quint-1-phase-xt.shtml	Power Supplies
23209248	QUINT-PS/3AC/24DC/20/CO Power Supply - QUINT power supply for DIN rail mounting with SFB (Selective Fuse Breaking) Technology, with protective coating, input: 3-phase, output: 24 V DC/20 A	https://www.perle.com/products/industrial-power-supply/quint-3-phase-xt.shtml	Power Supplies
27024092	TC EXTENDER 2001 ETH-2S Long Range Fast Ethernet Extender: 1 port 10/100Base-TX (RJ-45). SHDSL via 4-pin terminal blocks. Links up to 20km. 24VDC, 18W EU wall power adapter with tinned leads included.	https://www.perle.com/products/ethernet-extenders/tc-extender-2001-eth-2s.shtml	Ethernet Extender: TC EXTENDER
27024098	TC EXTENDER 2001 ETH-2S Long Range Fast Ethernet Extender: 1 port 10/100Base-TX (RJ-45). SHDSL via 4-pin terminal blocks. Links up to 20km.	https://www.perle.com/products/ethernet-extenders/tc-extender-2001-eth-2s.shtml	Ethernet Extender: TC EXTENDER
27030058	INJ 1000 DIN Rail PoE Injector: 30 W PoE+ compliant, two RJ45 sockets, 10/100/1000 Mbps, IP20	https://www.perle.com/products/poe-injectors/din-rail-inj-1000.shtml	PoE Injector
27030068	INJ 1000-T DIN Rail PoE Injector: 30 W PoE+ compliant , two RJ45 sockets, 10/100/1000 Mbps, IP20, expanded temperature range of -40°C ... 75°C	https://www.perle.com/products/poe-injectors/din-rail-inj-1000.shtml	PoE Injector

Part #	Description	Product Datasheet	Product Group
27030078	INJ 1010 DIN Rail PoE Injector: 60 W Type 3 Hi-PoE compliant, two RJ45 sockets, 10/100/1000 Mbps, IP20	https://www.perle.com/products/poe-injectors/din-rail-inj-1000.shtml	PoE Injector
27030088	INJ 1010-T DIN Rail PoE Injector: 60 W Type 3 Hi-PoE compliant, two RJ45 sockets, 10/100/1000 Mbps, IP20, expanded temperature range of -40°C ... 75°C	https://www.perle.com/products/poe-injectors/din-rail-inj-1000.shtml	PoE Injector
27030098	INJ 1100-T DIN Rail PoE Injector with electrical isolation: 30 W PoE+ compliant, two RJ45 sockets, 10/100/1000 Mbps, IP20, expanded temperature range of -40°C ... 75°C, potential separation	https://www.perle.com/products/poe-injectors/din-rail-inj-1100-t.shtml	PoE Injector
27030108	INJ 1110-T DIN Rail PoE Injector with electrical isolation: 60 W Type 3 Hi-PoE compliant, two RJ45 sockets, 10/100/1000 Mbps, IP20, expanded temperature range of -40°C ... 75°C, potential separation	https://www.perle.com/products/poe-injectors/din-rail-inj-1100-t.shtml	PoE Injector
27030118	INJ 2101-T DIN Rail PoE+ Injector with surge protection: 30 W PoE+ compliant, 1 x RJ45 socket, 1 x screw terminal block, 10/100/1000 Mbps, IP20, potential separation, shield contacting with strain relief, shield current monitoring	https://www.perle.com/products/poe-injectors/din-rail-inj-2100-t.shtml	PoE Injector
27030128	INJ 2102-T DIN Rail PoE+ Injector with surge protection: 30 W PoE+ compliant, 1 x RJ45 socket, 1 x IDC terminal block, 10/100/1000 Mbps, IP20, potential separation, shield contacting with strain relief, shield current monitoring	https://www.perle.com/products/poe-injectors/din-rail-inj-2100-t.shtml	PoE Injector
27030138	INJ 2111-T DIN Rail Hi-PoE Injector with surge protection: 60 W Type 3 Hi-PoE compliant, 1 x RJ45 socket, 1 x screw terminal block, 10/100/1000 Mbps, IP20, potential separation, shield contacting with strain relief, shield current monitoring	https://www.perle.com/products/poe-injectors/din-rail-inj-2100-t.shtml	PoE Injector
27030148	INJ 2112-T DIN Rail Hi-PoE Injector with surge protection: 60 W Type 3 Hi-PoE compliant, 1 x RJ45 socket, 1 x IDC terminal block, 10/100/1000 Mbps, IP20, potential separation, shield contacting with strain relief, shield current monitoring	https://www.perle.com/products/poe-injectors/din-rail-inj-2100-t.shtml	PoE Injector
27030158	PP-RJ-RJ DIN Rail Patch Panel: two RJ45 sockets, 10/100/1000 Mbps, IP20	https://www.perle.com/products/patch-panels/din-rail-pp-rj.shtml	Patch Panel
27030168	PP-RJ-SC DIN Rail Patch Panel: 1 x RJ45 socket, 1 x screw terminal block, 10/100/1000 Mbps, IP20, shield contacting with strain relief	https://www.perle.com/products/patch-panels/din-rail-pp-rj.shtml	Patch Panel
27030188	PP-RJ-SCC DIN Rail Patch Panel: 1 x RJ45 socket, 1 x Push-in terminal block, 10/100/1000 Mbps, IP20, shield contacting with strain relief	https://www.perle.com/products/patch-panels/din-rail-pp-rj.shtml	Patch Panel
27030198	PP-RJ-IDC DIN Rail Patch Panel: 1 x RJ45 socket, 1 x IDC terminal block, 10/100/1000 Mbps, IP20, shield contacting with strain relief	https://www.perle.com/products/patch-panels/din-rail-pp-rj.shtml	Patch Panel

Part #	Description	Product Datasheet	Product Group
27030208	PP-RJ-RJ-F DIN Rail Patch Panel with surge protection: two RJ45 sockets, 10/100/1000 Mbps, IP20, shield current monitoring	https://www.perle.com/products/patch-panels/din-rail-pp-rj-f.shtml	Patch Panel
27030218	PP-RJ-SC-F DIN Rail Patch Panel with surge protection: 1 x RJ45 socket, 1 x screw terminal block, 10/100/1000 Mbps, IP20, shield contacting with strain relief, shield current monitoring	https://www.perle.com/products/patch-panels/din-rail-pp-rj-f.shtml	Patch Panel
27030228	PP-RJ-SCC-F DIN Rail Patch Panel with surge protection: 1 x RJ45 socket, 1 x Push-in terminal block, 10/100/1000 Mbps, IP20, shield contacting with strain relief, shield current monitoring	https://www.perle.com/products/patch-panels/din-rail-pp-rj-f.shtml	Patch Panel
27030238	PP-RJ-IDC-F DIN Rail Patch Panel with surge protection: 1 x RJ45 socket, 1 x IDC terminal block, 10/100/1000 Mbps, IP20, shield contacting with strain relief, shield current monitoring	https://www.perle.com/products/patch-panels/din-rail-pp-rj-f.shtml	Patch Panel
27083262	PSI-MOS-RS485W2/FO 850 T - RS485 2-wire to fiber Converter: Terminal block serial to 2x duplex fiber multimode 850nm (ST) [4.2km, 2.6 miles] – 24VDC EU wall power adapter included	https://www.perle.com/products/serial-fiber-converters/psi-mos-rs484w2-fo850t-rs485-to-dual-fiber.shtml	Serial Extender: PSI-MOS Serial to Fiber
27083268	PSI-MOS-RS485W2/FO 850 T - RS485 2-wire to fiber Converter: Terminal block serial to 2x duplex fiber multimode 850nm (ST) [4.2km, 2.6 miles]	https://www.perle.com/products/serial-fiber-converters/psi-mos-rs484w2-fo850t-rs485-to-dual-fiber.shtml	Serial Extender: PSI-MOS Serial to Fiber
27083392	PSI-MOS-RS485W2/FO 850 E - RS485 2-wire to fiber Converter: Terminal block serial to duplex fiber multimode 850nm (ST) [4.2km, 2.6 miles] – 24VDC EU wall power adapter included	https://www.perle.com/products/serial-fiber-converters/psi-mos-rs485w2-fo850e-rs485-to-fiber.shtml	Serial Extender: PSI-MOS Serial to Fiber
27083398	PSI-MOS-RS485W2/FO 850 E - RS485 2-wire to fiber Converter: Terminal block serial to duplex fiber multimode 850nm (ST) [4.2km, 2.6 miles]	https://www.perle.com/products/serial-fiber-converters/psi-mos-rs485w2-fo850e-rs485-to-fiber.shtml	Serial Extender: PSI-MOS Serial to Fiber
27083552	PSI-MOS-RS422/FO 850 E - RS422/485 4-wire to fiber Converter: Terminal block serial to duplex fiber multimode 850nm (ST) [4.2km, 2.6 miles] – 24VDC EU wall power adapter included	https://www.perle.com/products/serial-fiber-converters/psi-mos-rs422-fo850e-rs422-to-fiber.shtml	Serial Extender: PSI-MOS Serial to Fiber
27083558	PSI-MOS-RS422/FO 850 E - RS422/485 4-wire to fiber Converter: Terminal block serial to duplex fiber multimode 850nm (ST) [4.2km, 2.6 miles]	https://www.perle.com/products/serial-fiber-converters/psi-mos-rs422-fo850e-rs422-to-fiber.shtml	Serial Extender: PSI-MOS Serial to Fiber
27083712	PSI-MOS-RS232/FO 850 E - RS232 to fiber Converter: DB9M serial to duplex fiber multimode 850nm (ST) [4.2km, 2.6 miles] – 24VDC EU wall power adapter included	https://www.perle.com/products/serial-fiber-converters/psi-mos-rs232-fo850e-rs232-to-fiber.shtml	Serial Extender: PSI-MOS Serial to Fiber
27083718	PSI-MOS-RS232/FO 850 E - RS232 to fiber Converter: DB9M serial to duplex fiber multimode 850nm (ST) [4.2km, 2.6 miles]	https://www.perle.com/products/serial-fiber-converters/psi-mos-rs232-fo850e-rs232-to-fiber.shtml	Serial Extender: PSI-MOS Serial to Fiber

Part #	Description	Product Datasheet	Product Group
27083972	PSI-MOS-RS422/FO 850 T - RS422/485 4-wire to fiber Converter: Terminal block serial to 2x duplex fiber multimode 850nm (ST) [4.2km, 2.6 miles]– 24VDC EU wall power adapter included	https://www.perle.com/products/serial-fiber-converters/psi-mos-rs422-fo850t-rs422-to-dual-fiber.shtml	Serial Extender: PSI-MOS Serial to Fiber
27083978	PSI-MOS-RS422/FO 850 T - RS422/485 4-wire to fiber Converter: Terminal block serial to 2x duplex fiber multimode 850nm (ST) [4.2km, 2.6 miles]	https://www.perle.com/products/serial-fiber-converters/psi-mos-rs422-fo850t-rs422-to-dual-fiber.shtml	Serial Extender: PSI-MOS Serial to Fiber
27084232	PSI-MOS-RS232/FO 850 T - RS232 to fiber Converter: DB9M serial to 2x duplex fiber multimode 850nm (ST) [4.2km, 2.6 miles]– 24VDC EU wall power adapter included	https://www.perle.com/products/serial-fiber-converters/psi-mos-rs232-fo850t-rs232-to-dual-fiber.shtml	Serial Extender: PSI-MOS Serial to Fiber
27084238	PSI-MOS-RS232/FO 850 T - RS232 to fiber Converter: DB9M serial to 2x duplex fiber multimode 850nm (ST) [4.2km, 2.6 miles]	https://www.perle.com/products/serial-fiber-converters/psi-mos-rs232-fo850t-rs232-to-dual-fiber.shtml	Serial Extender: PSI-MOS Serial to Fiber
27085622	PSI-MOS-RS485W2/FO1300 E - RS485 2-wire to fiber Converter: Terminal block serial to duplex fiber 1300nm (SC). Multimode [27km, 16.7 miles], single mode [45km, 28 miles] – 24VDC EU wall power adapter included	https://www.perle.com/products/serial-fiber-converters/psi-mos-rs485w2-fo1300e-rs485-to-fiber.shtml	Serial Extender: PSI-MOS Serial to Fiber
27085628	PSI-MOS-RS485W2/FO1300 E - RS485 2-wire to fiber Converter: Terminal block serial to duplex fiber 1300nm (SC). Multimode [27km, 16.7 miles], single mode [45km, 28 miles]	https://www.perle.com/products/serial-fiber-converters/psi-mos-rs485w2-fo1300e-rs485-to-fiber.shtml	Serial Extender: PSI-MOS Serial to Fiber
27085752	PSI-MOS-RS422/FO1300 E - RS422/485 4-wire to fiber Converter: Terminal block serial to duplex fiber 1300nm (SC). Multimode [27km, 16.7 miles], single mode [45km, 28 miles] – 24VDC EU wall power adapter included	https://www.perle.com/products/serial-fiber-converters/psi-mos-rs422-fo1300e-rs422-to-fiber.shtml	Serial Extender: PSI-MOS Serial to Fiber
27085758	PSI-MOS-RS422/FO1300 E - RS422/485 4-wire to fiber Converter: Terminal block serial to duplex fiber 1300nm (SC). Multimode [27km, 16.7 miles], single mode [45km, 28 miles]	https://www.perle.com/products/serial-fiber-converters/psi-mos-rs422-fo1300e-rs422-to-fiber.shtml	Serial Extender: PSI-MOS Serial to Fiber
27085882	PSI-MOS-RS232/FO1300 E - RS232 to fiber Converter: DB9M serial to duplex fiber 1300nm (SC). Multimode [27km, 16.7 miles], single mode [45km, 28 miles] – 24VDC EU wall power adapter included	https://www.perle.com/products/serial-fiber-converters/psi-mos-rs232-fo1300e-rs232-to-fiber.shtml	Serial Extender: PSI-MOS Serial to Fiber
27085888	PSI-MOS-RS232/FO1300 E - RS232 to fiber Converter: DB9M serial to duplex fiber 1300nm (SC). Multimode [27km, 16.7 miles], single mode [45km, 28 miles]	https://www.perle.com/products/serial-fiber-converters/psi-mos-rs232-fo1300e-rs232-to-fiber.shtml	Serial Extender: PSI-MOS Serial to Fiber
27095618	DIN rail connector, UL 8A / cUL 6A, 150 V, Data & Power Pin positions: 5P, Width 17.5, Color: green - Pack of 10 TBUS connectors	https://www.perle.com/products/product_detail.asp?a=4&i=27095618&c=1283	Accessories: DIN Rail

Part #	Description	Product Datasheet	Product Group
27444162	PSM-ME-RS232/RS485-P - RS232 to RS485 Converter: RS-232 DB9M to RS-422/485 terminal block – 24VDC EU wall power adapter included	https://www.perle.com/products/serial-extenders/psm-me-rs232-rs485-converter.shtml	Serial Extender: PSM-ME Converter
27444168	PSM-ME-RS232/RS485-P - RS232 to RS485 Converter: RS-232 DB9M to RS-422/485 terminal block	https://www.perle.com/products/serial-extenders/psm-me-rs232-rs485-converter.shtml	Serial Extender: PSM-ME Converter
27444292	PSM-ME-RS485/RS485-P - RS-485 Repeater. For electrical isolation and range increase in RS-485 2-wire bus systems. Connections via terminal block– 24VDC EU wall power adapter included	https://www.perle.com/products/serial-extenders/psm-me-rs485-repeater.shtml	Serial Extender: PSM-ME RS485 Repeater
27444298	PSM-ME-RS485/RS485-P - RS-485 Repeater. For electrical isolation and range increase in RS-485 2-wire bus systems. Connections via terminal block	https://www.perle.com/products/serial-extenders/psm-me-rs485-repeater.shtml	Serial Extender: PSM-ME RS485 Repeater
27444612	PSM-ME-RS232/RS232-P - Interface converter for the electrical isolation of RS-232 interfaces (4 channels). Connections via DB9M and terminal block– 24VDC EU wall power adapter included	https://www.perle.com/products/serial-extenders/psm-me-rs232-serial-isolator.shtml	Serial Extender: PSM-ME Isolator
27444618	PSM-ME-RS232/RS232-P - Interface converter for the electrical isolation of RS-232 interfaces (4 channels). Connections via DB9M and terminal block	https://www.perle.com/products/serial-extenders/psm-me-rs232-serial-isolator.shtml	Serial Extender: PSM-ME Isolator
28015938	DT-TELE-SHDSL - surge protection device for two SHDSL telecommunications interfaces (ports). Connection: RJ45 (RJ12/RJ11) and plug-in screw terminal block	https://www.perle.com/products/surge-protectors/dt-tele-shdsl-surge-protector.shtml	Surge Protector
28664918	TRIO-PS/1AC/48DC/5 DIN-Rail Power Supply: 48 VDC, 240 Watt with universal 85 to 264 VAC, 30 to 56V DC output range adjustable, -25 to 70°C extended operating temperature.		Power Supplies
28665018	TRIO-PS/1AC/48DC/10 DIN Rail Power Supply: 48 VDC, 480 Watt with universal 85 to 264 VAC, 30 to 56V DC output range adjustable, -25 to 70C extended operating temperature.		Power Supplies
28665308	TRIO-PS/600DC/24DC/20 Power Supply - TRIO DC/DC converter for DIN rail mounting, 1-phase, input: 600 V DC, output: 24 V DC/20 A	https://www.perle.com/products/industrial-power-supply/trio-dc-dc-high-input.shtml	Power Supplies
28666958	QUINT-PS/1AC/48DC/20 Power Supply - QUINT power supply for DIN rail mounting with SFB (Selective Fuse Breaking) Technology, input: 1-phase, output: 48 V DC/20 A	https://www.perle.com/products/industrial-power-supply/quint-ps-1ac-48dc-20-28666958.shtml	Power Supplies
28667218	QUINT-PS/1AC/12DC/20 Power Supply - QUINT power supply for DIN rail mounting with SFB (Selective Fuse Breaking) Technology, input: 1-phase, output: 12 V DC/20 A	https://www.perle.com/products/industrial-power-supply/quint-ps-1ac-12dc-20-28667218.shtml	Power Supplies

Part #	Description	Product Datasheet	Product Group
28667478	QUINT-PS/1AC/24DC/3.5 Power Supply - QUINT power supply for DIN rail mounting with SFB (Selective Fuse Breaking) Technology, input: 1-phase, output: 24 V DC/3.5 A	https://www.perle.com/products/industrial-power-supply/quint-ps-1ac-24dc-3.5-28667478.shtml	Power Supplies
28667898	QUINT-PS/1AC/24DC/40 Power Supply - QUINT power supply for DIN rail mounting with SFB (Selective Fuse Breaking) Technology, input: 1-phase, output: 24 V DC/40 A	https://www.perle.com/products/industrial-power-supply/quint-ps-1ac-24dc-40-28667898.shtml	Power Supplies
28668028	QUINT-PS/3AC/24DC/40 Power Supply - QUINT power supply for DIN rail mounting with SFB (Selective Fuse Breaking) Technology, input: 3-phase, output: 24 V DC/40 A	https://www.perle.com/products/industrial-power-supply/quint-3-phase.shtml	Power Supplies
28669838	MINI-SYS-PS-100-240AC/24DC/1.5 Power Supply - For use with modular TBUS DIN rail connector system. 24VDC / 1.5 A, 36 Watts with universal 85 to 264 VAC, -25 C to 70 C extended operating temperature.	https://www.perle.com/products/industrial-din-rail-power-supplies.shtml	Power Supplies
28685388	STEP-PS/1AC/12DC/1 Power Supply - STEP power supply for DIN rail mounting, input: 1-phase, output: 12 V DC/1 A	https://www.perle.com/products/industrial-power-supply/step-ps-1ac-12dc-1-28685388.shtml	Power Supplies
28685418	STEP-PS/1AC/5DC/6.5 Power Supply - STEP power supply for DIN rail mounting, input: 1-phase, output: 5 V DC/6.5 A	https://www.perle.com/products/industrial-power-supply/step-ps-1ac-5dc-16.5-28685418.shtml	Power Supplies
28685548	STEP-PS/1AC/12DC/1.5/FL Power Supply - STEP power supply for DIN rail mounting, input: 1-phase, output: 12 V DC/1.5 A	https://www.perle.com/products/industrial-power-supply/step-ps-1ac-12dc-1.5-fl-28685548.shtml	Power Supplies
28685678	STEP-PS/1AC/12DC/1.5 Power Supply - STEP power supply for DIN rail mounting, input: 1-phase, output: 12 V DC/1.5 A	https://www.perle.com/products/industrial-power-supply/step-ps-1ac-12dc-1.5-28685678.shtml	Power Supplies
28685708	STEP-PS/1AC/12DC/3 Power Supply - STEP power supply for DIN rail mounting, input: 1-phase, output: 12 V DC/3 A	https://www.perle.com/products/industrial-power-supply/step-ps-1ac-12dc-3-28685708.shtml	Power Supplies
28685838	STEP-PS/1AC/12DC/5 Power Supply - STEP power supply for DIN rail mounting, input: 1-phase, output: 12 V DC/5 A	https://www.perle.com/products/industrial-power-supply/step-ps-1ac-12dc-5-28685838.shtml	Power Supplies
28685968	STEP-PS/1AC/24DC/0.5 Power Supply - STEP power supply for DIN rail mounting, input: 1-phase, output: 24 V DC/0.5 A	https://www.perle.com/products/industrial-power-supply/step-ps-1ac-24dc-0.5-28685968.shtml	Power Supplies

Part #	Description	Product Datasheet	Product Group
28686198	STEP-PS/1AC/15DC/4 Power Supply - STEP power supply for DIN rail mounting, input: 1-phase, output: 15 V DC/4 A	https://www.perle.com/products/industrial-power-supply/step-ps-1ac-15dc-4-28686198.shtml	Power Supplies
28686228	STEP-PS/1AC/24DC/0.75/FL Power Supply - STEP power supply for DIN rail mounting, input: 1-phase, output: 24 V DC/0.75 A	https://www.perle.com/products/industrial-power-supply/step-ps-1ac-24dc-0.75-fl-28686228.shtml	Power Supplies
28686358	STEP-PS/1AC/24DC/0.75 Power Supply - STEP power supply for DIN rail mounting, input: 1-phase, output: 24 V DC/0.75 A	https://www.perle.com/products/industrial-power-supply/step-ps-1ac-24dc-0.75-28686358.shtml	Power Supplies
28686488	STEP-PS/1AC/24DC/1.75 Power Supply - STEP power supply for DIN rail mounting, input: 1-phase, output: 24 V DC/1.75 A	https://www.perle.com/products/industrial-power-supply/step-ps-1ac-24dc-1.75-28686488.shtml	Power Supplies
28686518	STEP-PS/1AC/24DC/2.5 Power Supply - STEP power supply for DIN rail mounting, input: 1-phase, output: 24 V DC/2.5 A	https://www.perle.com/products/industrial-power-supply/step-ps-1ac-24dc-2.5-28686518.shtml	Power Supplies
28686648	STEP-PS/1AC/24DC/4.2 Power Supply - STEP power supply for DIN rail mounting, input: 1-phase, output: 24 V DC/4.2 A	https://www.perle.com/products/industrial-power-supply/step-ps-1ac-24dc-4.2-28686648.shtml	Power Supplies
28686778	STEP-PS/1AC/24DC/3.8/C2LPS Power Supply - STEP power supply for DIN rail mounting, input: 1-phase, output: 24 V DC/3.8 A	https://www.perle.com/products/industrial-power-supply/step-ps-1ac-24dc-3.8-c2lps-28686778.shtml	Power Supplies
28686808	STEP-PS/1AC/48DC/2 Power Supply - STEP power supply for DIN rail mounting, input: 1-phase, output: 48 V DC/2 A	https://www.perle.com/products/industrial-power-supply/step-ps-1ac-48dc-2-28686808.shtml	Power Supplies
28687168	STEP-PS/48AC/24DC/0.5 Power Supply - STEP power supply for DIN rail mounting, input: 1-phase, output: 24 V DC/0.5 A	https://www.perle.com/products/industrial-power-supply/step-ps-48ac-24dc-0.5-28687168.shtml	Power Supplies
28810078	DT-LAN-CAT.6+ - surge protection device for Ethernet Transmission speeds up to 10G. Connection: dual RJ45	https://www.perle.com/products/surge-protectors/dt-lan-cat6-surge-protector.shtml	Surge Protector
28900148	DIN rail connector, UL 8A / cUL 6A, 150 V, Power Pin positions: 2P Gold, Width 17.5, Color: black - Pack of 10 TBUS connectors	https://www.perle.com/products/product_detail.asp?a=4&i=28900148&c=1283	Accessories: DIN Rail
29029918	UNO-PS/1AC/24DC/30W Power Supply - UNO power supply for DIN rail mounting, input: 1-phase, output: 24 V DC/30 W	https://www.perle.com/products/industrial-power-supply/uno-ps-1ac-24dc-30w-29029918.shtml	Power Supplies

Part #	Description	Product Datasheet	Product Group
29029928	UNO-PS/1AC/24DC/60W Power Supply - UNO power supply for DIN rail mounting, input: 1-phase, output: 24 V DC/60 W	https://www.perle.com/products/industrial-power-supply/uno-ps-1ac-24dc-60w-29029928.shtml	Power Supplies
29029938	UNO-PS/1AC/24DC/100W Power Supply - UNO power supply for DIN rail mounting, input: 1-phase, output: 24 V DC/100 W	https://www.perle.com/products/industrial-power-supply/uno-ps-1ac-24dc-100w-29029938.shtml	Power Supplies
29029948	UNO-PS/1AC/24DC/90W/C2LPS Power Supply - UNO power supply for DIN rail mounting, input: 1-phase, output: 24 V DC/90 W	https://www.perle.com/products/industrial-power-supply/uno-ps-1ac-24dc-90w-c2lps-29029948.shtml	Power Supplies
29029958	UNO-PS/1AC/48DC/60W Power Supply - UNO power supply for DIN rail mounting, input: 1-phase, output: 48 V DC/60 W	https://www.perle.com/products/industrial-power-supply/uno-ps-1ac-48dc-60w-29029958.shtml	Power Supplies
29029968	UNO-PS/1AC/48DC/100W Power Supply - UNO power supply for DIN rail mounting, input: 1-phase, output: 48 V DC/100 W	https://www.perle.com/products/industrial-power-supply/uno-ps-1ac-48dc-100w-29029968.shtml	Power Supplies
29029978	UNO-PS/1AC/12DC/100W Power Supply - UNO power supply for DIN rail mounting, input: 1-phase, output: 12 V DC/100 W	https://www.perle.com/products/industrial-power-supply/uno-ps-1ac-12dc-100w-29029978.shtml	Power Supplies
29029988	UNO-PS/1AC/12DC/30W Power Supply - UNO power supply for DIN rail mounting, input: 1-phase, output: 12 V DC/30 W	https://www.perle.com/products/industrial-power-supply/uno-ps-1ac-12dc-30w-29029988.shtml	Power Supplies
29029998	UNO-PS/1AC/12DC/55W Power Supply - UNO power supply for DIN rail mounting, input: 1-phase, output: 12 V DC/55 W	https://www.perle.com/products/industrial-power-supply/uno-ps-1ac-12dc-55w-29029998.shtml	Power Supplies
29030008	UNO-PS/1AC/15DC/30W Power Supply - UNO power supply for DIN rail mounting, input: 1-phase, output: 15 V DC/30 W	https://www.perle.com/products/industrial-power-supply/uno-ps-1ac-15dc-30w-29030008.shtml	Power Supplies
29030018	UNO-PS/1AC/15DC/55W Power Supply - UNO power supply for DIN rail mounting, input: 1-phase, output: 15 V DC/55 W	https://www.perle.com/products/industrial-power-supply/uno-ps-1ac-15dc-55w-29030018.shtml	Power Supplies
29030028	UNO-PS/1AC/15DC/100W Power Supply - UNO power supply for DIN rail mounting, input: 1-phase, output: 15 V DC/100 W	https://www.perle.com/products/industrial-power-supply/uno-ps-1ac-15dc-100w-29030028.shtml	Power Supplies

Part #	Description	Product Datasheet	Product Group
29031448	TRIO-PS-2G/ 1AC/24DC/5/B+D Power Supply - TRIO power supply with push-in connection for DIN rail mounting, input: 1-phase, output: 24 V DC/5 A	https://www.perle.com/products/industrial-power-supply/trio-ps-2g-1ac-24dc-5-b+d-29031448.shtml	Power Supplies
29031458	TRIO-PS-2G/ 1AC/24DC/10/B+D Power Supply - TRIO power supply with push-in connection for DIN rail mounting, input: single phase, output: 24 V DC/10 A	https://www.perle.com/products/industrial-power-supply/trio-ps-2g-1ac-24dc-10-b+d-29031458.shtml	Power Supplies
29031478	TRIO-PS-2G/ 1AC/24DC/3/C2LPS Pwr Supply - TRIO power supply with push-in connection for DIN rail mounting, input: 1-phase, output: 24 V DC/3 A C2LPS	https://www.perle.com/products/industrial-power-supply/trio-ps-2g-1ac-24dc-3-c2lps-29031478.shtml	Power Supplies
29031488	TRIO-PS-2G/ 1AC/24DC/5 Power Supply - TRIO power supply with push-in connection for DIN rail mounting, input: 1-phase, output: 24 V DC/5 A	https://www.perle.com/products/industrial-power-supply/trio-ps-2g-1ac-24dc-5-29031488.shtml	Power Supplies
29031498	TRIO-PS-2G/ 1AC/24DC/10 Power Supply - TRIO power supply with push-in connection for DIN rail mounting, input: single phase, output: 24 V DC/10 A	https://www.perle.com/products/industrial-power-supply/trio-ps-2g-1ac-24dc-10-29031498.shtml	Power Supplies
29031518	TRIO-PS-2G/ 1AC/24DC/20 Power Supply - TRIO power supply with push-in connection for DIN rail mounting, input: single-phase, output: 24 V DC/20 A	https://www.perle.com/products/industrial-power-supply/trio-ps-2g-1ac-24dc-20-29031518.shtml	Power Supplies
29031538	TRIO-PS-2G/3AC/24DC/5 Power Supply - TRIO power supply with push-in connection for DIN rail mounting, input: 3-phase, output: 24 V DC/5 A	https://www.perle.com/products/industrial-power-supply/trio-3-phase.shtml	Power Supplies
29031548	TRIO-PS-2G/3AC/24DC/10 Power Supply - TRIO power supply with push-in connection for DIN rail mounting, input: 3-phase, output: 24 V DC/10 A	https://www.perle.com/products/industrial-power-supply/trio-3-phase.shtml	Power Supplies
29031558	TRIO-PS-2G/3AC/24DC/20 Power Supply - TRIO power supply with push-in connection for DIN rail mounting, input: 3-phase, output: 24 V DC/20 A	https://www.perle.com/products/industrial-power-supply/trio-3-phase.shtml	Power Supplies
29031568	TRIO-PS-2G/3AC/24DC/40 Power Supply - TRIO supply for DIN rail mounting, input: 3-phase, output: 24 V DC/40 A	https://www.perle.com/products/industrial-power-supply/trio-3-phase.shtml	Power Supplies
29031578	TRIO-PS-2G/ 1AC/12DC/5/C2LPS Pwr Supply - TRIO power supply with push-in connection for DIN rail mounting, input: 1-phase, output: 12 V DC/5 A C2LPS	https://www.perle.com/products/industrial-power-supply/trio-ps-2g-1ac-12dc-5-c2lps-29031578.shtml	Power Supplies
29031588	TRIO-PS-2G/ 1AC/12DC/10 Power Supply - TRIO power supply with push-in connection for DIN rail mounting, input: 1-phase, output: 12 V DC/10 A	https://www.perle.com/products/industrial-power-supply/trio-ps-2g-1ac-12dc-10-29031588.shtml	Power Supplies
29031598	TRIO-PS-2G/1AC/48DC/5 Power Supply - TRIO supply for DIN rail mounting, input: 1-phase, output: 48 V DC / 5 A	https://www.perle.com/products/industrial-power-supply/trio-ps-2g-1ac-48dc-5-29031598.shtml	Power Supplies

Part #	Description	Product Datasheet	Product Group
29031608	TRIO-PS-2G/1AC/48DC/10 Power Supply - TRIO power supply with push-in connection for DIN rail mounting, input: single phase, output: 48 V DC/10 A	https://www.perle.com/products/industrial-power-supply/trio-ps-2g-1ac-48dc-10-29031608.shtml	Power Supplies
29043718	UNO-PS/2AC/24DC/90W/C2LPS Power Supply - UNO power supply for DIN rail mounting, input: 2-phase, output: 24 V DC/90 W	https://www.perle.com/products/industrial-power-supply/uno-2-phase.shtml	Power Supplies
29043728	UNO-PS/1AC/24DC/240W Power Supply - UNO supply for DIN rail mounting, input: single-phase, output: 24 V DC/240 W	https://www.perle.com/products/industrial-power-supply/uno-ps-1ac-24dc-240w-29043728.shtml	Power Supplies
29043748	UNO-PS/1AC/5DC/25W Power Supply - UNO power supply for DIN rail mounting, input: 1-phase, output: 5 V DC/25 W	https://www.perle.com/products/industrial-power-supply/uno-ps-1ac-5dc-25w-29043748.shtml	Power Supplies
29043758	UNO-PS/1AC/5DC/40W Power Supply - UNO power supply for DIN rail mounting, input: 1-phase, output: 5 V DC/40 W	https://www.perle.com/products/industrial-power-supply/uno-ps-1ac-5dc-40w-29043758.shtml	Power Supplies
29043768	UNO-PS/1AC/24DC/150W Power Supply - UNO supply for DIN rail mounting, input: 1-phase, output: 24 V DC/150 W	https://www.perle.com/products/industrial-power-supply/uno-ps-1ac-24dc-150w-29043768.shtml	Power Supplies
29045978	QUINT4-PS/1AC/24DC/1.3/SC Power Supply - QUINT power supply with Screw connection, DIN rail mounting, input: 1-phase, output: 24 V DC / 1.3 A	https://www.perle.com/products/industrial-power-supply/quint-ps-1ac-24dc-1.3-sc-29045978.shtml	Power Supplies
29045988	QUINT4-PS/1AC/24DC/2.5/SC Power Supply - QUINT power supply with Screw connection, DIN rail mounting, input: 1-phase, output: 24 V DC / 2.5 A	https://www.perle.com/products/industrial-power-supply/quint-ps-1ac-24dc-2.5-sc-29045988.shtml	Power Supplies
29045998	QUINT4-PS/1AC/24DC/3.8/SC Power Supply - QUINT power supply with Screw connection, DIN rail mounting, input: 1-phase, output: 24 V DC / 3.8 A	https://www.perle.com/products/industrial-power-supply/quint-ps-1ac-24dc-3.8-sc-29045998.shtml	Power Supplies
29046008	QUINT4-PS/1AC/24DC/5 Power Supply - QUINT power supply with free choice of output characteristic curve, SFB (selective fuse breaking) technology, and NFC interface, input: 1-phase, output: 24 V DC/5 A	https://www.perle.com/products/industrial-power-supply/quint-ps-1ac-24dc-5-29046008.shtml	Power Supplies
29046018	QUINT4-PS/1AC/24DC/10 Power Supply - QUINT power supply with free choice of output characteristic curve, SFB (selective fuse breaking) technology, and NFC interface, input: 1-phase, output: 24 V DC/10 A	https://www.perle.com/products/industrial-power-supply/quint-ps-1ac-24dc-10-29046018.shtml	Power Supplies
29046028	QUINT4-PS/1AC/24DC/20 Power Supply - QUINT power supply with free choice of output characteristic curve, SFB (selective fuse breaking) technology, and NFC interface, input: 1-phase, output: 24 V DC/20 A	https://www.perle.com/products/industrial-power-supply/quint-ps-1ac-24dc-20-29046028.shtml	Power Supplies

Part #	Description	Product Datasheet	Product Group
29046088	QUINT4-PS/1AC/12DC/15 Power Supply - QUINT power supply with free choice of output characteristic curve, SFB (selective fuse breaking) technology, and NFC interface, input: 1-phase, output: 12 V DC/15 A	https://www.perle.com/products/industrial-power-supply/quint-ps-1ac-12dc-15-29046088.shtml	Power Supplies
29046108	QUINT4-PS/1AC/48DC/5 Power Supply - QUINT power supply for DIN rail mounting with free choice of output characteristic curve and SFB (Selective Fuse Breaking) technology, input: 1-phase, output: 48 V DC / 5 A	https://www.perle.com/products/industrial-power-supply/quint-ps-1ac-48dc-5-29046108.shtml	Power Supplies
29046118	QUINT4-PS/1AC/48DC/10 Power Supply - QUINT power supply for DIN rail mounting with free choice of output characteristic curve and SFB (Selective Fuse Breaking) technology, input: 1-phase, output: 48 V DC / 10 A	https://www.perle.com/products/industrial-power-supply/quint-ps-1ac-48dc-10-29046118.shtml	Power Supplies
29046218	QUINT4-PS/3AC/24DC/10 Power Supply - QUINT power supply with free choice of output characteristic curve, SFB (selective fuse breaking) technology, and NFC interface, input: 3-phase, output: 24 V DC/10 A	https://www.perle.com/products/industrial-power-supply/quint-3-phase.shtml	Power Supplies
29046228	QUINT4-PS/3AC/24DC/20 Power Supply - QUINT power supply with free choice of output characteristic curve, SFB (selective fuse breaking) technology, and NFC interface, input: 3-phase, output: 24 V DC/20 A	https://www.perle.com/products/industrial-power-supply/quint-3-phase.shtml	Power Supplies
29049458	STEP-PS/277AC/24DC/3.5 Power Supply - STEP power supply for DIN rail mounting, output 24 V DC/3.5 A, 1-phase	https://www.perle.com/products/industrial-power-supply/step-ps-1ac-24dc-3.5-29049458.shtml	Power Supplies
29050078	QUINT-PS/12DC/12DC/8 Power Supply - QUINT DC/DC converter for DIN rail mounting with SFB (selective fuse breaking) technology, input: 12 V DC, output: 12 V DC/8 A	https://www.perle.com/products/industrial-power-supply/quint-ps-12dc-12dc-8-29050078.shtml	Power Supplies
29050088	QUINT-PS/48DC/48DC/5 Power Supply - QUINT DC/DC converter for DIN rail mounting with SFB (selective fuse breaking) technology, input: 48 V DC, output: 48 V DC/5 A	https://www.perle.com/products/industrial-power-supply/quint-ps-48dc-48dc-5-29050088.shtml	Power Supplies
29050098	QUINT-PS/60-72DC/24DC/10 Power Supply - QUINT DC/DC converter with wide range input for DIN rail mounting with SFB (Selective Fuse Breaking) technology, input: 60-72 V DC, output 24 V DC / 10 A	https://www.perle.com/products/industrial-power-supply/quint-ps-60-72dc-24dc-10-29050098.shtml	Power Supplies
29050108	QUINT-PS/96-110DC/24DC/10 Power Supply - QUINT DC/DC converter with wide range input for DIN rail mounting with SFB (selective fuse breaking) technology, input: 96 - 110 V DC, output: 24 V DC/10 A	https://www.perle.com/products/industrial-power-supply/quint-ps-96-110dc-24dc-10-29050108.shtml	Power Supplies
29050118	QUINT-PS/60-72DC/24DC/10/CO Power Supply - QUINT DC/DC converter with wide range input for DIN rail mounting with SFB (Selective Fuse Breaking) technology, input: 60-72 V DC, output 24 V DC / 10 A	https://www.perle.com/products/industrial-power-supply/quint-ps-60-72dc-24dc-10-co-29050118.shtml	Power Supplies

Part #	Description	Product Datasheet	Product Group
29050128	QUINTPS/96-110DC/24DC/10/CO Power Supply - QUINT DC/DC converter with wide range input for DIN rail mounting with SFB (selective fuse breaking) technology, input: 96 - 110 V DC, output: 24 V DC/10 A	https://www.perle.com/products/industrial-power-supply/quint-ps-96-110dc-24dc-10-co-29050128.shtml	Power Supplies
29063008	UNO-PS/350-900DC/24DC/60W Power Supply - UNO DC/DC converter with wide range input, for DIN rail mounting, input: 350 ... 900 V DC, output: 24 V DC/60 W	https://www.perle.com/products/industrial-power-supply/uno-dc-dc.shtml	Power Supplies
29095758	QUINT4-PS/1AC/24DC/1.3/PT Power Supply - QUINT power supply with Push-in technology, DIN rail mounting, input: 1-phase, output: 24 V DC / 1.3 A	https://www.perle.com/products/industrial-power-supply/quint-ps-1ac-24dc-1.3-pt-29095758.shtml	Power Supplies
29095768	QUINT4-PS/1AC/24DC/2.5/PT Power Supply - QUINT power supply with Push-in technology, DIN rail mounting, input: 1-phase, output: 24 V DC / 2.5 A	https://www.perle.com/products/industrial-power-supply/quint-ps-1ac-24dc-2.5-29095768.shtml	Power Supplies
29095778	QUINT4-PS/1AC/24DC/3.8/PT Power Supply - QUINT power supply with Push-in technology, DIN rail mounting, input: 1-phase, output: 24 V DC / 3.8 A	https://www.perle.com/products/industrial-power-supply/quint-ps-1ac-24dc-3.8-pt-29095778.shtml	Power Supplies
900-82180-0001-000	NVIDIA Jetson Tx1 Module	https://developer.nvidia.com/embedded/faq	NVIDIA Jetson Tx1
900-82888-0000-000	NVIDIA Jetson AGXxavier Module	https://developer.nvidia.com/embedded/faq	NVIDIA Jetson AGX Xavier
900-83310-0001-000	NVIDIA Jetson Tx2 Module	https://developer.nvidia.com/embedded/faq	NVIDIA Jetson Tx2
900-83489-0000-000	NVIDIA Jetson Tx2i Industrial Module	https://developer.nvidia.com/embedded/faq	NVIDIA Jetson Tx2i
940-7R375-0001-000	NVIDIA Jetson TK1 Development Kit	https://developer.nvidia.com/embedded-computing	NVIDIA Jetson TK1 Dev Kit
945-13450-0000-000	NVIDIA Jetson Nano Development Kit	https://developer.nvidia.com/embedded-computing	NVIDIA Jetson Nano Dev Kit
945-82371-0005-000	NVIDIA Jetson Tx1 Development Kit	https://developer.nvidia.com/embedded-computing	NVIDIA Jetson Tx1 Dev Kit
945-82771-0005-000	NVIDIA Jetson Tx2 Development Kit	https://developer.nvidia.com/embedded-computing	NVIDIA Jetson Tx2 Dev Kit
ADG001	PCI to PC/104-Plus adapter. RoHS Compliant.	http://connecttech.com/product/pci-to-pc104-plus-adapter/	PCI to PC/104-Plus Adapter
ADG003	ISA to PC/104 adapter. RoHS Compliant.	http://connecttech.com/?s=ADG003	ISA to PC/104 Adapter

Part #	Description	Product Datasheet	Product Group
ADG004	PCI to cPCI adapter. RoHS Compliant.	http://connecttech.com/?s=ADG004	PCI to CompactPCI Adapter
ADG005	PCI dump switch card. RoHS Compliant.	http://connecttech.com/?s=ADG005	PCI Dump Switch Card
ADG006	PC/104-Plus to MiniPCI adapter. RoHS Compliant.	http://connecttech.com/?s=ADG006	PC/104-Plus to Mini PCI Adapter
ADG010	PCI Express Burn-in Rack. RoHS Compliant.	http://connecttech.com/product/pci-express-pcie-burn-in-rack-adapter/	PCI Express (PCIe) Burn-in Rack Adapter
ADG013	PCI-104 to PMC adapter. RoHS Compliant.	http://connecttech.com/product/pci-104-to-pmc-adapter/	PCI-104 to PMC Adapter
ADG016	PCI Express to PCIe/104 adapter. RoHS Compliant.	http://connecttech.com/product/pci-express-to-pcie104-pci104-express-adapter/	PCI Express to PCIe/104 (PCI/104-Express) Adapter
ADG017	PCIe/104 to PCI Express adapter for top mount CPU. RoHS Compliant.	http://connecttech.com/product/pcie104-to-pci-express-adapter-top-stacking-model/	PCIe/104 to PCI Express Adapter Top Stacking Model
ADG018	PCI Express Dump Switch card. RoHS Compliant.	http://connecttech.com/product/pci-express-dump-switch-card/	PCI Express Dump Switch Card
ADG021	PCIe/104 to PCI Express adapter for bottom mount CPU. RoHS Compliant.	http://connecttech.com/product/pcie104-to-pci-express-adapter-bottom-stacking-model/	PCIe/104 to PCI Express Adapter Bottom Stacking Model
ADG028	PCIe/104 to Mini-PCIe Card Adapter - single bank PCIe/104 connector. RoHS Compliant.	http://connecttech.com/product/pci104-express-to-single-dual-mini-pcie-pci-express-mini-card-adapter/	PCI/104-Express to Single/Dual Mini-PCIe (PCI Express Mini Card) Adapter
ADG034	PCIe/104 to Mini-PCIe Adapter - 3x bank PCIe/104 connector. RoHS Compliant.	http://connecttech.com/?s=ADG034	PCI/104-Express to Single/Dual Mini-PCIe (PCI Express Mini Card) Adapter
ADG036	PCI/104-Express Adapter allows for the testing and development of one Full Mini-PCIe Card in a PCIe/104 or PCI/104-Express stack. A SIM card socket is installed for Wireless networking and Telephony applications. 3-bank PCIe/104 connector allows Top or Bottom PCIe/104 stacking with appropriate PCI Express Lane switching. Also has 2x USB and a passive pass-through PCI-104 connector installed. RoHS Compliant.	http://connecttech.com/product/pci104-express-to-single-dual-mini-pcie-pci-express-mini-card-adapter/	PCI/104-Express to Single/Dual Mini-PCIe (PCI Express Mini Card) Adapter
ADG038	PCIe/104 Bus Extender allows an increase of one additional board height to your PCIe/104 or PCI/104-Express stack. RoHS Compliant.	http://connecttech.com/product/pcie104-bus-extender/	PCIe/104 Bus Extender
ADG039	SUMIT to PCIe/104 Adapter. RoHS Compliant.	http://connecttech.com/product/sumit-to-pcie104-adapter/	SUMIT to PCIe/104 Adapter

Part #	Description	Product Datasheet	Product Group
ADG040	PCI/104-Express to PCI Express Cable adapter allows testing and development of a x1 lane PCI Express device outside of the PCIe/104 and/or PCI/104-Express system stack using the PCI Express cabling specification. Temp. -20°C to +85°C. RoHS Compliant.	http://connecttech.com/product/pcie104-to-pci-express-cable-adapter/	PCIe/104 to PCI Express Cable Adapter
ADG041	PCI/104-Express to PCI Express Cable adapter allows testing and development of a x1 lane PCI Express device outside of the PCIe/104 and/or PCI/104-Express system stack using the PCI Express cabling specification. Includes support for longer PCI Express cable lengths. Temp. 0°C to +70°C. RoHS Compliant.	http://connecttech.com/product/pcie104-to-pci-express-cable-adapter/	PCIe/104 to PCI Express Cable Adapter
ADG042	Qseven to COM Express Adapter. RoHS Compliant.	http://connecttech.com/product/qseven-to-com-express-adapter/	Qseven to COM Express® Adapter
ADG043	PCI-104 to PC/104 adapter allows for the testing and development of a PC/104 peripheral card in a PCI-104 stack. RoHS Compliant.	http://connecttech.com/product/pci-104-to-pc104-adapter/	PCI-104 to PC/104 Adapter
ADG044	PCIe/104 (PCI/104-Express) Adapter allows for the testing and development of two Full or Half Mini-PCIe Cards. SIM card sockets are available for Wireless networking and Telephony applications. Top or Bottom PCIe/104 stacking with appropriate PCI Express Lane switching. Also supports a passive pass-through PCI-104 connector (optionally installed). RoHS Compliant.	http://connecttech.com/product/pci104-express-to-single-dual-mini-pcie-pci-express-mini-card-adapter/	PCI/104-Express to Single/Dual Mini-PCIe (PCI Express Mini Card) Adapter
ADG046	PCI-104 Adapter allows testing and development of a Full or Half Mini-PCIe Card (52 pin) in your PCI-104 stack. RoHS Compliant.	http://connecttech.com/product/pci-104-to-mini-pcie-card-adapter/	PCI-104 to Mini-PCIe Card Adapter
ADG047	PCI-104 Adapter allows testing and development of a Full or Half Mini-PCIe Card (76 pin) in your PCI-104 stack. RoHS Compliant.	http://www.connecttech.com/pdf/ADG0460-Manual.pdf	PCI-104 to Mini-PCIe Card Adapter
ADG048	PCI-104 Adapter allows testing and development of a Full or Half Mini-PCIe Card (76 pin) in your PCI-104 stack. RoHS Compliant.	http://www.connecttech.com/pdf/ADG0460-Manual.pdf	PCI-104 to Mini-PCIe Card Adapter
ADG049	PCIe/104 (PCI/104-Express) Adapter allows for the testing and development of two Full or Half Mini-PCIe Cards. SIM card sockets are installed for Wireless networking and Telephony applications. Supports Top or Bottom PCIe/104 stacking with appropriate PCI Express Lane switching and three bank PCIe/104 connector. Client USBx 2 and Host USBx 1 ports. Diagnostic PCIe Link LEDs. RoHS Compliant.	http://connecttech.com/product/pci104-express-to-single-dual-mini-pcie-pci-express-mini-card-adapter/	PCI/104-Express to Single/Dual Mini-PCIe (PCI Express Mini Card) Adapter

Part #	Description	Product Datasheet	Product Group
ADG050	PCIe/104 (PCI/104-Express) Adapter allows for the testing and development of two Full or Half Mini-PCIe Cards. SIM card sockets are installed for Wireless networking and Telephony applications. Supports Top or Bottom PCIe/104 stacking with appropriate PCI Express Lane switching and one bank PCIe/104 connector. Client USBx 2 and Host USBx 1 ports. Includes 120 pin PCI-104 pass through connector. Diagnostic PCIe Link LEDs. RoHS Compliant.	http://connecttech.com/product/pci104-express-to-single-dual-mini-pcie-pci-express-mini-card-adapter/	PCI/104-Express to Single/Dual Mini-PCIe (PCI Express Mini Card) Adapter
ADG051	PCIe/104 (PCI/104-Express) Adapter allows for the testing and development of two Full or Half Mini-PCIe Cards. SIM card sockets are installed for Wireless networking and Telephony applications. Supports Top or Bottom PCIe/104 stacking with appropriate PCI Express Lane switching and a one bank PCIe/104 connector. Client USBx 2 and Host USBx 1 ports. Diagnostic PCIe Link LEDs. RoHS Compliant.	http://connecttech.com/product/pci104-express-to-single-dual-mini-pcie-pci-express-mini-card-adapter/	PCI/104-Express to Single/Dual Mini-PCIe (PCI Express Mini Card) Adapter
ADG052	PCI/PCI Express to PMC/XMC adapter allows for the testing and development of any 32-bit PCI card or x1, x4, x8 PCI Express card in a PMC or xMC system. RoHS Compliant.	http://connecttech.com/product/pci-pcie-to-pmc-xmc-adapter/	PCI/PCIe to PMC/XMC Adapter
ADG053	COM Express Bus Extender allows for a complete pass through connection of all available signal and power COM Express pins. Provides for easy access to a COM Express module or carrier during debugging or as a `connector saver` for a testing environment. RoHS Compliant.	http://connecttech.com/product/com-express-bus-extender/1	COM Express® Bus Extender
ADG054	PCIe/104 to PCI-104 Adapter allows for up to four PCI-104 add-on modules to be used with a PCIe/104 SBC. RoHS Compliant.	http://connecttech.com/product/pcie104-to-pci-104-adapter/	PCIe/104 to PCI-104 Adapter
ADG061	SMART Battery Adapter allows the use of an Inspired Energy 204x series (or equivalent) battery to be installed and operated in a PC/104 stack. RoHS Compliant. Not all NC204x batteries fit within the PC/104 space, currently supported batteries include: NC2040A24, NC2040HD24, NC2040HD29, NC2040LT29, NC2040HD34	http://connecttech.com/product/smart-battery-adapter/	SMART Battery Adapter
ADG075	PCIe/104 to Single Mini-PCIe Adapter allows for the testing and development of a Full or Half Mini-PCIe Card. 3 bank PCIe/104 connector allows Top or Bottom PCIe/104 stacking. RoHS Compliant.	http://connecttech.com/product/mini-pcie-carrier/	Mini PCIe Carrier

Part #	Description	Product Datasheet	Product Group
ADG077	PCIe/104 to Dual Mini-PCIe Adapter allows for the testing and development of a Full or Half Mini-PCIe Cards. 3 bank PCIe/104 connector allows Top or Bottom PCIe/104 stacking. A USB Hub provides connection to the Mini-PCIe USB Ports if required. RoHS Compliant.	http://connecttech.com/product/mini-pcie-carrier/	Mini PCIe Carrier
ADG078	PCIe/104 to Quad Mini PCIe Adapter top stacking model	http://connecttech.com/product/pcie104-quad-mini-pciemsata/	PCIe/104 Quad Mini PCIe/mSATA
ADG080	PCIe/104 to Quad Mini PCIe Adapter bottom stacking model	http://connecttech.com/product/pcie104-quad-mini-pciemsata/	PCIe/104 Quad Mini PCIe/mSATA
ADG087	PCIe/104 to Quad Mini PCIe Adapter top stacking model, uses only one PCIe x1 Lane with onboard PCIe switch	http://connecttech.com/product/pcie104-quad-mini-pciemsata/	PCIe/104 Quad Mini PCIe/mSATA
ADG092	M.2 to PCIe/104 Adapter Dual MB-Key (cellular or SDD) Variant. Features: > 2x M.2 MB-Key connectors > Stack-up or stack-down support > Three LEDs per card for Wi-Fi and cellular status signals > Headers to support routing Wi-Fi and cellular status signals off-board > Two micro-SIM card slots to supplement cellular functionality > Two cellular radio shut-off (W_DISABLE#1,#2) DIP switches per card	http://connecttech.com/product/pcie-104-to-m-2-adapter/	PCIe/104 to M.2 Adapter
ADG095	XMC to PCIe/104 adapter. Allows xMC mezzanine cards to stack on PCIe/104, supports up to PCIe x8. RoHS Compliant.	http://connecttech.com/product/xmc-pcie104-adapter/	XMC to PCIe/104 Adapter
ADG097	PCIe/104 to Dual Mini-PCIe Adapter allows for the testing and development of a Full or Half Mini-PCIe Cards. 3 bank PCIe/104 connector allows Top or Bottom PCIe/104 stacking. A USB Hub provides connection to the Mini-PCIe USB Ports if required. PCI-104 pass through connector RoHS Compliant.	http://connecttech.com/product/mini-pcie-carrier/	Mini PCIe Carrier
ADG098	PCIe/104 to Single Mini-PCIe Adapter allows for the testing and development of a Full or Half Mini-PCIe Card. 3 bank PCIe/104 connector allows Top or Bottom PCIe/104 stacking. PCI-104 pass through. RoHS Compliant.	http://connecttech.com/product/mini-pcie-carrier/	Mini PCIe Carrier
ASG001	Astro Carrier for NVIDIA® Jetson™ TX1 - Astro is specifically designed to work with the NVIDIA® Jetson™ TX1 supercomputer-on-module. Astro for Jetson TX1 is a full featured carrier using board to board connectors that allows for use with off the shelf breakout boards or custom, application specific break out boards. Astro offers 2xGbE, 2xUSB2, 1xUSB3, 1xHDMI, 3xCSI, 1xI2C, 1xAux, 4xGPIO, 1xMiniPCIe, 1xmSATA. RoHS Compliant.	http://connecttech.com/product/astro-carrier-for-nvidia-jetson-tx2-tx1/	Astro Carrier for NVIDIA® Jetson™ TX2/TX2i/TX1

Part #	Description	Product Datasheet	Product Group
ASG002	ELROY is an Astro Carrier for NVIDIA® Jetson™ TX1 single board design includes dualx2 MIPI CSI-2 Video Inputs, dual half size or one single full length Mini-PCIe/mSATA expansion, HDMI Video, USB 3.0 and 2.0, x GbE, 2x RS-232/485, 1x microSD, SPI, I2C, GPIO, 87mm x 50mm, -40°C to +85°C. RoHS Compliant.	http://connecttech.com/product/asg002-elroy-carrier-for-nvidia-jetson-tx2-tx1/	Elroy Carrier for NVIDIA® Jetson™ TX2/TX2i/TX1
ASG003	Orbitty Carrier for NVIDIA® Jetson™ TX1. 187mm x 50mm, 1x USB 3.0, 1x USD 2.0, OTG, 1x HDMI, 1x GbE, 1x Micro SD, 2x 3.3V UART, 12C and 4x GPIO. -40 to +85C. RoHS Compliant.	http://connecttech.com/product/orbitty-carrier-for-nvidia-jetson-tx2-tx1/	Orbitty Carrier for NVIDIA® Jetson™ TX2/TX2i/TX1
ASG004	Astro Carrier for NVIDIA® Jetson™ TX1 with no GMSL video support. RoHS Compliant.	http://connecttech.com/product/astro-carrier-for-nvidia-jetson-tx2-tx1/	Astro Carrier for NVIDIA® Jetson™ TX2/TX2i/TX1
ASG006	Spacely Carrier for TX1/TX2 up to 6 MIPI CSI-2, tailored IO for easy connection to Pixhawk Autopilot, 2x GbE, 1x uHDMI, 2x USB 3.0, 2x USB 2.0, 1x USB OTG, 1x miniPCIe Slot, mSATA Slot, CAN 2.0b port, 2x UART, I2C, SPI, 14 GPIO all at +3.3V IO, optional GPS/GNSS module, -40°C to +85°C. RoHS Compliant.	http://connecttech.com/product/spacely-carrier-nvidia-jetson-tx2-jetson-tx1/	Spacely Carrier for NVIDIA® Jetson™ TX2/TX2i/TX1
ASG007	Cogswell Carrier for TX1/TX2 5x Gigabit Ethernet Ports: 4x IEEE 802.3af (PoE) 15.4W PSE Gigabit Ethernet Ports OR 2x IEEE 802.3at (PoE+) 25.5W PSE Gigabit Ethernet Ports, 1x USB 3.0, 1x USB 2.0, 1x USB OTG, 2x RS-232, 1x miniPCIe, 1x mSATA, 1x CAN 2.0b Port, 12V input only required, -40°C to +85°C. RoHS Compliant.	http://connecttech.com/product/cogswell-carrier-nvidia-jetson-tx2-jetson-tx1/	Cogswell Carrier for NVIDIA® Jetson™ TX2/TX2i/TX1
ASG008	Sprocket Carrier for TX1/TX2 1x USB OTG, 1x4 lane MIPI CSI-2, 2x 3.3V UART, I2C, 4x GPIO, +9V to +16V DC Input, all components fit "under" TX2/TX1 module, -40°C to +85°C. RoHS Compliant.	http://connecttech.com/resource-center/downloads-sprocket-carrier-asg008/	Sprocket Carrier for NVIDIA® Jetson™ TX2/TX2i/TX1
BBG001	BlueStorm/Express Opto, 4 ports RS-232/422/485, 3kV optical isolation and surge suppression. RoHS Compliant.	http://connecttech.com/product/pci-express-bluestorm-express-opto/	PCI Express: BlueStorm/Express Opto
BBG001-01	BlueStorm/Express Opto, 4 ports RS-232/422/485, 3kV optical isolation and surge suppression, RJ-45 to DB-9 cables. RoHS Compliant.	http://connecttech.com/product/pci-express-bluestorm-express-opto/	PCI Express: BlueStorm/Express Opto
BBG003	BlueStorm/Express Opto (1kV), 8 ports RS-232/422/485, 1kV optical isolation on ports 5-8, RoHS Compliant.	http://connecttech.com/product/pci-express-bluestorm-express-opto/	PCI Express: BlueStorm/Express Opto
BBG003-01	BlueStorm/Express Opto (1kV), 8 ports RS-232/422/485, 1kV optical isolation on ports 5-8, DB-9 cables. RoHS Compliant.	http://connecttech.com/product/pci-express-bluestorm-express-opto/	PCI Express: BlueStorm/Express Opto
BBG008-01	BlueStorm/Express Opto 8 port RS-232/422/485 PCI Express card with opto isolation on all ports. CBG143 DB-9 cables, RoHS Compliant.	http://connecttech.com/product/pci-express-bluestormexpress-isolated/	PCI Express: BlueStorm/Express Isolated

Part #	Description	Product Datasheet	Product Group
BCG001	BlueStorm/LP Express Opto, 2 ports RS-232/422/485 low profile card with optical isolation and LEDs on the bracket indicating Rx and Tx activity. RoHS Compliant.	http://connecttech.com/product/pci-express-bluestorm-express-lp-opto/	PCI Express: BlueStorm/Express LP Opto
BCG001-01	BlueStorm/LP Express Opto, 2 ports RS-232/422/485 low profile card with optical isolation and LEDs on the bracket indicating Rx and Tx activity. Includes RJ-45 to DB-9 cables. RoHS Compliant.	http://connecttech.com/product/pci-express-bluestorm-express-lp-opto/	PCI Express: BlueStorm/Express LP Opto
BCG002	BlueStorm/LP Express Opto, 2 ports RS-232/422/485 low profile card with optical isolation and LEDs on the bracket indicating Rx and Tx activity. RoHS Compliant.	http://connecttech.com/product/pci-express-bluestorm-express-lp-opto/	PCI Express: BlueStorm/Express LP Opto
BCG002-01	BlueStorm/LP Express Opto, 2 ports RS-232/422/485 low profile card with optical isolation and LEDs on the bracket indicating Rx and Tx activity. Includes RJ-45 to DB-9 cables. RoHS Compliant.	http://connecttech.com/product/pci-express-bluestorm-express-lp-opto/	PCI Express: BlueStorm/Express LP Opto
BCG003-01	BlueStorm/LP Express Opto, 2 ports RS-232/422/485 low profile card with optical isolation and LEDs on standard height bracket indicating Rx and Tx activity. Includes RJ-45 to DB-9 cables. RoHS Compliant.	http://connecttech.com/product/pci-express-bluestorm-express-lp-opto/	PCI Express: BlueStorm/Express LP Opto
BCG004	BlueStorm/Express LP Opto, 4 ports RS-232/422/485, 2kV optical isolation. RoHS Compliant.	http://connecttech.com/product/pci-express-bluestormexpress-isolated/	PCI Express: BlueStorm/Express Isolated
BCG004-01	BlueStorm/Express LP Opto, 4 ports RS-232/422/485, 2kV optical isolation, includes DB-9 cables. RoHS Compliant.	http://connecttech.com/product/pci-express-bluestormexpress-isolated/	PCI Express: BlueStorm/Express Isolated
BDG001-01	BlueStorm/Express Isolated, 8 ports RS-232, 2kV of electrical isolation port-to-port when used with CBG058, DB-9 cable, RoHS Compliant.	http://connecttech.com/product/pci-express-bluestormexpress-isolated/	PCI Express: BlueStorm/Express Isolated
BEG001	BlueStorm/Express, 2 ports RS-232/422/485, includes surge suppression, 2 male DB-9's on board. RoHS Compliant.	http://connecttech.com/product/pci-express-bluestorm-express/	PCI Express: BlueStorm/Express
BEG002-01	BlueStorm/Express, 4 ports RS-232/422/485, includes surge suppression, DB-9 cables. RoHS Compliant.	http://connecttech.com/product/pci-express-bluestorm-express/	PCI Express: BlueStorm/Express
BEG002-02	BlueStorm/Express, 4 ports RS-232/422/485, includes surge suppression, DB-25 cables. RoHS Compliant.	http://connecttech.com/product/pci-express-bluestorm-express/	PCI Express: BlueStorm/Express
BEG005-01	BlueStorm/Express, 8 ports RS-232/422/485, includes surge suppression, DB-9 cables. RoHS Compliant.	http://connecttech.com/product/pci-express-bluestorm-express/	PCI Express: BlueStorm/Express
BEG005-02	BlueStorm/Express, 8 ports RS-232/422/485, includes surge suppression, DB-25 cables. RoHS Compliant.	http://connecttech.com/product/pci-express-bluestorm-express/	PCI Express: BlueStorm/Express
BEG005-03	BlueStorm/Express, 8 ports RS-232/422/485, includes surge suppression, external DB-9 I/O box. RoHS Compliant.	http://connecttech.com/product/pci-express-bluestorm-express/	PCI Express: BlueStorm/Express
BEG006	BlueStorm/Express, 16 ports RS-232/422/485, includes surge suppression, RoHS Compliant.	http://connecttech.com/product/pci-express-bluestorm-express/	PCI Express: BlueStorm/Express

Part #	Description	Product Datasheet	Product Group
BEG006-01	BlueStorm/Express, 16 ports RS-232/422/485, includes surge suppression, DB-9 cables. RoHS Compliant.	http://connecttech.com/product/pci-express-bluestorm-express/	PCI Express: BlueStorm/Express
BEG006-02	BlueStorm/Express, 16 ports RS-232/422/485, includes surge suppression, DB-25 cables. RoHS Compliant.	http://connecttech.com/product/pci-express-bluestorm-express/	PCI Express: BlueStorm/Express
BEG006-03	BlueStorm/Express, 16 ports RS-232/422/485, includes surge suppression, external DB-9 I/O box. RoHS Compliant.	http://connecttech.com/product/pci-express-bluestorm-express/	PCI Express: BlueStorm/Express
BEG011-01	BlueStorm/Express, 16 ports RS-232, includes surge suppression, DB-9 cables. RoHS Compliant.	http://connecttech.com/product/pci-express-bluestorm-express-8-16-rs-232/	PCI Express: BlueStorm/Express 8/16 RS-232
BFG002-01	BlueStorm/Express LP, 8 ports RS-232/422/485 surge suppression, DB-9 cables. RoHS Compliant.	http://connecttech.com/product/pci-express-bluestorm-express-lp/	PCI Express: BlueStorm/Express LP
BFG002-02	BlueStorm/Express LP, 8 ports RS-232/422/485, surge suppression, DB-25 cables. RoHS Compliant.	http://connecttech.com/product/pci-express-bluestorm-express-lp/	PCI Express: BlueStorm/Express LP
BFG002-03	BlueStorm/Express LP, 8 ports RS-232/422/485, surge suppression, external DB-9 I/O box. RoHS Compliant.	http://connecttech.com/product/pci-express-bluestorm-express-lp/	PCI Express: BlueStorm/Express LP
BLG006-01	BlueStorm/LP, 2 ports RS-232, includes surge suppression, additional standard height bracket, DB-9 cables. RoHS Compliant.	http://connecttech.com/product/bluestormlp-rs-232/	BlueStorm/LP RS-232
BLG008-01	BlueStorm/LP, 2 ports RS-232, includes surge suppression, additional low profile bracket, DB-9 cables. RoHS Compliant.	http://connecttech.com/product/bluestormlp-rs-232/	BlueStorm/LP RS-232
BLG010-01	BlueStorm/LP, 2 ports RS-422/485, includes surge suppression, additional standard height bracket, DB-9 cables. RoHS Compliant.	http://connecttech.com/product/bluestormlp-rs-485/	BlueStorm/LP RS-485
BLG012-01	BlueStorm/LP, 2 ports RS-422/485, includes surge suppression, additional low profile bracket, DB-9 cables. RoHS Compliant.	http://connecttech.com/product/bluestormlp-rs-485/	BlueStorm/LP RS-485
BLG018-01	BlueStorm/LP, 4 ports RS-232, includes surge suppression, additional standard height bracket, DB-9 cables. RoHS Compliant.	http://connecttech.com/product/bluestormlp-rs-232/	BlueStorm/LP RS-232
BLG018-05	BlueStorm/LP, 4 ports RS-232, includes surge suppression, additional standard height bracket, DB-25 cables. RoHS Compliant.	http://connecttech.com/product/bluestormlp-rs-232/	BlueStorm/LP RS-232
BLG020-01	BlueStorm/LP, 4 ports RS-232, includes surge suppression, additional low profile bracket, DB-9 cables. RoHS Compliant.	http://connecttech.com/product/bluestormlp-rs-232/	BlueStorm/LP RS-232
BLG020-05	BlueStorm/LP, 4 ports RS-232, includes surge suppression, additional low profile bracket, DB-25 cables. RoHS Compliant.	http://connecttech.com/product/bluestormlp-rs-232/	BlueStorm/LP RS-232
BLG022-01	BlueStorm/LP, 4 ports RS-422/485, includes surge suppression, additional standard height bracket, DB-9 cables. RoHS Compliant.	http://connecttech.com/product/bluestormlp-rs-485/	BlueStorm/LP RS-485
BLG022-05	BlueStorm/LP, 4 ports RS-422/485, includes surge suppression, additional standard height bracket, DB-25 cables. RoHS Compliant.	http://connecttech.com/product/bluestormlp-rs-485/	BlueStorm/LP RS-485

Part #	Description	Product Datasheet	Product Group
BLG024-01	BlueStorm/LP, 4 ports RS-422/485, includes surge suppression, additional low profile bracket, DB-9 cables. RoHS Compliant.	http://connecttech.com/product/bluestormlp-rs-485/	BlueStorm/LP RS-485
BLG024-05	BlueStorm/LP, 4 ports RS-422/485, includes surge suppression, additional low profile bracket, DB-25 cables. RoHS Compliant.	http://connecttech.com/product/bluestormlp-rs-485/	BlueStorm/LP RS-485
BLG026-01	BlueStorm/LP, 2 ports RS-232 and 2 ports RS-422/485, includes surge suppression, additional standard height bracket, DB-9 cables. RoHS Compliant.	http://connecttech.com/product/bluestormlp-rs-485/	BlueStorm/LP RS-485
BLG026-05	BlueStorm/LP, 2 ports RS-232 and 2 ports RS-422/485, includes surge suppression, additional standard height bracket, DB-25 cables. RoHS Compliant.	http://connecttech.com/product/bluestormlp-rs-485/	BlueStorm/LP RS-485
BLG028-01	BlueStorm/LP, 2 ports RS-232 and 2 ports RS-422/485, includes surge suppression, additional low profile bracket, DB-9 cables. RoHS Compliant.	http://connecttech.com/product/bluestormlp-rs-485/	BlueStorm/LP RS-485
BLG033-01	BlueStorm/LP, 8 ports RS-232, includes surge suppression, additional standard height bracket, DB-9 cables. RoHS Compliant.	http://connecttech.com/product/bluestormlp-rs-232/	BlueStorm/LP RS-232
BLG033-03	BlueStorm/LP, 8 ports RS-232, includes surge suppression, additional standard height bracket, external DB-9 I/O box. RoHS Compliant.	http://connecttech.com/product/bluestormlp-rs-232/	BlueStorm/LP RS-232
BLG033-05	BlueStorm/LP, 8 ports RS-232, includes surge suppression, additional standard height bracket, DB-25 cables. RoHS Compliant.	http://connecttech.com/product/bluestormlp-rs-232/	BlueStorm/LP RS-232
BLG035-01	BlueStorm/LP, 8 ports RS-232, includes surge suppression, additional low profile bracket, DB-9 cables. RoHS Compliant.	http://connecttech.com/product/bluestormlp-rs-232/	BlueStorm/LP RS-232
BLG035-03	BlueStorm/LP, 8 ports RS-232, includes surge suppression, additional low profile bracket, external DB-9 I/O box. RoHS Compliant.	http://connecttech.com/product/bluestormlp-rs-232/	BlueStorm/LP RS-232
BLG035-05	BlueStorm/LP, 8 ports RS-232, includes surge suppression, additional low profile bracket, DB-25 cables. RoHS Compliant.	http://connecttech.com/product/bluestormlp-rs-232/	BlueStorm/LP RS-232
BLG037-01	BlueStorm/LP, 8 ports RS-422/485, includes surge suppression, additional standard height bracket, DB-9 cables. RoHS Compliant.	http://connecttech.com/product/bluestormlp-rs-485/	BlueStorm/LP RS-485
BLG037-03	BlueStorm/LP, 8 ports RS-422/485, includes surge suppression, additional standard height bracket, external DB-9 I/O box. RoHS Compliant.	http://connecttech.com/product/bluestormlp-rs-485/	BlueStorm/LP RS-485
BLG037-05	BlueStorm/LP, 8 ports RS-422/485, includes surge suppression, additional standard height bracket, DB-25 cables. RoHS Compliant.	http://connecttech.com/product/bluestormlp-rs-485/	BlueStorm/LP RS-485
BLG039-01	BlueStorm/LP, 8 ports RS-422/485, includes surge suppression, additional low profile bracket, DB-9 cables. RoHS Compliant.	http://connecttech.com/product/bluestormlp-rs-485/	BlueStorm/LP RS-485
BLG039-03	BlueStorm/LP, 8 ports RS-422/485, includes surge suppression, additional low profile bracket, external DB-9 I/O box. RoHS Compliant.	http://connecttech.com/product/bluestormlp-rs-485/	BlueStorm/LP RS-485

Part #	Description	Product Datasheet	Product Group
BLG039-05	BlueStorm/LP, 8 ports RS-422/485, includes surge suppression, additional low profile bracket, DB-25 cables. RoHS Compliant.	http://connecttech.com/product/bluestormlp-rs-485/	BlueStorm/LP RS-485
BLG041-01	BlueStorm/LP, 4 ports RS-232 and 4 ports RS-422/485, includes surge suppression, additional standard height bracket, DB-9 cables. RoHS Compliant.	http://connecttech.com/product/bluestormlp-rs-485/	BlueStorm/LP RS-485
BLG041-03	BlueStorm/LP, 4 ports RS-232 and 4 ports RS-422/485, includes surge suppression, additional standard height bracket, external DB-9 I/O box. RoHS Compliant.	http://connecttech.com/product/bluestormlp-rs-485/	BlueStorm/LP RS-485
BLG041-05	BlueStorm/LP, 4 ports RS-232 and 4 ports RS-422/485, includes surge suppression, additional standard height bracket, DB-25 cables. RoHS Compliant.	http://connecttech.com/product/bluestormlp-rs-485/	BlueStorm/LP RS-485
BLG043-01	BlueStorm/LP, 4 ports RS-232 and 4 ports RS-422/485, includes surge suppression, additional low profile bracket, DB-9 cables. RoHS Compliant.	http://connecttech.com/product/bluestormlp-rs-485/	BlueStorm/LP RS-485
BLG043-03	BlueStorm/LP, 4 ports RS-232 and 4 ports RS-422/485, includes surge suppression, additional low profile bracket, external DB-9 I/O box. RoHS Compliant.	http://connecttech.com/product/bluestormlp-rs-485/	BlueStorm/LP RS-485
BLG043-05	BlueStorm/LP, 4 ports RS-232 and 4 ports RS-422/485, includes surge suppression, additional low profile bracket, DB-25 cables. RoHS Compliant.	http://connecttech.com/product/bluestormlp-rs-485/	BlueStorm/LP RS-485
BLG049-01	BlueStorm/LP, 6 ports RS-232 and 2 ports RS-422/485, includes surge suppression, additional standard height bracket, DB-9 cables. RoHS Compliant.	http://connecttech.com/product/bluestormlp-rs-485/	BlueStorm/LP RS-485
BLG049-03	BlueStorm/LP, 6 ports RS-232 and 2 ports RS-422/485, includes surge suppression, additional standard height bracket, external DB-9 I/O box. RoHS Compliant.	http://connecttech.com/product/bluestormlp-rs-485/	BlueStorm/LP RS-485
BLG049-05	BlueStorm/LP, 6 ports RS-232 and 2 ports RS-422/485, includes surge suppression, additional standard height bracket, DB-25 cables. RoHS Compliant.	http://connecttech.com/product/bluestormlp-rs-485/	BlueStorm/LP RS-485
BLG051-01	BlueStorm/LP, 6 ports RS-232 and 2 ports RS-422/485, includes surge suppression, additional low profile bracket, DB-9 cables. RoHS Compliant.	http://connecttech.com/product/bluestormlp-rs-485/	BlueStorm/LP RS-485
BLG051-03	BlueStorm/LP, 6 ports RS-232 and 2 ports RS-422/485, includes surge suppression, additional low profile bracket, external DB-9 I/O box. RoHS Compliant.	http://connecttech.com/product/bluestormlp-rs-485/	BlueStorm/LP RS-485

Part #	Description	Product Datasheet	Product Group
BLG051-05	BlueStorm/LP, 6 ports RS-232 and 2 ports RS-422/485, includes surge suppression, additional low profile bracket, DB-25 cables. RoHS Compliant.	http://connecttech.com/product/bluestormlp-rs-485/	BlueStorm/LP RS-485
BMG006-01	Blue Heat/Net Sync, 4 port synchronous/asynchronous communication device, includes one CBG006, a 6ft CAT5 RJ-45 cable and a MSG007 universal power supply with line cord. RoHS Compliant.	http://connecttech.com/product/blue-heatnet-sync/	Blue Heat/Net Sync
BNG004-03	Blue Heat/Net, 8 ports RS-232 with Ethernet cable, includes one MSG005 EU power supply. RJ-45 serial connectors. RoHS Compliant.	http://connecttech.com/product/blue-heatnet-4-or-8/	Blue Heat/Net
BNG004-04	Blue Heat/Net, 8 ports RS-232 with Ethernet cable, includes one MSG007 and a universal supply. RJ-45 serial connectors. RoHS Compliant.	http://connecttech.com/product/blue-heatnet-4-or-8/	Blue Heat/Net
BNG006-01	Blue Heat/Net, 4 ports RS-232/422/485 with Ethernet cable and one MSG007 universal power supply. DB-9 serial connectors. RoHS Compliant.	http://connecttech.com/product/blue-heatnet-4-or-8/	Blue Heat/Net
BNG008-01	Blue Heat/Net, 8 ports RS-232/422/485 with Ethernet cable and one MSG007 universal power supply. DB-9 serial connectors. RoHS Compliant.	http://connecttech.com/product/blue-heatnet-4-or-8/	Blue Heat/Net
BNG008-02	Blue Heat/Net, 8 ports RS-232/422/485 with Ethernet cable, includes one MSG007 universal power supply. Ships with an additional power option, a 9-30V screw terminal and is 1U rack mount height with brackets available for mounting in a 19" rack (MSG029-included), DB-9 serial connectors. RoHS Compliant.	http://connecttech.com/product/blue-heatnet-4-or-8/	Blue Heat/Net
BNG009-03	Blue Heat/Net includes: one BNG009, a Blue Heat/Net 2 port RS-232 adapter; one CBG006, a 6ft CAT5 RJ-45 cable and one MSG005, an EU power supply. Industrial Temp. -40°C to 85°C. DB-9 serial connectors. RoHS Compliant.	http://connecttech.com/product/blue-heatnet-2/	Blue Heat/Net 2
BNG009-04	Blue Heat/Net includes: one BNG009, a Blue Heat/Net 2 port RS-232 adapter; one CBG006, a 6ft CAT5 RJ-45 cable and one MSG007, a universal power supply. Industrial Temp. -40°C to 85°C. DB-9 serial connectors. RoHS Compliant.	http://connecttech.com/product/blue-heatnet-2/	Blue Heat/Net 2
BNG009-05	Blue Heat/Net includes: one BNG009 Blue Heat/Net 2 port RS-232 adapter; one CBG006, a 6ft CAT5 RJ-45 cable and includes PoE and 36-56VDC input with screw down terminal connector. DB-9 serial connectors. RoHS Compliant.	http://connecttech.com/product/blue-heatnet-2/	Blue Heat/Net 2
BNG010-03	Blue Heat/Net includes: one BNG010, a Blue Heat/Net 2 port RS-232/422/485 adapter; one CBG006, a 6ft CAT5 RJ-45 cable and one MSG005, and an EU power supply. Industrial Temp. -40°C to 85°C. DB-9 serial connectors. RoHS Compliant.	http://connecttech.com/product/blue-heatnet-2/	Blue Heat/Net 2

Part #	Description	Product Datasheet	Product Group
BNG010-04	Blue Heat/Net includes: one BNG010, a Blue Heat/Net 2 port RS-232/422/485 adapter; one CBG006, a 6ft CAT5 RJ-45 cable and one MSG007, universal power supply. Industrial Temp. -40°C to 85°C. DB-9 serial connectors. RoHS Compliant.	http://connecttech.com/product/blue-heatnet-2/	Blue Heat/Net 2
BNG010-09	Blue Heat/Net includes: one BNG010 Blue Heat/Net 2 port RS-232/422/485 adapter; one CBG006, a 6ft CAT5 RJ-45 cable and includes PoE and 36-56VDC input with screw down terminal connector. DB-9 serial connectors. RoHS Compliant.	http://connecttech.com/product/blue-heatnet-2/	Blue Heat/Net 2
BSG001	BlueStorm/SP Opto, 4 ports RS-232/422/485, includes 3kV optical isolation and surge suppression. RoHS Compliant.	http://connecttech.com/product/bluestormsp-opto/	BlueStorm/SP Opto
BSG001-01	BlueStorm/SP Opto, 4 ports RS-232/422/485, includes 3kV optical isolation and surge suppression, RJ-45 to DB-9 cables. RoHS Compliant.	http://connecttech.com/product/bluestormsp-opto/	BlueStorm/SP Opto
BTG001	BlueStorm/SP, 8 ports RS-232/422/485, includes surge suppression. RoHS Compliant.	http://connecttech.com/product/bluestormsp/	BlueStorm/SP
BTG001-01	BlueStorm/SP, 8 ports RS-232/422/485, surge suppression, DB-9 cables. RoHS Compliant.	http://connecttech.com/product/bluestormsp/	BlueStorm/SP
BTG007	BlueStorm/SP, 8 ports RS-232. RoHS Compliant.	http://connecttech.com/product/bluestormsp/	BlueStorm/SP
BTG007-01	BlueStorm/SP, 8 ports RS-232, DB-9 cables. RoHS Compliant.	http://connecttech.com/product/bluestormsp/	BlueStorm/SP
BTG008	BlueStorm/SP RJ-11, 8 ports RS-232, surge suppression, six RJ-11 connectors, two 10-pin headers. RoHS Compliant.	http://connecttech.com/resource-center/downloads-for-bluestormsp-rj-11-btg008/	BlueStorm/SP RJ-11
BTG008-01	BlueStorm/SP RJ-11, 8 ports RS-232, surge suppression, six RJ-11 connectors, two 10-pin headers, DB-9 cable. RoHS Compliant.	http://connecttech.com/resource-center/downloads-for-bluestormsp-rj-11-btg008/	BlueStorm/SP RJ-11
CAG04DX	4 port DB-9 cable for use with legacy Blue Heat and Dflex products. RoHS Compliant.		
CAG04MT	4 port DB-25 DTE cable for use with legacy Blue Heat, DFlex and Intellicon products. RoHS Compliant.		
CAG08DB25	8 port DB-25 cable for use with legacy Blue Heat, DFlex and Intellicon-Flex. RoHS Compliant.		

Part #	Description	Product Datasheet	Product Group
CAG08FXDX	8 port DB-9 cable for use with legacy Blue Heat, Dflex and Intellicon-Flex. RoHS Compliant.		
CAG104	10 pin header to 1x DB-9 male connector for DAC		
CAG8104	Xtreme/104 cable, DB-9, 1 required for every 4 ports. RoHS Compliant.		
CBG001	26 pin header to 1x DB-25 female or GPIO		
CBG002	BlueStorm, 2 port cable, DB-9 (0.300m). RoHS Compliant.		
CBG003	BlueStorm, 4 port cable, DB-9 (0.300m). RoHS Compliant.		
CBG006	Ethernet cable, CAT5 RJ45 cable (1.83m). RoHS Compliant.		
CBG007	BlueStorm, 4 port cable, DB-25 (0.305m). RoHS Compliant.		
CBG009	BlueStorm, 8 port cable, DB-9 (0.305m). RoHS Compliant.		
CBG013	Xtreme/104 Isolated, RS-232 cable, 4 required per board. RoHS Compliant.		
CBG014	Xtreme/104 Isolated, RS-232/422/485 cable, 8 required per board. RoHS Compliant.		
CBG026	BlueStorm, 8 port cable, DB-25 (0.305m). RoHS Compliant.		
CBG028	BlueStorm, 8 port cable, DB-25 (1.22m). RoHS Compliant.		
CBG033	VHDCI to 8xDB9M 1220mm RoHS		
CBG067	10 CCT locking connector to DB-9 male, 12 per board. RoHS Compliant.		
CBG103	Micro-USB to USB-A programming cable. RoHS Compliant.		
CBG112	6-pin MiniTek w/Latch CTIC-00431 power cable unterminated forxDG024		
CBG113	DisplayPort++ panel mount to 20-pin MiniTek w/Latch		
CBG117	RJ-45 panel mount to 10-pin MiniTek w/Latch cable. (MPG104 requires 2x CBG117 per board)		
CBG121	Dual DB9 to Minitek 20 pin cable		
CBG125	LVDS (DP20A-40DS) to Un-Terminated Wires		
CBG136	RTC Battery Cable		
CBG145	HDMI Female to 20-Pin Minitek Cable		
CBG162	External I/O Cable		
CBG163	R.FL to SMA Female Cable		
CBG190	10-pin Minitek to Flying Lead Cable optional CANbus cable		
CBG191	DB9 to 10-pin Header 2mm.		
CBG202	10-pin MiniTek w/Latch serial breakout cable forxDG024		
CBG209	8 Port Breakout Cable forxDG024 andXDG032.		
CBG210	8 Port Breakout Cable forxDG025 andXDG033.		
CBG212	XDG025 Serial Cable		
CBG213	XDG025 Power Cable		

Part #	Description	Product Datasheet	Product Group
CBG214	HSC (MHF4) to SMA Female Cable		
CBG225	Flying Lead Cable - U.FL to SMA 10-pin PicoBlade IO cable w/Flying Leads (2 required per board)		
CBG249	6-pin PicoBlade IO cable w/Flying Leads		
CBG250	3-pin PicoBlade IO cable w/Flying Leads		
CCG001	COM Express Type 2 Basic and Compact module Carrier Board with PCI-104 and PCIe/104 bus, LVDS, HDMI, VGA, 4x USB 2.0, 2x SATA, 1x mSATA, CF, Audio, Ethernet, 4x RS-232, 4x RS-485, GPIO, -30C to +80C, RoHS Compliant.	http://connecttech.com/resource-center/downloads-for-com-express-type-2-carrier-board-ccg001/	COM Express® Type 2 Carrier Board
CCG007	COM Express Type 6 PMC/XMC Carrier - a full featured carrier includes 2x PMC/XMC slots, 4x mini PCIe slots, dual gigabit Ethernet, HDMI, DisplayPort, DVI, LVDS, VGA, 8 USB ports (4xUSB 3.0), HD Audio, 3x RS232, 2 RS485, 8 bits GPIO and +9V to +36V DC input. Designed to fit in a 19" rack. RoHS Compliant.	http://connecttech.com/product/com-express-type-6-pmcxmc-carrier-board/	COM Express® Type 6 PMC/XMC Carrier Board
CCG008	COM Express Type 6 Ultra Lite Carrier - a full featured compact carrier, 125mm x 95mm. Provides 2x Gigabit Ethernet, MicroSD card slot, 2x mini PCIe/mSATA slots, HDMI, LVDS, VGA, 2x SATA, 3x RS232, 2x RS485, 6 USB Ports: 4 USB 3.0 ports, 2 USB 2.0 ports available via DIL header, 8 bits GPIO, +12V DC input, -40 to +85C. RoHS Compliant.	http://connecttech.com/product/com-express-type-6-ultra-lite-carrier-board/	COM Express® Type 6 Ultra Lite Carrier Board
CCG010	COM Express Type 10 Mini Carrier Board, 84mm x 55mm with 2x mini PCIe, mSATA, SATA, 2x GBE, 6x USB 2.0, LVDS, DisplayPort/HDMI/DVI/VGA, HD Audio, 2x RS-232/422/485. RoHS Compliant.	http://connecttech.com/product/com-express-type-10-mini-carrier-board/	COM Express® Type 10 Mini Carrier Board
CCG011	COM Express Type 6 Ultra Lite Carrier - a full-featured compact carrier, 125mm x 95mm. Provides 2x Gigabit Ethernet, MicroSD card slot, 2x mini PCIe slots, HDMI, LVDS, VGA, 2x SATA, 2x mSATA, 3x RS232, 2x RS485, 8 bits GPIO, +12V DC input. Connectors replaced with low-profile shrouded locking pin-headers. USB2.0 ONLY RoHS Compliant.	http://connecttech.com/product/com-express-type-6-rugged-ultra-lite-carrier-board/	COM Express® Type 6 Rugged Ultra Lite Carrier Board
CCG012	COM Express Type 6 Ultra Lite Carrier - a full-featured compact carrier, 125mm x 95mm. Provides 2x Gigabit Ethernet, MicroSD card slot, 2x mini PCIe slots, HDMI, LVDS, VGA, 2x SATA, 2x mSATA, 3x RS232, 2x RS485, 8 bits GPIO, +12V DC input. Connectors replaced with low-profile shrouded locking pin-headers. USB2.0& USB3.0 RoHS Compliant.	http://connecttech.com/product/com-express-type-6-rugged-ultra-lite-carrier-board/	COM Express® Type 6 Rugged Ultra Lite Carrier Board

Part #	Description	Product Datasheet	Product Group
CCG013	COM Express Type 6 Rugged Carrier is small in size, 170mm x 165mm and features all locking pin connectors. The carrier provides 2x PMC/XMC expansion, 4x USB 3.0, 2x USB 2.0, 2x GBE, MicroSD card slot, 2x mini PCIe slots, 2x DisplayPort++, LVDS, VGA, 2x SATA, 2x mSATA, 1x RS232, 8 bits GPIO, +12V to +48V DC input. RoHS Compliant.	http://connecttech.com/product/com-express-type-6-pmcxmc-ultra-lite-carrier/	COM Express® Type 6 PMC/XMC Ultra Lite Carrier
CCG016	COM Express Type 6 Rugged Carrier is small in size, 190mm x 165mm and features all locking pin connectors. The carrier provides 2x PMC/XMC expansion, 4x USB 3.0, 2x USB 2.0, 2x GBE, MicroSD card slot, 2x mini PCIe slots, 2x DisplayPort++, LVDS, VGA, 2x SATA, 2x mSATA, 1x RS232, 8 bits GPIO, +12V to +48V DC input. RoHS Compliant.	http://connecttech.com/product/com-express-type-6-pmcxmc-lite-carrier/	COM Express® Type 6 PMC/XMC Lite Carrier
CCG017	COM Express Type 6 104e Carrier Board, 125mm x 95mm with PCIe/104 bus, 2x Gigabit Ethernet, 2x Mini- PCIe/mSATA, 1x DisplayPort/HDMI/DVI (on board switching), 1x VGA, 1x LVDS, 4x USB 3.0, 2x RS-232/RS-485, HD Audio +12VDC input, rugged latching connectors, -40o C to +85o C, RoHS Compliant.	http://connecttech.com/product/com-express-type-6-104e/	COM Express® Type 6 104e
CCG018	COM Express Type 6 104e Carrier Board, 125mm x 95mm with PCIe/104 bus, 4x PCIe x1 Links, 1x PEG Link (PCIe x16), 2x Gigabit Ethernet, 2x Mini-Pcie/mSATA, 1x DisplayPort/HDMI/DVI (on board switching), 1x VGA, 1x LVDS, 4x USB 3.0, 2x RS-232/RS-485, HD Audio +12VDC input, rugged latching connectors, -40o C to +85o C, RoHS Compliant.	http://connecttech.com/product/com-express-type-6-104e/	COM Express® Type 6 104e
CCG020	COM Express Type 10 Mini Carrier Board, 84mm x 55mm with 2x mini PCIe, mSATA, 2x GBE, 2x USB2.0, 2x USB3.0, LVDS, DisplayPort/HDMI/DVI/VGA, HD Audio, 2x RS-232/422/485. RoHS Compliant.	http://connecttech.com/product/com-express-type-10-mini-carrier-board/	COM Express® Type 10 Mini Carrier Board
CCG022	COM Express Type 10 Mini Carrier Board, 84mm x 73.415mm with 2x half size mini PCIe, mSATA, 2x GBE, 2x USB2.0, 2x USB3.0 Type A (if supported by COM Express module), LVDS, HDMI, 8-bit GPIO, SMBus, I2C, HD Audio, 2x RS-232/422/485, 6 to 14V DC input, -40°C to +85°C. RoHS Compliant.	http://connecttech.com/product/com-express-type-10-pc-connector-carrier/	COM Express® Type 10 PC Connector Carrier
CCG030	COM Express Type 10 carrier utilizing high density connector for use with Connect Tech breakout boards or custom designed breakout boards. RoHS Compliant.	http://connecttech.com/product/com-express-type-10-stacking-carrier/	COM Express® Type 10 Stacking Carrier

Part #	Description	Product Datasheet	Product Group
CCG060	COM Express Type 6 carrier utilizing high density connector, 125mm x 95mm (4.92" x 3.74"), 3x Mini PCIe Modules, 4x GbE Ports with On-Board Magnetics, PCI Express x16 Bus Design Access, use with Off-the-Shelf or Custom designed breakout boards, -40o C to +85o C. RoHS Compliant.	http://connecttech.com/product/com-express-type-6-stacking-carrier/	COM Express® Type 6 Stacking Carrier
CCG070	COM Express Type 7 Carrier Featuring: Two Ports of 10G SFP+, Two Ports of RJ45 GbE (1000Base-T), Four USB 3.0 ports, Two USB 2.0 ports, One external SATA connector, Two mini PCIe slots, One M.2 2280 SSD slot (M Key), One Serial Port. RoHS Compliant.	http://connecttech.com/product/com-express-type-7-carrier-board/	COM Express® Type 7 Carrier Board
CKG001	Qseven Cable Kit: VGA, GbE, USB (dual), Serial, ATX power, 5V only power, keyboard and mouse, LVDS unterminated, backlight unterminated, SATA, power button, fan unterminated. RoHS Compliant.	http://connecttech.com/cables/ckg001/	CKG001 Cable Kit
CKG005	QCG005 Cable Kit: Qseven LVDS unterminated (CBG076). Qseven Backlight unterminated (CBG078). Qseven SATA (CBG079). Qseven USB (dual) x 2 (CBG071). RoHS Compliant.		CKG005 Cable Kit
CKG006	QCG006 Cable Kit: HDMI Cable (CBG086). SATA Cable x 2 (CBG079). Qseven LVDS unterminated (CBG076). Qseven Backlight unterminated (CBG078). Qseven USB (dual) x 4 (CBG071). RoHS Compliant.		CKG006 Cable Kit
CKG007	CCG001 Cable Kit: Backlight unterminated (CBG078), LVDS unterminated (CBG076), Serial (CBG073), VGA (CBG070), SATA Signal and Power (CBG090), Power button (CBG080). RoHS Compliant.	http://connecttech.com/cables/ckg007/	CKG007 Cable Kit
CKG009	Cable kit for CCG008, includes cable for serial, GPIO, VGA, SATA and power. RoHS Compliant.	http://connecttech.com/cables/ckg009/	CKG009 Cable Kit
CKG014	Cable Kit for CCG010, includes 3x Dual USB 2.0, Dual DB-9, Power Cable, DisplayPort, 2x Ethernet, Dual Audio. RoHS Compliant.	http://connecttech.com/cables/ckg014/	CKG014 Cable Kit
CKG015	Cable Kit for CCG010, includes 1x Dual USB 2.0, Power Cable, DisplayPort, 1x Ethernet. RoHS Compliant.	http://connecttech.com/cables/ckg015/	CKG015 Cable Kit
CKG018	Cables for QCG015: CBG076 LVDS unterminated, CBG078 Backlight unterminated, CBG079 SATA, 2x CBG071 dual 2.0 USB, CBG065 Ethernet, CBG129 Micro HDMI to HDMI A, CBG127 DB9 serial.		CKG018 Cable Kit
CKG019	Cable set for XDG007/XDG008/XDG009/XDG019/XDG020/XDG021. 8x RJ-45 panel mount to MiniTek w/Latch (CBG117) and 1x DB-9 panel mount to 10-pin MiniTek w/Latch (CBG127). RoHS Compliant.	http://connecttech.com/cables/ckg019/	CKG019 Cable Kit

Part #	Description	Product Datasheet	Product Group
CKG020	Cable kit for CCG011 (full), includes 1x CBG104 -Dual USB 2.0 panel mount to 8-pin MiniTek w/Latch, 2x CBG130 -Dual USB 3.0 panel mount to 20-pin MiniTek w/Latch, 1x CBG120 -VGA to 10-pin MiniTek w/Latch, 2x CBG113 - Display Port panel mount to 20-pin MiniTec w/Latch, 2x CBG117 -RJ-45 panel mount to 10-pin MiniTek w/Latch, 1x CBG118 -Dual 3.5mm Stereo Audio panel mount to 8-pin MiniTek w/Latch, 3x CBG121 -Dual DB-9 panel mount to 20-pin MiniTek w/Latch, 2x CBG090 -SATA Signal and Power Combo Cable, 1x CBG116 -System Cable, Unterminated wires to 20-pin MiniTek w/Latch. RoHS Compliant.	http://connecttech.com/cables/ckg020/	CKG020 Cable Kit
CKG021	Starter cable kit for CCG011 /CCG012/CCG013/CCG016 and VXG series, includes 1x CBG104 - Dual USB 2.0 panel mount to 8-pin MiniTek w/Latch, 1x CBG120 - VGA to 10-pin MiniTek w/Latch, 1x CBG117 - RJ-45 panel mount to 10-pin MiniTek w/Latch, 1x CBG090-SATA Signal and Power Combo Cable. RoHS Compliant.	http://connecttech.com/cables/ckg021/	CKG021 Cable Kit
CKG026	Full Cable Kit for VXGxxx, 2x SATA HDD + Power cable (CBG090), 1x VGA to 10-pin MiniTek cable (CBG120), 3x Dual DB9 to 20-pin MiniTek cable (CBG121), 1x Dual USB 2.0 to 8-pin MiniTek cable (CBG104), 6x Displayport to 20-pin cable (CBG113), 2x RJ-45 to 10-pin MiniTek cable (CBG117), 1x Dual Audio to 8-pin MiniTek cable (CBG118), 1x System- Mics to 20-pin MiniTek cable (CBG116), 2x Dual USB 3.0 to 20-pin Locking Intel Style Header (CBG131). RoHS Compliant.	http://connecttech.com/cables/ckg026/	CKG026 Cable Kit
CKG029	Cableset for xDG010/XDG012/XDG022, 2x CBG117, 1x CAG104. RoHS Compliant.	http://connecttech.com/cables/ckg029/	CKG029 Cable Kit
CKG031	Starter Cable Kit for QCG202, QKG20x series, 1x CBG090 SATA HDD Signal and Power Cable, 1x CBG104 Dual USB 2.0 to 8-Pin Minitek Cable, 1x CBG113 DisplayPort to 20-Pin Minitek Cable, 1x CBG117 RJ-45 to 10-Pin Minitek Cable, 1x CBG118 Dual Audio to 8-Pin Minitek Cable, 1x CBG127 DB-9 to Minitek Cable, 1x CBG134 10-Pin Minitek System Cable. RoHS Compliant.	http://connecttech.com/cables/ckg031/	CKG031 Cable Kit
CKG033	Cableset for xDG013/XDG023, 12x CBG117, 1x CAG104. RoHS Compliant.		CKG033 Cable Kit
CKG034	Cableset for SMARC/SL carrier board, 1x camera cable, 1 x SATA CBG079 , 1x Dual USB 2.0 CBG104, 1x GbE CBG117, 1x HD Audio CBG118, 1x DB-9 CBG127, 1x System CBG134, 1x HDMI CBG145		CKG034 Cable Kit

Part #	Description	Product Datasheet	Product Group
CKG035	Cable Kit for CCG020, includes CBG104 Dual USB 2.0, CBG111 Dual DB-9, CBG112 Power Cable, CBG113 DisplayPort, 2x CBG117 Ethernet, CBG118 Dual Audio, CBG116 System Cable. CBG160 Dual USB 3.0 to 20-pin RA USB3.0 Cable Panel Mount: Right Angle Inner Exit, CBG288 Dual USB 3.0 to 20-pin RA USB3.0 Cable Panel Mount: Vertical Exit , CBG287Dual USB 3.0 to 20-pin RA USB3.0 Cable Panel Mount: Right Angle Outer Exit. RoHS Compliant.	http://connecttech.com/cables/ckg035/	CKG035 Cable Kit
CKG041	Starter Cable Kit for Astro Breakout Board xBG201. 1x CBG118- 8-pin MiniTek w/Latch, 1x CBG190- 10-pin MiniTek w/Latch, 1x CBG111- 10-pin MiniTek w/Latch, 1x CBG136- RTC battery, 1x CBG112- 6-pin MiniTek w/Latch. RoHS Compliant.	http://connecttech.com/cables/ckg041/	CKG041 Cable Kit
CKG042	Cable Kit for ELROY- ASG002. CBG111 – Dual DB9 Panel Mount to 10-Pin MiniTek, CBG112 – Power Cable (Unterminated) to 6-Pin MiniTek, CBG116 – System Cable (Unterminated) to 20-Pin MiniTek, CBG117 – RJ-45 Panel Mount to 10-Pin MiniTek, CBG131 – Dual USB 3.0 Cable to Intel Style Header, CBG145 – HDMI Female Panel Mount to 20-Pin MiniTek. RoHS Compliant.	http://connecttech.com/cables/ckg042/	CKG042 Cable Kit
CKG043	CBG116 - System Misc. to 20 pin Minitek Cable, CBG136 - RTC Battery Cable, CBG247 - Micro USB Cable. RoHS Compliant.	http://connecttech.com/cables/ckg043/	CKG043 Cable Kit
CKG044	Cable Kit for CCG022 includes 1x CBG111 Dual DB-9 to Minitek Cable, 1x CBG112 Power Cable - Unterminated wires to 6-pin MiniTek w/Latch, 1x CBG116 System Cable - Unterminated wires to 20-pin MiniTek w/Latch, 1x CBG118 Dual 3.5mm Stereo Audio panel mount to 8-pin MiniTek w/Latch	http://connecttech.com/cables/ckg044/	CKG044 Cable Kit
CKG045	ASG006 Cable Kit: 2x CBG116 System Cable - Unterminated wires to 20-pin MiniTek w/Latch, 2x CBG117RJ-45 to Minitek Cable, 1x CBG104Dual USB 2.0 panel mount to 8-pin MiniTek w/Latch, 1x CBG191 DB9 to 10-pin Header 2mm.	http://connecttech.com/cables/ckg045/	CKG045 Cable Kit
CKG049	Cable Kit for SRG004. 2 x CBG248, 10-pin picoblade IO cable w/Flying Leads CBG249: 6-pin picoblade RS232 cable w/Flying Leads CBG250: 3-pin picoblade I2C cable w/Flying Leads CBG136: RTC Battery Cable RoHS Compliant.		CKG049 Cable Kit

Part #	Description	Product Datasheet	Product Group
CKG053	Full Cable Kit for VXGxxx, 2x SATA HDD + Power cable (CBG090), 1x VGA to 10-pin MiniTek cable (CBG120), 3x Dual DB9 to 20-pin MiniTek cable (CBG121), 1x Dual USB 2.0 to 8-pin MiniTek cable (CBG104), 6x Displayport to 20-pin cable (CBG113), 2x RJ-45 to 10-pin MiniTek cable (CBG117), 1x Dual Audio to 8-pin MiniTek cable (CBG118), 1x System-Mics to 20-pin MiniTek cable (CBG116), 2x CBG160 Dual USB 3.0 to 20-pin RA USB3.0 Cable Panel Mount: Right Angle Inner Exit, 2x CBG287 Dual USB 3.0 to 20-pin RA USB3.0 Cable Panel Mount: Right Angle Outer Exit, 2x CBG288 Dual USB 3.0 to 20-pin RA USB3.0 Cable Panel Mount: Vertical Exit. RoHS Compliant.	http://connecttech.com/cables/ckg053/	CKG053 Cable Kit
CKG055	Cable kit for CCG012 (full), includes 1x CBG104 - Dual USB 2.0 panel mount to 8-pin MiniTek w/Latch, 2x CBG160 – Dual USB 3.0 Cable to 20-pin RA USB3.0 Cable Panel Mount: Right Angle Inner Exit, 2x CBG287 - Dual USB 3.0 to 20-pin RA USB3.0 Cable Panel Mount: Right Angle Outer Exit , 2x CBG288 - Dual USB 3.0 to 20-pin RA USB3.0 Cable Panel Mount: Vertical Exit, 1x CBG120-VGA to 10-pin MiniTek w/Latch, 2x CBG117-RJ-45 panel mount to 10-pin MiniTek w/latch, 2x CBG090 SATA Signal and Power Combo Cable, 2x CBG113 Display port ++ panel mount to 20-pin MiniTek w/latch, 1x CBG118 Dual 3.5mm Stereo Audio panel mount to 8-pin MiniTek w/latch, 3x CBG121 Dual DB-9 panel mount to 20-pin MiniTek w/latch, 1x CBG116 System Cable, unterminated wired to 20-pin MiniTek w/latch. RoHS Compliant.	http://connecttech.com/cables/ckg055/	CKG055 Cable Kit
CKG056	Starter Cablesset for CCG017 & CCG018, CBG090 SATA HDD signal and power cable, CBG113 DisplayPort to 20-Pin Minitex, CBG117 RJ-45 to 10-pin MiniTek, CBG118 Dual Audio to 8-pin MiniTek cable, CBG120 VGA to 10-pin MiniTek, CBG287 Dual USB 3.0 to 20-pin RA USB3.0 Cable Panel Mount: Right Angle Outer Exit, CBG288 Dual USB 3.0 to 20-pin RA USB3.0 Cable Panel Mount: Vertical Exit,, CBG145 HDMI Female to 20-pin MiniTek cable, CBG186 COM Express 16-pin MiniTek System Cable. RoHS Compliant.	http://connecttech.com/cables/ckg056/	CKG056 Cable Kit

Part #	Description	Product Datasheet	Product Group
CKG057	*RECOMENDED* Full Cablesset for CCG017 & CCG018, CBG090 SATA HDD signal and power cable, CBG111 Dual DB-9 Panel Mount to 10-pin MiniTek, 2x CBG113 DisplayPort to 20-Pin Minitek, 2x C BG117 RJ-45 to 10- pin MiniTek, CBG118 Dual Audio to 8-pin MiniTek cable, CBG120 VGA to 10-pin MiniTek, 2x CBG287 Dual USB 3.0 to 20-pin RA USB3.0 Cable Panel Mount: Right Angle Outer Exit, 2x CBG288 Dual USB 3.0 to 20-pin RA USB3.0 Cable Panel Mount: Vertical Exit, 2x CBG145 HDMI Female to 20-pin MiniTek cable, CBG186 COM Express 16-pin MiniTek System Cable. RoHS Compliant.	http://connecttech.com/cables/ckg057/	CKG057 Cable Kit
CKG058	Cable Kit for CCG020, includes CBG104 Dual USB 2.0, CBG112 Power Cable, CBG113 DisplayPort, 2x CBG117 Ethernet, CBG116 System Cable. CBG160 Dual USB 3.0 to 20-pin RA USB3.0 Cable Panel Mount: Right Angle Inner Exit, CBG288 Dual USB 3.0 to 20-pin RA USB3.0 Cable Panel Mount: Vertical Exit , CBG287Dual USB 3.0 to 20-pin RA USB3.0 Cable Panel Mount: Right Angle Outer Exit. RoHS Compliant.	http://connecttech.com/cables/ckg058/	CKG058 Cable Kit
CKG062	Cablesset for CCG013/CCG016 includes 1x CBG104 - Dual USB 2.0 panel mount to 8-pin MiniTek w/Latch, 2x CBG160 Dual USB 3.0 to 20-pin RA USB3.0 Cable Panel Mount: Right Angle Inner Exit, 2x CBG287 Dual USB 3.0 to 20-pin RA USB3.0 Cable Panel Mount: Right Angle Outer Exit, 2x CBG288 Dual USB 3.0 to 20-pin RA USB3.0 Cable Panel Mount: Vertical Exit, 1x CBG120 -VGA to 10-pin MiniTek w/Latch, 2x CBG117 - RJ-45 panel mount to 10-pin MiniTek w/Latch, 2x CBG090 SATA Signal and Power Combo Cable, 2x CBG113 DisplayPort++ panel mount to 20-pin MiniTek w/latch, 1x CBG118 Dual 3.5mm Stereo Audio panel mount to 8-pin MiniTek w/Latch, 1x CBG121 Dual DB-9 panel mount to 20-pin MiniTek w/latch, 1x CBG116 System Cable, unterminated wires to 20-pin MiniTek w/latch. RoHS Compliant.		CKG062 Cable Kit
CNG001	CANpro/104 Opto, PC/104 form factor, 2 ports, 3kV optical isolation. RoHS Compliant.		CANpro/104 Opto
CNG001-01	CANpro/104 Opto, PC/104 form factor, 2 ports, 3kV optical isolation, DB-9 cables. RoHS Compliant.		CANpro/104 Opto
CNG002	CANpro/104 Opto, 2 ports, 3kV optical isolation, 2x DB-9 connectors on board. RoHS Compliant.		CANpro/104 Opto
CPG001	ComSync/PCI-104, 2 port synchronous multi-protocol. RoHS Compliant.		ComSync/PCI-104

Part #	Description	Product Datasheet	Product Group
CPG001-01	ComSync/PCI-104, 2 port synchronous multi-protocol, DB-25 cables. RoHS Compliant.	http://connecttech.com/product/comsyncpci-104/	ComSync/PCI-104
CPG004	ComSync/PCI-104 Gen3 features the Zilog ESCC 85230 allowing for an extended Temp. operating range of -40 to +85 degrees C. Gen 3 offers DMA support and multiple electrical interfaces that are software selectable including RS-232, RS-422, RS-449, EIA-530, EIA-530/A, V.35 and X.21. RoHS Compliant.	http://connecttech.com/product/comsync-pci-104-gen-3/	ComSync/PCI-104 Gen. 3
CRG001	CANpro/104-Plus Opto, PCI-104 form factor, 2 ports 3kV optical isolation. Pass through PC/104 bus. RoHS Compliant.	http://connecttech.com/product/canpro104-plus-opto/	CANpro/104-Plus Opto
CRG001-01	CANpro/104-Plus Opto, PCI-104 form factor, 2 ports 3kV optical isolation, DB-9 cables. Pass through PC/104 bus. RoHS Compliant.	http://connecttech.com/product/canpro104-plus-opto/	CANpro/104-Plus Opto
CSG001	ComSync/104, 2 port synchronous multi-protocol. RoHS Compliant.	http://connecttech.com/product/comsync104/	ComSync/104
CSG001-01	ComSync/104, 2 port synchronous multi-protocol with 26 pin to DB-25 cables	http://connecttech.com/product/comsync104/	ComSync/104
CSG005	ComSync/104, 2 port synchronous multi-protocol, industrial Temp. -40°C to 85°C. RoHS Compliant.	http://connecttech.com/product/comsync104/	ComSync/104
CSG005-01	ComSync/104, 2 port synchronous multi-protocol with 26 pin to DB-25 cables, industrial Temp. -40°C to 85°C. RoHS Compliant.	http://connecttech.com/product/comsync104/	ComSync/104
CVS001	Specifically designed for use with GigE Vision Cameras. x Gigabit Ethernet Channels – 4x PoE, 2x PoE+ PSE Gigabit Ports. Only a single +12V input required; No external 48V PoE power required 1x USB 3.0, 1x USB 2.0, 1x USB OTG, 2x RS-232, 1x miniPCIe, 1x mSATA. Extended Temp. Range -20°C to +80°C. Mounting option (Surface Edge Mount)	http://connecttech.com/product/cogswell-vision-system/	Cogswell Vision System, Powered by NVIDIA® Jetson™ TX2/TX1
D7G001	COM Express Type 7 + GPU Embedded System. CPU: Xeon® D1577 1.3/2.1GHz 24MB Cache, with 48GB DDR4 2400MT/s ECC Memory, 45W (16C), GPU: NVIDIA Quadro P5000 (100W, 2048 CUDA Cores). With Active Cooling Solution. 2x 10G, 4x HDMI Variant	http://connecttech.com/product/com-express-type-7-gpu-embedded-system/	COM Express® Type 7 + GPU Embedded System
D7G002	COM Express Type 7 + GPU Embedded System. CPU: Xeon® D1577 1.3/2.1GHz 24MB Cache, with 48GB DDR4 2400MT/s ECC Memory, 45W (16C), GPU: NVIDIA Quadro P3000 (75W, 1280 CUDA Cores). With Active Cooling Solution. 2x 10G, 4x HDMI Variant	http://connecttech.com/product/com-express-type-7-gpu-embedded-system/	COM Express® Type 7 + GPU Embedded System

Part #	Description	Product Datasheet	Product Group
D7G003	COM Express Type 7 + GPU Embedded System. CPU: Xeon® D1577 1.3/2.1GHz 24MB Cache, with 48GB DDR4 2400MT/s ECC Memory, 45W (16C), GPU: NVIDIA Tesla P6 (90W, 2048 CUDA Cores). With Active Cooling Solution. 2x 10G, No Display Output Variant	http://connecttech.com/product/com-express-type-7-gpu-embedded-system/	COM Express® Type 7 + GPU Embedded System
D7G004	COM Express Type 7 + GPU Embedded System. CPU: Xeon® D1559 1.6/2.1GHz 18MB Cache, with 48GB DDR4 2400MT/s ECC Memory, 45W (12C) (eTEMP), GPU: NVIDIA Quadro P5000 (100W, 2048 CUDA Cores). With Active Cooling Solution. 2x 10G, 4x HDMI Variant	http://connecttech.com/product/com-express-type-7-gpu-embedded-system/	COM Express® Type 7 + GPU Embedded System
D7G005	COM Express Type 7 + GPU Embedded System. CPU: Xeon® D1559 1.6/2.1GHz 18MB Cache, with 48GB DDR4 2400MT/s ECC Memory, 45W (12C) (eTEMP), GPU: NVIDIA Quadro P3000 (75W, 1280 CUDA Cores). With Active Cooling Solution. 2x 10G, 4x HDMI Variant	http://connecttech.com/product/com-express-type-7-gpu-embedded-system/	COM Express® Type 7 + GPU Embedded System
D7G006	COM Express Type 7 + GPU Embedded System. CPU: Xeon® D1559 1.6/2.1GHz 18MB Cache, with 48GB DDR4 2400MT/s ECC Memory, 45W (12C) (eTEMP), GPU: NVIDIA Tesla P6 (90W, 2048 CUDA Cores). With Active Cooling Solution. 2x 10G, No Display Output Variant	http://connecttech.com/product/com-express-type-7-gpu-embedded-system/	COM Express® Type 7 + GPU Embedded System
D7G010	COM Express Type 7 + GPU Embedded System with Intel® Atom™ C3958 processor with 16 Cores, 2.0GHz core frequency, 16MB Cache, with 48GB DDR4 2400MT/s ECC Memory. Features 4x10 GbE, 31W TDP, commercial Temp. range. GPU: NVIDIA Quadro P5000 (100W, 2048 CUDA Cores). With Active Cooling Solution. 4x HDMI Variant	http://connecttech.com/product/com-express-type-7-gpu-embedded-system/	COM Express® Type 7 + GPU Embedded System
D7G011	COM Express Type 7 + GPU Embedded System with Intel® Atom™ C3958 processor with 16 Cores, 2.0GHz core frequency, 16MB Cache, with 48GB DDR4 2400MT/s ECC Memory. Features 4x10 GbE, 31W TDP, commercial Temp. range. GPU: NVIDIA Quadro P3000 (75W, 1280 CUDA Cores). With Active Cooling Solution. 4x HDMI Variant	http://connecttech.com/product/com-express-type-7-gpu-embedded-system/	COM Express® Type 7 + GPU Embedded System
D7G012	COM Express Type 7 + GPU Embedded System with Intel® Atom™ C3958 processor with 16 Cores, 2.0GHz core frequency, 16MB Cache, with 48GB DDR4 2400MT/s ECC Memory. Features 4x10 GbE, 31W TDP, commercial Temp. range. GPU: NVIDIA Tesla P6 (90W, 2048 CUDA Cores). With Active Cooling Solution. No Display Output Variant	http://connecttech.com/product/com-express-type-7-gpu-embedded-system/	COM Express® Type 7 + GPU Embedded System
DAG001	Xtreme I/O, 24 inputs and 24 outputs of Digital I/O. 0 to +40V input voltage, PCI-104, 3kV optical isolation. RoHS Compliant.	http://connecttech.com/product/xtreme-io-opto/	Xtreme I/O Opto

Part #	Description	Product Datasheet	Product Group
DAG003	Xtreme/I/O ADC-DAC, 32 single ended/16 differential channels of 16-bit 100Ksps analog inputs, 4 channels of 16-bit analog outputs and 16-bits of bidirectional digital IO. RoHS Compliant.	http://connecttech.com/product/xtreme-io-adc-dac/	Xtreme I/O ADC-DAC – PCI-104 Analog and Digital Data Acquisition Board
DAG004	Xtreme/I/O ADC-DAC, 32 single ended/16 differential channels of 16-bit 100Ksps analog inputs and 16-bits of bidirectional digital IO. RoHS Compliant.	http://connecttech.com/product/xtreme-io-adc-dac/	Xtreme I/O ADC-DAC – PCI-104 Analog and Digital Data Acquisition Board
DAG005	Xtreme/I/O ADC-DAC, 16 single ended/8 differential channels of 12-bit 100Ksps analog inputs and 16-bits of bidirectional digital IO. RoHS Compliant.	http://connecttech.com/product/xtreme-io-adc-dac/	Xtreme I/O ADC-DAC – PCI-104 Analog and Digital Data Acquisition Board
DAG103	Xtreme I/O Express ADC-DAC PCIe/104 , 32 single ended channels, split into groups of 8, 16 bit 500Ksps (per group) 62.5 Ksps (per channel) 4 analog output channels 16 bit, 40°C to 85°C RoHS Compliant.	http://connecttech.com/product/xtreme-io-express-adc-dac/	Xtreme I/O Express ADC-DAC – PCIe/104 Analog and Digital Peripheral Board
DBG002	FreeForm Daughter Board, mates to FBG014, reconfigurable FPGA modules, 2x RS-232/422/485 synchronous serial channels. RoHS Compliant.	http://connecttech.com/product/daughter-board/	FreeForm/104 Daughter Board
DCV-01672-N2-GP	Cooler Master DCV-01672-N2-GP		Heat Sink
DEV011	XDG025 24 port switch, xHG102 heatplate, custom breakout board, custom development "sled", universal AC/DC desktop power supply, fully integrated, RoHS Compliant.		
DEV016	Development Kit for FreeForm/104 - includes JTAG programming cable (JTAG3), universal power supply		
DEV016	Development Kit for FreeForm/104 - includes JTAG programming cable (JTAG3), universal power supply		
DEV017	Development Kit for FreeForm/104 - includes JTAG programming cable (JTAG3), universal power supply		
DXG101	COM Express + GPU Embedded System. CPU: Intel® Xeon® E3-1505L V5 (4x 2.0 / 2.8 GHz, 8MB cache, 25 W) - 32GB DDR4, GPU: NVIDIA GeForce GTX 1050 Ti (75W, 768 CUDA Cores). With Active Cooling Solution (with Integrated Support Frame). 0°C to +55°C	http://connecttech.com/product/com-express-gpu-embedded-system/	COM Express® + GPU Embedded System
DXG102	COM Express + GPU Embedded System. CPU: Intel® Xeon® E3-1515L V5 (4x 2,8GHz / 3.7GHz, 8MB cache, 35 W) - 32GB DDR4, GPU: NVIDIA GeForce GTX 1080 (Pascal, 2560 CUDA Cores, 150W). With Active Cooling Solution (with Integrated Support Frame). 0°C to +55°C	http://connecttech.com/product/com-express-gpu-embedded-system/	COM Express® + GPU Embedded System

Part #	Description	Product Datasheet	Product Group
DXG201	COM Express + GPU Embedded System. CPU: Intel® Xeon® E3-1505M V6 (4x 3.0 / 4.0 GHz, 8MB Cache, 45W) - 32GB DDR4, GPU: NVIDIA Quadro P5000 (100W, 2048 CUDA Cores). With Active Cooling Solution (with Integrated Support Frame). 0°C to +55°C	http://connecttech.com/product/com-express-gpu-embedded-system/	COM Express® + GPU Embedded System
DXG202	COM Express + GPU Embedded System. CPU: Intel® Xeon® E3-1505L V6 (4x 2.2 / 3.0 GHz, 8MB Cache, 25W) - 32GB DDR4, GPU: NVIDIA Quadro P3000 (75W, 1280 CUDA Cores). With Active Cooling Solution (with Integrated Support Frame). 0°C to +55°C	http://connecttech.com/product/com-express-gpu-embedded-system/	COM Express® + GPU Embedded System
DXG203	COM Express + GPU Embedded System. CPU: Intel® Xeon® E3-1515M V5 (4x 2,8GHz / 3.7GHz, 8MB cache, 35 W) - 32GB DDR4, GPU: NVIDIA Quadro P5000 (100W, 2048 CUDA Cores). With Active Cooling Solution (with Integrated Support Frame). 0°C to +55°C	http://connecttech.com/product/com-express-gpu-embedded-system/	COM Express® + GPU Embedded System
DXG204	COM Express + GPU Embedded System. CPU: Intel® Xeon® E3-1505L V5 (4x 2.0 / 2.8 GHz, 8MB cache, 25W) - 32GB DDR4, GPU: NVIDIA Quadro P3000 (75W, 1280 CUDA Cores). With Active Cooling Solution (with Integrated Support Frame). 0°C to +55°C	http://connecttech.com/product/com-express-gpu-embedded-system/	COM Express® + GPU Embedded System
ECG001-01	Echo/ISA 8, 8 ports RS-232, male DB-9 cables. RoHS Compliant.	http://connecttech.com/product/echoisa/	Echo/ISA
ECG001-02	Echo/ISA 8, 8 ports RS-232, external DB-9 I/O box. RoHS Compliant.	http://connecttech.com/product/echoisa/	Echo/ISA
ECG001-03	Echo/ISA 8, 8 ports RS-232 male DB-25 cables. RoHS Compliant.	http://connecttech.com/product/echoisa/	Echo/ISA
ECG002-01	Echo/ISA 8, 8 ports RS-422/485, male DB-9 cables. RoHS Compliant.	http://connecttech.com/product/echoisa/	Echo/ISA
ECG002-02	Echo/ISA 8, 8 ports RS-422/485, external DB-9 I/O box. RoHS Compliant.	http://connecttech.com/product/echoisa/	Echo/ISA
ECG002-03	Echo/ISA 8, 8 ports RS-422/485, male DB-25 cables. RoHS Compliant.	http://connecttech.com/product/echoisa/	Echo/ISA
ECG003-01	Echo/ISA 8, 4 ports RS-232, 4 ports RS-422/485, male DB-9 cables. RoHS Compliant.	http://connecttech.com/product/echoisa/	Echo/ISA
ECG003-02	Echo/ISA 8, 4 ports RS-232, 4 ports RS-422/485, external DB-9 I/O box. RoHS Compliant.	http://connecttech.com/product/echoisa/	Echo/ISA
ECG003-03	Echo/ISA 8, 4 ports RS-232, 4 ports RS-422/485, male DB-25 cables. RoHS Compliant.	http://connecttech.com/product/echoisa/	Echo/ISA
ECG006-01	Echo/ISA 8, 6 ports RS-232, 2 ports RS-422/485, male DB-9 cables. RoHS Compliant.	http://connecttech.com/product/echoisa/	Echo/ISA
ELG001	i.MX6Q 800MHz Cortex-A9 Quad Core 800Mhz, 1 GB DDR3, 2x RS-232, 2x microSD, Wifi IEEE802.11b/g/n, integrated Bluetooth, HDMI and LVDS display, audio output w/headphone amplification, +5VDC input, -40 to +85C, 72x100mm, RoHS Compliant.	http://connecttech.com/product/arctic-edge-imx6/	ArcticEdge/iMX6

Part #	Description	Product Datasheet	Product Group
ESG301	12 Port 10/100/1000 Mbps Managed Switch Box, -40°C to +85°C , RoHS Compliant.	http://connecttech.com/product/linq-gbe-rugged-managed-ethernet-switch-box/	LINQ/GbE Rugged Managed Ethernet Switch Box
ESG302	24 Port 10/100/1000 Mbps Managed Switch Box, -40°C to +85°C , RoHS Compliant.	http://connecttech.com/product/linq-gbe-rugged-managed-ethernet-switch-box/	LINQ/GbE Rugged Managed Ethernet Switch Box
ESG401	KUBE/Intel with Intel Atom E3845, 1.91 GHz Quad-Core, 2GB DDR3L 1333, 64GB Storage, 802.11 a/b/g/n 2.4GHz Wireless, 1xHDMI, 2x USB 2.0, 2x Gigabit Ethernet, +9V to +36V Power Input, designed for IP67/68, DO-160, and MIL-810G RoHS Compliant.	http://connecttech.com/product/the-kube/	The Kube
ESG501-02	ROSIE is a small form factor, rugged embedded system based on the NVIDIA® Jetson™ TX1. Housed in a compact enclosure with optional mounting brackets, ROSIE features NVIDIA Maxwell™ architecture with 256 CUDA cores delivering over 1 TeraFLOPs of performance with a 64-bit ARM A57 CPU. ROSIE's rugged system also provides USB, HDMI, 2x Gigabit Ethernet, WiFi, and Bluetooth capabilities. Custom face plates are easily accommodated using Connect Tech design services. ROSIE is designed to MIL-STD 810g and IP67/68. RoHS Compliant. Europe/Japan.	http://connecttech.com/product/rosie-embedded-system-with-nvidia-jetson-tx2-tx1/	Rosie Embedded System with NVIDIA® Jetson™ TX2/TX2i/TX1
ESG503-22	RUDI Enclosure with NVIDIA TX2 Jetson, 8 GB L128 bit DDR4 Memory, 32 GB eMMC 5.1 Flash Storage, 802.11 ac. Wifi with Bluetooth 4.0, 1x HDMI, 2x USB 3.0, 4x USB 2.0, 1x OTG USB 2.0 port, 2x Gigabit Ethernet, 1x CANBus, SIM Card slot (only for mPCIe), SD Card Slot (full size), +12V Barrel Power Input, Manual Power On/Off. RoHS Compliant. EU Countries/Ukraine/Turkey/Japan	http://connecttech.com/product/rudi-embedded-system-with-nvidia-jetson-tx2-tx1/	Rudi Embedded System with NVIDIA® Jetson™ TX2 or TX1
ESG506-02	RUDI Enclosure with NVIDIA TX2 Jetson, 8 GB L128 bit DDR4 Memory, 32 GB eMMC 5.1 Flash Storage, 802.11 ac Wifi with Bluetooth 4.0, 1x HDMI, 2x USB 3.0, 4x USB 2.0, 1x OTG USB 2.0 port, 2x Gigabit Ethernet, 1x CAN Bus, SIM Card slot (only for mPCIe), SD Card Slot (full size), Auto-Power On Mode, with 2 Pin Locking Terminal Power Connector. RoHS Compliant. Europe/Japan	http://connecttech.com/product/rudi-embedded-system-with-nvidia-jetson-tx2-tx1/	Rudi Embedded System with NVIDIA® Jetson™ TX2 or TX1
ESG506-22	RUDI Enclosure with NVIDIA TX2 Jetson, 8 GB L128 bit DDR4 Memory, 32 GB eMMC 5.1 Flash Storage, 802.11 ac Wifi with Bluetooth 4.0, 1x HDMI, 2x USB 3.0, 4x USB 2.0, 1x OTG USB 2.0 port, 2x Gigabit Ethernet, 1x CAN Bus, SIM Card slot (only for mPCIe), SD Card Slot (full size), Auto-Power On Mode, with 2 Pin Locking Terminal Power Connector. RoHS Compliant. Europe/Japan	http://connecttech.com/product/rudi-embedded-system-with-nvidia-jetson-tx2-tx1/	Rudi Embedded System with NVIDIA® Jetson™ TX2 or TX1

Part #	Description	Product Datasheet	Product Group
ESG701	V7G GPU System Xeon® D1577 1.3/2.1GHz 24MB, 45W NVIDIA Quadro P5000 (100W, 2048 CUDA Cores). 2x 10GbE, 4x HDMI Variant. 2U/Half Rack enclosure system, with rack mount brackets.	http://connecttech.com/product/v7g-system/	V7G GPU System
ESG702	V7G GPU System Xeon® D1577 1.3/2.1GHz 24MB Cache, with 48GB DDR4 2400MT/s ECC Memory, 45W (16C), GPU: NVIDIA Quadro P3000 (75W, 1280 CUDA Cores). 2x 10GbE, 4x HDMI Variant. 2U/Half Rack enclosure system, with rack mount brackets.	http://connecttech.com/product/v7g-system/	V7G GPU System
ESG703	V7G GPU System Xeon® D1577 1.3/2.1GHz 24MB Cache, with 48GB DDR4 2400MT/s ECC Memory, 45W (16C), GPU: NVIDIA Tesla P6 (90W, 2048 CUDA Cores). 2x 10GbE, no Display Output Variant. 2U/Half Rack enclosure system, with rack mount brackets.	http://connecttech.com/product/v7g-system/	V7G GPU System
ESG704	V7G GPU System Xeon® D1559 1.6/2.1GHz 18MB Cache, with 48GB DDR4 2400MT/s ECC Memory, 45W (12C) (eTEMP), GPU: NVIDIA Quadro P5000 (100W, 2048 CUDA Cores). 2x 10GbE, 4x HDMI Variant. 2U/Half Rack enclosure system, with rack mount brackets. 2U/Half Rack enclosure system, with rack mount brackets.	http://connecttech.com/product/v7g-system/	V7G GPU System
ESG705	V7G GPU System Xeon® D1559 1.6/2.1GHz 18MB Cache, with 48GB DDR4 2400MT/s ECC Memory, 45W (12C) (eTEMP), GPU: NVIDIA Quadro P3000 (75W, 1280 CUDA Cores). 2x 10GbE 4x HDMI Variant. 2U/Half Rack enclosure system, with rack mount brackets.	http://connecttech.com/product/v7g-system/	V7G GPU System
ESG706	V7G GPU System Xeon® D1559 1.6/2.1GHz 18MB Cache, with 48GB DDR4 2400MT/s ECC Memory, 45W (12C) (eTEMP), GPU: NVIDIA Tesla P6 (90W, 2048 CUDA Cores). 2x 10G, No Display Output Variant. 2U/Half Rack enclosure system, with rack mount brackets.	http://connecttech.com/product/v7g-system/	V7G GPU System
ESG710	V7G GPU System with Intel® Atom™ C3958 processor with 16 Cores, 2.0GHz core frequency, 16MB Cache, with 48GB DDR4 2400MT/s ECC Memory. Features 4x 10GbE, 31W TDP, commercial Temp. range. GPU: NVIDIA Quadro P5000 (100W, 2048 CUDA Cores). 4x HDMI Variant. 2U/Half Rack enclosure system, with rack mount brackets.	http://connecttech.com/product/v7g-system/	V7G GPU System

Part #	Description	Product Datasheet	Product Group
ESG711	V7G GPU System with Intel® Atom™ C3958 processor with 16 Cores, 2.0GHz core frequency, 16MB Cache, with 48GB DDR4 2400MT/s ECC Memory. Features 4x10 GbE, 31W TDP, commercial Temp. range. GPU: NVIDIA Quadro P3000 (75W, 1280 CUDA Cores). 4x HDMI Variant. 2U/Half Rack enclosure system, with rack mount brackets.	http://connecttech.com/product/v7g-system/	V7G GPU System
ESG712	V7G GPU System with Intel® Atom™ C3958 processor with 16 Cores, 2.0GHz core frequency, 16MB Cache, with 48GB DDR4 2400MT/s ECC Memory. Features 4x10 GbE, 31W TDP, commercial Temp. range. GPU: NVIDIA Tesla P6 (90W, 2048 CUDA Cores). No Display Output Variant. 2U/Half Rack enclosure system, with rack mount brackets.	http://connecttech.com/product/v7g-system/	V7G GPU System
FBG006	FreeForm/104, Spartan-3E FPGA, 500,000 gates, on-board flash, standard core includes 96 digital I/O and 6 counter/timers, industrial Temp. range, right angle connectors. RoHS Compliant.	http://connecttech.com/product/freeform104/	FreeForm/104
FBG014	FreeForm/104, Spartan-3E FPGA, 500,000 gates, on-board flash, standard core includes 96 digital I/O and 6 counter/timers, industrial Temp. range, vertical connectors. RoHS Compliant.		FreeForm/PCI-104
FCG001	FreeForm/PCI-104, Virtex-5 (LX30T) FPGA, 3 million logic gates, DDR2-400 and flash memory, 64 single ended or 32 LVDS I/O, 2x Ethernet ports and 2x RS-485 ports. RoHS Compliant.	http://connecttech.com/product/freeformpci-104/	FreeForm/PCI-104
FCG002	FreeForm/PCI-104, Virtex-5 (LX30T) FPGA, 64 single ended 3.3V I/O, 2x 10/100 Ethernet ports, 2x RS-485, industrial Temp. range. RoHS Compliant.	http://connecttech.com/product/freeformpci-104/	FreeForm/PCI-104
FCG003	FreeForm/PCI-104, Virtex-5 (FX30T) FPGA, 3 million gates, 64 single ended or 32 LVDS I/O, 2x 10/100 Ethernet, 2x RS-485, PowerPC. industrial Temp. range. RoHS Compliant.	http://connecttech.com/product/freeformpci-104/	FreeForm/PCI-104
FCG004	FreeForm/PCI-104, Virtex-5 (FX30T) FPGA, 3 million gates, 64 single ended 3.3V I/O, 2x 10/100 Ethernet, 2x RS-485, includes PowerPC, industrial Temp. range. RoHS Compliant.	http://connecttech.com/product/freeformpci-104/	FreeForm/PCI-104
FCG005	FreeForm/PCI-104, Virtex-5 (LX50T) FPGA, 5 million gates, 64 single ended or 32 LVDS I/O, 2x 10/100 Ethernet, 2x RS-485, industrial Temp. range. RoHS Compliant.	http://connecttech.com/product/freeformpci-104/	FreeForm/PCI-104

Part #	Description	Product Datasheet	Product Group
FCG006	FreeForm/PCI-104, Virtex-5 (LX50T) FPGA, 5 million gates, 64 single ended 3.3V I/O, 2x 10/100 Ethernet, 2x RS-485, industrial Temp. range. RoHS Compliant.	http://connecttech.com/product/freeformpci-104/	FreeForm/PCI-104
FDG001	FreeForm/Express S6, Spartan-6 LX45T FPGA, 128MB DDR3, 2x10/100/1000 Ethernet, 1xRS232 serial, LPC FMC connector. RoHS Compliant.	http://connecttech.com/product/freeformexpress-s6/	FreeForm/Express S6
FDG002	FreeForm/Express S6, Spartan-6 LX100T FPGA and includes 128MB DDR3, 2x10/100/1000 Ethernet, 1xRS232 serial, and LPC FMC connector. RoHS Compliant.	http://connecttech.com/product/freeformexpress-s6/	FreeForm/Express S6
GPS-06T	GPS Active antenna with RF protection circuit, low profile +3VDC to +6VDC input +28dB gain, sma connector.	http://connecttech.com/product/mini-pcie-gps/	Mini PCIe GPS
HA-DX-16	OptiLogix 16-Channel Digital Extension / BRI ISDN-2 (8 port)	https://optilogix.com/uploads/HyperArray.pdf	TDM to LAN Converter for Telephony Call Recording (Hot- swap Module)
HA-DX-16- ALC	OptiLogix 16-Channel Alcatel Digital Extension	https://optilogix.com/uploads/HyperArray.pdf	TDM to LAN Converter for Telephony Call Recording (Hot- swap Module)
HA-HS-16	OptiLogix 16-Channel Analog CO or Extension (FSK CLI support)	https://optilogix.com/uploads/HyperArray.pdf	TDM to LAN Converter for Telephony Call Recording (Hot- swap Module)
HA-PRI-60	OptiLogix 60-Channel (Dual ISDN-30/QSIG/DASS-2/DPNSS)	https://optilogix.com/uploads/HyperArray.pdf	TDM to LAN Converter for Telephony Call Recording (Hot- swap Module)
HA-RACK-10	10 module slots HyperArray 19" rack 3U (including power supply)	https://optilogix.com/uploads/HyperArray.pdf	OptiLogix HyperArray Rack
HA-RACK-10-PSU2	10 module slots HyperArray 19" rack 3U (including dual redundant power supply)	https://optilogix.com/uploads/HyperArray.pdf	OptiLogix HyperArray Rack
HA-RACK-20	20 module slots HyperArray 19" rack 3U (including power supply)	https://optilogix.com/uploads/HyperArray.pdf	OptiLogix HyperArray Rack
HA-RACK-20-PSU2	20 module slots HyperArray 19" rack 3U (including dual redundant power supply)		OptiLogix HyperArray Rack
HA-T1-46	OptiLogix 46-Channel (Dual T1 PRI-ISDN)	https://optilogix.com/uploads/HyperArray.pdf	TDM to LAN Converter for Telephony Call Recording (Hot- swap Module)
HP-DX-04	OptiLogix 4-Channel Digital Extension / BRI ISDN-2 (2 port)	https://optilogix.com/uploads/HyperPCI.pdf	PCI Telephony Call Recording Board
HP-DX-08	OptiLogix 8-Channel Digital Extension / BRI ISDN-2 (4 port)	https://optilogix.com/uploads/HyperPCI.pdf	PCI Telephony Call Recording Board
HP-DX-16	OptiLogix 16-Channel Digital Extension / BRI ISDN-2 (8 port)	https://optilogix.com/uploads/HyperPCI.pdf	PCI Telephony Call Recording Board
HP-DX-16-ALC	OptiLogix 16-Channel Alcatel Digital Extension	https://optilogix.com/uploads/HyperPCI.pdf	PCI Telephony Call Recording Board
HP-HS-04	OptiLogix 4-Channel Analog CO or Extension (FSK CLI support)	https://optilogix.com/uploads/HyperPCI.pdf	PCI Telephony Call Recording Board
HP-HS-08	OptiLogix 8-Channel Analog CO or Extension (FSK CLI support)	https://optilogix.com/uploads/HyperPCI.pdf	PCI Telephony Call Recording Board

Part #	Description	Product Datasheet	Product Group
HP-HS-16	OptiLogix 16-Channel Analog CO or Extension (FSK CLI support)	https://optilogix.com/uploads/HyperPCI.pdf	PCI Telephony Call Recording Board
HP-IS-04	OptiLogix 4-Channel BRI ISDN-2 (2 port)	https://optilogix.com/uploads/HyperPCI.pdf	PCI Telephony Call Recording Board
HP-IS-08	OptiLogix 8-Channel BRI ISDN-2 (4 port)	https://optilogix.com/uploads/HyperPCI.pdf	PCI Telephony Call Recording Board
HP-IS-16	OptiLogix 16-Channel BRI ISDN-2 (8 port)	https://optilogix.com/uploads/HyperPCI.pdf	PCI Telephony Call Recording Board
HP-PRI-08	OptiLogix 8-Channel (Fractional ISDN-30)	https://optilogix.com/uploads/HyperPCI.pdf	PCI Telephony Call Recording Board
HP-PRI-12	OptiLogix 12-Channel (Fractional ISDN-30)	https://optilogix.com/uploads/HyperPCI.pdf	PCI Telephony Call Recording Board
HP-PRI-16	OptiLogix 16-Channel (Fractional ISDN-30)	https://optilogix.com/uploads/HyperPCI.pdf	PCI Telephony Call Recording Board
HP-PRI-20	OptiLogix 20-Channel (Fractional ISDN-30)	https://optilogix.com/uploads/HyperPCI.pdf	PCI Telephony Call Recording Board
HP-PRI-30	OptiLogix 30-Channel (Euro ISDN-30/QSIG/DASS-2/DPNSS)	https://optilogix.com/uploads/HyperPCI.pdf	PCI Telephony Call Recording Board
HP-PRI-60	OptiLogix 60-Channel (Dual ISDN-30/QSIG/DASS-2/DPNSS)	https://optilogix.com/uploads/HyperPCI.pdf	PCI Telephony Call Recording Board
HP-T1-23	OptiLogix 23-Channel (T1 PRI-ISDN)	https://optilogix.com/uploads/HyperPCI.pdf	PCI Telephony Call Recording Board
HP-T1-46	OptiLogix 46-Channel (Dual T1 PRI-ISDN)	https://optilogix.com/uploads/HyperPCI.pdf	PCI Telephony Call Recording Board
HU-DX-04	OptiLogix 4-Channel Digital Extension / BRI ISDN-2 (2 port)	https://optilogix.com/uploads/HyperUSB.pdf	USB Telephony Call Recording Device
HU-DX-08	OptiLogix 8-Channel Digital Extension / BRI ISDN-2 (4 port)	https://optilogix.com/uploads/HyperUSB.pdf	USB Telephony Call Recording Device
HU-HS-04	OptiLogix 4-Channel Analog CO or Extension (FSK CLI support)	https://optilogix.com/uploads/HyperUSB.pdf	USB Telephony Call Recording Device
HU-HS-08	OptiLogix 8-Channel Analog CO or Extension (FSK CLI support)	https://optilogix.com/uploads/HyperUSB.pdf	USB Telephony Call Recording Device
HU-IS-04	OptiLogix 4-Channel BRI ISDN-2 (2 port)	https://optilogix.com/uploads/HyperUSB.pdf	USB Telephony Call Recording Device
HU-IS-08	OptiLogix 8-Channel BRI ISDN-2 (4 port)	https://optilogix.com/uploads/HyperUSB.pdf	USB Telephony Call Recording Device
HU-PRI-08	OptiLogix 8-Channel (Fractional ISDN-30)	https://optilogix.com/uploads/HyperUSB.pdf	USB Telephony Call Recording Device
HU-PRI-12	OptiLogix 12-Channel (Fractional ISDN-30)	https://optilogix.com/uploads/HyperUSB.pdf	USB Telephony Call Recording Device
HU-PRI-16	OptiLogix 16-Channel (Fractional ISDN-30)	https://optilogix.com/uploads/HyperUSB.pdf	USB Telephony Call Recording Device
HU-PRI-20	OptiLogix 20-Channel (Fractional ISDN-30)	https://optilogix.com/uploads/HyperUSB.pdf	USB Telephony Call Recording Device
HU-PRI-30	OptiLogix 30-Channel (Euro ISDN-30/QSIG/DASS-2/DPNSS)	https://optilogix.com/uploads/HyperUSB.pdf	USB Telephony Call Recording Device
HU-T1-23	OptiLogix 23-Channel (T1 PRI-ISDN)	https://optilogix.com/uploads/HyperUSB.pdf	USB Telephony Call Recording Device
HX-DX-08	OptiLogix 8-Channel Digital Extension / BRI ISDN-2 (4 port)	https://optilogix.com/uploads/HyperXpress.pdf	PCI Express Telephony Call Recording Board
HX-DX-16	OptiLogix 16-Channel Digital Extension / BRI ISDN-2 (8 port)	https://optilogix.com/uploads/HyperXpress.pdf	PCI Express Telephony Call Recording Board
HX-DX-16-ALC	OptiLogix 16-Channel Alcatel Digital Extension	https://optilogix.com/uploads/HyperXpress.pdf	PCI Express Telephony Call Recording Board
HX-HS-08	OptiLogix 8-Channel Analog CO or Extension (FSK CLI support)	https://optilogix.com/uploads/HyperXpress.pdf	PCI Express Telephony Call Recording Board
HX-HS-16	OptiLogix 16-Channel Analog CO or Extension (FSK CLI support)	https://optilogix.com/uploads/HyperXpress.pdf	PCI Express Telephony Call Recording Board

Part #	Description	Product Datasheet	Product Group
HX-IS-08	OptiLogix 8-Channel BRI ISDN-2 (4 port)	https://optilogix.com/uploads/HyperXpress.pdf	PCI Express Telephony Call Recording Board
HX-IS-16	OptiLogix 16-Channel BRI ISDN-2 (8 port)	https://optilogix.com/uploads/HyperXpress.pdf	PCI Express Telephony Call Recording Board
HX-PRI-16	OptiLogix 16-Channel (Fractional ISDN-30)	https://optilogix.com/uploads/HyperXpress.pdf	PCI Express Telephony Call Recording Board
HX-PRI-20	OptiLogix 20-Channel (Fractional ISDN-30)	https://optilogix.com/uploads/HyperXpress.pdf	PCI Express Telephony Call Recording Board
HX-PRI-30	OptiLogix 30-Channel (ISDN-30/QSIG/DASS-2/DPNSS)	https://optilogix.com/uploads/HyperXpress.pdf	PCI Express Telephony Call Recording Board
HX-PRI-30-LP	OptiLogix 30-Channel Low Profile Version of the HX-PRI-30	https://optilogix.com/uploads/HyperXpress.pdf	PCI Express Telephony Call Recording Board
HX-PRI-60	OptiLogix 60-Channel (Dual ISDN-30/QSIG/DASS-2/DPNSS)	https://optilogix.com/uploads/HyperXpress.pdf	PCI Express Telephony Call Recording Board
HX-PRI-60-LP	OptiLogix 60-Channel Low Profile Version of the HX-PRI-60	https://optilogix.com/uploads/HyperXpress.pdf	PCI Express Telephony Call Recording Board
HX-T1-23	OptiLogix 23-Channel (T1 PRI-ISDN)	https://optilogix.com/uploads/HyperXpress.pdf	PCI Express Telephony Call Recording Board
HX-T1-46	OptiLogix 46-Channel (Dual T1 PRI-ISDN)	https://optilogix.com/uploads/HyperXpress.pdf	PCI Express Telephony Call Recording Board
I4802064XX	Intellicon-2, 2 ports RS-422/485, 64K RAM	http://connecttech.com/product/intelliconisa/	Intellicon/ISA
I4804064XX	Intellicon-4, 4 ports RS-422/485, 64K RAM, DB-9 cables	http://connecttech.com/product/intelliconisa/	Intellicon/ISA
IA808064XX	Intellicon-6+2, 6 ports RS-232, 2 ports RS-422/485, 64K RAM, DB-25 cables	http://connecttech.com/product/intelliconisa/	Intellicon/ISA
IAT02064XX	Intellicon-2, 2 ports RS-232, 64K RAM	http://connecttech.com/product/intelliconisa/	Intellicon/ISA
IAT04064MT	Intellicon-4, 4 ports RS-232, 64K RAM, DB-25 cables	http://connecttech.com/product/intelliconisa/	Intellicon/ISA
IAT08064MT	Intellicon-8, 8 ports RS-232, 64K RAM, DB-25 cables	http://connecttech.com/product/intelliconisa/	Intellicon/ISA
IP-DX-08	OptiLogix 8-Channel Digital Extension / BRI ISDN-2 (4 port)	https://optilogix.com/uploads/HyperPacket.pdf	TDM to LAN Converter for Telephony Call Recording

Part #	Description	Product Datasheet	Product Group
IP-DX-16	OptiLogix 16-Channel Digital Extension / BRI ISDN-2 (8 port)	https://optilogix.com/uploads/HyperPacket.pdf	TDM to LAN Converter for Telephony Call Recording
IP-DX-16-ALC	OptiLogix 16-Channel Alcatel Digital Extension	https://optilogix.com/uploads/HyperPacket.pdf	TDM to LAN Converter for Telephony Call Recording
IP-HS-08	OptiLogix 8-Channel Analog CO or Extension (FSK CLI support)	https://optilogix.com/uploads/HyperPacket.pdf	TDM to LAN Converter for Telephony Call Recording
IP-HS-16	OptiLogix 16-Channel Analog CO or Extension (FSK CLI support)	https://optilogix.com/uploads/HyperPacket.pdf	TDM to LAN Converter for Telephony Call Recording
IP-PRI-30	OptiLogix 30-Channel (Euro ISDN-30/QSIG/DASS-2/DPNSS)	https://optilogix.com/uploads/HyperPacket.pdf	TDM to LAN Converter for Telephony Call Recording
IP-T1-23	OptiLogix 23-Channel (T1 PRI-ISDN)	https://optilogix.com/uploads/HyperPacket.pdf	TDM to LAN Converter for Telephony Call Recording
IP-T1-46	OptiLogix 46-Channel (Dual T1 PRI-ISDN)	https://optilogix.com/uploads/HyperPacket.pdf	TDM to LAN Converter for Telephony Call Recording
M2G201	U-Blox NEO-7N GNSS receiver. M.2 Socket 2, Type-2242-S3-B. RoHS Compliant.	http://connecttech.com/product/m-2-gps/	M.2 GPS
M2G202	M.2 GPS Receiver (Battery included) populated with NEO -7N module	http://connecttech.com/product/m-2-gps/	M.2 GPS
M2G203	M.2 GPS Receiver (Battery not included) populated with NEO - M8N module	http://connecttech.com/product/m-2-gps/	M.2 GPS
M2G204	M.2 GPS Receiver (Battery included) populated with NEO - M8N module	http://connecttech.com/product/m-2-gps/	M.2 GPS
M2G205	M.2 GPS Receiver (Battery not included) populated with NEO - M8L module	http://connecttech.com/product/m-2-gps/	M.2 GPS
M2G206	M.2 GPS Receiver (Battery included) populated with NEO -M8L module (10pc MOQ)	http://connecttech.com/product/m-2-gps/	M.2 GPS
MPG001	Mini PCI-Express Serial card, includes 2x RS-232/422/485 serial ports. Vertical latching connector. Connected via Mini PCIe USB. RoHS Compliant.	http://connecttech.com/product/mini-pci-express-serial/	Mini PCI Express Serial
MPG002	Mini PCI-Express Serial card, includes 2x RS-232/422/485 serial ports. Vertical nonlatching connector. Connected via Mini PCIe USB. RoHS Compliant.	http://connecttech.com/product/mini-pci-express-serial/	Mini PCI Express Serial
MPG003	Mini PCI-Express Serial card, includes 2x RS-232/422/485 serial ports. Vertical latching connector. Connected via Mini PCIe USB. RoHS Compliant.	http://connecttech.com/product/mini-pci-express-serial/	Mini PCI Express Serial

Part #	Description	Product Datasheet	Product Group
MPG004	Mini PCI-Express Serial card, includes 2x RS-232/422/485 serial ports. Vertical nonlatching connector. Connected via Mini PCIe USB. RoHS Compliant.	http://connecttech.com/product/mini-pci-express-serial/	Mini PCI Express Serial
MPG101	Mini PCI-Express GbE card, includes 1x Gigabit Ethernet port. Connected via PCI Express. Right angle connector. RoHS Compliant.	http://connecttech.com/product/mini-pcie-gbe/	Mini PCIe GbE
MPG102	Mini PCI-Express GbE card, includes 1x Gigabit Ethernet port. Connected via PCI Express. Vertical connector. RoHS Compliant.	http://connecttech.com/product/mini-pcie-gbe/	Mini PCIe GbE
MPG104	Mini PCI-Express GbE card, includes 2x Gigabit Ethernet port. Connected via PCI Express. 2nd port connected via daughter card. RoHS Compliant.	http://connecttech.com/product/mini-pcie-gps/	Mini PCIe GPS
MPG201	NEO-7 GPS module (no battery). RoHS Compliant.	http://connecttech.com/product/mini-pcie-gps/	Mini PCIe GPS
MPG202	NEO-7 GPS module with battery. RoHS Compliant.	http://connecttech.com/product/mini-pcie-gps/	Mini PCIe GPS
MPG203	NEO-M8N GPS module (no battery). RoHS Compliant.	http://connecttech.com/product/mini-pcie-gps/	Mini PCIe GPS
MPG204	NEO-M8N GPS module with battery. RoHS Compliant.	http://connecttech.com/product/mini-pcie-gps/	Mini PCIe GPS
MPG205	Neo-M8L GPS module (no battery). Dead reckoning. RoHS Compliant.	http://connecttech.com/product/mini-pcie-gps/	Mini PCIe GPS
MPG206	Neo-M8L GPS module with battery. Dead reckoning. RoHS Compliant.	http://connecttech.com/product/mini-pcie-gps/	Mini PCIe GPS
MPG207	Mini PCIe GPS with NEO-M8U. No Battery Included. RoHS Compliant.	http://connecttech.com/product/mini-pcie-gps/	Mini PCIe GPS
MPG208	Mini PCIe GPS with NEO-M8U. Battery included. RoHS Compliant.	http://connecttech.com/product/mini-pcie-gps/	Mini PCIe GPS
MPG401	Mini PCIe 16 ADC input channels 16-bit resolution, 500kSPS, -40°C to +85°C – RoHS Compliant.	http://connecttech.com/product/mini-pcie-adc/	Mini PCIe ADC
MSG009	Optional DIN rail mounting kit (for DB-9 models only)		
MSG029	Rack mount kit for BNG006/BNG008/BMG006		
MSG030	Plastic DIN rail kit for Blue Heat/Net 2		

Part #	Description	Product Datasheet	Product Group
MSG054	ESG302 Mounting Kit RoHS Compliant.		
MSG055	ESG301 Mounting Kit RoHS Compliant.		
MSG056	Mounting brackets for ESG401/ESG501		
MSG062	AC/DC Power Supply for Astro Products. 90-264VAC Input, 12VDC Output, 2A Output, 24W. RoHS Compliant.		
MSG063	AC/DC Power Supply for Elroy Products. 90-264VAC Input, 12VDC Output, 2A Output, 24W. RoHS Compliant.		
MSG064	AC/DC Power Supply for Orbitty Products. 90-264VAC Input, 12VDC Output, 2A Output, 24W. RoHS Compliant.		
MSG068	5v desktop power adapter to 2-pin 3.5mm terminal plug		
PSG001	PC/104-Plus -xtreme/PSU +6V to +36V DC input, +5V @ 10A, +12V @ 5A , and +5V- Standby @ 1.2A output, RoHS Compliant.	http://connecttech.com/product/xtremepsu-power-supply/	Xtreme/PSU Power Supply
PSG002	PC/104 -xtreme/PSU +6V to +36V DC input, +5V @ 10A, +12V @ 5A , and +5V- Standby @ 1.2A output, RoHS Compliant.	http://connecttech.com/product/xtremepsu-power-supply/	Xtreme/PSU Power Supply
PSG003	PCI-104 -xtreme/PSU +6V to +36V DC input, +5V @ 10A, +12V @ 5A , and +5V- Standby @ 1.2A output, RoHS Compliant.	http://connecttech.com/product/xtremepsu-power-supply/	Xtreme/PSU Power Supply
PSG004	PCIe/104 -xtreme/PSU +6V to +36V DC input, +5V @ 10A, +12V @ 5A , and +5V- Standby @ 1.2A output, RoHS Compliant.	http://connecttech.com/product/xtremepsu-power-supply/	Xtreme/PSU Power Supply
PSG005	PCI/104-Express -xtreme/PSU +6V to +36V DC input, +5V @ 10A, +12V @ 5A , and +5V- Standby @ 1.2A output, RoHS Compliant.	http://connecttech.com/product/xtremepsu-power-supply/	Xtreme/PSU Power Supply
PSG006	No bus installed -xtreme/PSU +6V to +36V DC input, +5V @ 10A, +12V @ 5A , and +5V- Standby @ 1.2A output, RoHS Compliant.	http://connecttech.com/product/xtremepsu-power-supply/	Xtreme/PSU Power Supply
PSG007	PC/104-Plus -xtreme/PSU , +6V to +36V DC input, +5V @ 10A, +12V @ 5A, +3.3V @ 10A, -12V @ 1.0A, and +5V- Standby @ 1.2A output, RoHS Compliant.	http://connecttech.com/product/xtremepsu-xp-power-supply/	Xtreme/PSU-XP Power Supply
PSG008	PC/104 -xtreme/PSU , +6V to +36V DC input, +5V @ 10A, +12V @ 5A, +3.3V @ 10A, -12V @ 1.0A, and +5V- Standby @ 1.2A output, RoHS Compliant.	http://connecttech.com/product/xtremepsu-xp-power-supply/	Xtreme/PSU-XP Power Supply
PSG009	PCI-104 -xtreme/PSU , +6V to +36V DC input, +5V @ 10A, +12V @ 5A, +3.3V @ 10A, -12V @ 1.0A, and +5V- Standby @ 1.2A output, RoHS Compliant.	http://connecttech.com/product/xtremepsu-xp-power-supply/	Xtreme/PSU-XP Power Supply
PSG010	PCIe/104 -xtreme/PSU , +6V to +36V DC input, +5V @ 10A, +12V @ 5A, +3.3V @ 10A, -12V @ 1.0A, and +5V- Standby @ 1.2A output, RoHS Compliant.	http://connecttech.com/product/xtremepsu-xp-power-supply/	Xtreme/PSU-XP Power Supply

Part #	Description	Product Datasheet	Product Group
PSG011	PCI/104-Express -xtreme/PSU , +6V to +36V DC input, +5V @ 10A, +12V @ 5A, +3.3V @ 10A, -12V @ 1.0A, and +5V-Standby @ 1.2A output, RoHS Compliant.	http://connecttech.com/product/xtremepsu-xp-power-supply/	Xtreme/PSU-XP Power Supply
PSG012	No bus installed -xtreme/PSU , +6V to +36V DC input, +5V @ 10A, +12V @ 5A, +3.3V @ 10A, -12V @ 1.0A, and +5V-Standby @ 1.2A output, RoHS Compliant.	http://connecttech.com/product/xtremepsu-xp-power-supply/	Xtreme/PSU-XP Power Supply
PSG013	Xtreme/PSU-UC Power Supply with onboard Ultra Capacitors. High efficiency, high powered PC/104 form factor power supply, wide input voltage range that accepts +8 to+36V DC, and provides 115W total output power with +5V, +12V and +5V Standby output voltages.	http://connecttech.com/product/xtremepsu-uc-power-supply/	Xtreme/PSU-UC Power Supply
PXG101	PC/104-Plus -xtreme/PSU Isolated SP Series, +9V to +36V DC input, 1.5kV isolation, +5V @ 15A, +12V @ 6A and +3.3V @ 5A output, RoHS Compliant.	http://connecttech.com/product/xtremepsu-isolated-power-supply/	Xtreme/PSU Isolated Power Supply
PXG102	PC/104 -xtreme/PSU Isolated SP Series, +9V to +36V DC input, 1.5kV isolation, +5V @ 15A, +12V @ 6A and +3.3V @ 5A output, RoHS Compliant.	http://connecttech.com/product/xtremepsu-isolated-power-supply/	Xtreme/PSU Isolated Power Supply
PXG103	PCI-104 -xtreme/PSU Isolated SP Series, +9V to +36V DC input, 1.5kV isolation, +5V @ 15A, +12V @ 6A and +3.3V @ 5A output, RoHS Compliant.	http://connecttech.com/product/xtremepsu-isolated-power-supply/	Xtreme/PSU Isolated Power Supply
PXG104	PCIe/104 -xtreme/PSU Isolated SP Series, +9V to +36V DC input, 1.5kV isolation, +5V @ 15A, +12V @ 6A and +3.3V @ 5A output, RoHS Compliant.	http://connecttech.com/product/xtremepsu-isolated-power-supply/	Xtreme/PSU Isolated Power Supply
PXG105	PCI/104-Express -xtreme/PSU Isolated SP Series, +9V to +36V DC input, 1.5kV isolation, +5V @ 15A, +12V @ 6A and +3.3V @ 5A output, RoHS Compliant.	http://connecttech.com/product/xtremepsu-isolated-power-supply/	Xtreme/PSU Isolated Power Supply
PXG106	No bus installed -xtreme/PSU Isolated SP Series, +9V to +36V DC input, 1.5kV isolation, +5V @ 15A, +12V @ 6A and +3.3V @ 5A output, RoHS Compliant.	http://connecttech.com/product/xtremepsu-isolated-power-supply/	Xtreme/PSU Isolated Power Supply
PXG107	PC/104-Plus -xtreme/PSU Isolated SP Series, +9V to +36V DC input, 1.5kV isolation, +5V @ 15A and +12V @ 6A output, RoHS Compliant.	http://connecttech.com/product/xtremepsu-isolated-power-supply/	Xtreme/PSU Isolated Power Supply
PXG108	PC/104 -xtreme/PSU Isolated SP Series, +9V to +36V DC input, 1.5kV isolation, +5V @ 15A and +12V @ 6A output, RoHS Compliant.	http://connecttech.com/product/xtremepsu-isolated-power-supply/	Xtreme/PSU Isolated Power Supply
PXG109	PCI-104 -xtreme/PSU Isolated SP Series, +9V to +36V DC input, 1.5kV isolation, +5V @ 15A and +12V @ 6A output, RoHS Compliant.	http://connecttech.com/product/xtremepsu-isolated-power-supply/	Xtreme/PSU Isolated Power Supply

Part #	Description	Product Datasheet	Product Group
PXG110	PCIe/104 -xtreme/PSU Isolated SP Series, +9V to +36V DC input, 1.5kV isolation, +5V @ 15A and +12V @ 6A output, RoHS Compliant.	http://connecttech.com/product/xtremepsu-isolated-power-supply/	Xtreme/PSU Isolated Power Supply
PXG111	PCI/104-Express -xtreme/PSU Isolated SP Series, +9V to +36V DC input, 1.5kV isolation, +5V @ 15A and +12V @ 6A output, RoHS Compliant.	http://connecttech.com/product/xtremepsu-isolated-power-supply/	Xtreme/PSU Isolated Power Supply
PXG112	No bus installed -xtreme/PSU Isolated SP Series, +9V to +36V DC input, 1.5kV isolation, +5V @ 15A and +12V @ 6A output, RoHS Compliant.	http://connecttech.com/product/xtremepsu-isolated-power-supply/	Xtreme/PSU Isolated Power Supply
PXG201	PC/104-Plus -xtreme/PSU Isolated LP Series, +9V to +36V DC input, 1.5kV isolation, +5V @ 15A and +3.3V @ 20A output, RoHS Compliant.	http://connecttech.com/product/xtremepsu-isolated-power-supply/	Xtreme/PSU Isolated Power Supply
PXG202	PC/104 -xtreme/PSU Isolated LP Series, +9V to +36V DC input, 1.5kV isolation, +5V @ 15A and +3.3V @ 20A output, RoHS Compliant.	http://connecttech.com/product/xtremepsu-isolated-power-supply/	Xtreme/PSU Isolated Power Supply
PXG203	PCI-104 -xtreme/PSU Isolated LP Series, +9V to +36V DC input, 1.5kV isolation, +5V @ 15A and +3.3V @ 20A output, RoHS Compliant.	http://connecttech.com/product/xtremepsu-isolated-power-supply/	Xtreme/PSU Isolated Power Supply
PXG204	PCIe/104 -xtreme/PSU Isolated LP Series, +9V to +36V DC input, 1.5kV isolation, +5V @ 15A and +3.3V @ 20A output, RoHS Compliant.	http://connecttech.com/product/xtremepsu-isolated-power-supply/	Xtreme/PSU Isolated Power Supply
PXG205	PCI/104-Express -xtreme/PSU Isolated LP Series, +9V to +36V DC input, 1.5kV isolation, +5V @ 15A and +3.3V @ 20A output, RoHS Compliant.	http://connecttech.com/product/xtremepsu-isolated-power-supply/	Xtreme/PSU Isolated Power Supply
PXG206	No bus installed -xtreme/PSU Isolated LP Series, +9V to +36V DC input, 1.5kV isolation, +5V @ 15A and +3.3V @ 20A output, RoHS Compliant.	http://connecttech.com/product/xtremepsu-isolated-power-supply/	Xtreme/PSU Isolated Power Supply
PXG301	PC/104-Plus -xtreme/PSU Isolated HP Series, +18V to +36V DC input, 2.25kV isolation, +5V @ 15A, +12v @ 10A and +3.3V @ 5A output, RoHS Compliant.	http://connecttech.com/product/xtremepsu-isolated-power-supply/	Xtreme/PSU Isolated Power Supply
PXG302	PC/104 -xtreme/PSU Isolated HP Series, +18V to +36V DC input, 2.25kV isolation, +5V @ 15A, +12v @ 10A and +3.3V @ 5A output, RoHS Compliant.	http://connecttech.com/product/xtremepsu-isolated-power-supply/	Xtreme/PSU Isolated Power Supply
PXG303	PCI-104 -xtreme/PSU Isolated HP Series, +18V to +36V DC input, 2.25kV isolation, +5V @ 15A, +12v @ 10A and +3.3V @ 5A output, RoHS Compliant.	http://connecttech.com/product/xtremepsu-isolated-power-supply/	Xtreme/PSU Isolated Power Supply
PXG304	PCIe/104 -xtreme/PSU Isolated HP Series, +18V to +36V DC input, 2.25kV isolation, +5V @ 15A, +12v @ 10A and +3.3V @ 5A output, RoHS Compliant.	http://connecttech.com/product/xtremepsu-isolated-power-supply/	Xtreme/PSU Isolated Power Supply
PXG305	PCI/104-Express -xtreme/PSU Isolated HP Series, +18V to +36V DC input, 2.25kV isolation, +5V @ 15A, +12v @ 10A and +3.3V @ 5A output, RoHS Compliant.	http://connecttech.com/product/xtremepsu-isolated-power-supply/	Xtreme/PSU Isolated Power Supply

Part #	Description	Product Datasheet	Product Group
PXG306	No bus installed -xtreme/PSU Isolated HP Series, +18V to +36V DC input, 2.25kV isolation, +5V @ 15A, +12V @ 10A and +3.3V @ 5A output, RoHS Compliant.	http://connecttech.com/product/xtremepsu-isolated-power-supply/	Xtreme/PSU Isolated Power Supply
PXG307	PC/104-Plus -xtreme/PSU Isolated HP Series, +18V to +36V DC input, 2.25kV isolation, +5V @ 15A and +12V @ 10A output, RoHS Compliant.	http://connecttech.com/product/xtremepsu-isolated-power-supply/	Xtreme/PSU Isolated Power Supply
PXG308	PC/104 -xtreme/PSU Isolated HP Series, +18V to +36V DC input, 2.25kV isolation, +5V @ 15A and +12V @ 10A output, RoHS Compliant.	http://connecttech.com/product/xtremepsu-isolated-power-supply/	Xtreme/PSU Isolated Power Supply
PXG309	PCI-104 -xtreme/PSU Isolated HP Series, +18V to +36V DC input, 2.25kV isolation, +5V @ 15A and +12V @ 10A output, RoHS Compliant.	http://connecttech.com/product/xtremepsu-isolated-power-supply/	Xtreme/PSU Isolated Power Supply
PXG310	PCIe/104 -xtreme/PSU Isolated HP Series, +18V to +36V DC input, 2.25kV isolation, +5V @ 15A and +12V @ 10A output, RoHS Compliant.	http://connecttech.com/product/xtremepsu-isolated-power-supply/	Xtreme/PSU Isolated Power Supply
PXG311	PCI/104-Express -xtreme/PSU Isolated HP Series, +18V to +36V DC input, 2.25kV isolation, +5V @ 15A and +12V @ 10A output, RoHS Compliant.	http://connecttech.com/product/xtremepsu-isolated-power-supply/	Xtreme/PSU Isolated Power Supply
PXG312	No bus installed -xtreme/PSU Isolated HP Series, +18V to +36V DC input, 2.25kV isolation, +5V @ 15A and +12V @ 10A output, RoHS Compliant.	http://connecttech.com/product/xtremepsu-isolated-power-supply/	Xtreme/PSU Isolated Power Supply
QCG001	PCIe/104 Single Board Computer, PCI Express, USB 2.0, SATA, LPC interface, Gigabit Ethernet, serial, LVDS display. RoHS Compliant. Qseven module required.	http://connecttech.com/product/pcie104-single-board-computer/	PCIe/104 Single Board Computer
QCG002	PCI-104 Single Board Computer, USB 2.0, SATA, LPC interface, Gigabit Ethernet, serial, LVDS display. RoHS Compliant. Qseven module required.	http://connecttech.com/product/pci-104-qseven-carrier-board/	PCI-104 Qseven Carrier Board
QCG005	PicoITX carrier, Mini-PCIe with SIM card expansion, 4x USB 2.0, SATA, and LVDS display interface. RoHS Compliant. Qseven module required.	http://connecttech.com/product/ultra-lite-and-lite-qseven-carrier-boards/	Ultra Lite and Lite Qseven Carrier Boards
QCG006	128x100mm carrier, 2x Mini-PCIe with SIM card expansion, HDMI video/audio, 8x USB 2.0, SATA, and LVDS display interface. RoHS Compliant. Qseven module required.	http://connecttech.com/product/ultra-lite-and-lite-qseven-carrier-boards/	Ultra Lite and Lite Qseven Carrier Boards
QCG011	Qseven PicoITX Carrier Board, 100x 72 mm with Mini- PCIe, SIM card connector, 1x Gigabit Ethernet, 4x USB 2.0, 1x USB Client, 1x SATA, and LVDS display interface. -40°C to 85°C. RoHS Compliant. Qseven module required.	http://connecttech.com/product/ultra-lite-and-lite-qseven-carrier-boards/	Ultra Lite and Lite Qseven Carrier Boards
QCG015	Qseven PicoITX Carrier Board, 100x72 mm with mSATA SSD slot, 1x Gigabit Ethernet, 4x USB 2.0, 1x USB Client, 1x SATA, LVDS display interface, micro HDMI. -40°C to 85°C. RoHS Compliant. Qseven module required.	http://connecttech.com/product/ultra-lite-and-lite-qseven-carrier-boards/	Ultra Lite and Lite Qseven Carrier Boards

Part #	Description	Product Datasheet	Product Group
QCG202	Qseven Gen 2.0 Carrier Board designed for Intel Bay Trail series. 146.05 x 131.76mm, 2x Mini-PCIe/mSATA, 16 bit GPIO, 2x SATA links, 1x DisplayPort/HDMI/DVI, 1x LVDS, 5x RS-232/RS-485, 1x USB 3.0, 4x USB 2.0, 2x Gigabit Ethernet, 1x microSD Card, HD audio, +12V to +36VDC input, -40°C to 85°C. RoHS Compliant.	http://connecttech.com/product/trailblazer-sbc/	TrailBlazer/SBC
QKG201	Intel® Atom™ E3845 Quad Core 1.91GHz, 2MB L2 Cache, 2GB 1333MT/s DDR3L Memory, 4GB eMMC Flash 2x Mini-PCIe/mSATA, 16 bit GPIO, 2x SATA, 1x DisplayPort/HDMI/DVI, 1x LVDS, 5x RS-232/422/485, 1x USB 3.0, 4x USB 2.0, 2x GbE Ethernet, 1x microSD, HD Audio input/output, +12VDC to 36VDC input, -40 to +85C. RoHS Compliant.	http://connecttech.com/product/trailblazer-sbc/	TrailBlazer/SBC
QKG202	Intel® Atom™ E3825 Dual Core 1.33GHz, 1MB L2 Cache, 2GB 1066MT/s DDR3L Memory, 4GB eMMC Flash 2 x Mini-PCIe/mSATA, 16 bit GPIO, 2x SATA, 1x DisplayPort/HDMI/DVI, 1x LVDS, 5x RS-232/422/485, 1x USB 3.0, 4x USB 2.0, 2x GbE Ethernet, 1x microSD, HD Audio input/output, +12VDC to 36VDC input, -40 to +85C. RoHS Compliant.	http://connecttech.com/product/trailblazer-sbc/	TrailBlazer/SBC
QKG203	Intel® Atom™ E3815 Single Core 1.46GHz, 512kB L2 Cache, 2GB 1066MT/s DDR3L Memory, 4GB eMMC Flash 2 x Mini-PCIe/mSATA, 16 bit GPIO, 2x SATA, 1x DisplayPort/HDMI/DVI, 1x LVDS, 5x RS-232/422/485, 1x USB 3.0, 4x USB 2.0, 2x GbE Ethernet, 1x microSD, HD Audio input/output, +12VDC to 36VDC input, -40 to +85C. RoHS Compliant.	http://connecttech.com/product/trailblazer-sbc/	TrailBlazer/SBC
RTG001	RTM for use with GraphiteVPX/CPU Modules Features include: - USB2x8, including x2 USB3 channels - SATAx2 - GbEx2 - GPIO - I2C - Audio - Serial ports RoHS Compliant.		GraphiteVPX
RTG002	RTM for use with GraphiteVPX/GbE modules Features Include: - RJ-45 x16 GbE ports - Serial communication port for the console GbE Switch interface - I2C access for on board Temp. sensors. - Serial LED decoding for Port Activity and Link Speed. RoHS Compliant.		GraphiteVPX
RTG004	RTM for VPG003 provides: 1 - HDMI display output, 2 - USB3 interfaces, 1 - USB2/OTG port, 1 - SATA port, 6 - CSI Camera ports, 2 - GbE ports, 1 - UART port. Includes external reset and force recovery switch. Access to the Geographical Address (GA) lines, and I2C bus. RoHS Compliant.		GraphiteVPX
SCG001	PCI-104 -xtreme/PSU-UPS, +6V to +36V DC input, +3.3V @10A, +5V @10A, +12V @ 5A, -12V @0.05A, and +5V standby @1A, features SMART battery charging. RoHS Compliant.	http://connecttech.com/product/xtremepsu-ups-power-supply/	Xtreme/PSU-UPS Power Supply

Part #	Description	Product Datasheet	Product Group
SCG002	No bus installed -xtreme/PSU-UPS, +6V to +36V DC input, +3.3V @10A, +5V @10A, +12V @ 5A , -12V @0.05A, and +5V standby @1A, features SMART battery charging. RoHS Compliant.	http://connecttech.com/product/xtremepsu-ups-power-supply/	Xtreme/PSU-UPS Power Supply
SDG001	PCI/104-Express stackable dual mSATA SSD carrier. Supports 2 SSD modules with capacities of up to 128GB or more. Operates from power via PCIe/104, PCI-104 or external power. RoHS Compliant. Both PCIe/104 and PCI-104 stacking connectors installed. RoHS Compliant.	http://connecttech.com/product/ssd104-sata-stackable-ssd/	SSD/104 SATA Stackable SSD
SDG002	PCIe/104 stackable dual mSATA SSD carrier. Supports 2 SSD modules with capacities of up to 128GB or more. Operates from power via PCIe/104 or external power. RoHS Compliant. PCIe/104, Only the PCIe/104 stacking connector is installed. RoHS Compliant.	http://connecttech.com/product/ssd104-sata-stackable-ssd/	SSD/104 SATA Stackable SSD
SDG003	PCI-104 stackable dual mSATA SSD carrier. Supports 2 SSD modules with capacities of up to 128GB or more. Operates from power via PCI-104 or external power. RoHS Compliant. PCI-104, Only the PCI-104 stacking connector is installed. RoHS Compliant.	http://connecttech.com/product/ssd104-sata-stackable-ssd/	SSD/104 SATA Stackable SSD
SDG004	PC/104 form factor stackable dual mSATA SSD carrier. Supports 2 SSD modules with capacities of up to 128GB or more. Operates from external power. RoHS Compliant. No Bus, No stacking bus connectors installed. RoHS Compliant.	http://connecttech.com/product/ssd104-sata-stackable-ssd/	SSD/104 SATA Stackable SSD
SDG006	PCIe/104 board allows the use of a standard 2.5" SATA drive in a Type II PCIe/104 stack. RoHS Compliant.	http://connecttech.com/product/ssd-104-sata-2-5-drive-carrier/	SSD/104 SATA 2.5" Drive Carrier
SDG007	PCIe/104 stackable dual mSATA SSD carrier. Can operate from power via PCIe/104 or external power and connects the SATA lanes in the TYPE 2 PCIe/104 Bus to both mSATA drives. Bottom stacking. RoHS Compliant.		SSD/104 SATA 2,5" Drive Carrier
SERNSS01	1 Port Terminal/Device/Console Server - Express Replacement 1 Year Maintenance Contract	https://www.perle.com/support_services/maintenance_agreement.shtml	Service Contracts
SERNSS02	2 Port Terminal Device/Console Server - Express Replacement 1 Year Maintenance Contract	https://www.perle.com/support_services/maintenance_agreement.shtml	Service Contracts
SERNSS02F	2 Port Terminal Device/Console Server - Express Replacement 1 Year Maintenance Contract, French	https://www.perle.com/support_services/maintenance_agreement.shtml	Service Contracts
SERNSS04	4 Port Terminal/Device/Console Servers - Express Replacement 1 Year Maintenance Contract	https://www.perle.com/support_services/maintenance_agreement.shtml	Service Contracts
SERNSS04F	4 Port Terminal/Device/Console Servers - Express Replacement 1 Year Maintenance Contract, French	https://www.perle.com/support_services/maintenance_agreement.shtml	Service Contracts

Part #	Description	Product Datasheet	Product Group
SERNSS08	8 Port Terminal/Device/Console Servers - Express Replacement 1 Year Maintenance Contract	https://www.perle.com/support_services/maintenance_agreement.shtml	Service Contracts
SERNSS08F	8 Port Terminal/Device/Console Servers - Express Replacement 1 Year Maintenance Contract, French	https://www.perle.com/support_services/maintenance_agreement.shtml	Service Contracts
SERNSS16	16 to 18 Port Terminal/Device/Console Servers - Express Replacement 1 Year Maintenance Contract	https://www.perle.com/support_services/maintenance_agreement.shtml	Service Contracts
SERNSS16F	16 to 18 Port Terminal/Device/Console Servers - Express Replacement 1 Year Maintenance Contract, French	https://www.perle.com/support_services/maintenance_agreement.shtml	Service Contracts
SERNSS24	24 Port Terminal/Device/Console Servers - Express Replacement 1 Year Maintenance Contract	https://www.perle.com/support_services/maintenance_agreement.shtml	Service Contracts
SERNSS24F	24 Port Terminal/Device/Console Servers - Express Replacement 1 Year Maintenance Contract, French	https://www.perle.com/support_services/maintenance_agreement.shtml	Service Contracts
SERNSS32	32 to 34 Port Terminal/Device/Console Servers - Express Replacement 1 Year Maintenance Contract	https://www.perle.com/support_services/maintenance_agreement.shtml	Service Contracts
SERNSS32F	32 to 34 Port Terminal/Device/Console Servers - Express Replacement 1 Year Maintenance Contract, French	https://www.perle.com/support_services/maintenance_agreement.shtml	Service Contracts
SERNSS48	48 to 50 Port Terminal/Device/Console Servers - Express Replacement 1 Year Maintenance Contract	https://www.perle.com/support_services/maintenance_agreement.shtml	Service Contracts
SERNSS48F	48 to 50 Port Terminal/Device/Console Servers - Express Replacement 1 Year Maintenance Contract, French	https://www.perle.com/support_services/maintenance_agreement.shtml	Service Contracts
SERRPS08	8 Plug Remote Power Switch - Express Replacement 1 Year Maintenance Contract.	https://www.perle.com/support_services/maintenance_agreement.shtml	Service Contracts
SERRPS16	16 Plug Remote Power Switch - Express Replacement 1 Year Maintenance Contract.	https://www.perle.com/support_services/maintenance_agreement.shtml	Service Contracts
SIMM-20MA	20mA Current Loop SLIM module		SIMM
SIMM-F232	RS-232 FAST SLIM module, 460 K baud; for use with DFlex/FAST products only		SIMM
SIMM-RS232	RS-232 SLIM module		SIMM
SIMM-RS423	RS-423 SLIM module		SIMM
SIMM-RS485	RS-422/485 SLIM module		SIMM
SRG001	SMARC/SL carrier board for both +3.3V and +1.8V. SMARC Modules, Mini-PCIe/mSATA with External SATA switching, Gigabit Ethernet, HDMI Video, and MIPI CSI Camera interface on CSI-0. -40°C to 85°C, RoHS Compliant.	http://connecttech.com/product/smarcsl/	SMARC/SL

Part #	Description	Product Datasheet	Product Group
SRG002	SMARC/SL carrier board for both +3.3V and +1.8V SMARC Modules, Mini-PCIe/mSATA with External SATA switching, Gigabit Ethernet, HDMI Video, and MIPI CSI Camera interface on CSI-1. -40°C to 85°C, RoHS Compliant.	http://connecttech.com/product/smarcsl/	SMARC/SL
SRG004	SMARC 2.0 compliant carrier, featuring 2x HDMI, 2x GBE, 2x USB3.0, 2x USB2.0 in standard front facing connectors. Also includes 1x mPCIe, 1x mSATA/mPCIe, 2x CSI interfaces, I2C, GPIO and RS232. RoHS Compliant.	http://connecttech.com/product/smarc-2-0-carrier/	SMARC 2.0 Carrier
V7G001	COM Express Type 7 + GPU Embedded System. CPU: Xeon® D1577 1.3/2.1GHz 24MB Cache, with 48GB DDR4 2400MT/s ECC Memory, 45W (16C), GPU: NVIDIA Quadro P5000 (100W, 2048 CUDA Cores). With Passive Heat Spreaders (Customer Designed End Thermal Solution). 2x 10G, 4x HDMI Variant	http://connecttech.com/product/com-express-type-7-gpu-embedded-system/	COM Express® Type 7 + GPU Embedded System
V7G002	COM Express Type 7 + GPU Embedded System. CPU: Xeon® D1577 1.3/2.1GHz 24MB Cache, with 48GB DDR4 2400MT/s ECC Memory, 45W (16C), GPU: NVIDIA Quadro P3000 (75W, 1280 CUDA Cores). With Passive Heat Spreaders (Customer Designed End Thermal Solution). 2x 10G, 4x HDMI Variant	http://connecttech.com/product/com-express-type-7-gpu-embedded-system/	COM Express® Type 7 + GPU Embedded System
V7G003	COM Express Type 7 + GPU Embedded System. CPU: Xeon® D1577 1.3/2.1GHz 24MB Cache, with 48GB DDR4 2400MT/s ECC Memory, 45W (16C), GPU: NVIDIA Tesla P6 (90W, 2048 CUDA Cores). With Passive Heat Spreaders (Customer Designed End Thermal Solution). 2x 10G, No Display Output Variant	http://connecttech.com/product/com-express-type-7-gpu-embedded-system/	COM Express® Type 7 + GPU Embedded System
V7G004	COM Express Type 7 + GPU Embedded System. CPU: Xeon® D1559 1.6/2.1GHz 18MB Cache, with 48GB DDR4 2400MT/s ECC Memory, 45W (12C) (eTEMP), GPU: NVIDIA Quadro P5000 (100W, 2048 CUDA Cores). With Passive Heat Spreaders (Customer Designed End Thermal Solution). 2x 10G, 4x HDMI Variant	http://connecttech.com/product/com-express-type-7-gpu-embedded-system/	COM Express® Type 7 + GPU Embedded System
V7G005	COM Express Type 7 + GPU Embedded System. CPU: Xeon® D1559 1.6/2.1GHz 18MB Cache, with 48GB DDR4 2400MT/s ECC Memory, 45W (12C) (eTEMP), GPU: NVIDIA Quadro P3000 (75W, 1280 CUDA Cores). With Passive Heat Spreaders (Customer Designed End Thermal Solution). 2x 10G, 4x HDMI Variant	http://connecttech.com/product/com-express-type-7-gpu-embedded-system/	COM Express® Type 7 + GPU Embedded System

Part #	Description	Product Datasheet	Product Group
V7G006	COM Express Type 7 + GPU Embedded System. CPU: Xeon® D1559 1.6/2.1GHz 18MB Cache, with 48GB DDR4 2400MT/s ECC Memory, 45W (12C) (eTEMP), GPU: NVIDIA Tesla P6 (90W, 2048 CUDA Cores). With Passive Heat Spreaders (Customer Designed End Thermal Solution). 2x 10G, No Display Output Variant	http://connecttech.com/product/com-express-type-7-gpu-embedded-system/	COM Express® Type 7 + GPU Embedded System
V7G010	COM Express Type 7 + GPU Embedded System with Intel® Atom™ C3958 processor with 16 Cores, 2.0GHz core frequency, 16MB Cache, with 48GB DDR4 2400MT/s ECC Memory. Features 4x10GbE, 31W TDP, commercial Temp. range. GPU: NVIDIA Quadro P5000 (100W, 2048 CUDA Cores). With Passive Heat Spreaders (Customer Designed End Thermal Solution). 4x HDMI Variant	http://connecttech.com/product/com-express-type-7-gpu-embedded-system/	COM Express® Type 7 + GPU Embedded System
V7G011	COM Express Type 7 + GPU Embedded System with Intel® Atom™ C3958 processor with 16 Cores, 2.0GHz core frequency, 16MB Cache, with 48GB DDR4 2400MT/s ECC Memory. Features 4xGbE, 31W TDP, commercial Temp. range. GPU: NVIDIA Quadro P3000 (75W, 1280 CUDA Cores). With Passive Heat Spreaders (Customer Designed End Thermal Solution). 4x HDMI Variant	http://connecttech.com/product/com-express-type-7-gpu-embedded-system/	COM Express® Type 7 + GPU Embedded System
V7G012	COM Express Type 7 + GPU Embedded System with Intel® Atom™ C3958 processor with 16 Cores, 2.0GHz core frequency, 16MB Cache, with 48GB DDR4 2400MT/s ECC Memory. Features 4x10GbE 31W TDP, commercial Temp. range. GPU: NVIDIA Tesla P6 (90W, 2048 CUDA Cores). With Passive Heat Spreaders (Customer Designed End Thermal Solution). No Display Output Variant	http://connecttech.com/product/com-express-type-7-gpu-embedded-system/	COM Express® Type 7 + GPU Embedded System
VPG001	The GraphiteVPX/CPU is a VITA 65 compliant 3U single board computer based on the Intel® Atom E3845 (Bay Trail) Quad Core processor. RoHS Compliant.	http://connecttech.com/product/graphite-vpx-cpu-3u-vpx-sbc/	GraphiteVPX/CPU – 3U VPX SBC
VPG003	GraphiteVPX/CPU is a VITA 65 compliant 3U single board computer based on the NVIDIA Jetson TX1 module. RoHS Compliant.	http://connecttech.com/product/graphite-vpx-cpu-tx2-tx1/	GraphiteVPX/CPU – 3U VPX SBC
VPG003-21	GraphiteVPX/CPU is a VITA 65 compliant 3U single board computer based on the NVIDIA Jetson TX2 module. RoHS Compliant.	http://connecttech.com/product/graphite-vpx-cpu-tx2-tx1/	GraphiteVPX/CPU – 3U VPX SBC
VPG003-31	GraphiteVPX/CPU is a VITA 65 compliant 3U single board computer based on the NVIDIA Jetson TX2i module.	http://connecttech.com/product/graphite-vpx-cpu-tx2-tx1/	GraphiteVPX/CPU – 3U VPX SBC

Part #	Description	Product Datasheet	Product Group
VPG101	GraphiteVPX/XMC-PMC is a VITA 65 compliant 3U peripheral carrier card that brings PCIe Gen 3.0 capable features to a mezzanine carrier. Complete with a x8 Gen 3 PCIe capable VITA 42xMC interface for all the newest, high-end mezzanine cards, as well as a 64-bit 133MHz PCI-X capable interface for use with all of your legacy PCI based PMC mezzanines. RoHS Compliant.	http://connecttech.com/product/graphite-vpx-xmc-pmc/	GraphiteVPX/XMC-PMC
VPG201	GraphiteVPX/GbE Managed Ethernet Switch provides Carrier Grade Ethernet switching capabilities in a small 3U embedded form factor. Vitesse 7429 chipset features an embedded MIPS 32-bit CPU, 1Gb external memory and DMA-based frame extraction and insertion support timing over packet, Ethernet OAM, and performance monitoring. Conduction cooled or Air cooled Heatsink option, 20x GbE (10/100/1000 Ethernet)Ports -16 to VPX backplane, 4 to front panel IO, Web GUI or CLI Management, Supports 3U OpenVPX profile: MOD3-SWH-16T-16.4.7-1, Extended Temp. Range-40°C to +85°C. RoHS Compliant.	http://connecttech.com/product/graphite-vpx-gbe-managed-ethernet-switch/	GraphiteVPX/GbE – Managed Ethernet Switch
VPG202	GraphiteVPX/GbE Managed Ethernet Switch provides Carrier Grade Ethernet switching capabilities in a small 3U embedded form factor. Vitesse 7429 chipset features an embedded MIPS 32-bit CPU, 1Gb external memory and DMA-based frame extraction and insertion support timing over packet, Ethernet OAM, and performance monitoring. Conduction cooled 16x GbE (10/100/1000 Ethernet) Ports - to VPX backplane, Web GUI or CLI Management, Supports 3U OpenVPX profile: MOD3-SWH-16T-16.4.7-1, Extended Temp. Range-40°C to +85°C. RoHS Compliant.	http://connecttech.com/product/graphite-vpx-gbe-managed-ethernet-switch/	GraphiteVPX/GbE – Managed Ethernet Switch
VXG101	COM Express + GPU Embedded System. CPU: Intel® Xeon® E3-1505L V5 (4x 2.0 / 2.8 GHz, 8MB cache, 25 W) - 32GB DDR4, GPU: NVIDIA GeForce GTX 1050 Ti (75W, 768 CUDA Cores). With Passive Heat Spreaders (Customer Designed End Thermal Solution). -40°C to +85°C	http://connecttech.com/product/com-express-gpu-embedded-system/	COM Express® + GPU Embedded System
VXG102	COM Express + GPU Embedded System. CPU: Intel® Xeon® E3-1515M V5 (4x 2,8GHz / 3.7GHz, 8MB cache, 35 W) - 32GB DDR4, GPU: NVIDIA GeForce GTX 1080 (150W, 2560 CUDA Cores). With Passive Heat Spreaders (Customer Designed End Thermal Solution). 0°C to +55°C	http://connecttech.com/product/com-express-gpu-embedded-system/	COM Express® + GPU Embedded System

Part #	Description	Product Datasheet	Product Group
VXG201	COM Express + GPU Embedded System. CPU: Intel® Xeon® E3-1505M V6 (4x 3.0 / 4.0 GHz, 8MB Cache, 45W) - 32GB DDR4, GPU: NVIDIA Quadro P5000 (100W, 2048 CUDA Cores). With Passive Heat Spreaders (Customer Designed End Thermal Solution). 0°C to +55°C	http://connecttech.com/product/com-express-gpu-embedded-system/	COM Express® + GPU Embedded System
VXG202	COM Express + GPU Embedded System. CPU: Intel® Xeon® E3-1505L V6 (4x 2.2 / 3.0 GHz, 8MB Cache, 25W) - 32GB DDR4, GPU: NVIDIA Quadro P3000 (75W, 1280 CUDA Cores). With Passive Heat Spreaders (Customer Designed End Thermal Solution). 0°C to +55°C	http://connecttech.com/product/com-express-gpu-embedded-system/	COM Express® + GPU Embedded System
VXG203	COM Express + GPU Embedded System. CPU: Intel® Xeon® E3-1515M V5 (4x 2,8GHz / 3.7GHz, 8MB cache, 35 W) - 32GB DDR4, GPU: NVIDIA Quadro P5000 (100W, 2048 CUDA Cores). With Passive Heat Spreaders (Customer Designed End Thermal Solution). 0°C to +55°C	http://connecttech.com/product/com-express-gpu-embedded-system/	COM Express® + GPU Embedded System
VXG204	COM Express + GPU Embedded System. CPU: Intel® Xeon® E3-1505L V5 (4x 2.0 / 2.8 GHz, 8MB cache, 25 W) - 32GB DDR4, GPU: NVIDIA Quadro P3000 (75W, 1280 CUDA Cores). With Passive Heat Spreaders (Customer Designed End Thermal Solution). 0°C to +55°C	http://connecttech.com/product/com-express-gpu-embedded-system/	COM Express® + GPU Embedded System
VXG301	COM Express + GPU Embedded System. CPU: Intel® Xeon® E3-1505M V6 (4x 3.0 / 4.0 GHz, 8MB Cache, 45W) - 32GB DDR4, GPU: NVIDIA Tesla M6 (100W, 1536 CUDA Cores). With Passive Heat Spreaders (Customer Designed End Thermal Solution). 0°C to +55°C	http://connecttech.com/product/com-express-gpu-embedded-system/	COM Express® + GPU Embedded System
VXG302	COM Express + GPU Embedded System. CPU: Intel® Xeon® E3-1515M V5 (4x 2,8GHz / 3.7GHz, 8MB cache, 35 W) - 32GB DDR4, GPU: NVIDIA Tesla M6 (100W, 1536 CUDA Cores). With Passive Heat Spreaders (Customer Designed End Thermal Solution). 0°C to +55°C	http://connecttech.com/product/com-express-gpu-embedded-system/	COM Express® + GPU Embedded System
WH4A01	WhiteHEAT/USB, 4 ports RS-232, DB-9 connectors	http://connecttech.com/product/whiteheatusb/	WhiteHEAT/USB
XBG001	24 Port Vertical Breakout Board for xDG024, RoHS Compliant.	http://connecttech.com/product/xtreme-gbe-24-port-managed-carrier-ethernet-switch/	Xtreme/GbE 24-Port Managed Carrier Ethernet Switch
XBG002	8 port RJ45 vertical breakout board for XDG024, XDG025; XDG032 and XDG033.	http://connecttech.com/product/xtreme-gbe-24-port-managed-carrier-ethernet-switch/	Xtreme/GbE
XBG003	8 port RJ45 right angle breakout board for XDG024, XDG025; XDG032 and XDG033.	http://connecttech.com/product/xtreme-gbe-24-port-managed-carrier-ethernet-switch/	Xtreme/GbE
XBG009	Xtreme/GbE SFP Breakout Board		

Part #	Description	Product Datasheet	Product Group
XBG101	1x Mini-PCIe Full Size (No USB), 1x mSATA Full Sized, 1x DisplayPort, 1x LVDS Header, 2x RS-232/485 Header, 2x USB 3.0, 4x USB 2.0, 2x GbE RJ-45, 3.5mm Stereo Jack with Mic, 4x GPI Test Points, 4x GPO Test Points, +12V Input. RoHS Compliant.	http://connecttech.com/product/com-express-type-10-stacking-carrier/	COM Express® Type 10 Stacking Carrier
XBG102	1x Mini-PCIe/mSATA Full Size, 1x HDMI, 2x RS-232/485 Header, 2x USB 3.0, 2x USB 2.0 Header, 2x GbE RJ-45, HD Audio Header, +12V Input. RoHS Compliant.	http://connecttech.com/product/com-express-type-10-stacking-carrier/	COM Express® Type 10 Stacking Carrier
XBG201	Astro Breakout Out Board for NVIDIA® Jetson™ TX1 - The Astro Carrier provides access to features found on the Jetson TX1 module in an extremely small footprint (87mmx 57mm/3.43" x 2.24"). It makes use of a high density, board-to-board connector that allows for use with Connect Tech's off the shelf or custom designed break out boards. RoHS Compliant.	http://connecttech.com/product/astro-carrier-for-nvidia-jetson-tx2-tx1/	Astro Carrier for NVIDIA® Jetson™ TX2/TX2i/TX1
XBG301	Development Carrier Board for (XDG201)xtreme/10G Managed Ethernet Switch/Router. Enables ethernet connections to 4x 10G via SFP+, 4x 1G via SFP and 24 x 1GbE via RJ-45 connectors. RoHS Compliant.	http://connecttech.com/product/xtreme10g-managed-ethernet-switchrouter/	Xtreme/10G Managed Ethernet Switch/Router
XBG601	COM Express Type 6 Maximized Breakout Board for CCG060, 195mm x 137.5mm (7.677" x 5.414"), 3x Mini- PCIe/mSATA Full Size (No USB), 1x M.2 Key M (PCI Express or SATA), 1x DisplayPort, 1x HDMI, 1x VGA, 2x RS-232/RS-485, 4x USB 3.0, 4x USB 2.0, 4x RJ-45 Gigabit Ethernet (10/100/1000), HD Audio 3.5mm Stereo Jack, 1x PCI Express x16 Card Slot with Additional +12.0V Power, 1x FAN Header, 1x RESET Button, 1x PWR Button, +12.0V to +48.0V DC Input, -40oC to +85oC	http://connecttech.com/product/com-express-type-6-stacking-carrier/	COM Express® Type 6 Stacking Carrier
XDG004	Xtreme/GbE Gen-II Managed Switch, 8-port Layer 2+ in PC/104 form factor. No PC/104 bus installed, -40 to +85C, RoHS Compliant.	http://connecttech.com/product/xtremegbe-managed-carrier-ethernet-switch/	Xtreme/GbE Managed Carrier Ethernet Switch
XDG005	Xtreme/GbE Gen-II Managed Switch, 8-port Layer 2+ in PC/104 form factor. PC/104 bus installed, -40 to +85C, RoHS Compliant.	http://connecttech.com/product/xtremegbe-managed-carrier-ethernet-switch/	Xtreme/GbE Managed Carrier Ethernet Switch
XDG006	Xtreme/GbE Gen-II Managed Switch, 8-port Layer 2+ in PC/104 form factor. PCIe/104 bus installed, -40 to +85C, RoHS Compliant.	http://connecttech.com/product/xtremegbe-managed-carrier-ethernet-switch/	Xtreme/GbE Managed Carrier Ethernet Switch
XDG007	Xtreme/GbE Gen-II Managed Switch, 8-port Layer 2+ in PC/104 form factor. Ruggedized latching connectors. No PC/104 bus installed, -40 to +85C, RoHS Compliant.	http://connecttech.com/product/xtremegbe-managed-carrier-ethernet-switch/	Xtreme/GbE Managed Carrier Ethernet Switch
XDG008	Xtreme/GbE Gen-II Managed Switch, 8-port Layer 2+ in PC/104 form factor. Ruggedized latching connectors. PC/104 bus installed, -40 to +85C, RoHS Compliant.	http://connecttech.com/product/xtremegbe-managed-carrier-ethernet-switch/	Xtreme/GbE Managed Carrier Ethernet Switch

Part #	Description	Product Datasheet	Product Group
XDG009	Xtreme/GbE Gen-II Managed Switch, 8-port Layer 2+ in PC/104 form factor. Ruggedized latching connectors. PCIe/104 bus installed, -40 to +85C, RoHS Compliant.	http://connecttech.com/product/xtremegbe-managed-carrier-ethernet-switch/	Xtreme/GbE Managed Carrier Ethernet Switch
XDG010	Xtreme/Gbe Gen-II Managed Switch, 12-port Layer 2+ in PC/104 form factor, 10x low profile RJ45, 2x ruggedized latching connectors, PCIe/104 bus installed,-40 to +85C, RoHS Compliant.	http://connecttech.com/product/xtremegbe-managed-carrier-ethernet-switch/	Xtreme/GbE Managed Carrier Ethernet Switch
XDG012	Xtreme/Gbe Gen-II Managed Switch, 12-port Layer 2+ in PC/104 form factor, 10x low profile RJ45, 2x ruggedized latching connectors, no bus ,-40 to +85C, RoHS Compliant.	http://connecttech.com/product/xtremegbe-managed-carrier-ethernet-switch/	Xtreme/GbE Managed Carrier Ethernet Switch
XDG013	Xtreme/Gbe Gen-II Managed Switch, 12-port Layer 2+ in PC/104 form factor, 12x ruggedized latching connectors, PCIe/104 bus installed,-40 to +85C, RoHS Compliant.	http://connecttech.com/product/xtremegbe-managed-carrier-ethernet-switch/	Xtreme/GbE Managed Carrier Ethernet Switch
XDG016	Xtreme/GbE Gen-II Managed Switch, 8-port Layer 2+ in PC/104 form factor. Conduction cooled heatplate. No PC/104 bus installed, -40 to +85C, RoHS Compliant.	http://connecttech.com/product/xtremegbe-managed-carrier-ethernet-switch/	Xtreme/GbE Managed Carrier Ethernet Switch
XDG017	Xtreme/GbE Gen-II Managed Switch, 8-port Layer 2+ in PC/104 form factor. Conduction cooled heatplate. PC/104 bus installed, -40 to +85C, RoHS Compliant.	http://connecttech.com/product/xtremegbe-managed-carrier-ethernet-switch/	Xtreme/GbE Managed Carrier Ethernet Switch
XDG018	Xtreme/GbE Gen-II Managed Switch, 8-port Layer 2+ in PC/104 form factor. Conduction cooled heatplate. PCIe/104 bus installed, -40 to +85C, RoHS Compliant.	http://connecttech.com/product/xtremegbe-managed-carrier-ethernet-switch/	Xtreme/GbE Managed Carrier Ethernet Switch
XDG019	Xtreme/GbE Gen-II Managed Switch, 8-port Layer 2+ in PC/104 form factor. Conduction cooled heatplate. Ruggedized latching connectors. No PC/104 bus installed, -40 to +85C, RoHS Compliant.	http://connecttech.com/product/xtremegbe-managed-carrier-ethernet-switch/	Xtreme/GbE Managed Carrier Ethernet Switch
XDG020	Xtreme/GbE Gen-II Managed Switch, 8-port Layer 2+ in PC/104 form factor. Conduction cooled heatplate. Ruggedized latching connectors. PC/104 bus installed, 40 to +85C, RoHS Compliant.	http://connecttech.com/product/xtremegbe-managed-carrier-ethernet-switch/	Xtreme/GbE Managed Carrier Ethernet Switch
XDG021	Xtreme/GbE Gen-II Managed Switch, 8-port Layer 2+ in PC/104 form factor. Conduction cooled heatplate. Ruggedized latching connectors. PCIe/104 bus installed, -40 to +85C, RoHS Compliant.	http://connecttech.com/product/xtremegbe-managed-carrier-ethernet-switch/	Xtreme/GbE Managed Carrier Ethernet Switch
XDG022	Xtreme/Gbe Gen-II Managed Switch, 12-port Layer 2+ in PC/104 form factor, 10x low profile RJ45, 2x ruggedized latching connectors, Conduction cooled heatplate. PCIe/104 bus installed,-40 to +85C, RoHS Compliant.	http://connecttech.com/product/xtremegbe-managed-carrier-ethernet-switch/	Xtreme/GbE Managed Carrier Ethernet Switch

Part #	Description	Product Datasheet	Product Group
XDG023	Xtreme/Gbe Gen-II Managed Switch, 12-port Layer 2+ in PC/104 form factor, 12x ruggedized latching connectors, Conduction cooled heatplate. PCIe/104 bus installed, -40 to +85C, RoHS Compliant.	http://connecttech.com/product/xtremegbe-managed-carrier-ethernet-switch/	Xtreme/GbE Managed Carrier Ethernet Switch
XDG024	Xtreme/GbE 24-port Managed Switch, 24-port Layer 2+ Gigabit Ethernet Switch, PCIe/104 bus RoHS Compliant.	http://connecttech.com/product/xtreme-gbe-24-port-managed-carrier-ethernet-switch/	Xtreme/GbE 24-Port Managed Carrier Ethernet Switch
XDG025	Xtreme/GbE 24-port version- No bus connector. Board to Board Model. RoHS Compliant.	http://connecttech.com/product/xtreme-gbe-24-port-managed-carrier-ethernet-switch/	Xtreme/GbE 24-Port Managed Carrier Ethernet Switch
XDG029	Xtreme/Gbe Gen-II Managed Switch, 12-port Layer 2+ in PC/104 form factor, 12x ruggedized latching connectors, Conduction cooled heatplate. No bus connector, -40 to +85C, RoHS Compliant.	http://connecttech.com/product/xtreme-gbe-24-port-managed-carrier-ethernet-switch/	Xtreme/GbE 24-Port Managed Carrier Ethernet Switch
XDG032	Xtreme/GbE 24-port Managed Switch, 8-port Layer 2+ Gigabit Ethernet Switch, with top side SFP connector for XBG009, no bus RoHS Compliant.	http://connecttech.com/product/xtreme-gbe-24-port-managed-carrier-ethernet-switch-xdg032/	Xtreme/GbE 24-Port Managed Carrier Ethernet Switch
XDG033	Xtreme/GbE 24-port Managed Switch, 8-port Layer 2+ Gigabit Ethernet Switch, with bottom side SFP connector for XBG009, no bus RoHS Compliant.	http://connecttech.com/product/xtreme-gbe-24-port-managed-carrier-ethernet-switch-xdg032/	Xtreme/GbE 24-Port Managed Carrier Ethernet Switch
XDG101	PCIe/104 Dual 10G board is a dual-port 10 Gigabit Ethernet controller, 0° C to 55°. RoHS Compliant.	http://connecttech.com/product/pcie104-dual-10gbe/	PCIe/104 Dual 10GbE
XDG201	36 port Managed Switch (4x 10GbE; 8x 1GbE [SGMI]; 24x 1GbE) high-density board-to-board connector, +4V to 14V input range, 85mm x 85mm module -40o C to +85o C. RoHS Compliant.	http://connecttech.com/product/xtreme10g-managed-ethernet-switchrouter/	Xtreme/10G Managed Ethernet Switch/Router
XDG201-01	36 port Managed Switch (4x 10GbE; 8x 1GbE [SGMI]; 24x 1GbE) high-density board-to-board connector, +4V to 14V input range, 85mm x 85mm module -40o C to +85o C. With XHG201 Conduction Cooled Heatplate installed. RoHS Compliant.	http://connecttech.com/product/xtreme10g-managed-ethernet-switchrouter/	Xtreme/10G Managed Ethernet Switch/Router
XEG003	Xtreme/104-Express 4 port hardware configurable for RS-232/422/485, 256 byte FIFOs and 9 bit data mode support. -40°C to 85°C, RoHS Compliant.	http://connecttech.com/product/xtreme-104-express-serial-board/	Xtreme/104-Express – Serial Board
XEG003-01	Xtreme/104-Express 4 port hardware configurable for RS-232/422/485, 256 byte FIFOs and 9 bit data mode support, DB-9 Cables. -40°C to 85°C RoHS Compliant.	http://connecttech.com/product/xtreme-104-express-serial-board/	Xtreme/104-Express – Serial Board
XEG004	PCIe/104 4 port hardware configurable for RS-232/422/485, 256 byte FIFOs and 9 bit data mode support. -40°C to 85°C, RoHS Compliant.	http://connecttech.com/product/xtreme-104-express-serial-board/	Xtreme/104-Express – Serial Board

Part #	Description	Product Datasheet	Product Group
XEG004-01	PCIe/104 4 port hardware configurable for RS-232/422/485, 256 byte FIFOs and 9 bit data mode support. DB-9 Cables, -40°C to 85°C, RoHS Compliant.	http://connecttech.com/product/xtreme-104-express-serial-board/	Xtreme/104-Express – Serial Board
XEG005	Xtreme/104-Express 8 port hardware configurable for RS-232/422/485, 256 byte FIFOs and 9 bit data mode support. -40°C to 85°C, RoHS Compliant.	http://connecttech.com/product/xtreme-104-express-serial-board/	Xtreme/104-Express – Serial Board
XEG005-01	Xtreme/104-Express 8 port hardware configurable for RS-232/422/485, 256 byte FIFOs and 9 bit data mode support, DB-9 Cables. -40°C to 85°C, RoHS Compliant.	http://connecttech.com/product/xtreme-104-express-serial-board/	Xtreme/104-Express – Serial Board
XEG006	PCIe/104 8 port hardware configurable for RS-232/422/485, 256 byte FIFOs and 9 bit data mode support. -40°C to 85°C, RoHS Compliant.	http://connecttech.com/product/xtreme-104-express-serial-board/	Xtreme/104-Express – Serial Board
XEG006-01	PCIe/104 8 port hardware configurable for RS-232/422/485, 256 byte FIFOs and 9 bit data mode support. DB-9 Cables, -40°C to 85°C, RoHS Compliant.	http://connecttech.com/product/xtreme-104-express-serial-board/	Xtreme/104-Express – Serial Board
XFG001	Xtreme/104-Express Opto, 4 ports RS-232/422/485, includes 3kV optical isolation, RoHS Compliant.	http://connecttech.com/?s=XFG001	Xtreme/104-Express Opto – Serial Board
XFG001-01	Xtreme/104-Express Opto, 4 ports RS-232/422/485, includes 3kV optical isolation, DB-9 cables, RoHS Compliant.	http://connecttech.com/?s=XFG001	Xtreme/104-Express Opto – Serial Board
XFG002	Xtreme/104-Express Opto, 8 ports RS-232/422/485, includes 3kV optical isolation, RoHS Compliant.	http://connecttech.com/?s=XFG002	Xtreme/104-Express Opto – Serial Board
XFG002-01	Xtreme/104-Express Opto, 8 ports RS-232/422/485, includes 3kV optical isolation, DB-9 cables, RoHS Compliant.	http://connecttech.com/?s=XFG002	Xtreme/104-Express Opto – Serial Board
XHG102	Conduction Cooled Heatplate foXDG025		Heat Sink
XHG201	Conduction Cooled Heatplate for the (XDG201) Xtreme/10G Managed Ethernet Switch/Router RoHS Compliant.	http://connecttech.com/product/xtreme10g-managed-ethernet-switchrouter/	Xtreme/10G Managed Ethernet Switch/Router
XHG301	Passive Finned Heatsink for the NVIDIA TX1 Module RoHS Compliant.	http://connecttech.com/?s=XHG301	NVIDIA® Jetson™ TX2/TX1 Passive Heat Sink
XHG302	Active Thermal Heatsink for the NVIDIA TX1 Module RoHS Compliant.	http://connecttech.com/?s=XHG302	NVIDIA® Jetson™ TX2/TX1 Active Heat Sink
XIG011	Xtreme/PCI-104 Opto with jumper-selectable electrical interfaces for each port (either RS-232 or RS-422/485), and provides 1.0 kV AC RMS Optical Isolation on all ports. Industrial Temp. range, -40 to +85 degrees C. RoHS Compliant. Only Ports 1-8 are fractional baud rate capable.modules. RoHS Compliant.	http://connecttech.com/product/xtremepci-104-opto-12-port/	Xtreme/PCI-104 Opto – 12 Port

Part #	Description	Product Datasheet	Product Group
XMG001	Xtreme/MIO is a multi-protocol, all-in-one board that provides 2 CAN ports, 4x RS-232 serial ports, 1x RS-485/J1708 port and dual sockets for MultiTech	http://connecttech.com/product/xtrememulti-io/	Xtreme/Multi-I/O
XMG001-01	Xtreme/MIO is a multi-protocol, all-in-one board that provides 2 CAN ports, 4x RS-232 serial ports, 1x RS-485/J1708 port and dual sockets for MultiTech modules, DB9 cables. RoHS Compliant.	http://connecttech.com/product/xtrememulti-io/	Xtreme/Multi-I/O
XOG005	Xtreme/104-Plus Opto, 4 ports RS-232/422/485, 3kV optical isolation, industrial Temp. -40°C to 85°C. RoHS Compliant.	http://connecttech.com/product/xtreme104-plus-opto/	Xtreme/104-Plus Opto
XOG005-01	Xtreme/104-Plus Opto, 4 ports RS-232/422/485, 3kV optical isolation, industrial Temp. -40°C to 85°C, DB-9 cables. RoHS Compliant.	http://connecttech.com/product/xtreme104-plus-opto/	Xtreme/104-Plus Opto
XPG002	Xtreme/104-Plus, 4 ports RS-232/422/485, industrial Temp. -40°C to 85°C. RoHS Compliant.	http://connecttech.com/product/xtreme104-plus/	Xtreme/104-Plus
XPG002-01	Xtreme/104-Plus, 4 ports RS-232/422/485, industrial Temp. -40°C to 85°C, DB-9 cables. RoHS Compliant.	http://connecttech.com/product/xtreme104-plus/	Xtreme/104-Plus
XPG003	Xtreme/104-Plus, 8 ports RS-232/422/485, industrial Temp. -40°C to 85°C. RoHS Compliant.	http://connecttech.com/product/xtreme104-plus/	Xtreme/104-Plus
XPG003-01	Xtreme/104-Plus, 8 ports RS-232/422/485, industrial Temp. -40°C to 85°C, DB-9 cables-RoHS Compliant.	http://connecttech.com/product/xtreme104-plus/	Xtreme/104-Plus
XPG024	Xtreme/104-Plus, 16 ports RS-232/422/485, industrial Temp. -40°C to 85°C, PCI and ISA connector. RoHS Compliant.	http://connecttech.com/product/xtreme104-plus-16-port/	Xtreme/104-Plus 16 Port
XPG024-01	Xtreme/104-Plus, 16 ports RS-232/422/485, industrial Temp. -40°C to 85°C, PCI and ISA connector, DB-9 cables. RoHS Compliant.	http://connecttech.com/product/xtreme104-plus-16-port/	Xtreme/104-Plus 16 Port
XT007-01	Xtreme/104 Isolated, 4 ports RS-232, 8 ports RS-232/422/485, 1kV AC electrical isolation on all ports, (115.2Kbps RS-232), (460.8 Kbps RS-422/485)	http://connecttech.com/product/xtreme104-isolated/	Xtreme/104 Isolated
XT009-01	Xtreme/104 Isolated, 4 ports RS-232, 8 ports RS-232/422/485, 1kV AC electrical isolation on all ports, (115.2Kbps RS-232), (1.5 Mbps RS-422/485)		
XTG290200	Xtreme/104, 2 ports RS-232/422/485, 3 kV optical isolation. RoHS Compliant.	http://connecttech.com/product/xtreme104-opto-pc104-serial/	Xtreme/104 Opto – PC/104 Serial
XTG290201	Xtreme/104, 2 ports RS-232/422/485, 3 kV optical isolation, DB-9 cables. RoHS Compliant.	http://connecttech.com/product/xtreme104-opto-pc104-serial/	Xtreme/104 Opto – PC/104 Serial
XTG290220	Xtreme/104, 2 ports RS-232/422/485, 3 kV optical isolation, industrial Temp. -40°C to 85°C. RoHS Compliant.	http://connecttech.com/product/xtreme104-opto-pc104-serial/	Xtreme/104 Opto – PC/104 Serial

Part #	Description	Product Datasheet	Product Group
XTG290221	Xtreme/104, 2 ports RS-232/422/485, 3 kV optical isolation, industrial Temp. -40°C to 85°C, DB-9 cables. RoHS Compliant.	http://connecttech.com/product/xtreme104-opto-pc104-serial/	Xtreme/104 Opto – PC/104 Serial
XTG400000	Xtreme-4/104, 4 ports RS-232. RoHS Compliant.	http://connecttech.com/product/xtreme104-rs-232-pc104-serial-expansion/	Xtreme/104 RS-232 – PC/104 Serial Expansion
XTG400001	Xtreme-4/104, 4 ports RS-232, DB-9 cables. RoHS Compliant.	http://connecttech.com/product/xtreme104-rs-232-pc104-serial-expansion/	Xtreme/104 RS-232 – PC/104 Serial Expansion
XTG490000	Xtreme-4/104, 4 ports RS-232/422/485. RoHS Compliant.	http://connecttech.com/product/xtreme104-pc104-serial-expansion/	Xtreme/104 – PC/104 Serial Expansion
XTG490001	Xtreme-4/104, 4 ports RS-232/422/485, DB-9 cables. RoHS Compliant.	http://connecttech.com/product/xtreme104-pc104-serial-expansion/	Xtreme/104 – PC/104 Serial Expansion
XTG490020	Xtreme-4/104, 4 ports RS-232/422/485, industrial Temp. -40°C to 85°C. RoHS Compliant.	http://connecttech.com/product/xtreme104-pc104-serial-expansion/	Xtreme/104 – PC/104 Serial Expansion
XTG490021	Xtreme-4/104, 4 ports RS-232/422/485, industrial Temp. -40°C to 85°C, DB-9 cables. RoHS Compliant.	http://connecttech.com/product/xtreme104-pc104-serial-expansion/	Xtreme/104 – PC/104 Serial Expansion
XTG490200	Xtreme/104, 4 ports RS-232/422/485, 3 kV optical isolation. RoHS Compliant.	http://connecttech.com/product/xtreme104-opto-pc104-serial/	Xtreme/104 Opto – PC/104 Serial
XTG490201	Xtreme/104, 4 ports RS-232/422/485, 3 kV optical isolation, DB-9 cables. RoHS Compliant.	http://connecttech.com/product/xtreme104-opto-pc104-serial/	Xtreme/104 Opto – PC/104 Serial
XTG490220	Xtreme/104, 4 ports RS-232/422/485, 3 kV optical isolation, industrial Temp. -40°C to 85°C. RoHS Compliant.	http://connecttech.com/product/xtreme104-opto-pc104-serial/	Xtreme/104 Opto – PC/104 Serial
XTG490221	Xtreme/104, 4 ports RS-232/422/485, 3 kV optical isolation, industrial Temp. -40°C to 85°C, DB-9 cables. RoHS Compliant.	http://connecttech.com/product/xtreme104-opto-pc104-serial/	Xtreme/104 Opto – PC/104 Serial
XTG800000	Xtreme-8/104, 8 ports RS-232. RoHS Compliant.	http://connecttech.com/product/xtreme104-rs-232-pc104-serial-expansion/	Xtreme/104 RS-232 – PC/104 Serial Expansion
XTG800001	Xtreme-8/104, 8 ports RS-232, DB-9 cables. RoHS Compliant.	http://connecttech.com/product/xtreme104-rs-232-pc104-serial-expansion/	Xtreme/104 RS-232 – PC/104 Serial Expansion
XTG800020	Xtreme-8/104, 8 ports RS-232, industrial Temp. -40°C to 85°C. RoHS Compliant.	http://connecttech.com/product/xtreme104-rs-232-pc104-serial-expansion/	Xtreme/104 RS-232 – PC/104 Serial Expansion
XTG800021	Xtreme-8/104, 8 ports RS-232, industrial Temp. -40°C to 85°C, DB-9 cables. RoHS Compliant.	http://connecttech.com/product/xtreme104-rs-232-pc104-serial-expansion/	Xtreme/104 RS-232 – PC/104 Serial Expansion
XTG890000	Xtreme-8/104, 8 ports RS-232/422/485. RoHS Compliant.	http://connecttech.com/product/xtreme104-pc104-serial-expansion/	Xtreme/104 – PC/104 Serial Expansion
XTG890001	Xtreme-8/104, 8 ports RS-232/422/485, DB-9 cables. RoHS Compliant.	http://connecttech.com/product/xtreme104-pc104-serial-expansion/	Xtreme/104 – PC/104 Serial Expansion

Part #	Description	Product Datasheet	Product Group
XTG890020	Xtreme-8/104, 8 ports RS-232/422/485, industrial Temp. -40°C to 85°C. RoHS Compliant.	http://connecttech.com/product/xtreme104-pc104-serial-expansion/	Xtreme/104 – PC/104 Serial Expansion
XTG890021	Xtreme-8/104, 8 ports RS-232/422/485, industrial Temp. -40°C to 85°C, DB-9 cables. RoHS Compliant.	http://connecttech.com/product/xtreme104-pc104-serial-expansion/	Xtreme/104 – PC/104 Serial Expansion
80741	Dialogic NaturalAccess 16-port NaturalConference license	https://www.sangoma.com/temp/datasheets/CG-Media-Boards.pdf	NaturalConference license
82391	Dialogic G.723.1 vocoder for Natural Access 2005-1 or later	https://www.sangoma.com/temp/datasheets/CG-Media-Boards.pdf	G.723.1 vocoder
82392	Dialogic G.729a vocoder for Natural Access 2005-1 or later	https://www.sangoma.com/temp/datasheets/CG-Media-Boards.pdf	G.729a vocoder
82408	Dialogic® CG Series CG 6565C/64-2L/16TE Dual 10/100/1000Base-T Ethernet and 16 software-selectable T1/E1, CompactPCI, 12 DSPs No longer certified for shipment in China Ports on the board must be licensed for G.723 and/or G.729a if used For E1 75-ohm connections, an external balun is required Customer may purchase signal entry panel kits to break each RJ-21 connectors into 8 RJ-48C connectors; see part numbers 82923-1 and 82923-2	https://portal.sangoma.com/marketing/resources/2580/Sangoma%20Corporate/Datasheets/Dialogic-CG-Media-Boards.pdf	Media Processing Board
82409	Dialogic® CG Series CG 6565C/128-2L/16TE Dual 10/100/1000Base-T Ethernet and 16 software-selectable T1/E1, CompactPCI, 24 DSPs No longer certified for shipment in China Ports on the board must be licensed for G.723 and/or G.729a if used For E1 75-ohm connections, an external balun is required Customer may purchase signal entry panel kits to break each RJ-21 connectors into 8 RJ-48C connectors; see part numbers 82923-1 and 82923-2	https://www.sangoma.com/temp/datasheets/CG-Media-Boards.pdf	Media Processing Board
83080	Dialogic SIP Evaluation License- 90 days, 128 sessions Runtime license requires lock code for activation Licensed number of ports (sessions) are additive	https://www.sangoma.com/temp/datasheets/CG-Media-Boards.pdf	SIP Evaluation License
83105	Dialogic® CG Series CG 6565E/64-2L/4TE PCIe Dual 10/100/1000Base-T Ethernet and quad software-selectable T1/E1, full size, 12 DSPs Ports on the board must be licensed for G.723 and/or G.729a if used	https://www.sangoma.com/temp/datasheets/CG-Media-Boards.pdf	Media Processing Board

Part #	Description	Product Datasheet	Product Group
83108	Dialogic® CG Series CG 6565e/64-2L/8TE PCIe Dual 10/100/1000Base-T Ethernet and octal software-selectable T1/E1, full size, 12 DSPs Ports on the board must be licensed for G.723 and/or G.729a if used For E1 75-ohm connections, an external balun is required Customer may purchase signal entry panel kits to break each mRJ-21 connectors into 8 RJ-48C connectors; see part numbers 82924-1 and 82924-2	https://www.sangoma.com/temp/datasheets/CG-Media-Boards.pdf	Media Processing Board
83110	Dialogic® CG Series - Dual 10/100/1000Base-T Ethernet and no T1/E1 trunks, full size PCIEs, 12 DSPs Ports on the board must be licensed for G.723 and/or G.729a if used	https://www.sangoma.com/temp/datasheets/CG-Media-Boards.pdf	Media Processing Board
83198	Dialogic® CG Series - Dual 10/100/1000Base-T Ethernet and dual software-selectable T1/E1, full size PCIe, 3 DSPs Ports on the board must be licensed for G.723 and/or G.729a if used	https://www.sangoma.com/temp/datasheets/CG-Media-Boards.pdf	Media Processing Board
83199	Dialogic® CG Series - Dual 10/100/1000Base-T Ethernet and quad software-selectable T1/E1, full size PCIe, 3 DSPs Ports on the board must be licensed for G.723 and/or G.729a if used	https://www.sangoma.com/temp/datasheets/CG-Media-Boards.pdf	Media Processing Board
83201	Dialogic® CG Series Dual 10/100/1000Base-T Ethernet and octal software-selectable T1/E1, full size PCIe, 6 DSPs Ports on the board must be licensed for G.723 and/or G.729a if used For E1 75-ohm connections, an external balun is required Customer may purchase signal entry panel kits to break each mRJ-21 connectors into 8 RJ-48C connectors; see part numbers 82924-1 and 82924-2	https://www.sangoma.com/temp/datasheets/CG-Media-Boards.pdf	Media Processing Board
83202	Dialogic® CG Series - Dual 10/100/1000Base-T Ethernet and quad software-selectable T1/E1, full size PCIe, 6 DSPs Ports on the board must be licensed for G.723 and/or G.729a if used	https://www.sangoma.com/temp/datasheets/CG-Media-Boards.pdf	Media Processing Board
83289	Dialogic® CG Series CG 6565E/32-2L/4TE media processing board (Avaya Special 700479082)	https://portal.sangoma.com/marketing/resources/2002/Sangoma Corporate/Portal Images/CG6565E.png	Media Processing Board
A142-X3713KIT	Sangoma A142-X3713KIT 2 Port PCI Serial Card x.21 Interface	https://portal.sangoma.com/marketing/resources/1022/Sangoma Corporate/Datasheets/Digital-PRI-Cards-Datasheet-web.pdf	Synchronous Serial Card
A144-E3911KIT	Sangoma A144-E3911KIT 4 port PCI Serial card EIA530 Interface	https://portal.sangoma.com/marketing/resources/1022/Sangoma Corporate/Datasheets/Digital-PRI-Cards-Datasheet-web.pdf	Synchronous Serial Card
A144-EE3911KIT	Sangoma A144-EE3911KIT 4 port PCIe Serial card EIA530 Interface	https://portal.sangoma.com/marketing/resources/1022/Sangoma Corporate/Datasheets/Digital-PRI-Cards-Datasheet-web.pdf	Synchronous Serial Card

Part #	Description	Product Datasheet	Product Group
A144-R	Sangoma A144-R 4 Port PCI Serial Card RS232 Interface	https://portal.sangoma.com/marketing/resources/1022/Sangoma%20Corporate/Datasheets/Digital-PRI-Cards-Datasheet-web.pdf	Synchronous Serial Card
A144-R	Sangoma A144-R 4 Port PCI Serial Card RS232 Interface	https://portal.sangoma.com/marketing/resources/1022/Sangoma%20Corporate/Datasheets/Digital-PRI-Cards-Datasheet-web.pdf	Synchronous Serial Card
A144-R3807KIT	Sangoma A144-R3807KIT 4 Port PCI Serial Card + RS232 Cables	https://portal.sangoma.com/marketing/resources/1022/Sangoma%20Corporate/Datasheets/Digital-PRI-Cards-Datasheet-web.pdf	Synchronous Serial Card
A144-R3807KIT	Sangoma A144-R3807KIT 4 Port PCI Serial Card + RS232 Cables	https://portal.sangoma.com/marketing/resources/1022/Sangoma%20Corporate/Datasheets/Digital-PRI-Cards-Datasheet-web.pdf	Synchronous Serial Card
A144-R38KIT	Sangoma A144-R38KIT 4 Port PCI Serial Card RS232 + 4 Port Cable	https://portal.sangoma.com/marketing/resources/1022/Sangoma%20Corporate/Datasheets/Digital-PRI-Cards-Datasheet-web.pdf	Synchronous Serial Card
A144-RE	Sangoma A144-RE 4 Port PCI Serial Card RS232 Interface	https://portal.sangoma.com/marketing/resources/1022/Sangoma%20Corporate/Datasheets/Digital-PRI-Cards-Datasheet-web.pdf	Synchronous Serial Card
A144-V	Sangoma A144-V 4 port PCI Serial card EIA530 Interface	https://portal.sangoma.com/marketing/resources/1022/Sangoma%20Corporate/Datasheets/Digital-PRI-Cards-Datasheet-web.pdf	Synchronous Serial Card
A144-VE	Sangoma A144-VE 4 port PCIe Serial card V.35 Interface	https://portal.sangoma.com/marketing/resources/1022/Sangoma%20Corporate/Datasheets/Digital-PRI-Cards-Datasheet-web.pdf	Synchronous Serial Card
305-396	Dialogic Diva V4PRI/E1/T1-120 PCIe - 96-/120-port, enhanced voice, Half Size Form Factor, Bundle with 120 ch Modem license	https://www.sangoma.com/temp/datasheets/Diva-VxPRI-Multi-Span.pdf	Diva V PRI
305-397	Dialogic Diva V2PRI/E1/T1-60 PCIe - 48-/60-port, enhanced voice, Half Size Form Factor, Bundle with 60 ch Modem license	https://www.sangoma.com/temp/datasheets/Diva-VxPRI-Multi-Span.pdf	Diva V PRI
305-398	Dialogic Diva V1PRI/E1/T1-30 PCIe - 24-/30-port, enhanced voice, Half Size Form Factor, Bundle with 30 ch Modem license	https://www.sangoma.com/temp/datasheets/Diva-VxPRI-Multi-Span.pdf	Diva V PRI
305-403	Dialogic Diva V-4PRI E1 T1-120 96-120PT PCIe - 96-/120-port, enhanced voice, Full Size Form Factor, Bundle with 120 ch Modem license	https://www.sangoma.com/temp/datasheets/Diva-VxPRI-Multi-Span.pdf	Diva V PRI
306-304	Dialogic Diva PRI/E1-30 PCIE 30PORT PCIe - 30-port, enhanced voice, fax (V.34), modem, Full Size Form Factor. No longer certified for shipment in China.	https://www.sangoma.com/temp/datasheets/Diva-VxPRI-Multi-Span.pdf	Diva PRI
306-320	Dialogic Diva PRI/E1/T1CTI PCIE-24/30PT PCIe - 24/30-port, basic voice, no fax, no modem, Low Profile Form Factor (Contains LP Bracket). No longer certified for shipment in China.	https://www.sangoma.com/temp/datasheets/Diva-VxPRI-Multi-Span.pdf	Diva PRI
306-341	Dialogic Diva 4BRI-8 8PRT PCIe - 8 Channels fax (V.34), Half Size Form Factor. No longer certified for shipment in China.	https://www.sangoma.com/temp/datasheets/Diva-BRI-Boards.pdf	Diva BRI

Part #	Description	Product Datasheet	Product Group
306-342	Diva Diva 2BRI-4 4PRT PCIe - 2 Channels fax (V.34), Low Profile Form Factor (Contains LP Bracket). No longer certified for shipment in China.	https://www.sangoma.com/temp/datasheets/Diva-BRI-Boards.pdf	Diva BRI
306-380	Dialogic Diva UM4BRI8 PCIe-8 Port PCIe - 8-port, 4 Channel fax (V.34), Half Size Form Factor. No longer certified for shipment in China.	https://www.sangoma.com/temp/datasheets/Diva-BRI-Boards.pdf	Diva UM-BRI
306-382	Dialogic Diva UM BRI2 PCIe - 2-port, 1 Channel fax (V.34), Low Profile Form Factor (with additional LP bracket). No longer certified for shipment in China.	https://www.sangoma.com/temp/datasheets/Diva-BRI-Boards.pdf	Diva UM-BRI
306-386	Dialogic Diva Analog 2 PCIe - 2 Channels fax (V.34), Loop-Start, Low Profile Form Factor	https://www.sangoma.com/temp/datasheets/Diva-Analog-Boards.pdf	Diva Analog
306-387	Dialogic Diva UM 2 PCIe - 2-port Analog, 1 Channel fax (V.34), Loop-Start, Low Profile Form Factor	https://www.sangoma.com/temp/datasheets/Diva-Analog-Boards.pdf	Diva UM-Analog
306-388	Dialogic Diva UM Analog 4 PCIe - 4-port Analog, 2 Channels fax (V.34), Loop-Start, Half Size Form Factor	https://www.sangoma.com/temp/datasheets/Diva-Analog-Boards.pdf	Diva UM-Analog
306-389	Dialogic Diva Analog-4 PCIe - 4 Channels fax (V.34), Loop-Start, Half Size Form Factor	https://www.sangoma.com/temp/datasheets/Diva-Analog-Boards.pdf	Diva Analog
306-390	Dialogic Diva Analog-8 PCIe - 8 Channels fax (V.34), Loop-Start, Half Size Form Factor	https://www.sangoma.com/temp/datasheets/Diva-Analog-Boards.pdf	Diva UM-Analog
306-392	Dialogic Diva PRI/E1/T1-CTI OCie - 24-port, enhanced voice, 12 Channel fax (V.34), modem, Full Size Form Factor. No longer certified for shipment in China.	https://www.sangoma.com/temp/datasheets/Diva-BRI-Boards.pdf	Diva UM-PRI
306-395	Dialogic Diva Analog-8 PCIe - 8 Channels fax (V.34), Loop-Start, Half Size Form Factor	https://www.sangoma.com/temp/datasheets/Diva-Analog-Boards.pdf	Diva Analog
306-396	Dialogic Diva V-4PRI/E1/T1-120 - 96-/120-port PCIe, enhanced voice, Half Size Form Factor, feature upgrade to UM/Fax, Modem, Fax and VoIP is possible via Licenses. No longer certified for shipment in China.	https://www.sangoma.com/temp/datasheets/Diva-VxPRI-Multi-Span.pdf	Diva V PRI
306-397	Dialogic Diva V-2PRI/E1/T1-60 PCIe - 48-/60-port, enhanced voice, Half Size Form Factor, feature upgrade to UM/Fax, Modem, Fax and VoIP is possible via Licenses. No longer certified for shipment in China.	https://www.sangoma.com/temp/datasheets/Diva-VxPRI-Multi-Span.pdf	Diva V PRI
306-398	Dialogic Diva V-1PRI/E1/T1-30 PCIe - 24-/30-port, PCIe, enhanced voice, Half Size Form Factor, feature upgrade to UM/Fax, Modem, Fax and VoIP is possible via Licenses. No longer certified for shipment in China.	https://www.sangoma.com/temp/datasheets/Diva-VxPRI-Multi-Span.pdf	Diva V PRI

Part #	Description	Product Datasheet	Product Group
306-403	Dialogic Diva V-4PRI/E1/T1-120 PCIe - 96-/120-port, enhanced voice, Full Size Form Factor, feature upgrade to UM/Fax, Modem, Fax and VoIP is possible via Licenses. No longer certified for shipment in China.	https://www.sangoma.com/temp/datasheets/Diva-VxPRI-Multi-Span.pdf	Diva V PRI
306-404	Dialogic Diva V-8PRI/E1/T1-240 PCIe - 192-/240-port, enhanced voice, Full Size Form Factor, feature upgrade to UM/Fax, Modem, Fax and VoIP is possible via Licenses. No longer certified for shipment in China.	https://www.sangoma.com/temp/datasheets/Diva-VxPRI-Multi-Span.pdf	Diva V PRI
306-427	Dialogic DNI2410TEPE2HMP Octal Span T1/E1 Digital Network Interface Board for Host Media Processing Software, onboard echo cancellation, half-length, standard-height PCIe	https://www.sangoma.com/temp/datasheets/HMP-DNI-Half-Length-PCIe-Boards.pdf	DNI2410TEPE2HMP
306-428	Dialogic DNI1210TEPE2HMP Quad Span T1/E1 Digital Network Interface board for Host Media Processing Software, onboard echo cancellation, half-length, standard-height PCIe	https://www.sangoma.com/temp/datasheets/HMP-DNI-Half-Length-PCIe-Boards.pdf	DNI1210TEPE2HMP
306-483	Dialogic DNI310TEPE2HMP Single Span T1/E1 Digital Network Interface Board for Host Media Processing Software, onboard echo cancellation, half-length, standard-height PCIe	https://www.sangoma.com/temp/datasheets/HMP-DNI-Half-Length-PCIe-Boards.pdf	DNI310TEPE2HMP
306-484	Dialogic DNI610TEPE2HMP Dual Span T1/E1 Digital Network Interface board for Host Media Processing Software, onboard echo cancellation, half-length, standard-height PCIe	https://www.sangoma.com/temp/datasheets/HMP-DNI-Half-Length-PCIe-Boards.pdf	DNI610TEPE2HMP
310-892	DMG2120DTISQ 4-span T1/E1 Media Gateway, Survivable	https://wiki.sangoma.com/display/DMG/Dialogic+2000+Media+Gateway+Series	Dialogic Media Gateway
310-935	Dialogic D/4PCIUFEQ 4-port Analog, Loop-Start, PCIe (4 voice, 4 fax)	https://www.sangoma.com/temp/datasheets/HMP-D4PCIUF-D4PCIU4S-Media-Boards.pdf	D4PCIUFEQ
310-936	Dialogic D4PCIU4SEQ 4-port Analog, Loop-Start, PCIe (4 voice, 4 speech)	https://www.sangoma.com/temp/datasheets/HMP-D4PCIUF-D4PCIU4S-Media-Boards.pdf	D4PCIU4SEQ
310-942	Dialogic D4PCIUFEQEU 4-port Analog, Loop-Start, PCIe, Europe (4 voice, 4 fax)	https://www.sangoma.com/temp/datasheets/HMP-D4PCIUF-D4PCIU4S-Media-Boards.pdf	D4PCIUFEQEU
601-294	Dialogic Diva BRI-2 PCIe v1 Cornet	https://www.sangoma.com/temp/datasheets/Diva-BRI-Boards.pdf	Diva BRI
82298-08	Dialogic 8-session SIP license for NaturalAccess Runtime license requires lock code for activation Licensed number of ports (sessions) are additive	https://www.sangoma.com/temp/datasheets/CG-Media-Boards.pdf	SIP under NCC Runtime License
82298-128	Dialogic 128-session SIP license for NaturalAccess Runtime license requires lock code for activation Licensed number of ports (sessions) are additive	https://www.sangoma.com/temp/datasheets/CG-Media-Boards.pdf	SIP under NCC Runtime License
82298-16	Dialogic 16-session SIP license for NaturalAccess Runtime license requires lock code for activation Licensed number of ports (sessions) are additive	https://www.sangoma.com/temp/datasheets/CG-Media-Boards.pdf	SIP under NCC runtime license

Part #	Description	Product Datasheet	Product Group
82298-256	Dialogic 256-session SIP license for NaturalAccess Runtime license requires lock code for activation Licensed number of ports (sessions) are additive	https://www.sangoma.com/temp/datasheets/CG-Media-Boards.pdf	SIP under NCC Runtime License
82298-32	Dialogic 32-session SIP license for NaturalAccess Runtime license requires lock code for activation Licensed number of ports (sessions) are additive	https://www.sangoma.com/temp/datasheets/CG-Media-Boards.pdf	SIP under NCC runtime license
82298-512	Dialogic 512-session SIP license for NaturalAccess Runtime license requires lock code for activation Licensed number of ports (sessions) are additive	https://www.sangoma.com/temp/datasheets/CG-Media-Boards.pdf	SIP under NCC Runtime License
82298-64	Dialogic 64-session SIP license for NaturalAccess Runtime license requires lock code for activation Licensed number of ports (sessions) are additive	https://www.sangoma.com/temp/datasheets/CG-Media-Boards.pdf	SIP under NCC Runtime License
82384N	Dialogic® CG Series Dual 10/100Base-T Ethernet and quad software-selectable T1/E1, full size PCI, 3 DSPs Non-N on-the market RoHS-compliant product available for shipment only within the EU Ports on the board must be licensed for G.723 and/or G.729a if used.	https://www.sangoma.com/temp/datasheets/CG-Media-Boards.pdf	Media Processing Board
82385N	Dialogic® CG Series Dual 10/100Base-T Ethernet and quad software-selectable T1/E1, full size PCI, 6 DSPs Non-N on-the market RoHS-compliant product available for shipment only within the EU Ports on the board must be licensed for G.723 and/or G.729a if used.	https://www.sangoma.com/temp/datasheets/CG-Media-Boards.pdf	Media Processing Board
82926N	Dialogic® CG Series Dual 10/100Base-T Ethernet and single software-selectable T1/E1, full size PCI, 2 DSPs Non-N on-the market RoHS-compliant product available for shipment only within the EU Ports on the board must be licensed for G.723 and/or G.729a if used	https://www.sangoma.com/temp/datasheets/CG-Media-Boards.pdf	Media Processing Board
8785-01	Dialogic NaturalAccess 1-port NaturalFax license	https://www.sangoma.com/temp/datasheets/CG-Media-Boards.pdf	NaturalFax license
881-762N	Dialogic D120JCTLSW 12-port Analog, Loop-Start, PCI. Non-N on-the market RoHS-compliant product available for shipment only within the EU.	https://www.sangoma.com/temp/datasheets/JCT-D120JCTLS-Boards.pdf	D120JCTLSW

Part #	Description	Product Datasheet	Product Group
881-770	Dialogic D41JCTLSW 4-port Analog, Loop-Start, PCI	https://www.sangoma.com/temp/datasheets/JCT-D41JCTLS-Boards.pdf	D41JCTLSW
881-775	Dialogic D4PCIUFW 4-port Analog, Loop-Start, PCI (4 voice, 4 fax)	https://www.sangoma.com/temp/datasheets/HMP-D4PCIUF-D4PCIU4S-Media-Boards.pdf	D4PCIUF
884-214N	DMG1008LSW 8-port Media Gateway between analog FXO lines and SIP network. Non-N on-the market RoHS-compliant product available for shipment only within the EU. No longer certified for shipment in China.	https://wiki.sangoma.com/display/DMG/Dialogic+1000+Media+Gateway+Series	Dialogic Media Gateway
884-578	Dialogic D120JCTLSEWEU 12-port Analog, Loop-Start, PCIe, Europe	https://www.sangoma.com/temp/datasheets/JCT-D120JCTLS-Boards.pdf	D120JCTLSEEU
884-589	Dialogic D480JCT2T1EW 48-port Digital T1, PCIe. No longer certified for shipment in China	https://www.sangoma.com/temp/datasheets/JCT-D480-D600-Boards.pdf	D480JCT2T1E
884-592	Dialogic D600JCT2E1120EW 60-port Digital E1, PCIe	https://www.sangoma.com/temp/datasheets/JCT-D480-D600-Boards.pdf	D600JCT2E1120E
884-594	Dialogic D120JCTLSEW 12-port Analog, Loop-Start, PCIe	https://www.sangoma.com/temp/datasheets/JCT-D120JCTLS-Boards.pdf	D120JCTLSE
887-491	Dialogic D41JCTLSEW 4-port Analog, Loop-Start, PCIe	https://www.sangoma.com/temp/datasheets/JCT-D41JCTLS-Boards.pdf	D41JCTLSE
887-492	Dialogic VFX 41JCT-LS-EW 4-port Analog, Loop-Start, PCIe	https://www.sangoma.com/temp/datasheets/JCT-VFX41JCTLS-Boards.pdf	VFX41JCTLSE
887-531	Dialogic D240JCTT1EW 24-port Digital T1, PCIe. No longer certified for shipment in China	https://www.sangoma.com/temp/datasheets/JCT-D240-D300-Boards.pdf	D240JCTT1E
887-532	Dialogic D82JCTUEW 8-port PBX integration board, PCIe, RoHS 5/6. No longer certified for shipment in China	https://www.sangoma.com/temp/datasheets/PBX-Integration-Board-D82JCTU.pdf	D82JCTUE
887-533	Dialogic D300JCTE1120EW 30-port Digital E1, PCIe.	https://www.sangoma.com/temp/datasheets/JCT-D240-D300-Boards.pdf	D300JCTE1120E
887-628	Dialogic D42JCTUEW 4-port PBX integration board, PCIe, RoHS 5/6. No longer certified for shipment in China	https://www.sangoma.com/temp/datasheets/PBX-Integration-Boards-D42JCTU.pdf	D42JCTUE
A101-DEKIT	Sangoma A101DE 1 port T1/E1/J1 PCIe 1024 tap (128ms) hardware based echo canceller across 30 channels AFT card supporting single T1/E1 or fractional T1/E1 data streams	https://portal.sangoma.com/marketing/resources/1022/Sangoma%20Corporate/Datasheets/Digital-PRI-Cards-Datasheet-web.pdf	Synchronous Serial Card
A101-DKIT	Sangoma A101D 1 port T1/E1/J1 PCI 1024 tap (128ms) hardware based echo canceller across 30 channels AFT card supporting single T1/E1 or fractional T1/E1 data streams	https://portal.sangoma.com/marketing/resources/1022/Sangoma%20Corporate/Datasheets/Digital-PRI-Cards-Datasheet-web.pdf	Synchronous Serial Card
A101-EKIT	Sangoma A101E 1 port T1/E1/J1 PCIe AFT card supporting single T1/E1 or fractional T1/E1 data streams	https://portal.sangoma.com/marketing/resources/1022/Sangoma%20Corporate/Datasheets/Digital-PRI-Cards-Datasheet-web.pdf	Synchronous Serial Card
A101-KIT	Sangoma A101 1 port T1/E1/J1 PCI AFT card supporting single T1/E1 or fractional T1/E1 data streams	https://portal.sangoma.com/marketing/resources/1022/Sangoma%20Corporate/Datasheets/Digital-PRI-Cards-Datasheet-web.pdf	Synchronous Serial Card

Part #	Description	Product Datasheet	Product Group
A102-DEKIT	Sangoma A102DE 2 port T1/E1/J1 PCIe 1024 tap (128ms) hardware based echo canceller across 60 channels AFT card supporting dual T1/E1 or fractional T1/E1 data streams	https://portal.sangoma.com/marketing/resources/1022/Sangoma%20Corporate/Datasheets/Digital-PRI-Cards-Datasheet-web.pdf	Synchronous Serial Card
A102-DKIT	Sangoma A102D 2 port T1/E1/J1 PCI 1024 tap (128ms) hardware based echo canceller across 60 channels AFT card supporting dual T1/E1 or fractional T1/E1 data streams	https://portal.sangoma.com/marketing/resources/1022/Sangoma%20Corporate/Datasheets/Digital-PRI-Cards-Datasheet-web.pdf	Synchronous Serial Card
A102-EKIT	Sangoma A102E 2 port T1/E1/J1 PCIe AFT card supporting dual T1/E1 or fractional T1/E1 data streams	https://portal.sangoma.com/marketing/resources/1022/Sangoma%20Corporate/Datasheets/Digital-PRI-Cards-Datasheet-web.pdf	Synchronous Serial Card
A102-KIT	Sangoma A102 2 port T1/E1/J1 PCI AFT card supporting dual T1/E1 or fractional T1/E1 data streams	https://portal.sangoma.com/marketing/resources/1022/Sangoma%20Corporate/Datasheets/Digital-PRI-Cards-Datasheet-web.pdf	Synchronous Serial Card
A104-DEKIT	Sangoma A104DE 4 port T1/E1/J1 PCIe 1024 tap (128ms) hardware based echo canceller across 120 channels AFT card supporting quad T1/E1 or fractional T1/E1 data streams	https://portal.sangoma.com/marketing/resources/1022/Sangoma%20Corporate/Datasheets/Digital-PRI-Cards-Datasheet-web.pdf	Synchronous Serial Card
A104-DKIT	Sangoma A104D 4 port T1/E1/J1 PCI 1024 tap (128ms) hardware based echo canceller across 120 channels AFT card supporting Quad T1/E1 or fractional T1/E1 data streams	https://portal.sangoma.com/marketing/resources/1022/Sangoma%20Corporate/Datasheets/Digital-PRI-Cards-Datasheet-web.pdf	Synchronous Serial Card
A104-EKIT	Sangoma A104E 4 port T1/E1/J1 PCIe AFT card supporting quad T1/E1 or fractional T1/E1 data streams	https://portal.sangoma.com/marketing/resources/1022/Sangoma%20Corporate/Datasheets/Digital-PRI-Cards-Datasheet-web.pdf	Synchronous Serial Card
A104-KIT	Sangoma A104 4 port T1/E1/J1 PCI AFT card supporting quad T1/E1 or fractional T1/E1 data streams	https://portal.sangoma.com/marketing/resources/1022/Sangoma%20Corporate/Datasheets/Digital-PRI-Cards-Datasheet-web.pdf	Synchronous Serial Card
A108-DEKIT	Sangoma A108DE 8 port T1/E1/J1 PCIe 1024 tap (128ms) hardware based echo canceller across 240 channels AFT card supporting eight T1/E1 or fractional T1/E1 data streams	https://portal.sangoma.com/marketing/resources/1022/Sangoma%20Corporate/Datasheets/Digital-PRI-Cards-Datasheet-web.pdf	Synchronous Serial Card
A108-DKIT	Sangoma A108D 8 port T1/E1/J1 PCI 1024 tap (128ms) hardware based echo canceller across 240 channels AFT card supporting eight T1/E1 or fractional T1/E1 data streams	https://portal.sangoma.com/marketing/resources/1022/Sangoma%20Corporate/Datasheets/Digital-PRI-Cards-Datasheet-web.pdf	Synchronous Serial Card
A108-EKIT	Sangoma A108DE 8 port T1/E1/J1 PCIe AFT card supporting eight T1/E1 or fractional T1/E1 data streams	https://portal.sangoma.com/marketing/resources/1022/Sangoma%20Corporate/Datasheets/Digital-PRI-Cards-Datasheet-web.pdf	Synchronous Serial Card
A108-KIT	Sangoma A108 8 port T1/E1/J1 PCI AFT card supporting eight T1/E1 or fractional T1/E1 data streams	https://portal.sangoma.com/marketing/resources/1022/Sangoma%20Corporate/Datasheets/Digital-PRI-Cards-Datasheet-web.pdf	Synchronous Serial Card
A116-DEPNLKIT	Sangoma A1116 16 port T1/E1/J1 PCIe w/EC HW Kit w/Breakout Panel and 648	https://portal.sangoma.com/marketing/resources/1022/Sangoma%20Corporate/Datasheets/Digital-PRI-Cards-Datasheet-web.pdf	Synchronous Serial Breakout Panel
A116-EPNLKIT	Sangoma A1116-E Kit 16 port T1/E1/J1 PCIe Kit w/breakout panel and 648 cable	https://portal.sangoma.com/marketing/resources/1022/Sangoma%20Corporate/Datasheets/Digital-PRI-Cards-Datasheet-web.pdf	Synchronous Serial Breakout Panel

Part #	Description	Product Datasheet	Product Group
A142-E3711KIT	A142-E3711KIT 2 port PCI Serial Card EIA530 Interface + Cables	https://portal.sangoma.com/marketing/resources/1022/Sangoma%20Corporate/Datasheets/Digital-PRI-Cards-Datasheet-web.pdf	Synchronous Serial Card
A142-E37KIT	A142-E37KIT 2 port PCI Serial Card EIA530 Interface	https://portal.sangoma.com/marketing/resources/1022/Sangoma%20Corporate/Datasheets/Digital-PRI-Cards-Datasheet-web.pdf	Synchronous Serial Card
A142-EE37KIT	A142-EE37KIT 2 Port PCIe Serial Card V.35 2 Port Cable	https://portal.sangoma.com/marketing/resources/1022/Sangoma%20Corporate/Datasheets/Digital-PRI-Cards-Datasheet-web.pdf	Synchronous Serial Card
A142-R3607KIT	A142-R3607KIT 2 Port PCI Serial Card + RS232 Cables	https://portal.sangoma.com/marketing/resources/1022/Sangoma%20Corporate/Datasheets/Digital-PRI-Cards-Datasheet-web.pdf	Synchronous Serial Card
A142-R36KIT	A142-R36KIT 2 Port PCI Serial Card + RS232 2 Port Cable	https://portal.sangoma.com/marketing/resources/1022/Sangoma%20Corporate/Datasheets/Digital-PRI-Cards-Datasheet-web.pdf	Synchronous Serial Card
A142-RE3607KIT	A142-RE3607KIT 2 Port PCIe Serial Card + RS232 Cables	https://portal.sangoma.com/marketing/resources/1022/Sangoma%20Corporate/Datasheets/Digital-PRI-Cards-Datasheet-web.pdf	Synchronous Serial Card
A142-RE36KIT	A142-RE36KIT 2 Port PCIe Serial Card + RS232 2 Port Cable	https://portal.sangoma.com/marketing/resources/1022/Sangoma%20Corporate/Datasheets/Digital-PRI-Cards-Datasheet-web.pdf	Synchronous Serial Card
A142-V3708KIT	A142-V3708KIT 2 Port PCI Serial Card + V.35 Cables	https://portal.sangoma.com/marketing/resources/1022/Sangoma%20Corporate/Datasheets/Digital-PRI-Cards-Datasheet-web.pdf	Synchronous Serial Card
A142-V37KIT	A142-V37KIT 2 Port PCI Serial Card + V.35 2 Port Cable	https://portal.sangoma.com/marketing/resources/1022/Sangoma%20Corporate/Datasheets/Digital-PRI-Cards-Datasheet-web.pdf	Synchronous Serial Card
A142-VE3708KIT	A142-VE3708KIT 2 Port PCIe Serial Card V.35 Cables	https://portal.sangoma.com/marketing/resources/1022/Sangoma%20Corporate/Datasheets/Digital-PRI-Cards-Datasheet-web.pdf	Synchronous Serial Card
A142-VE37KIT	A142-VE37KIT 2 Port PCIe Serial Card V.35 2 Port Cable	https://portal.sangoma.com/marketing/resources/1022/Sangoma%20Corporate/Datasheets/Digital-PRI-Cards-Datasheet-web.pdf	Synchronous Serial Card
A142-XE3713KIT	A142-XE3713KIT 2 Port PCIe Serial Card x.21 Interface	https://portal.sangoma.com/marketing/resources/1022/Sangoma%20Corporate/Datasheets/Digital-PRI-Cards-Datasheet-web.pdf	Synchronous Serial Card
A142-XE37KIT	A142-XE37KIT 2 Port PCIe Serial Card x.21 Interface w/Split Cable	https://portal.sangoma.com/marketing/resources/1022/Sangoma%20Corporate/Datasheets/Digital-PRI-Cards-Datasheet-web.pdf	Synchronous Serial Card
A144-RE3807KIT	A144-RE3807KIT 4 Port PCIe Serial Card + RS232 Cables	https://portal.sangoma.com/marketing/resources/1022/Sangoma%20Corporate/Datasheets/Digital-PRI-Cards-Datasheet-web.pdf	Synchronous Serial Card
A144-RE38KIT	A144-RE38KIT 4 Port PCIe Serial Card + RS232 4 Port Cable	https://portal.sangoma.com/marketing/resources/1022/Sangoma%20Corporate/Datasheets/Digital-PRI-Cards-Datasheet-web.pdf	Synchronous Serial Card
A144-V3908KIT	A144-V3908KIT 4 Port PCI Serial Card + V.35 Cables	https://portal.sangoma.com/marketing/resources/1022/Sangoma%20Corporate/Datasheets/Digital-PRI-Cards-Datasheet-web.pdf	Synchronous Serial Card

Part #	Description	Product Datasheet	Product Group
A144-V39KIT	A144-V39KIT 4 Port PCI Serial Card + V.35 4 Port Cable	https://portal.sangoma.com/marketing/resources/1022/Sangoma%20Corporate/Datasheets/Digital-PRI-Cards-Datasheet-web.pdf	Synchronous Serial Card
A144-VE3908KIT	A144-VE3908KIT 4 Port PCIe Serial Card + V.35 Cables	https://portal.sangoma.com/marketing/resources/1022/Sangoma%20Corporate/Datasheets/Digital-PRI-Cards-Datasheet-web.pdf	Synchronous Serial Card
A144-VE39KIT	A144-VE39KIT 4 Port PCIe Serial Card + V.35 4 Port Cable	https://portal.sangoma.com/marketing/resources/1022/Sangoma%20Corporate/Datasheets/Digital-PRI-Cards-Datasheet-web.pdf	Synchronous Serial Card
A144-X3913KIT	A144-X3913KIT 4 Port DB25 Octopus Cable & 4 X .21 Cables	https://portal.sangoma.com/marketing/resources/1022/Sangoma%20Corporate/Datasheets/Digital-PRI-Cards-Datasheet-web.pdf	Synchronous Serial Card
A144-X3913KIT	A144-X3913KIT 4 Port DB25 Octopus Cable & 4 X .21 Cables	https://portal.sangoma.com/marketing/resources/1022/Sangoma%20Corporate/Datasheets/Digital-PRI-Cards-Datasheet-web.pdf	Synchronous Serial Card
A144-X39KIT	A144-X39KIT 4 Port DB25 Octopus Cable	https://portal.sangoma.com/marketing/resources/1022/Sangoma%20Corporate/Datasheets/Digital-PRI-Cards-Datasheet-web.pdf	Synchronous Serial Card
A144-XE3913 KIT	A144-XE3913 KIT 4 Port DB25 Octopus Cable & 4 X .21 Cables	https://portal.sangoma.com/marketing/resources/1022/Sangoma%20Corporate/Datasheets/Digital-PRI-Cards-Datasheet-web.pdf	Synchronous Serial Card
D100-030	Sangoma Transcoding Card PCI - license for 30 concurrent transcodes with options through software upgrades to upgrade to 400 concurrent transcodes.	https://portal.sangoma.com/marketing/resources/1010/Sangoma%20Corporate/Datasheets/Digital-BRI-Cards-Datasheet-web.pdf	Transcoder
D100-030E	Sangoma Transcoding Card PCIe - license for 30 concurrent transcodes with options through software upgrades to upgrade to 400 concurrent transcodes.	https://portal.sangoma.com/marketing/resources/1010/Sangoma%20Corporate/Datasheets/Digital-BRI-Cards-Datasheet-web.pdf	Transcoder
D100-060	Sangoma Transcoding Card PCI - license for 60 concurrent transcodes with options through software upgrades to upgrade to 400 concurrent transcodes.	https://portal.sangoma.com/marketing/resources/1010/Sangoma%20Corporate/Datasheets/Digital-BRI-Cards-Datasheet-web.pdf	Transcoder
D100-060E	Sangoma Transcoding Card PCIe - license for 60 concurrent transcodes with options through software upgrades to upgrade to 400 concurrent transcodes.	https://portal.sangoma.com/marketing/resources/1010/Sangoma%20Corporate/Datasheets/Digital-BRI-Cards-Datasheet-web.pdf	Transcoder
D100-120	Sangoma Transcoding Card PCI - license for 120 concurrent transcodes with options through software upgrades to upgrade to 400 concurrent transcodes.	https://portal.sangoma.com/marketing/resources/1010/Sangoma%20Corporate/Datasheets/Digital-BRI-Cards-Datasheet-web.pdf	Transcoder
D100-120E	Sangoma Transcoding Card PCIe - license for 120 concurrent transcodes with options through software upgrades to upgrade to 400 concurrent transcodes.	https://portal.sangoma.com/marketing/resources/1010/Sangoma%20Corporate/Datasheets/Digital-BRI-Cards-Datasheet-web.pdf	Transcoder

Part #	Description	Product Datasheet	Product Group
D100-240	Sangoma Transcoding Card PCI - license for 240 concurrent transcodes with options through software upgrades to upgrade to 400 concurrent transcodes.	https://portal.sangoma.com/marketing/resources/1010/Sangoma%20Corporate/Datasheets/Digital-BRI-Cards-Datasheet-web.pdf	Transcoder
D100-240E	Sangoma Transcoding Card PCIe - license for 240 concurrent transcodes with options through software upgrades to upgrade to 400 concurrent transcodes.	https://portal.sangoma.com/marketing/resources/1010/Sangoma%20Corporate/Datasheets/Digital-BRI-Cards-Datasheet-web.pdf	Transcoder
D100-400	Sangoma Transcoding Card PCI - license for 400 concurrent transcodes with options through software upgrades to upgrade to 400 concurrent transcodes.	https://portal.sangoma.com/marketing/resources/1010/Sangoma%20Corporate/Datasheets/Digital-BRI-Cards-Datasheet-web.pdf	Transcoder
D100-400E	Sangoma Transcoding Card PCIe - license for 400 concurrent transcodes with options through software upgrades to upgrade to 400 concurrent transcodes.	https://portal.sangoma.com/marketing/resources/1010/Sangoma%20Corporate/Datasheets/Digital-BRI-Cards-Datasheet-web.pdf	Transcoder
D100-UPG-030	Sangoma Transcoding Card license upgrade from 30 sessions to 60 sessions	https://portal.sangoma.com/marketing/resources/1010/Sangoma%20Corporate/Datasheets/Digital-BRI-Cards-Datasheet-web.pdf	Transcoder
D150-BOX030	Sangoma Transcoding Card mounted inside a case with license for 30 concurrent transcodes with options through software upgrades to upgrade to 400 concurrent transcodes.	https://portal.sangoma.com/marketing/resources/1010/Sangoma%20Corporate/Datasheets/Digital-BRI-Cards-Datasheet-web.pdf	Transcoder
D150-BOX060	Sangoma Transcoding Card mounted inside a case with license for 60 concurrent transcodes with options through software upgrades to upgrade to 400 concurrent transcodes.	https://portal.sangoma.com/marketing/resources/1010/Sangoma%20Corporate/Datasheets/Digital-BRI-Cards-Datasheet-web.pdf	Transcoder
D150-BOX120	Sangoma Transcoding Card mounted inside a case with license for 120 concurrent transcodes with options through software upgrades to upgrade to 400 concurrent transcodes.	https://portal.sangoma.com/marketing/resources/1010/Sangoma%20Corporate/Datasheets/Digital-BRI-Cards-Datasheet-web.pdf	Transcoder
D150-BOX240	Sangoma Transcoding Card mounted inside a case with license for 240 concurrent transcodes with options through software upgrades to upgrade to 400 concurrent transcodes.	https://portal.sangoma.com/marketing/resources/1010/Sangoma%20Corporate/Datasheets/Digital-BRI-Cards-Datasheet-web.pdf	Transcoder
D150-BOX400	Sangoma Transcoding Card mounted inside a case with license for 400 concurrent transcodes with options through software upgrades to upgrade to 400 concurrent transcodes.	https://portal.sangoma.com/marketing/resources/1010/Sangoma%20Corporate/Datasheets/Digital-BRI-Cards-Datasheet-web.pdf	Transcoder
D150-ETH030	Sangoma Transcoding Card for 30 concurrent transcodes with options through software upgrades to upgrade to 400 concurrent transcodes.	https://portal.sangoma.com/marketing/resources/1010/Sangoma%20Corporate/Datasheets/Digital-BRI-Cards-Datasheet-web.pdf	Transcoder
D150-ETH060	Sangoma Transcoding Card for 60 concurrent transcodes with options through software upgrades to upgrade to 400 concurrent transcodes.	https://portal.sangoma.com/marketing/resources/1010/Sangoma%20Corporate/Datasheets/Digital-BRI-Cards-Datasheet-web.pdf	Transcoder
D150-ETH120	Sangoma Transcoding Card for 120 concurrent transcodes with options through software upgrades to upgrade to 400 concurrent transcodes.	https://portal.sangoma.com/marketing/resources/1010/Sangoma%20Corporate/Datasheets/Digital-BRI-Cards-Datasheet-web.pdf	Transcoder

Part #	Description	Product Datasheet	Product Group
D150-ETH240	Sangoma Transcoding Card for 240 concurrent transcodes with options through software upgrades to upgrade to 400 concurrent transcodes.	https://portal.sangoma.com/marketing/resources/1010/Sangoma%20Corporate/Datasheets/Digital-BRI-Cards-Datasheet-web.pdf	Transcoder
D150-ETH400	Sangoma Transcoding Card for 400 concurrent transcodes with options through software upgrades to upgrade to 400 concurrent transcodes.	https://portal.sangoma.com/marketing/resources/1010/Sangoma%20Corporate/Datasheets/Digital-BRI-Cards-Datasheet-web.pdf	Transcoder
D150-UPG-030	Sangoma Transcoding Card license upgrade from 30 sessions to 60 sessions for the D150 family of Transcoding cards.	https://portal.sangoma.com/marketing/resources/1010/Sangoma%20Corporate/Datasheets/Digital-BRI-Cards-Datasheet-web.pdf	Transcoder
D500-100E	Sangoma Transcoding Card PCIe - license for 400 concurrent transcodes with options through upgrades to upgrade to 2000 concurrent transcodes.	https://portal.sangoma.com/marketing/resources/1010/Sangoma%20Corporate/Datasheets/Digital-BRI-Cards-Datasheet-web.pdf	Transcoder
D500-200E	Sangoma Transcoding Card PCIe - license for 800 concurrent transcodes with options through upgrades to upgrade to 2000 concurrent transcodes	https://portal.sangoma.com/marketing/resources/1010/Sangoma%20Corporate/Datasheets/Digital-BRI-Cards-Datasheet-web.pdf	Transcoder
D500-300E	Sangoma Transcoding Card PCIe - license for 1200 concurrent transcodes with options through upgrades to upgrade to 2000 concurrent transcodes.	https://portal.sangoma.com/marketing/resources/1010/Sangoma%20Corporate/Datasheets/Digital-BRI-Cards-Datasheet-web.pdf	Transcoder
D500-400E	Sangoma Transcoding Card PCIe - license for 1600 concurrent transcodes with options through upgrades to upgrade to 2000 concurrent transcodes.	https://portal.sangoma.com/marketing/resources/1010/Sangoma%20Corporate/Datasheets/Digital-BRI-Cards-Datasheet-web.pdf	Transcoder
D500-500E	Sangoma Transcoding Card PCIe - license for 2000 concurrent transcodes with options through upgrades to upgrade to 2000 concurrent transcodes.	https://portal.sangoma.com/marketing/resources/1010/Sangoma%20Corporate/Datasheets/Digital-BRI-Cards-Datasheet-web.pdf	Transcoder
D500-UPG-400	Sangoma Transcoding Card license and hardware module upgrade for 400 sessions for the D500 family of Transcoding cards. Please note a single D500 card cannot support more then 2000 total sessions so make sure you do not purchase more add ons then the card can handle.	https://portal.sangoma.com/marketing/resources/1010/Sangoma%20Corporate/Datasheets/Digital-BRI-Cards-Datasheet-web.pdf	Transcoder
G01-030	Dialogic Diva VoIP Codec - adds the AMR-NB, G.729 and Rtaudio CODECs to Diva V-xPRI Boards.		Diva VoIP Codec License
G01-031	Dialogic Diva G.723 Codec - adds the G.723 VoIP CODEC to Diva V-xPRI Boards.		Diva G.723 Codec License
G01-032	Dialogic Diva V.34 Fax License - adds V.34 Fax to Diva V-xPRI Boards.		Diva V.34 Fax License
G01-033	Dialogic Diva Data Modem License - adds Modem support to Diva V-xPRI Boards.		Diva Data Modem License
G01-036	Dialogic Diva SS7SBMTP2D4 MTP2 4 Link Software License		SS7 License
G02-036	Dialogic Diva SS7SBMTP2D2 MTP2 2 Link Software License		SS7 License

Part #	Description	Product Datasheet	Product Group
G03-036	Dialogic Diva SS7SBMTP2D1 MTP2 1 Link Software License		SS7 License
G04-036	Dialogic Diva SS7SBMTP2D8 MTP2 8 Link Software License		SS7 License
G05-036	Dialogic Diva SS7SBMTP2D16 MTP2 16 Link Software License		SS7 License
SBCM-ENT-D0100-025	Vega MSBG SBC with 1 x E1T1, 25 calls	https://portal.sangoma.com/marketing/resources/1148/Sangoma%20Corporate/Datasheets/SBC-Series-Datasheet-web.pdf	Session Border Controller
SBCM-ENT-D0200-025	Vega MSBG SBC with 2 x E1T1, 25 calls	https://portal.sangoma.com/marketing/resources/1148/Sangoma%20Corporate/Datasheets/SBC-Series-Datasheet-web.pdf	Session Border Controller
SBCM-ENT-D0400-025	Vega MSBG SBC with 4 x E1T1, 25 calls	https://portal.sangoma.com/marketing/resources/1148/Sangoma%20Corporate/Datasheets/SBC-Series-Datasheet-web.pdf	Session Border Controller
SBCT-CAR-0250-DA1	Sangoma Netborder SBC 250 Calls 1U This Sangoma Netborder SBC comes with 250 call path license and software upgradeable to 2000 call paths. Comes in a 1U form factor with a Dual AC power supply. The most cost effective, easiest to provision, and easiest to manage line of Session Border Controllers on the market. Sangoma's NetBorder Carrier SBC provides full featured, carrier class security and interconnection at the edge of carrier networks.	https://portal.sangoma.com/marketing/resources/1148/Sangoma%20Corporate/Datasheets/SBC-Series-Datasheet-web.pdf	Session Border Controller
SBCT-CAR-0500-DA1	Sangoma Netborder SBC 500 Calls 1U. This Sangoma Netborder SBC comes with 500 call path license and software upgradeable to 2000 call paths. Comes in a 1U form factor with a Dual AC power supply. The most cost effective, easiest to provision, and easiest to manage line of Session Border Controllers on the market. Sangoma's NetBorder Carrier SBC provides full featured, carrier class security and interconnection at the edge of carrier networks.	https://portal.sangoma.com/marketing/resources/1148/Sangoma%20Corporate/Datasheets/SBC-Series-Datasheet-web.pdf	Session Border Controller
SBCT-CAR-1000-DA1	Sangoma Netborder SBC 1000 Calls 1U. This Sangoma Netborder SBC comes with 1000 call path license and software upgradeable to 2000 call paths. Comes in a 1U form factor with a Dual AC power supply. The most cost effective, easiest to provision, and easiest to manage line of Session Border Controllers on the market. Sangoma's NetBorder Carrier SBC provides full featured, carrier class security and interconnection at the edge of carrier networks.	https://portal.sangoma.com/marketing/resources/1148/Sangoma%20Corporate/Datasheets/SBC-Series-Datasheet-web.pdf	Session Border Controller

Part #	Description	Product Datasheet	Product Group
SBCT-CAR-2000-DA1	Sangoma Netborder SBC 2000 Calls 1U. This Sangoma Netborder SBC comes with 2000 call path license and software upgradeable to 4000 call paths. Comes in a 1U form factor with a Dual AC power supply. The most cost effective, easiest to provision, and easiest to manage line of Session Border Controllers on the market. Sangoma's NetBorder Carrier SBC provides full featured, carrier class security and interconnection at the edge of carrier networks.	https://portal.sangoma.com/marketing/resources/1148/Sangoma%20Corporate/Datasheets/SBC-Series-Datasheet-web.pdf	Session Border Controller
SBCT-CAR-4000-DA1	Sangoma Netborder SBC 4000 Calls 1U This Sangoma Netborder SBC comes with 4000 call path license. Comes in a 1U form factor with a Dual AC power supply. The most cost effective, easiest to provision, and easiest to manage line of Session Border Controllers on the market. Sangoma's NetBorder Carrier SBC provides full featured, carrier class security and interconnection at the edge of carrier networks.	https://portal.sangoma.com/marketing/resources/1148/Sangoma%20Corporate/Datasheets/SBC-Series-Datasheet-web.pdf	Session Border Controller
SBCT-CAR-U0050	Netborder SBC 50 Call Upgrade Kit	https://portal.sangoma.com/marketing/resources/1148/Sangoma%20Corporate/Datasheets/SBC-Series-Datasheet-web.pdf	Session Border Controller
SBCT-CAR-U0250	Netborder SBC 250 Call Upgrade Kit	https://portal.sangoma.com/marketing/resources/1148/Sangoma%20Corporate/Datasheets/SBC-Series-Datasheet-web.pdf	Session Border Controller
SBCT-ENT-025	Vega Enterprise SBC 25 Calls The Vega SBC 1U Appliance is a scalable session border control gateway in the Vega family of gateways with up to 250 calls. The Vega SBC 1U Appliance with upto 250 calls works with both enterprises and carriers to perform a variety of functions including converting between protocols, transcoding, resource limiting and threat prevention.	https://portal.sangoma.com/marketing/resources/1148/Sangoma%20Corporate/Datasheets/SBC-Series-Datasheet-web.pdf	Session Border Controller
SBCT-ENT-050	Vega Enterprise SBC 50 Calls The Vega SBC 1U Appliance is a scalable session border control gateway in the Vega family of gateways with up to 250 calls. The Vega SBC 1U Appliance with upto 250 calls works with both enterprises and carriers to perform a variety of functions including converting between protocols, transcoding, resource limiting and threat prevention.	https://portal.sangoma.com/marketing/resources/1148/Sangoma%20Corporate/Datasheets/SBC-Series-Datasheet-web.pdf	Session Border Controller

Part #	Description	Product Datasheet	Product Group
SBCT-ENT-100	Vega Enterprise SBC 100 Calls The Vega SBC 1U Appliance is a scalable session border control gateway in the Vega family of gateways with up to 250 calls. The Vega SBC 1U Appliance with upto 250 calls works with both enterprises and carriers to perform a variety of functions including converting between protocols, transcoding, resource limiting and threat prevention.	https://portal.sangoma.com/marketing/resources/1148/Sangoma%20Corporate/Datasheets/SBC-Series-Datasheet-web.pdf	Session Border Controller
SBCT-ENT-250	Vega Enterprise SBC 250 Calls The Vega SBC 1U Appliance is a scalable session border control gateway in the Vega family of gateways with up to 250 calls. The Vega SBC 1U Appliance with upto 250 calls works with both enterprises and carriers to perform a variety of functions including converting between protocols, transcoding, resource limiting and threat prevention.	https://portal.sangoma.com/marketing/resources/1148/Sangoma%20Corporate/Datasheets/SBC-Series-Datasheet-web.pdf	Session Border Controller
SBCT-ENT-U025	Vega Enterprise SBC 25 Call Upgrade Kit	https://portal.sangoma.com/marketing/resources/1148/Sangoma%20Corporate/Datasheets/SBC-Series-Datasheet-web.pdf	Session Border Controller
SBCT-HYB-025	Vega Vm/Hybrid SBC 25 Calls The Vega SBC VM/Hybrid is a scalable session border control gateway in the Vega family of gateways with up to 500 calls. With the Vega SBC VM/Hybrid the session border controller is maintained on a virtual machine and the Media RTP is offload to an included Sangoma D150 media module reducing the load on the SBC for maximum scalability.	https://portal.sangoma.com/marketing/resources/1148/Sangoma%20Corporate/Datasheets/SBC-Series-Datasheet-web.pdf	Session Border Controller
SBCT-HYB-050	Vega Vm/Hybrid SBC 50 Calls The Vega SBC VM/Hybrid is a scalable session border control gateway in the Vega family of gateways with up to 500 calls. With the Vega SBC VM/Hybrid the session border controller is maintained on a virtual machine and the Media RTP is offload to an included Sangoma D150 media module reducing the load on the SBC for maximum scalability.	https://portal.sangoma.com/marketing/resources/1148/Sangoma%20Corporate/Datasheets/SBC-Series-Datasheet-web.pdf	Session Border Controller
SBCT-HYB-100	Vega Vm/Hybrid SBC 100 Calls The Vega SBC VM/Hybrid is a scalable session border control gateway in the Vega family of gateways with up to 500 calls. With the Vega SBC VM/Hybrid the session border controller is maintained on a virtual machine and the Media RTP is offload to an included Sangoma D150 media module reducing the load on the SBC for maximum scalability.	https://portal.sangoma.com/marketing/resources/1148/Sangoma%20Corporate/Datasheets/SBC-Series-Datasheet-web.pdf	Session Border Controller

Part #	Description	Product Datasheet	Product Group
SBCT-HYB-250	Vega Vm/Hybrid SBC 250 Calls The Vega SBC VM/Hybrid is a scalable session border control gateway in the Vega family of gateways with up to 500 calls. With the Vega SBC VM/Hybrid the session border controller is maintained on a virtual machine and the Media RTP is offload to an included Sangoma D150 media module reducing the load on the SBC for maximum scalability.	https://portal.sangoma.com/marketing/resources/1148/Sangoma%20Corporate/Datasheets/SBC-Series-Datasheet-web.pdf	Session Border Controller
SBCT-HYB-500	Vega Vm/Hybrid SBC 500 Calls The Vega SBC VM/Hybrid is a scalable session border control gateway in the Vega family of gateways with up to 500 calls. With the Vega SBC VM/Hybrid the session border controller is maintained on a virtual machine and the Media RTP is offload to an included Sangoma D150 media module reducing the load on the SBC for maximum scalability.	https://portal.sangoma.com/marketing/resources/1148/Sangoma%20Corporate/Datasheets/SBC-Series-Datasheet-web.pdf	Session Border Controller
SBCT-HYB-U025	Vega Vm/Hybrid SBC 25 Call Upgrade Kit The Vega SBC VM/Hybrid is a scalable session border control gateway in the Vega family of gateways with up to 500 calls. With the Vega SBC VM/Hybrid the session border controller is maintained on a virtual machine and the Media RTP is offload to an included Sangoma D150 media module reducing the load on the SBC for maximum scalability.	https://portal.sangoma.com/marketing/resources/1148/Sangoma%20Corporate/Datasheets/SBC-Series-Datasheet-web.pdf	Session Border Controller
SBCT-SMB-005	Vega SMB SBC 5 Calls The Vega SMB SBC 5 Call Path Appliance is a scalable session border control gateway in the Vega family of gateways that includes 5 call paths with software upgrade ability to 30 calls and designed for the SMB market to perform a variety of functions including converting between protocols, transcoding, resource limiting and threat prevention.	https://portal.sangoma.com/marketing/resources/1148/Sangoma%20Corporate/Datasheets/SBC-Series-Datasheet-web.pdf	Session Border Controller
SBCT-SMB-010	Vega SMB SBC 10 Calls The Vega SMB SBC 10 Call Path Appliance is a scalable session border control gateway in the Vega family of gateways that includes 10 call paths with software upgrade ability to 30 calls and designed for the SMB market to perform a variety of functions including converting between protocols, transcoding, resource limiting and threat prevention.	https://portal.sangoma.com/marketing/resources/1148/Sangoma%20Corporate/Datasheets/SBC-Series-Datasheet-web.pdf	Session Border Controller

Part #	Description	Product Datasheet	Product Group
SBCT-SMB-020	<p>Vega SMB SBC 20 Calls</p> <p>The Vega SMB SBC 20 Call Path Appliance is a scalable session border control gateway in the Vega family of gateways that includes 20 call paths with software upgrade ability to 30 calls and designed for the SMB market to perform a variety of functions including converting between protocols, transcoding, resource limiting and threat prevention.</p>	https://portal.sangoma.com/marketing/resources/1148/Sangoma%20Corporate/Datasheets/SBC-Series-Datasheet-web.pdf	Session Border Controller
SBCT-SMB-030	<p>Vega SMB SBC 30 Calls</p> <p>The Vega SMB SBC 30 Call Path Appliance is a scalable session border control gateway in the Vega family of gateways that includes 30 call paths with software upgrade ability to 30 calls and designed for the SMB market to perform a variety of functions including converting between protocols, transcoding, resource limiting and threat prevention.</p>	https://portal.sangoma.com/marketing/resources/1148/Sangoma%20Corporate/Datasheets/SBC-Series-Datasheet-web.pdf	Session Border Controller
SBCT-SMB-FLEX	<p>Vega SMB SBC. Requires the purchase of Flex SBC licenses.</p> <p>The Vega SMB SBC Appliance is a scalable session border control gateway with up to 30 calls. The SMB SBC Appliance with up to 30 calls works with a variety of functions including converting between protocols, transcoding, resource limiting and threat prevention. Includes 0 call paths with ability for up to 30 calls using our Flex SBC licenses that have to be purchased separately.</p>	https://portal.sangoma.com/marketing/resources/1148/Sangoma%20Corporate/Datasheets/SBC-Series-Datasheet-web.pdf	Session Border Controller
SBCT-SMB-U05	<p>Vega SMB SBC 5 Call Upgrade Kit</p> <p>The Vega SBC 1U Appliance is a scalable session border control gateway in the Vega family of gateways with up to 60 calls with Transcoding card. The Vega SBC 1U Appliance with upto 60 calls designed for the SMB market to perform a variety of functions including converting between protocols, transcoding, resource limiting and threat prevention.</p>	https://portal.sangoma.com/marketing/resources/1148/Sangoma%20Corporate/Datasheets/SBC-Series-Datasheet-web.pdf	Session Border Controller
SBCT-VMS-005	<p>Vega Vm/Software SBC 5 Calls</p> <p>The Vega SBC VM/Software is scalable virtual machine ready session border control gateway software in the Vega family of gateways with up to 4000 calls. With the Vega SBC VM/Software both the transcoding and media handling are handled by the software.</p>	https://portal.sangoma.com/marketing/resources/1148/Sangoma%20Corporate/Datasheets/SBC-Series-Datasheet-web.pdf	Session Border Controller
SBCT-VMS-010	<p>Vega Vm/Software SBC 10 Calls</p> <p>The Vega SBC VM/Software is scalable virtual machine ready session border control gateway software in the Vega family of gateways with up to 4000 calls. With the Vega SBC VM/Software both the transcoding and media handling are handled by the software.</p>	https://portal.sangoma.com/marketing/resources/1148/Sangoma%20Corporate/Datasheets/SBC-Series-Datasheet-web.pdf	Session Border Controller

Part #	Description	Product Datasheet	Product Group
SBCT-VMS-025	Vega Vm/Software SBC 25 Calls The Vega SBC VM/Software is scalable virtual machine ready session border control gateway software in the Vega family of gateways with up to 500 calls. With the Vega SBC VM/Software both the transcoding and media handling are handled by the software.	https://portal.sangoma.com/marketing/resources/1148/Sangoma%20Corporate/Datasheets/SBC-Series-Datasheet-web.pdf	Session Border Controller
SBCT-VMS-050	Vega Vm/Software SBC 50 Calls The Vega SBC VM/Software is scalable virtual machine ready session border control gateway software in the Vega family of gateways with up to 500 calls. With the Vega SBC VM/Software both the transcoding and media handling are handled by the software.	https://portal.sangoma.com/marketing/resources/1148/Sangoma%20Corporate/Datasheets/SBC-Series-Datasheet-web.pdf	Session Border Controller
SBCT-VMS-100	Vega Vm/Software SBC 100 Calls The Vega SBC VM/Software is scalable virtual machine ready session border control gateway software in the Vega family of gateways with up to 500 calls. With the Vega SBC VM/Software both the transcoding and media handling are handled by the software.	https://portal.sangoma.com/marketing/resources/1148/Sangoma%20Corporate/Datasheets/SBC-Series-Datasheet-web.pdf	Session Border Controller
SBCT-VMS-1000	Vega Vm/Software SBC 1000 Calls The Vega SBC VM/Software is scalable virtual machine ready session border control gateway software in the Vega family of gateways with up to 750 calls. With the Vega SBC VM/Software both the transcoding and media handling are handled by the software.	https://portal.sangoma.com/marketing/resources/1148/Sangoma%20Corporate/Datasheets/SBC-Series-Datasheet-web.pdf	Session Border Controller
SBCT-VMS-250	Vega Vm/Software The Vega SBC VM/Software is scalable virtual machine ready session border control gateway software in the Vega family of gateways with up to 500 calls. With the Vega SBC VM/Software both the transcoding and media handling are handled by the software.	https://portal.sangoma.com/marketing/resources/1148/Sangoma%20Corporate/Datasheets/SBC-Series-Datasheet-web.pdf	Session Border Controller
SBCT-VMS-500	Vega Vm/Software SBC 500 Calls The Vega SBC VM/Software is scalable virtual machine ready session border control gateway software in the Vega family of gateways with up to 500 calls. With the Vega SBC VM/Software both the transcoding and media handling are handled by the software.	https://portal.sangoma.com/marketing/resources/1148/Sangoma%20Corporate/Datasheets/SBC-Series-Datasheet-web.pdf	Session Border Controller

Part #	Description	Product Datasheet	Product Group
SBCT-VMS-U005	Vega Vm/Software SBC 5 Call Upgrade Kit The Vega SBC VM/Software is scalable virtual machine ready session border control gateway software in the Vega family of gateways with up to 4000 calls. With the Vega SBC VM/Software both the transcoding and media handling are handled by the software.	https://portal.sangoma.com/marketing/resources/1148/Sangoma%20Corporate/Datasheets/SBC-Series-Datasheet-web.pdf	Session Border Controller
SBCT-VMS-U025	Vega Vm/Software SBC 25 Call Upgrade Kit The Vega SBC VM/Software is scalable virtual machine ready session border control gateway software in the Vega family of gateways with up to 500 calls. With the Vega SBC VM/Software both the transcoding and media handling are handled by the software.	https://portal.sangoma.com/marketing/resources/1148/Sangoma%20Corporate/Datasheets/SBC-Series-Datasheet-web.pdf	Session Border Controller
SS7G-AP01	Sangoma SS7 Gateways 1U with 1 T1 Ports Appliance with AC power. 1 port E1/T1 SS7 VoIP Gateway Telco grade echo cancellation TDM protocol support: SS7, PRI, MFCR2 VoIP protocols: SIP V2/RFC3261, SIGTRAN M2UA RFC 3331, SCTP RFC 2960, Megaco/H248, H.323 Call Routing Fully featured webgui for configuration, monitoring and diagnostics	https://portal.sangoma.com/marketing/resources/1049/Sangoma%20Corporate/Datasheets/NSG-Datasheet-web.pdf	SS7
SS7G-AP02	Sangoma SS7 Gateways 1U with 2 T1 Ports Appliance with AC power.2 ports E1/T1 SS7 VoIP Gateway Telco grade echo cancellation TDM protocol support: SS7, PRI, MFCR2 VoIP protocols: SIP V2/RFC3261, SIGTRAN M2UA RFC 3331, SCTP RFC 2960, Megaco/H248, H.323 Call Routing Fully featured webgui for configuration, monitoring and diagnostics	https://portal.sangoma.com/marketing/resources/1049/Sangoma%20Corporate/Datasheets/NSG-Datasheet-web.pdf	SS7
SS7G-AP04	Sangoma SS7 Gateways 1U with 4 T1 Ports Appliance with AC power. 4 ports E1/T1 SS7 VoIP Gateway Telco grade echo cancellation TDM protocol support: SS7, PRI, MFCR2 VoIP protocols: SIP V2/RFC3261, SIGTRAN M2UA RFC 3331, SCTP RFC 2960, Megaco/H248, H.323 Call Routing Fully featured webgui for configuration, monitoring and diagnostics	https://portal.sangoma.com/marketing/resources/1049/Sangoma%20Corporate/Datasheets/NSG-Datasheet-web.pdf	SS7

Part #	Description	Product Datasheet	Product Group
SS7G-AP08	Sangoma SS7 Gateways 1U with 8 T1 Ports Appliance with AC power. 8 ports E1/T1 SS7 VoIP Gateway Telco grade echo cancellation TDM protocol support: SS7, PRI, MFCR2 VoIP protocols: SIP V2/RFC3261, SIGTRAN M2UA RFC 3331, SCTP RFC 2960, Megaco/H248, H.323 Call Routing Fully featured webgui for configuration, monitoring and diagnostics	https://portal.sangoma.com/marketing/resources/1049/Sangoma%20Corporate/Datasheets/NSG-Datasheet-web.pdf	SS7
SS7G-AP16	Sangoma SS7 Gateways 1U with 16 T1 Ports Appliance with AC power. 16 ports E1/T1 SS7 VoIP Gateway Telco grade echo cancellation TDM protocol support: SS7, PRI, MFCR2 VoIP protocols: SIP V2/RFC3261, SIGTRAN M2UA RFC 3331, SCTP RFC 2960, Megaco/H248, H.323 Call Routing Fully featured webgui for configuration, monitoring and diagnostics	https://portal.sangoma.com/marketing/resources/1049/Sangoma%20Corporate/Datasheets/NSG-Datasheet-web.pdf	SS7
SS7G-AP32	Sangoma SS7 Gateways 1U with 32 T1 Ports Appliance with AC power. 32 ports E1/T1 SS7 VoIP Gateway Telco grade echo cancellation TDM protocol support: SS7, PRI, MFCR2 VoIP protocols: SIP V2/RFC3261, SIGTRAN M2UA RFC 3331, SCTP RFC 2960, Megaco/H248, H.323 Call Routing Fully featured webgui for configuration, monitoring and diagnostics	https://portal.sangoma.com/marketing/resources/1049/Sangoma%20Corporate/Datasheets/NSG-Datasheet-web.pdf	SS7
SS7G-AP64-E1T1	Sangoma SS7 Gateways 3U with 64 T1 Ports Appliance with Dual AC power. Note. 4-6 Week Lead Time from time of order. 64 ports E1/T1 SS7 VoIP Gateway Telco grade echo cancellation TDM protocol support: SS7, PRI, MFCR2 VoIP protocols: SIP V2/RFC3261, SIGTRAN M2UA RFC 3331, SCTP RFC 2960, Megaco/H248, H.323 Call Routing Fully featured webgui for configuration, monitoring and diagnostics	https://portal.sangoma.com/marketing/resources/1049/Sangoma%20Corporate/Datasheets/NSG-Datasheet-web.pdf	SS7
Vega 4x4 VS0174	Vega 4x4 Flexible Analog Gateway – 4x4 Chassis Gateway Appliance	https://www.sangoma.com/assets/docs/datasheets/en/vega_series.pdf	Vega
Vega 4x4 VS1909	Vega 4x4 Flexible Analog Gateway – GEN GEN Module Gateway Appliance	https://www.sangoma.com/assets/docs/datasheets/en/vega_series.pdf	Vega
Vega 4x4 VS1910	Vega 4x4 Flexible Analog Gateway – LOOP GEN – FXS Module Gateway Appliance	https://www.sangoma.com/assets/docs/datasheets/en/vega_series.pdf	Vega
Vega 4x4 VS1911	Vega 4x4 Flexible Analog Gateway – FWIC Module Gateway Appliance	https://www.sangoma.com/assets/docs/datasheets/en/vega_series.pdf	Vega

Part #	Description	Product Datasheet	Product Group
Vega 4x4 VS1912	Vega 4x4 Flexible Analog Gateway – GEN LOOP – FXO Module Gateway Appliance	https://www.sangoma.com/assets/docs/datasheets/en/vega_series.pdf	Vega
VEGA-03K-2400KIT	Vega 3000G Gateway Appliance with 24 VS0173	https://portal.sangoma.com/marketing/resources/1205/Sangoma%20Corporate/Datasheets/Vega-3000-Analog-Gateway-datasheet-web.pdf	Vega
VEGA-03K-2FXO	Vega Expansion Chip for the Vega 3050G 50 FXS VEGA-03K-5000 VS0184 gateway. This module adds a single 2 port FXO module into the Vega 3050 for failover and expansion ports.	https://www.sangoma.com/wp-content/uploads/2016/06/Vega-3050-Analog-Gateway-Datasheet-web.pdf	Vega
VEGA-03K-5000	Vega 3050G Gateway Appliance with 50 Port FXS VS0184	https://www.sangoma.com/wp-content/uploads/2016/06/Vega-3050-Analog-Gateway-Datasheet-web.pdf	Vega
VEGA-050-0004KIT	Vega 50 4 FXO Appliance VS0119	https://www.sangoma.com/wp-content/uploads/2016/05/Vega-50-Media-Gateway-datasheet-web.pdf	Vega
VEGA-050-0008KIT	Vega 50 8 FXO Appliance VS0118	https://www.sangoma.com/wp-content/uploads/2016/05/Vega-50-Media-Gateway-datasheet-web.pdf	Vega
VEGA-100-030KIT	Vega 100G 1 Port T1-E1 VEGA-100-030KIT VS0164	https://www.sangoma.com/wp-content/uploads/2016/05/Vega-100-200-400-Gateway-datasheet-web.pdf	Vega
VEGA-100G-RMB	Vega 100G/200G and 3000G Rackmount Bracket Replacements (Mounts 1 unit per 1U)	https://portal.sangoma.com/marketing/resources/1205/Sangoma%20Corporate/Datasheets/Vega-3000-Analog-Gateway-datasheet-web.pdf	Vega
VEGA-200-060KIT	Vega 200G 2 Port T1-E1 VEGA-200-060KIT VS0157	https://www.sangoma.com/wp-content/uploads/2016/05/Vega-100-200-400-Gateway-datasheet-web.pdf	Vega
VEGA3K-3000G-PBR	Replacement Power Brick for Vega 3000, 100G and 200G. Does not include Power Cord. Need to order Power Cord separate if needed.	https://portal.sangoma.com/marketing/resources/1205/Sangoma%20Corporate/Datasheets/Vega-3000-Analog-Gateway-datasheet-web.pdf	Vega
VEGA-400G-RMB	Vega 400G or Vega 3050G Rackmount Bracket (Mounts 1 unit per 1U)	https://www.sangoma.com/assets/docs/datasheets/en/vega400.pdf	Vega
VEGA-400-VS1878	Vega 400GF High Precision Clock Module VS1878	https://www.sangoma.com/assets/docs/datasheets/en/vega400.pdf	Vega
VEGA-4NG-030	Vega 400G 4 Port T1-E1 30 Channels software upgradeable to 120 Channels VS0158	https://www.sangoma.com/assets/docs/datasheets/en/vega400.pdf	Vega
VEGA-4NG-060	Vega 400G 4 Port T1-E1 60 Channels software upgradeable to 120 Channels VS0158	https://www.sangoma.com/assets/docs/datasheets/en/vega400.pdf	Vega
VEGA-4NG-090	Vega 400G 4 Port T1-E1 90 Channels software upgradeable to 120 Channels VS0158	https://www.sangoma.com/assets/docs/datasheets/en/vega400.pdf	Vega
VEGA-4NG-120	Vega 400G 4 Port T1-E1 120 Channels VS0158	https://www.sangoma.com/assets/docs/datasheets/en/vega400.pdf	Vega

Part #	Description	Product Datasheet	Product Group
VEGA-4NGF-030	Vega 400GF 4 Port T1-E1 30 Channels for fax applications, software upgradeable to 120 Channels (VS0258). Includes a High Performance Clock and hardware based Error Correction Mode (ECM) for reliable Faxing that the standard voice versions Vega 400G version does not have. This product replaces the End of Life Dialogic DMG2000 series gateways. This product is also Dialogic SR142 certified for faxing. Unlock additional channels using SKUs for license upgrade for standard Vega 400G.	https://www.sangoma.com/assets/docs/datasheets/en/vega400.pdf	Vega
VEGA-4NGF-U030	VEGA 400G, 30 Channel Upgrade Kit VEGA-4NGF-U030	https://www.sangoma.com/assets/docs/datasheets/en/vega400.pdf	Vega
VEGA-4NG-U030	VEGA 400G, 30 Channel Upgrade Kit VEGA-4NG-U030	https://www.sangoma.com/assets/docs/datasheets/en/vega400.pdf	Vega
VEGA-60G-0004	Vega 60 4 Port FXO gateway.	https://portal.sangoma.com/marketing/resources/1244/Sangoma%20Corporate/Datasheets/Vega-60-Media-Gateway-Datasheet-web.pdf	Vega
VEGA-60G-0008	Vega 60 8 Port FXO gateway.	https://portal.sangoma.com/marketing/resources/1244/Sangoma%20Corporate/Datasheets/Vega-60-Media-Gateway-Datasheet-web.pdf	Vega
VEGA-60G-02BRI	Vega 60 2 Port BRI gateway.	https://portal.sangoma.com/marketing/resources/1244/Sangoma%20Corporate/Datasheets/Vega-60-Media-Gateway-Datasheet-web.pdf	Vega
VEGA-60G-0400	Vega 60 4 Port FXS gateway.	https://portal.sangoma.com/marketing/resources/1244/Sangoma%20Corporate/Datasheets/Vega-60-Media-Gateway-Datasheet-web.pdf	Vega
VEGA-60G-0404	Vega 60 4 Port FXS and 4 Port FXO gateway	https://portal.sangoma.com/marketing/resources/1244/Sangoma%20Corporate/Datasheets/Vega-60-Media-Gateway-Datasheet-web.pdf	Vega
VEGA-60G-04B04S	Vega 60 4 Port BRI gateway with 4 FXS.	https://portal.sangoma.com/marketing/resources/1244/Sangoma%20Corporate/Datasheets/Vega-60-Media-Gateway-Datasheet-web.pdf	Vega
VEGA-60G-04BRI	Vega 60 4 Port BRI gateway.	https://portal.sangoma.com/marketing/resources/1244/Sangoma%20Corporate/Datasheets/Vega-60-Media-Gateway-Datasheet-web.pdf	Vega
VEGA-60G-0800	Vega 60 8 Port FXS gateway.	https://portal.sangoma.com/marketing/resources/1244/Sangoma%20Corporate/Datasheets/Vega-60-Media-Gateway-Datasheet-web.pdf	Vega
VEGA-60G-DRMB	Vega 60G Dual Rackmount Bracket (Mounts 2 units side by side per 1U)	https://portal.sangoma.com/marketing/resources/1244/Sangoma%20Corporate/Datasheets/Vega-60-Media-Gateway-Datasheet-web.pdf	Vega
VEGA-60G-RMB	Vega 60G Rackmount Bracket (Mounts 1 unit per 1U)	https://portal.sangoma.com/marketing/resources/1244/Sangoma%20Corporate/Datasheets/Vega-60-Media-Gateway-Datasheet-web.pdf	Vega
VEGA-60G-WMB	Vega 60G Wallmount Bracket	https://portal.sangoma.com/marketing/resources/1244/Sangoma%20Corporate/Datasheets/Vega-60-Media-Gateway-Datasheet-web.pdf	Vega

Part #	Description	Product Datasheet	Product Group
VEGA60-PBR	Replacement Power Brick for Vega 50 and 60. Does not include Power Cord. Need to order Power Cord separate if needed.	https://portal.sangoma.com/marketing/resources/1244/Sangoma%20Corporate/Datasheets/Vega-60-Media-Gateway-Datasheet-web.pdf	Vega
FS4100	1 port USB synchronous and asynchronous adapter - V3 (X.21 / V.35 / RS232 / EIA530 / RS422 / RS449 / RS485), async, Bitstream and HDLC run-time support for custom applications plus TCP/IP operation on Linux and Windows and a Line Monitor. NRZ, NRZI, FM1, FM0, Manchester Encoding, Conditioned Di-Phase Selectable. APIs for Linux, Windows 10, 8, 7, Vista, Server 2016, 2012, 2008. Support to permit TCP/IP - PPP to run over the adapter. To develop applications to use the APIs order the FarSync SDK. USB cable included, other cables are ordered separately	https://www.farsite.com/synchronous_usb_v.35_x.21_rs530/FarSync_USB_synchronous_adapter_Linux_Windows.shtml	FarSync Flex
FS4140	Universal PCI 1 port bus mastering synchronous card (X.21 / V.35 / RS232 / EIA530 / RS422 / RS449), Bitstream and HDLC run-time support for custom applications plus TCP/IP operation on Linux and Windows. includes: APIs for Linux, Windows 10, 8, 7, Vista, Server 2016, 2012, 2008. Support to permit TCP/IP - PPP to run over the adapter. To develop applications to use the APIs order the FarSync SDK. Cables are ordered separately	https://www.farsite.com/synchronous_X.21_RS422_V.35_RS530_PCI_PCl_e_cards/farsync_pci-x_v.35_x.21_rs232c_sync_card.shtml	FarSync T1U
FS4150	1 port E1 / T1 card, Universal PCI with BNC and RJ48C (RJ45) connectors, includes an API for customer applications and support for TCP/IP operation. Details: transparent, unstructured T1 and E1 G.703 lines, T1 and E1 fractional (G.703/G.704). Includes: APIs for Linux, Windows 10, 8, 7, Vista, Server 2016, 2012, 2008. Support to allow TCP/IP to run over the adapter. To develop applications to use the APIs order the FarSync SDK. Includes a 2m cable with RJ48C Connectors.	https://www.farsite.com/synchronous_X.21_RS422_V.35_RS530_PCI_PCl_e_cards/farsync_e1_G.703_G.704_pci_card_linux_windows.shtml	FarSync TE1

Part #	Description	Product Datasheet	Product Group
FS4151	<p>1 port E1 / T1 card, Universal PCI with a RJ48C (RJ45) connectors, includes an API for customer applications and support for TCP/IP operation.</p> <p>Details: transparent, unstructured T1 and E1 G.703 lines, T1 and E1 fractional (G.703/G.704).</p> <p>Includes: APIs for Linux, Windows 10, 8, 7, Vista, Server 2016, 2012, 2008. Support to allow TCP/IP to run over the adapter. To develop applications to use the APIs order the FarSync SDK. Includes a 2m cable with RJ48C Connectors.</p>		FarSync TE1R
FS4155	<p>1 port E1 / T1 PCI express card with BNC and RJ48C (RJ45) connectors, includes a APIs for customer applications and support for TCP/IP operation.</p> <p>Details: transparent, unstructured T1 and E1 G.703 lines, T1 and E1 fractional (G.703/G.704). External clock in via SMA connector.</p> <p>Includes: APIs for Linux, Windows 10, 8, 7, Vista, Server 2016, 2012, 2008. Support to allow TCP/IP to run over the adapter. To develop applications to use the APIs order the FarSync SDK. Includes a 2m cable with RJ48C Connectors.</p>	https://www.farsite.com/E1_G.703_G.704_PCl_e_cards/farsync_e1_G.703_G.704_PCl_e_card_linux_windows.shtml	FarSync TE1e
FS4240	<p>Universal PCI 2 port bus mastering synchronous card (X.21 / V.35 / RS232 / EIA530 / RS422 / RS449), Bitstream and HDLC run-time support for custom applications plus TCP/IP operation on Linux and Windows.</p> <p>includes: APIs for Linux, Windows 10, 8, 7, Vista, Server 2016, 2012, 2008. Support to permit TCP/IP - PPP to run over the adapter. To develop applications to use the APIs order the FarSync SDK. Cables are ordered separately</p>	https://www.farsite.com/synchronous_X.21_RS422_V.35_RS530_PCl_PCl_e_cards/FarSync_PCl_V.35_RS422_X.21_2_port_synchr_ous_card.shtml	FarSync T2U
FS4250	<p>PCIe 2 port bus mastering synchronous card (X.21 / V.35 / RS232 / EIA530 / RS422 / RS449), Bitstream and HDLC run-time support for custom applications plus TCP/IP operation on Linux and Windows.</p> <p>includes: APIs for Linux, Windows 10, 8, 7, Vista, Server 2016, 2012, 2008. Support to permit TCP/IP - PPP to run over the adapter. To develop applications to use the APIs order the FarSync SDK. Cables are ordered separately</p>	https://www.farsite.com/synchronous_X.21_RS422_V.35_RS530_PCl_PCl_e_cards/FarSync_PCl_V.35_RS422_X.21_2_port_synchr_ous_card.shtml	FarSync T2Ue

Part #	Description	Product Datasheet	Product Group
FS4256	<p>PCI Express 2 port bus mastering synchronous low profile card (X.21 / V.35 / RS232 / EIA530 / RS422 / RS449 / RS485) with highly flexible clocking options, Bitstream and HDLC run-time support for custom applications plus TCP/IP operation on Linux and Windows.</p> <p>NRZ, FM1, FM0, Conditioned Diphas or Manchester Encoding selectable, other encodings can be developed to order.</p> <p>APIs for Linux, Windows 10, 8, 7, Vista, Server 2016, 2012, 2008.</p> <p>Support to allow TCP/IP to run over the adapter.</p> <p>To develop applications to use the API order the FarSync SDK.</p> <p>Cables are ordered separately</p>	https://www.farsite.com/synchronous_X.21_RS422_V.35_RS530_PCI_PCIe_cards/FarSync_PCIe_V.35_RS422_X.21_2_port_synchrinous_card.shtml	FarSync T2Ee
FS4280	<p>PMC 2 port synchronous bus mastering adapter with Front I/O (X.21 / V.35 / RS232 / EIA530 / RS422 / RS449), also Rear I/O, Bitstream and HDLC run-time support for custom applications plus TCP/IP operation on Linux and Windows</p> <p>Includes:</p> <p>APIs for Linux, Windows 10, 8, 7, Vista, Server 2016, 2012, 2008.</p> <p>To develop applications to use the APIs order the FarSync SDK</p> <p>Cables are ordered separately for the FarSync T2U-PMC-F, no cables are supplied for the FarSync T2U-PMC-R.</p>	https://www.farsite.com/synchronous_pmc_cards/farsync_pmc_synchronous_2_port_card_v.35_rs232_rs422_x.21.shtml	FarSync T2U-PMC-F
FS4281	<p>PMC 2 port synchronous bus mastering adapter with Rear I/O (X.21 / V.35 / RS232 / EIA530 / RS422 / RS449), Bitstream and HDLC run-time support for custom applications plus TCP/IP operation on Linux and Windows.</p> <p>Includes:</p> <p>APIs for Linux, Windows 10, 8, 7, Vista, Server 2016, 2012, 2008.</p> <p>To develop applications to use the APIs order the FarSync SDK</p> <p>Cables are ordered separately for the FarSync T2U-PMC-F, no cables are supplied for the FarSync T2U-PMC-R.</p>	https://www.farsite.com/synchronous_pmc_cards/farsync_pmc_synchronous_2_port_card_v.35_rs232_rs422_x.21.shtml	FarSync T2U-PMC-R

Part #	Description	Product Datasheet	Product Group
FS4440	<p>Universal PCI 4 port bus mastering synchronous card (X.21 / V.35 / RS232 / RS422 / EIA530 / RS449), Bitstream and HDLC run-time support for custom applications plus TCP/IP operation on Linux and Windows.</p> <p>Includes: APIs for Linux, Windows 10, 8, 7, Vista, Server 2016, 2012, 2008. Support to allow TCP/IP to run over the adapter. To develop applications to use the APIs order the FarSync SDK. Cables are ordered separately</p>	https://www.farsite.com/synchronous_X.21_RS422_V.35_RS530_PCl_e_cards/FarSync_PCl_e_X.V.35_RS422_RS530_4_port_sync_card.shtml	FarSync T4U
FS4446	<p>Universal PCI Synchronous and Asynchronous 4 port bus mastering card (X.21 / V.35 / RS232 / EIA530 / RS422 / RS449 / RS485), Bitstream and HDLC run-time support for custom applications plus TCP/IP operation on Linux and Windows.</p> <p>Highly flexible clocking options include external clock source via a H.100 bus and clock frequency multiplication and division. NRZ, FM1, FM0, Conditioned Diphase or Manchester Encoding selectable, other encoding can be developed to order.</p> <p>Includes: APIs for Linux, Windows 10, 8, 7, Vista, Server 2016, 2012, 2008. Support to allow TCP/IP to run over the adapter. To develop applications to use the APIs order the FarSync SDK. Cables are ordered separately</p>		FarSync T4E+
FS4450	<p>PCIe 4 port bus mastering synchronous card (X.21 / V.35 / RS232 / RS422 / EIA530 / RS449), Bitstream and HDLC run-time support for custom applications plus TCP/IP operation on Linux and Windows</p> <p>Includes: APIs for Linux, Windows 10, 8, 7, Vista, Server 2016, 2012, 2008. Support to allow TCP/IP to run over the adapter. To develop applications to use the APIs order the FarSync SDK. Cables are ordered separately</p>	https://www.farsite.com/synchronous_X.21_RS422_V.35_RS530_PCl_e_cards/FarSync_PCl_e_synchronous_card_Linux_Windows.shtml	FarSync T4Ue

Part #	Description	Product Datasheet	Product Group
FS4451	<p>PCIe 4 port bus mastering synchronous and asynchronous card (X.21 / V.35 / RS232 / RS422 / EIA530 / RS449), Bitstream and HDLC run-time support for custom applications plus TCP/IP operation on Linux and Windows</p> <p>Includes: APIs for Linux, Windows 10, 8, 7, Vista, Server 2016, 2012, 2008. Support to allow TCP/IP to run over the adapter. To develop applications to use the APIs order the FarSync SDK. Cables are ordered separately</p>		FarSync T4Ue + Async
FS4456	<p>PCIe Synchronous and Asynchronous 4 port bus mastering card (X.21 / V.35 / RS232 / EIA530 / RS485 / RS422 / RS449), Bitstream and HDLC run-time support for custom applications plus TCP/IP operation on Linux and Windows. NRZ, NRZI, Manchester Encoding, Conditioned Diphase, FM1 or FM0 selectable, other encoding can be developed to order. Highly flexible clocking options. Includes: APIs for Linux, Windows 10, 8, 7, Vista, Server 2016, 2012, 2008. Support to allow TCP/IP to run over the adapter. To develop applications to use the APIs order the FarSync SDK. Cables are ordered separately</p>	https://www.farsite.com/synchronous_X.21_RS422_V.35_RS530_PCI_PCl_e_cards/farsync_t4ee_pcie_synchronous_card.shtml	FarSync T4Ee
FS4901	Mounting plates for the FarSync Flex, set of 2, can be fitted without opening the case		FarSync Flex
FS6011	Single combined RS232 (V.24) and EIA-530 (RS422) DTE 1,5m cable, DB25M connector.	https://www.farsite.com/custsupp/documents/fs6011v2_kcr1-v2.pdf	FarSync Flex
FS6016	Line Monitor 1,5m cable for RS232 (V.24) and EIA-530 (RS422) with DB25M to DB25F pass-through	https://www.farsite.com/custsupp/documents/FS6016_KCR-MON_v1.1.pdf	FarSync Flex
FS6017	Line Monitor 1,5m cable for X.21 (V.11) with DB15M to DB15F pass-through	https://www.farsite.com/custsupp/documents/FS6017_KCX-MON_v1.1.pdf	FarSync Flex
FS6019	Single RS449 DTE 1,5m cable, DB37M connector.	https://www.farsite.com/custsupp/documents/FS6019_KC449.pdf	FarSync Flex
FS6031	Single RS232 (V.24) and RS530 (RS422) DTE 1,5m cable - same cable for both, DB25M connector		FarSync T2U-PMC-F Cable
FS6032	Single X.21 (V.11) DTE 2m cable - DB15M connector		DCX1
FS6033	Single V.35 DTE 2m cable - M34M connector		DCV1

Part #	Description	Product Datasheet	Product Group
FS6034	Single RS449 DTE 2m cable - DB25M connector		DC449
FS6041	Quad X.21 (V.11) DTE 1,5m cable, DB15M connectors.	https://www.farsite.com/custsupp/documents/FS6041_mcx4.pdf	FarSync TU4 Cable
FS6042	Quad V.35 DTE 1,5m cable, M34M connectors.	https://www.farsite.com/custsupp/documents/FS6042_mcv4.pdf	FarSync TU4 Cable
FS6043	Quad RS232 (V.24) DTE 1,5m cable, DB25M connectors.	https://www.farsite.com/custsupp/documents/FS6043_mcr4.pdf	FarSync TU4 Cable
FS6045	Quad X.21 (V.11) DCE 2m cable, DB15F connectors.		FarSync TU4 Cable
FS6046	Quad RS232 (V.24) DCE 2m cable, DB25F connectors.		FarSync TU4 Cable
FS6047	Quad port X.21 (V.11) DTE 2,5m cable - DB15M connectors		HGX4
FS6048	Quad port V.35 DTE 2,5m cable - M34M connectors		HCV4
FS6049	Quad port RS449 DTE 3,5m cable - DB37M connectors		HC449
FS6052	EIA-530 to X.21 (V.11) DTE transition 0,5m cable - DB15M connector, 1 port	https://www.farsite.com/custsupp/documents/FS6052_TCX1.pdf	TCX1
FS6053	EIA-530 to V.35 DTE transition 0,5m cable - M34M connector, 1 port	https://www.farsite.com/custsupp/documents/FS6053_TCV1.pdf	TCV1
FS6054	EIA-530 to RS449 DTE transition 1,5m cable - DB37M connector, 1 port	https://www.farsite.com/custsupp/documents/FS6054_TC449.pdf	TC449
FS6061	Single RS232 (V.24) DTE 1,5m cable with DB25M connector		FarSync T1U/T2U Cable
FS6062	Single X.21 (V.11) DTE 1,5m cable, DB15M connector.	https://www.farsite.com/custsupp/documents/FS6062_UCX1.pdf	FarSync Flex
FS6062	Single X.21 (V.11) DTE 1,5m cable with DB15M connector		FarSync T1U/T2U Cable
FS6063	Single V.35 DTE 1,5m cable, M34M connector.	https://www.farsite.com/custsupp/documents/FS6063_UCV1.pdf	FarSync Flex
FS6063	Single V.35 DTE 1,5m cable with M34M connector		FarSync T1U/T2U Cable
FS6064	Single EIA-530 (RS530, RS422) DTE 1,5m cable with DB37M connector	https://www.farsite.com/custsupp/documents/FS6064_U530.pdf	FarSync T1U/T2U Cable
FS6070	Single combined RS232 (V.24) and EIA-530 (RS422) DCE 2m cable, DB25F connector.		FarSync Flex
FS6071	Single RS232 (V.24) DCE 2m cable with DB25F connector		FarSync T1U/T2U Cable
FS6074	Quad port conversion 0,5m cable, allows UCR1, UCV1, UCX1, UX35C and U530 cables to be used		FarSync TU4 Cable
FS6075	Single X.21 (V.11) DCE 2m cable, DB15F connector.		FarSync Flex
FS6075	Single X.21 (V.11) DCE 2m cable with DB15F connector		FarSync T1U/T2U Cable
FS6076	Quad port EIA-530 (RS422) and RS232 DTE cable, DB25M connectors, 2m. Also supports X.21, V.35 and RS449 interfaces with addition of conversion cables TCV1, TCX1 and TC449 listed below.	https://www.farsite.com/custsupp/documents/FS6076_HCR4.pdf	FarSync T4E+ Cable

Part #	Description	Product Datasheet	Product Group
FS6077	Dual port EIA-530 (RS422) and RS232 DTE cable 1,5m - DB25M connectors. Also supports X.21, V.35 and RS449 interfaces for a mixed connector operation with addition of conversion cables TCV1, TCX1 and TC449.	https://www.farsite.com/custsupp/documents/fs6077_fcr2.pdf	FarSync T2Ee Cable
FS6078	Dual port X.21 (V.11) DTE 2m cable -DB15M connectors		FarSync T2Ee Cable
FS6079	Dual port V.35 DTE 2m cable - M34M connectors		FarSync T2Ee Cable
FS6080	Dual port RS449 DTE 3m cable - DB37M connectors		FarSync T2Ee Cable
FS6090	X.21 double shielded 0,5m crossover cable - DB15F connectors. Suitable for FarLinX and FarSync products	https://www.farsite.com/custsupp/documents/FS6090_null-mx.pdf	Null-MX
FS6091	X.21 double shielded 15m extension cable, DB15M to DB15F connector		X21-EXT
FS6093	X.21 to RS449 – Converts the X.21 presentation from the FarSync 0,5m cable to RS449 (DB37M connector) when the card is generating the line clock (Internal clocking).	https://www.farsite.com/custsupp/documents/RS449_X.21_conversion.pdf	X.21-449-INT
FS6094	X.21 to RS449 – Converts the X.21 presentation from the FarSync 0,5m cable to RS449 (DB37M connector) when the clock is generated by the line (DCE).	https://www.farsite.com/custsupp/documents/RS449_X.21_conversion.pdf	X.21-449-EXT
FS6095	Single V.35 DCE 1,5m cable with M34F connector- use where card has to generate the line clocks	https://www.farsite.com/custsupp/documents/FS6095_UX35C.pdf	FarSync Flex
FS6095	Single V.35 DCE 1,5m cable with M34F connector- use where card has to generate the line clocks		FarSync T1U/T2U Cable
FS6097	Combined RS232 (V.24) and RS530 (RS422, EIA 530) double shielded 0,5m crossover cable - DB25F connectors. Suitable for FarLinX and FarSync products.	https://www.farsite.com/custsupp/documents/FS6097_NULL-MR4.pdf	Null-MR4
FS9610	Developers Toolkit - software, manuals and sample applications for using the APIs with FarSite engineering support for the FarSync T1U, T2U, T4U, T2Ue, T2Ee, T2U-PMC, T4Ue, T4E+, T4Ee, TE1, TE1R, TE1e, and Flex adapters.	https://www.farsite.com/synchronous_X.21_RS422_V.35_RS530_PCI_PCle_cards/FarSync_SDK.shtml	FarSync SDK